MASTER FLUID SOLUTIONS

TRIM MicroSol 585XT.

High-lubricity semi-synthetic micro-emulsion metalworking fluid delivering extended sump life and excellent foam control against earlier generation semi-synthetics.

PRODUCT RANGE
Soluble Cutting Fluids

APPLICATION

- Titanium and high-nickel alloy machining
- Aerospace aluminium and exotic alloys
- Grinding, turning, drilling, tapping and milling
- Heavy-duty roughing and long cycle-time operations

BENEFITS

- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Rolls-Royce	CSS 127, Nuclear Class A – A17929
Airbus	80-T-30-4010
Boeing	BAC5008
Safran	PCS-4001 / 4002 / PR6300 Index A
Pratt	& Whitney PMC 9362
Bombardier	BAMS 569-001
GE	Aviation SDS# EVEN-11232
Lockheed	Martin G34.62 / G74.0051 / F74.0051
Aerojet	ASTM F 945
Applied	Materials UHV
Lord	Corporation MTL-S-0136

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Type		**Semi-synthetic micro-emulsion**
Light Duty, %		**4.0 – 6.5**
Moderate Duty, %		**6.5 – 8.5**
Heavy Duty, %		**8.5 – 10.0**
Chlorine	ASTM D808	**None**
Formaldehyde Releasers		**None**
Nitrites / Phenols		**None**

Typical values. They do not form a specification.

PACK SIZES

205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS on request

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063