AUTOMOTIVE

# TURBOLUBE HD 10W-40.

Semi-synthetic engine oil suitable for many cars and light commercial vehicles with either turbocharged or normally-aspirated engines.

PRODUCT RANGE
**Passenger Car Engine Oils**

| 89.9 cSt | 13.6 cSt | 0.867 | 205 °C |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Specific Gravity @ 15.6 | Flash point |

## APPLICATION

- Older passenger cars
- Light commercial vehicles
- Turbocharged and naturally aspirated engines

**NOT RECOMMENDED**

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

## BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Viscosity Grade | SAE J300 | **SAE 10W-40** |
| Base Oil | | **Semi-synthetic** |
| Specific Gravity @ 15.6°C | | **0.867** |
| Kinematic Viscosity @ 40°C, cSt | | **89.9** |
| Kinematic Viscosity @ 100°C, cSt | | **13.6** |
| Viscosity Index | ASTM D2270 | **152** |
| Flash Point (COC), °C | | **205** |
| Pour Point, °C | ASTM D97 | **-30** |

Typical values. They do not form a specification.

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **API** | SG/CF-4 |

## PACK SIZES

1 L, 5 L, 20 L, 205 L

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0733

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063