COMMERCIAL VEHICLES

TURBOPLUS 10W-40.

Heavy-duty semi-synthetic engine oil for diesel and petrol engines in commercial vehicles and fleet applications.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

106.0 cSt	16.0 cSt	0.876	190 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Mixed commercial fleets
- Vehicles without after-treatment
- Combined diesel and petrol fleet stock

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Semi-synthetic**
Kinematic Viscosity @ 40°C, cSt		**106.0**
Kinematic Viscosity @ 100°C, cSt		**16.0**
Viscosity Index	ASTM D2270	**162**
Specific Gravity @ 15.6°C		**0.876**
Flash Point (COC), °C		**190**
TBN, mg KOH/g	ASTM D2896	**10.7**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 11 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CI-4/SL
ACEA	E7, E5, A3/B4
MB	228.3
MAN	3275
Volvo	VDS-3
Mack	EO-M+
Cummins	CES 20076/20077/20078
Deutz	DQC III-10
Daimler Truck	DTFR 15B110

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0669

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063