GREASES

ULTRA HIGH TEMPERATURE GREASE.

The extreme end of the range: a graphite dispersion in polyalkylene glycol for service up to 600 °C.

PRODUCT RANGE

High Temperature Greases

128 cSt	25 cSt	Nil	2
Viscosity @ 40°C	Viscosity @ 100°C	Dropping point	NLGI grade

APPLICATION

- Furnace door and charging gear
- Kiln car bearings and running gear
- Heat treatment plant
- Anywhere above the limit of every other grease

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Black**
Base Oil		**Polyalkaline glycol**
NLGI Classification		**2**
Dropping Point (ASTM D2265)		**Nil**
Micronised Graphite Content, %		**15**
Base Fluid Viscosity (IP71) @ 40°C, cSt		**128**
Base Fluid Viscosity (IP71) @ 100°C, cSt		**25**
Operating Temperature Range, °C	dry film	**-30°C to +200°C (grease film); 200°C to 600**

Typical values. They do not form a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0891

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063