TEXTILE LUBRICANTS

UNILUBE WWA.

UNILUBE WWA is an aqueous solution of synthetic water-soluble lubricants formulated for application as a yarn dressing at beaming off after warping or at re-beaming.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Yarn dressing at beaming off / re-beaming, Woollen Yarn 2.0-6.0%
- Worsted Yarn 2.0-4.0%
- Synthetic/Wool Blend 1.6-4.0%
- Synthetic/Cotton Blend 0.8-3.6%
- Synthetic Staple 0.8-3.6%
- Synthetic Filament 0.6-1.6%
- Linen & Linen Blends 3.9-4.0%

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Water-white viscous liquid**
% Activity, %		**25 ± 1**
pH		**6.0-8.0**
Ionic Character		**Nonionic**
Viscosity (B4 Ford Cup), °C		**< 20 secs @ 20**
Anti-static Properties		**Excellent**
Solubility, °C		**Soluble in water and dry cleaning solvents at 50-100**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS FG0003

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063