SPECIALITIES

UNIVERSAL ANTIFREEZE 50:50.

The conventional blue coolant supplied ready mixed at 50:50, giving frost protection to -40 °C straight from the drum.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Workshop servicing where mix accuracy matters
- Roadside and field top-ups
- Hard water areas where dilution would scale the system
- Fleet operations standardising on one product

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Blue**
Conforms to British Standard		**BS 6580:2010**
Freeze Point Protection, °C		**-40**
Specific Gravity	ASTM D1298	**1.06-1.075**
pH Value 50% Aqueous Solution		**7.8**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0942

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063