INDUSTRIAL OILS

VACUUM PUMP OIL 320.

A mineral vacuum pump oil for rotary and slide vane pumps.

PRODUCT RANGE
Vacuum & Airline Oils

288 – 352 cSt	25.1 cSt	>240 °C	-8 °C
Viscosity @ 40°C	Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Rotary vane and slide vane vacuum pumps
- Vacuum packing and forming lines
- Laboratory and process vacuum systems
- Vacuum lifting and handling equipment

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity (cSt) @ 40°C		288 – 352
Kinematic Viscosity (cSt) @ 100°C		25.1
Viscosity Index	ASTM D2270	101
Density @ 15.6°C		0.900 – 0.950
Flash Point (COC), °C		>240
Pour Point, °C		-8
Vapour Pressure kPa @ 20°C		<0.1

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IV0324

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063