INDUSTRIAL OILS

# VACUUM PUMP OIL 68.

A mineral vacuum pump oil for rotary and slide vane pumps.

PRODUCT RANGE
Vacuum & Airline Oils

| 8.8 cSt | >224 °C | -24 °C |
|---|---|---|
| Viscosity @ 100°C | Flash point | Pour point |

## APPLICATION

- Rotary vane and slide vane vacuum pumps
- Vacuum packing and forming lines
- Laboratory and process vacuum systems
- Vacuum lifting and handling equipment

### NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Kinematic Viscosity (cSt) @ 40°C | | 61.2 – 74.8 |
| Kinematic Viscosity (cSt) @ 100°C | | 8.8 |
| Viscosity Index | ASTM D2270 | 102 |
| Density @ 15.6°C | | 0.870 – 0.885 |
| Flash Point (COC), °C | | >224 |
| Pour Point, °C | | -24 |
| Vapour Pressure kPa @ 20°C | | <0.1 |

Typical values. They do not form a specification.

## PACK SIZES

5 L, 20 L, 205 L

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IV0068

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063