METALWORKING FLUIDS

VANISHING OIL S26.

VANISHING OIL S26 is a low viscosity lubricant designed for high speed presswork operations producing relatively small or flat components, formulated with natural ester for film strength and surface finish, based on a lo

PRODUCT RANGE
Drawing & Forming Oils

2 mm2/s cSt	0.812	56 °C
Viscosity @ 40°C	Specific Gravity @20	Flash point

APPLICATION

- Drawing
- stamping and blanking
- light to moderate draws
- high speed operations
- light to medium gauge sheet

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Light yellow**
Viscosity @40°C		**2 mm2/s**
Chlorine	ASTM D808	**No**
Sulphur		**No**
Ester		**Yes**
Flash Point, °C		**56**
Specific Gravity @20°C		**0.812**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0026

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063