GREASES

WHITE BRAKE GREASE.

A calcium 12-hydroxystearate grease with 5% zinc oxide, for brake hardware.

PRODUCT RANGE
Automotive Greases

APPLICATION

- Brake slider pins and caliper hardware
- Backing plate contact points
- Preventing seized brake components
- General corrosion protection on chassis fittings

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Off-white smooth grease**
NLGI classification		**2**
Base Oil		**Highly refined mineral oil**
Thickener		**Calcium 12 hydroxy stearate**
Zinc oxide content, %		**5**
Operating temperature range, °C		**-20°C to +110**
Water washout @38°C (ASTM D1264), %		**2**
Water washout @79°C (ASTM D1264), %		**5**
Dropping point (IP132)		**+140°C min**

Typical values. They do not form a specification.

PACK SIZES

500 g, 3 kg, 12.5 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0906

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063