GREASES

WIRE ROPE GREASE 00.

A semi-fluid moly grease for wire rope and chain.

PRODUCT RANGE
Semi-Fluid & Centralised Greases

APPLICATION

- Dockside and ship crane ropes
- Draglines and dragline ropes
- Hoist and mobile crane ropes
- Chains exposed to weather and sea water

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Semi-Fluid Grease**
Colour	ASTM D1500	**Grey/Black**
NLGI Classification		**00**
Base Oil		**Solvent Refined Mineral Oil**
Thickener		**Lithium Soap**
Solids Content		**Molybdenum Disulphide**
Emcor (IP 220)		**0 : 0**
Four Ball Weld Load (IP 239) kgs		**315**
Wear Load Index		**70**
Timken OK Load (IP 326) lbs		**40**
Operating Temperature Range, °C		**-40°C to +140**

Typical values. They do not form a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0410

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063