INDUSTRIAL OILS

WIRE ROPE LUBRICANT.

A solvent-carried, moly-fortified wire rope lubricant.

PRODUCT RANGE
Industrial Specialities

APPLICATION

- Crane and winch ropes
- Dockside and marine wire rope
- Lift and hoist ropes
- Forestry winch and skidder cable
- Ropes exposed to salt water

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Grey/black liquid**
Base Fluid		**Mineral Oil**
Carrier Solvent		**Odourless Kerosene**
Solids Content	3% after solvent evaporation	**2% Molybdenum Disulphide**
Timken OK Load (IP326)		**20kg**
Shell Four Ball Weld Load (IP239)		**320kg**
Dynamic Corrosion Resistance EMCOR (IP220)		**0:0**
Temperature Range, °C		**-40°C to 120**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0905

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063