SPECIALITIES

X-OAT LONGLIFE VCS-2 ANTIFREEZE.

A premium MEG-based extended life coolant using the latest OAT chemistry, free from 2-EHA, nitrites and borates.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Systems specifying 2-EHA free coolant
- Volvo, Mack and Renault VCS-2 requirements
- Jaguar Land Rover STJLR.03.5212
- Extended-life fills in mixed fleets

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 16 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
JIS	K2234-2018
CATERPILLAR/PERKINS, CLAAS, DAF, VOITH	
ISUZU/UD	TRUCKS
JOHN	DEERE POWER SYSTEMS
JAGUAR	ST JLRL.03.5212
LAND	ROVER ST JLRL.03.5212
MACK	VCS-2
RENAULT	VCS-2
VOLVO	VCS-2

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pink/Light Red Colour**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0564

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063