

QA Bug Report — Softomedia Live Platform

Project: Softomedia Live 2026 (Digital Screen Network Management Platform)
Tech Stack: React 18 + Vite 5 frontend, Express.js backend, Firestore (NoSQL), Zustand state management
Auth: JWT-based, role-governed. Roles: superadmin, contentmanager, techoperator, retaileradmin, advertiser
Reference files: database_schema.md, data_dictionary.md, url_screen_inventory.md, user_stories_use_cases.md

1. Super Admin — CPM Pricing

Route: /dashboard/admin/pricing

BUG — Section Label Overlay Toggle

Description: Add a toggle in the Super Admin UI that enables/disables overlay labels (section/zone names) visible on the network map or player view. This is a debugging/troubleshooting tool intended for internal use only.

- Toggle should be visible only to users with `role === 'superadmin'` (see `data_dictionary.md` → User Entity).
- Persisting the toggle state in-memory (Zustand store) is sufficient; it does not need to be saved to Firestore.
- When ON: section name labels are rendered over the relevant UI zones.
- When OFF: labels are hidden (default state for all users including Super Admin).

2. Users — /dashboard/admin/users

Reference: `url_screen_inventory.md` → Route 14 (/dashboard/admin/users) — "IAM control. Reads/Writes `users` collection."

BUG — "Add User" Form Does Not Save

Description: Clicking "Add User" opens a modal/dialogue. The form must capture the following 4 fields (mapped to Firestore `users` collection — see `data_dictionary.md` → User Entity):

UI Label	DB Field	Type	Validation
Full Name	name	string	Required, min length 1
Email	email	string	Required, unique, valid email format

UILabel	DB Field	Type	Validation
Role	role	string (enum)	Required. Values: superadmin, contentmanager, techoperator, retaileradmin, advertiser
Assign to Advertiser	linkedentityid	string (FK)	Conditional—required when role == 'advertiser' or role == 'retaileradmin'

- The "Create User" button must POST to the users API and write a new document to the Firestore `users` collection.
- On success, the new user must appear immediately in the Users table (optimistic update or re-fetch).
- The `status` field should default to `active` on creation.
- Auto-populate `createdat` and `updatedat` via `BaseRepository` audit fields.

BUG — Actions Column Missing Delete Functionality

Description: The `Actions` column in the `Users` table row is missing a `Delete` action.

- Add a delete icon (suggest: `Trash2` from `Lucide React` — consistent with the existing icon library per `tech_stack.md`).
- On click: show a confirmation prompt before permanently removing the user document from Firestore.
- On confirm: call `DELETE /api/users/:id`, remove the document from the `users` collection, and remove the row from the table.

3. Retailers — /dashboard/admin/retailers

Reference: `url_screen_inventory.md` → Route 15 (`/dashboard/admin/retailers`) — "B2B relationship management. Reads/Writes `retailers` and `stores`."

BUG — "Add Retailer" Dialogue Does Not Persist

Description: The "Add Retailer" dialogue opens but the new Retailer is not being added to the `Retailers` table after submission.

- Form fields map to the Firestore `retailers` collection (see `data_dictionary.md` → `Retailer Entity`): `name`, `logo`, `contactemail`, `contractstart`, `status`.
- On submit: `POST /api/retailers` → write new doc to `retailers` collection.
- On success: new Retailer must appear in the `Retailers` table. Re-fetch or append to local state.

BUG — Remove Retailer Not Implemented

Description: No delete functionality exists for Retailer rows.

- Add a Remove action to the Retailers table row Actions column.
- On click: confirmation prompt → `DELETE /api/retailers/:id` → remove from `retailers` collection and from UI.
- Consider cascading impact: associated `stores` and `screens` records reference this `retailerid`. Decide on a hard-delete vs. soft-delete strategy (recommend: set `status = 'inactive'` rather than hard-delete to preserve referential integrity with loops, `impressions`, etc.).

BUG — Make Retailer Inactive Not Implemented

Description: There is no way to toggle a Retailer's operational status.

- Add a Make Inactive action (or toggle) on the Retailer row.
- This should `PATCH /api/retailers/:id` and set `status` to `inactive` in the Firestore `retailers` collection.
- The `status` field accepts: `active`, `inactive` (see `database_schema.md` → `retailers` collection).
- Reflect the status change visually in the table row (e.g., a status badge).

4. Advertisers — `/dashboard/admin/advertisers`

Reference: `url_screen_inventory.md` → Route 17 (`/dashboard/admin/advertisers`) — reads/writes `advertisers` collection.

BUG — "Add Advertiser" Dialogue Does Not Persist

Description: The "Add Advertiser" dialogue opens but the new Advertiser is not being saved to the Advertisers table.

- Form fields map to the Firestore `advertisers` collection (see `data_dictionary.md` → Advertiser Entity): `name`, `logo`, `industry`, `contactemail`, `budget`, `status`.
- On submit: `POST /api/advertisers` → write new doc to `advertisers` collection with `id` prefixed `adv`.
- On success: new Advertiser must appear in the Advertisers table immediately.

BUG — Remove Advertiser Not Implemented

Description: No delete functionality exists for Advertiser rows.

- Add a Remove action to the Advertisers table row Actions column.
- On click: confirmation prompt → `DELETE /api/advertisers/:id` → remove from `advertisers` collection.

- Note the same cascading concern as Retailers: campaigns reference advertiserid. Recommend soft-delete: set status = 'suspended' rather than hard-deleting.

5. Demo Player — /player

Reference: url_screen_inventory.md → Route 1 (/player) — "Primary playback engine for physical hardware. Reads from loops and media."

BUG — Playback Requires Correct Selection Sequence

Description: The Demo Player must enforce a cascading selection sequence before playback begins:

1. Select Retailer → populates Store dropdown (filters stores by retailerid)
 2. Select Store → populates Screen dropdown (filters screens by storeid)
 3. Select Screen → loads the schedule for that specific screen
- Data model: retailers → stores (FK: retailerid) → screens (FK: storeid) → loops (FK: screenid + date + hour)
 - No playback should be possible until all three levels are selected.

BUG — Demo Player Must Play Full Day Schedule

Description: The player currently does not play the full schedule of a specific day correctly.

- On play: fetch all loops documents for the selected screenid and today's date (or a user-selected date).
- Each loop has 12 slots (loops collection → slots array, index 0–11). Play each slot's creativeurl once per loop, in order.
- Every loop in the day's schedule should be played exactly once per cycle — do not repeat a loop until all loops for the day have been played.
- Reference: user_stories_use_cases.md → Use Case 5 (Daily Loop Generation) for loop structure details.

6. Store Hours — /dashboard/admin/hours

Reference: url_screen_inventory.md → Route 16 (/dashboard/admin/hours) — "Reads/Writes storedefaulthours."

No bugs noted. This item was listed in QA notes without a specific issue. No changes required at this time.

7. Network Map

Reference: Part of the Admin or Retailer dashboard — likely `/dashboard/admin` or `/dashboard/retailer`.

BUG — Map Does Not Render

Description: The network map component is present in the UI but is not displaying.

- Likely cause: map library not initialized or a missing API key / config.
- The platform uses Google Cloud Platform (see `tech_stack.md` → Infrastructure). If using Google Maps, verify the Maps JavaScript API key is available and correctly passed to the map component.
- Alternatively, if using a different mapping library (e.g., Leaflet, Mapbox), verify the CDN or npm dependency is loaded and the container `div` has a non-zero height/width set in CSS.
- Each pin/marker on the map should represent a store record. Use `stores.address` + `stores.city` fields for geolocation (see `data_dictionary.md` → Store Entity).
- Investigate: is the map container receiving a `height: 0` or `display: none` from a parent component? This is the most common cause of blank map renders.

8. Brand Dashboard — `/dashboard/brand`

Reference: `url_screen_inventory.md` → Routes 19–20. Route 19 = Brand Dashboard, Route 20 = Campaign Wizard (`/dashboard/brand/campaign/new`).

OK — Preview Demo

No action needed. Feature is working correctly. Do not modify.

OK — New Campaign Wizard (`/dashboard/brand/campaign/new`)

Working correctly. Do not modify.

BUG — Campaign Edit Does Not Work

Route: Campaign list table → Actions column → Edit button.

Description: Clicking Edit on a Campaign row does not navigate to the Campaign edit view.

- **Expected behavior:** Clicking Edit should navigate to (or open) the Campaign edit view, pre-populated with all existing campaign data for that campaign (`id`, `name`, `advertiserid`, `startdate`, `enddate`, `budget`, `status`, `creativeurl`, etc. — see `data_dictionary.md` → Campaign Entity).
- **Implementation guidance:** Re-use the "New Campaign" wizard (`/dashboard/brand/campaign/new`) with the existing campaign's data pre-filled. Pass the `campaignId` as a route param or state: e.g., `/dashboard/brand/campaign/:id/edit` or load it into the Campaign Wizard's Zustand/local state with an `editMode: true` flag.

- The wizard steps and field validations defined for New Campaign apply identically to Edit Campaign.
- On save: PUT /api/campaigns/:id to update the existing document in the campaigns Firestore collection.

INFO — Campaign Pause Action

Currently no functionality. Leave as-is for now. No changes required.

INFO — Campaign Settings Action

Currently no functionality. Leave as-is for now. No changes required.

BUG — Campaign Status Column Shows Incorrect Values

Description: The Status column in the Campaign table should display Live only for campaigns that are currently running at the time of viewing.

- A campaign is "Live" when: `campaign.status === 'live'` AND today's date falls within `startdate ≤ today ≤ enddate`.
- A campaign that has `status === 'live'` in Firestore but whose `enddate` has passed should display as Completed (or Ended).
- A campaign with a future `startdate` should display as Scheduled (maps to status: `'scheduled'` in the DB).
- Derive the displayed status client-side from the `status` DB field combined with the current date. Do not rely solely on the raw `status` field value for display.
- Status enum in DB: `draft`, `pendingapproval`, `scheduled`, `live`, `ended` (see `data_dictionary.md` → Campaign Entity).

9. Retailer Dashboard — /dashboard/retailer

Reference: `url_screen_inventory.md` → Routes 21-24.

BUG — "Report Issue" Not Functional

Listed as a known bug. Needs implementation plan — details TBD.

BUG — Disconnect / Reestablish Not Functional

Listed as a known bug. Needs implementation plan — details TBD.

BUG — Schedule Calendar Not Functional

Listed as a known bug. Needs implementation plan — details TBD.

BUG — Approval History "Go Back" Navigation Broken

Route: `/dashboard/retailer/history` (Route 24 — Playback History).

Description: The "Go Back" button in the Approval History / Playback History view does not navigate back to the Retailer dashboard (`/dashboard/retailer`).

- **Fix:** replace the broken back button handler with `navigate('/dashboard/retailer')` using React Router's `useNavigate()` hook, or use `<Link to="/dashboard/retailer">`.
- Verify that `DashboardLayout.jsx` breadcrumb/back navigation is correctly wired for the Retailer persona routes.

10. Demo Player — Add Location

Context: This is a Super Admin action. The platform does not yet have a Retailer login flow. Until it does, Super Admin performs Retailer-level actions.

BUG — "Add Location" Does Not Create a New Store

Description: Entering a store name in the Add Location form and submitting does not create a new store in the database.

- On submit: `POST /api/stores` → write new document to Firestore `stores` collection.
- Required fields: `name` (store name entered), `retailerId` (must be selected — see Retailer Selector bug below), `address`, `city`, `status` (default: `active`) — see `data_dictionary.md` → Store Entity.
- On success: the new store should appear in the store list/selector immediately.

BUG — No Retailer Context Selector for Super Admin (Testing Aid)

Description: Since there is no Retailer login yet, Super Admin needs a way to act in the context of a specific Retailer when using Retailer-facing views (e.g., Add Location, Demo Player).

Fix: Add a Retailer selector dropdown adjacent to the "Retailer Command Center" heading (or in the top header for Retailer-persona views).

- Populate the dropdown from the Firestore `retailers` collection (fetch all active retailers: `GET /api/retailers`).
- Display value: `retailer.name`. Store value: `retailer.id`.
- Selecting a Retailer sets the active `retailerId` context in Zustand/local state, which is then used for all subsequent API calls on that page (e.g., fetching stores, screens, loops scoped to that Retailer).
- This is a testing/admin tool only. It should only be visible when `role === 'superadmin'`.

11. Store Locations — Data Audit

QUESTION — Unexpected Store Locations Appearing

Observation: The UI is showing 4 Store Locations that were not expected.

Investigation required:

- Query the Firestore `stores` collection and list all documents with their `retailerid`, `name`, `city`, and `status` fields.
- Cross-reference each `retailerid` against the `retailers` collection to identify which Retail Partner each store belongs to.
- Likely cause: seed/mock data (the platform uses an in-memory `MOCKSTORAGE` fallback in `BaseRepository.js` — see `tech_stack.md`) may have pre-populated test store records. Confirm whether these are legitimate records or leftover mock data.
- **Resolution:** If mock/seed data, either clear the `MOCKSTORAGE` records or add a filter in the UI to exclude stores not linked to the currently selected Retailer context.

12. Tech Ops Dashboard — `/dashboard/tech`

Reference: `url_screen_inventory.md` → Route 25 (`/dashboard/tech`) — "Hardware Stats, Error Log, Health Badges. Real-time monitoring of screen fleet."

BUG — Tech Ops View Shows Incomplete Data

Description: The Tech Ops dashboard should display comprehensive, aggregated network-wide data.

Expected data scope:

- **Sum of all Retail Partners** — total count of all active `retailers`.
- **Sum of all Store Locations** — total count of all `stores` across all `retailers` (not scoped to a single Retailer).
- **Sum of all Screens** — total count of all `screens` across all `stores` and `retailers`.
- Additionally: real-time status breakdown (online / offline / error) for `screens`, consistent with the `screens.status` field values: `online`, `offline`, `error` (see `database_schema.md` → `screens` collection).

Fix: The API calls powering this view must not be filtered by a single `retailerid`. They should aggregate across all records:

- `GET /api/retailers` → total count
- `GET /api/stores` (no retailer filter) → total count
- `GET /api/screens` (no store/retailer filter) → total count + status breakdown

Roles with access to this view: superadmin, techoperator (see data_dictionary.md → User Entity → Role enum).

End of QA Bug Report