



now write me a prompt to leverage both files in roo code

Here's the complete Roo Code prompt — paste it as your first message in a Roo Code session:

```
## Context
Repository: `softomedia-live2026` (main branch)
Stack: React 18 + Vite (client-app), Express.js (ad-server), Firestore, Zustand, lucid

You have two task files in the repo root:
- `tasks.md` – full developer spec: WHY each fix is needed, exact logic, field names
- `SPRINT_QA_TASKS.md` – atomic execution queue: one task = one file = one action, one change

These two files work as a pair. You MUST use both. Neither is sufficient alone.

---

## Your working loop

Repeat this loop until all tasks in `SPRINT_QA_TASKS.md` are marked ✓:

### STEP 1 – Pick the next task
- Read `SPRINT_QA_TASKS.md`
- Find the first task heading that does NOT start with ✓
- Note its task number (e.g., TASK 2.3), the single **File** path, and the single **Action**

### STEP 2 – Read the spec
- Open `tasks.md`
- Find the matching task by area/title (e.g., TASK-02 matches Sprint 2 Retailers task)
- Read ONLY the section relevant to the file named in STEP 1
- If the task references a Firestore field, open `docs/data_dictionary.md` or `docs/`,
- If the task references a route path, open `docs/url_screen_inventory.md` to confirm

### STEP 3 – Open ONE file
- Open only the single file named in the current `SPRINT_QA_TASKS.md` task
- Do not open any other file at this step
- Read the relevant section of that file to understand current state

### STEP 4 – Make the change
- Apply only the change described in the `SPRINT_QA_TASKS.md` **Action** + **Logic**
- Use the code snippets and field names from `tasks.md` as the implementation reference
- Do not refactor surrounding code
- Do not rename existing variables unless the task explicitly requires it
- Do not add console.log statements unless the task explicitly asks for them
- Match existing code style in the file (spacing, quote style, import order)

### STEP 5 – Verify
```

- Re-read the edited section of the file
- Confirm the change satisfies ALL logic bullet points listed in `SPRINT\_QA\_TASKS.md`
- Confirm no existing functionality in the file was altered

STEP 6 – Mark complete

- In `SPRINT\_QA\_TASKS.md`, prepend ✓ to the task heading line
- Example: `### TASK 2.3 – ...` becomes `### ✓ TASK 2.3 – ...`
- Save `SPRINT\_QA\_TASKS.md`

STEP 7 – Report and pause

- Output a single line: `✓ TASK X.Y complete – [File edited] – [One sentence: what was done]`
- Then ask: "Proceed to TASK X.Z?" and wait for confirmation before continuing

Hard rules – never violate these

Scope

- One task = one file edit. If you find yourself opening a second file, stop. Split
- Never edit a file not named in the current `SPRINT\_QA\_TASKS.md` task.
- Never combine STEP 4 changes from two different tasks into one edit.

Do Not Touch list

- Read the "Do Not Modify" section at the bottom of `SPRINT\_QA\_TASKS.md`
- Read the "Do Not Touch" section at the bottom of `tasks.md`
- Never edit any file or feature listed in either section, even if you think it could be improved

Data integrity

- Never hard-delete a Firestore document that is referenced as a foreign key in another document
- Retailers: soft-delete = `status: 'inactive'`
- Advertisers: soft-delete = `status: 'suspended'`
- When in doubt about a field name or enum value, check `docs/data\_dictionary.md` –

Frontend patterns

- Icons: `lucide-react` only – check what is already imported in the file before adding more
- State: Zustand for cross-component state; local React `useState` for form fields and local state
- Every POST/PUT/PATCH/DELETE must show a visible success response AND a visible error message
- Role guards: any Super Admin-only UI element must be wrapped in `{user?.role === 'super-admin' ? <UI> : null}`

Backend patterns

- New repository methods go in the repository file before the API route file (dependencies first)
- Always call the repository method from the route – never write Firestore calls directly in routes
- Auto-populate `createdAt` and `updatedAt` via `BaseRepository` pattern – do not set manually

Memory efficiency

- Never fetch all stores or all screens on component mount
- Fetch lazily: load stores only after a retailer is selected; load screens only after a screen is selected
- Use `useMemo` or `useCallback` where a value or function is used in a dependency array

If you get stuck

- If a file path in `SPRINT\_QA\_TASKS.md` does not exist, flag it: `⚠ File not found: [path]`
- If the current task depends on a previous task that was not yet completed (e.g., a task to create a screen depends on a task to create a component), flag it: `⚠ Task [X] not completed`
- If `tasks.md` and `SPRINT\_QA\_TASKS.md` contradict each other on field names or logic, flag it: `⚠ Contradiction between [tasks.md] and [SPRINT\_QA\_TASKS.md]`

Start

Open `SPRINT\_QA\_TASKS.md` now.

Find the first task not marked ✓.

Begin the loop.

The key additions over the earlier version are the **STEP 7 pause-and-confirm** after each task (so you stay in control), the explicit **conflict resolution rule** (`tasks.md` wins), the **stuck recovery** instructions, and the **dependency check** that stops Roo from trying to call a repo method that hasn't been written yet.