



04 Linked Lists

Problem: Large Arrays!

Linked List: A array that grows according to needs

Linked List: Code

Size of a Liniked List

A recursive solution

Printing elements of a linked list

Find the element at the ith position

A recursive solution

Append element to end of the list

Full code

HW: Insert element at a position in the list

HW: Concatenate 2 lists

HW: Reverse a list

04 Linked Lists

Problem: Large Arrays!

```
#define MAX_MEMBERS 100
```

```
typedef struct SocialNet {  
    Person members[MAX_MEMBERS];  
    int size;  
} SocialNet;
```

Linked List: A array that grows according to needs

Linked List: Code

```
typedef struct Node {  
    Person data;  
    struct Node* next;  
} Node;  
  
typedef Node* LinkedList;
```

```
Node third = {  
    {"Alice", 22},  
    NULL  
};  
Node second = {  
    {"Bob", 26},  
    &third  
};  
Node first = {  
    {"Charlie", 20},  
    &second  
};
```

```
LinkedList L = &first;
```

Size of a Liniked List

```
int size(LinkedList l) {  
    int s = 0;  
    while (l != NULL) {  
        l = l->next;  
        s ++;  
    }  
    return s;  
}
```

A recursive solution

```
int size(LinkedList l) {  
    return l==NULL? 0: size(l->next) + 1;  
}
```

Printing elements of a linked list

```
void print_list(LinkedList l) {  
    while (l != NULL) {  
        printf("%s\t\t%d\n", l->data.name, l->data.age);  
        l = l->next;  
    }  
}
```

Find the element at the ith position

```
Person* element_at(int pos, LinkedList l) {
    int s = 0;
    while (l != NULL) {
        if (s == pos) return &(l->data);
        l = l->next;
        s ++;
    }
    return NULL;
}
```

A recursive solution

```
Person* element_at_recursive(int pos, LinkedList l) {
    // TODO
    if (l==NULL) return NULL;
    if (pos == 0) {return &(l->data);}
    else { return element_at(pos-1, l->next); }

    // return pos == 0 ? &(l->data): element_at(pos-1, l->next);
}
```

Append element to end of the list

```
LinkedList append(Person p, LinkedList l) {
```

```

// Node D = {"Raj", 18}, NULL}; Local Variable! Will not work.
Node* D = (Node *) malloc(sizeof(Node));
D->data = p;
D->next = NULL;
if (l == NULL) return D; // if l is empty just return D.
while (l->next != NULL) {
    l = l->next;
}
l->next = D;
return l;
}

```

Full code

```

#include "stdio.h"
#include "stdlib.h"
#define MAX_NAME_LEN 100

typedef struct Person {
    char name[MAX_NAME_LEN];
    int age;
} Person;

typedef struct Node {
    Person data;
    struct Node* next;
} Node;

typedef Node* LinkedList;

```

```

void print_list(LinkedList l) {
    printf("-----\n");
    while (l != NULL) {
        printf("%s\t\t%d\n", l->data.name, l->data.age);
        l = l->next;
    }
    printf("-----\n");
}

```

```

int size(LinkedList l) {
    int s = 0;
    while (l != NULL) {
        l = l->next;
        s ++;
    }
    return s;
    // Simpler recursive solution
    // return l==NULL? 0: size(l->next) + 1;
}

```

```

Person* element_at(int pos, LinkedList l) {
    int s = 0;
    while (l != NULL) {
        if (s == pos) return &(l->data);
        l = l->next;
        s ++;
    }
    return NULL;
}

```

```

Person* element_at_recursive(int pos, LinkedList l) {
    // TODO
    if (l==NULL) return NULL;
}

```

```

    if (pos == 0)    {return &(amp;1->data);}
    else { return element_at(pos-1, 1->next); }

    // return pos == 0 ? &(1->data): element_at(pos-1, 1->next);
}

```

```

LinkedList append(Person p, LinkedList l) {

```

```

    // Node D = {"Raj", 18}, NULL};
    Node* D = (Node *) malloc(sizeof(Node));
    D->data = p;
    D->next = NULL;
    if (l == NULL) return D;
    while (l->next != NULL) {
        l = l->next;
    }
    l->next = D;
    return l;
}

```

```

int main() {
    Node third = {
        {"Alice", 22},
        NULL
    };
    Node second = {
        {"Bob", 26},
        &third
    };
    Node first = {
        {"Charlie", 20},
        &second
    };
}

```

```

Person D = {"Raj", 18};

LinkedList l = &first;
printf("Size of the list is %d\n", size(l));
print_list(l);
printf("Element at 1st position: %s\n", element_at(1,l)->name);
printf("Element at 2nd position: %s\n", element_at(2,l)->name);
append(D, l);
printf("List after appending\n");
print_list(l);
return 0;
}

```

HW: Insert element at a position in the list

```

LinkedList insert(Person p, int pos, LinkedList l) {
    // TODO
}

```

HW: Concatenate 2 lists

```

LinkedList concat(LinkedList l1, LinkedList l2) {
    // TODO
}

```

HW: Reverse a list


```
LinkedList reverse(LinkedList l) {  
    // TODO  
}
```