# 4200 - Formal Languages: Final Exam

Fall 2020

May 1, 2020 at  $8{:}00$  -  $10{:}30\mathrm{am}$ 

Student:

**Directions:** The test is open-book and open-note, but using electronic devices (e.g. phone, tablets or computers) during the exam is NOT allowed. For each problem, show your work completely. Give reasons for all answers.

There are 7 problems for a total of 85 points.

## Problem 1

10 points

$$A = \{0, 1, 2\}^*$$
  
 $B = \{0, 1\}^*$   
 $C = A - B$ 

For each of the languages (A, B, and C), write down five example strings in it. Define a <u>deterministic</u> finite automaton (DFA) that recognizes the language C.

### 10 points

Define a regular expression that recognizes the set A that passwords that satisfy the following criteria:

- Minimum password length: 2
- Maximum password length: 4
- Each character in the password must be one of the following LaTeX: { a, b, c, A, B, C, 1, 2, 3 }
- Password must contain at least one upper-case letter
- Password must contain at least one number

#### Answer:

$$\Sigma = \{a, b, c, A, B, C, 1, 2, 3\} \tag{1}$$

$$U = \{A, B, C\} \tag{2}$$

$$N = \{1, 2, 3\} \tag{3}$$

$$\alpha =$$
 (4)

$$NU \cup UN$$
 (5)

$$\cup \Sigma NU \cup \Sigma UN \cup U\Sigma N \cup UN\Sigma \cup N\Sigma U \cup NU\Sigma$$
 (6)

#### 15 points

Given a language  $E = \{1^n 0^m 0^{2n+1} \mid n, m \ge 0 \}$ . Please answer the following questions:

- 1. Is the above language regular or non-regular?
- 2. Is the above language context-free or not?
- 3. Is the above language Turing-recognizable or not?
- 4. Based on your answers to the above questions, please answer one of the following:
  - a. If you answer E is regular and context-free, please provide an NFA or a regular expression that recognizes E.
  - b. If you answer E is regular and NOT context-free, please provide a proof (showing E is not context-free) using Pumping Lemma for Context-free Languages.
  - c. If you answer E is NOT regular and context-free, please provide a proof (showing E is not regular) using Pumping Lemma for Regular Languages.
  - d. If you answer E is NOT regular and NOT context-free, please provide a proof (showing E is not context-free) using Pumping Lemma for Context-free Languages.

#### 15 points

Given a language  $G=\{1^x0^y1^x0^y\mid x,y\geq 0\ \}\cup \{1^k0^n1^k0^v\mid k,v,n\geq 0\ \}.$  Please answer the following questions:

- 1. Is the above language regular or non-regular?
- 2. Is the above language context-free or not?
- 3. Is the above language Turing-recognizable or not?
- 4. Based on your answers to the above two questions, please answer one of the following:
  - a. If you answer G is regular and context-free, please provide an NFA or a regular expression that recognizes G.
  - b. If you answer G is regular and NOT context-free, please provide a proof (showing G is not context-free) using Pumping Lemma for Context-free Languages.
  - c. If you answer G is NOT regular and context-free, please provide a proof (showing G is not regular) using Pumping Lemma for Regular Languages.
  - d. If you answer G is NOT regular and NOT context-free, please provide a proof (showing G is not context-free) using Pumping Lemma for Context-free Languages.

## 15 points

Given a language  $H=\{1^x0^y1^x0^y\mid x,y\geq 0\ \}\cap \{1^k0^n1^k0^v\mid k,v,n\geq 0\ \}.$  Please answer the following questions:

- 1. Is the above language regular or non-regular?
- 2. Is the above language context-free or not?
- 3. Is the above language Turing-recognizable or not?
- 4. Based on your answer to question 1 above, please answer one of the following:
  - a. If you answer H is regular, please provide an NFA or a regular expression that recognizes H.
  - b. If you answer H is NOT regular, please provide a proof (showing H is not regular) using Pumping Lemma for Regular Languages.