Selecting, Not Smoothing: Physically Grounded Object Trajectories from Egocentric Video for Dexterous Robot Imitation

V2D Challenge 2026 — Track 3 Technical Report

Kiarash Ghasemzadeh[1]
[1]University of Alberta & Amii, kghasemz@ualberta.ca

Abstract: We present our Track 3 system, which turns an egocentric stereo recording of a person manipulating kitchen objects into a dexterous robot-hand policy in simulation. Using only our own reconstructions (no provided scans or motion capture), we estimate metric object meshes, hand motion and 6-DoF object trajectories, ground them physically, and train one policy per episode with soft actor-critic. Our main lesson is that object trajectories must be *selected* globally rather than smoothed locally: we keep every FoundationPose hypothesis per frame and choose a whole-sequence path with SAM 3 masks and TrackEverything 3D point tracks, which removes the 180° flips and self-spins that make human motion impossible to imitate. Simulator-side grounding (settled resting poses, collision geometry, hands pushed out of objects) matters as much as pose accuracy. Our best submission reaches AUC 0.584, SP-SR 0.650 and MPPE 6.06 cm.

1. Introduction

Track 3 of the Video to Data challenge [9] asks for an end-to-end transfer: from an egocentric video (colour camera plus a mono stereo pair) a robot policy must re-enact the human manipulation in the Flash-CHORD simulator [8] with floating Sharpa hands, and the objects it moves are scored against hidden ground truth; reconstructed meshes are scored separately (CD-O). Chaining off-the-shelf components fails at the hand–object interface: under hand occlusion and for near-symmetric objects (a spoon, a lid, flat boards) per-frame poses flip by up to 180°, held objects spin relative to the hand, and resting objects start tilted into the table. A robot cannot imitate such references. Recent work tackles the same interface by multi-hypothesis selection [2], contact-aware factor graphs [5], learned hand/object trust [15], agentic generation [14] and diffusion denoising [6]. Our contributions:

- SelectTrack: whole-sequence selection among all FoundationPose [20] hypotheses, scored by hand-aware SAM 3 silhouettes [1] and constrained by TrackEverything [4] 3D point tracks, followed by physically motivated filters;
- simulator grounding: simulator-settled starts, hand depenetration, container-aware collision and data-driven mesh corrections, which turned several never-solved episodes into successes;

2. Approach

Perception. We rectify the published colour-to-stereo extrinsic (3.4 vs. 18.9 px reprojection error), run FoundationStereo [21] for metric depth and DROID-SLAM [16] for ego-motion, and fit the round table plane for gravity. SAM 3 [1] segments objects and hands. Object meshes come from SAM 3D Objects [12] on automatically picked unoccluded views, metrically scaled by stereo depth; the consensus of several samples is kept. Hands are Dyn-HaMR [22] MANO [11] trajectories in metric scale; the few frames it misses (3157392%) fall back to WiLoR [10] keypoints triangulated across the stereo pair.

Object trajectories (SelectTrack). For every frame t we keep all $K \approx 252$ refined FoundationPose hypotheses X_t^k with scores s_t^k, instead of the argmax. TrackEverything [4] supplies surface points $p_n(t)$ tracked in the SLAM world (seeded on object masks minus hand pixels). Following the multi-hypothesis idea of Hand2Robot [2], we decode one hypothesis per frame by Viterbi,

$$\min_{k_{1:T}} \sum_t \Big[1 - \hat{s}_t^{k_t}\,\mathrm{IoU}_t^{k_t} + \lambda_p\, d_{\mathrm{surf}}(X_t^{k_t}) + \lambda_m \textstyle\sum_n \big\| X_t^{k_t}(X_{t-1}^{k_{t-1}})^{-1} p_n(t-1) - p_n(t) \big\| \Big], \tag{1}$$

where IoU ignores hand pixels (a covering hand is not evidence), d_{surf} is the distance of visible tracked points to the hypothesis surface, and the pairwise term demands that consecutive hypotheses move the tracked points as they actually moved; a flip or spin




Figure 1: Learned policy re-enacting the dust-pan episode (eval ep. 38): grasp at the ring handle, carry, set down. This episode was never solved before simulator-settled starts and stickier contact (own-reference MP-SR $0 \rightarrow 0.98$).

becomes expensive. Tracks are then anchored in the object frame so that points seen far apart in time land on the same mesh location. Physical filters follow: a speed-limit Viterbi that keeps, flips or drops frames ($\leq 20°$, 6 cm per frame), a rest hold for untouched objects, a spin guard letting held objects rotate only with the holding hand plus slip (inspired by [5, 15]), and exact twist unwrapping for rotationally symmetric cups. A VICON-style soft pose graph [5] improved mocap accuracy slightly but cannot escape a 180° flip; we also considered [7, 17, 23].

Simulator grounding. Reconstructed fingers sat 2–4 cm inside cups, so reset shoved hand and cup apart; we translate each hand (time-smoothed) out of every object. Resting objects carried a $\sim 12°$ tilt about the camera's horizontal axis—the least observable direction—and tipped at reset; we drop each scene into the simulator for 2 s without the robot and adopt the settled poses as initial rests (accepted if $\leq 20°/3$ cm). Collision is CoACD [19] on walls only for containers, a dish-rack slot is carved where the sweeper really stood, and cups get a solid base. Two meshes were corrected from measurements: the pitcher base (resting 36 mm above the table in three episodes) and the dust pan thickness (top surface vs. stereo depth: 17.3→2.3 mm).

Policy learning. One FlashSAC [3, 8] policy per episode (2048 worlds, 250 M steps, real-time playback) with the reward $r = 40\, r_{\text{obj}} + 5\, r_{\text{cloc}} + 10\, r_{\text{wrench}} + 5\, r_{\text{prog}} + 200\, \mathbb{1}_{\text{done}} - \ldots$, i.e. object keypoint tracking, human contact locations, contacts able to support the object, progress while every object is within 3 cm/0.3 rad, and a completion bonus, with termination limits annealed from 3× to the official values. We train two seeds and a stickier contact (friction 1.5) and submit, per episode, the run with the best own-reference MP-SR, then SP-SR, then AUC.

3. Experiments and Results

Table 1 shows the official scores of successive submissions: every component improved AUC, SP-SR, RPE and MPPE (about 12th of 37 by summed rank). SAC clearly outperformed PPO [13] on identical data and reward (median reference progress 0.62 after 250 M steps vs. 0.27 after 492 M; App. A). Simulator settling cut the mean rotation of resting objects during the first 3 s from 12.3° to 5.0° and made the dust-pan, sweeper and board episodes solvable (Fig. 1). Two findings were negative: rigidly locking held objects to the reconstructed palm lowered mocap accuracy (0.87→0.55–0.72 of carried frames within 15°/3 cm), because the palm frame drifts and objects genuinely slip; and hand-only refinement [6] cannot repair object poses. Most tellingly, 16 of 20 episodes pass MP-SR against our own reconstruction but only 3 against the hidden ground truth.

Submission	AUC↑	SP↑	MP↑	RPE↓	MPPE↓	CD-O↓
fusion baseline (t3)	0.504	0.50	0.15	9.23	8.60	0.407
+ SelectTrack, grounding	0.532	0.55	**0.20**	8.10	7.82	0.407
+ 2nd seed	0.553	0.60	0.15	7.54	7.18	0.401
+ settled starts, friction	**0.584**	**0.65**	0.15	**7.35**	**6.06**	**0.401**
leader	0.765	0.80	0.50	3.85	3.00	–

Table 1: Official test scores (20 evaluation episodes, own meshes). RPE, MPPE, CD-O in cm.

4. Conclusion

Global hypothesis selection with point-track consistency, plus simulator-side grounding, makes egocentric human motion imitable by a dexterous robot hand; the remaining gap is reconstruction accuracy, especially the camera-depth tilt of resting objects and centimetre offsets of held ones. Feeding simulator feedback back into the reconstruction (as in DeepSimHO [18]) and refining meshes jointly with poses are the most promising next steps. Code: https://github.com/KiaRational/v2d-track3.

References

[1] Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, et al. SAM 3: Segment anything with concepts. *arXiv preprint arXiv:2511.16719*, 2025.

[2] Zetao Du, Weiqing Wang, Hanbing Zhang, Yimiao Zhou, Ye Shi, Liang Wang, and Jingya Wang.

Hand2Robot: Object-centric 4D hand reconstruction from human demonstrations for robotics. *arXiv preprint arXiv:2610.15769*, 2026.

[3] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *ICML*, 2018.

[4] Ayush Jain, Sreeharsha Paruchuri, Ishita Gupta, Fan Zhang, Tanner Schmidt, Jakob Engel, Katerina Fragkiadaki, and Adam W. Harley. TrackEverything: Long horizon dense tracking via de-duplicating 3D scene representations. *arXiv preprint arXiv:2609.30222*, 2026.

[5] Youbeen Jeon, Uiseong Shin, Hwanchul La, Jaeseong Kang, Hyelim Choi, and Yongseok Lee. VICON: Visual-inertial-contact based hand-object tracking for manipulation datasets. *arXiv preprint arXiv:2610.05180*, 2026.

[6] Xueyi Liu and Li Yi. GeneOH diffusion: Towards generalizable hand-object interaction denoising via denoising diffusion. In *ICLR*, 2024.

[7] Van Nguyen Nguyen, Christian Forster, Sindi Shkodrani, Vincent Lepetit, Bugra Tekin, Cem Keskin, and Tomas Hodan. GoTrack: Generic 6DoF object pose refinement and tracking. *arXiv preprint arXiv:2506.07155*, 2025.

[8] NVIDIA. Video to data: Robotic grounding technical report (FlashCHORD). https://nvidia-isaac.github.io/video_to_data/chord/chord.pdf, 2026.

[9] NVIDIA. Video to data (V2D) challenge 2026. https://nvidia-isaac.github.io/video_to_data/v2d_challenge/, 2026.

[10] Rolandos Alexandros Potamias, Jinglei Zhang, Jiankang Deng, and Stefanos Zafeiriou. WiLoR: End-to-end 3D hand localization and reconstruction in-the-wild. In *CVPR*, 2025.

[11] Javier Romero, Dimitrios Tzionas, and Michael J. Black. Embodied hands: Modeling and capturing hands and bodies together. *ACM Transactions on Graphics (SIGGRAPH Asia)*, 36(6), 2017.

[12] SAM 3D Team, Xingyu Chen, Fu-Jen Chu, Pierre Gleize, Kevin J. Liang, Alexander Sax, et al. SAM 3D: 3dfy anything in images. *arXiv preprint arXiv:2511.16624*, 2025.

[13] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[14] Jin-Chuan Shi, Binhong Ye, Tao Liu, Junzhe He, Yangjinhui Xu, Xiaoyang Liu, Zeju Li, Hao Chen, and Chunhua Shen. AGILE: Hand-object interaction reconstruction from video via agentic generation. In *SIGGRAPH*, 2026.

[15] Jisu Shin, Junoh Lee, JunGyu Lee, Inhwan Bae, Dohyeon Lee, Hokyun Im, Youngwoon Lee, and Hae-Gon Jeon. ComPose: When to trust hands for object pose tracking. *arXiv preprint arXiv:2605.23523*, 2026.

[16] Zachary Teed and Jia Deng. DROID-SLAM: Deep visual SLAM for monocular, stereo, and RGB-D cameras. In *NeurIPS*, 2021.

[17] Jonathan Tremblay, Bowen Wen, Valts Blukis, Balakumar Sundaralingam, Stephen Tyree, and Stan Birchfield. DiffDOPE: Differentiable deep object pose estimation. *arXiv preprint arXiv:2310.00463*, 2023.

[18] Rong Wang, Wei Mao, and Hongdong Li. DeepSimHO: Stable pose estimation for hand-object interaction via physics simulation. In *NeurIPS*, 2023.

[19] Xinyue Wei, Minghua Liu, Zhan Ling, and Hao Su. Approximate convex decomposition for 3D meshes with collision-aware concavity and tree search. *ACM Transactions on Graphics (SIGGRAPH)*, 41(4), 2022.

[20] Bowen Wen, Wei Yang, Jan Kautz, and Stan Birchfield. FoundationPose: Unified 6D pose estimation and tracking of novel objects. In *CVPR*, 2024.

[21] Bowen Wen, Matthew Trepte, Joseph Aribido, Jan Kautz, Orazio Gallo, and Stan Birchfield. FoundationStereo: Zero-shot stereo matching. In *CVPR*, 2025.

[22] Zhengdi Yu, Stefanos Zafeiriou, and Tolga Birdal. DynHaMR: Recovering 4D interacting hand motion from a dynamic camera. In *CVPR*, 2025.

[23] Bowei Zhang, Lei Ke, Adam W. Harley, and Katerina Fragkiadaki. TAPIP3D: Tracking any point in persistent 3D geometry. In *NeurIPS*, 2025.




Figure 4: Own-reference MP-SR per scored episode and training run; outlined: run submitted.




Figure 5: Hard episodes across runs: settled starts and friction 1.5 solve the dust pan (e38) and boards (e25).

A. Additional Results




Figure 2: SAC vs. PPO on the same 40 episodes and contact reward (median over episodes, band 25–75th percentile). Drops are curriculum stage changes (assistance reduced, termination tightened).




Figure 3: Object-pose variants vs. public mocap (development only). SELECTTRACK trades a little carried-frame accuracy for the removal of flips and spins, which is what the robot needs.