



Statistical tools for high-throughput data analysis

Licence:




Search...

[Home](#)[Basics](#)[Data](#)[Visualize](#)[Analyze](#)[Products](#)[Contribute](#)[Support](#)[About](#)

[Home](#) / [Easy Guides](#) / [R software](#) / [Data Visualization](#) / [ggplot2 - Essentials](#) /
ggplot2 scatter plots : Quick start guide - R software and data visualization


[Actions menu for module Wiki](#)

ggplot2 scatter plots : Quick start guide - R software and data visualization

 Ads by Google[Data Software](#)[R Programming](#)[Color R](#)[Create a Graph](#)[Tools](#)

- [Prepare the data](#)
- [Basic scatter plots](#)
- [Label points in the scatter plot](#)
 - [Add regression lines](#)
 - [Change the appearance of points and lines](#)
- [Scatter plots with multiple groups](#)
 - [Change the point color/shape/size automatically](#)
 - [Add regression lines](#)
 - [Change the point color/shape/size manually](#)
- [Add marginal rugs to a scatter plot](#)
- [Scatter plots with the 2d density estimation](#)
- [Scatter plots with ellipses](#)
- [Scatter plots with rectangular bins](#)
- [Scatter plot with marginal density distribution plot](#)
- [Customized scatter plots](#)
- [Infos](#)

This article describes how create a **scatter plot** using **R software** and **ggplot2** package. The function **geom_point()** is used.



Prepare the data

mtcars data sets are used in the examples below.

```
# Convert cyl column from a numeric to a factor variable
mtcars$cyl <- as.factor(mtcars$cyl)
head(mtcars)
```





| ## | mpg | cyl | disp | hp | drat | wt | qsec | vs | am | gear | carb |
|----------------------|------|-----|------|-----|------|-------|-------|----|----|------|------|
| ## Mazda RX4 | 21.0 | 6 | 160 | 110 | 3.90 | 2.620 | 16.46 | 0 | 1 | 4 | 4 |
| ## Mazda RX4 Wag | 21.0 | 6 | 160 | 110 | 3.90 | 2.875 | 17.02 | 0 | 1 | 4 | 4 |
| ## Datsun 710 | 22.8 | 4 | 108 | 93 | 3.85 | 2.320 | 18.61 | 1 | 1 | 4 | 1 |
| ## Hornet 4 Drive | 21.4 | 6 | 258 | 110 | 3.08 | 3.215 | 19.44 | 1 | 0 | 3 | 1 |
| ## Hornet Sportabout | 18.7 | 8 | 360 | 175 | 3.15 | 3.440 | 17.02 | 0 | 0 | 3 | 2 |
| ## Valiant | 18.1 | 6 | 225 | 105 | 2.76 | 3.460 | 20.22 | 1 | 0 | 3 | 1 |

Basic scatter plots

Simple scatter plots are created using the R code below. The color, the size and the shape of points can be changed using the function **geom_point()** as follow :


```
geom_point(size, color, shape)
```

```
library(ggplot2)
# Basic scatter plot
ggplot(mtcars, aes(x=wt, y=mpg)) + geom_point()
# Change the point size, and shape
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point(size=2, shape=23)
```



Note that, the size of the points can be controlled by the values of a continuous variable as in the example below.

```
# Change the point size
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point(aes(size=qsec))
```




Read more on point shapes : [ggplot2 point shapes](#)

Label points in the scatter plot

The function **geom_text()** can be used :

```
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point() +
  geom_text(label=rownames(mtcars))
```



Read more on text annotations : [ggplot2 - add texts to a plot](#)

Add regression lines

The functions below can be used to add regression lines to a scatter plot :

- **geom_smooth()** and **stat_smooth()**
- **geom_abline()**

geom_abline() has been already described at this link : [ggplot2 add straight lines to a plot](#).




Only the function **geom_smooth()** is covered in this section.

A simplified format is :

```
geom_smooth(method="auto", se=TRUE, fullrange=FALSE, level=0.95)
```

- **method** : smoothing method to be used. Possible values are **lm**, **glm**, **gam**, **loess**, **rlm**.
 - **method = "loess"**: This is the default value for small number of observations. It computes a smooth local regression. You can read more about **loess** using the R code **?loess**.
 - **method = "lm"**: It fits a **linear model**. Note that, it's also possible to indicate the formula as **formula = y ~ poly(x, 3)** to specify a degree 3 polynomial.
- **se** : logical value. If TRUE, confidence interval is displayed around smooth.
- **fullrange** : logical value. If TRUE, the fit spans the full range of the plot
- **level** : level of confidence interval to use. Default value is 0.95

```
# Add the regression line
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point()+
  geom_smooth(method=lm)
# Remove the confidence interval
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point()+
  geom_smooth(method=lm, se=FALSE)
# Loess method
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point()+
  geom_smooth()
```




Change the appearance of points and lines

This section describes how to change :

- the color and the shape of points
- the line type and color of the regression line
- the fill color of the confidence interval

```
# Change the point colors and shapes
# Change the line type and color
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point(shape=18, color="blue")+
  geom_smooth(method=lm, se=FALSE, linetype="dashed",
    color="darkred")
# Change the confidence interval fill color
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point(shape=18, color="blue")+
  geom_smooth(method=lm, linetype="dashed",
    color="darkred", fill="blue")
```



Note that a transparent color is used, by default, for the confidence band. This can be changed by using the argument `alpha` : `geom_smooth(fill="blue", alpha=1)`

Read more on point shapes : [ggplot2 point shapes](#)

Read more on line types : [ggplot2 line types](#)




Scatter plots with multiple groups

This section describes how to change point colors and shapes automatically and manually.

Change the point color/shape/size automatically

In the R code below, point shapes, colors and sizes are controlled by the levels of the factor variable `cyl` :



```
# Change point shapes by the levels of cyl
ggplot(mtcars, aes(x=wt, y=mpg, shape=cyl)) +
  geom_point()
# Change point shapes and colors
ggplot(mtcars, aes(x=wt, y=mpg, shape=cyl, color=cyl)) +
  geom_point()
# Change point shapes, colors and sizes
ggplot(mtcars, aes(x=wt, y=mpg, shape=cyl, color=cyl, size=cyl)) +
  geom_point()
```



Add regression lines

Regression lines can be added as follow :


```
# Add regression lines
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point() +
  geom_smooth(method=lm)
# Remove confidence intervals
# Extend the regression lines
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point() +
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE)
```



Note that, you can also change the line type of the regression lines by using the aesthetic *linetype = cyl*.

The fill color of confidence bands can be changed as follow :

```
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point() +
  geom_smooth(method=lm, aes(fill=cyl))
```




Change the point color/shape/size manually

The functions below are used :

- `scale_shape_manual()` for point shapes
- `scale_color_manual()` for point colors
- `scale_size_manual()` for point sizes

```
# Change point shapes and colors manually
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point() +
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE)+
  scale_shape_manual(values=c(3, 16, 17))+
  scale_color_manual(values=c('#999999', '#E69F00', '#56B4E9'))+
  theme(legend.position="top")
```


```
# Change the point sizes manually
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl))+
  geom_point(aes(size=cyl)) +
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE)+
  scale_shape_manual(values=c(3, 16, 17))+
  scale_color_manual(values=c('#999999', '#E69F00', '#56B4E9'))+
  scale_size_manual(values=c(2,3,4))+
  theme(legend.position="top")
```

It is also possible to *change manually point and line colors* using the functions :

- `scale_color_brewer()` : to use color palettes from *RColorBrewer* package
- `scale_color_grey()` : to use grey color palettes

```
p <- ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point() +
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE)+
  theme_classic()
# Use brewer color palettes
p+scale_color_brewer(palette="Dark2")
# Use grey scale
p + scale_color_grey()
```



Read more on ggplot2 colors here : [ggplot2 colors](#)

Add marginal rugs to a scatter plot

The function `geom_rug()` can be used :




```
geom_rug(sides = "b1")
```

sides : a string that controls which sides of the plot the rugs appear on. Allowed value is a string containing any of "trbl", for top, right, bottom, and left.

```
# Add marginal rugs
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point() + geom_rug()

# Change colors
ggplot(mtcars, aes(x=wt, y=mpg, color=cyl)) +
  geom_point() + geom_rug()

# Add marginal rugs using faithful data
ggplot(faithful, aes(x=eruptions, y=waiting)) +
  geom_point() + geom_rug()
```






Scatter plots with the 2d density estimation

The functions **geom_density_2d()** or **stat_density_2d()** can be used :

```
# Scatter plot with the 2d density estimation
sp <- ggplot(faithful, aes(x=eruptions, y=waiting)) +
  geom_point()
sp + geom_density_2d()
```

```
# Gradient color
sp + stat_density_2d(aes(fill = ..level..), geom="polygon")
# Change the gradient color
sp + stat_density_2d(aes(fill = ..level..), geom="polygon")+
  scale_fill_gradient(low="blue", high="red")
```





Read more on ggplot2 colors here : [ggplot2 colors](#)

Scatter plots with ellipses

The function **stat_ellipse()** can be used as follow:

```
# One ellipse around all points
ggplot(faithful, aes(waiting, eruptions))+
  geom_point()+
  stat_ellipse()
# Ellipse by groups
p <- ggplot(faithful, aes(waiting, eruptions, color = eruptions > 3))+
  geom_point()
p + stat_ellipse()
# Change the type of ellipses: possible values are "t", "norm", "euclid"
p + stat_ellipse(type = "norm")
```



Scatter plots with rectangular bins

The number of observations is counted in each bins and displayed using any of the functions below :

- **geom_bin2d()** for adding a heatmap of 2d bin counts
- **stat_bin_2d()** for counting the number of observation in rectangular bins
- **stat_summary_2d()** to apply function for 2D rectangular bins

The simplified formats of these functions are :

```
plot + geom_bin2d(...)
plot+stat_bin_2d(geom=NULL, bins=30)
plot + stat_summary_2d(geom = NULL, bins = 30, fun = mean)
```

- **geom** : geometrical object to display the data
- **bins** : Number of bins in both vertical and horizontal directions. The default value is 30
- **fun** : function for summary


The data sets *diamonds* from ggplot2 package is used :

```
head(diamonds)
```

```
##   carat      cut  color clarity depth table price    x    y    z
## 1  0.23    Ideal     E    SI2   61.5    55   326  3.95  3.98  2.43
## 2  0.21   Premium     E    SI1   59.8    61   326  3.89  3.84  2.31
## 3  0.23     Good     E    VS1   56.9    65   327  4.05  4.07  2.31
## 4  0.29   Premium     I    VS2   62.4    58   334  4.20  4.23  2.63
## 5  0.31     Good     J    SI2   63.3    58   335  4.34  4.35  2.75
## 6  0.24 Very Good     J   VVS2   62.8    57   336  3.94  3.96  2.48
```

Plot


```
p <- ggplot(diamonds, aes(carat, price))
p + geom_bin2d()
```



Change the number of bins :


Change the number of bins

```
p + geom_bin2d(bins=10)
```



Or specify the width of bins :

```
# Or specify the width of bins
p + geom_bin2d(binwidth=c(1, 1000))
```



Scatter plot with marginal density distribution plot

Step 1/3. Create some data :

```
set.seed(1234)
x <- c(rnorm(500, mean = -1), rnorm(500, mean = 1.5))
y <- c(rnorm(500, mean = 1), rnorm(500, mean = 1.7))
group <- as.factor(rep(c(1,2), each=500))
df <- data.frame(x, y, group)
head(df)
```

```
##           x           y group
## 1 -2.20706575 -0.2053334    1
## 2 -0.72257076  1.3014667    1
## 3  0.08444118 -0.5391452    1
## 4 -3.34569770  1.6353707    1
## 5 -0.57087531  1.7029518    1
## 6 -0.49394411 -0.9058829    1
```




Step 2/3. Create the plots :

```
# scatter plot of x and y variables
# color by groups
scatterPlot <- ggplot(df, aes(x, y, color=group)) +
  geom_point() +
  scale_color_manual(values = c('#999999', '#E69F00')) +
```

```

theme(legend.position=c(0,1), legend.justification=c(0,1))
scatterPlot
# Marginal density plot of x (top panel)
xdensity <- ggplot(df, aes(x, fill=group)) +
  geom_density(alpha=.5) +
  scale_fill_manual(values = c('#999999', '#E69F00')) +
  theme(legend.position = "none")
xdensity
# Marginal density plot of y (right panel)
ydensity <- ggplot(df, aes(y, fill=group)) +
  geom_density(alpha=.5) +
  scale_fill_manual(values = c('#999999', '#E69F00')) +
  theme(legend.position = "none")
ydensity

```



Create a blank placeholder plot :

```

blankPlot <- ggplot()+geom_blank(aes(1,1))+
  theme(plot.background = element_blank(),
        panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        panel.border = element_blank(),
        panel.background = element_blank(),
        axis.title.x = element_blank(),
        axis.title.y = element_blank(),
        axis.text.x = element_blank(),
        axis.text.y = element_blank(),
        axis.ticks = element_blank()
  )

```


Step 3/3. Put the plots together:

To put multiple plots on the same page, the package **gridExtra** can be used. Install the package as follow :

```
install.packages("gridExtra")
```

Arrange ggplot2 with adapted height and width for each row and column :

```
library("gridExtra")
grid.arrange(xdensity, blankPlot, scatterPlot, ydensity,
             ncol=2, nrow=2, widths=c(4, 1.4), heights=c(1.4, 4))
```





Read more on how to arrange multiple ggplots in one page : [ggplot2 - Easy way to mix multiple graphs on the same page](#)

Customized scatter plots

```
# Basic scatter plot
ggplot(mtcars, aes(x=wt, y=mpg)) +
  geom_point()+
  geom_smooth(method=lm, color="black")+
  labs(title="Miles per gallon \n according to the weight",
       x="Weight (lb/1000)", y = "Miles/(US) gallon")+
  theme_classic()
# Change color/shape by groups
# Remove confidence bands
p <- ggplot(mtcars, aes(x=wt, y=mpg, color=cyl, shape=cyl)) +
  geom_point()+
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE)+
```






```
labs(title="Miles per gallon \n according to the weight",
     x="Weight (lb/1000)", y = "Miles/(US) gallon")
p + theme_classic()
```



Change colors manually :

```
# Continuous colors
p + scale_color_brewer(palette="Paired") + theme_classic()
# Discrete colors
p + scale_color_brewer(palette="Dark2") + theme_minimal()
# Gradient colors
p + scale_color_brewer(palette="Accent") + theme_minimal()
```



Read more on ggplot2 colors here : [ggplot2 colors](#)

Infos



This analysis has been performed using **R software** (ver. 3.2.4) and **ggplot2** (ver. 2.1.0)



Enjoyed this article? I'd be very grateful if you'd help it spread by emailing it to a friend, or sharing it on Twitter, Facebook or Linked In.

Show me some love with the like buttons below... Thank you and please don't forget to share and comment below!!

Ads by Google

[Create a Graph](#)

[3D Chart Excel](#)

[Plot Map](#)

[Excel Data Graph](#)

[Share](#) 10

[Like](#) 10

[Tweet](#)

[Share](#)



[Save](#)

[Share](#)

57




Recommended for You!


Machine Learning Essentials

Practical Guide in R

Alboukadel KASSAMBARA




Practical Guide to Cluster Analysis in R




Practical Guide to Principal Component Methods in R

sthda.com/english

Machine Learning Essentials:
Practical Guide in R



R Graphics Essentials for Great Data Visualization



Network Analysis and Visualization in R



More books on R and data science

Want to Learn More on R Programming and Data Science?

Follow us by Email

Subscribe
by FeedBurner

On Social Networks:
on Social Networks



Get involved :



Click to **follow us** on Facebook and Google+ :



Comment this article by clicking on "Discussion" button (top-right position of this page)

This page has been seen 203437 times

Sign in


Login**Password****Auto connect** [Register](#)  [Forgotten password](#)**Welcome!**

Want to Learn More on R Programming and Data Science?

Follow us [by Email](#)

by [FeedBurner](#)

on Social Networks

 Ads by Google

[Data Analysis R](#)[Scatter Plot](#)[Histogram Graph](#)[R Programming](#) [factoextra](#) [survminer](#) [ggpubr](#) [ggcorrplot](#) [fastqcr](#)



Zoho Books
A complete accounting
and GST filing solution.


- Invoicing
- Inventory
- GST filing
- Banking
- Multi-user

• **Mobile app**

₹ **2499**/year + tax


SIGN UP NOW >

Our Books




R Graphics Essentials for Great Data Visualization: 200 Practical Examples You Want to Know for Data Science

★ **NEW!!**




Practical Guide to Cluster Analysis in R



Practical Guide to Principal Component Methods in R

3D Plots in R

STHDA



Guest Book

I have neer used any machine learning things before, so this website was extremely useful in introducing the basics of working with clustering in R Studio! What a nice and "down to earth" way of expla... [\[Read more\]](#)

By *Kate*

[Guest Book](#)

 **R-Bloggers**

Newsletter

Email



Boosted by PHPBoost

Recommended for you



ggplot2.stripchart : Easy
one dimensional scatt...

www.sthda.com



GGPlot Cheat Sheet for
Great Customization...

www.sthda.com



Correspondence
Analysis: Theory and P...

www.sthda.com

AddThis