

# Introduction I - R basics

## R for Stata Users

Luiza Andrade, Leonardo Viotti & Rob Marty

June 2019



# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

This training requires that you have R installed in your computer:

## Instructions

- Please visit (<https://cran.r-project.org>) and select a Comprehensive R Archive Network (CRAN) mirror close to you.
- If you're in the US, you can directly visit the mirror at Berkley university at (<https://cran.cnr.berkeley.edu>).
- we also strongly suggest installing R studio. You can get it in (<https://www.rstudio.com/>), but you need to install R first.

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

These training sessions will offer a quick introduction to R, its amazing features and why it is so much better than Stata.

This first session will present the basic concepts you will need to use R.

The next sessions will include:

- **Introduction to R part II**
- **Data Processing**
- **Descriptive Analysis**
- **Data Visualization**

For the most recent versions of these trainings, visit the R-training GitHub repo at <https://github.com/worldbank/dime-r-training>

Some advantages of R over Stata:

- It is less specialized:
  - More flexibility when programming.
  - Many more functionalities.
- Much broader network of users:
  - More resources online, which makes using Google a lot easier. You'll never want to see Statalist again in your life.
  - Development of new features and bug fixes happens faster.
- It is way cooler.

Some possible disadvantages of R:

- Higher cost of entry than Stata.
- Stata is more specialized:
  - Certain common tasks are simpler in Stata.
- Stata has wider adoption among micro-econometricians.
  - Network externalities in your work environment.
  - Development of new specialized techniques and tools could happen faster (e.g. *ietoolkit*).



Here are some other advantages:

- R is a free and open source software!
- It allows you to have several data sets open simultaneously.
- It can run complex Geographic Information System (GIS) analyses.
- You can use it for web scrapping.
- You can run machine learning algorithms with it.
- You can create complex Markdown documents. This presentation, for example, is entirely done in RStudio.
- You can create interactive dashboards and online applications with the Shiny package.

Python is even more flexible and has more users than R. So, why should I bother to learn R?

- Despite being super popular for data science, Python has fewer libraries developed for econometrics.
- Python is a bit harder to set up and get started.
- It can be a harder to find help only for statistics and econometrics especially for beginners.

# Outline


- 1 Installation
- 2 Introduction
- 3 **Getting started**
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

Let's start by loading the data set we'll be using:

## Exercise 1: Import data

- 1 In RStudio, go to File > Import Dataset > From Excel and open the `cs_s0_s5_household.xls` file.
  - Depending on your Rstudio version, it might be File > Import Dataset > From CSV
- 2 The file should be in `GitHub/dime-r-training/DataWork/DataSets/Final`
- 3 Change the name to `cs` on the import window

# Getting started



# Getting started

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function Addins

Project: (None)

Console Terminal Jobs

Import Excel Data

File/URL:

D:/Downloads/cs\_s0\_s5\_household.xls

Browse...

Data Preview:

hhid (double)	province (character)	district (character)	ur2012 (character)	ur2_2012 (character)	region (character)	weight (double)	clust (double)	rwanda (character)	surv (cha
100001	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100002	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100003	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100004	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100005	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100006	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100007	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100008	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100009	Kigali City	Nyarugenge	Urban	Urban	Kigali City	71.45979	10001	All Rwanda	Pa
100010	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100011	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100012	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100013	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100014	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100015	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa
100016	Kigali City	Nyarugenge	Urban	Urban	Kigali City	120.59451	10002	All Rwanda	Pa

Previewing first 50 entries.

Import Options:

Name: cs Max Rows: 10000 ☒ First Row as Names

Sheet: Default Skip: 0 ☒ Open Data Viewer

Range: A1:D10 NA:

Code Preview:

```
library(readxl)
cs <- read_excel("D:/Downloads/cs_s0_s5_household.xls")
View(cs)
```


Import Cancel

Reading Excel files using readxl

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface**
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

# RStudio interface






# RStudio interface

The screenshot displays the RStudio interface with the following components:


- Menu Bar:** File, Edit, Code, View, Plots, Session, Build, Debug, Profile, Tools, Help.
- Toolbar:** Includes icons for file operations, running code, and adding packages.
- Source Editor:** Shows a file named 'Untitled1' with a CSV dataset. The columns are: hhid, province, district, ur2012, ur2\_2012, region, weight, clust, and rwnde. The data rows show information for various locations in Rwanda, such as Kigali City and Nyarugenge.
- Console:** Displays the R version (4.0.2), copyright information, and a welcome message. It also shows the execution of the following R code:

```
> library(readxl)
> cs <- read_excel("D:/Downloads/cs_s0_s5_household.xls")
> View(cs)
>
```
- Environment Pane:** Shows the current environment with a variable 'cs' containing 14419 observations and 76 variables.
- Plots Pane:** Currently empty.
- Files Pane:** Shows the file structure of the project.


# RStudio interface




# RStudio interface



# RStudio interface



# RStudio interface



# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R**
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

- In Stata, you can open ONE dataset at a time, and perform operations that can change the dataset.
- You can also have other things, such as matrices, macros and tempfiles, but they are secondary, and most functions only use the main dataset.
- If you wish to do any non-permanent changes to your data, you'll need to preserve the original data to keep it intact.

R works in a completely different way:

- You can have as many datasets (objects) as you wish or your computer's memory allows.
- Operations will only have lasting effects if you store them.



- Everything that exists in R's memory – variables, datasets, functions – is an object.
- You could think of an object like a chunk of data with some properties that has a name by which you call it.
- If you create an object, it is going to be stored in memory until you delete it or quit R.
- Whenever you run anything you intend to use in the future, you need to store it as an object.

To better understand the idea, we're going to use the data we opened from the Rwanda's EICV data. First, let's take a look at the data.

Type the following code to explore the data:

```
# We can use the function View() to browse the whole data  
View(eicv)
```

```
# Alternatively we can print the first 6 obs. with head()  
head(eicv)
```

# Data in R

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function Addins Project: (None)

Untitled1\* x whr x MASTER.R x

Filter

	country	region	year	happy_rank	happy_score	gdp_pc	family	health	freedom
1	Norway	Western Europe	2017	1	7.537	1.61646318	1.5335236	0.796666503	0.6354225
2	Denmark	Western Europe	2017	2	7.522	1.48238301	1.5511216	0.792565525	0.6260067
3	Iceland	Western Europe	2017	3	7.504	1.48063302	1.6105740	0.833552122	0.6271626
4	Switzerland	Western Europe	2017	4	7.494	1.56497955	1.5169117	0.858131289	0.6200705
5	Finland	Western Europe	2017	5	7.469	1.44357193	1.5402467	0.809157670	0.6179508
6	Netherlands	Western Europe	2017	6	7.377	1.50394464	1.4289392	0.810696125	0.5853844
7	Canada	North America	2017	7	7.316	1.47920442	1.4813490	0.834557652	0.6111009
8	New Zealand	Australia and New Zealand	2017	8	7.314	1.40570605	1.5481951	0.816759706	0.6140621
9	Sweden	Western Europe	2017	9	7.284	1.49438727	1.4781622	0.830875158	0.6129241
10	Australia	Australia and New Zealand	2017	10	7.284	1.48441494	1.5100420	0.843886793	0.6016073
11	Israel	Middle East and Northern Africa	2017	11	7.213	1.37538242	1.3762900	0.838404000	0.4059886
12	Costa Rica	Latin America and Caribbean	2017	12	7.079	1.10970628	1.4164037	0.759509265	0.5801316
13	Austria	Western Europe	2017	13	7.006	1.48709726	1.4599450	0.815328419	0.5677661
14	United States	North America	2017	14	6.993	1.54625928	1.4199206	0.774286628	0.5057405
15	Ireland	Western Europe	2017	15	6.977	1.53570664	1.5507311	0.800783634	0.5721102

Showing 1 to 16 of 469 entries

Console

# Data in R

```
eicv
```

```
## # A tibble: 14,419 x 76
##       hhid province district ur2012 ur2_2012 region weight clust rwanda surveyyh
##       <dbl> <chr>      <chr>    <chr>  <chr>    <chr>    <dbl> <dbl> <chr>  <chr>
## 1 100001 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 2 100002 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 3 100003 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 4 100004 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 5 100005 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 6 100006 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 7 100007 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 8 100008 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 9 100009 Kigali ~ Nyaruge~ Urban  Urban   Kigal~    71.5 10001 All R~ Panel
## 10 100010 Kigali ~ Nyaruge~ Urban  Urban   Kigal~   121. 10002 All R~ Panel
## # ... with 14,409 more rows, and 66 more variables: quintile <chr>,
## # poverty <dbl>, Consumption <dbl>, hhtype <chr>, s0q19m <dbl>, s0q19y <dbl>,
## # s0qb <chr>, s5aq1 <chr>, s5aq2 <chr>, s5aq3 <chr>, s5aq4 <chr>,
## # s5aq5 <chr>, s5aq6 <chr>, s5aq7y <chr>, s5aq7m <chr>, s5aq8 <chr>,
## # s5aq9 <chr>, s5aq10 <chr>, s5aq11 <chr>, s5bq1 <chr>, s5bq2 <chr>,
## # s5bq3a <chr>, s5bq3b <chr>, s5bq4a <chr>, s5bq4b <chr>, s5bq5 <chr>,
## # s5bq6a <chr>, s5bq6b <chr>, s5bq7 <chr>, s5bq8 <chr>, s5bq9a <chr>,
## # s5bq9b <chr>, s5bq10 <chr>, s5bq11 <chr>, s5cq1 <chr>, s5cq2 <chr>,
## # s5cq3 <chr>, s5cq4 <chr>, s5cq5 <chr>, s5cq6 <chr>, s5cq7 <chr>,
## # s5cq8 <chr>, s5cq9a <chr>, s5cq9b <chr>, s5cq10 <chr>, s5cq11 <chr>.
```

Now, let's try some simple manipulations. First, assume we're only interested in data of the year 2015.

## Exercise 2: Subset the data

- 1 Subset the data set, keeping only observations where variable `region` equals Kigali City.

*# To do that we'll use the `subset()` function*

```
subset(eicv, region == "Kigali City")
```

- 2 Then, look again at the first 6 observations

*# Use the `head()` function again*

```
head(eicv)
```

# Data in R

```
head(eicv)
```

```
## # A tibble: 6 x 12
##   hhid province district ur2012 ur2_2012 region weight clust rwanda surveyh
##   <dbl> <chr>    <chr>    <chr> <chr>    <chr>    <dbl> <dbl> <chr> <chr>
## 1 100001 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 2 100002 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 3 100003 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 4 100004 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 5 100005 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 6 100006 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## # ... with 2 more variables: quintile <chr>, poverty <dbl>
```

We can see that nothing happened to the original data. This happens because we didn't store the edit we made anywhere.

To store an object, we use the assignment operator (`<-`):

```
# Assign the Answer to the Ultimate Question of Life,  
# the Universe, and Everything
```

```
x <- 42
```

From now on, `x` is associated with the stored value (until you replace it, delete it, or quit the R session).

## Exercise 3: Create an object

Create a new data set, called `kigali`, that is a subset of the `eicv` data set containing only data from the Kigali City region.

```
# Using the same function but now assigning it to an object  
kigali <- subset(eicv, region == "Kigali City")
```

```
# Display the 5 first obs. of the new data  
head(kigali)
```

```
# Notice that we still have the original data set intact  
head(kigali)
```



# Data in R

```
head(kigaly)
```


```
## # A tibble: 6 x 12
##   hhid province district ur2012 ur2_2012 region weight clust rwanda surveyh
##   <dbl> <chr>    <chr>    <chr> <chr>    <chr>    <dbl> <dbl> <chr> <chr>
## 1 100001 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 2 100002 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 3 100003 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 4 100004 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 5 100005 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 6 100006 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## # ... with 2 more variables: quintile <chr>, poverty <dbl>
```

# Data in R

```
head(kigaly)
```

```
## # A tibble: 6 x 12
##   hhid province district ur2012 ur2_2012 region weight clust rwanda surveyh
##   <dbl> <chr>    <chr>    <chr> <chr>    <chr>    <dbl> <dbl> <chr> <chr>
## 1 100001 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 2 100002 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 3 100003 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 4 100004 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 5 100005 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## 6 100006 Kigali ~ Nyaruge~ Urban  Urban  Kigal~    71.5 10001 All R~ Panel
## # ... with 2 more variables: quintile <chr>, poverty <dbl>
```

You can also see that your environment pane now has two objects:



## Two important concepts to take note:

- ❶ In R, if you want to change your data, you need to store it in an object.
- ❷ It is possible to simply replace the original data. This happens if you assign the new object to the same name as the original.
- ❸ Print (display) is built into R. If you execute any action without storing it, R will simply print the results of that action but won't save anything in the memory.

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions**
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

# Quick intro to functions

`head()`, `View()`, `subset()` and `read.csv()` are functions!

- Functions in R take named arguments (unlike in Stata that you have arguments and options).
- Usually the first argument is the object you want to use the function on, e.g. `subset(kigali, ...)`
- Functions usually return values that you can store in an object, print or use directly as an argument of another function.

We will explore these ideas in depth in the next session.

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects**
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

Objects are the building blocks of R programming. This section will explore some of the most common classes, focused on data structures.

This will give you the foundation to explore your data and construct analytical outputs.



# R objects

## What is an object?

- An object is like a global in Stata, it's something you can refer to later in your code to get a value.
- But while you can only put a number or a string in a global you can put anything into an object: strings, data sets, vectors, graphs, functions, etc.
- Objects also have attributes that can be used to manipulate it.

Here are the object classes we will cover today:

- **Vectors:** an uni-dimensional object that stores a sequence of values
- **Data frames:** a combination of different vectors of the same length (the same as your data set in Stata)
- **Lists:** a multidimensional object that can store several objects of different dimension

# R objects

## Vectors

A vector is an uni-dimensional object composed by one or more scalars of the same type.

Use the following code to create vectors in two different ways

```
# Creating a vector with the c() function
```

```
v1 <- c(1,1,2,3,5)
```

```
# Alternative way to create an evenly spaced vector
```

```
v2 <- 1:5
```

You can use brackets for indexing

```
# Print the 4th element of the vector
```

```
v2[4]
```

```
## [1] 4
```

# R objects

## Vectors

To R, each of the columns of `eicv` is a vector.

### Calling a vector from a `data.frame` column

We use the `$` to call vectors (variables) by their names in a `data.frame`

Type the following code:

```
# Create a vector with the values of the `year` variable  
region_vec <- eicv$region  
  
# See the 3 first elements of the year column  
eicv$region[1:3]  
  
## [1] "Kigali City" "Kigali City" "Kigali City"
```

# R objects

## Data Frames

The `eicv` and `kigali` objects are both data frames. You can also construct a new data frame from scratch by combining vectors with the same number of elements .

Now, type the following code to create a new data frame

```
# Dataframe created by biding vectors
```

```
df1 <- data.frame(v1,v2)
```

```
df1
```

```
##      v1 v2
## 1     1  1
## 2     1  2
## 3     2  3
## 4     3  4
## 5     5  5
```

Since a data frame has two dimensions, you can use indexing on both:

### Numeric indexing

```
# The first column of whr  
eicv[,1]
```

```
# The 45th line of whr  
eicv[45,]
```

```
# Or the 45th element of the first column  
eicv[45,1]
```

Alternatively, you can use the column names for indexing, which is the same as using the \$ sign.

### Names indexing

```
# Or the 22th element of the province column  
eicv[22,"province"] # The same as eicv$province[22]
```

```
## # A tibble: 1 x 1  
##   province  
##   <chr>  
## 1 Kigali City
```

Lists are more complex objects that can contain many objects of different classes and dimensions.

The outputs of many functions, a regression for example, are similar to lists.

It would be beyond the scope of this introduction to go deep into them, but here's a quick example

Combine several objects of different types in a list

```
# Use the list() function  
lst <- list(v1, df1, 45)
```

Print the list yourself to see how it looks like.



# R objects

## Lists

```
# Check the contents of lst
```

```
print(lst)
```

```
## [[1]]
```

```
## [1] 1 1 2 3 5
```

```
##
```

```
## [[2]]
```

```
##      v1 v2
```

```
## 1    1  1
```

```
## 2    1  2
```

```
## 3    2  3
```

```
## 4    3  4
```

```
## 5    5  5
```

```
##
```

```
## [[3]]
```

```
## [1] 45
```

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data**
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

# Basic types of data

R has different kinds of data that can be recorded inside objects. They are very similar to what you have in Stata, and the main types are string, integer, numeric, factor and boolean.

Let's start with the simpler ones:

## Strings

A sequence of characters and are usually represented between double quotes. They can contain single letters, words, phrases or even some longer text.

## Integer and numeric

As in Stata, these are two different ways to store numbers. They are different because they use memory differently. As default, R stores numbers in the numeric format (double).

# Basic types of data

## Strings

Now we'll use string data to practice some basic object manipulations in R.

### Exercise 4: Create a vector of strings

Create a string vector containing the names of commonly used statistical software in order of importance:

```
# Creating string vector  
str_vec <- c("R",  
             "Python",  
             "SAS",  
             "Excel",  
             "Stata")
```

Now print them to check them out.

### Exercise 5: Concatenate strings

- 1 Create a scalar (a vector of one element) containing the phrase “is better than” and call it `str_scalar`.
- 2 Use the function `paste()` with 3 arguments separated by commas:
  - The first argument as the 1st element of `str_vec`.
  - The second argument as the `str_scalar`.
  - The third argument as the 5th element of `str_vec`.
- 3 If you're not sure where to start, type:

```
help(paste)
```

# Basic types of data

## Strings

```
### Using the paste function to combine strings
```

```
# Scalar
```

```
str_scalar <- "is better than"
```

```
# Using the paste() function
```

```
paste(str_vec[1], str_scalar, str_vec[5])
```

```
## [1] "R is better than Stata"
```

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data**
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix

# Advanced types of data

R also has other more complex ways of storing data. These are the most used:

## Factors

Factors are numeric categorical values with text label, equivalent to labelled variables in Stata. Turning strings into factors makes it easier to run different analyses on them and also uses less space in your memory.

## Booleans


Booleans are logical binary variables, accepting either TRUE or FALSE as values. They are automatically generated when performing logical operations



# Advanced types of data

## Factors

In eicv, we can see that `country` and `region` are factor variables. In your environment panel, there is the information of the type of all variables, and for factors the number of levels.



# Advanced types of data

## Factors

We'll learn how to deal with factors in detail on the next session, since they are very important for us. For now, here are two important things to keep in mind when using them:

### Warning:

Unlike Stata, in R

- 1 You use the labels to refer to factors
- 2 You cannot choose the underlying values

# Advanced types of data

## Booleans

Boolean data is the result of logical conditions

- Whenever you're using an `if` statement in Stata, you're implicitly using boolean data.
- The difference is that in R, this can be done in 2 steps.

# Advanced types of data

## Booleans

### Exercise 6:

Create boolean vector with the condition of Consumption below average:

```
# Create vector
```

```
bool_vec <- eicv$Consumption < mean(eicv$Consumption)
```

```
# See the 6 first elements of the vector
```

```
head(bool_vec)
```

```
## [1] TRUE FALSE FALSE TRUE FALSE TRUE
```

# Advanced types of data

## Booleans

Let's use the boolean vector created to add a dummy variable in the `whr` data set for the same condition.

### Exercise 6:

- 1 Create a column in `whr` containing zeros and call it `rank_low`. You can do this by typing:

```
eicv$rank_low <- 0
```

- 2 Use `bool_vec` to index the lines of the `income_low` column and replace all observations that meet the condition with the value 1.

```
eicv$rank_low[bool_vec] <- 1
```

# Advanced types of data

## Booleans

```
# Replace with 1 those obs that meet the condition  
eicv$rank_low [bool_vec] <- 1  
# is the same as  
eicv$rank_low[eicv$Consumption < mean(eicv$Consumption)] <- 1  
# This in stata would be  
# replace rank_low = 1 if (...)  
  
# We can use the summary function to get descriptives  
summary(eicv$rank_low)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.  
##  0.0000  0.0000  1.0000  0.7427  1.0000  1.0000
```

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow**
- 11 Useful resources
- 12 Appendix

Help in R works very much like in Stata: the help files usually start with a brief description of the function, explain its syntax and arguments and list a few examples. There are two ways to access help files:

## Exercise 7: Use help

```
# The help() function
```

```
help(summary)
```

```
# and its abbreviation
```

```
?summary
```



- The biggest difference, however, is that R has a much wider user community and it has a lot more online resources.
- For instance, in 2014, Stata had 11 dedicated blogs written by users, while R had 550.<sup>1</sup>
- The most powerful problem-solving tool in R, however, is Google. Searching the something yields tons of results.
- Often that means a Stack Overflow page where someone asked the same question and several people gave different answers. Here's a typical example: <https://stackoverflow.com/questions/1660124/how-to-sum-a-variable-by-group>

---

<sup>1</sup>Check <http://r4stats.com/articles/popularity/> for more.

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources**
- 12 Appendix

## Blogs and online courses:

- Surviving graduate econometrics with R:  
<https://thetarzan.wordpress.com/2011/05/24/surviving-graduate-econometrics-with-r-the-basics-1-of-8/>
- CRAN's manuals: <https://cran.r-project.org/manuals.html>
- R programming in Coursera:  
<https://www.coursera.org/learn/r-programming>
- R programming for dummies:  
<http://www.dummies.com/programming/r/>
- R bloggers: <https://www.r-bloggers.com/>
- R statistics blog: <https://www.r-statistics.com/>
- The R graph gallery: <https://www.r-graph-gallery.com/>

## Books:

- R for Stata Users - Robert A. Muenchen and Joseph Hilbe
- R Graphics Cookbook - Winston Chang
- R for Data Science - Hadley Wickham and Garrett Grolemund

Thank you!

# Outline

- 1 Installation
- 2 Introduction
- 3 Getting started
- 4 RStudio interface
- 5 Data in R
- 6 Functions
- 7 R objects
- 8 Basic types of data
- 9 Advanced types of data
- 10 Help, Google and Stackoverflow
- 11 Useful resources
- 12 Appendix**

R's syntax is a bit heavier than Stata's:

- Parentheses to separate function names from its arguments.
- Commas to separate arguments.
- For comments we use the # sign.
- You can have line breaks inside function statements.
- In R, functions can be treated much like any other object Therefore, they can be passed as arguments to other functions.

Similarly to Stata:

- Square brackets are used for indexing.
- Curly braces are used for loops and if statements.
- Largely ignores white spaces.

# Appendix - RStudio interface

## Script

Where you write your code. Just like a do file.

## Console

Where your results and messages will be displayed. But you can also type commands directly into the console, as in Stata.

## Environment

What's in R's memory.

## The 4th pane

Can display different things, including plots you create, packages loaded and help files.



A matrix is a bi-dimensional object composed by one or more vectors of the same type.

Type the following code to test two different ways of creating matrices

```
# Matrix created by joining two vectors:
```

```
m1 <- cbind(v1,v1)
```

```
# Matrix using the
```

```
m2 <- matrix(c(1,1,2,3,5,8), ncol = 2)
```

## Appendix - Matrices

Now use the following code to check the elements of these matrices by indexing

```
# Matrix indexing: typing matrix[i,j] will give you  
# the element in the ith row and jth column of that matrix  
#m2[1,2]
```

```
# Matrix indexing: typing matrix[i,] will give you the  
# ith row of that matrix  
m1[1,]
```

```
# Matrix indexing: typing matrix[,j] will give you the  
# jth column of that matrix (as a vector)  
m1[,2]
```

# Appendix - Advanced types of data - Factors

## Factors

Create a factor vector using the following code

```
# Basic factor vector
```

```
num_vec <- c(1,2,2,3,1,2,3,3,1,2,3,3,1)
```

```
fac_vec <- factor(num_vec)
```

```
# A bit fancier factor vector
```

```
fac_vec <- factor(num_vec, labels=c("A", "B", "C"))
```

```
# Change labels
```

```
levels(fac_vec) = c('One', 'Two', 'Three')
```

## Appendix - Numbers and integers

Two scalars, one with a round number the other with a fractional part

*# a numeric scalar with an integer number*

```
int <- 13
```

```
num <- 12.99
```

## Appendix - Numbers and integers

Now we can see the objects classes with the `class()` function and test it with the `is.integer()` and `is.numeric()` functions.

*# you can see the number's format using the class function:*

```
class(int)
```

```
## [1] "numeric"
```

```
class(num)
```

```
## [1] "numeric"
```

*# you can test the class with the is. method*

```
is.integer(int)
```

```
## [1] FALSE
```

```
is.numeric(int)
```

```
## [1] TRUE
```

Did you notice anything strange? That happens because the default way R stores numbers is *numeric*, which is equivalent to *double* in Stata.

# Appendix - Numbers and integers

## Numbers and integers

We can, however, coerce objects into different classes. We just need to be careful because the result might not be what we're expecting.

Use the *as.integer()* and *round()* functions on the *num* object to see the difference:

```
as.integer(num)
```

```
## [1] 12
```

```
# and
```

```
round(num)
```

```
## [1] 13
```