

L11: Square root SAM ($\sqrt{\text{SAM}}$)

* Summary of L10: Smoothing and mapping


SLAM as a Factor graph (prev. Bayes network)

$$\theta^* = \arg \max_{\theta} p(X, M | Z, u) = \arg \min_{\theta} \{ \underbrace{\sum \| \cdot \|_{Z_i}^2}_{\text{odometry, observation and prior factors}} \}$$

$$\delta^* = \arg \min \| A \delta - b \|_Z^2 \quad (\text{LLSQ})$$

1) 1st order Taylor

$$2) \| e \|_Z^2 = \| Z^{-T/2} e \|_2^2$$



$AS = b$ iteratively solved until convergence,

* $A^T A = \Lambda$ (Information matrix)

we presented SAM as a MAP estimator of $x_{0:t}$ in

$$\arg \max_{\theta} P(X, M, z, u)$$

\downarrow (-log)
linearization.

$$\arg \min_{\delta} \|A\delta - b\|_2^2 \quad \left(\text{In fact, all these factors express a distribution as well.} \right)$$

$$\|A\delta - b\|_2^2 = (A\delta - b)^T (A\delta - b)$$

$$= \delta^T A^T A \delta - \delta^T A^T b - b^T A \delta + b^T b \quad \left\{ \begin{array}{l} = \\ \text{if } b = A\mu \end{array} \right.$$

$$= \delta^T \underbrace{A^T A}_{\Lambda} \delta - 2 \delta^T A^T A \mu + \mu^T A^T A \mu =$$

$$= (\delta - \mu)^T A^T A (\delta - \mu)$$

(Gaussian prior
of the error δ of
the state.

* Normal equation

$$A^T A \delta = A^T b$$

$$\delta = (A^T A)^{-1} A^T b \quad \text{inversion } O(n^3)$$

A is sparse \rightarrow exploit by SOTA linear algebra.

* Cholesky factorization

$$\Lambda = A^T A = L \cdot L^T = R^T R$$


(inversion matrix) $\Delta \nabla \Delta \nabla$

$$\text{chol} \begin{cases} A^T A \delta = A^T b \\ R^T R \delta = A^T b \end{cases}$$

Hence, square root methods

$$\begin{cases} R^T \cdot y = A^T b \\ R \cdot \delta = y \end{cases}$$

Solved efficiently by back-substitution



$$= \begin{bmatrix} \vdots \\ \vdots \\ \vdots \\ \vdots \end{bmatrix} \text{ back/4}$$

var. \rightarrow easy.

Ex:

$$\begin{bmatrix} 1 & 0 & 0 \\ 5 & 7 & 0 \\ 6 & -7 & 3 \end{bmatrix} \begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} 2 \\ 5 \\ 5 \end{bmatrix}$$

$$1) y_1 = 2$$

$$2) 5 \cdot 2 + 7 \cdot y_2 = 5$$

$$y_2 = -\frac{5}{7}$$

$$3) 6y_1 - 7y_2 + 3y_3 = 5$$

$$6 \cdot 2 - 7 \cdot \left(-\frac{5}{7}\right) + 3y_3 = 5 \Rightarrow y_3 = \frac{5 - 12 - 5}{3} = 4$$

Cholesky factorization requires to solve 2 systems by backsubstitution

QR factorization

$$Q^T A = \begin{bmatrix} R \\ 0 \end{bmatrix}$$

Q: orthonormal matrix (square)

R: Upper triangular matrix.

$$Q^T b = \begin{bmatrix} d \\ e \end{bmatrix}$$

$$\|As - b\|_2^2 = \|Q^T A s - Q^T b\|_2^2 =$$

$$= \left\| \begin{bmatrix} R \\ 0 \end{bmatrix} s - \begin{bmatrix} d \\ e \end{bmatrix} \right\|_2^2 = \|R s - d\|_2^2 + \|e\|_2^2$$

$$\boxed{R s = d}$$

1 backsubstitution.

No need to calculate $\Lambda = A^T A$

Computationally equivalent to Cholesky (for dense matrices)

Is R the same as for Cholesky?

$$\Lambda = A^T A = (QR)^T QR = R^T \underbrace{Q^T Q}_I R = R^T R$$

Cholesky with positive diagonal terms is unique.

* Schur - complement (g2o, Kummerle '2011)

$$\Lambda = A^T A = \begin{bmatrix} \Lambda_x & \Lambda_{xm} \\ \Lambda_{mx} & \boxed{\Lambda_m} \end{bmatrix}, \quad d = \begin{bmatrix} d_x \\ d_m \end{bmatrix}, \quad A^T b = \begin{bmatrix} b_x \\ b_m \end{bmatrix}$$

diagonal = easy to invert!

$$A^T A d = A^T b$$

$$\begin{cases} \Lambda_x d_x + \Lambda_{xm} d_m = b_x \\ \Lambda_{mx} d_x + \Lambda_m d_m = b_m \end{cases} \quad \left(\times \Lambda_{xm} \Lambda_m^{-1} \right)$$

$$\begin{cases} \Lambda_x d_x + \Lambda_{xm} d_m = b_x \\ \Lambda_{xm} \Lambda_m^{-1} \Lambda_{mx} d_x + \cancel{\Lambda_{xm} \Lambda_m^{-1} \Lambda_m} d_m = \Lambda_{xm} \Lambda_m^{-1} b_m \end{cases}$$

$$(\Lambda_x - \Lambda_{xm} \Lambda_m^{-1} \Lambda_{mx}) d_x + 0 = b_x - \Lambda_{xm} \Lambda_m^{-1} b_m$$

Schur complement

1) solve $S \boxed{d_x} = b_s$ using Cholesky for instance.

$$2) \Lambda_{mx} d_x + \Lambda_m d_m = b_m$$


$$d_m = \Lambda_m^{-1} (b_m - \Lambda_{mx} d_x)$$

* Ordering of nodes to enhance solutions

Every graph has an optimal ordering of nodes:

- fewer edges when eliminating nodes
(equivalent to backsubstitution in linear algebra)
- fewer fill-ins in the square root factorization.


Ex:



$$\Lambda = A^T A$$

	a	b	c	d	e	f	g
a	x	x	x	x	x		
b	x	x					
c	x		x				
d	x			x			
e	x				x	x	
f					x	x	x
g						x	x

eliminate (a)



$$\Lambda'$$

	b	c	d	e	f	g
b	x	x	x	x		
c	x	x	x	x		
d	x	x	x	x		
e	x	x	x	x	x	x
f				x	x	x
g					x	x

New information matrix is denser than expected.

Adjacency matrix has more (factors) rows $A'_{8 \times 6}$
while before $A_{6 \times 7}$

* Minimum order degree

Intuition: The number of edges captures how connected the node is and we want to minimize that.

Permute the nodes on a non-decreasing order (heuristic)
(Solving the optimal ordering is NP-hard)

Ex:

	b	c	d	g	e	f	a
b	x						x
c		x					x
d			x				x
g				x			
e					x	x	x
f				x	x	x	
a	x	x	x		x		x

This ordered (permuted)
 $\Lambda_P = \Lambda(p, p)$ provides
less fill-ins during
factorization

colperm ($A^T A$) Cholsky

colperm (A) QR

CGLAND heuristic for ordering nodes (Davis' 2001)

As reported in Dellavent' 2006 they performed better using Cholsky and cglamd. But it is problem dependent.