

HW06 — API Testing Report

Student: Lê Tuấn Lộc (23127404)

Scope and method

Three APIs were selected from distinct pools: `POST /api/login` (FR-02), `POST /api/checkout` (FR-08), and `PUT /api/admin/orders/:id/status` (FR-10/FR-18). Every pool contains 35 AI-generated cases reviewed by a human and 5 human extensions. The final matrix records a contract oracle separately from the observed-SUT oracle; this prevents a known defect reproducer from being misreported as a conforming result.

Verified execution

Pool	Cases	Requests	Assertions	Failures	Raw result
A	40	40	167	0	<code>newman-reports/pool-a/cases/</code>
B	40	160	281	0	<code>newman-reports/pool-b/report.json</code>
C	40	120	240	0	<code>newman-reports/pool-c/report.json</code>

All requests inject `X-Student-Id: 23127404` ; the Newman console records this with `[HW06 EVIDENCE]` . An authentic Postman Console capture shows the header in a successful request at `postman/screenshots/postman_console_23127404.png` . Pool A runs one isolated fixture per row to prevent lockout state leakage. Pool B uses login → cart → checkout → cart-query workflow. Pool C uses individually seeded fixture orders, then authenticates both roles before the status update.

Human audit and extensions

All AI-generated rows were marked `VALID` after reconciliation with the requirement and live response. The extension set focuses on weaknesses an initial single-request prompt missed: persistent lockout state, password exposure, cart-to-order integrity, terminal state immutability, and role authorization. Full per-row rationale is in the Excel workbook.

Verified defects

The six reproducible root defects are listed in `bugs/bug-report.md` . The checkout defects are one root cause (the endpoint does not consult cart state) with multiple demonstrated consequences: empty checkout, amount tampering, and cart not cleared.

The corresponding public GitHub Issues are [#162](#), [#163](#), [#164](#), [#165](#), [#166](#), and [#167](#). Their authentic page captures are stored in `bugs/screenshots/` .

Postman/Newman features

Collections, local environment, iteration data, variables, pre-request scripts, Chai assertions, JSON reporting, workflow fixtures, and Newman CLI were used. Mock servers and monitors were not used and are not claimed.

CI/CD and skill

The workflow is included in `cicd/workflows/api-tests.yml` . The all-pass evidence is commit [d07a9b1](#) and its [GitHub Actions run](#). The required intentional red evidence is commit [aa32d91](#) and its [GitHub Actions run](#): it intentionally expected `999` for `TC-LOGIN-01` and received `200` . The current test data restores the correct `200` expectation; authentic captures are in `cicd/screenshots/` . The reusable generator and its pseudocode are in `agent-skills/api-test-generator/` ; the diagram source is preserved as Mermaid. Video: <https://youtu.be/RjtRRfqsz7s>.