

Base44 Integration & Debugging Guide

Resolving Regional API Constraints and Fixing Broken Reports from Hong Kong

Quick Summary: If your Base44 report is currently failing to generate, it is highly likely due to backend regional restrictions affecting developer API endpoint handshakes. Since Base44 executes logic on server instances, using unrestricted connections or internal functions resolves the block immediately.

Why the Mobile App Works vs. the API Restrictions

Google opens consumer-facing mobile/web layers under standard retail Terms of Service globally, leading to functional mobile apps. However, production developer pipelines, Vertex AI environments, and granular API key permissions go through rigid corporate compliance. If an application utilizes a developer key from an unlisted endpoint region, backend validation will fail and block data transfers.

Option 1: Fix via Native Base44 Model (Recommended)

The fastest way to restore your report without updating code or managing security tokens is to route operations through Base44's built-in execution layers. This completely isolates your pipeline from local configuration errors.

1

Enter App Editor Chat

Open your project dashboard and locate the building chat window inside the Base44 app workspace.

2

Submit Prompt to AI Builder

Provide clear operational directions to let the AI swap out the failing configuration block. Paste the following text:

"The current reporting logic is broken due to API restrictions. Please switch the background generation step to use the native Base44 'Invoke LLM' integration instead of an external API key."

3

Deploy and Re-test

Allow the builder to finish reconstructing the backend functions, then click **Deploy** or **Publish** to bring the reporting tools back online.

Option 2: Swap to Globally Open API Providers

If your structured logic explicitly requires external API capabilities, standardizing on a globally available ecosystem (like OpenAI or Anthropic Claude) guarantees stability in Hong Kong.

1

Generate a Valid Developer Key

Log into your OpenAI or Anthropic developer console, navigate to the API Access section, and generate a new production secret key token.

2

Register Token in Base44 Secrets

Navigate to **Dashboard** → **Secrets** → **Add Secret** inside Base44. Name your secret identifier precisely, such as `OPENAI_API_KEY`, and securely paste the string.

3

Update Processing Prompts

Instruct the AI builder chat to adjust your data maps: *"Update the data processing function for this report to pull from my saved OPENAI_API_KEY secret instead of the old key."*

Troubleshooting Layout & Payload Failures

If your connection status is healthy but report generation still encounters errors, review the structure of your data payloads using the reference matrix below:

Common Error Mode	Root Cause Analysis	Remediation Step
Empty JSON Arrays	The parser didn't strictly lock parameters into a structured output matrix.	Ask the chat: <i>"Enforce a strict JSON schema structure for the report data engine output."</i>
Token Limits Exceeded	The data block passed directly into the report compilation loop is too large.	Filter, aggregate, or limit input rows using a data slice before passing fields into the LLM step.
Function Errors (Code 500)	Broken variables or undefined parameters within the backend execution block.	Toggle the AI assistant into Discuss Mode and ask: <i>"Review the internal execution logs for this reporting function and repair the broken variables."</i>

Security Advisory: Never paste raw development credentials into frontend views or visible chat elements. Always use the secure Secrets Manager framework.