

Course: Web Application Development

Lab Instructor: Pham Lam

Email: pqslam@hcmiu.edu.vn

Lab 3 - Introduction to Servlet Programming

Content:

- Introduction to Java Servlet Technology
- How to create a servlet and run on Eclipse IDE
- Practices and Exercises

Duration: 3 hours+

Part 1: Introduction to Servlet and Servlet Life Cycle.

- **Recall: What is Servlet?**
 - o A *servlet* is a Java programming language class that is used to extend the capabilities of servers that host applications access via a request-response programming model.
 - o Although servlets can respond to any type of request, they are commonly used to extend the applications hosted by web servers. For such applications, Java Servlet technology defines HTTP-specific servlet classes.
- **How Java support Servlet Programming**
 - o The `javax.servlet` and `javax.servlet.http` packages provide interfaces and classes for writing servlets. All servlets must implement the Servlet interface, which defines servlet life-cycle methods.
 - o The **HttpServlet** class provides methods, such as **doGet** and **doPost**, for handling HTTP-specific services.
 - o When implementing a generic service, you can use or extend the **GenericServlet** class provided with the Java Servlet API.
- **Tomcat Servlet/JSP container**
 - o **Tomcat** can act as a stand-alone Web server and also as a servlet/JSP engine for other Web servers. When you download the Tomcat server, you really get a number of packages. **Catalina** and **Jasper** are the names of the servlet and JSP containers.
 - o Tomcat by itself is a web server. This means that you can use Tomcat to service HTTP requests for servlets, as well as static files (HTML, image files, and so on). In practice, however, since it is faster for non-servlet, non-JSP requests, Tomcat normally is used as a module with another more robust web server, such as Apache web server or Microsoft Internet Information Server (IIS).

- o Tomcat is not a J2EE application server. However, as J2EE app servers must themselves contain a servlet container to support the servlet/JSP APIs, J2EE app servers can embed Tomcat into their code to provide support for the Servlet and JSP APIs. One example of just such an application server is the popular open source JBoss J2EE app server (<http://www.jboss.org/>).

- Servlet Life Cycle


- o The `javax.servlet.Servlet` interface defines the methods that all servlets must implement and, among others, three methods that are known as **life-cycle methods**:

```
public void init(ServletConfig config) throws ServletException
```

```
public void service(ServletRequest req, ServletResponse res) throws ServletException, IOException
```

```
public void destroy()
```

- o These life-cycle methods are each called at separate times during the life span of a servlet, from the initial creation to the moment it's removed from service and destroyed. These methods are called in the following order:



1. When the servlet is constructed, it is initialized with the `init()` method.

2. Any requests from clients are handled initially by the `service()` method before delegating to the `doXxx()` methods in the case of an `HttpServlet`. The `service()` method is responsible for processing the request and returning the response.

3. When the servlet needs to be removed from service, it's destroyed with the `destroy()` method, then garbage collected and finalized. When the container decides to take a servlet out of service, it first ensures that any `service()` method calls have been completed.

- o The `init` method is called by the servlet container after the servlet class has been instantiated. The servlet container calls this method exactly once to indicate to the servlet that the servlet is being placed into service. The `init` method is important also because the servlet container passes a `ServletConfig` object, which contains the configuration values stated in the `web.xml` file for this application.
- o The `service` method is called by the servlet container after the servlet's `init` method to allow the servlet to respond to a request. The servlet container passes a `ServletRequest` object and the `ServletResponse` object. The


ServletRequest object contains the client's request and the ServletResponse contains the servlet's response.

- o The servlet container calls the **destroy** method before removing a servlet instance from service. This normally happens when the servlet container is shut down or the servlet container needs some free memory.

(More information: refer from textbook: *Core Servlets and Java Server Pages*)

Part 2: How to create a servlet and run on Eclipse IDE

- Create new **Dynamic Web Project** (if you don't have one).
- Right click on your project (on **Project Explorer** panel), **New** → **Servlet**




The screenshot shows the 'Create Servlet' dialog box in Eclipse. The title bar says 'Create Servlet'. Below the title bar, it says 'Specify class file destination.' and there is a blue 'S' icon. The dialog has several input fields: 'Project:' with a dropdown menu showing 'wad_test'; 'Source folder:' with a text box showing '/wad_test/src' and a 'Browse...' button; 'Java package:' with a text box showing 'hcmiu.scse.wad' and a 'Browse...' button; 'Class name:' with a text box showing 'WelcomeServlet'; and 'Superclass:' with a text box showing 'javax.servlet.http.HttpServlet' and a 'Browse...' button. There is a checkbox labeled 'Use an existing Servlet class or JSP' which is currently unchecked. Below this checkbox is another 'Class name:' text box showing 'WelcomeServlet' and a 'Browse...' button. At the bottom of the dialog, there is a row of buttons: a help icon (?), '< Back', 'Next >', 'Cancel', and 'Finish'.

****Note:**

- **Project:** name of your created project.
- **Source folder:** the root folder where new Servlet file will be saved to. Default is the **src** folder in your project.
- **Java package:** the sub folders/paths to your Servlet file. Mainly used for source code management. In this case, I use *hcmiu.scse.wad* for my Java package (my new Servlet file will be saved to *wad_test/src/hcmiu/scse/wad/*)
- **Class name:** The name of your Servlet
- **Supperclass:** The parent class of your Servlet, It should be *javax.servlet.http.HttpServlet* by default.

- At this point, you can choose **Finish** to create your new Servlet or **Next** for advanced options.
- If you select **Next**, you will be asked to enter servlet deployment descriptor specific information.



Create Servlet

Enter servlet deployment descriptor specific information.

Name:

Description:

Initialization parameters:

Name	Value	Description
------	-------	-------------

URL mappings:


/WelcomeServlet

☐ Asynchronous Support

****Note:**

- **Description:** you may provide a short description for your Servlet.
- **Initialization Parameters:** Some parameters used in your Servlet.
- **URL mappings:** the url point to Servlet. The default value is the name of your Servlet. The complete URL will be <http://localhost:{port}/{NameOfYourProject}/{YourServletName}>. Example: http://localhost:8080/wad_test/WelcomeServlet

- Choose **Finish** to create new Servlet or **Next** for other options.
- If you select **Next**, you will be asked to specify modifiers, interfaces, and method stubs.



Create Servlet

Specify modifiers, interfaces to implement, and method stubs to generate.

Modifiers: ☒ public ☐ abstract ☐ final

Interfaces:


Which method stubs would you like to create?

<input checked="" type="checkbox"/> Constructors from superclass	<input type="checkbox"/> destroy	<input type="checkbox"/> getServletConfig
<input checked="" type="checkbox"/> Inherited abstract methods	<input type="checkbox"/> service	<input checked="" type="checkbox"/> doGet
<input type="checkbox"/> init	<input type="checkbox"/> doPut	<input type="checkbox"/> doDelete
<input type="checkbox"/> getServletInfo	<input type="checkbox"/> doOptions	<input type="checkbox"/> doTrace
<input checked="" type="checkbox"/> doPost		
<input type="checkbox"/> doHead		

Note:

- **Interfaces:** define the interface you want your new Servlet implement.
- **Method Stubs:** selecting the functions you want your Servlet override from parent classes. By default, *doPost* and *doGet* are selected. In some cases (especially your course project), you may need other methods (such as *init*, *destroy*, *doPut*, *doDelete*) as well.


- Click **Finish** to complete all reconfiguration and create your new Servlet.



- Try to modify your **doGet** function to print out something. For example:


```
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {  
    // TODO Auto-generated method stub  
    response.getWriter().println("Welcome to your first Servlet");  
}
```

- Run your project and access to the Servlet (by URL) to see the result:




Part 3: Practices and Exercises.

Exercise1: design a form (ThreeParams.JSP) as below:




The screenshot shows a Microsoft Internet Explorer window titled "JSP Page - Microsoft Internet Explorer". The address bar displays "http://localhost:8084/TestServlet/". The page content is titled "Conllect Three Parameters" (note the typo). It contains three text input fields labeled "First Parameter", "Second Parameter", and "Third Parameter". The first field contains "Jonh", the second contains "David", and the third contains "Salar". Below these fields is a "Submit" button.

After input three values in the textbox -> click Submit button, it call result page GetThreeParam.class (this file is built from GetThreeParam.java)




The screenshot shows a Microsoft Internet Explorer window titled "Reading Three Request Parameters - Microsoft Internet Explorer". The address bar displays "http://localhost:8084/TestServlet/ThreeParams?param1=Jonh¶m2=David¶m3=Salar". The page content is titled "Reading Three Request Parameters". It displays a bulleted list of the received parameters: "param1: Jonh", "param2: David", and "param3: Salar".

Exercise 2: Design form Personal Information (PersonalInfor.jsp)



The screenshot shows a Microsoft Internet Explorer window titled "JSP Page - Microsoft Internet Explorer". The address bar displays "http://localhost:8084/TestServlet/PersonalInfor.jsp". The page content is titled "Personal Information". It contains several form fields: "ID" (text input with "IT090078"), "Name" (text input with "Nguyen Thi Kieu Linh"), "Email" (text input with "ntkl@yahoo.com.vn"), "Gender" (radio buttons for "Male" and "Female", with "Female" selected), "Major" (dropdown menu with "Business Administration" selected), and "Interesting Field" (text area with "Reading books, Swimming, etc."). At the bottom are "Insert" and "Cancel" buttons.

The result from GetInfor.java




Reading Personal Information - Microsoft Internet Explorer

Address: http://localhost:8084/TestServlet/GetInfor

Reading Personal Information	
ID	IT090078
Name	Nguyen Thi Kieu Linh
Email	ntkl@yahoo.com.vn
Gender	Female
Major	Business Administration
Interesting Field	Reading books, Swimming, etc.

Exercise 3: Design a register form, use Servlet to get all information when user click the Submit button and put into a new page.



JSP Page - Microsoft Internet Explorer

Address: http://localhost:8084/Lab1WP/RegisterForm.jsp

School of Computer Science & Engineering

Register Form

Full Name

ID

Email

Gender ☒ Male ☐ Female

Field of study

☐ Principle of EE 1

☐ Computer Network

List of subjects ☐ Web Application Development

☐ Object Oriented Programming

☐ Computer Graphics

Comments

The result show parameter Servlet (RegisterCourse.java)

Exercise 4 (bonus): You are required to modify the servlet in **Exercise 3**. When a user clicks on Submit button, all information will be sent to your email. You can use any technology, service or third party library to support the development of email function.