17 November 2025

A Comprehensive Review of Artificial Intelligence for Proactive and Adaptive Cybersecurity

Divesh Shyamkant Bari

Abstract

The traditional, reactive security measures have been rendered inadequate by the escalating sophistication and frequency of cyber threats. This paper reviews recent research on the integration of Artificial Intelligence (AI), Machine Learning (ML), Deep Learning (DL) into the domain of cybersecurity. Foundational principles of current cybersecurity systems along with their limitations against modern, large-scale attacks is outlined in this paper. Then the paradigm shift towards proactive threat hunting and the adoption of advanced architectures is examined. These architectures include Heterogeneous and Hierarchical Graph Neural Networks (HGNNs), for robust intrusion and anomaly detection. Furthermore, we explore the transformative role played by Large Language Models (LLMs) in threat intelligence and scam detection, highlighting novel approaches such as Retrieval-Augmented Generation (RAG) for temporal adaptation and multi-model voting systems for adversarial robustness. This review also considers and addresses the threat of offensive AI, the critical need for privacy preserving techniques like Federated Learning, and specific applications in IoT/OT environments. Finally, we discuss critical challenges, including model interpretability and adversarial vulnerabilities, outlining future research directions for creating resilient, selfadaptive security ecosystems.

Keywords

artificial intelligence, computing and processing, deep learning, explainable ai, federated learning, graph neural networks, intrusion detection, large language models, machine learning, offensive ai, threat hunting

Posted on 17 November 2025 — CC-BY 4.0 — This is a preprint and has not been peer reviewed. Data may be preliminary. — https://doi.org/10.36227/techrxiv.176339197.78312572/v1

A Comprehensive Review of Artificial Intelligence for Proactive and Adaptive Cybersecurity

Divesh Shyamkant Bari
Department of Artificial Intelligence and Data Science
Genba Sopanrao Moze College of Engineering, Balewadi
Pune, India
diveshbari13@gmail.com

***Abstract*—The traditional, reactive security measures have been rendered inadequate by the escalating sophistication and frequency of cyber threats. This paper reviews recent research on the integration of Artificial Intelligence (AI), Machine Learning (ML), Deep Learning (DL) into the domain of cybersecurity. Foundational principles of current cybersecurity systems along with their limitations against modern, large-scale attacks is outlined in this paper. Then the paradigm shift towards proactive threat hunting and the adoption of advanced architectures is examined. These architectures include Heterogeneous and Hierarchical Graph Neural Networks (HGNNs), for robust intrusion and anomaly detection. Furthermore, we explore the transformative role played by Large Language Models (LLMs) in threat intelligence and scam detection, highlighting novel approaches such as Retrieval-Augmented Generation (RAG) for temporal adaptation and multi-model voting systems for adversarial robustness. This review also considers and addresses the threat of offensive AI, the critical need for privacy preserving techniques like Federated Learning, and specific applications in IoT/OT environments. Finally, we discuss critical challenges, including model interpretability and adversarial vulnerabilities, outlining future research directions for creating resilient, self-adaptive security ecosystems.**

***Index Terms*—Artificial Intelligence, Machine Learning, Deep Learning, Large Language Models, Intrusion Detection, Threat Hunting, Graph Neural Networks, Explainable AI, Offensive AI, Federated Learning**

I. Introduction

The digital landscape is increasingly besieged by complex, evolving cyber threats that easily bypass conventional, signature-based security defenses. High-profile incidents such as the SolarWinds supply chain attack, the Colonial Pipeline ransomware incident, and widespread exploitation of zero day vulnerabilities like Log4j have starkly demonstrated the inadequacy of reactive security postures. As noted by Nnamani [1], this reality necessitates a fundamental transformation in cybersecurity strategies, moving from static, rule-based systems to dynamic, adaptive entities powered by Artificial Intelligence (AI). AI and Machine Learning (ML) have emerged as formidable allies in this arena, offering unparalleled capabilities in analyzing vast datasets to detect anomalies and predict potential threats before they materialize [2].

This paper reviews a diverse body of recent research that highlights the multi-faceted application of AI in cybersecurity. Beyond simple automation, proactive threat-hunting techniques are explored [4], along with sophisticated deep learning architectures for complex data structures [9]-[11], and the growing role of Large Language Models (LLMs) [5]. Additionally, specific implementations that address the "black box" problem through Explainable AI (XAI) are examined [6], along with methods to enhance model robustness against adversarial attacks [7]. By synthesizing these diverse strands of research, a comprehensive overview of the current state-of-the-art techniques is provided, including offensive uses of AI and privacy-preserving techniques. Additionally, challenges that hinder the development of fully autonomous and resilient cyber defense systems are investigated.

II. Current Cybersecurity Landscape

Before diving deep into advanced AI applications, it is necessary to understand the foundational mechanisms of current cybersecurity systems and why they struggle against modern threats.

A. Traditional Mechanisms and Limitations

Current cybersecurity relies heavily on reactive and signature-based methodologies.

- **Signature-Based Detection:** Antivirus software and Intrusion Detection Systems (IDS) use databases of known threat signatures to identify malware. While effective against known threats, they are blind to zero-day attacks and polymorphic malware that alters its code to evade detection [1], [6].
- **Rule-Based Systems:** Firewalls and Security Information and Event Management (SIEM) systems use predefined rules to filter traffic and correlate events [4]. These static rules often fail to adapt to dynamic attacker tactics, such as "living off the land" attacks where legitimate tools are used for malicious purposes [9].
- **Anomaly-Based Detection (Traditional):** Early anomaly detection relied on simple statistical baselines. These systems often suffer from high false-positive rates due to benign but unusual user behavior, leading to "alert fatigue" for security analysts [6], [10].

B. Impact of recent Large-Scale attacks

- **SolarWinds (2020):** A sophisticated supply chain attack where attackers compromised the software update mechanism of SolarWinds Orion. This allowed them to infiltrate thousands of organizations, including government agencies, undetected for months. Traditional perimeter defenses failed because the initial compromise came from a trusted source.
- **Colonial Pipeline (2021):**A ransomware attack that successfully shut down a major U.S. fuel pipeline. The attack exploited a compromised password for an old VPN account, demonstrating how a single point of failure can bypass complex security stacks that lack behavioral monitoring.
- **Log4j (2021):**A critical zero-day vulnerability in a widely used Java logging library. The sheer ubiquity of the library and the ease of exploitation overwhelmed traditional patch management and vulnerability scanning processes, requiring rapid, automated identification and mitigation at a scale only AI-driven systems could potentially manage effectively.

These incidents underscore the critical need for intelligent, proactive, and adaptive capabilities that can detect subtle behavioral anomalies and unknown threats, capabilities that are central to modern AI and ML technologies.

III. THE SHIFT TO PROACTIVE THREAT HUNTING

Building on the limitations of traditional systems, Osinaike et al. [4] argue for a paradigm shift towards AI-powered proactive threat hunting. By leveraging ML and DL algorithms, organizations can transition from passively waiting for alerts to actively searching for hidden threats within their networks. This involves analyzing massive, real-time datasets to detect subtle behavioral changes and anomalies that human analysts might miss. Technologies such as anomaly detection, behavioral analysis, and Natural Language Processing (NLP) for parsing unstructured threat data are central to this proactive stance. The goal is to reduce the "dwell time" of attackers by predicting and neutralizing threats before they cause significant damage [4].

IV. ADVANCED ARCHITECTURES FOR ANOMALY DETECTION

As cyber data becomes more complex, simple statistical models are often insufficient. Recent research has focused on advanced deep learning architectures capable of modeling the intricate, interconnected nature of network entities.

A. Graph-Based Approaches

Cybersecurity data is inherently heterogeneous and dynamic, involving diverse entities like users, hosts, and files interacting over time. Jiang et al. [9] provide a comprehensive survey of Heterogeneous Graph Neural Networks (HGNNs) for anomaly detection. They argue that traditional homogeneous graph models fail to capture the rich semantic and temporal dependencies in real-world cyber systems. These HGNNs address this by incorporating type-aware transformations and relation-sensitive aggregation [9].

Beyond heterogeneous models, Hierarchical Graph Neural Networks (HGNNs) offer another powerful paradigm, particularly for multi-modal data fusion. Zhang et al. [11] demonstrate this in a spatial morphology context, using a hierarchical structure to integrate diverse data modalities—images, text, and scalar metrics—via specialized input and communication nodes. Adapting such hierarchical, multi-modal frameworks to cybersecurity could significantly enhance detection by simultaneously processing diverse data streams, such as network traffic visualizations, unstructured threat report texts, and tabular log data, within a unified graph structure [11].




Fig. 1. Conceptual illustration of a Heterogeneous Graph Neural Network (HGNN) modeling diverse entities (users, hosts, files) and their interactions in a cybersecurity context. Source: [9].

Building on these advanced graph concepts, Biradar et al. [10] propose a novel hybrid architecture that synergizes Graph Neural Networks (GNNs) with Recurrent Neural Networks (RNNs) and multi-head attention mechanisms. Their model captures both spatial dependencies (via GNNs) and temporal dynamics (via LSTM networks) in network traffic. The core of their interpretability lies in the multi-head attention mechanism, where attention weights for each head i are computed as:

$$\text{Attention}(Q_i, K_i, V_i) = \text{softmax}\left(\frac{Q_i K_i^T}{\sqrt{d_k}}\right) V_i \qquad (1)$$

where Q_i, K_i, and V_i are the query, key, and value matrices, and d_k is the dimension of the keys [10]. This integrated attention mechanism not only enhances feature selection but also improves interpretability by highlighting critical time steps and features during an attack.

B. Automated and Explainable ML

The complexity of designing effective ML pipelines is a significant barrier to adoption. Yakubu et al. [6] address this by introducing an automated framework for Denial of Service (DoS) detection. They leverage the Tree-based Pipeline Optimization Tool (TPOT) to automate model selection and




Fig. 2. High-level overview of a hybrid GNN-RNN-Attention architecture for intrusion detection, processing spatial data through GNNs and temporal sequences through RNNs before attention-based feature prioritization. Source: [10].

feature optimization, reducing manual experimentation. Crucially, they integrate SHapley Additive exPlanations (SHAP) to provide transparency.

To rigorously evaluate such models, especially in imbalanced datasets common in cybersecurity, standard accuracy is often insufficient. Metrics like the F1-score and Area Under the Receiver Operating Characteristic Curve (AUROC) are essential:

$$\text{F1-Score} = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \tag{2}$$

$$\text{AUROC} = \int_0^1 \text{TPR}(\text{FPR}^{-1}(x))\, dx \tag{3}$$

where TPR is the True Positive Rate and FPR is the False Positive Rate. These metrics provide a more nuanced view of model performance, balancing false positives and false negatives [9], [10].

C. Other Deep Learning Applications

Other architectures are also being explored. Kim et al. [3] investigated the use of Convolutional Neural Networks (CNNs) for enhancing security in script development. While their proof-of-concept used the Fashion MNIST dataset as a proxy for image-based script analysis, it highlights the potential of computer vision techniques in identifying malicious visual patterns in code or software interfaces [3].

V. Large Language Models in Cybersecurity

The advent of Large Language Models (LLMs) has opened new frontiers in cybersecurity, from automated threat intelligence to novel attack vectors

A. Adapting to New Threats

A critical limitation of standard LLMs is their static knowledge base, which quickly becomes outdated as new vulnerabilities emerge. Borah et al. [8] propose a Retrieval-Augmented Generation (RAG) framework to address this. By connecting the LLM to external, up-to-date cybersecurity databases (like CVE repositories), their hybrid sparse-dense retriever ensures that the model's reasoning is grounded in the latest threat intelligence.




Fig. 3. A Retrieval-Augmented Generation (RAG) framework for cybersecurity, showing how an LLM queries an external knowledge base of up-to-date threat intelligence before generating a response. Source: [8].

B. Defending Against Adversarial Attacks

LLMs themselves are vulnerable to adversarial manipulation. Chang et al. [7] introduce "Scam Shield," a Hierarchical Scam Detection System (HSDS) designed to withstand adversarial text perturbations (e.g., synonym replacement) used by scammers to bypass filters. Their system employs a computationally efficient multi-model voting front-end for initial classification, escalating only ambiguous cases to a robust, fine-tuned LLaMA model. This hybrid approach balances high detection accuracy with computational efficiency [7].

C. Security of LLM Applications

Integrating LLMs into security tools introduces new risks, such as prompt injection attacks. Somani and Cherukuri [5] discuss frameworks like "Encrypted Prompts" to secure LLM interactions. By embedding permissions and using cryptographic techniques, organizations can ensure that LLMs act only within authorized scopes, mitigating the risk of them being hijacked for malicious purposes [5].

VI. Offensive AI: The Adversarial Landscape

AI is a dual-use technology, and its capabilities are increasingly being weaponized by threat actors. Understanding this "offensive AI" landscape is crucial for developing robust defenses.

- **AI-Powered Malware:** Attackers are using AI to develop malware that can adapt its behavior to evade detection by traditional security tools. By learning from the target environment, this malware can blur its code or delay execution until it detects a vulnerable state [12].
- **Deepfakes and Social Engineering:** Generative Adversarial Networks (GANs) are used to create hyper-realistic deepfake audio and video. These are increasingly deployed in highly targeted social engineering attacks (like

Business Email Compromise) to impersonate executives and authorize fraudulent fund transfers [13].

- **Automated Vulnerability Discovery:** AI tools can scan software at unprecedented speeds to identify zero-day vulnerabilities, allowing attackers to weaponize them before patches are available [12].

VII. Privacy-Preserving AI in Cybersecurity

Effective cybersecurity often requires sharing threat intelligence across organizations, but this raises significant privacy and regulatory concerns. Privacy-preserving AI techniques are emerging as a critical solution.

- **Federated Learning (FL):** FL allows multiple organizations to collaboratively train a shared intrusion detection model without sharing their raw network traffic data. Instead, they share only model updates (gradients), preserving data privacy while benefiting from collective intelligence [14].
- **Differential Privacy (DP):** DP adds carefully calibrated noise to datasets or model outputs, ensuring that no individual user's data can be reverse-engineered from the AI model, thus enabling compliance with regulations like GDPR.

VIII. Domain-Specific Applications: IoT and OT Security

The Internet of Things (IoT) and Operational Technology (OT) environments present unique security challenges due to their resource-constrained devices and critical real-world impact.

- **Resource Constraints:** Standard deep learning models are often too computationally heavy for edge devices like sensors or industrial controllers. Research is focusing on "lightweight" AI models(compressed via techniques like knowledge distillation or quantization)that can run directly on these devices for real-time anomaly detection.
- **Physical Consequences:** In OT environments (e.g., power grids, manufacturing), a cyberattack can have physical consequences. AI models here must be highly accurate and explainable, as false positives can lead to costly operational downtime.

IX. Comparative Summary of Surveyed Works

Table I provides a comparative summary of the key methodologies and contributions reviewed in this paper.

X. Challenges and Future Directions

Despite these advancements, several critical challenges remain. Data quality and the scarcity of labeled datasets for rare attack types continue to hinder model training [4], [9]. The "black box" nature of many advanced models necessitates further research into interpretability techniques to foster trust among human analysts [6]. Furthermore, as AI defenses evolve, so too does adversarial AI, leading to a perpetual "cat and mouse" game that requires models to be continuously retrained and hardened against evasion techniques [4], [7]. Future research must focus on developing standardized benchmarks, enhancing real-time adaptive capabilities, and creating unified frameworks that seamlessly integrate human expertise with autonomous AI systems [9].

XI. Conclusion

The integration of AI into cybersecurity represents a necessary evolution to counter modern threats. From proactive threat hunting and advanced graph modeling to adaptable LLMs and automated, explainable pipelines, the research reviewed here demonstrates the immense potential of these technologies. Moving forward, a holistic approach that addresses interpretability, robustness, privacy, and real-world scalability will be essential for building the next generation of resilient cyber defenses.

References

[1] C. C. Nnamani, "Exploiting AI Capabilities: An in-Depth Analysis of Artificial Intelligence Integration in Cybersecurity for Threat Detection and Response," *International Journal of Education, Management, and Technology*, vol. 2, no. 3, pp. 268-286, Dec. 2024.

[2] F. Greene, "AI and Machine Learning in Combating Cyber Threats," *International Journal of Advanced and Innovative Research*, vol. 10, no. 1, 2021.

[3] T.-h. Kim et al., "Enhancing cybersecurity through script development using machine and deep learning for advanced threat mitigation," *Scientific Reports*, vol. 15, Art. no. 8297, 2025.

[4] T. Osinaike, A. Yetunde, and C. V. Onyenagubo, "A Survey of AI-Powered Proactive Threat-Hunting Techniques: Challenges and Future Directions," *International Journal for Multidisciplinary Research (IJFMR)*, vol. 6, no. 6, Nov.-Dec. 2024.

[5] R. Somani and A. K. Cherukuri, "Large Language Models for Cyber Security," arXiv preprint arXiv:2511.04508, 2025.

[6] P. B. Yakubu et al., "Automated and Explainable Denial of Service Analysis for AI-Driven Intrusion Detection Systems," arXiv preprint arXiv:2511.04114, 2025.

[7] C.-W. Chang et al., "Scam Shield: Multi-Model Voting and Fine-Tuned LLMs Against Adversarial Attacks," arXiv preprint arXiv:2511.01746, 2025.

[8] A. Borah, M. T. Alam, and N. Rastogi, "Adapting Large Language Models to Emerging Cybersecurity using Retrieval Augmented Generation," arXiv preprint arXiv:2510.27080, 2025.

[9] L. Jiang, R. Ryan, Q. Li, and N. Ferdosian, "A Survey of Heterogeneous Graph Neural Networks for Cybersecurity Anomaly Detection," arXiv preprint arXiv:2510.26307, 2025.

[10] J. Biradar, S. Shah, and T. Naik, "Attention Augmented GNN RNN-Attention Models for Advanced Cybersecurity Intrusion Detection," arXiv preprint arXiv:2510.25802, 2025.

[11] J. Zhang, Z. Zhu, J. Deng, Y. Li, and B. Wang, "Multi-Modal Feature Fusion for Spatial Morphology Analysis of Traditional Villages via Hierarchical Graph Neural Networks," arXiv preprint arXiv:2510.27208, 2025.

[12] CrowdStrike, "Most Common AI-Powered Cyberattacks," crowdstrike.com. [Online]. Available: https://www.crowdstrike.com/en-us/cybersecurity-101/cyberattacks/ai-powered-cyberattacks/. [Accessed: Nov. 9, 2025].

[13] HyperVerge, "Top 10 Examples of Deepfake Across The Internet," hyperverge.co. [Online]. Available: https://hyperverge.co/blog/examples-of-deepfakes/. [Accessed: Nov. 9, 2025].

[14] P. Gupta et al., "Federated Learning for Distributed Intrusion Detection," *IJRASET*, vol. 13, no. 5, May 2025.

TABLE I
COMPARATIVE SUMMARY OF KEY AI ARCHITECTURES IN CYBERSECURITY

Ref.	**Core Technology**	**Primary Application**	**Key Dataset(s)**	**Key Contribution/Result**
[10]	Hybrid GNN-LSTM	Intrusion Detection	UNSW-NB15	97.5% Acc., high interpretability via attention.
[9]	Heterogeneous GNNs	Anomaly Detection	Multiple (survey)	Taxonomy of node, edge, subgraph anomalies.
[11]	Hierarchical GNNs	Multi-modal Analysis	Custom Village Data	Efficient fusion of image, text, and scalar data.
[6]	AutoML (TPOT) + SHAP	DoS Detection	CICIDS2017	Automated pipeline selection with explainability.
[8]	LLM + RAG	Threat Intelligence	CVE/CWE Data	Dynamic adaptation to new vulnerabilities.
[7]	Ensemble + Fine-tuned LLM	Scam Detection	Custom Adversarial	90% Acc. vs adversarial text perturbations.