

# HIGH DENSITY 1U 48 PORT PATCH PANEL

High density patch panel from Norden exceeds TIA and ISO component specifications, supporting network convergence protocols, delivering maximum bandwidth and extended reliability for all LAN multimedia, and Power over Ethernet applications. Each port in front of the panel is numbered and has a designated label area for clear port identification. Keystone outlets can be snapped in to the 19" frame without the need for tooling of any type.

The tool-less jack termination offers fast and reliable installation of unshielded & shielded cable, quick and easy in termination. A rear cable management bar is supplied which acts as a stress reliever of terminated cables. All performance parameters, including NEXT, FEXT Attenuation and Return Loss are designed to meet the Cabling standard. 19" 1U 48 port patch panel comes with mini cable ties, cage nuts and rear cable as standard.



## COMPLIANCE

EIA-310-D, ISO/IEC 11801:2011  
ISO/IEC 11281:2002  
IEC 60603-7-51:2010, IEC 60603-7-4.5:2010  
EN 50173-2: 2007  
ANSI / TIA-568-C.2:2009

## DESIGN & MATERIALS

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| Panel Type               | Flat                                                      |
| Panel Style              | Unloaded                                                  |
| Mounting Style           | Tool Less (Module)                                        |
| Panel Width              | 483mm (19")                                               |
| Panel Height             | 44mm (1.75")                                              |
| Panel Depth              | 125mm                                                     |
| Outlet Style             | Unkeyed RJ-45                                             |
| Outlets                  | 48 Ports                                                  |
| Angle                    | 90 Degree                                                 |
| Connector Module Holder  | High Impact, Flame-Retardant Plastic Compound, UL 94 V-0. |
| Cover Color and Material | Black or White, Powder Coated Steel                       |

## STANDARDS

|                     |                                             |
|---------------------|---------------------------------------------|
| Wiring Standards    | EIA/TIA 568 A/B                             |
| Flammability rating | UL 94V-0                                    |
| Safety Rating       | UL1863                                      |
| Transmission        | ISO/IEC 11801:2002 ANSI /TIA/EIA-568.B.2-10 |

## ORDERING INFORMATION

| Part Number   | Description                                    |
|---------------|------------------------------------------------|
| 121-33T09048L | Cat 6 High Density UTP Patch Panel 1U 48 Port  |
| 121-34T09048L | Cat 6 High Density STP Patch Panel 1U 48 Port  |
| 121-43T09048L | Cat 6A High Density UTP Patch Panel 1U 48 Port |
| 121-44T09048L | Cat 6A High Density STP Patch Panel 1U 48 Port |