

PRODUCT SPECIFICATIONS

LUMISPLIT 2.10 / LUMISPLIT 1.6

Description: Technical specifications LumiSplit 2.10 / 1.6 v1.0.1

MADE IN BELGIUM

Luminex reserves the right to modify the technical specifications at any given time without prior notice.
No rights can be claimed from these specifications.

TECHNICAL SPECIFICATIONS

LUMISPLIT 2.10		LUMISPLIT 1.6	
			
CONNECTIVITY DMX INPUT			
	4 x Neutrik 5 pin XLR (male) (2 at the front, 2 at the rear)	1 x Neutrik 5 pin XLR (male) DMX OUTPUT	
	10 x Neutrik 5 pin XLR (female)	1 x Neutrik 5 pin XLR (female) for thru connectivity	
POWER			
	1 x Neutrik PowerCON TRUE1 In/Out	1 x Neutrik PowerCON TRUE1 In/Out	
DMX/RDM FEATURES			
Supported protocols	DMX512 (1986 & 1990), DMX512-A, RDM ANSI E1.20		
RDM discoverable	Yes		
RDM filter per input	Yes, through input button		
RDM filter per output	Yes, available through the front panel and RDM	Yes, available through RDM	
DMX backup mode	Yes**	No	
HTP/LTP merger	Yes**	No	
Regeneration mode	Yes, available through the front panel and RDM**	Yes, available through RDM**	
Dark mode	Yes, available through the front panel and RDM**	Yes, available through RDM**	
DMX zone selection	Selection of the DMX zone per output	No	
User presets	2, can be saved and recalled from the front panel*	2, available through RDM**	
DMX port isolation	Optic and galvanic isolation per port (except THRU)		
Short circuit protection	Yes		
Terminated outputs	Yes		
STATUS REPORT			
Power	1 x RGB LED on the front panel		
DMX input	2 x RGB LED on the front panel	1 x RGB LED on the front panel	
Lockable front panel	Yes		
POWER			
Power input	100 – 240V AC; 16A; 50-60Hz		
Power output	MAX 15A		
Power consumption	Max15W		
Fuse	No user-serviceable fuse		

TECHNICAL SPECIFICATIONS

LUMISPLIT 2.10		LUMISPLIT 1.6	
			
PHYSICAL DIMENSION (WDXH)			
482 x 204.85 x 44 mm		303 x 210 x 44 mm (with ears: 482 x 210 x 44 mm)	
WEIGHT			
2,54 kg		2,38 kg	
PACKAGING (WDXXH)			
530 x 330 x 80 mm			
ENVIRONMENTAL			
Operating temperature	0 to 50°C		
Storage temperature	-10 to 70°C		
Humidity	5 to 95%		
APPROVALS CERTIFICATIONS			
		CE, RoHS Compliance, FCC Part 15*, CFR 47*, Class A*	
STANDARDS			
		UL 60950-1* CAN/CSA-C22.2 No.60950-1* CAN/ICES-003(A)* IEC 60950-1* EN 60950-1 EN55022 (CISPR22) EN55024 (CISPR24)	

LUMISPLIT 2.10



LUMISPLIT 1.6

