

## 深圳市鼎科实业有限公司

## SHENZHEN TOP-TECH INDUSTRIAL CO.,LTD.

## 研发新项目申请表


报告号:

项目名称: TM	IQQ <b>9</b> V/_}			主芯片方案	: TSUMV59	XU	
项目申请人:	胀立芳			项目申请时	间: 2013-2-1	18	
了 公版 ·	▼ 客户定制板	客户名称:_	U004	项目编号:			
市场现状分析。	及针对市场:按照 [						
	2				•	e de	,
					·		
板卡分类	▼TV板	□ PC 板	其他				ā
	VGA		DVI		₩ HDMI	1路	
	PC AUDIO -		YPBPR		<b>▼</b> AV	2路	y
	同轴/光纤		▼ TV	,	CI _		
功能端子要	SCART		AVOUT		<b>工</b> 耳机	·	
求	LINE OUT		√内置DVD,	用HDMZ的	内置安卓	<u> </u>	
	VSB	<u> </u>	一功放2:	*8 <u>₩</u>			
	│ <b>▽</b> 电源接口 <u>1</u>	2V+5V+5VP+5	5VS+STB				
	其他						
结构要求	请与之前做的 TM	MQQ8 结构及	发 I/O 一致				
其他要求	2. 必须能支持 1: 3. 需要外接 HDI 4. 需要支持蓝光 5. 客户要求使用 6. 需要使用客户	5.6 寸以上的 MIITO4 小板 : DVD, 3D, 更好的功放 !的专用遥控 :制板能支持	IC,声音输出具体 器;	屏; QQ8 一样; POWER ON 与 本要求请见附件	2013	<b>中加量2%</b> 10k( <sup>)</sup> F 功能需要分开控制 SUMV39LE, TSUM	<b>制)</b>
各部门审核 及建议	业务部 13/2 一位 2013.	0218	研发部	2	测试部	The Design of	N.
最终审核:	,						

Allow Audio Out From Earphone Output Keep Same Level Output To Speaker But Cut Off Audio Out To Speakers At 150HZ


Only Allow 150HZ & Up To The Speakers In The TV

Use 8W Output Power From Amplifier IC



2. Green


Frequency As Speaker Out Allow Audio Out From Earphone Output Keep Same Level &



1. RED Button

**Buttons To USE** 

## Side Elevation of MST182VG V8.0



Below you will find the detailed feature

CHIPSET	MST6M182VG		
MARKET AREA	Asia		
	English Chinese (Fre	English Chinese (French Spanish Polish Portuguese Italian German, Duto 1	Management of the Control
CON LANGUAGE	h,Russian)(Option)		
		VIDEO SYSTEM PAL/SECAM, NTSC (Option)	
*	7	SOUND SYSTEM BG, DK, I, M	
		RECEIVE CHANNEL   ATV:200	
	CVBS	1.0Vp-p +/-5%	
	YPbPr / YCbCr	4801, 480p, 5761, 576p, 720p, 1080i, 1080p	

POWER

supply

5V,12V

12V Input

Low power consumable mode: standby <0.5W

5V,5VS,12V

Build-in power

Format Color

480i、480p、576i、576p、720p、1080i、1080p Format Up to 1920\*1080@60HZ

480i, 480p, 576i, 576p, 720p, 1080i, 1080p

When Connect Audio Out & TV Speakers. **Come From Both Audio Output Sound Must** When Turn Off TV Audio **Any Popping Noise Output Must Not Make** 

RESOLUTIONS

FULL HD panel interface

Support up to 10-bit dual LVDS

CH-, CH+, MENU, VOL-, VOL+, SOURCE, ON/OFF

140


2\*8 W @ 80


FUNCTION **EXPANSION AUDIO INPUT** 

> AV Audio Input PC-RGB Manage DC Adapter To panel

YES 8

COMB FILTER AUDIO OUTPUT





Suggestion: Use Better amplifier IC Like ST Brand To Improve Audio Output quality To Speakers

If Customer Wants To Only Use
Earphone Output Without The TV
Speakers He Must Select
Earphone Out In the Menu Under
Sound Settings


## Function Name On OSD: Sansui Super Sound 4

To Speaker But Cut Off Audio Out To Speakers At 220HZ Allow Audio Out From Earphone Output Keep Same Level Output

Only Allow 200HZ & Up To The Speakers In The TV

**Boost Treble Output By 25%** 

Use 10W Output Power From Amplifier IC



4. Blue


## Function Name On OSD: Sansui Super Sound 3

Allow Audio Out From Earphone Output Keep Same Level Output To Speaker But Cut Off Audio Out To Speakers At 200HZ

Only Allow 200HZ & Up To The Speakers In The TV

**Boost Treble Output By 20%** 

Use 10W Output Power From Amplifier IC



# VISIONARY EXCELLENCE



15.497