



---

# Indexing 2

**Instructor: Beom Heyn Kim**

[beomheyunkim@hanyang.ac.kr](mailto:beomheyunkim@hanyang.ac.kr)

Department of Computer Science

---



# Overview

---

- B+-Tree Index Files I
- Assignments




# B+-Tree Index Files

---

- Disadvantage of index-sequential files
  - Performance degrades as file grows (overflow blocks)
  - Periodic reorganization of entire file is required
- Advantage of B<sup>+</sup>-tree index files:
  - Automatically reorganizes itself with small, local, changes, in the face of insertions and deletions.
  - Reorganization of the entire file is not required to maintain performance.
- (Minor) disadvantage of B<sup>+</sup>-trees:
  - Extra insertion and deletion overhead for performance, and extra space overhead.
- Advantages of B<sup>+</sup>-trees outweigh disadvantages
  - B<sup>+</sup>-trees are used extensively



# Example of B+-Tree





# B+-Tree Index Files (Cont.)

---

A B<sup>+</sup>-tree is a rooted tree satisfying the following properties:

- All paths from root to leaf are of the same length (balanced tree)
- Each node that is not a root or a leaf has between  $\lceil n/2 \rceil$  and  $n$  children.
- A leaf node has between  $\lceil (n-1)/2 \rceil$  and  $n-1$  values
- Special cases:
  - If the root is not a leaf, it has at least 2 children.
  - If the root is a leaf (that is, there are no other nodes in the tree), it can have between 0 and  $(n-1)$  values.



# B+-Tree Node Structure

- Typical node

$P_1$	$K_1$	$P_2$	$\dots$	$P_{n-1}$	$K_{n-1}$	$P_n$
-------	-------	-------	---------	-----------	-----------	-------

- $K_i$  are the search-key values
  - $P_i$  are pointers to children (for non-leaf nodes) or pointers to records or buckets of records (for leaf nodes).
- The search-keys in a node are ordered

$$K_1 < K_2 < K_3 < \dots < K_{n-1}$$


(Initially assume no duplicate keys, address duplicates later)



# Leaf Nodes in B+-Trees

Properties of a leaf node:

- For  $i = 1, 2, \dots, n-1$ , pointer  $P_i$  points to a file record with search-key value  $K_i$ ,
- If  $L_i, L_j$  are leaf nodes and  $i < j$ ,  $L_i$ 's search-key values are less than or equal to  $L_j$ 's search-key values
- $P_n$  points to next leaf node in search-key order (for efficient sequential processing of the file)





# Non-leaf Nodes in B+-Trees

- Non-leaf nodes form a multi-level sparse index on the leaf nodes. For a non-leaf node with  $m$  pointers:
  - All the search-keys in the subtree to which  $P_1$  points are less than  $K_1$
  - For  $2 \leq i \leq n - 1$ , all the search-keys in the subtree to which  $P_i$  points have values greater than or equal to  $K_{i-1}$  and less than  $K_i$
  - All the search-keys in the subtree to which  $P_n$  points have values greater than or equal to  $K_{n-1}$
  - General structure




The number of pointers (i.e.  $n$ ) in a node is called the fanout of the node





# Example of B+-Tree

- B<sup>+</sup>-tree for *instructor* file ( $n = 6$ )



- Leaf nodes must have between 3 and 5 values ( $\lceil (n-1)/2 \rceil$  and  $n-1$ , with  $n = 6$ ).
- Non-leaf nodes other than root must have between 3 and 6 children ( $\lceil n/2 \rceil$  and  $n$  with  $n = 6$ ).
- Root must have at least 2 children.



# Observations about B<sup>+</sup>-trees

- Since the inter-node connections are done by pointers, “logically” close blocks need not be “physically” close.
- The non-leaf levels of the B<sup>+</sup>-tree form a hierarchy of sparse indices.
- The B<sup>+</sup>-tree contains a relatively small number of levels
  - Level below root has at least  $2 * \lceil n/2 \rceil$  values
  - Next level has at least  $2 * \lceil n/2 \rceil * \lceil n/2 \rceil$  values
  - .. etc.
  - If there are  $K$  search-key values in the file, the tree height is no more than  $\lceil \log_{\lceil n/2 \rceil}(K) \rceil$
  - thus searches can be conducted efficiently.
- Insertions and deletions to the main file can be handled efficiently, as the index can be restructured in logarithmic time (as we shall see).



# Overview

---

- B+-Tree Index Files I
- Assignments



# Assignments

---

- Reading: Ch14.3.1



---

**The End**

---