



WCAG 2.1 Level AA Success Criteria

COMPLIANCE AUDIT

For github.com/kimbug29/sewbugtips.git | Verdict: Semi-compliant

accessiBe is the web accessibility **market leader**, powering the accessibility of **tens-of-thousands** of websites, from **small businesses** to industry-leading **enterprises**.

This audit evaluates the adherence level of **github.com/kimbug29/sewbugtips.git** as of Mon Nov 22 2021, to the "Web Content Accessibility Guidelines" (WCAG) 2.1 level AA success criteria.

Below you'll find the results for dozens of tests that focus mainly on 3 categories: **screen-reader** adjustments (for blind users), **keyboard navigation** adjustments (for the motor impaired) and **UI, design, and readability** adjustments (for the vision impaired).

This audit is subjected to the [terms of service](#)

#	Requirement	Relevant	Successes	Failures	Score
1	Interactive elements such as links, buttons and form fields should all be navigable using the keyboard by either using a focusable element (a, button, input, etc.) or including the "tabindex" attribute that equals to "0".	No	0	5	-

Code snapshots of some failed elements

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Why GitHub? <svg x="0" y="0" viewBox="0 0 14 8" xml:space="preserve" fill="none" class="icon-chevron-down-mktg position-absolute...
```

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Explore <svg x="0" y="0" viewBox="0 0 14 8" xml:space="preserve" fill="none" class="icon-chevron-down-mktg position-absolute pos...
```

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Pricing <svg x="0" y="0" viewBox="0 0 14 8" xml:space="preserve" fill="none" class="icon-chevron-down-mktg position-absolute pos...
```

```
<summary class="btn css-truncate" data-hotkey="w" title="Switch branches or tags" > <svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-git-branch"> <path fill-r...
```

```
<summary data-hydro-click="{&quot;event_type&quot;:&quot;repository.click&quot;,&quot;payload&quot;:{&quot;repository_id&quot;:412962477,&quot;target&quot;:&quot;CLONE_OR_DOWNLOAD_BUTTON&quot;,&quot;originating_url&quot;:&quot;https://github.com/kimb...
```

2	Interactive elements that can be navigated using the keyboard should be surrounded by a visual outline whenever they are focused.	Yes	Pass	-	100%
3	Active popups should include an "aria-modal" attribute that equals to "true", and a "role" attribute that equals to "dialog", so screen-reader users know	No	0	0	-

how to navigate within it.

4	Every page should include hidden links that by clicking on them (either using keyboard navigation or a screen-reader), the user will "skip" certain blocks directly to main landmarks such as main content, menu or footer.	No	Fail	-	-
---	---	----	------	---	---

Code snapshots of some failed elements

```
<a class="lh-condensed-ultra d-block no-underline Bump-link--hover position-relative Link--secondary py-2" data-hydro-click="{&quot;event_type&quot;:&quot;analytics.event&quot;,&quot;payload&quot;:{&quot;category&quot;:&quot;Header dropdown (logged o...
```

5	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should be wrapped inside an element with an "aria-hidden" attribute that equals to "false", or include it directly, and have it dynamically changed to "true" when they become visible.	No	0	0	-
6	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should include a "tabindex" attribute that is below 0, and have it dynamically changed to 0 when they become visible.	No	0	0	-
7	Tables that are being used as layout structures should include a "role" attribute that equals to "presentation" to indicate to screen-readers that it is not really a table.	No	0	0	-
8	If nested tables are used (a table element within a table cell), set the nested tables "role" attribute to "presentation".	No	0	0	-

9	Tables that are missing a THEAD row with TH elements, should include a "role" attribute that equals to "rowheader" on the TD elements of the TR that represents the visual table headings.	No	0	0	-
10	Menus should either be built using the HTML5 "nav" element or include a "role" attribute that equals to "menu" or "navigation" to indicate a navigation landmark for screen-readers.	Yes	2	0	100%

Code snapshots of some successful elements

```
<nav class="mt-0 px-3 px-lg-0 mb-5 mb-lg-0" aria-label="Global"> <ul class="d-lg-flex li
st-style-none" > <li class="mr-0 mr-lg-3 position-relative flex-wrap flex-justify-between fl
ex-items-center border-bottom border-lg-bottom...
```

```
<nav data-pjax="#js-repo-pjax-container" aria-label="Repository" data-view-component
="true" class="js-repo-nav js-sidenav-container-pjax js-responsive-underlinenav overflow
-hidden UnderlineNav px-3 px-md-4 px-lg-5" > <ul data-view-component="true"...
```

11	Menu items that have a dropdown menu include an "aria-haspopup" attribute that equals to "true".	No	0	3	-
----	--	----	---	---	---

Code snapshots of some failed elements

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary
class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg
-inline-block" > Why GitHub? <svg x="0" y="0" viewBox="0 0 1...
```

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary
class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg
-inline-block" > Explore <svg x="0" y="0" viewBox="0 0 14 8"...
```

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary
class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg
-inline-block" > Pricing <svg x="0" y="0" viewBox="0 0 14 8"...
```

12	Menu items that have a dropdown menu include an "aria-expanded" attribute that equals to "false" that changes to "true" and back when opening or closing the dropdown.	No	0	3	-
----	--	----	---	---	---

Code snapshots of some failed elements

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Why GitHub? <svg x="0" y="0" viewBox="0 0 1...
```

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Explore <svg x="0" y="0" viewBox="0 0 14 8"...
```

```
<details class="HeaderMenu-details details-overlay details-reset width-full"> <summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap d-block d-lg-inline-block" > Pricing <svg x="0" y="0" viewBox="0 0 14 8"...
```

13	An H1 title provides information to blind-users using screen-readers of what the main topic of the page is and each page should have exactly one H1 title.	No	Fail	-	-
----	--	----	------	---	---

Code snapshots of some failed elements

```
<h1 class=" d-flex flex-wrap flex-items-center wb-break-word f3 text-normal"> <svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-repo color-fg-muted mr-2"> <path ...
```

```
<h1 dir="auto"><a id="user-content-sewbugtips" class="anchor" aria-hidden="true" href="#sewbugtips" ><svg class="octicon octicon-link" viewBox="0 0 16 16" version="1.1" width="16" height="16" aria-hidden="true"><path fill-rule="evenodd" d="M7.775 3.2...
```

14	HTML title elements (H1-6) should	Yes	9	0	
----	-----------------------------------	-----	---	---	--

have texts. If images or links are used, they should include an alternative or screen-reader only text.

100%

15	Elements that visually appear as titles but are coded with a non-heading HTML Tag should include a "role" attribute that equals to "heading" or have their tags fixed.	No	0	0	-
16	Title levels should not be skipped and should be built with consistent hierarchy. For example: you cannot have "h4" titles and "h2" titles without having "h3" titles.	Yes	Pass	-	100%
17	Visually deleted texts (often used to show a previous price of a sale) should include an "aria-label" attribute or a screen-reader only text that explains this is deleted text.	No	0	0	-
18	Breadcrumbs main element should include a "role" attribute that equals to "navigation" and an "aria-label" attribute that describes the functionality."	No	0	0	-
19	Ratings/scores that are represented visually using stars, meters or other indicators should either have an "aria-label" attribute or a screen-reader only texts conveying the score/rate.	No	0	0	-
20	Making use of an accessibility interface helps to ensure that vision impaired users can adjust some of the UI and the design (font-size, colors, spacing, etc.) to their needs. It is not a compliance requirement, but can help to improve compliance.	No	0	0	-

21	Iframe elements should include a "title" or an "aria-label" attribute explaining the purpose, the functionality or the destination of the iframe, or be tagged hidden for screen-readers if irrelevant.	No	0	0	-
22	Elements that behave as buttons but are built using other tags such as span, div, a or others, should include a "role" attribute that equals to "button".	No	0	0	-
23	Buttons should include text explaining their functionality, and if icons are used as buttons, a screen-reader only text or an "aria-label" attribute should be used for that description.	No	0	0	-
24	Links should include text that is setting expectations to what page they are leading to. If empty links are used as layout wrapping elements, a screen-reader only text or an "aria-label" attribute should be used for that description.	Yes	62	0	100%

Code snapshots of some successful elements

```
<a href="#start-of-content" class="px-2 py-4 color-bg-accent-emphasis color-text-white show-on-focus js-skip-to-content" >Skip to content</a>
```

```
<a class="mr-4 color-fg-inherit" href="https://github.com/" aria-label="Homepage" data-ga-click="(Logged out) Header, go to homepage, icon:logo-wordmark" > <svg height="32" aria-hidden="true" viewBox="0 0 16 16" version="1.1" width="32" data-...
```

```
<a class="HeaderMenu-link no-underline py-3 d-block d-lg-inline-block" data-hydro-click="{&quot;event_type&quot;:&quot;analytics.event&quot;,&quot;payload&quot;:{&quot;category&quot;:&quot;Header menu top item (logged out)&quot;,&quot;action&quot;:&quot;...&quot;}">
```

```
<a href="/login?return_to=https%3A%2F%2Fgithub.com%2Fkimbug29%2Fsewbugtips" class="HeaderMenu-link flex-shrink-0 no-underline" data-hydro-click="{&quot;event_type&quot;:&quot;authentication.click&quot;,&quot;payload&quot;:{&quot;location_in_page&quot;:&quot;...&quot;}">
```



```
<a href="/signup?ref_cta=Sign+up&ref_loc=header+logged+out&ref_page=%2F%3Cuser-name%3E%2F%3Crepo-name%3E&source=header-repo&source_repo=KimBug29%2FSewBugTips" class="HeaderMenu-link flex-shrink-0 d-inline-block no-underline border col...
```

```
<a class="url fn" rel="author" data-hovercard-type="user" data-hovercard-url="/users/KimBug29/hovercard" data-octo-click="hovercard-link-click" data-octo-dimensions="link_type:self" href="/KimBug29" >KimBug29</a>
```

```
<a data-pjax="#repo-content-pjax-container" href="/KimBug29/SewBugTips" >SewBug Tips</a>
```

```
<a href="/login?return_to=%2FKimBug29%2FSewBugTips" rel="nofollow" data-hydro-click="{&quot;event_type&quot;:&quot;authentication.click&quot;,&quot;payload&quot;:{&quot;location_in_page&quot;:&quot;notification subscription menu watch&quot;,&quot;rep...
```

```
<a href="/login?return_to=%2FKimBug29%2FSewBugTips" rel="nofollow" data-hydro-click="{&quot;event_type&quot;:&quot;authentication.click&quot;,&quot;payload&quot;:{&quot;location_in_page&quot;:&quot;star button&quot;,&quot;repository_id&quot;:41296247...
```

```
<a class="social-count js-social-count" href="/KimBug29/SewBugTips/stargazers" aria-label="0 users starred this repository" data-singular-suffix="user starred this repository" data-plural-suffix="users starred this repository" > 0 </a>
```

25	Links that open in a new tab or a new window should either have an "aria-label" attribute or a screen-reader only element explaining to screen-readers that this opens in a new tab.	No	0	0	-
26	Carousels should include an "aria-label" attribute that equals to "carousel"/"slider" or something else that indicates the functionality, as well as be tagged as a landmark for screen-readers using a "role" tag that equals to "contentinfo".	No	0	0	-
27	Control elements such as next and previous icons should include an "aria-	No	0	0	-

label" attribute or a screen-reader only text that explains the functionality to screen-readers.

28	A common accessibility mistake is to treat carousels as live regions using the "aria-live" attribute and the "polite" or the "assertive" values. Using this practice will cause screen-readers to cut and skip announcements.	No	0	0	-
29	Carousel pagination items (usually used as small dots at the bottom of the carousel) should indicate their functionality and slide number they control using an "aria-label" and a screen-reader only text.	No	0	0	-
30	The title tag of the HEAD section (also the title that appears in the browser tab and Search Engine result pages) should exist and describe the name of the current webpage for screen-reader users.	Yes	Pass	-	100%

Code snapshots of some successful elements

```
<title>GitHub - KimBug29/SewBugTips: This site provides SEWING 101 information with i  
images, fabric terminology, and sew much more!</title>
```

31	The HTML tag should include a "lang" attribute that represents the main language of the webpage so screen-readers can calibrate on it for blind users.	Yes	Pass	-	100%
----	--	-----	------	---	------

Code snapshots of some successful elements

```
<html lang="en" data-color-mode="auto" data-light-theme="light" data-dark-theme="d  
ark"><head> <base href="https://github.com"><meta name="aceClient" content="tr  
ue"><meta name="aceToken" content="619af8bdaf8f88a135192cee"><meta name=
```

"aceWebsite" ...

32	The meta viewport tag should allow vision impaired users to pinch-zoom at least double the standard scaling using the user-scalable="yes" and maximum-scale={2 or higher} content strings.	Yes	Pass	-	100%
----	--	-----	------	---	------

Code snapshots of some successful elements

```
<meta name="viewport" content="width=device-width">
```

33	Landmarks such as main content and footer should be built using their corresponding HTML5 element or include a description using an "aria-label" attribute and a "role" tag that equals to "contentinfo" or "main". Landmarks such as search and navigation are tested in other sections.	Yes	2	1	67%
----	---	-----	---	---	-----

Code snapshots of some successful elements

```
<main id="js-repo-pjax-container" data-pjax-container=""> <div id="repository-container-header" class="pt-3 hide-full-screen mb-5" style="background-color: var(--color-page-header-bg);" data-pjax-replace=""> <div class="d...
```

Code snapshots of some failed elements

```
<div class="footer container-xl width-full p-responsive" role="contentinfo"> <div class="position-relative d-flex flex-row-reverse flex-lg-row flex-wrap flex-lg-nowrap flex-justify-center flex-lg-justify-between pt-6 pb-2 mt-6 f6 color-fg-muted bor...
```

34	Form fields should either include an "aria-label" attribute or a connected	Yes	Pass	-	100%
----	--	-----	------	---	------

LABEL element describing the requirement of the field (email, phone, name, etc.).

Code snapshots of some successful elements

```
<input type="text" class="form-control input-sm header-search-input jump-to-field js-jump-to-field js-site-search-focus js-site-search-field is-clearable" data-hotkey="s,/" name="q" data-test-selector="nav-search-input" placeholder="Search" data-unsc...
```

35	Form elements cannot have the same ID, or else their corresponding label will provide false information.	No	0	0	-
36	Required form fields should include an "aria-required" attribute that equals to "true" so blind users using screen-readers know their validation.	No	0	0	-
37	The validity status of every form element must be represented in the code at all times using the "aria-invalid" attributes and the "true/false" values, and change dynamically when the status changes.	No	0	0	-
38	aria-describedby and aria-labeledby attributes should be connected by ID to an element that either has text description or an "aria-label" attribute.	Yes	Pass	-	100%

Code snapshots of some successful elements

```
<div role="grid" aria-labelledby="files" class="Details-content--hidden-not-important js-navigation-container js-active-navigation-container d-md-block" data-pjax=""> <div class="sr-only" role="row" > <div role="columnheader">Type</div>...
```

39	All forms should have a submission button that is built as an input type	No	Fail	-	-
----	--	----	------	---	---

"submit" or a "button" element, or include a "role" tag that equals to "button". Buttons can be hidden if the form can be submitted using the Enter key.

Code snapshots of some failed elements

```
<form class="js-site-search-form" role="search" aria-label="Site" data-scope-type="Repository" data-scope-id="412962477" data-scoped-search-url="/KimBug29/SewBugTips/search" data-owner-scoped-search-url="/users/KimBug29/search" data-unscoped-search-U...
```

40	Search forms should include a "role" tag that equals to "search" (or be wrapped by one) to indicate a search landmark for screen-readers.	Yes	Pass	-	100%
----	---	-----	------	---	------

Code snapshots of some successful elements

```
<form class="js-site-search-form" role="search" aria-label="Site" data-scope-type="Repository" data-scope-id="412962477" data-scoped-search-url="/KimBug29/SewBugTips/search" data-owner-scoped-search-url="/users/KimBug29/search" data-unscoped-search-U...
```

41	Font sizes should be at least 11px in size in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.	Yes	Pass	-	100%
----	---	-----	------	---	------

42	Letter spacing should not be set to below -1px in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.	Yes	Pass	-	100%
----	---	-----	------	---	------

43	Elements that have texts should meet a minimum contrast ratio of 4.5:1	Yes	83	30	73%
----	--	-----	----	----	-----

between their foreground (usually text color) and background color.

Code snapshots of some successful elements

```
<a href="#start-of-content" class="px-2 py-4 color-bg-accent-emphasis color-text-white
show-on-focus js-skip-to-content" >Skip to content</a>
```

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap
d-block d-lg-inline-block" > Why GitHub? <svg x="0" y="0" viewBox="0 0 14 8" xml:spa
ce="preserve" fill="none" class="icon-chevon-down-mktg position-absolute...
```

```
<a class="HeaderMenu-link no-underline py-3 d-block d-lg-inline-block" data-hydro-click="{"event_type":"analytics.event","payload":{"category":"Header menu top item (logged out)","action":&#x2026;
```

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap
d-block d-lg-inline-block" > Explore <svg x="0" y="0" viewBox="0 0 14 8" xml:space="
preserve" fill="none" class="icon-chevron-down-mktg position-absolute pos...
```

```
<summary class="HeaderMenu-summary HeaderMenu-link px-0 py-3 border-0 no-wrap
d-block d-lg-inline-block" > Pricing <svg x="0" y="0" viewBox="0 0 14 8" xml:space="p
reserve" fill="none" class="icon-chevон-down-mktg position-absolute pos...
```

```
<a href="/login?return_to=https%3A%2F%2Fgithub.com%2Fkimbug29%2Fsewbugtips"
class="HeaderMenu-link flex-shrink-0 no-underline" data-hydro-click="{&quot;event_type&quot;:&quot;authentication.click&quot;,&quot;payload&quot;:{&quot;location_in_page&quot;...
```

```
<a href="/signup?ref_cta=Sign+up&ref_loc=header+logged+out&ref_page=%2F%3Cuser-name%3E%2F%3Crepo-name%3E&source=header-repo&source_repo=KimBug29%2FSewBugTips" class="HeaderMenu-link flex-shrink-0 d-inline-block no-underline border col...
```

```
<a class="url fn" rel="author" data-hovercard-type="user" data-hovercard-url="/users/KimBug29/hovercard" data-octo-click="hovercard-link-click" data-octo-dimensions="link_type:self" href="/KimBug29" >KimBug29</a>
```

/

```
<a data-pjax="#repo-content-pjax-container" href="/KimBug29/SewBugTips" >SewBug  
Tips</a>
```

Code snapshots of some failed elements

```
<strong>1</strong>
```

```
<span class="color-fg-muted">branch</span>
```

```
<strong>0</strong>
```

```
<span class="color-fg-muted">tags</span>
```

```
<summary data-hydro-click="{&quot;event_type&quot;:&quot;repository.click&quot;,&quot;payload&quot;:{&quot;repository_id&quot;:412962477,&quot;target&quot;:&quot;CLONE_OR_DOWNLOAD_BUTTON&quot;,&quot;originating_url&quot;:&quot;https://github.com/kimb...
```

```
<h2 class="mb-3 h4">About</h2>
```

```
<p class="f4 mt-3"> This site provides SEWING 101 information with images, fabric terminology, and sew much more! </p>
```

```
<a class="Link--muted" href="#readme" > <svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-book mr-2" > <path fill-rule="evenodd" d="M0 1.75A.75.75 0 01.75 1h4...
```

```
<a href="/KimBug29/SewBugTips/blob/master/LICENSE" class="Link--muted" > <svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-law mr-2" > <path fill-rule="evenodd...
```

```
<a href="/KimBug29/SewBugTips/releases" data-view-component="true" class="Link--primary no-underline" > Releases </a>
```

45	Background images that are not just for decoration purposes and should have the same treatment as standard images and include a "role" attribute that equals to "img" and an alternative text description in an "aria-label" attribute.	No	0	0	-
46	Font icons, SVG or images that are being used as spacers, decorations or their purpose is already described by the content should include a "role" attribute that equals to "presentation" or "none".	Yes	47	5	90%

Code snapshots of some successful elements

```
<svg height="32" aria-hidden="true" viewBox="0 0 16 16" version="1.1" width="32" data-view-component="true" class="octicon octicon-mark-github" > <path fill-rule="evenodd" d="M8 0C3.58 0 0 3.58 0 8c0 3.54 2.29 6.53 5.47 7.59.407.55.175.55-.38 0...
```

```
<svg aria-hidden="true" height="24" viewBox="0 0 16 16" version="1.1" width="24" data-view-component="true" class="octicon octicon-three-bars" > <path fill-rule="evenodd" d="M1 2.75A.75.75 0 011.75 2h12.5a.75.75 0 10 1.5H1.75A.75.75 0 011 2.75zm...
```

```
<svg aria-hidden="true" height="24" viewBox="0 0 24 24" version="1.1" width="24" data-view-component="true" class="octicon octicon-x color-fg-muted" > <path fill-rule="evenodd" d="M5.72 5.72a.75.75 0 011.06 0L12 10.94l5.22-5.22a.75.75 0 111.06 1....
```

```
<svg x="0" y="0" viewBox="0 0 14 8" xml:space="preserve" fill="none" class="icon-chevron-down-mktg position-absolute position-lg-relative" ><path d="M1,1l6.2,6L13,1" ></path></svg>
```

```
<svg xmlns="http://www.w3.org/2000/svg" width="22" height="20" aria-hidden="true" class="mr-1 header-search-key-slash" ><path fill="none" stroke="#979A9C" opacity=".4" d="M3.55h12c1.7 0 3 1.3 3 3v13c0 1.7-1.3 3-3 3h-12c-1.7 0-3-1.3-3-3v-13c0-1.7 1.3...
```

```
<svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-repo color-fg-muted mr-2" > <path fill-rule="evenodd" d="M2 2.5A2.5 2.5 0 014.5 0h8.75a.75.75 0 01.75.75v12.5a.75.75...
```

```
<span ></span>
```



```
<svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-bell" > <path d="M8 16a2 2 0 01.9 85-1.75c.017-.137-.097-.25-.235-.25h-3.5c-.138 0-.252.113-.235.25A2 2 0 008 16z" ...
```

```
<svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-star v-align-text-bottom mr-1" > <path fill-rule="evenodd" d="M8 .25a.75.75 0 01.673.418l1.882 3.815 4.216 12a.75.75...
```

```
<svg aria-hidden="true" height="16" viewBox="0 0 16 16" version="1.1" width="16" data-view-component="true" class="octicon octicon-repo-forked" > <path fill-rule="evenodd" d="M5 3.25a.75.75 0 11-1.5 0 .75.75 0 011.5 0zm0 2.122a2.25 2.25 0 10-1.5 ...
```

Code snapshots of some failed elements

```
<span data-view-component="true" class="progress-pjax-loader js-pjax-loader-bar Progress position-fixed width-full" > <span style="width: 0%;" data-view-component="true" class="Progress-item progress-pjax-loader-bar color-bg-info-inverse" ></span...
```

```
<span style="width: 0%;" data-view-component="true" class="Progress-item progress-pjax-loader-bar color-bg-info-inverse" ></span>
```

```
<span class="dropdown-caret"></span>
```

```
<svg style="box-sizing: content-box; color: var(--color-icon-primary);" width="32" height="32" viewBox="0 0 16 16" fill="none" data-view-component="true" class="anim-rotate" > <circle cx="8" cy="8" r="7" stroke="currentColor" stroke-opacity="0.25...
```

47	Figure elements that are used to display images should have a "role" attribute that equals to "none" and the image provide itself should provide the description using an "alt" attribute.	No	0	0	-
48	Every "area" element of a "map" tag should be regarded as a standard image and receive an alternative text description using an "alt" attribute.	No	0	0	-

49	Small or hidden tracker pixel images (often used for analytics or marketing purposes) should include a "role" attribute that equals to "none" or "presentation" so they are excluded from screen-readers.	No	0	0	-
----	---	----	---	---	---