



Calibration Certificate / Kalibrierschein

Issued by the calibration laboratory / Erstellt durch das Kalibrierlaboratorium

ProfEC Ventus GmbH

Member of / Mitglied im

Deutschen Kalibrierdienst

accredited to / akkreditiert nach **DIN EN ISO/IEC 17025:2018**

Object

Gegenstand

Manufacturer Adolf Thies GmbH & Co. KG

Hersteller D-37083 Göttingen

Germany

Cup Anemometer

4.3351.10.000 Type

Тур

Serial Number 09244802 / -

Fabrikat/Serien-Nr.

Customer SerFac

Jeollanam-do Auftraggeber

Republic of Korea

3153-2024 Order No.

Auftragsnummer

Numer of pages 6

Anzahl der Seiten

Date of Calibration 13.09.2024

Datum der Kalibrierung

This calibration certificate may not be reproduced other than in full except with the permission of the issuing laboratory. Calibration certificates without signature are not valid.

Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Auszüge oder Änderungen bedürfen der Genehmigung des ausstellenden Kalibrierlaboratoriums. Kalibrierscheine ohne Unterschrift haben keine Gültigkeit.

Date Approval of the certificate of calibration by Datum Freigabe des Kalibrierscheins durch

14.10.2024







26228 D-K-19142-01-00 09/2024

Calibration Mark Kalibrierzeichen

This calibration certificate documents the metrological traceability to national standards, which realize the units of measurement according to the International System of Units (SI). The DAkkS is signatory to the multilateral agreements of the European cooperation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates. The user is obliged to have the object recalibrated at

appropriate intervals. Dieser Kalibrierschein dokumentiert die metrologische Rückführung auf nationale Normale zur Darstellung der Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Die DAkkS ist Unterzeichner der multilateralen Übereinkommen der European co-operation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Ka-

librierscheine. Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der

Benutzer verantwortlich.





26228

D-K-

19142-01-00

09/2024

Object Cup Anemometer

Kalibriergegenstand

Calibration procedure ISO / IEC 61400-50-1: 2022, Chapter 8

Kalibrierverfahren

Place of calibration Wind Tunnel Center (MEASNET) at Carl von Ossietzky University, Oldenburg

Ort der Kalibrierung

Test Conditions Wind tunnel area / 8000 cm²

Messbedingungen Wind Tunnel Querschnittsfläche ¹

Anemometer frontal area / 274 cm²

Anenometer Querschnittsfläche ²

Diameter of mounting pipe / 33.7 mm

Durchmesser des Montagerohrs ³

Blockage ratio of tested object / 0.034 [-]

Vorstauverhältnis des Prüflings ⁴

Software Version / CAC Prog v2.1

Auswertesoftware

Ambient Conditions Air temperature / 23.1 °C \pm 0.2 K

Umgebungsbedingungen Luft Temperatur

Air pressure / 1022.8 hPa \pm 0.3 hPa

Luftdruck

Relative air humidity / 52.8 % \pm 1.7 %

Relative Luftfeuchtigkeit

Remarks none

Anmerkungen

Revision 0

Revision

This calibration certificate has been generated electronically and signed manually.

Dieser Kalibrierschein wurde elektronisch erzeugt und manuell signiert.





¹Nozzle cross-section area of the tested object incl. mounting pipe / Querschnitt der Auslassdüse des Windkanals

²Projected cross-section area of the tested object incl. mounting pipe / Querschnittsfläche (Schattenwurf) des Prüflings inkl. Montagerohr

³Diameter of mounting pipe / Durchmesser des Montagerohrs

 $^{^4}$ Ratio 2 to 1 /Verhältnis von 2 zu 1

26228 D-K-19142-01-00 09/2024

Calibration Result 5

Kalibrierergebnis

File: 26228

| Wind Speed Wind Tunnel | Measurement Sensor | Extended Uncertainty* (k=2) | |
|-------------------------------|--------------------|------------------------------------|--|
| Windgeschwindigkeit Windkanal | Messung Prüfling | Erweiterte Messunsicherheit* (k=2) | |
| m/s | Hz | m/s | |
| 3.911 | 80.433 | 0.10 | |
| 5.833 | 122.000 | 0.10 | |
| 7.779 | 164.767 | 0.10 | |
| 9.757 | 207.733 | 0.10 | |
| 11.725 | 250.967 | 0.10 | |
| 13.740 | 294.700 | 0.10 | |
| 15.672 | 337.700 | 0.10 | |
| 14.704 | 316.167 | 0.10 | |
| 12.738 | 273.167 | 0.10 | |
| 10.750 | 229.833 | 0.10 | |
| 8.769 | 186.633 | 0.10 | |
| 6.796 | 142.967 | 0.10 | |
| 4.861 | 101.233 | 0.10 | |

Remark:

Vermerk:

DAkkS is signatory to the multilateral agreements of the European co-operation for Accreditation (EA) and of the International Laboratory Accreditation Cooperation (ILAC) for the mutual recognition of calibration certificates.





^{*} The extended uncertainty assigned to the measurement results is obtained by multiplying the standard uncertainty by the coverage factor k=2. It has been determined in accordance with EA-4/02 M: 2022. The value of the measured value lies within the assigned range of values with a probability of 95%.

^{*}Angegeben ist die erweiterte Messunsicherheit, die sich aus der Standardmessunsicherheit durch Multiplikation mit dem Erweiterungsfaktor k=2 ergibt. Sie wurde gemäß EA-4/02 M: 2022 ermittelt. Der Wert der Messgröße liegt mit einer Wahrscheinlichkeit von 95% im zugeordneten Wertintervall. Die Deutsche Akkreditierungsstelle GmbH ist Unterzeichnerin der multilateralen Übereinkommen der European cooperation for Accreditation (EA) und der International Laboratory Accreditation Cooperation (ILAC) zur gegenseitigen Anerkennung der Kalibrierscheine.

⁵Calibration results only count for the tested circumstances, the tested sensor and environmental conditions during which calibration took place.

Annex

Detailed Calibration Results

DAkkS calibration no. 26228

Test object Cup Anemometer

Manufacturer / Type Adolf Thies GmbH & Co. KG / 4.3351.10.000

Body serial number ⁶ 09244802

Cup serial number

Date of calibration 13.09.2024

Ambient conditions

Air temperature 23.1 °C
Air pressure 1022.8 hPa
Humidity 52.8 %




Range of regression 4 m/s – 16 m/s

Slope $0.04574 \text{ (m/s)/(Hz)} \pm 0.00004 \text{ (m/s)/(Hz)}$

Offset $0.2421 \text{ m/s} \pm 0.0093 \text{ m/s}$

Standard error y 0.012 m/s Correlation coefficient 0.999992 [-]

Remarks none



ProfEC Ventus GmbH is a Calibration Laboratory accredited by the German Accreditation Body (Deutsche Akkreditierungsstelle, DAkkS), registration: D-K-19142-01-00

ProfEC Ventus GmbH is member of MEASNET (Measuring Network of Wind Energy Institutes) and participating in the anemometer and wind vane calibration expert working group of MEASNET.

⁶Body serial number OR device serial number if only one serial number is given for the test object






Annex

Instrumentation

| Position | Sensor | Manufacturer | Туре | Calibration |
|----------|-------------------------------|---------------|------------|-------------|
| 1 | Pitot static and dynamic tube | Airflow | NPL 8 mm | 09.04.15 |
| 2 | Pitot static and dynamic tube | Airflow | NPL 8 mm | 08.04.15 |
| 3 | Pitot static and dynamic tube | Airflow | NPL 8 mm | 02.04.15 |
| 4 | Pitot static and dynamic tube | Airflow | NPL 8 mm | 10.04.15 |
| 5 | Differential Pressure | Setra | 239 | 27.07.23 |
| 6 | Differential Pressure | Setra | 239 | 27.07.23 |
| 7 | Differential Pressure | Setra | 239 | 27.07.23 |
| 8 | Differential Pressure | Setra | 239 | 27.07.23 |
| 9 | Barometer | Vaisala | PTB110 | 27.07.23 |
| 10 | Thermometer | Galltec | KRC 1/5-ME | 08.08.23 |
| 11 | Humidity sensor | Galltec | KRC 1/5-ME | 08.08.23 |
| 12 | Wind tunnel control | ProfEC Ventus | CPU 44172 | 30.01.23 |

Table1: Description of the data acquisition system

Photo of the calibration set-up



Calibration set-up of the anemometer calibration in the wind tunnel at Carl von Ossietzky University, Oldenburg⁷. The anemometer shown may differ from the calibrated one. Remark: The proportion of the set- up is not true to scale due to imaging geometry.

Compliance with IEC and MEASNET calibration procedure

The calibration procedure in all aspects is in compliance with procedure ISO / IEC 61400-50-1:2022.

The calibration procedure in all aspects is in compliance with MEASNET Anemometer Calibration Procedure - Version 3: 2020





⁷Carl-von.Ossietzky-Straße 11, 26129 Oldenburg

Annex

References

- [1] M. Hölzer, 2023 Working Instruction: Measuring Velocity of Gases for Cup Anemometer Calibration
- [2] ISO / IEC 61400-50-1 Ed.1: 2022 Wind measurement Application of meteorological mast, nacelle and spinner mounted instruments
- [3] MEASNET Anemometer Calibration Procedure Version 3: 2020
- [4] EA-4/02 M: 2022 Evaluation of the Uncertainty of Measurement In Calibration

Contact Information of Calibration Laboratory



ProfEC Ventus GmbH Marie-Curie-Str 1 26129 Oldenburg Germany

www.profec-ventus.com shop.profec-ventus.com info@profec-ventus.com

Client Contact Details

SerFac co, Ltd. c/o Ji-Hun Ban 15,Pyeonghwa-ro 140beon-gil Mokpo-si, Jeollanam-do Republic of Korea