


# Procedia

## Computer Science



**Knowledge-Based and Intelligent Information & Engineering Systems 19th Annual Conference, KES-2015, Singapore, September 2015 Proceedings**

Editors of the Volume:

Liya Ding, Charles Pang, Leong Mun Kew,  
Lakhmi C. Jain and Robert J. Howlett

## Contents

Preface	
L. Ding, C. Pang, M.-K. Leong, L.C. Jain, R.J. Howlett	1
Conversational Informatics: Toward Cultivating Wisdom from Conversational Interaction	
T. Nishida	7
Agent's Security during Communication in Mobile Agents System	
C. Zrari, H. Hachicha, K. Ghedira	17
Single-succedent System Approach to Boolean BI	
N. Kamide	27
Judging Emotion from EEGs Based on an Association Mechanism	
S. Tsuchiya, M. Morimoto, M. Imono, H. Watabe	37
KAMET II Conceptual Modeling Language, a Visual and Consistent Language Proved Using Concept Algebra	
O. Cairó, K. Poblete	45
A Simile Recognition System Using a Commonsense Sensory Association Method	
E. Yoshimura, M. Imono, S. Tsuchiya, H. Watabe	55
Selecting Start-Up Businesses in a Public Venture Capital Financing Using Fuzzy PROMETHEE	
E. Afful-Dadzie, Z.K. Oplatková, S. Nabareseh	63
From a Ranking System to a Confidence Aware Semi-Automatic Classifier	
E. Malherbe, Y. Vanrompay, M.-A. Aufaure	73
Hybrid Metaheuristics within a Holonic Multiagent Model for the Flexible Job Shop Problem	
H.E. Nouri, O.B. Driss, K. Ghédira	83
A Domain Knowledge Based Method on Active and Focused Information Service for Decision Support within Big Data Environment	
X. Jin, S. Zong, Y. Li, S. Wu, W. Yin, W. Ge	93
Generalizing Hierarchical Structure of Indices for Japanese Legal Documents	
T.T.N. Le, M. Le Nguyen, A. Shimazu	103
Personalised Learning Materials Based on Dyslexia Types: Ontological Approach	
A.Y. Alsobhi, N. Khan, H. Rahanu	113
An Iterative Projective Clustering Method	
R. Avros, Z. Frenkel, D. Toledano-Kitai, Z. Volkovich	122
EEG-based Detection of TV Commercials Effects	
T. Nomura, Y. Mitsukura	131
User Intent Estimation from Access Logs with Topic Model	
K. Uetsuji, H. Yanagimoto, M. Yoshioka	141
Pattern-based Transformation of Diagrammatic Conceptual Models for Semantic Enrichment in the Web of Data	
R.A. Buchmann, D. Karagiannis	150
Towards a Timely Root Cause Analysis for Complex Situations in Large Scale Telecommunications Networks	
M. Schaaf, G. Wilke, T. Mikkola, E. Bunn, I. Hela, H. Wache, S.G. Grivas	160
Development of Ontology for Information Literacy	
K. Hiroko, K. Kouji, H. Motohiro, H. Takaaki	170
Dynamic Objective Sampling in Many-Objective Optimization	
M.E. Breaban, A. Iftene	178
Simulation of Electrohydrodynamic Phenomenon Using Computational Intelligence Methods	
J. Wojtowicz, H. Wojtowicz, W. Wajs	188
Adaptive Global Schema Generation from Heterogeneous Metadata Schemas	
R.Z. Rebaï, F. Mnif, C.A. Zayani, I. Amous	197
Abstracting Anonymization Techniques: A Prerequisite for Selecting a Generalization Algorithm	
F.B. Fredj, N. Lammari, I. Comyn-Wattiau	206
Cognitive Network Framework for Heterogeneous Wireless Networks	
A. Al-Saadi, R. Setchi, Y. Hicks	216
Towards a Formal Model of the Lean Enterprise	
P. Masai, P. Parrend, C. Zanni-Merk	226
Personalization of Trending Tweets Using Like-Dislike Category Model	
L. Weilin, G.K. Hoon	236

Media Characteristics and Social Networks-enabled Knowledge Integration in Cooperative Work D.C. Hong, S. Liang .....	246
A Multi Objective Evolutionary Algorithm for Solving a Real Health Care Fleet Optimization Problem C. Catania, C. Zanni-Merk, F. de Bertrand de Beuvron, P. Collet .....	256
Applying Bipartite Network Approach to Scarce Data: Modeling Habitat Suitability of a Marine Mammal Species L.C. Ying, J. Labadin, W.Y. Chai, A.A. Tuen, C. Peter .....	266
A Mobile Agent View Synchronization System to Uphold a Trajectory Data Warehouse W. Oueslati, H. Hamdi, Z. Dhouioui, J. Akaichi .....	276
Control Strategies for Hybrid Vehicles in Mountainous Areas S. Brouk, M. Buey, S. Ly, M. Pedron, S. Burgalat .....	284
Development of Emotion-Weather Maps K. Misue, K. Taguchi .....	292
Extended Query Pattern Graph and Heuristics-Based SPARQL Query Planning F. Song, O. Corby .....	302
A New Heuristic for Solving the Parking Assignment Problem S. Abidi, S. Krichen, E. Alba, J.M. Molina .....	312
Leveraging User Ratings for Resource-Poor Sentiment Classification N.X. Bach, T.M. Phuong .....	322
Transfer AdaBoost SVM for Link Prediction in Newly Signed Social Networks Using Explicit and PNR Features A.-T. Nguyen-Thi, P.Q. Nguyen, T.D. Ngo, T.-A. Nguyen-Hoang .....	332
Visualization of Key Factor Relation in Clinical Pathway T. Yamashita, B. Flanagan, Y. Wakata, S. Hamai, Y. Nakashima, Y. Iwamoto, N. Nakashima, S. Hirokawa .....	342
Tracking Living Cells in Microscopic Images and Description of the Kinetics of the Cells P. Perner .....	352
A Perspective on Knowledge Based and Intelligent Systems Implementation in Industrie 4.0 C. Toro, I. Barandiaran, J. Posada .....	362
Depth Sensor Based Automatic Hand Region Extraction by Using Time-Series Curve and its Application to Japanese Finger-spelled Sign Language Recognition K. Inoue, T. Shiraishi, M. Yoshioka, H. Yanagimoto .....	371
Global Iterative Closet Point Using Nested Annealing for Initialization T.N. Linh, H. Hiroshi .....	381
Cognitive Aspects of Object Recognition – Recognition of Objects by Texture P. Perner .....	391
Towards Ontology Matching Based System through Terminological, Structural and Semantic Level A. Essayeh, M. Abed .....	403
An Approach to Detection of Tampering in Water Meters I. Monedero, F. Biscarri, J.I. Guerrero, M. Roldán, C. León .....	413
Beat Detection of Blood Vessel from SLO Eye Fundus Moving Image K. Yamada, E. Uchino, N. Suetake, R. Kawata .....	422
Human Action Recognition Based on Spectral Domain Features H. Imtiaz, U. Mahbub, G. Schaefer, S.Y. Zhu, Md. Atiqur Rahman Ahad .....	430
A Social Platform for Knowledge Gathering and Exploitation, towards the Deduction of Inter-enterprise Collaborations A. Montarnal, T. Wang, S. Trupitl, F. Bénaben, M. Laurus, J. Lamothe .....	438
Indicator Based Ant Colony Optimization for Multi-Objective Knapsack Problem I.B. Mansour, I. Alaya .....	448
Evolving and Discovering Tetris Gameplay Strategies S. Phon-Amnuaisuk .....	458
Optimization of Stego Image Retaining Secret Information Using Genetic Algorithm with 8-connected PSNR R. Roy, S. Laha .....	468
A Hierarchical Decomposition Framework for Modeling Combinatorial Optimization Problems M. Chaieb, J. Jemai, K. Mellouli .....	478
Graph-based Methods for Significant Concept Selection G. Karim, T.-K. Mouna, T. Lynda, B.J. Maher .....	488
Statistical and Semantic Approaches for Tweet Contextualization M.A. Zingla, L. Chiraz, Y. Slimani, C. Berrut .....	498
Graphical Models for Multi-Dialect Arabic Isolated Words Recognition E. Zarrouk, Y. BenAyed, F. Gargouri .....	508
Agent-based Movement Analysis and Location Prediction in Cellular Networks M. Vukovic, D. Jevtic .....	517
Influencer Events in Episode Rules: A Way to Impact the Occurrence of Events L. Fahed, A. Brun, A. Boyer .....	527

Extraction of Interlingual Documents Clusters Based on Closed Concepts Mining M. Chebel, C. Latiri, E. Gaussier .....	537
A Unified Framework for Semantic Comparison of Objects: Extension to Semantic Graph Comparison M. Harzallah, G. Berio .....	547
A Web-based Platform for Automated Diabetic Retinopathy Screening J.T. Arenas-Cavalli, S.A. Ríos, M. Pola, R. Donoso .....	557
Application of Subspace Method and Sparse Coding to Tissue Characterization of Coronary Plaque for High-Speed Classification S. Furukawa, E. Uchino, T. Azetsu, N. Suetake .....	564
Edge-based Mining of Frequent Subgraphs from Graph Streams A. Cuzzocrea, Z. Han, F. Jiang, C.K. Leung, H. Zhang .....	573
Implicit Social Networking: Discovery of Hidden Relationships, Roles and Communities among Consumers V. Podobnik, I. Lovrek .....	583
Development of a Fuzzy-based Multi-agent System for E-commerce Settings B.M. Balachandran, M. Mohammadian .....	593
A Semantic Framework for Continuous U-health Services Provisioning M. Echeverría, A. Jimenez-Molina, S.A. Ríos .....	603
Approximation to Expected Support of Frequent Itemsets in Mining Probabilistic Sets of Uncertain Data A. Cuzzocrea, C.K. Leung, R.K. MacKinnon .....	613
On Parallelization of the NIS-Apriori Algorithm for Data Mining M. Wu, H. Sakai .....	623
A Hybrid ILS-VND Based Hyper-heuristic for Permutation Flowshop Scheduling Problem H. Yahyaoui, S. Krichen, B. Derbel, E.-G. Talbi .....	632
Similarities of Frequent Following Patterns and Social Entities K. Kawagoe, C. Kai-Sang Leung .....	642
A Study of Immunity-based Urban System: A Morphological Approach C.-H. Chen, L.-F. Hsu .....	652
Improve the Adaptation Navigation in Educational Cross-systems L. Ghorbel, C.A. Zayani, I. Amous .....	662
Verification of Smoke Detection in Video Sequences Based on Spatio-temporal Local Binary Patterns M. Favorskaya, A. Pyataeva, A. Popov .....	671
Image Categorization Using Color G-SURF Invariant to Light Intensity M. Favorskaya, A. Proskurin .....	681
SecondDEP: Resilient Computing that Prevents Shellcode Execution in Cyber-Attacks T. Okamoto .....	691
Effective Method for Rear-end Collision Warning System T. Ito, K. Osawa .....	700
Survey on Anomaly Detection Using Data Mining Techniques S. Agrawal, J. Agrawal .....	708
Acceleration Based Particle Swarm Optimization for Graph Coloring Problem J. Agrawal, S. Agrawal .....	714
An Autonomous Emergency Warning System Based on Cloud Servers and SNS G. Buribayeva, T. Miyachi, A. Yeshmukhametov, Y. Mikami .....	722
Automatic Detection of Polyp Using Hessian Filter and HOG Features Y. Iwahori, A. Hattori, Y. Adachi, M.K. Bhuyan, R.J. Woodham, K. Kasugai .....	730
Object Tracking with Improved Detector of Objects Similar to Target S. Fukui, R. Nishiyama, Y. Iwahori, M.K. Bhuyan, R.J. Woodham .....	740
Improvement of Features Extraction Process and Classification of Cervical Cancer for the NeuralPap System S.N. Sulaiman, N.A. Mat-Isa, N.H. Othman, F. Ahmad .....	750
Evaluating Denoising Performances of Fundamental Filters for T2-Weighted MRI Images I.S. Isa, S.N. Sulaiman, M. Mustapha, S. Darus .....	760
Neural Network Techniques for Cancer Prediction: A Survey S. Agrawal, J. Agrawal .....	769
Hand-motion Analysis for Development of Double-unders Skill S. Yoshioka, K. Matsuura, N. Gotoda .....	775
Recent Advancement in Machine Learning Based Internet Traffic Classification N. Namdev, S. Agrawal, S. Silkari .....	784
Standing in Line Behavior Extraction Method by Radio Information N. Suzuki, K. Tsuda .....	792
An Efficient Prediction Model for OTC Medicine Effect with the Package Inserts Information T. Ikoma, Y. Fujita, M. Takahashi, K. Tsuda .....	800
A Framework of MRI Fat Suppressed Imaging Fusion System for Femur Abnormality Analysis B.C.C. Meng, U.K. Ngah, B.E. Khoo, I.L. Shuaib, M.E. Aziz .....	808

Mixed Integer Programming Approach on Examination Proctor Assignment Problem T. Koide .....	818
Estimation of Phyletic Trees from Cladograms and Birth Orders A. Mutoh, S. Ota, R. Enosawa, N. Inuzuka .....	824
Methods for Evaluating Pictures and Extracting Music by 2D DFA and 2D FFT H. Kawakatsu .....	834
A Proposal of Topic Map Based Chatterbot for Non-English Natural Language Input M. Kimura .....	841
A Variable Selection Method Considering Cluster Loading for Labeled High Dimension Low Sample Size Data J. Chen, M. Sato-Ilic .....	850
Greenhouse Environmental Control System Based on SW-SVR Y. Kaneda, H. Ibayashi, N. Oishi, H. Mineno .....	860
A Mobile Robot for Fall Detection for Elderly-Care T. Sumiya, Y. Matsubara, M. Nakano, M. Sugaya .....	870
Clustering Mutual Funds Based on Investment Similarity T. Sakakibara, T. Matsui, A. Mutoh, N. Inuzuka .....	881
Tag-based Chat Support System to Remind Users of Contents of Past Conversations R. Tanaka, J. Itou, J. Munemori .....	891
Communication Support System for Enabling Group Management of Community Units K. Otsuka, J. Itou, J. Munemori .....	900
The Effectiveness of D-Case Application Knowledge on a Safety Process N. Kobayashi, S. Yamamoto .....	908
Proposal and Comparison of an Idea Generation Support System Presenting Words for the Use of Scarce Knowledge People J. Itou, T. Higashi, J. Munemori .....	918
Scenario-based Experiments for the Design of a Presentation Support System for Non-Native Speakers X. Zhao, T. Yuizono, J. Munemori .....	926
Fuzzy Random Weighted Weber Problems in Facility Location T. Uno, K. Kato, H. Katagiri .....	936
Development of Web Learning Support System Using “My Dictionary” in English Study H. Usami, H. Eguchi, M. Ozaki, Y. Adachi .....	944
Detecting Erase Strokes from Online Handwritten Notes Using Support Vector Classification M. Miura, Y. Kobayashi .....	952
A Systematic Knowledge Education Approach for Safety-Critical System Development S. Yamamoto .....	960
A Study on Deliberate Presumptions of Customer Payments with Reminder in the Absence of Face-to-face Contact Transactions M. Takahashi, H. Azuma, K. Tsuda .....	968
Analog Neural Circuit and Hardware Design of Deep Learning Model M. Kawaguchi, N. Ishii, M. Umeno .....	976
Alternative-ingredient Recommendation Based on Co-occurrence Relation on Recipe Database R. Yamanishi, N. Shino, Y. Nishihara, J. Fukumoto, A. Kaizaki .....	986
A Constructing Algorithm for Appropriate Piecewise Linear Membership Function Based on Statistics and Information Theory T. Hasuike, H. Katagiri, H. Tsubaki .....	994
A Study on Growth Model of OSS Projects to Estimate the Stage of Lifecycle Y. Kuwata, H. Miura .....	1004
A Web-based Application for Writing Novels S. Nishihara, M. Miura .....	1014
Investigating Network-based Proximity in American Biotechnology D.-S. Lee .....	1021
Time Series Analysis of the in Class Page View History of Digital Teaching Materials Using Cross Table K. Dobashi .....	1032
Mutual Support in Energy Sector: Toward Energy Resilience N.B. Mulyono .....	1041
Path Optimization for Electrical PCB Inspections with Alignment Operations Using Multiple Cameras H. Katagiri, G. Qingqiang, W. Bin, T. Muranaka, H. Hamori, K. Kato .....	1051
Solving Bin Packing Problem with a Hybrid Genetic Algorithm for VM Placement in Cloud M.A. Kaaouache, S. Bouamama .....	1061
GPU-PSO: Parallel Particle Swarm Optimization Approaches on Graphical Processing Unit for Constraint Reasoning: Case of Max-CSPs N. Dali, S. Bouamama .....	1070
Meeting Scheduling Based on Swarm Intelligence H. Salem, A.B. Hassine .....	1081
A Case-based Management System for Secure Software Development Using Software Security Knowledge M. Saito, A. Hazeyama, N. Yoshioka, T. Kobashi, H. Washizaki, H. Kaiya, T. Ohkubo .....	1092

Guided Genetic Algorithm: A New Template Concept H.B. Othman, M. Tagina .....	1101
A Hybrid Lagrangian Search Ant Colony Optimization Algorithm for the Multidimensional Knapsack Problem W. Nakbi, I. Alaya, W. Zouari .....	1109
Automatic Feature Point Selection through Hybrid Metaheuristics Based on Tabu Search and Memetic Algorithm for Augmented Reality T. Matsui, Y. Katagiri, H. Katagiri, K. Kato .....	1120
P-J Matching Model of Knowledge Workers L. Zhang, W. Fei, L. Wang .....	1128
Feature Extraction from Numerical Evaluation in Online Hotel Reviews K. Tsujii, M. Takahashi, K. Tsuda .....	1138
Virtual Engineering Object / Virtual Engineering Process: A Specialized form of Cyber Physical System for Industrie 4.0 S.I. Shafiq, C. Sanin, E. Szczerbicki, C. Toro .....	1146
Study on Hiring Decision: Analyzing Rejected Applicants by Mining Individual Job Placement Data of Public Employment Security Offices H. Asano, K. Tanaka, Y. Fujita, K. Tsuda .....	1156
Supporting Teachers for Descriptive Quiz in Large Class—Find Imperfect Understandings by Using Typing Information T. Haruhiko, H. Kenji, K. Hiroharu, T. Shinji .....	1164
The Experiment of Sweden Game and the Evaluations of Gaming Result M. Kawaguchi, H. Kanematsu, N. Baba .....	1170
Visualizing History for Qualitative Explanation of Valuable Events Using Tangled String Y. Ohsawa, T. Hayashi .....	1178
Promotion of Active Learning at National Institute of Technology, Gifu College N. Ogawa, A. Shimizu .....	1186
Evaluation For Students' Learning Manner Using Eye Blinking System in Metaverse D.M. Barry, N. Ogawa, A. Dharmawansa, H. Kanematsu, Y. Fukumura, T. Shirai, K. Yajima, T. Kobayashi .....	1195
Shape and Layout Understanding Method Using Brain Machine Interface for Idea Creation Support System H. Hasegawa, S. Shibasaki, Y. Ito .....	1205
An Analysis of Emotions in Reversed Japanese Sentences and Malay Sentences with NIRS M.N.A.M. Anuardi, A.K. Yamazaki, N.A. Rasid .....	1215
The Association between the Score and the Vocabulary in the Waka Essay by High School Student with Waka Learning System K. Toyose, N. Asaba, K. Nishino .....	1223
The Analysis of the Brain State Measuring by NIRS-based BMI in Answering Yes-no Questions K. Tanino, H. Miura, N. Matsuda, H. Taki .....	1233
Development of a Method for Visualization of Skills at Experiments and Practical Training Y. Takeichi, K. Yajima, S. Matsuhashi, K. Misono, S.-N. Suzuki, J. Sato, Y. Kato .....	1240
Verification of the Relationship between the Stock Performance and the Randomness of Price Fluctuation M. Tanaka-Yamawaki, XinYang, Y. Mikamori .....	1247
Relationship between Job Opportunities and Economic Environments Measured from Data in Internet Job Searching Sites A.-H. Sato, C. Shimizu, T. Mizuno, T. Ohnishi, T. Watanabe .....	1255
NFC-based Tangible User Interface for Information Curation and its Application to Analogy Game Y. Takama, T. Ito, H. Ishikawa .....	1263
Optimal Prices and Associated Factors of Product with Substitution for One Supplier and Multiple Retailers Supply Chain W. Fei, M. Du, G. Luo .....	1271
Knowledge Structuring and Reuse System Using RDF for Supporting Scenario Generation T. Hayashi, Y. Ohsawa .....	1281
The Role of Path Continuity in Lateral Vehicle Control M. Elbanhawi, M. Simic, R. Jazar .....	1289
Formal Model for Intelligent Route Planning M. Spichkova, M. Simic, H. Schmidt .....	1299
What Type of Information and Scheme does the Data Market Need? H. Hatanaka, A. Abe .....	1309
Tweet-mapping Method for Tourist Spots Based on Now-tweets and Spot-photos K. Oku, F. Hattori, K. Kawagoe .....	1318
Research on Value Evaluation of E-commerce Business Model L. Weiwei, D. Yue .....	1328
Long-term Collaboration Mechanism for Disruption Recovery Service in Public Tram Systems Y. Fang, A.Z. Zeng .....	1337
Optimization of Postal Distribution Network Based on Rendezvous with Heterogeneous Vehicles and Capacity Constraints L. Sun, H. Wang, J. Hou .....	1347
Prediction of Enterprise Purchases Using Markov Models in Procurement Analytics Applications A. Westerski, R. Kanagasabai, J. Wong, H. Chang .....	1357
Research of Oil Product Secondary Distribution Optimization Based on Collaborative Distribution X. Wang, H. Zhan, J. Zhang .....	1367

Pricing Strategies in Dual-online Channels Based on Consumers' Shopping Choice J. Lei, J. Jia, T. Wu	1377
An Improved Computer Interface Comprising a Recurrent Neural Network and a Natural User Interface J. Yang, R. Horie	1386
A Context-based Support System of Mobile Chinese Learning for Foreigners in China L. Sun, J. Hou, X. Hu, K. Al-mekhlafi	1396
Recommendation System for Grocery Store Considering Data Sparsity N. Sano, N. Machino, K. Yada, T. Suzuki	1406
Proposal of a Supporting System for Planning, Executing and Reflecting Tasks in Research Activities K. Miyamoto, H. Kunimune, M. Niimura	1414
LIDAR and Monocular Based Overhanging Obstacle Detection J. Young, M. Simic	1423
A Conversational Agent to Encourage Willingness to Communicate in the Context of English as a Foreign Language E. Ayedoun, Y. Hayashi, K. Seta	1433
Research in Vehicles with Thermal Energy Recovery Systems A. Royale, M. Simic	1443
Hybrid User-Item Based Collaborative Filtering N.P. Kumar, Z. Fan	1453
Auto-Categorization of HS Code Using Background Net Approach L. Ding, Z. Fan, D. Chen	1462
Asymmetric Characterization of Diversity in Symmetric Stable Marriage Problems: An Example of Agent Evacuation Y. Ishida, S. Hashimoto	1472
Chance for Conversation Activation on Shopping Activities Y. Hayashi, A. Abe	1482
A Preliminary Experiment to Investigate the Effects of Blue Backgrounds on a Tablet Screen for Elderly People A.K. Yamazaki, K. Eto	1490
Development of a Motion Learning Support System Arranging and Showing Several Coaches' Motion Data T. Yoshinaga, M. Soga	1497
A Decision Method for Returns Logistics Based on the Customer's Behaviour in E-commerce W. Wang	1506
Enhancement of Classifiers in HTM-CLA Using Similarity Evaluation Methods J. Balasubramaniam, C.B. Gokul Krishnaa, F. Zhu	1516
A Preliminary Examination of Effect of Massage and Aroma Oil Massage in Foot Care Nursing K. Eto, A.K. Yamazaki, K. Yonekura, M. Mukuda, Y. Kabasawa, H. Yoshida, K. Ito, M. Ogiwara	1524
Ontology-based Framework for Risk Assessment in Road Scenes Using Videos M.A. Mohammad, I. Kaloskampis, Y. Hicks, R. Setchi	1532
"If Thinking" Support System for Training Historical Thinking Y. Miki, T. Kojiri, K. Seta	1542
A Prescription for Cyber Physical Systems R.L. Hartung, A. Hakansson, E. Moradian	1552
Golf Learning Environment Enabling Overlaid Display of Expert's Model Motion and Learner's Motion Using KINECT T. Kora, M. Soga, H. Taki	1559
Proposition and Design of a Skill Learning Environment for Drawing onto 3D Objects Using AR K. Iwasako, M. Soga	1566
Reasoning Strategies in Smart Cyber-Physical Systems A. Håkansson, R. Hartung, E. Moradian	1575
Toward Resilient Sensor Networks with Spatiotemporal Interpolation of Missing Data: An Example of Space Weather Forecasting M. Tokumitsu, K. Hasegawa, Y. Ishida	1585
Development and Evaluation of a System for AR Enabling Realistic Display of Gripping Motions Using Leap Motion Controller R. Katahira, M. Soga	1595
Security in Multi-Agent Systems Y. Hedin, E. Moradian	1604
An Evaluation of Image Enhancement Techniques for Nailfold Capillary Skeletonisation N.P. Doshi, G. Schaefer, S.Y. Zhu	1613
CT Liver Segmentation Using Artificial Bee Colony Optimisation A. Mostafa, A. Fouad, M.A. Elfattah, A.E. Hassanien, H. Hefny, S.Y. Zhu, G. Schaefer	1622
Probabilistic Model to Analyze Patient Accessibility to Medical Facilities Using Geographic Information Systems S. Doi, H. Ide, S. Ogawa, K. Takabayashi, S. Fujita, S. Koike	1631
Segmentation of Clock Drawings Based on Spatial and Temporal Features Z. Harbi, Y. Hicks, R. Setchi, A. Bayer	1640
Automatic Classification of Facial Morphology for Medical Applications H. Abbas, Y. Hicks, D. Marshall	1649

Computer-aided Surgical Planning of Anterior Cruciate Ligament Reconstruction in MR Images K. Morita, S. Kobashi, K. Kashiwa, H. Nakayama, S. Kambara, M. Morimoto, S. Yoshiya, S. Aikawa .....	1659
Study of a Port Coordinator's Mental Workload Based on Facial Temperature K. Murai, K. Kitamura, Y. Hayashi .....	1668
Optimizing Variable Opaque Product Design in E-commerce Based on Blind Booking S. Bai, Z. Yan, L. Liu .....	1676
Verbalization Support for Motor Skill Using Form Drawing Tool Based on Skeleton Model R. Hashimoto, T. Kojiri .....	1687
A Communication Protocol for Different Communication Technologies in Cyber-Physical Systems M. Persson, A. Håkansson .....	1697
Feature Extraction Method for Clock Drawing Test T. Shigemori, Z. Harbi, H. Kawanaka, Y. Hicks, R. Setchi, H. Takase, S. Tsuruoka .....	1707
Examining the Relationships among National Culture, Individual-Level Cultural Variable and Consumer Attitudes K. Kishiya, G.E. Miracle .....	1715
Integrating Heterogeneous Data Sources for Planning Road Reconstruction T. Kimoto, T. Morita, T. Ishii, H. Suga, Y. Sugawara, T. Beppu, T. Yamaguchi .....	1720
Efficient Method to Determine Microarea with High Potential Demand for Broadband Services M. Iwashita, A. Inoue, T. Kurosawa, K. Nishimatsu .....	1728
Knowledge Construction for Efficient Man-month Estimation in Software Development T. Shida, Y. Fujita, K. Tsuda .....	1738
Simulating Resilient Server Using XEN Virtualization I. Winarno, Y. Ishida .....	1745
Fermi Estimate on the Web: Placing Sensor Networks on the Web with Noise Y. Ishida, R. Chiba .....	1753
Multi-type Edge Bundling in Force-Directed Layout and Evaluation R. Saga, T. Yamashita .....	1763
Visualization System for Shopping Path Y. Kaneko, S. Miyazaki, K. Yada .....	1772
Verification of Effect on Next Purchase when Many Vice Category Products are Brought K. Ishibashi, K. Miyazaki, K. Yada .....	1780
Packet Scheduling and Access Priority Control for QoS and Fairness in Wireless LAN L. Kongsili, A. Fujimoto, F. Uchio .....	1788
PID Tuning of Servo Motor Using Bat Algorithm K. Singh, P. Vasant, I. Elamvazuthi, R. Kannan .....	1798
Color Distinctiveness Feature for Person Identification without Face Information P. Li, H. Wu, Q. Chen .....	1809
Personal ID System by Means of Random Input Passwords M. Tanaka-Yamawaki, Y. Tanaka, K. Yoshii .....	1817
Dynamic Stock Correlation Network Y. Arai, T. Yoshikawa, H. Iyetomi .....	1826
Complex Principle Component Analysis on Dynamic Correlation Structure in Price Index Data Y. Kichikawa, Y. Arai, H. Iyetomi .....	1836
Investigation in Wireless Power Transmission for UAV Charging M. Simic, C. Bil, V. Vojisavljevic .....	1846
Toward Application of Immunity-based Model to Gait Recognition Using Smart Phone Sensors: A Study of Various Walking States Y. Watanabe .....	1856
A Note on Continuous Self-Identification as Self-Awareness: An Example of Robot Navigation Y. Ishida .....	1865
An Adaptive Predictor for System Property Forecasting P. Luong, J. Vrbaneck Jr., W. Wang .....	1875



19th International Conference on Knowledge Based and Intelligent Information and Engineering Systems

## Transfer AdaBoost SVM for Link Prediction in Newly Signed Social Networks using Explicit and PNR Features

Anh-Thu Nguyen-Thi\*, Phuc Quang Nguyen, Thanh Duc Ngo, Tu-Anh Nguyen-Hoang

*University of Information Technology, Vietnam National University HCMC, Quarter 6, Linh Trung Ward, Thu Duc Dist, Ho Chi Minh city 700000, Vietnam*

---

### Abstract

In signed social network, the user-generated content and interactions have overtaken the web. Questions of whom and what to trust has become increasingly important. We must have methods which predict the signs of links in the social network to solve this problem. We study signed social networks with positive links (friendship, fan, like, etc) and negative links (opposition, anti-fan, dislike, etc). Specifically, we focus how to effectively predict positive and negative links in newly signed social networks. With SVM model, the small amount of edge sign information in newly signed network is not adequate to train a good classifier. In this paper, we introduce an effective solution to this problem. We present a novel transfer learning framework is called Transfer AdaBoost with SVM (TAS) which extends boosting-based learning algorithms and incorporates properly designed RBFSVM (SVM with the RBF kernel) component classifiers. With our framework, we use explicit topological features and Positive Negative Ratio (PNR) features which are based on decision-making theory. Experimental results on three networks (Epinions, Slashdot and Wiki) demonstrate our method that can improve the prediction accuracy by 40% over baseline methods. Additionally, our method has faster performance time.

© 2015 The Authors. Published by Elsevier B.V. This is an open access article under the CC BY-NC-ND license

(<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of KES International

**Keywords:** Link Prediction; Signed Social Network; AdaBoost Algorithm

---

### 1. Introduction

As well as the development of online social network, user-generated content is created and consumed at impressive rates. With so much user interactions and contents are created, the question of whom and what to trust has become an increasingly important challenge. Fortunately, online social networks have allowed people to indicate whom they trust (*positive links*) and distrust (*negative links*). However, this does not solve the problem, we need a signed link prediction system which predicts the signs of links in online social network. Then, we can algorithmically use that positive and negative information to make suggestions to other users about whom they in turn should trust and help a user make decisions, sort and filter information, receive recommendations.

---

\* Corresponding author. Tel.: +84-090-737-9067

E-mail address: [thunta@uit.edu.vn](mailto:thunta@uit.edu.vn), [nguyenthianhthu6789@gmail.com](mailto:nguyenthianhthu6789@gmail.com)




Fig. 1. Framework of a signed link prediction system.

Examples include Epinions<sup>1</sup> whose users can express trust or distrust of others<sup>15</sup>, Slashdot<sup>2</sup> whose participants can declare others to be either friends or foes<sup>10</sup> and Wiki<sup>3</sup> whose users can vote for or against the promotion of others to adminship<sup>2</sup>. On Epinions, the trust and distrust information is used to determine the reviews shown, using an undisclosed algorithm. On Slashdot, the posts of users tagged as foes are given a lower score, and may thus be hidden. On Wiki, the voting information is used to automatically search for likely future administrators.

A signed link prediction system works through two phases: the offline and the online phases<sup>19</sup>. The overview of the whole framework is given in the Fig. 1. The purpose of offline phase is to learn a prediction model from the training data with three steps: preprocessing, feature extraction and training. The online phase begins with the step of preprocessing and feature extraction similar to the offline phase. Then, the prediction model (trained in the offline phase) is used to assign an edge to positive or negative.

Previous research of signed social networks<sup>14</sup> has shown that the prediction model makes a very strong assumption on the input network: *the signs of all links except the one to be predicted are known in advance*. Thus, we study the edge sign prediction problem with a more realistic setting. Given a newly signed social network, the paucity of available signs makes it difficult to train a good classifier to predict unknown link signs. To solve this problem, we consider leveraging another more mature signed social network, which has the abundant edge sign information. This approach is known as *transfer learning*<sup>16,17</sup>.

In this paper, we present a novel transfer learning framework called *TAS* which extends boosting-based learning algorithms and incorporates properly designed *RBF SVM* (SVM with the RBF kernel) component classifiers. With our framework, we use *explicit topological features*<sup>20</sup>. Besides, we propose to use *PNR feature*<sup>19</sup> which is based on the strong theory of decision-making. PNR is a generalizable feature and outperforms most state-of-the-art features in three criteria: accuracy, generalization and speed. Our experimental results on three real signed social networks demonstrate that our method can improve the prediction accuracy and reduces time to extract features, train and test data over baseline methods.

The rest of the paper is organized as follows. We discuss related work in Section 2. Section 3 presents our proposed method which is called *TAS*. Additionally, we present explicit features and PNR features which are used in our approach in this section. Section 4 shows the experimental results with discussions. Finally, we conclude the paper in Section 5.

## 2. Related Work

For the edge sign prediction problem, existing studies can be categorized into two major approaches: a matrix kernel approach<sup>9,10</sup> and a machine learning approach<sup>3,11</sup>. Guha et al<sup>9</sup> proposed their leading work on trust propagation in signed social network. Kunegis et al<sup>10</sup> extended the method of graphical spectrum analysis by using kernels taken

<sup>1</sup> [www.epinions.com](http://www.epinions.com)

<sup>2</sup> [slashdot.org](http://slashdot.org)

<sup>3</sup> [www.wikipedia.org](http://www.wikipedia.org)




Fig. 2. Our method for signed link prediction in newly signed social networks.

from signed Laplacian matrices of graphs. Leskovec et al<sup>11</sup> proposed *16-dimensional features* corresponding to 16 types of triads in the balance theory and used a logistic regression model to predict the sign of links. Kai-Yang et al<sup>3</sup> tried to improve the quality of feature representation. Instead of using triads, the authors took all cycles of  $m$  vertices containing predicted links. The major contribution of their studies is the connections to theories of balance and status in social psychology. However, in their studies, the prediction model makes a very strong assumption on the input network: the signs of all links except the one to be predicted are known in advance, which is not very practical in reality.

Thus, we study the edge sign prediction problem for a newly signed social network whose the edge sign information is very scarce. We try to develop a general framework for transfer learning based on *TrAdaBoost*<sup>4</sup>. We use *RBFSVM* (SVM with the RBF kernel) as component classifier in *TrAdaBoost*. Our method is called *TAS*. The overview of the whole our method is given in the Fig. 2. Our method considers to leverage another more mature signed social network (*Source Graph*) to construct a high-quality classification model for a newly signed social network (*Target Graph*). Thus, we need use generalizable features which can apply to many social networks. In our method, we use *explicit topological features*<sup>20</sup> (node degree, betweenness centrality, triad count and edge embeddedness) which express manifest properties of the edge instances. Instead of using explicit features, we use *PNR features* which are based on decision-making theory.

### 3. Proposed Method

This section describes our proposed method for edge sign prediction. Firstly, we present our formal definitions for the edge sign prediction problem. Secondly, we propose a TAS which likes learning algorithm in the transfer learning framework. Finally, we describe proposed features for the edge sign prediction problem.

#### 3.1. Problem Formulation

A newly signed social network is called *Target Graph* for edge sign prediction. It is a directed graph  $G_t = (V_t, E_t^l, E_t^u, S)$ . We let  $V_t$  denotes the set of vertices,  $E_t^l$  denotes the set of edges with sign labels,  $E_t^u$  denotes the set of edges whose signs are unknown, and  $S$  is a mapping function which denotes the signs of edges (*positive or negative*).

Because the paucity of available signs in newly signed social network makes it difficult to train a good classifier, we need to leverage another more mature signed social network. Thus, we have another directed graph  $G_s = (V_s, E_s, S)$  which is called *Source Graph*. We let  $V_s$  denotes the set of vertices,  $E_s$  denotes the set of edges with sign labels.

Formally, we let  $T = T_s \cup T_t$  denotes the training data.  $T_s = \{e_s, S(e_s)\}, \forall e_s \in E_s$ , and  $T_t = \{e_t, S(e_t)\}, \forall e_t \in E_t^l$ . Let  $E_t^u$  denotes the testing data. For an edge instance  $e = (u, v) \in T$ , we encode the essential information of edge into feature vector for training step. Each feature vector is labeled as positive or negative. Feature vectors which are extracted from training data and their labels are used to train a prediction model.

### 3.2. Transfer Learning Through TAS

Source graph may have a different joint distribution of the edge instances and the class labels from the target graph. Besides good knowledge, source graph also contains noisy data. The useful knowledge from source graph is advantageous to the process of classification, while the noisy part of the data does not affect the classifier too much. Thus, training data are abundant, but the basic classifiers learn from these data can not classify the testing data well due to different data distributions. We need a prediction model that leverages the labeled instances in both the source and target graphs. Therefore, we construct *Transfer AdaBoost with SVM*. To construct this prediction model, we borrow the AdaBoost idea from Dai et al.<sup>4</sup> and AdaBoost with SVM-based component classifiers from Li et al.<sup>13</sup>.

AdaBoost (Freund and Schapire, 1997)<sup>8</sup> is a learning framework which aims to boost the accuracy of a weak learner (component classifier) by carefully adjusting the weights of training instances and learns a classifier accordingly. But, for source graph training instances, when they are wrongly predicted due to distribution changes by the prediction model, these instances could be those that are the most dissimilar to the target graph instances. Therefore, this learning algorithm doesn't train a good classifier. To solve this problem, we borrow the *Transfer AdaBoost* from Dai et al, which extends AdaBoost (Freund and Schapire, 1997) for transfer learning. We should give edge instances in  $T_s$ , that are less similar to the target edge instances in  $T_t$ , smaller weights to weaken their impacts; conversely, for edge instances in  $T_s$  that are more similar to the target edge instances in  $T_t$ , we should give larger weights to attach more importance to them.

Previous researches of transfer learning that use Decision Trees<sup>6</sup> or Neural Networks<sup>18</sup> as component classifiers in AdaBoost have been reported. Still, some difficulties remain. What should be the suitable tree size when Decision Trees are used as component classifiers? How could the complexity be controlled to avoid overfitting when Neural Networks are used as component classifiers? To solve this problem, we borrow the *AdaBoostSVM* from Li et al. The AdaBoostSVM is AdaBoost incorporating properly designed RBFSVM (SVM with the RBF kernel) component classifiers. From Li et al.<sup>13</sup>, the distributions of accuracy and diversity over RBFSVM component classifiers by designing parameter adjusting strategies have promising results. Li et al demonstrate AdaBoost approach that uses RBFSVM component classifiers outperforms other AdaBoost approaches using component classifiers such as Decision Trees and Neural Networks. Thus, we incorporate properly designed RBFSVM (SVM with the RBF kernel) component classifiers in *Transfer AdaBoost*. RBFSVM uses two regularization parameters:  $C$  controls its model complexity and training error;  $\gamma$  is the free parameter of the Gaussian radial basis function. We select proper values of  $C$  and  $\gamma$  following Li et al.<sup>13</sup>.

A formal description of Transfer AdaBoost with SVM (TAS) is given in Algorithm 1. In TAS, we use  $w_1, \dots, w_n$  to denote the weights of edges in  $T_s$ , and  $w_{n+1}, \dots, w_{n+m}$  to denote the weights of edges in  $T_t$ . For an edge  $e$ ,  $P_t(e) \in [-1, 1]$  is the predicted edge sign for  $e$ , and  $S(e)$  is the true edge sign. Because the use of source graph is leverage for target graph, the source graph edges will never have a larger influence than the target graph edges. Therefore, the weights of source graph edges would never increase and are always less than those of target graph edges. For any target graph edge  $e_t \in E_t^l$ , its weight will always get increased by a factor of  $\beta_t^{-\frac{|P_t(e_t) - S(e_t)|}{2}} \in [1, +\infty)$ . For any source graph edge  $e_s \in E_s$ , its weight will always get decreased by a factor of  $\beta_s^{\frac{|P_t(e_s) - S(e_s)|}{2}} \in (0, 1]$ .

### 3.3. Proposed Features

Previous study of edge sign prediction problem for a newly signed social network<sup>20</sup> uses *explicit topological features* (node degree, betweenness centrality, triad count and edge embeddedness) which express manifest properties of the edge instances in the source or target graph and *latent topological features* which can capture the common patterns between source graph and target graph. However, with *latent feature*, when the distributional differences between the source and target graphs become larger, the transfer learning performance becomes worse. Thus, we need a feature which is more generalizable than *latent feature*. In this paper, we propose to use *PNR feature*<sup>19</sup> which is based on the strong theory of decision-making.

**Algorithm 1:** Transfer AdaBoost with SVM (TAS)

**Input:** The two labeled data  $T_s$  and  $T_t$ , the unlabeled data  $E_t^u$ , a SVM-based component classifiers RBFSVM, and the maximum number of iterations  $K$ .

**Output:** Edge sign classifier  $P$ .

**begin**

Let  $n \leftarrow |T_s|$ ,  $m \leftarrow |T_t|$

The initial weight vector, that  $w^1 = (w_1^1, \dots, w_n^1, w_{n+1}^1, \dots, w_{n+m}^1)$ . We allow the users to specify the initial values for  $w^1$ .

**for**  $t = 1, \dots, K$  **do**

1. Set  $q^t \leftarrow w^t / (\sum_{i=1}^{n+m} w_i^t)$

2. Call RBFSVM component classifier that is provided the combined training set  $T$  with the distribution  $q^t$  over  $T$  and the unlabeled data  $E_t^u$ ,  $P_t: F(e) \rightarrow P_t(e) \in [-1, 1]$ .

3. Calculate the error of  $P_t$  on  $T_t$ :

$$e_t = \frac{\sum_{i=n+1}^{n+m} q_i^t \cdot \frac{|P_t(e_i) - S(e_i)|}{2}}{\sum_{i=n+1}^{n+m} q_i^t}$$

4. If  $e_t > 0.5$ , select new appropriate parameters ( $C$  and  $\gamma$ ) following<sup>13</sup> for an RBF kernel. Then, go to (2).

5. Set  $\beta_t = \frac{e_t}{1-e_t}$ ,  $\beta = \frac{1}{1 + \sqrt{2 \ln(n)/K}}$

6. Update weight vector  $w^t$

$$w_i^{t+1} = \begin{cases} w_i^t \beta^{\frac{|P_t(e_i) - S(e_i)|}{2}} & 1 \leq i \leq n \\ w_i^t \beta_t^{-\frac{|P_t(e_i) - S(e_i)|}{2}} & n+1 \leq i \leq n+m \end{cases}$$

$$P(e) = \begin{cases} 1 & \text{if } \sum_{t=1}^K \log \frac{1}{\beta_t} \cdot P_t(e) \geq 0 \\ -1 & \text{otherwise} \end{cases}$$

We present how to construct PNR feature for edge sign prediction. For a directed edge  $e = (u, v)$ , we use  $d_{out}^+(u)$  to denote the number of positive outgoing edges at  $u$  and  $d_{out}^-(u)$  to denote the number of negative outgoing edges at  $u$ . Similarly,  $d_{in}^+(v)$  and  $d_{in}^-(v)$  are the number of positive and negative incoming edges at  $v$ . The term of  $\varepsilon$  is an extremely small value to ensure that the denominators are nonzero. We are interested in the ratios between four terms at  $u$  and  $v$ :

$$R_{out}(u) = \frac{d_{out}^+(u)}{d_{out}^-(u) + \varepsilon} \quad (1)$$

$$R_{in}(v) = \frac{d_{in}^+(v)}{d_{in}^-(v) + \varepsilon} \quad (2)$$

where  $R_{out}(u)$  is the proportion between positive and negative outgoing edges at  $u$  and  $R_{in}(v)$  is the proportion between positive and negative incoming edges at  $v$ . Additionally, since  $R_{out}$  and  $R_{in}$  may reach positive infinity, their wide values ranges cause difficulties in the learning step. To overcome this, a threshold  $t$  is used to cut the ranges down.

$$R_{out}^t(u) = \min(R_{out}(u), t) \quad (3)$$

$$R_{in}^t(v) = \min(R_{in}(v), t) \quad (4)$$

The PNR feature of the edge  $e = (u, v)$  is given by concatenating two limited ratios:

$$PNR(u, v) = (R_{out}^t(u), R_{in}^t(v)) \quad (5)$$

The strength of this feature is that it has a close connection with the decision-making theory in terms of past experience; benefit maximization; herd behaviour; anchoring and adjustment heuristic.

- *Past experience*: Past decisions influence on future decisions. An example is that a person usually gives more positive votes than negative votes. It becomes the habit that this person tends to give positive votes. For an edge  $e = (u, v)$ , the first element  $R_{out}(u)$  indicates the voting history of the voter  $u$ .
- *Benefit maximization*: The quality of the object affects directly the decisions of the voters and then, it should be considered for prediction. We can evaluate its quality indirectly by taking its incoming edges. The large value of  $R_{in}$  is an evidence for its good quality and otherwise. Generally, a good object tends to receive more positive votes from new people and otherwise.
- *Herd behaviour*: Herd behaviour in human societies is defined as a phenomenon in which independent people observe and mimic the actions of others, even mistaken. An example is that a person with many fans (large value of  $R_{in}$ ) may usually receive more friend requests than hostile relationships.
- *Anchoring and Adjustment heuristic*: Heuristics are general strategies which can help us make right decisions quickly. In fact, when a person wants to make friend with a stranger, such initial information (likes/dislikes, friends/enemies, etc) will be useful anchors for this person to reach better estimate. In the PNR feature, these anchors are encoded into the term of  $R_{in}$  to enrich prediction with necessary information.

While  $R_{out}$  represents the past experience of voters,  $R_{in}$  implies the principles of benefit maximization, herd behaviour, anchoring and adjustment heuristic. This theoretical foundation helps *PNR feature* significantly outperform the *latent feature* in all aspects: the accuracy, the generalization and the speed. Experimental results demonstrate that *PNR feature* is fitter than *latent feature* when we use them in the transfer learning performance.

We have constructed both explicit and PNR features for edge sign prediction. For an edge instance  $e = (u, v) \in E_t^l$  with label  $S(e)$ , we have 11 features, including node degrees  $deg_{out}(u)$  and  $deg_{in}(v)$ , betweenness centrality  $f_{bc}(u)$  and  $f_{bc}(v)$ , triad counts  $f_{FF}(e)$ ,  $f_{FB}(e)$ ,  $f_{BF}(e)$ ,  $f_{BB}(e)$ , edge embeddedness  $f_{eb}(e)$ , PNR features  $R_{out}^l(u)$  and  $R_{in}^l(v)$ . Similarly, we can define features for edge instances in  $E_s$ .

## 4. Experiments

In this section, we present our experiments to evaluate the our method. Firstly, we describe data preparation and evaluation methods. Secondly, we briefly introduce four baseline methods which are compared with our method and present some detailed settings of five methods. Finally, we present experimental results and discussions.

### 4.1. Data Preparation and Evaluation Methods

We use three online social networks Epinions, Slashdot and Wiki. All networks are downloaded from Stanford Large Network Dataset Collection<sup>4</sup>. Because the original graphs are too large and sparse, we select 19,987 nodes from Epinions, 15,999 nodes from Slashdot and 6,998 nodes from Wiki with the highest degrees<sup>20</sup>. Table 1 shows the statistics of the three extracted networks.

Table 1. Statistics of three extracted networks.

Galleries	Nodes	Edges	Positive Edges	Negative Edges	(%) Positive Edges
Epinions	19,987	634,209	555,601	78,608	87.6
Slashdot	15,999	371,122	283,993	87,129	76.5
Wiki	6,998	113,844	83,832	30,012	73.6

As the edge signs in all these networks are overwhelmingly positive, we overcome this bias by following the methodology of Guha et al.<sup>9</sup> to generate balanced databases. We consider each pair of networks out of the three. We

<sup>4</sup> <http://snap.stanford.edu/data/index.html>

use one network as the source graph and the other as the target graph. There are totally 6 pairs to test. In each target graph, we partition the edge instances into four parts. We use one part as the testing data  $E_t^u$  and randomly sample 10 percentage of edge instances in the remaining three parts to form the labeled edge set  $E_t^l$ . This  $E_t^l$  and  $E_s$  in the source graph form the training data.

To evaluate the our method, we use three degrees: *accuracy*, *precision* and *recall*<sup>5</sup>. Accuracy, precision and recall are the basic measures used in evaluating a classification model. Besides, we compare performance time of the methods.

#### 4.2. Experimental Settings

For evaluation purpose, we use MATLAB to set up following five methods:

- *Target*: using labeled edge instances in the target graph for training with SVM model (the RBF kernel).
- *Combine+Latent*: using all edge instances in the source graph and labeled edge instances in the target graph for training with SVM model (the RBF kernel).
- *TAS+Latent*: using all edge instances in the source graph and labeled edge instances in the target graph for training with TAS.
- *Combine+PNR*: using both source graph edges and labeled target graph edges for training with SVM model (the RBF kernel).
- *TAS+PNR* (our method): using both source graph edges and labeled target graph edges for training with TAS.

*Target*, *Combine+Latent* and *TAS+Latent* use the explicit and latent topological features that are proposed in<sup>20</sup>. *Combine+PNR* and *TAS+PNR* use our proposed features (explicit features and PNR features). Besides TAS algorithm, we use SVM model with a RBF kernel because this kernel usually outperforms the different kernels in both accuracy and convergence time<sup>1</sup>.

We construct latent features following<sup>20</sup>. However, Ye et al don't publish value of parameters such as the trade-off regularization parameter  $\alpha$  and the convergence threshold for an iterative update algorithm. Moreover, they don't also introduce classifier methods initializing latent feature matrices. Thus, after some preliminary test, we set trade-off parameter  $\alpha$  is 10, convergence threshold is  $10^{-1}$ . To initialize latent feature matrices, we implement Naive Bayes classifier (*a widely used classifier method*).

#### 4.3. Experiments Results and Discussions

We evaluate our method based on four criteria: accuracy, precision, recall and speed (performance time). We have 6 pairs (source - target) from three networks Epinions, Slashdot and Wiki. Fig 3 shows the accuracies of *Target*, *Combine+Latent*, *TAS+Latent*, *Combine+PNR* and *TAS+PNR* on 6 pairs. This shows that *TAS+PNR* has the best edge sign prediction result. In Fig 4, we present five Precision Recall Curve (PR curve) for methods on 6 pairs. The precision recall area under curve (PR AUC) is just the area under the PR curve. The higher it is, the better the method is. Therefore, our method has the best result on most pairs.

From Fig 3 and Fig 4, we can see that our method (*TAS+PNR*) can improve the prediction accuracy by 40% over baseline methods. In the first group of experiment, we use Epinions as the source graph and Slashdot as the target graph. *Target* has the worst result because these method uses only small amount of edge sign information in target graph. *Combine+Latent* can improve the accuracy over *Target* but the noise in the source edge instances may become more obvious. Thus, *TAS+Latent* has better than *Combine+Latent*. However, the latent feature becomes worse when the distributional differences between the source and target graph become large. The PNR feature that is based on the strong theory of decision-making has high generalization. Therefore, *Combine+PNR* and *TAS+PNR* have high accuracy. With TAS algorithm, we replace latent feature with PNR feature. Our method has the best result. We can observe similar trends in residual pairs.

In the end, we turn to the speed evaluation of methods. We measure the performance time of feature extraction, training and prediction. All our experiments are conducted on the same PCs with 2.90 GHz CPU and 12G RAM. First, we compare the speed of feature extraction. Then, we measure the performance time of training and prediction. Table






Fig. 3. Prediction Accuracy with 10% of Labeled Target Edge Instances.




Fig. 4. PR Curve with 10% of Labeled Target Edge Instances.

2 shows the speed of two way feature extraction: explicit features combine latent features, explicit features combine PNR features. In table 3 and table 4, we present the speed of training and prediction with SVM and TAS.

From table 2, table 3 and table 4, when we replace latent feature with PNR feature, the speed of feature extraction, training and prediction is faster. The performance time decrease because PNR has two benefits: low cost feature, simple implementation.



Table 2. Performance time (in minute) of feature extraction (E - Epinions, S - Slashdot, W - Wiki).

	E - S	E - W	S - E	S - W	W - E	W - S
<b>Explicit+Latent</b>	190.10	144.46	83.66	54.46	38.73	53.53
<b>Explicit+PNR</b>	<b>143.19</b>	<b>115.96</b>	<b>50.14</b>	<b>34.14</b>	<b>24.21</b>	<b>35.44</b>

Table 3. Performance time (in minute) of training and prediction with SVM (E - Epinions, S - Slashdot, W - Wiki).

	E - S	E - W	S - E	S - W	W - E	W - S
<b>Combine+Latent</b>	600.16	1595.10	4390.40	251.36	955.97	75.73
<b>Combine+PNR</b>	<b>8.84</b>	<b>7.22</b>	<b>18.19</b>	<b>30.16</b>	<b>2.17</b>	<b>2.37</b>

Table 4. Performance time (in minute) of training and prediction with TAS (E - Epinions, S - Slashdot, W - Wiki).

	E - S	E - W	S - E	S - W	W - E	W - S
<b>TAS+Latent</b>	4273.20	4865.50	8185.40	5016.60	852.42	978.84
<b>TAS+PNR</b>	<b>1070.40</b>	<b>1073.70</b>	<b>1772.00</b>	<b>1055.20</b>	<b>214.71</b>	<b>302.63</b>

## 5. Conclusion

In this paper, we studied the problem of signed link prediction in social networks that have both positive and negative links. We focus how to effectively predict sign links in newly signed social network whose the edge sign information is very scarce. We propose a novel transfer learning framework called *TAS* that extends boosting-based learning algorithms and incorporates properly designed RBF SVM component classifiers. *TAS* can select the most useful source graph instances as additional training data for predicting the labels of target graph techniques when the noise in the source graph instances cause the model to predict wrongly on the test edges from the target graph. Besides, we replace *latent feature* with *PNR feature* that is low cost feature and has a close connection with the decision-making theory in terms of past experience; benefit maximization; herd behaviour; anchoring and adjustment heuristic. The results of experiments on three networks Epinions, Slashdot and Wiki show that our method really improves on previous methods in two criteria accuracy and speed significantly.

## References

1. Ben-Hur A, Weston J. A Users Guide to Support Vector Machines. *Methods in Molecular Biology*; 2010. p. 223-239.
2. Burke M, Kraut R. Mopping up: Modeling wikipedia promotion decisions. In *Proc. CSCW*; 2008.
3. Chiang K, Nagarajan N, Tewari A, Dhillon IS. Exploiting longer cycles for link prediction in signed networks. In *Proceedings of the 20th ACM Conference on Information and Knowledge Management*; 2011. p. 1157-1162.
4. Dai W, Yang Q, Xue G, Yu Y. Boosting for Transfer Learning. *Proc. 24th Intl Conf. Machine Learning*; 2007. p. 193-200.
5. Davis J, Goadrich M. The relationship between precision-recall and roc curves. *Technical report 1551, University of Wisconsin Madison*; 2006.
6. Dietterich TG. An experimental comparison of three methods for constructing ensembles of decision trees: bagging, boosting, and randomization. *Machine Learning* 40 (2); 2000. p. 139-157.
7. DuBois T, Golbeck J, Srinivasan A. Predicting trust and distrust in social networks. In *Proceedings of the third IEEE International Conference on Social Computing, SocialCom*; 2011.
8. Freund Y, Schapire RE. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of Computer and System Sciences* 55 (1); 1997. p. 119-139.
9. Guha RV, Kumar R, Raghavan P, Tomkins A. Propagation of trust and distrust. In *Proc. 13th WWW*; 2004.
10. Kunegis J, Lommatzsch A, Bauckhage C. The Slashdot Zoo: Mining a social network with negative edges. In *Proc. 18th WWW*; 2009. p. 741-750.
11. Leskovec J, Huttenlocher D, Kleinberg J. Predicting positive and negative links in online social networks. In *WWW*; 2010. p. 641-650.
12. Leskovec J, Huttenlocher D, Kleinberg J. Signed networks in social media. In *Proc. 28th CHI*; 2010.
13. Li X, Wang L, Sung E. Adaboost with SVM-based component classifiers. *Engineering Applications of Artificial Intelligence*, 21; 2008.
14. Liben-Nowell D, Kleinberg J. The link prediction problem for social networks. In *CIKM*; 2003. p. 556-559.
15. Massa P, Avesani P. Controversial users demand local trust metrics: an experimental study on epinions.com community. In *AAAI 05, AAAI Press*; 2005. p. 121-126.

16. Pan SJ, Yang Q. A survey on transfer learning. *IEEE Transactions on Knowledge and Data Engineering*, 22; 2010. p. 1345-1359.
17. Raina R, Battle A, Lee H, Packer B, Ng AY. Self-taught learning: Transfer learning from unlabeled data. *In ICML*; 2007. p. 759-766.
18. Schwenk H, Bengio Y. Boosting neural networks. *Neural Computation* 12; 2000. p. 1869-1887.
19. Tuyen H, Thanh V, Bac L. A Decision-making based Feature for Link Prediction in Signed Social Networks. *In IEEE RIVF*; 2013. p. 169-174.
20. Ye J, Cheng H, Zhu Z, Chen M. Predicting positive and negative links in signed social networks by transfer learning. *In Proceedings of the 22nd international conference on World Wide Web, International World Wide Web Conferences Steering Committee*; 2013. p. 1477-1488.
21. Zhuang F, Luo P, Xiong H, He Q, Xiong Y, Shi Z. Exploiting associations between word clusters and document classes for cross-domain text categorization. *In SDM*; 2010.