

VMware Health Check · Synthetic Demo

EXECUTIVE SUMMARY

This is a fully synthetic report created for screenshots and demonstrations. It does not contain anonymized customer data. The fictional environment has healthy memory headroom, but one cluster has aggressive CPU allocation, five snapshots are stale, a host shows point-in-time memory pressure, and several network exceptions need an owner. Four invented legacy hosts also illustrate how lifecycle findings appear in a customer report.

ASSESSMENT AT A GLANCE

248

Synthetic workload
VMs

12

Synthetic hosts

3.89:1

Overall CPU ratio

0.54:1

Overall memory
ratio

5

Stale snapshots

2

Overprovisioned
datastores

Priority findings

HIGH · CAPACITY

One cluster has aggressive CPU allocation

DEMO-PROD-EDGE is at **5.69:1**. This is a screening signal, not a sizing conclusion. Review sustained CPU demand, ready time, NUMA, reservations, HA reserve, and failover behavior.

HIGH · SNAPSHOTS

Five snapshots exceed the 72-hour guidance

The oldest synthetic snapshot is **12 days**. Assign an owner, verify backup dependencies, and consolidate with adequate datastore headroom. Snapshots are not backups.

HIGH · HOST PRESSURE

Point-in-time memory pressure needs follow-up

One fictional host reports **93% memory use**. Confirm the condition with historical demand, ballooning, swapping, and latency data before changing capacity.

HIGH · NETWORK SECURITY

A port group permits promiscuous mode

One synthetic port group allows promiscuous mode, three allow forged transmits, and four use VLAN 0 or have no VLAN ID. Validate the purpose and scope of each exception.

MEDIUM · LIFECYCLE

Four legacy hosts approach support expiry

The fictional Legacy RackServer L200 family has a synthetic support end date of **31 December 2026**. Confirm entitlement and prepare a refresh plan. These vendor names and dates are deliberately invented.

MEDIUM · STORAGE

Two datastores are logically overprovisioned

DEMO-DS-17 is provisioned to **112%** and DEMO-DS-31 to **119%** of fictional physical capacity. Thin provisioning needs growth monitoring and recovery headroom.

MEDIUM · GUEST OPERATIONS

Tools and virtual hardware debt remain

VMware Tools is not running or installed on **11 VMs**, and **14 VMs** use older virtual hardware. Remediate by application group rather than mass-upgrading.

MEDIUM · LICENSING

Six VMs require a software licensing review

The synthetic name-based match is not proof of installed software. Confirm products, editions, metrics, virtualization boundaries, and contract terms.

Hyper-Threading is consistent

Inventory and capacity

CPU and memory overcommit

Formula: CPU = configured vCPUs on powered-on workloads ÷ physical host cores; memory = configured memory on powered-on workloads ÷ physical host memory. Templates and non-powered-on workloads are excluded. All values shown here are synthetic.

Recommended sequence

- 01

First: investigate the fictional 93% memory condition and confirm whether it represents sustained pressure.
- 02

Within 30 days: assign owners to stale snapshots and review promiscuous-mode and forged-transmit exceptions.
- 03

Within 60 days: baseline demand on DEMO-PROD-EDGE and decide whether placement, right-sizing, or capacity changes are justified.
- 04

During lifecycle planning: validate entitlement, firmware, and refresh lead time for the fictional legacy host family.

Coverage gaps and assumptions

- All data in this demonstration is invented and cannot support an operational decision.
- A real RVTools assessment is still a point-in-time inventory and needs historical CPU, memory, storage, and network performance data.
- Support entitlement, firmware advisories, backup success, HA policy, security baselines, and application ownership require evidence outside RVTools.
- Lifecycle findings in a real report are matched against current primary vendor sources for every distinct host vendor and model.

Method and sources

Demonstration method. This page shows how an RVTools health assessment is structured, but every inventory value, identifier, date, model, ratio, and finding is fabricated. No customer workbook or derived value was used.

Illustrative hardware lifecycle table.

SYNTHETIC VENDOR / MODEL	HOSTS	CPU AND HT	BIOS EVIDENCE	ILLUSTRATIVE LIFECYCLE STATUS
Example Systems Legacy RackServer L200	4	Example Xeon-class CPU HT available / active	ExampleBIOS 3.18 15 Mar 2023	Synthetic milestone: sale ended 31 Dec 2021; support ends 31 Dec 2026. Refresh planning required.
Example Systems Current RackServer C400	8	Example EPYC-class CPU HT available / active	ExampleBIOS 6.04 20 Feb 2026	Synthetic status: actively supported; no retirement date published.

Public methodology references: [Broadcom snapshot guidance](#) and [Broadcom virtual hardware guidance](#). The product lifecycle names and dates above are intentionally fictional.