

OCVS Migration Analysis · Synthetic Demo

EXECUTIVE SUMMARY

This is a fully synthetic report created for screenshots and demonstrations. It does not contain anonymized customer data. The fictional estate is a plausible HCX candidate but is not wave-ready: one VM is below the RAV hardware-version minimum, two large-memory VMs require target design, and snapshots, VMware Tools, removable media, network policy, and licensing items must be resolved before migration groups are finalized.

ASSESSMENT AT A GLANCE

248

Synthetic workload
VMs

2

VMs over 1 TiB RAM

5

VMs over 10 TiB

11

Tools findings

3

Connected CD/DVD

10/2

AMD / Intel hosts

Priority findings

PROFILE BLOCKER · RAV

One synthetic VM is below the RAV hardware minimum

DEMO-LEGACY-01 is shown at **hardware version 8**. RAV requires version 9 or newer. Validate appliance support and either remediate deliberately or select another migration method.

DESIGN REVIEW · SIZING

Two VMs exceed 1 TiB of configured memory

The fictional large-memory VMs affect target shape, NUMA, HA reserve, migration profile, outage planning, and performance validation. Size from sustained demand rather than configuration alone.

WAVE READINESS · SNAPSHOTS

Five stale snapshots should be cleared

Snapshot and backup locks can interfere with validation and replication. Confirm ownership and consolidate with storage headroom before assigning the VMs to a migration wave.

MIGRATION WARNING · TOOLS

VMware Tools needs attention on 11 VMs

Bulk Migration expects VMware Tools and can warn or fail validation when tools are missing or outdated. Separate supported appliance cases, remediate the rest, and run HCX Validate.

PROFILE CHANGER · MEDIA

Three VMs have connected CD/DVD devices

RAV prohibits attached virtual media. Another 46 synthetic devices are configured to reconnect at power-on. Remove nonessential media and check again immediately before each wave.

PLANNING INPUT · STORAGE

Five VMs exceed 10 TiB provisioned

This is a replication-duration screening threshold, not an OCVS limit. Model seed duration, churn, bandwidth, target storage performance, and rollback space.

PLANNING INPUT · CPU

The synthetic source mixes ten AMD and two Intel hosts

OCVS has Intel and AMD shapes, while every host shape in a target cluster must use the same processor vendor. Preserve vendor for live mobility where required or plan a powered-off method.

MAPPING REVIEW · NETWORK

Source network exceptions need explicit target decisions

One synthetic workload uses a standard vSwitch, four port groups use VLAN 0 or no VLAN ID, one allows promiscuous mode, and three allow forged transmits.

Six synthetic workloads need licensing validation

Several common disk and device blockers were not detected

Inventory and capacity

CPU and memory overcommit

Cluster	Hosts	Powered-On VMs	vCPU / Cores	CPU Ratio	VM / Host Memory	Memory Ratio	Powered Off
DEMO-PROD-CORE	6	142	756 / 192	3.94:1	7.6 TiB / 12.0 TiB	0.63:1	8
DEMO-PROD-EDGE	3	59	410 / 72	5.69:1	2.7 TiB / 4.5 TiB	0.60:1	6
DEMO-DEV-TEST	3	30	142 / 72	1.97:1	1.1 TiB / 4.5 TiB	0.24:1	3
Overall	12	231	1,308 / 336	3.89:1	11.4 TiB / 21.0 TiB	0.54:1	17

Formula: CPU = configured vCPUs on powered-on workloads ÷ physical host cores; memory = configured memory on powered-on workloads ÷ physical host memory. Templates and non-powered-on workloads are excluded. All values shown here are synthetic.

Recommended sequence

- 01 **Before target design:** select a processor-vendor strategy, candidate OCVS shapes, and storage architecture; validate large VMs against sustained demand.
- 02 **Before pilot:** resolve the fictional hardware-version constraint, establish interoperability, and prove DNS, NTP, routing, firewall, bandwidth, and latency readiness.
- 03 **Before each wave:** clear stale snapshots, remediate VMware Tools, detach media, freeze network mappings, confirm backup blackouts, and run HCX Validate.
- 04 **After each move:** verify guest networking, tools, performance, backup, application health, licensing placement, and rollback closure.

Coverage gaps and assumptions

- All data in this demonstration is invented and cannot support a migration decision.
- RVTools cannot prove HCX service-mesh readiness, compatibility, DNS/NTP, firewall reachability, bandwidth, latency, packet loss, or change rate.
- DirectPath I/O, IOMMU, vVol backing, application clusters, dependencies, outage tolerance, and rollback criteria require separate validation.
- A real target design must confirm region, shape availability, software bundle, storage, HA reserve, pricing, and HCX licensing.

Method and sources

Demonstration method. This page illustrates the OCVS/HCX report structure using fully fabricated inventory, identifiers, ratios, findings, and examples. No customer workbook or derived value was used.

Public methodology references: [Oracle Cloud VMware Solution overview](#); [Oracle HCX migration workflow](#); [Broadcom RAV guidance](#). Current platform details must be rechecked for a real assessment.