

Motheo Integrator Guide

Everything ERP and POS platforms need to integrate with Tax Compliance Gateway document submission and webhook workflows.

Before you start

Prerequisites

Configuration is handled in **Motheo Platform**, not through this API.

You need: - An active app **API key** - For Lesotho integrations, a registered **device UUID** - Configured provider settings - Configured webhook endpoint settings, if using webhooks

Important terminology

Tax documents are submitted as **JSON payloads**, not file uploads.

Submit documents using:

```
POST /api/v1/{document-type}
```

Authentication

All document endpoints require an app API key.

```
Authorization: Bearer {api_key}
```

Authentication errors

Status	Meaning
401	API key is missing or invalid
403	App is not active, for example live approval is still pending

When the app is not active, the response body includes the app **status**.

Tax documents

Supported routes

Document type	Submit	List	Get one
Invoice	POST /api/v1/invoices	GET /api/v1/invoices	GET /api/v1/invoices/{id}
Credit note	POST /api/v1/credit-notes	GET /api/v1/credit-notes	GET /api/v1/credit-notes/{id}
Debit note	POST /api/v1/debit-notes	GET /api/v1/debit-notes	GET /api/v1/debit-notes/{id}
Receipt	POST /api/v1/receipts	GET /api/v1/receipts	GET /api/v1/receipts/{id}
Payout	POST /api/v1/payouts	GET /api/v1/payouts	GET /api/v1/payouts/{id}

Required headers for document submission

Every POST request must include these headers.

Header	Required	Purpose
Authorization	Yes	App API key
Idempotency-Key	Yes	Enables safe retries. Maximum 255 characters.
Content-Type	Yes	Must be application/json

Idempotency

Use one Idempotency-Key per logical transaction, such as your own external_id.

Scenario	Result
Same key and same body	Original status and JSON body are replayed
Same key and different body	409 conflict
Original request still processing	409 with Retry-After: 5

Conflict response message:

Idempotency key conflict: request body differs from original.

Amounts and quantities

Field type	Format
Money fields	Integers in minor units, for example cents
<code>quantity</code>	Integer. Often thousandths, where <code>1000</code> represents <code>1.000</code>
<code>tax_rate_bps</code>	Basis points, where <code>1500</code> means 15% and <code>1600</code> means 16%

Money fields include:

- `unit_price`
- `line_total`
- `tax_amount`
- totals
- payment amounts

Request body

```
{
  "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "external_id": "rcpt-2026-00042",
  "currency": "LSL",
  "issued_at": "2026-05-28T10:15:00+00:00",
  "lines": [
    {
      "line_no": 1,
      "name": "Maize meal 5kg",
      "line_type": "sale",
      "quantity": 1000,
      "unit_price": 10000,
      "line_total": 10000,
      "taxes": [
        {
          "tax_code": "LS_1",
          "role": "primary",
          "tax_rate_bps": 1500,
          "tax_amount": 1500
        }
      ]
    }
  ],
  "payments": [
```

```
{
  "method": "cash",
  "amount": 11500
},
"totals": {
  "subtotal": 10000,
  "tax_total": 1500,
  "grand_total": 11500
}
}
```

Request fields

Field	Notes
<code>external_id</code>	Required. Your stable document ID per app.
<code>currency</code>	ISO 4217 currency code, 3 letters.
<code>issued_at</code>	ISO 8601 date/time.
<code>device_id</code>	Required for Lesotho. UUID from platform device setup.
<code>lines</code>	Minimum 1 line. <code>line_type</code> can be <code>sale</code> , <code>discount</code> , or <code>payout</code> .
<code>totals</code>	<code>subtotal</code> , <code>tax_total</code> , and <code>grand_total</code> are required.
<code>payments</code>	Required for Lesotho receipt-style documents.
<code>original_document</code>	Used by credit and debit notes to reference a prior receipt.
<code>receipt_notes</code>	Optional notes for the receipt.
<code>receipt_print_form</code>	Lesotho print format: <code>Receipt48</code> or <code>InvoiceA4</code> .

Country-specific validation errors return `422` with field errors. Examples include buyer requirements on Lesotho invoices, negative credit-note amounts, invalid tax codes, and closed fiscal periods.

Responses

Country	POST status	Response behavior
Kenya	<code>202 Accepted</code>	Returns a submission resource. Status progresses asynchronously.
Lesotho	<code>201 Created</code>	Returns a document resource with fiscal fields when synchronous.

To check the latest status, poll:

```
GET /api/v1/{type}/{id}
```

The response includes `submission` when loaded.

You can also use webhooks for terminal `submission.status` values.

List endpoints use cursor pagination:

```
GET /api/v1/{type}?cursor=...
```

Default page size: **20 items per page**.

Sample response: Lesotho receipt

Returned immediately after:

```
POST /api/v1/receipts
```

The receipt is fiscalised locally. The initial `submission.status` is `fiscalised` until Lekuka accepts it in the background. Once accepted, Tax Compliance Gateway sends a `tax_submission.accepted` webhook and later `GET` responses show `submission.status` as `accepted`.

```
{
  "id": "9f3c2a1b-4d5e-6f7a-8b9c-0d1e2f3a4b5c",
  "external_id": "rcpt-2026-00042",
  "document_type": "receipt",
  "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "currency": "LSL",
  "subtotal": 10000,
  "discount_total": 0,
  "tax_total": 1500,
  "grand_total": 11500,
  "lines_tax_inclusive": false,
  "buyer": null,
  "payments": [
    {
      "method": "cash",
      "amount": 11500
    }
  ],
  "receipt_notes": null,
  "original_document": null,
  "receipt_print_form": "Receipt48",
  "issued_at": "2026-05-28T10:15:00+00:00",
  "receipt_counter": 1,
  "receipt_global_no": 1,
  "receipt_hash": "YWJjZGVmZ2hpams...",
  "receipt_qr_data": "a1b2c3d4e5f6g7h8",
}
```

```

    "receipt_qr_url": "https://invoice.rsl.org.ls/
0000001234202605280000000001a1b2c3d4e5f6g7h8",
    "fiscal_day_no": 1,
    "submission": {
      "id": "7e8f9a0b-1c2d-3e4f-5a6b-7c8d9e0f1a2b",
      "status": "fiscalised",
      "provider_reference": null,
      "signature_data": null,
      "validation_errors": null,
      "error_code": null,
      "error_message": null,
      "submitted_at": null,
      "accepted_at": null,
      "failed_at": null
    },
    "created_at": "2026-05-28T10:15:01+00:00"
  }

```

Examples

Lesotho receipt

```

POST /api/v1/receipts
Authorization: Bearer {api_key}
Idempotency-Key: rcpt-2026-00042
Content-Type: application/json

```

```

{
  "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "external_id": "rcpt-2026-00042",
  "currency": "LSL",
  "issued_at": "2026-05-28T10:15:00+00:00",
  "lines": [
    {
      "line_no": 1,
      "name": "Maize meal 5kg",
      "line_type": "sale",
      "quantity": 1000,
      "unit_price": 10000,
      "line_total": 10000,
      "taxes": [
        {
          "tax_code": "LS_1",
          "role": "primary",
          "tax_rate_bps": 1500,
          "tax_amount": 1500
        }
      ]
    }
  ]
}

```

```

    }
  ]
}
],
"payments": [
  {
    "method": "cash",
    "amount": 11500
  }
],
"totals": {
  "subtotal": 10000,
  "tax_total": 1500,
  "grand_total": 11500
}
}

```

Lesotho fiscal invoice

Fiscal invoices require a `buyer`. Use `receipt_print_form` when printing A4 invoices.

```

POST /api/v1/invoices
Authorization: Bearer {api_key}
Idempotency-Key: inv-2026-00001
Content-Type: application/json

```

```

{
  "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "external_id": "inv-2026-00001",
  "currency": "LSL",
  "issued_at": "2026-05-28T11:00:00+00:00",
  "buyer": {
    "name": "Maseru Trading (Pty) Ltd",
    "tax_id": "20001234567"
  },
  "receipt_print_form": "InvoiceA4",
  "lines": [
    {
      "line_no": 1,
      "name": "Office supplies",
      "line_type": "sale",
      "quantity": 1000,
      "unit_price": 50000,
      "line_total": 50000,
      "taxes": [
        {
          "tax_code": "LS_1",

```

```

        "role": "primary",
        "tax_rate_bps": 1500,
        "tax_amount": 7500
      }
    ]
  },
  "payments": [
    {
      "method": "eft",
      "amount": 57500
    }
  ],
  "totals": {
    "subtotal": 50000,
    "tax_total": 7500,
    "grand_total": 57500
  }
}

```

Lesotho credit note

Credit-note amounts should be negative and should reference the original document.

```

POST /api/v1/credit-notes
Authorization: Bearer {api_key}
Idempotency-Key: cn-2026-00001
Content-Type: application/json

```

```

{
  "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "external_id": "cn-2026-00001",
  "currency": "LSL",
  "issued_at": "2026-05-28T12:00:00+00:00",
  "receipt_notes": "Customer return",
  "original_document": {
    "receipt_id": 1001
  },
  "lines": [
    {
      "line_no": 1,
      "name": "Maize meal 5kg",
      "line_type": "sale",
      "quantity": 1000,
      "unit_price": -10000,
      "line_total": -10000,
      "taxes": [

```



```

    {
      "tax_code": "LS_1",
      "role": "primary",
      "tax_rate_bps": 1500,
      "tax_amount": -1500
    }
  ]
},
"payments": [
  {
    "method": "cash",
    "amount": -11500
  }
],
"totals": {
  "subtotal": -10000,
  "tax_total": -1500,
  "grand_total": -11500
}
}

```

Submission statuses

```

pending → processing → submitted → accepted
                                   ↘ rejected
                                   ↘ failed

```

Lesotho may also use `fiscalised` on the synchronous path.

Webhooks

Tax Compliance Gateway sends outbound webhooks to your configured HTTPS endpoint when relevant events occur.

Webhook URL, secret, and event subscriptions are configured in **Motheo Platform** for each app. You do not register webhooks with the document API key.

Webhook events

Event	When it is sent
<code>tax_submission.accepted</code>	Tax authority accepted the submission

Event	When it is sent
<code>tax_submission.failed</code>	Technical or integration failure occurred
<code>tax_submission.rejected</code>	Authority rejected the submission because of validation or business rules
<code>fiscal_period.closing_soon</code>	Lesotho manual fiscal day is nearing auto-close

You only receive events your endpoint is subscribed to in the platform.

Delivery behavior

Property	Value
Method	<code>POST</code>
Retries	Up to 5 attempts
Backoff	<code>1s</code> , <code>5s</code> , <code>30s</code> , <code>60s</code>
Timeout	15 seconds

Respond with **2xx** quickly and process the webhook asynchronously.

Webhook headers

Header	Description
<code>Content-Type</code>	<code>application/json</code>
<code>X-Tax Compliance Gateway-Event</code>	Event name
<code>X-Tax Compliance Gateway-Delivery-Id</code>	UUID. Use this for idempotency on your side.
<code>X-Tax Compliance Gateway-Webhook-Id</code>	Webhook configuration ID
<code>X-Tax Compliance Gateway-Signature</code>	Present when a secret is set. Format: <code>sha256={hmac_sha256_hex}</code> of the raw body.

Verify webhook signature

Use the raw request body when calculating the HMAC.

```
$payload = file_get_contents('php://input');
$signature = $_SERVER['HTTP_X_Tax_Compliance_Gateway_SIGNATURE'] ?? '';
$expected = 'sha256=' . hash_hmac('sha256', $payload, $secret);

if (!hash_equals($expected, $signature)) {
    abort(401);
}
```

Payload: tax submission events

```
{
  "event": "tax_submission.accepted",
  "occurred_at": "2026-05-28T10:16:02+00:00",
  "delivery_id": "550e8400-e29b-41d4-a716-446655440000",
  "webhook_id": "webhook-uuid",
  "submission": {
    "id": "...",
    "status": "accepted",
    "provider_reference": "42",
    "signature_data": {},
    "validation_errors": null,
    "error_code": null,
    "error_message": null,
    "submitted_at": "...",
    "accepted_at": "...",
    "failed_at": null
  },
  "document": {
    "id": "...",
    "external_id": "rcpt-2026-00042",
    "document_type": "receipt",
    "device_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "currency": "LSL",
    "grand_total": 11500,
    "receipt_counter": 12,
    "receipt_global_no": 1042,
    "receipt_qr_url": "https://verify.example.ls/0000001234202605280000001042ABCD",
    "fiscal_day_no": 3,
    "lines": [],
    "tax_breakdown": [],
    "submission": {}
  }
}
```

Match webhooks using either:

- `document.external_id`
- `submission.id`

The same `delivery_id` may be retried, so webhook handlers should be idempotent.

Payload: `fiscal_period.closing_soon`

```
{
  "event": "fiscal_period.closing_soon",
  "occurred_at": "...",
  "delivery_id": "...",
  "webhook_id": "...",
  "fiscal_period": {
    "id": "...",
    "fiscal_day_no": 1,
    "status": "opened",
    "closes_at": "...",
    "minutes_remaining": 20
  },
  "device": {
    "id": "...",
    "name": "POS 1",
    "lekuka_device_id": 12345
  }
}
```

Integration flow

```
sequenceDiagram
    participant ERP
    participant Tax Compliance Gateway
    participant TaxAuthority

    ERP->>Tax Compliance Gateway: POST /api/v1/invoices + Idempotency-Key
    Tax Compliance Gateway-->>ERP: 202 Accepted
    Tax Compliance Gateway->>TaxAuthority: Submit asynchronously
    TaxAuthority-->>Tax Compliance Gateway: Result
    Tax Compliance Gateway->>ERP: POST webhook tax_submission.accepted
    ERP->>Tax Compliance Gateway: GET /api/v1/invoices/{id} optional
```

Recommended flow

1. Submit the document with an `Idempotency-Key`.
2. Store the returned document and submission IDs.
3. Handle webhook events or poll `GET /api/v1/{type}/{id}` until `submission.status` is terminal.
4. On failure or rejection, inspect:
 5. `error_message`
 6. `validation_errors`
 7. `error_code`

Integration checklist

Documents

- [] Use a unique `Idempotency-Key` per business transaction.
- [] For Lesotho, provide a valid `device_id`.
- [] For Lesotho, make sure the fiscal period is open.
- [] Use the correct tax codes for the app's country.
- [] Send money fields as integer minor units.
- [] Send `tax_rate_bps` as basis points.

Webhooks

- [] HTTPS endpoint is reachable from Tax Compliance Gateway.
- [] Endpoint responds with `2xx` quickly.
- [] Verify `X-Tax Compliance Gateway-Signature` when a secret is configured.
- [] Make handlers idempotent using `delivery_id`.
- [] Process webhook work asynchronously.

Error reference

HTTP status	Meaning
<code>401</code>	Invalid API key
<code>403</code>	App not active
<code>404</code>	Document not found or not owned by this app
<code>409</code>	Idempotency conflict
<code>422</code>	Validation errors, <code>FISCAL_PERIOD_NOT_OPEN</code> , or <code>FISCAL_PERIOD_EXPIRED</code>