RESEARCH ARTICLE

Resource-Elastic Amharic LLMs through the Integration of TTT Scaling Laws and Neuromorphic Principles for Sovereign Green Computing

Kindie Alebachew[a]*, Durga Prasad Sharma[a]†, Messay Samuel[a]‡ and Mohammed Abebe[a]§

[a]*Faculty of Software Engineering and Computer Science, Arba Minch Institute of Technology, Arba Minch University, Arba Minch, Ethiopia*

ABSTRACT

Training and adapting large language models (LLMs) typically require substantial high-performance computing infrastructure, restricting equitable participation for morphologically rich, low-resource languages such as Amharic. This paper proposes and experimentally validates a compute-optimal, resource-elastic adaptation and inference framework designed for Amharic language modeling under strict energy constraints. We compare a monolithic dense transformer baseline against a modular Resource-Elastic Transformer (RET) comprising $E_{\max} = 8$ parameter-efficient experts equipped with Rank-Stabilized Low-Rank Adapters (RSLoRA, rank $r = 4$, $\alpha = 16$). Using a sub-linear complexity routing policy $\alpha(c) = c^{\beta}$ over normalized Zipfian word-rank complexity $c \in (0, 1]$, the model dynamically allocates active experts per token and triggers selective test-time training (TTT) with Best-of-N candidate reranking ($N = 5$) when token perplexity exceeds a routing threshold $\tau = 250.0$. Furthermore, a three-regime Adaptive Parameter Scheduler modulates routing sparsity (β) and TTT gradient steps in response to real-time energy budget depletion. Across multi-seed evaluations ($N = 200$ token transitions across three seeds and $N = 500$ extended ablation windows) sampled from a verified 1,201,750-pair Amharic Question Answering corpus, Language-Adaptive Pre-Training (LAPT) combined with compute-optimal elastic inference reduces mean perplexity from 313.83 (95% CI: $[310.13, 317.55]$) to 275.06 (95% CI: $[268.17, 281.68]$; Welch's t-test $p = 9.91 \times 10^{-22}$) while improving next-token prediction accuracy from 0.00% to 20.10% (BLEU-1 = 0.9950). Crucially, the compute-optimal pipeline activates only 24.50% of expert parameters, lowering inference energy by 4.08× from 2.62×10^{-4} J/token to 6.42×10^{-5} J/token (9.25×10^{-8} g CO_2e/token) and achieving a 3.63× improvement in Compute-Performance Ratio (CPR = 82.04 vs. 22.61 for dense LAPT+SFT). Sub-linear routing also attenuates the Spearman rank correlation between token morphological complexity and perplexity by 43.7% ($\rho = 0.0801, p = 0.0503$ to $\rho = 0.0451, p = 0.2711$), while RSLoRA achieves the lowest Carbon-Intensity of Adaptation (CIA $= 1.804 \times 10^{-2}$) among evaluated PEFT variants.

KEYWORDS

Large language models; Amharic language modeling; Resource-Elastic Transformer; Rank-Stabilized LoRA (RSLoRA); adaptive complexity routing; test-time training; Green AI; morphological complexity

*CONTACT Kindie Alebachew. Email: besukind@gmail.com, ORCID: https://orcid.org/0009-0005-2613-3914

†Email: dp.shiv08@gmail.com, ORCID: https://orcid.org/0000-0002-1654-901X

‡Email: mess.sama@gmail.com, ORCID: https://orcid.org/0000-0002-5070-2727

§Email: moshethio@gmail.com, ORCID: https://orcid.org/0000-0003-0622-4841

1. Introduction

Large language models (LLMs) have reshaped natural language processing (NLP) since 2017 through advances in transformer architectures and large-scale training corpora. Foundational models such as GPT-3 [1], PaLM [2], and LLaMA [3] achieved strong performance across conversational intelligence, reading comprehension, and open-ended text generation [4]. Subsequent frontier systems, such as those detailed in the GPT-4 Technical Report [5], further improved multi-turn dialogue, machine translation, and structured text generation across high-resource languages.

Empirical studies from OpenAI, Google, and Meta attribute many of these gains to simultaneous increases in parameter count, dataset scale, and pre-training compute [1–3, 6]. However, scaling-centric LLM development depends heavily on high-performance computing (HPC) clusters and web-scale curated datasets. These requirements raise financial cost, energy consumption, and infrastructural complexity, limiting research participation and deployment in low-resource linguistic communities such as Amharic [4, 7, 8]. Unlike high-resource languages, Amharic faces persistent constraints in standardized digital corpora, morphologically aware tokenization, and local GPU infrastructure, making brute-force dense adaptation impractical for sovereign localization.

While the Transformer architecture [9] serves as the foundation of modern NLP, recent studies emphasize the urgent need for Afro-centric NLP methodologies [10]. Approaches that rely exclusively on massive pre-training rarely address local data scarcity, agglutinative and fusional morphology, or severe hardware constraints [11]. Consequently, developing compute-efficient strategies across the entire LLM lifecycle—with transparent trade-offs between predictive quality and energy expenditure—remains essential under constrained computational budgets [12].

Recent progress in resource-constrained NLP has increasingly combined Parameter-Efficient Fine-Tuning (PEFT)—most notably Low-Rank Adaptation (LoRA) [13] and its rank-stabilized and weight-decomposed variants—with adaptive inference mechanisms. Concurrently, Test-Time Training (TTT) strategies have emerged to improve model robustness during inference by updating lightweight internal parameters on self-supervised test-time objectives [14]. Within Ethiopic and Amharic NLP, researchers have highlighted the need for architectures capable of handling dense root-and-pattern and affixation structures that produce heavy-tailed ("fat-tail") vocabulary distributions [10, 15]. This study bridges these paradigms by integrating a complexity-aware, sub-linear expert routing mechanism with selective PEFT-based test-time adaptation tailored for Amharic language modeling.

Classical neural scaling laws, including the Chinchilla framework, establish principles for balancing parameter count and training tokens during pre-training under a fixed FLOP budget [16]. Yet these analyses focus primarily on static pre-training allocation and offer limited guidance on downstream domain adaptation, inference-time compute elasticity, or parameter efficiency when base weights are frozen [17, 18]. For low-resource settings such as Amharic, computational efficiency must persist well beyond pre-training to accommodate fluctuating hardware budgets and domain shift during deployment [19]. Treating model effectiveness as a static property determined solely at pre-training overlooks dynamic strategies that modulate capacity per token during inference [20–22].

To address this gap, this study investigates three primary research questions:

- **RQ1 (Linguistic Adaptation & Complexity Routing):** To what extent can an autonomous, sub-linear complexity routing policy and perplexity-gated heuristic isolate and mitigate "fat-tail" morphological edge cases in Amharic language model inference without relying on uniform full-capacity dense execution?
- **RQ2 (Selective Test-Time Triage & Threshold Calibration):** How does varying the perplexity routing threshold τ govern the trade-off between test-time adaptation intervention rate and predictive perplexity on high-entropy Ethiopic token streams?
- **RQ3 (Green AI, PEFT Variants & Compute-Optimal Scheduling):** How do Rank-Stabilized Low-Rank Adapters (RSLoRA), alternative PEFT formulations (LoRA, DoRA), and budget-aware adaptive parameter scheduling affect the Carbon-Intensity of Adaptation (CIA), energy per token, and Compute-Performance Ratio (CPR) in resource-constrained Amharic NLP?

The primary objectives of this research are threefold: (1) to formalize compute-optimal adaptation (COA) across language-adaptive pre-training, parameter-efficient fine-tuning, and dynamic test-time inference [20]; (2) to prove and empirically validate a sub-linear Zipfian routing policy that guarantees strict energy reduction below dense execution while preserving full expert capacity for rare morphological forms [21, 23, 24]; and (3) to rigorously benchmark predictive quality and Green AI efficiency metrics on real Amharic question answering data [22]. By shifting focus from static dense scaling to dynamic resource elasticity, our framework aligns with Sovereign AI principles [25] and neuromorphic-inspired conditional computation [26] for sustainable language technology.

2. Related Works

This section reviews prior literature on neural scaling laws, cross-lingual adaptation under low-resource constraints, and adaptive inference via Mixture-of-Experts (MoE) and Test-Time Training (TTT).

2.1. Foundations of Scaling Laws and Compute Optimality

Empirical scaling laws characterize power-law relationships among model parameters (N), dataset size (D), and training compute (C) [1, 3, 4, 6]. Hoffmann et al. [16] demonstrated that compute-optimal pre-training requires scaling model capacity and training tokens in approximately equal proportions, showing that smaller models trained on sufficiently large corpora outperform under-trained larger models at fixed compute budgets.

Subsequent research has sought to extend compute-optimal principles to downstream fine-tuning and inference through parameter-efficient adapters such as LoRA [13], structured pruning, and data curation [20]. Nevertheless, standard scaling formulations assume uniform per-token floating-point operations (FLOPs) during both training and deployment, overlooking the substantial variance in linguistic difficulty across tokens [21, 22]. In morphologically rich Semitic languages such as Amharic, where a single orthographic word encodes subject, object, tense, aspect, negation, and prepositional clitics, uniform compute allocation either under-provisions capacity on rare inflections or wastes energy on frequent function words [22].

2.2. Cross-Lingual Dynamics and Low-Resource Constraints

Extending LLMs to multilingual regimes introduces capacity dilution—commonly termed the "curse of multilinguality"—where per-language fidelity degrades as more languages share a fixed parameter budget. Prior work addresses this challenge along two axes: (1) data-centric transfer via continual Language-Adaptive Pre-Training (LAPT), curated instruction tuning, and few-shot cross-lingual prompting [27, 28]; and (2) modular architectural specialization, including language-specific adapters and sparse Mixture-of-Experts routing [11, 24].

Recent efficiency-oriented multilingual paradigms further refine parameter allocation. Neuron-guided expert specialization reduces active parameters by approximately 40% while preserving low-resource representation quality [29]. English-pivoted Chain-of-Thought training separates latent reasoning from target-language generation [30], while curriculum learning in projects such as TildeOpen LLM sequences training data by structural complexity [31]. Representation Fine-Tuning (ReFT) adapts hidden representations directly [32], and the MERLIN framework aligns multilingual encoders with generative decoders across stages [33].

Despite these advances, Amharic NLP continues to face severe structural and infrastructural bottlenecks, including complex Ge'ez (*Fidel*) syllabic morphology, dialectal variation, and limited benchmark standardization [34]. Evaluation initiatives such as LLM Probe, SAHARA, AILuminate, and SurveyLens underscore persistent performance and calibration disparities in African languages when models are evaluated solely via translated Western benchmarks [35–38].

2.3. Adaptive Inference: Mixture-of-Experts and Test-Time Training

Adaptive computation seeks to decouple total model parameter capacity from per-token inference cost. Sparse Mixture-of-Experts (MoE) architectures dynamically route each token to a subset of feed-forward experts [24]. Concurrently, Test-Time Training (TTT) updates model parameters or low-rank states during inference using self-supervised objectives derived from the test input itself [14, 39].

While TTT improves out-of-distribution generalization on complex inputs, performing backpropagation on every test token introduces prohibitive latency and energy overhead on edge or CPU-bound hardware [40]. Table 1 summarizes representative scaling, adaptive inference, and multilingual training paradigms across the LLM lifecycle.

2.4. Synthesis and Research Gaps

Existing literature establishes strong foundations for static pre-training scaling [16, 22], parameter-efficient fine-tuning [13], and unconditional test-time training [14]. However, prior studies rarely unify these components under an explicit energy budget for morphologically rich, low-resource languages [7, 20, 21, 42–44]. Specifically, current research on Amharic language modeling lacks: (1) a mathematically grounded complexity routing rule linking Zipfian word-rank distributions to active expert ratios; (2) selective, threshold-gated test-time adaptation restricted to low-rank adapters; and (3) joint evaluation of linguistic fidelity alongside Green AI metrics such as Joules per token and Carbon-Intensity of Adaptation [34, 45].

Table 1. Overview of LLM scaling, adaptive inference, and multilingual adaptation strategies.

Category	Method	Lifecycle Stage	References	Core Mechanism
Foundation	Scaling Laws	Pre-training	[6, 16, 22, 41]	Power-law allocation balancing N, D, and compute C.
Adaptive	Sparse MoE	Train / Inference	[24]	Conditional sub-network activation per input token.
	Test-Time Training	Inference	[14, 39, 40]	Self-supervised parameter updates on test instances.
Multilingual	NeuronMoE	Train / Inference	[29]	Neuron-guided language-specific expert allocation.
	English-Pivot CoT	Train / Inference	[30]	Latent reasoning alignment for low-resource outputs.
	TildeOpen LLM	Pre-training	[31]	Curriculum sequencing by structural complexity.
	ReFT	Fine-tuning	[32]	Low-dimensional representation-space interventions.
	MERLIN	Alignment	[33]	Multi-stage cross-lingual encoder–LLM alignment.

3. Methodology

To ensure strict scientific reproducibility and traceability, every component of our methodology corresponds directly to the verified experimental codebase (`experiments003/experiment_pipeline.py`) and theoretical routing proof (`experiments003/theoretical_proof.md`).

3.1. Research Design and Four-Pipeline Experimental Framework

We employ a controlled four-pipeline progressive ablation design supplemented by two non-neural statistical baselines and three factorial/sensitivity ablation studies (RQ1–RQ3). All neural models are constructed with matched maximum feed-forward representational capacity so that performance and efficiency differences isolate the effects of Language-Adaptive Pre-Training (LAPT), sub-linear complexity routing, selective Test-Time Training (TTT) with Best-of-N reranking, and budget-aware parameter scheduling:

1. **Pipeline 1 — Dense Baseline (SFT) (`run_baseline`):** A monolithic dense transformer (`StandardDenseTransformer`) in which 100% of feed-forward parameters are activated uniformly for every token without LAPT pre-training, modular expert routing, or test-time gradient updates.

2. **Pipeline 2 — Intermediate Dense (LAPT + SFT) (`run_intermediate`):** A modular `ResourceElasticTransformer` that first undergoes continual Language-Adaptive Pre-Training (LAPT) on the initial 20% prefix of the Amharic token stream, followed by dense evaluation ($\beta \to 0$, forcing 100% expert activation across all $E_{\max} = 8$ experts) to establish the full-capacity adaptation ceiling.

3. **Pipeline 3 — Proposed Unconstrained (RET + TTT + Routing) (`run_proposed_unconstrained`):** Initializes from the LAPT+SFT adapted state of Pipeline 2 and enables sub-linear complexity routing ($\alpha(c) = c^{\beta}$ with $\beta = 0.5$),

combined with perplexity-gated test-time adapter updates ($\tau = 250.0$, $S_{\text{TTT}} = 2$ steps) and Best-of-N candidate reranking ($N_{\text{samples}} = 5$) under an unconstrained inference energy horizon.

4. **Pipeline 4 — Proposed Compute-Optimal (RET + TTT + Routing + Adaptive Scheduler) (`run_compute_optimal`):** Initializes from the LAPT+SFT adapted state of Pipeline 2 and integrates the `AdaptiveParameterScheduler`, which dynamically modulates the routing exponent β_t and TTT step count $S_{\text{TTT},t}$ at each token transition t according to the remaining energy budget ratio $B_{\text{remaining}}/B_{\text{total}}$ (with default budget $B_{\text{total}} = 0.01$ J).

In addition to the four neural pipelines, we evaluate two reference statistical baselines (`run_strong_baselines`) on the identical token stream and vocabulary V:

- **Uniform Random Baseline (`RandomBaseline`):** Assigns uniform probability $1/|V|$ to all vocabulary items, yielding a theoretical reference perplexity of exactly $|V|$ and uniform random token predictions.
- **Empirical Unigram Baseline (`UnigramBaseline`):** Estimates maximum-likelihood empirical token frequencies $p(w) = \text{count}(w)/M$ from the training prefix (20% split) and predicts $\arg\max_{w \in V} p(w)$ while assigning a clipped unigram evaluation perplexity on the sequence.

3.2. Dataset Description, Verification, and Preprocessing

3.2.1. Corpus Composition and Integrity Verification

The primary empirical data source is the Amharic Question Answering corpus stored at `experiments003/QAmdataset.json`. Independent cryptographic and structural verification (`experiments003/verify_dataset.py`) confirmed the integrity of the corpus (255, 983, 263 bytes, SHA-256 prefix `0e74404783e3cbe0...cde9296570`).

Table 2 summarizes the verified structural characteristics of the corpus. Every record follows a three-field JSON schema `{instruction, input, output}` in Ethiopic (*Fidel*) script:

- `instruction`: A uniform task prompt across all 1, 201, 750 entries (በሚከተለው ጥያቄ መሰረት ትክክለኛውን መልስ ስጥ። — "Provide the correct answer based on the following question.").
- `input`: 1, 201, 750 unique Amharic question sentences exhibiting diverse clitic, prefix, and suffix inflections, with zero empty or malformed entries.
- `output`: Concise Amharic answer strings drawn from 52 canonical response templates (mean length 2.09 ± 0.94 words).

3.2.2. Tokenization, Vocabulary Indexing, and Zipfian Complexity Scoring

In `load_real_dataset(filepath, num_samples)`, the first N_{samples} records are extracted from `QAmdataset.json`. For each record i, the question and answer fields are concatenated as $s_i = \text{input}_i \oplus \text{“ ”} \oplus \text{output}_i$. Punctuation characters in the set {., ?! :; ()“”} are stripped from word boundaries, and whitespace-delimited Amharic word tokens are collected into a corpus frequency counter.

Table 2. Verified structural and linguistic statistics of the Amharic Question Answering dataset (`QAmdataset.json`).

Field / Property	Total Records	Unique Values	Mean	Std. Dev.	Median	Min – Max
Corpus Records (N_{corpus})	1,201,750	1,201,750	—	—	—	—
`instruction` (characters)	1,201,750	1	36.00	0.00	36.0	36 – 36
`input` length (characters)	1,201,750	1,201,750	57.12	15.72	55.0	14 – 119
`input` length (words)	1,201,750	—	11.24	2.86	11.0	4 – 24
`output` length (characters)	1,201,750	52	8.78	6.87	6.0	2 – 29
`output` length (words)	1,201,750	—	2.09	0.94	2.0	1 – 4

Let $V = \{w_1, w_2, \ldots, w_{|V|}\}$ denote the vocabulary ordered by descending empirical frequency ($\text{count}(w_1) \geq \text{count}(w_2) \geq \cdots \geq \text{count}(w_{|V|})$), with 1-indexed integer identifiers $\text{id}(w_r) = r \in \{1, \ldots, |V|\}$ (and index 0 reserved for padding). Because rare, highly inflected Amharic word forms populate the high-rank Zipfian tail, each token w_r is assigned a normalized morphological complexity score equal to its relative Zipfian rank:

$$c(w_r) = \frac{r}{|V|} \in \left[\frac{1}{|V|}, 1.0\right]. \tag{1}$$

The concatenated token stream is truncated to a fixed evaluation window of N tokens $(x_1, x_2, \ldots, x_N)$ with corresponding complexity stream $(c_1, c_2, \ldots, c_N)$, defining $N - 1$ sequential autoregressive next-token transitions (x_t, y_t) where $y_t = x_{t+1}$ for $t \in \{1, \ldots, N-1\}$. Across our three verified evaluation windows:

- $N = 100$ (used in LAPT-adapted hyperparameter grid search): 99 token transitions, vocabulary size $|V| = 287$.
- $N = 200$ (used in primary multi-seed four-pipeline comparison and strong baselines across 3 seeds = 597 total transitions): 199 token transitions per seed, vocabulary size $|V| = 311$.
- $N = 500$ (used in extended single-seed budget, RQ1, RQ2, and RQ3 ablations): 499 token transitions, vocabulary size $|V| = 314$.

3.3. Model Architectures and Parameter-Efficient Fine-Tuning

3.3.1. Monolithic Dense Transformer Baseline

The `StandardDenseTransformer` maps an input token index $x_t \in \{1, \ldots, |V|\}$ through an embedding table $\mathbf{E} \in \mathbb{R}^{(|V|+1)\times d}$ with hidden dimension $d = 64$. The embedded representation $\mathbf{h}_t = \mathbf{E}[x_t] \in \mathbb{R}^d$ is processed by a monolithic two-layer feed-forward network (FFN) with expansion factor 32 (intermediate dimension $d_{\text{ff}}^{\text{dense}} = 32d = 2,048$), a ReLU activation, a residual connection, and an output projection head $\mathbf{W}_{\text{head}} \in \mathbb{R}^{d\times(|V|+1)}$:

$$\mathbf{z}_t = \mathbf{h}_t + \mathbf{W}_2\,\text{ReLU}(\mathbf{W}_1\mathbf{h}_t + \mathbf{b}_1) + \mathbf{b}_2, \quad \mathbf{W}_1 \in \mathbb{R}^{2048\times 64},\ \mathbf{W}_2 \in \mathbb{R}^{64\times 2048}, \tag{2}$$

$$\hat{\mathbf{y}}_t = \mathbf{W}_{\text{head}}\mathbf{z}_t + \mathbf{b}_{\text{head}}. \tag{3}$$

For every token t, the active parameter fraction of `StandardDenseTransformer` is $\alpha_{\text{eff}}(t) = 1.0$ (100%).

3.3.2. Resource-Elastic Transformer (RET) and PEFT Expert Formulation

To decouple parameter capacity from uniform per-token compute while matching the exact maximum representational capacity of the dense baseline, the `ResourceElasticTransformer` decomposes the $2,048$-dimensional FFN into $E_{\max} = 8$ parallel `ExpertModule` sub-networks, each with intermediate dimension $d_{\text{ff}}^{\text{expert}} = 4d = 256$ ($8 \times 256 = 2,048$).

Within each expert $e \in \{1, \ldots, E_{\max}\}$, both the up-projection ($\mathbb{R}^{64 \to 256}$) and down-projection ($\mathbb{R}^{256 \to 64}$) are implemented as `PEFTLinear` layers with frozen base weight matrix $\mathbf{W}_0 \in \mathbb{R}^{d_{\text{out}} \times d_{\text{in}}}$, bias $\mathbf{b}_0 \in \mathbb{R}^{d_{\text{out}}}$, low-rank adapter matrices $\mathbf{A} \in \mathbb{R}^{r \times d_{\text{in}}}$ (initialized via Kaiming uniform with $a = \sqrt{5}$) and $\mathbf{B} \in \mathbb{R}^{d_{\text{out}} \times r}$ (initialized to zero), rank $r = 4$, and scaling constant $\alpha_{\text{LoRA}} = 16$. The layer supports four selectable PEFT formulations:

$$\text{PEFTLinear}(\mathbf{u}) = \begin{cases} \mathbf{W}_0\mathbf{u} + \mathbf{b}_0, & \text{if } \texttt{peft_type} = \texttt{'none'}, \\ \mathbf{W}_0\mathbf{u} + \mathbf{b}_0 + \dfrac{\alpha_{\text{LoRA}}}{r}(\mathbf{BAu}), & \text{if } \texttt{peft_type} = \texttt{'lora'}, \\ \mathbf{W}_0\mathbf{u} + \mathbf{b}_0 + \dfrac{\alpha_{\text{LoRA}}}{\sqrt{r}}(\mathbf{BAu}), & \text{if } \texttt{peft_type} = \texttt{'rslora'}, \\ \text{DoRA}(\mathbf{u}; \mathbf{W}_0, \mathbf{B}, \mathbf{A}, \mathbf{m}) + \mathbf{b}_0, & \text{if } \texttt{peft_type} = \texttt{'dora'}. \end{cases} \tag{4}$$

In the Weight-Decomposed Low-Rank Adaptation (`'dora'`) formulation, let $\Delta\mathbf{W} = (\alpha_{\text{LoRA}}/r)\mathbf{BA}$ and $\mathbf{W}' = \mathbf{W}_0 + \Delta\mathbf{W}$. The directional matrix is normalized by its column-wise Euclidean norm $\|\mathbf{W}'\|_c$ and scaled by a learnable magnitude vector $\mathbf{m} \in \mathbb{R}^{d_{\text{out}}}$ initialized to $\|\mathbf{W}_0\|_c$. By default, our proposed pipelines employ Rank-Stabilized LoRA (`'rslora'`), whose $\alpha_{\text{LoRA}}/\sqrt{r} = 16/\sqrt{4} = 8.0$ scaling prevents gradient attenuation at low rank $r = 4$.

3.4. Theoretical Foundation: Sub-Linear Zipfian Routing Lemma

Given an input token x_t with normalized morphological complexity $c_t \in (0, 1]$ from Equation (1), the `ResourceElasticTransformer` determines the active expert fraction via a concave, sub-linear power-law policy parameterized by routing exponent $\beta > 0$:

$$\alpha(c_t) = \left(\text{clip}(c_t, 10^{-5}, 1.0)\right)^{\beta}. \tag{5}$$

The discrete number of active experts $E_{\text{active}}(c_t)$ and the effective active parameter ratio $\alpha_{\text{eff}}(c_t)$ are computed as:

$$E_{\text{active}}(c_t) = \max\left(1, \text{round}\left(\alpha(c_t) \cdot E_{\max}\right)\right), \qquad \alpha_{\text{eff}}(c_t) = \frac{E_{\text{active}}(c_t)}{E_{\max}}. \tag{6}$$

The forward representation averages the outputs of the first $E_{\text{active}}(c_t)$ active experts before applying the residual connection and output projection:

$$\mathbf{z}_t = \mathbf{h}_t + \frac{1}{E_{\text{active}}(c_t)} \sum_{e=1}^{E_{\text{active}}(c_t)} \text{Expert}_e(\mathbf{h}_t), \qquad \hat{\mathbf{y}}_t = \mathbf{W}_{\text{head}}\mathbf{z}_t + \mathbf{b}_{\text{head}}. \tag{7}$$

Lemma 3..1 (Sub-Linear Zipfian Routing Lemma)**.** *Let $c \in (0, 1]$ denote normalized token morphological complexity following a normalized Zipfian probability density $P(c) \propto c^{-s}$ ($s > 0$, $\int_0^1 P(c)\,dc = 1$) skewed toward frequent, low-complexity tokens. If the routing policy assigns active compute capacity according to $\alpha(c) = c^{\beta}$ with $0 < \beta < 1$ and maximum dense energy $E_{\max} > 0$, then:*

1. *The expected elastic inference energy* $E_{elastic} = \mathbb{E}_{c\sim P}[\alpha(c)E_{\max}]$ *is strictly bounded below the dense baseline energy:* $E_{elastic} < E_{\max}$.

2. *Peak representational capacity is asymptotically preserved for the rarest morphological edge cases:* $\lim_{c\to 1} \alpha(c) = 1$.

Proof. Because $0 < \beta < 1$, the mapping $\alpha(c) = c^\beta$ is strictly increasing and concave on $(0, 1]$, satisfying $0 < c^\beta < 1$ for all $c \in (0, 1)$. Since $P(c) > 0$ on $(0, 1]$ with $\int_0^1 P(c)\, dc = 1$, integrating over the complexity domain yields:

$$E_{\text{elastic}} = E_{\max} \int_0^1 P(c)c^\beta\, dc < E_{\max} \int_0^1 P(c) \cdot 1\, dc = E_{\max}. \tag{8}$$

Furthermore, taking the limit at the upper boundary of the Zipfian tail yields $\lim_{c\to 1^-} \alpha(c) = \lim_{c\to 1^-} c^\beta = 1$, ensuring that all $E_{\max}$ experts are recruited for maximum-complexity tokens ($c = 1$). □

3.5. Experimental Workflow, Selective TTT, and Adaptive Scheduling

Figure 1 illustrates the end-to-end execution workflow implemented in `experiment_pipeline.py`.




Figure 1. End-to-end adaptive execution workflow showing Zipfian complexity routing, perplexity-gated Test-Time Training (TTT) with Best-of-N reranking, and closed-loop energy budget scheduling.

3.5.1. Language-Adaptive Pre-Training (LAPT)

In Pipelines 2, 3, and 4, the `ResourceElasticTransformer` first undergoes Language-Adaptive Pre-Training on the initial 20% prefix of the evaluation token stream ($T_{\text{train}} = \lfloor 0.2N \rfloor$). All model parameters are optimized for 15 epochs using the Adam optimizer (`optim.Adam`) with learning rate $\eta_{\text{LAPT}} = 10^{-3}$ to minimize autoregressive cross-entropy loss:

$$\mathcal{L}_{\text{CE}}(\theta) = -\frac{1}{T_{\text{train}} - 1} \sum_{t=1}^{T_{\text{train}}-1} \log \frac{\exp(\hat{y}_{t,y_t})}{\sum_{v=0}^{|V|} \exp(\hat{y}_{t,v})}. \tag{9}$$

3.5.2. Perplexity-Gated Test-Time Training and Best-of-N Reranking

During autoregressive evaluation over $t \in \{1, \ldots, N-1\}$, each token x_t with complexity c_t is first evaluated in `torch.no_grad()` mode to obtain logits $\hat{\mathbf{y}}_t$, cross-entropy loss $\ell_t = \mathcal{L}_{\text{CE}}(\hat{\mathbf{y}}_t, y_t)$, and initial token perplexity $\text{PPL}_t = \exp(\ell_t)$. If PPL_t exceeds the routing threshold τ (set to $\tau = 250.0$ in Pipelines 3 and 4) and the scheduled TTT step count satisfies $S_{\text{TTT},t} > 0$, the token is routed to the slow adaptation path:

1. **Selective PEFT Adapter Update (`test_time_update`):** The model temporarily switches to training mode (`model.train()`), enabling gradients exclusively for low-rank adapter parameters containing `"lora"` ($\mathbf{A}, \mathbf{B}$) or `"m"` (DoRA magnitude vector) while keeping all base weights frozen. It executes $S_{\text{TTT},t}$ manual stochastic gradient descent steps with learning rate $\eta_{\text{TTT}} = 10^{-3}$ on the self-supervised logit activation objective $\mathcal{L}_{\text{TTT}}(x_t) = \frac{1}{|V|+1} \sum_{v=0}^{|V|} \hat{y}_{t,v}$:

$$\theta_{\text{PEFT}}^{(k+1)} = \theta_{\text{PEFT}}^{(k)} - \eta_{\text{TTT}} \nabla_{\theta_{\text{PEFT}}} \mathcal{L}_{\text{TTT}}(x_t), \quad k = 0, \ldots, S_{\text{TTT},t} - 1. \tag{10}$$

2. **Best-of-N Candidate Reranking (`best_of_n_rerank`):** Following the adapter update, the model reverts to evaluation mode and generates $N_{\text{samples}} = 5$ stochastic logit candidates by perturbing the adapted logits $\hat{\mathbf{y}}_t^{\text{adapt}}$ with independent Gumbel noise $\boldsymbol{\epsilon}_j \sim \text{Gumbel}(0, 0.5)$ for $j \in \{1, \ldots, N_{\text{samples}}\}$. Each candidate's top-1 token prediction is scored, and the adapted forward pass is evaluated to produce the updated post-TTT loss ℓ_t^{adapt} and perplexity $\text{PPL}_t^{\text{adapt}} = \exp(\ell_t^{\text{adapt}})$.

3.5.3. Three-Regime Adaptive Parameter Scheduler

In Pipeline 4, the `AdaptiveParameterScheduler` tracks cumulative energy expenditure $E_{\text{used}}(t) = \sum_{k=1}^{t} e_k$ against a total allocation B_{total} (default 0.01 J). At step t, let $r_B(t) = \max(0, (B_{\text{total}} - E_{\text{used}}(t))/B_{\text{total}}) \in [0, 1]$ denote the remaining budget fraction. The scheduler updates $(\beta_t, S_{\text{TTT},t})$ from base hyperparameters $(\beta_0 = 0.5, S_{\max} = 2)$ across three operational regimes:

$$(\beta_t, S_{\text{TTT},t}) = \begin{cases} (\beta_0,\ S_{\max}), & \text{if } r_B(t) > 0.5 \text{ (Rich)}, \\ (\min(1, \beta_0(1.5 - r_B(t))),\ \max(1, \lfloor 2 S_{\max} r_B(t) \rfloor)), & \text{if } 0.1 < r_B(t) \leq 0.5, \\ (2.0,\ 0), & \text{if } r_B(t) \leq 0.1 \text{ (Panic)}. \end{cases} \tag{11}$$

As the energy budget depletes into the Conservative and Panic regimes, increasing β_t toward 2.0 steepens the sub-linear routing curve $c_t^{\beta_t}$ (reducing active experts toward the minimum of 1 expert, or 12.5% active capacity) and suppresses test-time gradient updates $(S_{\text{TTT},t} \to 0)$.

3.6. Evaluation Metrics, Green AI Accounting, and Statistical Testing

Table 3 summarizes the linguistic, Green AI efficiency, and composite trade-off metrics implemented in `LinguisticMetrics` and `GreenAIMetrics`.

3.6.1. Linguistic Fidelity Metrics (`LinguisticMetrics`)

Let $\hat{w}_t$ and w_t^* denote the predicted and ground-truth Amharic word strings at transition $t \in \{1, \ldots, T\}$ $(T = N - 1)$.

Table 3. Summary of linguistic, computational efficiency, and Green AI trade-off metrics implemented in the evaluation pipeline.

Category	**Metric**	**Unit / Range**	**Mathematical Definition & Significance**
Linguistic	Perplexity (PPL ↓)	$[1, \infty)$	$\frac{1}{T}\sum_{t=1}^{T}\exp(\ell_t)$; measures token-level predictive uncertainty [22, 34].
	Token Accuracy (↑)	$[0, 100]\%$	Percentage of transitions where $\arg\max_v \hat{y}_{t,v} = y_t$.
	BLEU-1 (↑)	$[0, 1]$	Corpus unigram overlap between predicted and target word sequences.
	Char-F1 (↑)	$[0, \infty)$	Harmonic mean of character-level precision and recall proxies.
Efficiency	Active Ratio (α_{eff} ↓)	$[12.5, 100]\%$	Mean fraction of active experts $E_{\text{active}}(c_t)/E_{\max}$ across tokens.
	FLOPs / token (↓)	FLOPs	Floating-point operations accounting for forward, TTT backward, and reranking passes.
	Energy / token (↓)	Joules (J)	$\text{FLOPs}_{\text{total}} \times 10^{-9}$ J/FLOP hardware-neutral energy proxy [21, 45].
	Carbon (CO_2e ↓)	g CO_2e	(Joules/3600) × 400 g CO_2e/kWh carbon intensity estimate.
Trade-off	CIA (↓)	J · PPL	(Joules/token) × Mean PPL; Carbon-Intensity of Adaptation.
	CPR (↑)	%/ratio	ΔAccuracy/FLOPs Ratio; accuracy gain per unit relative compute [20].

- **Token Accuracy:** $\text{Acc} = \frac{1}{T}\sum_{t=1}^{T}\mathbb{I}(\hat{w}_t = w_t^*)$.
- **Unigram BLEU-1:** Let $O = \sum_{t=1}^{T}\mathbb{I}(\hat{w}_t \in \{w_1^*, \ldots, w_T^*\})$ denote the number of predicted tokens belonging to the reference vocabulary set of the evaluation window. Then BLEU-1 $= O/T$.
- **Character F1 (`Char-F1`):** For each transition t, let $C_{\text{pred},t}$ and $C_{\text{targ},t}$ denote the character lists of $\hat{w}_t$ and w_t^*. In `LinguisticMetrics.compute`, character overlap is computed as $m_t = \sum_{u \in C_{\text{pred},t}}\mathbb{I}(u \in C_{\text{targ},t})$, with precision proxy $p_t = m_t/|C_{\text{pred},t}|$, recall proxy $r_t = m_t/|C_{\text{targ},t}|$, and Char-F1$_t$ $= 2p_t r_t/(p_t + r_t)$. Note that because m_t tests set membership in $C_{\text{targ},t}$ without capping character multiplicity, when $|C_{\text{pred},t}| > |C_{\text{targ},t}|$ and predicted characters belong to $C_{\text{targ},t}$, r_t can exceed 1.0, yielding Char-F1 values slightly above 1.0 (e.g., 1.073–1.082). We preserve this exact implementation to maintain 100% numerical consistency with all logged artifacts while explicitly noting this property.

3.6.2. Green AI Energy and Carbon Formulations (`GreenAIMetrics`)

For a token transition t with active parameter ratio $\alpha_{\text{eff}}(c_t) \in [0.125, 1.0]$, total active FFN parameters are $P_{\text{active}}(t) = \alpha_{\text{eff}}(c_t) \cdot E_{\max} \cdot d \cdot d_{\text{ff}}^{\text{expert}} = \alpha_{\text{eff}}(c_t) \times 131,072$, corresponding to base forward FLOPs $\text{FLOPs}_{\text{base}}(t) = 2P_{\text{active}}(t)$ (a full dense forward pass requires 262,144 FLOPs). When TTT ($S_{\text{TTT},t} > 0$) and Best-of-N reranking ($N_{\text{samples}} = 5$) are triggered, each TTT step requires 3× forward FLOPs (forward + backward gradient + update) and each reranking candidate requires 1× forward FLOPs:

$$\text{FLOPs}_{\text{total}}(t) = \begin{cases} \text{FLOPs}_{\text{base}}(t) \cdot (1 + 3S_{\text{TTT},t} + N_{\text{samples}}), & \text{if } S_{\text{TTT},t} > 0 \text{ and } \text{PPL}_t > \tau, \\ \text{FLOPs}_{\text{base}}(t), & \text{otherwise.} \end{cases} \tag{12}$$

Hardware-neutral energy and carbon emissions are derived using standard CPU energy and grid carbon conversion constants:

$$e_t = \text{FLOPs}_{\text{total}}(t) \times 1.0 \times 10^{-9} \text{ J/FLOP}, \tag{13}$$

$$\text{CO}_2\text{e}_t = \frac{e_t}{3600 \text{ s/h}} \times 400 \text{ g CO}_2\text{e/kWh}. \tag{14}$$

Thus, a dense baseline forward pass ($\alpha_{\text{eff}} = 1.0, S_{\text{TTT}} = 0$) consumes exactly 2.62144×10^{-4} J/token (2.9127×10^{-8} g CO$_2$e/token). To jointly evaluate adaptation accuracy and energy cost across PEFT variants, we define the **Carbon-Intensity of Adaptation (CIA)**:

$$\text{CIA} = \left(\frac{1}{T}\sum_{t=1}^{T} e_t\right) \times \left(\frac{1}{T}\sum_{t=1}^{T} \text{PPL}_t\right), \tag{15}$$

and the **Compute-Performance Ratio (CPR)** relative to the Dense Baseline (Pipeline 1):

$$\text{CPR} = \frac{\text{Acc}_{\text{pipeline}} - \text{Acc}_{\text{baseline}}}{\alpha_{\text{eff,pipeline}}/\alpha_{\text{eff,baseline}}}. \tag{16}$$

3.6.3. Statistical Testing and Reproducibility Protocol

Multi-seed experiments execute over three deterministic seeds ($s \in \{42, 43, 44\}$), setting `torch.manual_seed(s)`, `np.random.seed(s)`, and `random.seed(s)`. We compute 95%

bootstrap confidence intervals over $B_{\text{boot}} = 1,000$ resamples with replacement, two-sided Welch's t-tests (`scipy.stats.ttest_ind(..., equal_var=False)`) and paired t-tests (`scipy.stats.ttest_rel`) for perplexity distributions, and two-sided Spearman rank correlations (ρ, `scipy.stats.spearmanr`) between token complexity c_t and perplexity PPL_t. All experiments were executed and independently verified on CPU (`PyTorch 2.10.0+cpu`, Python 3.13), with the trained model serialized to `model_checkpoint.pt` (1.32 MB).

4. Results and Analysis

All results reported in this section were independently verified by executing `experiments003/experiment_pipeline.py` across all evaluation configurations and cross-checking the newly generated outputs in `experiments003/experiment_results_verified/` against the existing artifacts in `experiments003/experiment_results/`. Numeric verification (`comparison_report.json`) confirmed exact reproducibility across all tables ($\max|\Delta| < 10^{-5}$).

4.1. Overview: Four-Pipeline Comparative Evaluation and Strong Baselines

Table 4 presents the primary four-pipeline comparison evaluated over $N = 200$ tokens per seed across three random seeds ($s \in \{42, 43, 44\}$, totaling 597 autoregressive token transitions, $|V| = 311$), alongside the extended single-seed $N = 500$ evaluation window (499 transitions, $|V| = 314$).

Table 4. Four-pipeline comparative evaluation across multi-seed ($N = 200$, 3 seeds, 597 transitions) and extended ($N = 500$, seed 42, 499 transitions) windows.

Window	Pipeline Configuration	Mean PPL ↓	95% Bootstrap CI	Active (%)	Energy (J/token)	Acc. (%)	BLEU-1 / C-F1
$N = 200$	1. Dense Baseline (SFT)	313.83	[310.13, 317.55]	100.00	2.621×10^{-4}	0.00	0.5427 / 0.9660
(3 seeds,	2. Intermediate Dense (LAPT+SFT)	273.02	[266.33, 279.41]	100.00	2.621×10^{-4}	22.61	1.0000 / 1.0753
$\|V\| = 311$)	3. Proposed Unconstrained (RET+TTT)	273.57	[266.92, 280.00]	35.74	9.369×10^{-5}	21.11	0.9950 / 1.0819
	4. Proposed Compute-Optimal	275.06	[268.17, 281.68]	24.50	6.422×10^{-5}	20.10	0.9950 / 1.0734
$N = 500$	1. Dense Baseline (SFT)	317.18	[314.76, 319.51]	100.00	2.621×10^{-4}	0.20	0.4910 / 0.9469
(1 seed,	2. Intermediate Dense (LAPT+SFT)	242.69	[230.20, 255.12]	100.00	2.621×10^{-4}	15.63	1.0000 / 1.0445
$\|V\| = 314$)	3. Proposed Unconstrained (RET+TTT)	245.74	[233.14, 258.44]	38.45	1.008×10^{-4}	13.83	1.0000 / 1.0609
	4. Proposed Compute-Optimal	250.58	[237.66, 263.56]	21.57	5.654×10^{-5}	12.42	1.0000 / 1.0454

Note: For $N = 200$ (3 seeds), Welch's two-sample t-test comparing Pipeline 1 vs. Pipeline 4 yields $p = 9.9075 \times 10^{-22}$, and carbon emissions for Pipeline 4 are 9.25×10^{-8} g CO_2e/token. For $N = 500$, the paired t-test comparing Pipeline 1 vs. Pipeline 3 yields $p = 2.2404 \times 10^{-26}$.

Several key empirical findings emerge from Table 4:

1. **Impact of Language-Adaptive Pre-Training (Pipeline 1 → Pipeline 2):** Adding 15 epochs of LAPT on the 20% prefix produces the largest absolute perplexity reduction across both windows: −40.81 PPL points (−13.00%, from 313.83 to 273.02) at $N = 200$ and −74.48 PPL points (−23.48%, from 317.18 to 242.69) at $N = 500$. Next-token prediction accuracy simultaneously increases from 0.00% to 22.61% ($N = 200$) and from 0.20% to 15.63% ($N = 500$), while BLEU-1 reaches 1.0000 because LAPT aligns output predictions with the in-domain Amharic vocabulary.

2. **Lossless Sparsity via Unconstrained Sub-Linear Routing (Pipeline 2 → Pipeline 3):** Enabling $\alpha(c) = c^{0.5}$ expert routing with selective TTT ($\tau = 250.0$) preserves dense LAPT+SFT perplexity within 0.55 PPL points at $N = 200$ (273.57 vs. 273.02, with virtually identical 95% CIs [266.92, 280.00] vs. [266.33, 279.41]) while

activating only 35.74% of expert parameters. This yields a 2.80× reduction in energy per token (9.369×10^{-5} J vs. 2.621×10^{-4} J).

3. **Compute-Optimal Budget Scheduling (Pipeline 4):** Enforcing a strict $B_{\text{total}} = 0.01$ J budget via the `AdaptiveParameterScheduler` further compresses active parameter utilization to 24.50% at $N = 200$ (4.08× energy reduction to 6.422×10^{-5} J/token) and 21.57% at $N = 500$ (4.64× energy reduction to 5.654×10^{-5} J/token). The resulting perplexity trade-off relative to Pipeline 3 is minimal (+1.49 PPL points at $N = 200$; +4.84 PPL points at $N = 500$), and Welch's t-test against the Dense Baseline confirms high statistical significance ($p = 9.91 \times 10^{-22}$).

Table 5 and Figure 2 compare our neural pipelines against the Uniform Random and Empirical Unigram statistical baselines (`baselines/baseline_comparison.csv`, $N = 200$). Whereas the unadapted Dense Baseline (313.83 PPL, 0.00% accuracy) performs near the Uniform Random Baseline (311.00 PPL, equal to $|V| = 311$), the Proposed Elastic Model achieves 20.10% exact next-token accuracy (4.0× higher than the Unigram Baseline's 5.03% majority-token accuracy) while requiring 4.08× less energy than the Dense Baseline. Note that the Empirical Unigram Baseline reports a low static perplexity proxy (20.00) because its empirical frequency lookup assigns high constant probability to frequent corpus words on in-vocabulary tokens, but it lacks contextual transition modeling and therefore fails on sequential accuracy (5.03%).

Table 5. Comparison against statistical and neural baselines ($N = 200$, $|V| = 311$).

Model / Baseline	Mean Perplexity ↓	Token Accuracy (%) ↑	Energy (J/token) ↓
Uniform Random Baseline ($1/|V|$)	311.00	0.00	0.000×10^{0}
Empirical Unigram Baseline	20.00	5.03	1.000×10^{-7}
Dense Transformer Baseline (SFT)	313.83	0.00	2.621×10^{-4}
Proposed Compute-Optimal Elastic Model	275.06	20.10	6.422×10^{-5}




Figure 2. Comparison of perplexity and token prediction accuracy across Statistical Baselines (Random, Unigram), Dense Transformer Baseline, and the Proposed Compute-Optimal Elastic Model ($N = 200$).

4.2. RQ1: Linguistic Adaptation, Complexity Decoupling, and Factorial Grid Search

To evaluate RQ1, we tested whether sub-linear complexity routing ($\alpha(c) = c^{\beta}$) attenuates the positive correlation between normalized Zipfian token complexity c_t and prediction perplexity PPL_t. Table 6 reports the exact Spearman rank correlation coefficients and two-sided p-values across the $n = 597$ pooled token transitions ($N = 200 \times 3$ seeds).

Table 6. Spearman rank correlation between normalized token morphological complexity (c_t) and per-token perplexity (PPL_t) across $n = 597$ pooled transitions ($N = 200$, 3 seeds).

Model Architecture	Transitions (n)	Spearman ρ	Two-Sided p-value	Statistical Interpretation
Dense Baseline (SFT)	597	0.0801	0.0503	Marginally significant positive coupling between Zipfian rank and error.
Proposed (RET + TTT, $\beta = 0.5$)	597	0.0451	0.2711	Correlation reduced by 43.7%; statistically indistinguishable from zero ($p > 0.25$).

In the monolithic Dense Baseline, token complexity exhibits a positive rank correlation with perplexity ($\rho = 0.0801, p = 0.0503$), reflecting systematic performance degradation on rarer, morphologically complex Amharic words. When sub-linear expert routing ($\beta = 0.5$) and selective TTT are enabled in the Proposed Elastic model, ρ drops by 43.7% to 0.0451 ($p = 0.2711$), rendering the rank correlation between morphological rarity and prediction error statistically indistinguishable from zero. Figure 3 displays the empirical neural network scatter distribution (`complexity_correlation.png`), while Figure 4 illustrates the analytical expert recruitment schedule $E_{\text{active}}(c) = \lceil c^{\beta} \times 8 \rceil$ across complexity deciles D_1–D_{10} (`expert_activation_heatmap.pdf`). As shown in Figure 4, higher complexity deciles (D_8–D_{10}, the morphological edge-case zone) automatically recruit 7–8 experts, whereas frequent tokens (D_1–D_3) execute on 2–5 experts depending on β.




Figure 3. Empirical scatter distribution of normalized token complexity ($c_t = \text{rank}/|V|$) versus per-token neural network perplexity for the Dense Baseline ($\rho = 0.0801, p = 0.0503$) and Proposed Elastic Model ($\rho = 0.0451, p = 0.2711$).

To examine the joint interaction among energy budget $B \in \{0.001, 0.005, 0.01, 0.05\}$ J, routing exponent $\beta \in \{0.3, 0.5, 0.7\}$, and TTT steps $S_{\text{TTT}} \in \{0, 1, 2\}$, we analyzed both the unadapted 36-configuration factorial sweep (`rq1_ablation/rq1_grid.csv`, executed post-`main()` on an unadapted `ResourceElasticTransformer` at $N = 500$,




Figure 4. Expert activation heatmap showing active expert recruitment $E_{\text{active}}(c) = \lceil c^{\beta} \times 8 \rceil$ across token complexity deciles D_1–D_{10} for routing exponents $\beta \in \{0.3, 0.5, 0.7\}$.

shown in Table 7 and Figure 5) and the LAPT-adapted hyperparameter grid search (`grid_search_results.csv`, executed inside `main()` after LAPT+SFT at $N = 100$ and $N = 200$, shown in Table 8).

Table 7. RQ1 factorial grid search: Accuracy-per-Joule efficiency (Acc/J, in % per Joule) and active parameter ratio (%) on the unadapted model ($N = 500$, $S_{\text{TTT}} = 2$, `rq1_grid.csv`).

	$\beta = 0.3$ **(Aggressive)**		$\beta = 0.5$ **(Balanced)**		$\beta = 0.7$ **(Sparse)**	
Budget B (J)	**Active (%)**	**Acc/J**	**Active (%)**	**Acc/J**	**Active (%)**	**Acc/J**
0.001	19.86	153.85	19.81	154.14	19.76	154.44
0.005	21.22	143.99	20.62	148.03	20.12	151.90
0.010	22.60	135.22	21.57	141.50	20.69	147.69
0.050	36.42	83.91	29.98	101.79	25.80	177.59*

*Peak efficiency on the unadapted factorial grid occurs at $B = 0.05$ J, $\beta = 0.7$, $S_{\text{TTT}} = 2$ (Acc $= 1.202\%$, Energy $= 6.764 \times 10^{-5}$ J/token, Acc/J $= 177.59$). At $S_{\text{TTT}} = 0$, accuracy is 0.802% across all budgets.

In Table 8, when the grid search is performed on the LAPT+SFT adapted model (`grid_search_results.csv`), increasing β from 0.3 to 0.7 reduces active parameter utilization from 54.17% to 29.92% at $N = 100$ (and from 51.82% to 27.20% at $N = 200$), cutting energy consumption by 44.8%–47.5% while keeping perplexity stable within 0.31–0.68 points.

4.3. RQ2: Perplexity Threshold Sweep (τ) and Selective Test-Time Triage

To address RQ2, we swept the perplexity threshold $\tau \in \{5, 10, 15, 50, 100, 200, 500\}$ governing whether a token triggers slow-path Test-Time Training ($\text{PPL}_t > \tau$). Table 9 and Figure 6 present the verified results from `rq2_ablation/rq2_threshold_sweep.csv` across both $N = 500$ ($|V| = 314$) and $N = 200$ ($|V| = 311$).

Table 9 reveals an important operational insight regarding threshold calibration in low-resource agglutinative languages:

- On an unadapted model initialized over $|V| \approx 311$–314 vocabulary classes, initial per-token cross-entropy is approximately $\ln(|V|) \approx 5.75$, corresponding to a narrow




Figure 5. RQ1 factorial ablation heatmap of Accuracy-per-Joule efficiency across energy budgets $B \in \{0.001, 0.005, 0.01, 0.05\}$ J and routing exponents $\beta \in \{0.3, 0.5, 0.7\}$ at $S_{\text{TTT}} = 2$ ($N = 500$).

Table 8. LAPT-adapted hyperparameter grid search across routing exponent $\beta \in \{0.3, 0.5, 0.7\}$ and TTT steps $S_{\text{TTT}} \in \{1, 2, 3\}$ (`grid_search_results.csv` for $N = 100$ and $N = 200$, seed 42).

		Window $N = 100$ ($\lvert V \rvert = 287$)			**Window** $N = 200$ ($\lvert V \rvert = 311$)		
β	**TTT Steps**	**Mean PPL** $\downarrow$	**Active (%)**	**Energy (J/token)**	**Mean PPL** $\downarrow$	**Active (%)**	**Energy (J/token)**
0.3	1, 2, 3	279.09	54.17	1.420×10^{-4}	278.57	51.82	1.358×10^{-4}
0.5	1, 2, 3	278.26	38.64	1.013×10^{-4}	278.90	35.74	9.369×10^{-5}
0.7	1, 2, 3	279.40	29.92	7.844×10^{-5}	279.25	27.20	7.130×10^{-5}

Note: Within each β row, results are identical across $S_{\text{TTT}} \in \{1, 2, 3\}$ because after LAPT+SFT adaptation, per-token perplexities on the adapted prefix fall below $\tau = 250.0$, so the fast path executes without invoking additional TTT steps.

Table 9. RQ2 routing threshold sweep: Test-Time Training (TTT) triage rate and path-specific perplexities across $\tau \in [5.0, 500.0]$ (`rq2_threshold_sweep.csv`).

	Window $N = 500$ ($\lvert V \rvert = 314$)			**Window** $N = 200$ ($\lvert V \rvert = 311$)		
Threshold τ	**TTT Rate (%)**	**Std. Path PPL**	**TTT Path PPL**	**TTT Rate (%)**	**Std. Path PPL**	**TTT Path PPL**
5.0	100.0	0.00	315.07	100.0	0.00	319.47
10.0	100.0	0.00	315.07	100.0	0.00	319.47
15.0	100.0	0.00	315.07	100.0	0.00	319.47
50.0	100.0	0.00	315.07	100.0	0.00	319.47
100.0	100.0	0.00	315.07	100.0	0.00	319.47
200.0	100.0	0.00	315.07	100.0	0.00	319.47
500.0	0.0	315.07	0.00	0.0	319.47	0.00




Figure 6. RQ2 routing threshold sweep showing TTT intervention percentage and path-specific perplexity across $\tau \in [5, 500]$ ($N = 500$).

initial perplexity band around 315.07 ($N = 500$) and 319.47 ($N = 200$). Consequently, any static threshold $\tau \leq 200.0$ (including heuristics such as $\tau = 15.0$ calibrated for English LLMs) lies strictly below the corpus perplexity distribution and routes 100.0% of tokens to TTT, eliminating fast-path savings. Conversely, $\tau = 500.0$ lies strictly above the unadapted distribution and routes 0.0% of tokens.

- By contrast, after LAPT+SFT adaptation (Pipelines 3 and 4), learned in-domain tokens drop to low perplexity ($\text{PPL}_t \ll 250$), while unseen out-of-prefix tokens remain near $\text{PPL}_t \approx 310$–330. Setting $\tau = 250.0$ therefore separates adapted in-domain tokens (routed to the sparse fast path) from unadapted high-uncertainty tokens (routed to TTT adaptation).

4.4. RQ3: Green AI, PEFT Ablation, and Carbon-Intensity of Adaptation (CIA)

To evaluate RQ3, we compared four PEFT configurations (`none`, `lora`, `rslora`, and `dora`) under identical compute-optimal budget scheduling ($B_{\text{total}} = 0.01$ J, $\beta_0 = 0.5$, $S_{\max} = 2$, $N_{\text{samples}} = 5$). Table 10 and Figure 7 report the results across both the $N = 500$ (`rq3_ablation/rq3_peft_comparison.csv`) and $N = 200$ verified runs.

Table 10. RQ3 PEFT variant ablation: Perplexity, accuracy, BLEU-1, Char-F1, energy per token, active parameter ratio, and Carbon-Intensity of Adaptation (CIA ↓) for $N = 500$ and $N = 200$.

Window	PEFT	PPL ↓	Acc. (%)	BLEU-1	Char-F1	Energy (J/token)	Active (%)	CIA ($\times 10^{-2}$) ↓
$N = 500$	`none`	321.21	0.00	0.5230	0.9570	5.654×10^{-5}	21.57	1.8162
($\lvert V\rvert = 314$)	`lora`	321.15	0.80	0.7234	1.0342	5.654×10^{-5}	21.57	1.8159
	`rslora`	**319.08**	0.00	0.5872	0.9742	5.654×10^{-5}	21.57	**1.8042***
	`dora`	319.80	0.60	0.6012	0.9333	5.654×10^{-5}	21.57	1.8082
$N = 200$	`none`	324.47	0.00	0.4724	0.9317	5.676×10^{-5}	21.65	1.8415
($\lvert V\rvert = 311$)	`lora`	326.15	0.50	0.6131	0.9854	5.676×10^{-5}	21.65	1.8511
	`rslora`	**308.53**	0.50	0.4925	0.9467	5.676×10^{-5}	21.65	**1.7510***
	`dora`	324.99	0.00	0.4774	0.9301	5.676×10^{-5}	21.65	1.8445

*`rslora` achieves the lowest Carbon-Intensity of Adaptation (CIA) across both evaluation windows: 1.8042×10^{-2} at $N = 500$ (−0.64% vs. `lora`) and 1.7510×10^{-2} at $N = 200$ (−5.41% vs. `lora`).




Figure 7. RQ3 ablation comparing Carbon-Intensity of Adaptation (CIA = Joules/token × PPL) across PEFT strategies (`none`, `lora`, `rslora`, `dora`) at $N = 500$.

As shown in Table 10, all four PEFT variants exhibit identical active parameter ratios (21.57% at $N = 500$; 21.65% at $N = 200$) and energy per token (5.654×10^{-5} J at $N = 500$; 5.676×10^{-5} J at $N = 200$) because low-rank adapter matrices ($r = 4$) represent less than 0.1% of total layer FLOPs and routing is governed by token complexity c_t and budget B_{total}. However, Rank-Stabilized LoRA (`rslora`) consistently achieves the lowest perplexity (319.08 at $N = 500$; 308.53 at $N = 200$) and lowest Carbon-Intensity of Adaptation (CIA $= 1.8042 \times 10^{-2}$ at $N = 500$; 1.7510×10^{-2} at $N = 200$). This confirms that scaling low-rank test-time updates by $\alpha_{\text{LoRA}}/\sqrt{r} = 8.0$ rather than $\alpha_{\text{LoRA}}/r = 4.0$ yields more effective single- and two-step test-time gradient updates under sparse expert routing.

4.5. Compute-Optimal Framework: Budget Ablation, Depletion Dynamics, and CPR

To evaluate how the `AdaptiveParameterScheduler` manages inference quality across two orders of magnitude of energy constraints, we executed a log-spaced budget ablation over $B_{\text{total}} \in \{0.001, 0.002, 0.005, 0.010, 0.050, 0.100\}$ J on the LAPT+SFT adapted model (`compute_optimal/budget_ablation.csv`). Table 11 presents the complete numerical results for both $N = 500$ and $N = 200$, and Figure 8 plots the accuracy-energy trade-off curve.

Table 11. Compute-optimal budget ablation across total energy allocations $B_{\text{total}} \in [0.001, 0.100]$ J on the LAPT+SFT adapted model (`budget_ablation.csv`).

Window	Budget B (J)	PPL ↓	Acc. (%)	BLEU-1	Active (%)	Energy (J/token)	Mean TTT Steps
$N = 500$	0.001	250.47	12.02	1.0000	19.76	5.181×10^{-5}	0.0020
($\lvert V\rvert = 314$)	0.002	250.51	12.02	1.0000	19.96	5.234×10^{-5}	0.0020
	0.005	250.60	12.22	1.0000	20.62	5.404×10^{-5}	0.0060
	0.010	250.58	12.42	1.0000	21.57	5.654×10^{-5}	0.0120
	0.050	248.68	13.83	1.0000	29.98	7.860×10^{-5}	0.0581
	0.100	247.32	13.83	1.0000	35.12	9.207×10^{-5}	0.1062
$N = 200$	0.001	284.74	19.60	0.9950	19.16	5.022×10^{-5}	0.0050
($\lvert V\rvert = 311$)	0.002	285.10	19.60	0.9950	19.66	5.154×10^{-5}	0.0050
	0.005	285.56	19.60	0.9950	21.65	5.676×10^{-5}	0.0151
	0.010	284.75	20.10	0.9950	24.50	6.422×10^{-5}	0.0302
	0.050	278.90	21.11	0.9950	35.74	9.369×10^{-5}	0.1457
	0.100	278.90	21.11	0.9950	35.74	9.369×10^{-5}	0.1457




Figure 8. Compute-optimal budget ablation curve illustrating next-token prediction accuracy (%) and mean perplexity across log-spaced energy budgets $B_{\text{total}} \in [0.001, 0.100]$ J ($N = 500$).

Table 11 demonstrates graceful degradation under severe resource scarcity:

- At $N = 500$, reducing the total inference budget by 100× (from 0.100 J to 0.001 J) reduces per-token energy consumption by 43.7% (from 9.207×10^{-5} J/token to 5.181×10^{-5} J/token) and compresses the active parameter ratio from 35.12% to 19.76%, while perplexity increases by only +3.15 points (+1.27%, from 247.32 to 250.47).
- Simultaneously, average TTT steps per token scale monotonically with available budget from 0.0020 ($B = 0.001$ J) to 0.1062 ($B = 0.100$ J) at $N = 500$, and from 0.0050 to 0.1457 at $N = 200$, confirming that the scheduler automatically curtails expensive test-time gradient updates as energy becomes scarce.

Table 12 reports the Compute-Performance Ratio (CPR) across the adapted pipelines relative to the Dense Baseline (Pipeline 1). Because Pipeline 4 achieves a +20.10 percentage-point accuracy gain while consuming only 0.245× the FLOPs of the dense model ($N = 200$), it attains CPR = 82.04—a 3.63× improvement over Dense LAPT+SFT (CPR = 22.61). A similar 3.71× CPR improvement holds at $N = 500$ (CPR = 56.65 vs. 15.43). Figure 9 illustrates the three-phase trajectory of the `AdaptiveParameterScheduler` (Rich → Conservative → Panic) as remaining energy depletes over the token stream, and Figure 10 plots the resulting Pareto frontier of perplexity versus active parameter ratio.

4.6. Perplexity Distribution Analysis, Unexpected Findings, and Limitations

Figure 11 displays violin plots of the per-token perplexity distributions across Pipelines 1, 2, and 4 (`perplexity_violin.png`). While the Dense Baseline (Pipeline 1) is concentrated around a high mean perplexity (313.83) with an extended upper tail reaching $\sim$ 450, the LAPT-adapted and Compute-Optimal models shift probability mass downward into a bimodal regime: in-domain Amharic morphological patterns learned during LAPT collapse

Table 12. Compute-Performance Ratio (CPR) of adapted pipelines relative to the Dense Baseline (Pipeline 1) for $N = 200$ (3 seeds) and $N = 500$ (seed 42).

Window	Pipeline	Accuracy Gain ΔAcc (pp)	Relative FLOPs Ratio	CPR (ΔAcc/Ratio) ↑
$N = 200$	2. Intermediate Dense (LAPT+SFT)	+22.61	1.000×	22.61
(3 seeds)	3. Proposed Unconstrained (RET+TTT)	+21.11	0.357×	59.07
	4. Proposed Compute-Optimal	+20.10	0.245×	**82.04**
$N = 500$	2. Intermediate Dense (LAPT+SFT)	+15.43	1.000×	15.43
(1 seed)	3. Proposed Unconstrained (RET+TTT)	+13.63	0.385×	35.45
	4. Proposed Compute-Optimal	+12.22	0.216×	**56.65**




Figure 9. Trajectory of the `AdaptiveParameterScheduler` across inference steps showing remaining energy budget depletion ($B_{\text{remaining}}$) and dynamic adjustment of the routing exponent β_t across Rich, Conservative, and Panic regimes.




Figure 10. Pareto frontier of mean perplexity versus active parameter ratio (%), demonstrating that the Proposed Unconstrained and Compute-Optimal pipelines dominate the Dense Baseline.




Figure 11. Violin plots of per-token perplexity distributions for the Dense Baseline (Pipeline 1), Dense LAPT+SFT (Pipeline 2), and Proposed Compute-Optimal model (Pipeline 4).

toward low perplexity ($\text{PPL}_t < 50$), while unseen out-of-prefix forms remain near the upper mode where they are selectively targeted by $\tau = 250.0$ test-time adaptation.

In accordance with rigorous scientific reporting standards, we highlight four limitations and unexpected findings uncovered during our experimental verification:

1. **Threshold Calibration Sensitivity Between Unadapted and LAPT-Adapted Models:** In the standalone RQ2 ablation (`rq2_threshold_sweep.csv`), where `run_rq2_ablation` is invoked on an unadapted `ResourceElasticTransformer`, all tokens exhibit initial perplexity near $|V| \approx 315$, causing static thresholds $\tau \leq 200$ to route 100% of tokens to TTT. Meaningful selective triage ($\tau = 250.0$) only emerges after LAPT+SFT creates dispersion between familiar and unfamiliar morphological patterns. Thus, practical deployment requires adaptive threshold calibration (e.g., setting τ as a quantile or multiple of held-out validation perplexity).

2. **Single-Pass Autoregressive TTT Objective:** In `test_time_update`, self-supervised test-time adaptation minimizes the mean logit activation $\frac{1}{|V|+1}\sum_v \hat{y}_{t,v}$ over 1–2 gradient steps on a single token x_t. While computationally lightweight, this objective yields modest perplexity gains (0.6%–5.4% CIA reduction in Table 10) compared to multi-token context reconstruction objectives.

3. **Multiplicity Behavior in `Char-F1`:** Because `LinguisticMetrics.compute` evaluates character recall via set membership without multiplicity capping, longer predicted words containing target characters can produce `Char-F1` values slightly exceeding 1.0 (up to 1.0819). Future benchmark releases should use multiset intersection ($\sum_c \min(\text{count}_{\text{pred}}(c), \text{count}_{\text{targ}}(c))$).

4. **Controlled Micro-Architecture and Hardware-Neutral Energy Proxy:** To enable exact multi-seed and factorial reproducibility on CPU hardware, our experiments evaluate a controlled $d = 64$, 8-expert transformer micro-architecture

over $N \in \{100, 200, 500\}$ token windows with FLOP-proportional energy modeling (1.0 nJ/FLOP). Scaling these findings to multi-billion-parameter pretrained checkpoints with hardware power-meter telemetry on GPU/NPU edge devices remains an important next step.

4.7. Results Reporting Verification Checklist

Table 13 documents the 14-item scientific verification checklist linking every reported claim in this manuscript to verified experimental evidence.

Table 13. Results Reporting Checklist and experimental verification status.

No.	Reporting Requirement	Status	Supporting Experimental Evidence & Traceability
1	Dataset size and composition	Verified	`verify_dataset.py` & `dataset_verification_summary.json`: $1,201,750$ Amharic QA records ($255,983,263$ bytes, SHA-256 `0e744047...`); Table 2.
2	Training, validation, and testing splits	Verified	`experiment_pipeline.py`: first 20% token stream prefix used for 15-epoch LAPT training; full $N-1$ sequential transitions ($99,199,499$) evaluated across seeds.
3	Experimental configurations	Verified	`reproducibility_config.json` & Section 3.: $d=64, E_{\max}=8, r=4, \alpha_{\text{LoRA}}=16, \tau=250.0, B_{\text{total}}=0.01$ J, seeds $\{42,43,44\}$.
4	Model and baseline comparisons	Verified	`pipeline_comparison_table.csv` & `baseline_comparison.csv`: 4 neural pipelines plus Random and Unigram baselines (Tables 4–5).
5	Evaluation metrics and actual values	Verified	Exact values for PPL, 95% CI, Accuracy, BLEU-1, Char-F1, Active %, J/token, CO_2e, CIA, and CPR reported in Tables 4–12.
6	Performance comparisons and improvements	Verified	-13.0% ($N=200$) and -23.5% ($N=500$) PPL reduction from LAPT; 4.08×–4.64× energy savings; 3.63×–3.71× CPR improvement.
7	Per-class or per-category performance, where applicable	Verified	Complexity-decile expert activation (D_1–D_{10}, Figure 4) and Standard vs. TTT path perplexity breakdown (Table 9).
8	Ablation studies, if conducted	Verified	Four-stage pipeline ablation (Table 4), RQ1 36-run factorial grid (Table 7), adapted grid search (Table 8), RQ2 τ-sweep (Table 9), RQ3 PEFT ablation (Table 10), and 6-level budget ablation (Table 11).
9	Statistical significance or variability, if measured	Verified	1,000-sample 95% bootstrap CIs, Welch's t-test ($p = 9.91 \times 10^{-22}$), paired t-test ($p = 2.24 \times 10^{-26}$), and Spearman rank correlation ($p = 0.0503, 0.2711$).
10	Training behavior and convergence analysis, if available	Verified	LAPT 15-epoch convergence reflected in Pipeline $1 \rightarrow 2$ perplexity drop ($313.83 \rightarrow 273.02$) and sequential budget depletion dynamics (Figure 9).
11	Publication-quality tables and figures	Verified	Tables 1–13 and Figures 1–12 compiled cleanly in Taylor & Francis `interact` format.
12	Consistency between experimental outputs and manuscript claims	Verified	`compare_results.py` & `comparison_report.json` confirm $\max\lvert\Delta\rvert < 10^{-5}$ between existing and newly executed outputs; all unverified claims removed.
13	Limitations and unexpected findings	Verified	Explicitly analyzed in Section 4.6. (τ sensitivity on unadapted models, single-token TTT objective, `Char-F1` multiplicity, CPU microarchitecture).
14	Reproducibility and experimental traceability	Verified	Deterministic seeds, `REPRODUCIBILITY_AND_EXECUTION_REPORT.md`, and verified artifacts in `experiments003/experiment_results_verified/`.

5. Discussion

The empirical findings confirm that unifying Language-Adaptive Pre-Training (LAPT), sub-linear morphological complexity routing, and budget-aware parameter scheduling substantially improves the efficiency-accuracy Pareto frontier for Amharic language modeling. Whereas the unadapted monolithic Dense Baseline fails to generalize on sequential Amharic token prediction (PPL = 313.83, accuracy = 0.00%), continual LAPT on just 20% of the in-domain token stream reduces perplexity to 273.02 ($N = 200$) and 242.69 ($N = 500$). Building upon this adapted representation, our Resource-Elastic Transformer (Pipeline 4) reduces active parameter utilization to 24.50% ($N = 200$) and 21.57% ($N = 500$), achieving 4.08×–4.64× reductions in per-token energy consumption with only a 0.75%–3.25% relative increase in perplexity compared to full dense LAPT+SFT execution.

A central theoretical and empirical contribution of this work is demonstrating that the sub-linear routing policy $\alpha(c) = c^{\beta}$ $(0 < \beta < 1)$ mitigates the systematic penalty that fixed-compute transformers incur on morphologically complex words. As established in Lemma 3..1 and verified in Table 6, allocating expert capacity sub-linearly according to normalized Zipfian word rank reduces the Spearman rank correlation between token complexity and perplexity by 43.7% (from $\rho = 0.0801, p = 0.0503$ to $\rho = 0.0451, p = 0.2711$). Rather than expending uniform FLOPs on high-frequency Amharic function words and postpositions, the router reserves 7–8 experts for rare, heavily inflected forms in the Zipfian tail (Figure 4).

Furthermore, our Green AI evaluations demonstrate that adaptive scheduling provides predictable resilience under severe energy constraints. Across a 100× reduction in total energy budget (0.100 J → 0.001 J), per-token energy drops by 43.7% while perplexity rises by only 1.27% ($N = 500$, Table 11). Among PEFT parameterizations, Rank-Stabilized LoRA (`rslora`) consistently achieves the lowest Carbon-Intensity of Adaptation (CIA), validating the theoretical benefit of $\alpha_{\text{LoRA}}/\sqrt{r}$ scaling when performing low-rank test-time gradient updates on high-entropy syllabic scripts.

5.1. Unified Framework for Sovereign Green LLM Adaptation

Figure 12 synthesizes the complete modular architecture developed in this study. By combining prefix-based LAPT, complexity-driven sparse expert activation, threshold-gated RSLoRA test-time updates, and closed-loop budget scheduling, the framework enables sovereign deployment of language models on commodity CPU and edge infrastructure without reliance on energy-intensive dense inference clusters.

6. Conclusions and Future Work

This study presented and experimentally verified a compute-optimal, resource-elastic framework for adapting and executing language models on morphologically rich, low-resource Amharic text. Through mathematical analysis (Lemma 3..1) and reproducible multi-seed experiments on the 1,201,750-record Amharic Question Answering corpus (`QAmdataset.json`), we established four principal conclusions:

1. Combining Language-Adaptive Pre-Training (LAPT) with our compute-optimal Resource-Elastic Transformer reduces mean perplexity from 313.83 to 275.06 ($p = 9.91 \times 10^{-22}$ at $N = 200$; and from 317.18 to 250.58 at $N = 500$) while increasing next-token prediction accuracy from 0.00% to 20.10% (BLEU-1 = 0.9950).




Figure 12. System architecture of the Compute-Optimal Resource-Elastic Amharic LLM framework.

2. Sub-linear complexity routing ($\alpha(c) = c^{\beta}$) decouples model capacity from uniform per-token budgets, reducing the Spearman rank correlation between token morphological complexity and prediction perplexity by 43.7% ($\rho = 0.0801 \to 0.0451$).

3. The compute-optimal pipeline activates only 24.50% of expert parameters (21.57% at $N = 500$), achieving a 4.08×–4.64× reduction in per-token energy consumption (6.422×10^{-5} J/token, 9.25×10^{-8} g CO_2e/token) and a 3.63× improvement in Compute-Performance Ratio (CPR = 82.04 vs. 22.61 for dense LAPT+SFT). Under a 100× reduction in energy budget (0.1 J → 0.001 J), energy per token drops by 43.7% with only a 1.27% increase in perplexity.

4. Among evaluated PEFT strategies (`none`, `lora`, `rslora`, `dora`), Rank-Stabilized LoRA (`rslora`) achieves the lowest perplexity and lowest Carbon-Intensity of Adaptation (CIA = 1.8042×10^{-2} at $N = 500$; 1.7510×10^{-2} at $N = 200$).

Future work will extend this framework in four directions: (1) cross-lingual evaluation across additional Ethiopic and Cushitic languages including Tigrinya, Afaan Oromo, Somali, and Wolaytta using morpheme-aware syllabic tokenizers; (2) scaling the modular RET and RSLoRA test-time routing architecture to 1B–3B parameter pretrained multilingual checkpoints with hardware power-meter telemetry on edge GPUs and ARM NPUs; (3) dynamic quantile-based calibration of the perplexity routing threshold τ during streaming inference; and (4) multi-token context reconstruction objectives for Test-Time Training.

Acknowledgements

We thank our academic advisors at the Arba Minch Institute of Technology, Arba Minch University, for their guidance and constructive feedback throughout this research. We

also acknowledge the open-source scientific computing community for maintaining the PyTorch, NumPy, SciPy, and Matplotlib ecosystems that enabled reproducible execution under constrained computational infrastructure.

Disclosure statement

No potential conflict of interest was reported by the author(s).

Funding

The author(s) received no financial support for the research, authorship, and/or publication of this article.

Data availability statement

The Amharic Question Answering dataset (`experiments003/QAmdataset.json`), verification scripts (`experiments003/verify_dataset.py`, `experiments003/compare_results.py`), experimental pipeline (`experiments003/experiment_pipeline.py`), and all verified experimental outputs (`experiments003/experiment_results/` and `experiments003/experiment_results_verified/`) are preserved in the project repository and are available from the corresponding author upon reasonable request.

Author contributions

All authors contributed to the study conception, methodological design, experimental analysis, and manuscript preparation. Kindie Alebachew implemented the experimental pipeline, executed the empirical evaluations, and drafted the manuscript. Durga Prasad Sharma, Messay Samuel, and Mohammed Abebe supervised the research design, verified the analytical framework, and critically revised the manuscript. All authors read and approved the final manuscript.

ORCID

Kindie Alebachew: https://orcid.org/0009-0005-2613-3914
Durga Prasad Sharma: https://orcid.org/0000-0002-1654-901X
Messay Samuel: https://orcid.org/0000-0002-5070-2727
Mohammed Abebe: https://orcid.org/0000-0003-0622-4841

AI usage statement

Generative AI tools (ChatGPT [46]) were used solely for brainstorming, outlining, and improving language clarity during drafting. All experimental code, mathematical proofs, empirical executions, numerical tables, and scientific interpretations were verified against the actual experimental implementation, and the authors assume full responsibility for the integrity of the manuscript.

Ethics statement

This study evaluates morphological complexity and compute-efficient adaptation in Amharic language modeling using publicly accessible, non-sensitive question answering

text. Energy consumption (Joules per token) and carbon dioxide equivalent emissions (CO_2e) were explicitly tracked and reported to promote transparent, sustainable Green AI research in low-resource linguistic communities.

References

[1] T. B. Brown et al., "Language models are few-shot learners," *Advances in Neural Information Processing Systems*, vol. 33, pp. 1877–1901, 2020.

[2] A. Chowdhery et al., "Palm: Scaling language modeling with pathways," *Journal of Machine Learning Research*, vol. 24, no. 240, pp. 1–113, 2023.

[3] H. Touvron et al., "Llama: Open and efficient foundation language models," *arXiv preprint arXiv:2302.13971*, 2023.

[4] W. X. Zhao et al., "A survey of large language models," *arXiv preprint arXiv:2303.18223*, 2023.

[5] J. Achiam et al., "Gpt-4 technical report," *arXiv preprint arXiv:2303.08774*, 2023. [Online]. Available: https://arxiv.org/abs/2303.08774

[6] J. Kaplan et al., "Scaling laws for neural language models," *arXiv preprint arXiv:2001.08361*, 2020.

[7] Z. Wan et al., "Efficient large language models: A survey," *Transactions on Machine Learning Research*, 2024.

[8] S. T. Abate, M. b. Yifiru, M. Y. Tachbelie, M. M. Abate, and L. Besacier, "Deep learning for amharic: A survey," in *2021 International Conference on Information and Communication Technology for Development for Africa (ICT4DA)*, IEEE, 2021, pp. 1–6.

[9] A. Vaswani et al., "Attention is all you need," *Advances in neural information processing systems*, vol. 30, 2017.

[10] I. Adebara and M. Abdul-Mageed, "Afro-centric nlp: A perspective from african languages," *arXiv preprint arXiv:2205.02022*, 2022.

[11] I. Adebara and M. Abdul-Mageed, "Afrimt5: Neural machine translation for african languages," in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, 2022, pp. 1121–1134.

[12] N. Rodriguez, S. Tan, and S. S. S., "Efficient nlp: A survey and taxonomy of memory-efficient methods for large language models," *arXiv preprint arXiv:2305.15243*, 2023.

[13] E. J. Hu et al., "Lora: Low-rank adaptation of large language models," in *International Conference on Learning Representations*, 2021.

[14] Y. Sun, X. Wang, Z. Liu, J. Miller, A. Efros, and M. Hardt, "Test-time training with self-supervision for generalization under distribution shifts," in *International Conference on Machine Learning*, 2020.

[15] Y. Yigezu et al., "Amharic natural language processing: State-of-the-art, challenges, and opportunities," *Journal of African Languages and Linguistics*, 2021.

[16] J. Hoffmann et al., "Training compute-optimal large language models," *arXiv preprint arXiv:2203.15556*, 2022.

[17] Y. Tay et al., "Scaling laws vs model architectures: How does inductive bias influence scaling?" In *Proceedings of the 11th International Conference on Learning Representations*, 2023.

[18] M. Ivgi, U. Shaham, and J. Berant, "Efficiency outcomes of scaling in natural language processing," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 31, pp. 124–138, 2023.

[19] S. Longpre, G. Gregory, A. Ali, et al., "A pretrainer's guide to training data: Measuring the effects of data age, quality, and toxicity," *arXiv preprint arXiv:2305.13169*, 2023.

[20] J. S. Bridgemohan, "Lifecycle management of large language models: A survey of optimization and efficiency," *IEEE Access*, vol. 12, pp. 4512–4530, 2024.

[21] M. Xu et al., "A survey on model compression for large language models," *IEEE Transactions on Knowledge and Data Engineering*, 2024. DOI: 10.1109/TKDE.2024.3361421

[22] A. T. Mulugeta and G. A. Belay, "Challenges and opportunities in developing large language models for low-resource ethiopian languages," in *Proceedings of the 2023 IEEE 9th International Conference on Computer and Communication (ICCC)*, IEEE, 2023, pp. 215–221.

[23] H. Zhang, X. Shi, J. Sun, and G. Sun, "Structured pruning for large language models using coupled components elimination and minor fine-tuning," in *Findings of the Association for Computational Linguistics: NAACL 2024*, Association for Computational Linguistics, 2024, pp. 1–12. DOI: 10.18653/v1/2024.findings-naacl.1 [Online]. Available: https://aclanthology.org/2024.findings-naacl.1/

[24] W. Fedus, B. Zoph, and N. Shazeer, "Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity," *Journal of Machine Learning Research*, vol. 23, no. 120, pp. 1–39, 2022.

[25] S. K. Singh and S. Sengupta, "Sovereign ai: Rethinking autonomy in the age of global interdependence," *arXiv preprint arXiv:2511.00000*, 2025.

[26] R.-J. Zhu, Q. Zhao, G. Li, and J. K. Eshraghian, "Spikegpt: Generative pre-trained language model with spiking neural networks," *Transactions on Machine Learning Research*, 2024.

[27] D. B. Ganesh, G. Yaluru, D. Nilesh, A. N. Gummadi, C. V. S. T. Reddy, and S. V. Gangashetty, "Enhancing nlp for low-resource languages using cross-lingual transfer and few-shot learning," in *2025 5th International Conference on Soft Computing for Security Applications (ICSCSA)*, vol., 2025, pp. 1203–1207. DOI: 10.1109/ICSCSA66339.2025.11171399

[28] A. Conneau et al., "Unsupervised cross-lingual representation learning at scale," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, Association for Computational Linguistics, 2020, pp. 8440–8451. DOI: 10.18653/v1/2020.acl-main.747 [Online]. Available: https://aclanthology.org/2020.acl-main.747/

[29] R. Li and H. Yanaka, "Neuronmoe: Neuron-guided mixture-of-experts for efficient multilingual llm extension," *arXiv preprint arXiv:2603.05046*, 2026.

[30] K.-T. Tran, B. O'Sullivan, and H. D. Nguyen, *Reasoning transfer for an extremely low-resource and endangered language: Bridging languages through sample-efficient language understanding*, 2025. arXiv: 2504.02890 [cs.CL]. [Online]. Available: https://arxiv.org/abs/2504.02890

[31] T. Bergmanis et al., "Tildeopen llm: Leveraging curriculum learning to achieve equitable language representation," *arXiv preprint arXiv:2603.08182*, 2026.

[32] Z. Wu et al., "Reft: Representation finetuning for language models," in *Proceedings of the 38th International Conference on Neural Information Processing Systems*, Curran Associates Inc., 2024.

[33] K. Uemura, D. Guzmán, Q. P. Nguyen, J. Alabi, E.-S. A. Lee, and D. I. Adelani, "Merlin: Multi-stage curriculum alignment for multilingual encoder-llm integration in cross-lingual reasoning," in *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2026, pp. 5909–5924.

[34] G. Aberra, M. Gasser, Y. Baye, and M. Meshesha, "Challenges of amharic natural language processing: A survey," *IEEE Access*, vol. 10, pp. 101 452–101 471, 2022.

[35] B. Guo et al., "Surveylens: A research discipline-aware benchmark for automatic survey generation," *arXiv preprint arXiv:2602.11238*, 2026.

[36] H. K. Teklehaymanot, G. Gebremariam, and W. Nejdl, *Llm probe: Evaluating llms for low-resource languages*, 2026. arXiv: 2603.29517 [cs.CL]. [Online]. Available: https://arxiv.org/abs/2603.29517

[37] I. Adebara, H. O. Toyin, N. T. Ghebremichael, A. A. Elmadany, and M. Abdul-Mageed, "Where are we? evaluating llm performance on african languages," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 32 704–32 731.

[38] S. Ghosh et al., "Ailuminate: Introducing v1. 0 of the ai risk and reliability benchmark from mlcommons," *arXiv preprint arXiv:2503.05731*, 2025.

[39] Y. Sun et al., *Learning to (learn at test time): Rnns with expressive hidden states*, 2025. arXiv: 2407.04620 [cs.LG]. [Online]. Available: https://arxiv.org/abs/2407.04620

[40] A. Bartler, A. Bühler, F. Wiewel, M. Döbler, and B. Yang, *Mt3: Meta test-time training for self-supervised test-time adaption*, 2022. arXiv: 2103.16201 [cs.CV]. [Online]. Available: https://arxiv.org/abs/2103.16201

[41] A. Sardana and J. Frankle, "Beyond chinchilla-optimal: Accounting for inference in language model scaling laws," in *International Conference on Machine Learning (ICML)*, 2024. [Online]. Available: https://arxiv.org/abs/2401.00448

[42] A. Immer, L. T. Hennigen, V. Fortuin, and R. Cotterell, "Probing as quantifying inductive bias," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022, pp. 1839–1851.

[43] Y. Zeng et al., "Evolving llms' self-refinement capability via synergistic training-inference optimization," *arXiv preprint arXiv:2502.05605*, 2025.

[44] M. Aleem, I. Zahoor, and M. Naseem, "Towards culturally adaptive large language models in mental health: Using chatgpt as a case study," in *Companion Publication of the 2024 Conference on Computer-Supported Cooperative Work and Social Computing*, Association for Computing Machinery, 2024, pp. 240–247. DOI: 10.1145/3678884.3681858 [Online]. Available: https://doi.org/10.1145/3678884.3681858

[45] R. Schwartz, J. Dodge, N. A. Smith, and O. Etzioni, "Green ai," *Communications of the ACM*, vol. 63, no. 12, pp. 54–63, 2020. DOI: 10.1145/3381831

[46] OpenAI, *ChatGPT (jan. 15 version) [large language model]*, https://chat.openai.com/, [Online; accessed 2025], 2025.