

# Creating and Adding a Preset

MiniMax H3 RunPod Installer — practical guide

A **preset** downloads a specific set of model files (often outside the three standard tiers `light` / `balanced` / `max`) and installs the matching ComfyUI workflow — **on top of** the regular install, never changing it. Leaving it unset (`H3_PRESETS` empty, the default) reproduces exactly the project's behavior before this feature existed.

This document explains how to **use** an existing preset, then, step by step, how to **create a new one** — using the real `aistudynow` preset already shipped with the project as the working example.

**NOTE** — A preset never affects `--tier` or `--workflows`. It only adds extra files, idempotently (a file that's already present and valid is never re-downloaded).

## 1. Using an existing preset

Two ways to activate one or more presets, whichever you prefer:

```
# On the command line
bash install.sh --preset=aistudynow
bash install.sh --only-models --preset=aistudynow # (re)download just this preset

# Several presets at once (comma-separated, no spaces)
bash install.sh --preset=aistudynow,other_preset
```

Or set it permanently in `config.env`:

```
H3_PRESETS="aistudynow"
```

An unknown preset name is ignored with a simple warning — never a blocking error.

## 2. Files involved in the project

|                              |                                                                                                                                                                   |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>config.env</b>            | Registry of known presets, and the manifest (which files, from which repo, into which folder) for each preset.                                                    |
| <b>lib/presets.sh</b>        | Generic engine: resolves <code>--preset=</code> , checks Hugging Face access, downloads files, installs the workflow. <b>Never needs editing</b> to add a preset. |
| <b>presets/&lt;name&gt;/</b> | Folder holding the ComfyUI workflow file(s) ( <code>.json</code> ) for the preset.                                                                                |
| <b>install.sh</b>            | Calls <code>resolve_h3_presets</code> , <code>download_preset_models</code> and <code>install_preset_workflows</code> after the standard install.                 |

→ Adding a preset therefore only touches `config.env` (3 registry/manifest lines) **and** a workflow `.json` file. `lib/presets.sh` stays generic and never needs to change.

### 3. Creating a new preset — step by step

Running example: we create a preset named mypreset.

#### 1 Pick a short, lowercase name

Letters/digits/underscore only (it's used as a bash variable suffix: PRESET\_MYPRESET). No spaces, no accents.

#### 2 For each model file, identify three pieces of information

|                      |                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| repo                 | The exact Hugging Face repo, e.g. Kijai/MiniMax-H3-experimental.                                                                                                    |
| path within the repo | The path exactly as it appears in the Hugging Face URL after .../resolve/main/ — it may include a subfolder (loras/xxx.safetensors) or not (file at the repo root). |
| local ComfyUI folder | Where the file must land under ComfyUI/models/: diffusion_models, vae, loras, text_encoders, etc.                                                                   |

#### 3 Add the manifest in config.env

In the Presets section of config.env, three changes:

##### a) Register the name

```
H3_PRESET_NAMES=(aistudynow mypreset)
```

##### b) Declare the manifest — an array PRESET\_<UPPERCASE\_NAME>, one line per file, format "repo|path\_in\_repo|local\_folder":

```
# shellcheck disable=SC2034
PRESET_MYPRESET=(
  "SomeAuthor/SomeRepo|diffusion_models/my_model.safetensors|"
  "SomeAuthor/SomeRepo|my_root_vae.safetensors|vae"
  "SomeAuthor/SomeRepo|loras/my_lora.safetensors|"
)
```

##### c) Attach the preset's workflow:

```
declare -A H3_PRESET_WORKFLOWS=(
  [aistudynow]="presets/aistudynow/MiniMax_H3_REF2V_AIStudyNow.json"
  [mypreset]="presets/mypreset/My_Workflow.json"
)
```

## The “local folder” field, in detail

This is the easiest part to get wrong. The rule: the local folder should be left empty *only if* the repo path already contains the right subfolder.

|                                             |                                                                                                                                                                                                                                            |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Repo path WITH a subfolder</b>           | e.g. <code>text_encoders/my_encoder.safetensors</code> or <code>loras/my_lora.safetensors</code> → local folder <b>empty</b> (""). The file lands in <code>models/text_encoders/...</code> or <code>models/loras/...</code> automatically. |
| <b>Repo path AT THE ROOT (no subfolder)</b> | e.g. <code>my_model.safetensors</code> → local folder must be set explicitly, e.g. <code>diffusion_models</code> or <code>vae</code> , otherwise the file ends up at the root of <code>models/</code> — ComfyUI won't find it.             |

**HEADS UP** — Double-check the exact filename and path directly in the “Files” tab of the Hugging Face repo (not just the download URL, which may have been copied from a README and contain a typo).

### 4 Drop in the workflow file

Export the ComfyUI workflow (“Export” / “Save (API format)” as needed — usually the non-API format for a direct import into the UI) and place it in a new folder:

```
mkdir -p presets/mypreset
cp my_exported_workflow.json presets/mypreset/My_Workflow.json
```

The filename must match exactly what was set in `H3_PRESET_WORKFLOWS` in step 3c.

### 5 Test it

```
bash install.sh --only-models --preset=mypreset
```

Check the output for: repo access confirmed, each file downloaded into the right subfolder of ComfyUI/models/, then the workflow copied into ComfyUI/user/default/workflows/. Running it again later with nothing changed re-downloads nothing (idempotent).

## 4. Full example already in place: “aistudynow”

The preset shipped with the project illustrates both cases (file at the repo root / file already in the right subfolder):

```
H3_PRESET_NAMES=(aistudynow)

PRESET_AISTUDYNOW=(
  "Kijai/MiniMax-H3-experimental|minimax_h3_ref2va_pruned_w4a8_mixed.safetensors|diffusion_models"
  "Kijai/MiniMax-H3-experimental|minimax_h3_video_vae_int8_convrot.safetensors|vae"
  "Kijai/MiniMax-H3-experimental|loras/minimax_h3_ref_lora_rank_256_bf16.safetensors|"
  "Comfy-Org/MiniMax-H3|text_encoders/qwen3vl_32b_minimax_h3_nvfp4_awq.safetensors|"
  "Comfy-Org/MiniMax-H3|vae/minimax_h3_audio_vae_fp32.safetensors|"
)

declare -A H3_PRESET_WORKFLOWS=(
  [aistudynow]="presets/aistudynow/MiniMax_H3_REF2V_AIStudyNow.json"
)
```

The first two lines come from a repo where the files sit at the root → local folder set explicitly (diffusion\_models, vae). The last three come from files already placed in the right repo subfolder → local folder left empty. The last two files (text encoder, audio VAE) are also used by the standard install: if already present, they are not re-downloaded.

## 5. Cheat sheet

```
# Use a preset
bash install.sh --preset=<name>
bash install.sh --only-models --preset=<name>

# Create a preset <name> – 4 actions
1. config.env : add <name> to H3_PRESET_NAMES
2. config.env : declare PRESET_<UPPERCASE_NAME>=("repo|repo_path|local_folder" ...)
3. config.env : attach the workflow in H3_PRESET_WORKFLOWS[<name>]
4. presets/<name>/ : drop the workflow .json file there
```

**NOTE** — No change to lib/presets.sh or install.sh is needed to add a preset: the engine is fully generic and reads the registry from config.env.