



<http://algs4.cs.princeton.edu>

4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ *context*



<http://algs4.cs.princeton.edu>


4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ *context*

Minimum spanning tree

Def. A **spanning tree** of G is a subgraph T that is:

- Connected.
- Acyclic.
- Includes all of the vertices.




graph G

Minimum spanning tree

Def. A **spanning tree** of G is a subgraph T that is:

- Connected.
- Acyclic.
- Includes all of the vertices.




not connected

Minimum spanning tree

Def. A **spanning tree** of G is a subgraph T that is:

- Connected.
- Acyclic.
- Includes all of the vertices.




not acyclic

Minimum spanning tree

Def. A **spanning tree** of G is a subgraph T that is:

- Connected.
- Acyclic.
- Includes all of the vertices.




not spanning

Minimum spanning tree

Given. Undirected graph G with positive edge weights (connected).

Goal. Find a min weight spanning tree.




edge-weighted graph G

Minimum spanning tree

Given. Undirected graph G with positive edge weights (connected).

Goal. Find a min weight spanning tree.




minimum spanning tree T
(cost = 50 = 4 + 6 + 8 + 5 + 11 + 9 + 7)

Brute force. Try all spanning trees?

Network design


MST of bicycle routes in North Seattle



<http://www.flickr.com/photos/ewedistrict/21980840>



Models of nature

MST of random graph



Medical image processing


MST describes arrangement of nuclei in the epithelium for cancer research



http://www.bccrc.ca/ci/ta01_archlevel.html

Medical image processing

MST dithering



<http://www.flickr.com/photos/quasimondo/2695389651>

Applications

MST is fundamental problem with diverse applications.

- Dithering.
- Cluster analysis.
- Max bottleneck paths.
- Real-time face verification.
- LDPC codes for error correction.
- Image registration with Renyi entropy.
- Find road networks in satellite and aerial imagery.
- Reducing data storage in sequencing amino acids in a protein.
- Model locality of particle interactions in turbulent fluid flows.
- Autoconfig protocol for Ethernet bridging to avoid cycles in a network.
- Approximation algorithms for NP-hard problems (e.g., TSP, Steiner tree).
- Network design (communication, electrical, hydraulic, computer, road).

<http://www.ics.uci.edu/~eppstein/gina/mst.html>



<http://algs4.cs.princeton.edu>


4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ *context*

Simplifying assumptions

- Graph is connected.
- Edge weights are distinct.

Consequence. MST exists and is unique.




Cut property

Def. A **cut** in a graph is a partition of its vertices into two (nonempty) sets.

Def. A **crossing edge** connects a vertex in one set with a vertex in the other.

Cut property. Given any cut, the crossing edge of min weight is in the MST.



Cut property: correctness proof


Def. A **cut** in a graph is a partition of its vertices into two (nonempty) sets.

Def. A **crossing edge** connects a vertex in one set with a vertex in the other.

Cut property. Given any cut, the crossing edge of min weight is in the MST.


Pf. Suppose min-weight crossing edge e is not in the MST.

- Adding e to the MST creates a cycle.
- Some other edge f in cycle must be a crossing edge.
- Removing f and adding e is also a spanning tree.
- Since weight of e is less than the weight of f , that spanning tree is lower weight.
- Contradiction. ■



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7 6-2


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7 6-2 0-7


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7 6-2 0-7 2-3


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7 6-2 0-7 2-3 1-7


Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.




MST edges

0-2 5-7 6-2 0-7 2-3 1-7 4-5

Greedy MST algorithm demo

- Start with all edges colored gray.
- Find cut with no black crossing edges; color its min-weight edge black.
- Repeat until $V - 1$ edges are colored black.



MST edges


0-2 5-7 6-2 0-7 2-3 1-7 4-5

Greedy MST algorithm: correctness proof


Proposition. The greedy algorithm computes the MST.

Pf.

- Any edge colored black is in the MST (via cut property).
- Fewer than $V-1$ black edges \Rightarrow cut with no black crossing edges.
(consider cut whose vertices are any one connected component)



a cut with no black crossing edges



fewer than $V-1$ edges colored black

Greedy MST algorithm: efficient implementations

Proposition. The greedy algorithm computes the MST.

Efficient implementations. Choose cut? Find min-weight edge?

Ex 1. Kruskal's algorithm. [stay tuned]


Ex 2. Prim's algorithm. [stay tuned]

Ex 3. Borůvka's algorithm.


Removing two simplifying assumptions

Q. What if edge weights are not all distinct?

A. Greedy MST algorithm still correct if equal weights are present!
(our correctness proof fails, but that can be fixed)




1	2	1.00
1	3	0.50
2	4	1.00
3	4	0.50



1	2	1.00
1	3	0.50
2	4	1.00
3	4	0.50

Q. What if graph is not connected?

A. Compute minimum spanning forest = MST of each component.



4	5	0.61
4	6	0.62
5	6	0.88
1	5	0.11
2	3	0.35
0	3	0.6
1	6	0.10
0	2	0.22

*can independently compute
MSTs of components*

Greed is good



Gordon Gecko (Michael Douglas) address to Teldar Paper Stockholders in Wall Street (1986)




4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ *context*

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.



an edge-weighted graph

graph edges
sorted by weight


↓

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.



an edge-weighted graph

graph edges
sorted by weight


↓

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.

does not create a cycle




in MST →

0-7	0.16
2-3	0.17
1-7	0.19

Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.



does not create a cycle


0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35

in MST \rightarrow

Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.



does not create a cycle


in MST →

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52

not in MST →

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.



creates a cycle


not in MST →

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

not in MST →

Kruskal's algorithm demo

Consider edges in ascending order of weight.

- Add next edge to tree T unless doing so would create a cycle.




a minimum spanning tree

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Kruskal's algorithm demo

Consider edges in ascending order of weight.


- Add next edge to tree T unless doing so would create a cycle.



a minimum spanning tree

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Kruskal's algorithm: visualization




Kruskal's algorithm: correctness proof

Proposition. [Kruskal 1956] Kruskal's algorithm computes the MST.

Pf. Kruskal's algorithm is a special case of the greedy MST algorithm.

- Suppose Kruskal's algorithm colors the edge $e = v-w$ black.
- Cut = set of vertices connected to v in tree T .
- No crossing edge is black.
- No crossing edge has lower weight. Why?





Kruskal's algorithm: implementation challenge

Challenge. Would adding edge $v-w$ to tree T create a cycle? If not, add it.

How difficult?

- $E + V$
- V ← run DFS from v , check if w is reachable
(T has at most $V - 1$ edges)
- $\log V$
- $\log^* V$ ← use the union-find data structure !
- 1




Kruskal's algorithm: implementation challenge


Challenge. Would adding edge $v-w$ to tree T create a cycle? If not, add it.

Efficient solution. Use the **union-find** data structure.

- Maintain a set for each connected component in T .
- If v and w are in same set, then adding $v-w$ would create a cycle.
- To add $v-w$ to T , merge sets containing v and w .



Case 1: adding $v-w$ creates a cycle



Case 2: add $v-w$ to T and merge sets containing v and w

Kruskal's algorithm: Java implementation

```
public class KruskalMST
{
    private Queue<Edge> mst = new Queue<Edge>();

    public KruskalMST(EdgeWeightedGraph G)
    {
        MinPQ<Edge> pq = new MinPQ<Edge>(G.edges());

        UF uf = new UF(G.V());
        while (!pq.isEmpty() && mst.size() < G.V()-1)
        {
            Edge e = pq.delMin();
            int v = e.either(), w = e.other(v);
            if (!uf.connected(v, w))
            {
                uf.union(v, w);
                mst.enqueue(e);
            }
        }
    }

    public Iterable<Edge> edges()
    { return mst; }
}
```

← build priority queue
(or sort)

← greedily add edges to MST

← edge v-w does not create cycle

← merge sets

← add edge to MST

Kruskal's algorithm: running time

Proposition. Kruskal's algorithm computes MST in time proportional to $E \log E$ (in the worst case).

Pf.

operation	frequency	time per op
build pq	1	E
delete-min	E	$\log E$
union	V	$\log^* V^\dagger$
connected	E	$\log^* V^\dagger$

\dagger amortized bound using weighted quick union with path compression

recall: $\log^* V \leq 5$ in this universe



Remark. If edges are already sorted, order of growth is $E \log^* V$.




<http://algs4.cs.princeton.edu>

4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ *context*

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93


Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7


Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7


Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7 0-2


Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7 0-2 2-3

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.

min weight edge with
exactly one endpoint in T



edges with exactly
one endpoint in T
(sorted by weight)

in MST →


5-7	0.28
1-5	0.32
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58

MST edges

0-7 1-7 0-2 2-3

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7 0-2 2-3 5-7

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.

min weight edge with
exactly one endpoint in T



edges with exactly
one endpoint in T
(sorted by weight)

in MST →


4-5	0.35
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58

MST edges

0-7 1-7 0-2 2-3 5-7

Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7 0-2 2-3 5-7 4-5


Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



Prim's algorithm demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




MST edges

0-7 1-7 0-2 2-3 5-7 4-5 6-2

Prim's algorithm demo


- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



MST edges

0-7 1-7 0-2 2-3 5-7 4-5 6-2

Prim's algorithm: visualization




Prim's algorithm: proof of correctness

Proposition. [Jarník 1930, Dijkstra 1957, Prim 1959]

Prim's algorithm computes the MST.

Pf. Prim's algorithm is a special case of the greedy MST algorithm.

- Suppose edge e = min weight edge connecting a vertex on the tree to a vertex not on the tree.
- Cut = set of vertices connected on tree.
- No crossing edge is black.
- No crossing edge has lower weight.




Prim's algorithm: implementation challenge

Challenge. Find the min weight edge with exactly one endpoint in T .

How difficult?

- E ← try all edges
- V
- $\log E$ ← use a priority queue!
- $\log^* E$
- 1




Prim's algorithm: lazy implementation

Challenge. Find the min weight edge with exactly one endpoint in T .


Lazy solution. Maintain a PQ of **edges** with (at least) one endpoint in T .

- Key = edge; priority = weight of edge.
- Delete-min to determine next edge $e = v-w$ to add to T .
- Disregard if both endpoints v and w are marked (both in T).
- Otherwise, let w be the unmarked vertex (not in T):
 - add to PQ any edge incident to w (assuming other endpoint not in T)
 - add e to T and mark w



Prim's algorithm (lazy) demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Prim's algorithm (lazy) demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



MST edges

0-7 1-7 0-2 2-3 5-7 4-5 6-2

Prim's algorithm: lazy implementation

```
public class LazyPrimMST
{
    private boolean[] marked;    // MST vertices
    private Queue<Edge> mst;     // MST edges
    private MinPQ<Edge> pq;     // PQ of edges

    public LazyPrimMST(WeightedGraph G)
    {
        pq = new MinPQ<Edge>();
        mst = new Queue<Edge>();
        marked = new boolean[G.V()];
        visit(G, 0);

        while (!pq.isEmpty() && mst.size() < G.V() - 1)
        {
            Edge e = pq.delMin();
            int v = e.either(), w = e.other(v);
            if (marked[v] && marked[w]) continue;
            mst.enqueue(e);
            if (!marked[v]) visit(G, v);
            if (!marked[w]) visit(G, w);
        }
    }
}
```

← assume G is connected

← repeatedly delete the
min weight edge $e = v-w$ from PQ

← ignore if both endpoints in T
← add edge e to tree

← add v or w to tree

Prim's algorithm: lazy implementation

```
private void visit(WeightedGraph G, int v)
{
    marked[v] = true;
    for (Edge e : G.adj(v))
        if (!marked[e.other(v)])
            pq.insert(e);
}
```

```
public Iterable<Edge> mst()
{ return mst; }
```

← add v to T

← for each edge $e = v-w$, add to PQ if w not already in T

Lazy Prim's algorithm: running time

Proposition. Lazy Prim's algorithm computes the MST in time proportional to $E \log E$ and extra space proportional to E (in the worst case).

Pf.

operation	frequency	binary heap
delete min	E	$\log E$
insert	E	$\log E$


Prim's algorithm: eager implementation

Challenge. Find min weight edge with exactly one endpoint in T .

← pq has at most one entry per vertex

Eager solution. Maintain a PQ of **vertices** connected by an edge to T , where priority of vertex v = weight of shortest edge connecting v to T .

- Delete min vertex v and add its associated edge $e = v-w$ to T .
- Update PQ by considering all edges $e = v-x$ incident to v
 - ignore if x is already in T
 - add x to PQ if not already on it
 - **decrease priority** of x if $v-x$ becomes shortest edge connecting x to T




0		
1	1-7	0.19
2	0-2	0.26
3	1-3	0.29
4	0-4	0.38
5	5-7	0.28
6	6-0	0.58
7	0-7	0.16

← red: on PQ

↑
black: on MST

Prim's algorithm (eager) demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.




an edge-weighted graph

0-7	0.16
2-3	0.17
1-7	0.19
0-2	0.26
5-7	0.28
1-3	0.29
1-5	0.32
2-7	0.34
4-5	0.35
1-2	0.36
4-7	0.37
0-4	0.38
6-2	0.40
3-6	0.52
6-0	0.58
6-4	0.93

Prim's algorithm (eager) demo

- Start with vertex 0 and greedily grow tree T .
- Add to T the min weight edge with exactly one endpoint in T .
- Repeat until $V - 1$ edges.



MST edges

0-7 1-7 0-2 2-3 5-7 4-5 6-2

v	edgeTo[]	distTo[]
0	-	-
7	0-7	0.16
1	1-7	0.19
2	0-2	0.26
3	2-3	0.17
5	5-7	0.28
4	4-5	0.35
6	6-2	0.40

Indexed priority queue

Associate an index between 0 and $N - 1$ with each key in a priority queue.

- Supports **insert** and **delete-the-minimum**.
- Supports **decrease-key** given the index of the key.

```
public class IndexMinPQ<Key extends Comparable<Key>>
```

```
    IndexMinPQ(int N)
```

*create indexed priority queue
with indices 0, 1, ..., $N - 1$*

```
    void insert(int i, Key key)
```

associate key with index i

```
    void decreaseKey(int i, Key key)
```

decrease the key associated with index i

```
    boolean contains(int i)
```

is i an index on the priority queue?

```
    int delMin()
```

*remove a minimal key and return its
associated index*

```
    boolean isEmpty()
```

is the priority queue empty?

```
    int size()
```


number of keys in the priority queue

Indexed priority queue implementation

Binary heap implementation. [see Section 2.4 of textbook]

- Start with same code as MinPQ.
- Maintain parallel arrays `keys[]`, `pq[]`, and `qp[]` so that:
 - `keys[i]` is the priority of `i`
 - `pq[i]` is the index of the key in heap position `i`
 - `qp[i]` is the heap position of the key with index `i`
- Use `swim(qp[i])` to implement `decreaseKey(i, key)`.

<code>i</code>	0	1	2	3	4	5	6	7	8
<code>keys[i]</code>	A	S	O	R	T	I	N	G	–
<code>pq[i]</code>	–	0	6	7	2	1	5	4	3
<code>qp[i]</code>	1	5	4	8	7	6	2	3	–



Prim's algorithm: which priority queue?

Depends on PQ implementation: V insert, V delete-min, E decrease-key.

PQ implementation	insert	delete-min	decrease-key	total
unordered array	1	V	1	V^2
binary heap	$\log V$	$\log V$	$\log V$	$E \log V$
d-way heap	$\log_d V$	$d \log_d V$	$\log_d V$	$E \log_{E/V} V$
Fibonacci heap	1^\dagger	$\log V^\dagger$	1^\dagger	$E + V \log V$

† amortized

Bottom line.

- Array implementation optimal for dense graphs.
- Binary heap much faster for sparse graphs.
- 4-way heap worth the trouble in performance-critical situations.
- Fibonacci heap best in theory, but not worth implementing.



<http://algs4.cs.princeton.edu>

4.3 MINIMUM SPANNING TREES

- ▶ *introduction*
- ▶ *greedy algorithm*
- ▶ *edge-weighted graph API*
- ▶ *Kruskal's algorithm*
- ▶ *Prim's algorithm*
- ▶ ***context***

Does a linear-time MST algorithm exist?

deterministic compare-based MST algorithms


year	worst case	discovered by
1975	$E \log \log V$	Yao
1976	$E \log \log V$	Cheriton-Tarjan
1984	$E \log^* V, E + V \log V$	Fredman-Tarjan
1986	$E \log (\log^* V)$	Gabow-Galil-Spencer-Tarjan
1997	$E \alpha(V) \log \alpha(V)$	Chazelle
2000	$E \alpha(V)$	Chazelle
2002	<i>optimal</i>	Pettie-Ramachandran
20xx	E	???



Remark. Linear-time randomized MST algorithm (Karger-Klein-Tarjan 1995).

Euclidean MST

Given N points in the plane, find MST connecting them, where the distances between point pairs are their **Euclidean** distances.



Brute force. Compute $\sim N^2/2$ distances and run Prim's algorithm.


Ingenuity. Exploit geometry and do it in $\sim c N \log N$.

Scientific application: clustering

k-clustering. Divide a set of objects classify into k coherent groups.

Distance function. Numeric value specifying "closeness" of two objects.

Goal. Divide into clusters so that objects in different clusters are far apart.



outbreak of cholera deaths in London in 1850s (Nina Mishra)

Applications.

- Routing in mobile ad hoc networks.
- Document categorization for web search.
- Similarity searching in medical image databases.
- Skycat: cluster 10^9 sky objects into stars, quasars, galaxies.


Single-link clustering

k-clustering. Divide a set of objects classify into k coherent groups.

Distance function. Numeric value specifying "closeness" of two objects.

Single link. Distance between two clusters equals the distance between the two closest objects (one in each cluster).

Single-link clustering. Given an integer k , find a k -clustering that maximizes the distance between two closest clusters.




Single-link clustering algorithm

“Well-known” algorithm in science literature for single-link clustering:

- Form V clusters of one object each.
- Find the closest pair of objects such that each object is in a different cluster, and merge the two clusters.
- Repeat until there are exactly k clusters.


Observation. This is Kruskal's algorithm.
(stopping when k connected components)



Alternate solution. Run Prim; then delete $k - 1$ max weight edges.

Dendrogram of cancers in human

Tumors in similar tissues cluster together.



Reference: Botstein & Brown group

■ gene expressed
■ gene not expressed