

Jurisdiction

1 Setting up

Create a directory named "jurisdiction" at the location **/gamewrapper/** and place all files with the corresponding parameters that need to be overridden into it. The title of the JSON file for jurisdiction must match the jurisdiction parameter received from the lobby when starting the games.

For example: /createToken?someparams&jurisdiction=uk

By using this request, the configuration file **/gamewrapper/jurisdiction/uk.json** will be utilized for the override action.

2 Structure of configuration file

Each jurisdiction configuration file consists of two parts: **gameConfig** and **wrapperConfig**.

```
1 {  
2   "gameConfig": {  
3     \\ game configurable parameters  
4   },  
5   "wrapperConfig": {  
6     \\ wrapper configurable parameters  
7   }
```

In the **gameConfig** section, all parameters that are configurable on the game side are specified (such as the autoplay button, stake...). Everything listed in this section will directly overwrite the game configuration. Important: All parameters found in the **gameConfig** section in the game's configuration can be overwritten.

In the **wrapperConfig** section, all parameters that are configurable on the wrapper side are specified (such as **gameName**, **clock**, **date**, **elapsedTime**...).

3 Example of Jurisdiction File

Attached is an example of a jurisdiction file that may exist, and it needs to be tailored to the needs of the game studio as each game has its own specifics.

In the game config section, specific game settings are located, such as "max-AutoplayOption." Additionally, **stakeValues**, **default stake**, and so on can be

configured there. This means that everything that can be found in the game-Config section in the initial configuration can also be found in the jurisdiction config for override.

```
1 {
2   "gameConfig" : {
3     "maxAutoplayOption" : 100,
4     "hasSpinStop" : false,
5     "hasAutoPlay" : true,
6     "hasTurbo" : false,
7     "enableSpaceBar": false,
8     "isSpaceBar": true,
9     "stakeValues": [0.01, 0.02, 0.04],
10    "defaultStake": 0.1,
11    "defaultLineCount": 40,
12    "lineCountRange": [40],
13    "autoplayOptions": [5, 10, 25, 50]
14  },
15  "wrapperConfig": {
16    "ui" : {
17      "bottomBar" : {
18        "elapsedTime" : true,
19        "lblNetAmount" : false
20      },
21      "topBar" : {
22        "elapsedTime" : true
23      }
24    },
25    "additional" : {
26      "gameName" : false,
27      "date" : true,
28      "clock" : false
29    }
30  }
31 }
```