

Primer MS

Single-part waterproofing primer based on silane polymers

Solvent-free, moisture-curing silane primer suitable for waterproofing and surface consolidation of substrates prior to the installation of prefinished multilayer parquet. Can be used on cementitious substrates with residual moisture up to 5%. Also suitable for heated substrates. Not suitable for substrates subject to continuous rising damp. It can also be used as a surface consolidator for gypsum-based substrates that produce dust. Specifically designed for subsequent parquet bonding with silane-based adhesives, but it can also be used with two-component reactive adhesives.



**PRIMERS
& SUB-FLOORS**

Technical Data at 20 °C, 60% R.H.

Appearance	Transparent liquid
Density	1,00 kg/litre
Recoating	min 1 hour, max 72 hours
Parquet bonding	min 1 hour, max 72 hours
Full curing	24 hours
Consumption	80 - 120 g/m ² as surface dust-proof hardener 200 - 250 g/m ² as waterproofing (in two coats)
Application temperature	> 10 °C
Storage	12 months
VOC content	0 g/litre
Tool cleaning	Immediately after use with Solvente S23
Packaging available	5 kg cans



CERTIFICATIONS



Substrate Preparation

Substrates must be absorbent, clean, free from grease and loose parts. Primer MS can be applied on cementitious screeds with residual moisture up to 5% (carbide hygrometer). Anhydrite substrates must be dry with a maximum moisture content of 0.5%; before applying the primer, sand the surface and vacuum the resulting dust.

Primer MS must not be applied on wet surfaces or where continuous rising damp is present – in such cases use Idroblok C3 as described in the related technical sheet. It can also be applied on existing ceramic flooring. Do not apply Primer MS on resilient flooring.

Instructions for Use

Primer MS is ready to use and must not be diluted. Apply Primer MS with a roller or brush. For surface consolidation, one coat is sufficient; for waterproofing, apply two coats at least 1 hour apart (within a maximum of 72 hours). Wood floor installation must be carried out within 72 hours after the application of the last coat, using silane-based adhesives.

Note

- In case of low temperatures and/or very dry environments, curing times will be extended. It is recommended not to use the product at temperatures below +10 °C or with relative air humidity below 40%.
- Primer MS is not suitable for waterproofing against rising damp.
- After use, close containers tightly and do not pour back into the can any unused product that has been taken out.

Safety Regulations

Product for professional use. Strictly follow the label instructions and consult the safety data sheet before using the product.

Disposal

Dispose of unused product and empty containers in compliance with current local legislation.



**PRIMERS
& SUB-FLOORS**



CERTIFICATIONS



The recommendations in this technical bulletin are indicative and in no way binding, since the methods and conditions of product use are beyond our control. We recommend verifying the actual suitability for the intended use.

Rev 01 – 17/09/2025.

This sheet cancels and replaces the previous one.