

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

1 Purpose and boundary

This is a synthetic AUTOSAR-style HLD for a classroom steering monitoring example. It is not an AUTOSAR standard, production ECU design or safety-certified system.

Document: SYN-HLD-001 | Version: v1 | Status: Learning example

Scope: component interfaces, declared signals, ports, timing and engineer review. No ASIL rating is assigned.

The example reads vehicle speed, computes steering control state and monitors steering angle. Outputs are design-review evidence only.

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

2 Component catalogue

Component: VehicleStateProvider | Role: publishes vehicle speed | Owner: VehicleInputs | RateMs: 10

Component: SteeringController | Role: consumes vehicle speed and publishes steering angle | Owner: SteeringControl | RateMs: 10

Component: SafetyMonitor | Role: consumes steering angle and checks range | Owner: Monitoring | RateMs: 10

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

3 Interface catalogue

Interface: VehicleSpeedIf | Direction: sender-receiver | DataElement: VehicleSpeed |
Type: float32

Interface: SteeringAngleIf | Direction: sender-receiver | DataElement: SteeringAngle |
Type: float32

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

4 Signal contracts

Signal: VehicleSpeed | Producer: VehicleStateProvider | Consumer: SteeringController |
Interface: VehicleSpeedIf | Type: float32 | ProducerUnit: km_per_h | ConsumerUnit:
km_per_h | PeriodMs: 20

Signal: SteeringAngle | Producer: SteeringController | Consumer: SafetyMonitor |
Interface: SteeringAngleIf | Type: float32 | ProducerUnit: deg | ConsumerUnit: deg |
PeriodMs: 10

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

5 Port mapping

Port: SpeedOut | Component: VehicleStateProvider | Direction: provided | Interface: VehicleSpeedIf

Port: SpeedIn | Component: SteeringController | Direction: required | Interface: VehicleSpeedIf

Port: AngleOut | Component: SteeringController | Direction: provided | Interface: SteeringAngleIf

Port: AngleIn | Component: SafetyMonitor | Direction: required | Interface: SteeringAngleIf

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

6 Review and limitations

Engineer review is mandatory before accepting any generated answer, extraction, revision finding or impact result.

No ASIL classification, hazard analysis, AUTOSAR conformance validation or production safety decision is defined in this HLD.

Model output must cite the document ID, version, page and section. Unsupported factual requests must be refused.

All names, interfaces and numeric values in this HLD were generated for the educational prototype.

AutoArch AI Synthetic HLD

SYN-HLD-001 | v1 | Synthetic educational data

7 Functional requirements

Requirement: REQ-001 | Text: VehicleStateProvider shall publish VehicleSpeed every 20 ms.

Requirement: REQ-002 | Text: SteeringController shall consume VehicleSpeed through VehicleSpeedIf.

Requirement: REQ-003 | Text: SafetyMonitor shall consume SteeringAngle through SteeringAngleIf.

Requirement: REQ-004 | Text: Engineer review shall be recorded separately before architecture approval.

Baseline review seed: all producer and consumer units match.