







Designator	Description	Comment	Footprint	LibRef	Quantity	Datasheet Link	Manufacturer_Par t_Number
B1	The TPS62933 is a high-efficiency, easy-to-use synchronous buck converter with a wide input voltage range of 3.8 V to 30 V	D IGUSSOCASGT	SOT583_TPS62933	TPS62933DRLR	1	https://www.ti.c om/lit/ds/symlin k/tps62933.pdf?ts =1626073394234	TPS62933DRLR
C1	0603 SMD Capacitor	100n	0603_SMD_C	0603_SMD_Capacitor	1		
C2	0603 SMD Capacitor	47p	0603_SMD_C	0603_SMD_Capacitor	1		
C3	1206 SMD Capacitor	10u	1206_SMD_C	1206_SMD_Capacitor	1		
C4	0805 SMD Capacitor	100n	0805_SMD_C	0805_SMD_Capacitor	1		
C5	0603 SMD Capacitor	33n	0603_SMD_C	0603_SMD_Capacitor	1		
C6	1210 SMD Capacitor	47u	1210_SMD_C	1210_SMD_Capacitor	1		
L	15µH Shielded Wirewound Inductor 5.03A 24.7mOhm Nonstandard	15u	DR127_SMD_L	DR127-150-R	1		
R1	0603 SMD Resistor	68k	0603_SMD_R	0603_SMD_Resistor	1		
R2	0603 SMD Resistor	1M	0603_SMD_R	0603_SMD_Resistor	1		
R3	0603 SMD Resistor	330k	0603_SMD_R	0603_SMD_Resistor	1		
R4	0603 SMD Resistor	130k	0603_SMD_R	0603_SMD_Resistor	1		
R5, R6	0603 SMD Resistor	10k	0603_SMD_R	0603_SMD_Resistor	2		