INSTITUTO TECNONÓLOGICO Y DE ESTUDIOS SUPERIORES DE MONTERREY

MASTERS THESIS PROPOSAL

Design of Polymer Solutions for the Fabrication of Conducting Carbon Nano-wires

Author: Antonio Osamu KATAGIRI Tanaka Principal Advisor: Dr. Héctor Alán AGUIRRE Soto

Co-advisor and
Director of Program:
Dra. Dora Iliana MEDINA
Medina

A thesis submitted in fulfillment of the requirements for the degree of Master of Science in Nanotechnology (MNT)

in

ITESM Campus Estado de México School of Engineering and Sciences Estado de México, Atizapan de Zaragoza, March 17, 2019

INSTITUTO TECNONÓLOGICO Y DE ESTUDIOS SUPERIORES DE MONTERREY

Campus Estado de México

Supervising Committee

The committee members, hereby, recommend that the proposal by Antonio Osamu KATAGIRI Tanakato be accepted to develop the thesis project as a partial requirement for the degree of Master of Science in Nanotechnology (MNT).

Dr. Héctor Alán AGUIRRE Soto Tecnológico de Monterrey *Principal Advisor*

1st committee member name 1st committee member institution *Committee Member*

2nd committee member name 2nd committee member institution *Committee Member*

Dra. Dora Iliana MEDINA Medina Director of Program in Nanotechnology School of Engineering and Sciences

Contents

Sı	apervising Committee	iii
Al	bstract	viii
1	Introduction	1
2	Problem Definition and Motivation	3
3	Hypothesis and Research Questions	5
4	Objectives	7
5	Theoretical Framework	9
6	Methodology	11
7	Work Plan	13

INSTITUTO TECNONÓLOGICO Y DE ESTUDIOS SUPERIORES DE MONTERREY

Abstract

Faculty: Nanotechnology School of Engineering and Sciences

Master of Science in Nanotechnology (MNT)

Design of Polymer Solutions for the Fabrication of Conducting Carbon Nano-wires

by Antonio Osamu KATAGIRI Tanaka

Carbon fibers are versatile materials composed of carbon chains with a wide range of applications. Carbon nanowires have been fabricated with a photoresist, but little is known about polymers that can produce more conductive carbon nanowires after pyrolysis. FFES or Far field electrospinning is a inexpensive process to produce polymer fibers, but with low accuracy due to electric instabilities. Near field electrospinning (NFES) is similar to FFES, but with a reduced distance between the fiber source and the collector and higher precision. Various polymer solutions have being tested and measured through NFSE and photopolymerization processes; it was found that it is not possible to predict the behaviour of the electrospinning process, so additional properties are to be considered to achieve a stable process. The properties of the polymer solution can be amended to obtain a electrospunable, photopolymerizable and pyrolyzable/graphitizable fibers. Analyse the rheology of different polymer solutions to determine if they can be easily electrospun at low voltages and then fabricate nanowires with them. Design polymer solutions that can be electrospun by NFES, photopolymerized, and then pyrolyzed into conducting carbon nanowires. The use of the newly designed polymer solution within the NFES-Photopolymerization-Pyrolysis process can be amended to achieve mass scale manufacturing of carbon nanowires in a cheap, continuous, simple and reproducible manner. The new/tailored polymer solution can be used to synthesize carbon nanowires with high conductive properties and reduced thickness.

keywords: tec, de, monterrey

Introduction

Problem Definition and Motivation

Hypothesis and Research Questions

Objectives

Theoretical Framework

Methodology

Work Plan