

INSTITUTO TECNOLÓGICO Y DE ESTUDIOS
SUPERIORES DE MONTERREY



A Review on Nano-Fiber Fabrication Methods by Near-Field Electrospinning

Author(s):

Antonio Osamu KATAGIRI Tanaka, Héctor Alán AGUIRRE Soto

ITESM Campus Monterrey
School of Engineering and Sciences

Monterrey, Nuevo León, June 10, 2019

INSTITUTO TECNOLÓGICO Y DE ESTUDIOS SUPERIORES DE
MONTERREY

Abstract

Faculty: Nanotechnology

School of Engineering and Sciences

A Review on Nano-Fiber Fabrication Methods by Near-Field Electrospinning

by Antonio Osamu KATAGIRI Tanaka, Héctor Alán AGUIRRE Soto

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

keywords: nanotechnology, nano-fiber, near-field electrospinning, NFES

1 Summary

TABLE 1.1: Electrospun Polymer Solutions - Solution and Process Parameters

Polymer	Solvent	NFES Variant	Polymer Solution and Process Properties	Fiber Characterization	Reference
Poly(ethylene oxide) (PEO)	Deionized water	Low-Voltage and Low-Electrical Field NFES	<ul style="list-style-type: none">• PEO Concentration: 1, 2, and 3 <i>wt%</i>• Rise in solution conductivity with the increase in PEO concentration• Solution Stirring: 24 <i>h</i> of free diffusion followed by 96 <i>h</i> of stirring at 30 <i>rpm</i>• 3 <i>mL</i> syringe• 27 gauge type 304 stainless steel needle• Solution deposition rate: lower than 1 $\mu\text{L}/\text{h}$• needle-to-collector distance: 1 <i>mm</i>	<ul style="list-style-type: none">• Diameter: 50-425 <i>nm</i>	[1]

TABLE 1.2: Electrospun Polymer Solutions - Solution and Process Parameters

Polymer	Solvent	NFES Variant	Polymer Solution and Process Properties	Fiber Characterization	Reference
			<ul style="list-style-type: none"> • NFES process initiated by an air interference with a glass microprobe tip (1 to 3 μm tip diameter) to overcome the surface tension • Time to produce a stable continuous jet: 45 <i>min</i> • Polymer jet initiated at 400-600 <i>V</i> and dispensed at 200-400 <i>V</i> • Collector linear speed: 10-40 <i>mm/s</i> • The voltage turned on when the solution formed a full-sized droplet of 500 μm diameter at the needle tip. 		[1]
Poly[2-methoxy-5-(2-ethylhexyloxy)-1,4-phenylenevinylene] (MEH-PPV) with Poly(ethylene oxide) (PEO)	acetonitrile / toluene mixture (65 / 35); acetic acid / toluene (17 / 83); pure toluene		<ul style="list-style-type: none"> • Concentrations: <ul style="list-style-type: none"> – MEH-PPV solution: 10 <i>mg</i> of MEH-PPV in 2 <i>mL</i> of toluene – 500 μL of MEH-PPV solution with 250 <i>mg</i> of PEO in 3.5 <i>mL</i> of acetonitrile / toluene (65 / 35) – 500 μL of MEH-PPV solution with 250 <i>mg</i> of PEO in 3 <i>mL</i> of acetic acid / toluene (17 / 83) 		[2]

TABLE 1.3: Electrospun Polymer Solutions - Solution and Process Parameters

- | | |
|---|--|
| <ul style="list-style-type: none"> – The resulting MEH-PPV/PEO concentration is 1:100 • Solution Stirring: <ul style="list-style-type: none"> – MEH-PPV solution stirred for 4 <i>h</i> – PEO solution stirred for 8 <i>h</i> – MEH-PPV/PEO solution stirred and ultrasonically agitated • Collector substrate: SiO₂/Si (oxide thickness = 800 <i>nm</i>) • needle-to-collector distance: 500 <i>μm</i> • <i>μm</i>-diameter tip Tungsten spinneret in a 26 gauge needle • Solution deposition rate: 50 <i>μL/h</i> • Electrostatic voltage: around 1.3 <i>kV</i> • x-y stage velocity: 50 <i>cm/s</i> | <ul style="list-style-type: none"> • distance between adjacent fibers: around 100 <i>μm</i> • Fiber diameter: around 100 <i>nm</i> |
|---|--|

[2]

TABLE 1.4: Electrospun Polymer Solutions - Solution and Process Parameters

Polymer	Solvent	NFES Variant	Polymer Solution and Process Properties	Fiber Characterization	Reference
					[3]
					[4]
					[5]
					[6]
					[7]
					[8]
					[9]
					[10]
					[11]
					[12]
					[14]
					[13]
					[15]
					[16]
					[17]
					[18]
					[19]
					[20]
					[21]
					[22]
					[23]
					[24]

References

- [1] Gobind S. Bisht et al. "Controlled Continuous Patterning of Polymeric Nanofibers on Three-Dimensional Substrates Using Low-Voltage Near-Field Electrospinning". In: *Nano Letters* 11.4 (Apr. 2011), pp. 1831–1837. ISSN: 1530-6984. DOI: [10.1021/nl2006164](https://doi.org/10.1021/nl2006164). URL: <https://pubs.acs.org/doi/10.1021/nl2006164>.
- [2] Daniela Di Camillo et al. "Near-field electrospinning of conjugated polymer light-emitting nanofibers". In: *Nanoscale* 5 (2013), pp. 11637–11642. DOI: [10.1039/C3NR03094F](https://doi.org/10.1039/C3NR03094F). URL: <https://arxiv.org/ftp/arxiv/papers/1310/1310.5101.pdf>.
- [3] Chieh Chang, Kevin Limkralassiri, and Liwei Lin. "Continuous near-field electrospinning for large area deposition of orderly nanofiber patterns". In: *Appl Phys Lett* (2008), p. 3. DOI: [10.1063/1.2975834](https://doi.org/10.1063/1.2975834). URL: http://www-bsac.eecs.berkeley.edu/publications/search/send%7B%5C_%7Dpublication%7B%5C_%7Dpdf2client.php?pubID=1217995664.
- [4] Paul D Dalton, T Joergensen, and Juergen Groll. "Additive manufacturing of scaffolds with sub-micron filaments via melt electrospinning writing Related content Patterned melt electrospun substrates for tissue engineering". In: (2015). DOI: [10.1088/1758-5090/7/3/035002](https://doi.org/10.1088/1758-5090/7/3/035002). URL: <https://iopscience.iop.org/article/10.1088/1758-5090/7/3/035002/pdf>.
- [5] Yongqing Duan et al. "Helix Electrohydrodynamic Printing of Highly Aligned Serpentine Micro/Nanofibers." In: *Polymers* 9.9 (Sept. 2017). ISSN: 2073-4360. DOI: [10.3390/polym9090434](https://doi.org/10.3390/polym9090434). URL: <http://www.ncbi.nlm.nih.gov/pubmed/30965737> <http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=PMC6418525>.
- [6] Ashish Gupta et al. "Novel Electrohydrodynamic Printing of Nanocomposite Biopolymer Scaffolds". In: *Journal of BIOACTIVE AND COMPATIBLE POLYMERS* 22 (2007). DOI: [10.1177/0883911507078268](https://doi.org/10.1177/0883911507078268). URL: <https://journals.sagepub.com/doi/pdf/10.1177/0883911507078268>.
- [7] YongAn Huang et al. "Versatile, kinetically controlled, high precision electrohydrodynamic writing of micro/nanofibers". In: *Scientific Reports* 4.1 (May 2015), p. 5949. ISSN: 2045-2322. DOI: [10.1038/srep05949](https://doi.org/10.1038/srep05949). URL: <http://www.nature.com/articles/srep05949>.

- [8] Jiaxin Jiang et al. "Electrohydrodynamic Direct-Writing Micropatterns with Assisted Airflow". In: *Micromachines* 9.9 (Sept. 2018), p. 456. ISSN: 2072-666X. DOI: 10.3390/mi9090456. URL: <http://www.mdpi.com/2072-666X/9/9/456>.
- [9] Jinseong Kim, Bohee Maeng, and Jungyul Park. "Characterization of 3D electrospinning on inkjet printed conductive pattern on paper". In: *Micro and Nano Systems Letters* 6.1 (Dec. 2018), p. 12. ISSN: 2213-9621. DOI: 10.1186/s40486-018-0074-1. URL: <https://mns-l-journal.springeropen.com/articles/10.1186/s40486-018-0074-1>.
- [10] Jongwan Lee et al. "Fabrication of Patterned Nanofibrous Mats Using Direct-Write Electrospinning". In: *Langmuir* 28.18 (May 2012), pp. 7267–7275. ISSN: 0743-7463. DOI: 10.1021/la3009249. URL: <http://pubs.acs.org/doi/10.1021/la3009249>.
- [11] Z H Liu et al. "Direct-write PVDF nonwoven fiber fabric energy harvesters via the hollow cylindrical near-field electrospinning process". In: (2014), pp. 25003–25014. DOI: 10.1088/0964-1726/23/2/025003. URL: <http://iopscience.iop.org/0964-1726/23/2/025003>.
- [12] Sung-Yong Min et al. "Large-scale organic nanowire lithography and electronics". In: *Nature Communications* 4.1 (June 2013), p. 1773. ISSN: 2041-1723. DOI: 10.1038/ncomms2785. URL: <http://www.nature.com/articles/ncomms2785>.
- [13] Cheng-Tang Pan et al. "Near-field electrospinning enhances the energy harvesting of hollow PVDF piezoelectric fibers". In: *RSC Advances* 5.103 (2015), pp. 85073–85081. ISSN: 2046-2069. DOI: 10.1039/C5RA16604G. URL: <http://xlink.rsc.org/?DOI=C5RA16604G>.
- [14] Cheng-Tang Pan et al. *Poly(γ -benzyl α , l-glutamate) in Cylindrical Near-Field Electrospinning Fabrication and Analysis of Piezoelectric Fibers*. Tech. rep. 2. 2014, pp. 63–73. URL: https://myukk.org/SM2017/sm%7B%5C_%7Dpdf/SM971.pdf.
- [15] Chiho Song et al. "Patterned polydiacetylene-embedded polystyrene nanofibers based on electrohydrodynamic jet printing". In: *Macromolecular Research* 23.1 (Jan. 2015), pp. 118–123. ISSN: 1598-5032. DOI: 10.1007/s13233-015-3024-2. URL: <http://link.springer.com/10.1007/s13233-015-3024-2>.
- [16] Daoheng Sun et al. "Near-Field Electrospinning". In: (2006). DOI: 10.1021/nl0602701. URL: <https://pubs.acs.org/doi/10.1021/nl0602701>.
- [17] Han Wang et al. "Research on Multinozzle Near-Field Electrospinning Patterned Deposition". In: *Journal of Nanomaterials* 2015 (July 2015), pp. 1–8. ISSN: 1687-4110. DOI: 10.1155/2015/529138. URL: <http://www.hindawi.com/journals/jnm/2015/529138/>.
- [18] Zhifeng Wang et al. "Controllable deposition distance of aligned pattern via dual-nozzle near-field electrospinning". In: *AIP Advances* 7.3 (Mar. 2017), p. 035310. ISSN: 2158-3226. DOI: 10.1063/1.4974936. URL: <http://aip.scitation.org/doi/10.1063/1.4974936>.
- [19] Zhifeng Wang et al. "Fabrication and evaluation of controllable deposition distance for aligned pattern by multi-nozzle near-field electrospinning". In: *AIP*

- Advances* 8.7 (July 2018), p. 075111. ISSN: 2158-3226. DOI: [10.1063/1.5032082](https://doi.org/10.1063/1.5032082). URL: <http://aip.scitation.org/doi/10.1063/1.5032082>.
- [20] Jiachen Xu et al. "Accuracy Improvement of Nano-fiber Deposition by Near-Field Electrospinning". In: *International Workshop on Microfactories IWMF2014.9th* (2014). URL: <http://conf.papercept.net/images/temp/IWMF/media/files/0041.pdf>.
- [21] Niannan Xue et al. "Rapid Patterning of 1-D Collagenous Topography as an ECM Protein Fibril Platform for Image Cytometry". In: *PLoS ONE* 9.4 (Apr. 2014). Ed. by Wei-Chun Chin, e93590. ISSN: 1932-6203. DOI: [10.1371/journal.pone.0093590](https://doi.org/10.1371/journal.pone.0093590). URL: <https://dx.plos.org/10.1371/journal.pone.0093590>.
- [22] Gaofeng Zheng et al. "Precision deposition of a nanofibre by near-field electrospinning". In: *Journal of Physics D: Applied Physics* 43.41 (Oct. 2010), p. 415501. ISSN: 0022-3727. DOI: [10.1088/0022-3727/43/41/415501](https://doi.org/10.1088/0022-3727/43/41/415501). URL: <http://stacks.iop.org/0022-3727/43/i=41/a=415501?key=crossref.304f8be16661d1ca2c851060187b28>.
- [23] Jiang-Yi Zheng et al. "Electrohydrodynamic Direct-Write Orderly Micro/Nanofibrous Structure on Flexible Insulating Substrate". In: *Journal of Nanomaterials* 2014 (May 2014), pp. 1–7. ISSN: 1687-4110. DOI: [10.1155/2014/708186](https://doi.org/10.1155/2014/708186). URL: <http://www.hindawi.com/journals/jnm/2014/708186/>.
- [24] Jie Zheng et al. "Polymer nanofibers prepared by low-voltage near-field electrospinning". In: *Chinese Physics B* 21.4 (2012), pp. 1–6. ISSN: 16741056. DOI: [10.1088/1674-1056/21/4/048102](https://doi.org/10.1088/1674-1056/21/4/048102).