

```
from sklearn.datasets import load_boston
```

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

```
df=load_boston()
```

C:\ProgramData\Anaconda3\lib\site-packages\sklearn\utils\deprecation.py:87: FutureWarning: Function load_boston is deprecated; `load_bos

The Boston housing prices dataset has an ethical problem. You can refer to the documentation of this function for further details.

The scikit-learn maintainers therefore strongly discourage the use of this dataset unless the purpose of the code is to study and educate about ethical issues in data science and machine learning.

In this special case, you can fetch the dataset from the original source::

```
import pandas as pd
import numpy as np
```

```
data_url = "http://lib.stat.cmu.edu/datasets/boston"
raw_df = pd.read_csv(data_url, sep="\s+", skiprows=22, header=None)
data = np.hstack([raw_df.values[::2, :], raw_df.values[1::2, :]])
target = raw_df.values[1::2, 2]
```

Alternative datasets include the California housing dataset (i.e. :func:`~sklearn.datasets.fetch_california_housing`) and the Ames housing dataset. You can load the datasets as follows::

```
from sklearn.datasets import fetch_california_housing
housing = fetch_california_housing()
```

for the California housing dataset and::

```
from sklearn.datasets import fetch_openml
housing = fetch_openml(name="house_prices", as_frame=True)
```

for the Ames housing dataset.

```
warnings.warn(msg, category=FutureWarning)
```

df



```
13.1, 13.5, 18.9, 20. , 21. , 24.7, 30.8, 34.9, 26.6, 25.3, 24.7,
21.2, 19.3, 20. , 16.6, 14.4, 19.4, 19.7, 20.5, 25. , 23.4, 18.9,
35.4, 24.7, 31.6, 23.3, 19.6, 18.7, 16. , 22.2, 25. , 33. , 23.5,
19.4, 22. , 17.4, 20.9, 24.2, 21.7, 22.8, 23.4, 24.1, 21.4, 20. ,
20.8, 21.2, 20.3, 28. , 23.9, 24.8, 22.9, 23.9, 26.6, 22.5, 22.2,
23.6, 28.7, 22.6, 22. , 22.9, 25. , 20.6, 28.4, 21.4, 38.7, 43.8,
33.2, 27.5, 26.5, 18.6, 19.3, 20.1, 19.5, 19.5, 20.4, 19.8, 19.4,
21.7, 22.8, 18.8, 18.7, 18.5, 18.3, 21.2, 19.2, 20.4, 19.3, 22. ,
20.3, 20.5, 17.3, 18.8, 21.4, 15.7, 16.2, 18. , 14.3, 19.2, 19.6,
23. , 18.4, 15.6, 18.1, 17.4, 17.1, 13.3, 17.8, 14. , 14.4, 13.4,
15.6, 11.8, 13.8, 15.6, 14.6, 17.8, 15.4, 21.5, 19.6, 15.3, 19.4,
17. , 15.6, 13.1, 41.3, 24.3, 23.3, 27. , 50. , 50. , 50. , 22.7,
25. , 50. , 23.8, 23.8, 22.3, 17.4, 19.1, 23.1, 23.6, 22.6, 29.4,
23.2, 24.6, 29.9, 37.2, 39.8, 36.2, 37.9, 32.5, 26.4, 29.6, 50. ,
```

```
10.8, 41.9, 47.5, 41.9, 43.1, 50. , 50. , 50. , 50. , 50. , 13.8,
13.8, 15. , 13.9, 13.3, 13.1, 10.2, 10.4, 10.9, 11.3, 12.3, 8.8,
7.2, 10.5, 7.4, 10.2, 11.5, 15.1, 23.2, 9.7, 13.8, 12.7, 13.1,
12.5, 8.5, 5. , 6.3, 5.6, 7.2, 12.1, 8.3, 8.5, 5. , 11.9,
27.9, 17.2, 27.5, 15. , 17.2, 17.9, 16.3, 7. , 7.2, 7.5, 10.4,
8.8, 8.4, 16.7, 14.2, 20.8, 13.4, 11.7, 8.3, 10.2, 10.9, 11. ,
9.5, 14.5, 14.1, 16.1, 14.3, 11.7, 13.4, 9.6, 8.7, 8.4, 12.8,
10.5, 17.1, 18.4, 15.4, 10.8, 11.8, 14.9, 12.6, 14.1, 13. , 13.4,
15.2, 16.1, 17.8, 14.9, 14.1, 12.7, 13.5, 14.9, 20. , 16.4, 17.7,
19.5, 20.2, 21.4, 19.9, 19. , 19.1, 19.1, 20.1, 19.9, 19.6, 23.2,
29.8, 13.8, 13.3, 16.7, 12. , 14.6, 21.4, 23. , 23.7, 25. , 21.8,
20.6, 21.2, 19.1, 20.6, 15.2, 7. , 8.1, 13.6, 20.1, 21.8, 24.5,
23.1, 19.7, 18.3, 21.2, 17.5, 16.8, 22.4, 20.6, 23.9, 22. , 11.9]],
'feature_names': array(['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD',
'TAX', 'PTRATIO', 'B', 'LSTAT'], dtype='<U7)'),
'DESCR': "... _boston_dataset:\n\nBoston house prices dataset\n-----\n\n**Data Set Characteristics:** \n\n
:Number of Instances: 506 \n\n :Number of Attributes: 13 numeric/categorical predictive. Median Value (attribute 14) is usually
the target.\n\n :Attribute Information (in order):\n          - CRIM      per capita crime rate by town\n          - ZN      proportion of residential land zoned for lots over 25,000 sq.ft.\n          - INDUS  proportion of non-retail business acres per
town\n          - CHAS    Charles River dummy variable (= 1 if tract bounds river; 0 otherwise)\n          - NOX      nitric oxides
concentration (parts per 10 million)\n          - RM        average number of rooms per dwelling\n          - AGE      proportion of
owner-occupied units built prior to 1940\n          - DIS      weighted distances to five Boston employment centres\n          - RAD
index of accessibility to radial highways\n          - TAX      full-value property-tax rate per $10,000\n          - PTRATIO  pupil-
teacher ratio by town\n          - B          1000(Bk - 0.63)^2 where Bk is the proportion of black people by town\n          - LSTAT   %
lower status of the population\n          - MEDV      Median value of owner-occupied homes in $1000's\n\n :Missing Attribute Values:
None\n\n :Creator: Harrison, D. and Rubinfeld, D.L.\n\nThis is a copy of UCI ML housing
dataset.\nhttps://archive.ics.uci.edu/ml/machine-learning-databases/housing/\n\nThis dataset was taken from the StatLib library
which is maintained at Carnegie Mellon University.\n\nThe Boston house-price data of Harrison, D. and Rubinfeld, D.L.
```

```
dataset = pd.DataFrame(df.data)
print(dataset.head())
```

| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 \ | |
|---|---------|------|------|-----|-------|-------|------|--------|-----|-------|------|--|
| 0 | 0.00632 | 18.0 | 2.31 | 0.0 | 0.538 | 6.575 | 65.2 | 4.0900 | 1.0 | 296.0 | 15.3 | |
| 1 | 0.02731 | 0.0 | 7.07 | 0.0 | 0.469 | 6.421 | 78.9 | 4.9671 | 2.0 | 242.0 | 17.8 | |
| 2 | 0.02729 | 0.0 | 7.07 | 0.0 | 0.469 | 7.185 | 61.1 | 4.9671 | 2.0 | 242.0 | 17.8 | |
| 3 | 0.03237 | 0.0 | 2.18 | 0.0 | 0.458 | 6.998 | 45.8 | 6.0622 | 3.0 | 222.0 | 18.7 | |
| 4 | 0.06905 | 0.0 | 2.18 | 0.0 | 0.458 | 7.147 | 54.2 | 6.0622 | 3.0 | 222.0 | 18.7 | |
| | | | | | | | | | | | | |
| | 11 | 12 | | | | | | | | | | |
| 0 | 396.90 | 4.98 | | | | | | | | | | |
| 1 | 396.90 | 9.14 | | | | | | | | | | |
| 2 | 392.83 | 4.03 | | | | | | | | | | |
| 3 | 394.63 | 2.94 | | | | | | | | | | |
| 4 | 396.90 | 5.33 | | | | | | | | | | |

```
dataset.columns=df.feature_names
```

```
dataset.head()
```

| | CRIM | ZN | INDUS | CHAS | NOX | RM | AGE | DIS | RAD | TAX | PTRATIO | B | LSTAT |
|---|---------|------|-------|------|-------|-------|------|--------|-----|-------|---------|--------|-------|
| 0 | 0.00632 | 18.0 | 2.31 | 0.0 | 0.538 | 6.575 | 65.2 | 4.0900 | 1.0 | 296.0 | 15.3 | 396.90 | 4.98 |
| 1 | 0.02731 | 0.0 | 7.07 | 0.0 | 0.469 | 6.421 | 78.9 | 4.9671 | 2.0 | 242.0 | 17.8 | 396.90 | 9.14 |
| 2 | 0.02729 | 0.0 | 7.07 | 0.0 | 0.469 | 7.185 | 61.1 | 4.9671 | 2.0 | 242.0 | 17.8 | 392.83 | 4.03 |
| 3 | 0.03237 | 0.0 | 2.18 | 0.0 | 0.458 | 6.998 | 45.8 | 6.0622 | 3.0 | 222.0 | 18.7 | 394.63 | 2.94 |
| 4 | 0.06905 | 0.0 | 2.18 | 0.0 | 0.458 | 7.147 | 54.2 | 6.0622 | 3.0 | 222.0 | 18.7 | 396.90 | 5.33 |

```
df.target.shape
```

(506,)

```
dataset["Price"]=df.target
```

```
dataset.head()
```

```

CRIM  ZN  INDUS  CHAS  NOX  RM  AGE  DIS  RAD  TAX  PTRATIO  B  LSTAT  Price
X=dataset.iloc[:, :-1] ## independent features
y=dataset.iloc[:, -1] ## dependent features

```

Linear Regression

```

# 0.00237 0.0 2.10 0.0 0.430 0.990 40.0 0.0022 0.0 222.0 10.1 394.00 2.94 33.4

from sklearn.model_selection import cross_val_score
from sklearn.linear_model import LinearRegression

lin_regressor=LinearRegression()
mse=cross_val_score(lin_regressor,X,y,scoring='neg_mean_squared_error',cv=5)
mean_mse=np.mean(mse)
print(mean_mse)

-37.13180746769905

```

Ridge Regression

```

from sklearn.linear_model import Ridge
from sklearn.model_selection import GridSearchCV

ridge=Ridge()
parameters={'alpha':[1e-15,1e-10,1e-8,1e-3,1e-2,1,5,10,20,30,35,40,45,50,55,100]}
ridge_regressor=GridSearchCV(ridge,parameters,scoring='neg_mean_squared_error',cv=5)
ridge_regressor.fit(X,y)

GridSearchCV(cv=5, estimator=Ridge(),
             param_grid={'alpha': [1e-15, 1e-10, 1e-08, 0.001, 0.01, 1, 5, 10,
                                   20, 30, 35, 40, 45, 50, 55, 100]},
             scoring='neg_mean_squared_error')

print(ridge_regressor.best_params_)
print(ridge_regressor.best_score_)

{'alpha': 100}
-29.905701947540383

```

Lasso Regression

```

from sklearn.linear_model import Lasso
from sklearn.model_selection import GridSearchCV
lasso=Lasso()
parameters={'alpha':[1e-15,1e-10,1e-8,1e-3,1e-2,1,5,10,20,30,35,40,45,50,55,100]}
lasso_regressor=GridSearchCV(lasso,parameters,scoring='neg_mean_squared_error',cv=5)

lasso_regressor.fit(X,y)
print(lasso_regressor.best_params_)
print(lasso_regressor.best_score_)

C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear_model\_coordinate_descent.py:647: ConvergenceWarning: Objective did not converge
model = cd_fast.enet_coordinate_descent(
C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear_model\_coordinate_descent.py:647: ConvergenceWarning: Objective did not converge
model = cd_fast.enet_coordinate_descent(
C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear_model\_coordinate_descent.py:647: ConvergenceWarning: Objective did not converge
model = cd_fast.enet_coordinate_descent(
C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear_model\_coordinate_descent.py:647: ConvergenceWarning: Objective did not converge
model = cd_fast.enet_coordinate_descent(
C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear_model\_coordinate_descent.py:647: ConvergenceWarning: Objective did not converge
model = cd_fast.enet_coordinate_descent(
{'alpha': 1}
-35.531580220694856

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=0)


prediction_lasso=lasso_regressor.predict(X_test)
prediction_ridge=ridge_regressor.predict(X_test)

```

```
import seaborn as sns
```

```
sns.distplot(y_test-prediction_lasso)
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2619: FutureWarning: `distplot` is a deprecated function and will be
warnings.warn(msg, FutureWarning)
<AxesSubplot:xlabel='Price', ylabel='Density'>
```



```
import seaborn as sns
```

```
sns.distplot(y_test-prediction_ridge)
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2619: FutureWarning: `distplot` is a deprecated function and will be
warnings.warn(msg, FutureWarning)
<AxesSubplot:xlabel='Price', ylabel='Density'>
```

