

Hans-Jürgen Schöning

Mastering PostgreSQL 10

Expert techniques on PostgreSQL 10 development and administration



Packt>

Mastering PostgreSQL 10

Expert techniques on PostgreSQL 10 development and administration

Hans-Jürgen Schöning



BIRMINGHAM - MUMBAI

Mastering PostgreSQL 10

Copyright © 2018 Packt Publishing

All rights reserved. No part of this book may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, without the prior written permission of the publisher, except in the case of brief quotations embedded in critical articles or reviews.

Every effort has been made in the preparation of this book to ensure the accuracy of the information presented. However, the information contained in this book is sold without warranty, either express or implied. Neither the author, nor Packt Publishing or its dealers and distributors, will be held liable for any damages caused or alleged to have been caused directly or indirectly by this book.

Packt Publishing has endeavored to provide trademark information about all of the companies and products mentioned in this book by the appropriate use of capitals. However, Packt Publishing cannot guarantee the accuracy of this information.

Commissioning Editor: Amey Varangaonkar

Acquisition Editor: Namrata Patil

Content Development Editor: Eisha Dsouza

Technical Editor: Varsha Shivhare

Copy Editors: Ulka Manjrekar, Safis Editing

Project Coordinator: Shweta H Birwatkar

Proofreader: Safis Editing

Indexer: Rekha Nair

Graphics: Kirk D'Penha

Production Coordinator: Shantanu Zagade

First published: January 2018

Production reference: 1300118

Published by Packt Publishing Ltd.

Livery Place

35 Livery Street

Birmingham

B3 2PB, UK.

ISBN 978-1-78847-229-6

www.packtpub.com



`mapt.io`

Mapt is an online digital library that gives you full access to over 5,000 books and videos, as well as industry leading tools to help you plan your personal development and advance your career. For more information, please visit our website.

Why subscribe?

- Spend less time learning and more time coding with practical eBooks and Videos from over 4,000 industry professionals
- Improve your learning with Skill Plans built especially for you
- Get a free eBook or video every month
- Mapt is fully searchable
- Copy and paste, print, and bookmark content

PacktPub.com

Did you know that Packt offers eBook versions of every book published, with PDF and ePub files available? You can upgrade to the eBook version at www.PacktPub.com and as a print book customer, you are entitled to a discount on the eBook copy. Get in touch with us at service@packtpub.com for more details.

At www.PacktPub.com, you can also read a collection of free technical articles, sign up for a range of free newsletters, and receive exclusive discounts and offers on Packt books and eBooks.

Contributors

About the author

Hans-Jürgen Schönig has 18 years of experience with PostgreSQL. He is the CEO of a PostgreSQL consulting and support company called Cybertec Schönig & Schönig GmbH. It has successfully served countless customers around the globe.

Before founding Cybertec Schönig & Schönig GmbH in 2000, he worked as a database developer at a private research company that focused on the Austrian labor market, where he primarily worked on data mining and forecast models. He has also written several books about PostgreSQL.

About the reviewer

Sheldon Strauch is a 23-year veteran of software consulting at companies such as IBM, Sears, Ernst & Young, and Kraft Foods. He has a bachelor's degree in business administration and leverages his technical skills to improve businesses' self-awareness. His interests include data gathering, management, and mining; maps and mapping; business intelligence; and the application of data analysis for continuous improvement. He is currently focusing on the development of end-to-end data management and mining at Enova International, a financial services company located in Chicago. In his spare time, he enjoys performing arts, particularly music, and traveling with his wife, Marilyn.

Packt is searching for authors like you

If you're interested in becoming an author for Packt, please visit authors.packtpub.com and apply today. We have worked with thousands of developers and tech professionals, just like you, to help them share their insight with the global tech community. You can make a general application, apply for a specific hot topic that we are recruiting an author for, or submit your own idea.

Table of Contents

Preface	1
Chapter 1: PostgreSQL Overview	5
What is new in PostgreSQL 10.0?	5
Understanding new database administration functions	6
Using additional information in pg_stat_activity	6
Introducing SCRAM-SHA-256	7
Improving support for replication	7
Understanding logical replication	7
Introducing quorum COMMIT	8
Partitioning data	9
Making use of CREATE STATISTICS	10
Improving parallelism	11
Introducing ICU encodings	11
Summary	12
Chapter 2: Understanding Transactions and Locking	13
Working with PostgreSQL transactions	14
Handling errors inside a transaction	16
Making use of SAVEPOINT	17
Transactional DDLs	18
Understanding basic locking	20
Avoiding typical mistakes and explicit locking	22
Considering alternative solutions	24
Making use of FOR SHARE and FOR UPDATE	25
Understanding transaction isolation levels	29
Considering SSI transactions	31
Observing deadlocks and similar issues	31
Utilizing advisory locks	34
Optimizing storage and managing cleanup	35
Configuring VACUUM and autovacuum	36
Digging into transaction wraparound-related issues	37
A word on VACUUM FULL	38
Watching VACUUM at work	39
Making use of snapshot too old	43
Summary	43

Chapter 3: Making Use of Indexes	44
Understanding simple queries and the cost model	45
Making use of EXPLAIN	46
Digging into the PostgreSQL cost model	48
Deploying simple indexes	50
Making use of sorted output	51
Using more than one index at a time	52
Using bitmap scans effectively	53
Using indexes in an intelligent way	54
Improving speed using clustered tables	56
Clustering tables	59
Making use of index only scans	60
Understanding additional b-tree features	61
Combined indexes	61
Adding functional indexes	62
Reducing space consumption	63
Adding data while indexing	65
Introducing operator classes	65
Hacking up an operator class for a b-tree	67
Creating new operators	67
Creating operator classes	71
Testing custom operator classes	71
Understanding PostgreSQL index types	72
Hash indexes	73
GiST indexes	73
Understanding how GiST works	74
Extending GiST	75
GIN indexes	76
Extending GIN	77
SP-GiST indexes	78
BRIN indexes	78
Extending BRIN indexes	80
Adding additional indexes	80
Achieving better answers with fuzzy searching	82
Taking advantage of pg_trgm	82
Speeding up LIKE queries	85
Handling regular expressions	86
Understanding full-text search - FTS	86
Comparing strings	87
Defining GIN indexes	88

Debugging your search	89
Gathering word statistics	90
Taking advantage of exclusion operators	91
Summary	92
Chapter 4: Handling Advanced SQL	93
Introducing grouping sets	93
Loading some sample data	94
Applying grouping sets	94
Investigating performance	97
Combining grouping sets with the FILTER clause	98
Making use of ordered sets	99
Understanding hypothetical aggregates	101
Utilizing windowing functions and analytics	102
Partitioning data	103
Ordering data inside a window	104
Using sliding windows	105
Abstracting window clauses	108
Making use of onboard windowing functions	108
The rank and dense_rank functions	109
The ntile() function	110
The lead() and lag() functions	111
The first_value(), nth_value(), and last_value() functions	114
The row_number() function	116
Writing your own aggregates	117
Creating simple aggregates	117
Adding support for parallel queries	121
Improving efficiency	121
Writing hypothetical aggregates	123
Summary	125
Chapter 5: Log Files and System Statistics	126
Gathering runtime statistics	126
Working with PostgreSQL system views	126
Checking live traffic	127
Inspecting databases	130
Inspecting tables	133
Making sense of pg_stat_user_tables	134
Digging into indexes	136
Tracking the background worker	137
Tracking, archiving, and streaming	138
Checking SSL connections	141
Inspecting transactions in real time	141

Tracking vacuum progress	142
Using pg_stat_statements	143
Creating log files	147
Configuring the postgresql.conf file	147
Defining log destination and rotation	148
Configuring syslog	150
Logging slow queries	150
Defining what and how to log	151
Summary	153
Chapter 6: Optimizing Queries for Good Performance	154
Learning what the optimizer does	154
Optimizations by example	155
Evaluating join options	155
Nested loops	156
Hash joins	156
Merge joins	156
Applying transformations	157
Inlining the view	157
Flattening subselects	158
Applying equality constraints	158
Exhaustive searching	159
Trying it all out	159
Making the process fail	160
Constant folding	161
Understanding function inlining	162
Join pruning	163
Speedup set operations	164
Understanding execution plans	166
Approaching plans systematically	166
Making EXPLAIN more verbose	168
Spotting problems	168
Spotting changes in runtime	169
Inspecting estimates	169
Inspecting buffer usage	171
Fixing high buffer usage	173
Understanding and fixing joins	173
Getting joins right	173
Processing outer joins	175
Understanding the join_collapse_limit variable	176
Enabling and disabling optimizer settings	177
Understanding genetic query optimization	180
Partitioning data	181
Creating partitions	182

Applying table constraints	184
Modifying inherited structures	185
Moving tables in and out of partitioned structures	186
Cleaning up data	187
Understanding PostgreSQL 10.0 partitioning	188
Adjusting parameters for good query performance	189
Speeding up sorting	192
Speeding up administrative tasks	194
Summary	194
Chapter 7: Writing Stored Procedures	195
Understanding stored procedure languages	195
The anatomy of a stored procedure	197
Introducing dollar quoting	198
Making use of anonymous code blocks	199
Using functions and transactions	199
Understanding various stored procedure languages	201
Introducing PL/pgSQL	202
Handling quoting	203
Managing scopes	206
Understanding advanced error handling	207
Making use of GET DIAGNOSTICS	208
Using cursors to fetch data in chunks	210
Utilizing composite types	214
Writing triggers in PL/pgSQL	215
Introducing PL/Perl	220
Using PL/Perl for datatype abstraction	221
Deciding between PL/Perl and PL/PerlU	223
Making use of the SPI interface	224
Using SPI for set returning functions	224
Escaping in PL/Perl and support functions	226
Sharing data across function calls	226
Writing triggers in Perl	227
Introducing PL/Python	227
Writing simple PL/Python code	228
Using the SPI interface	229
Handling errors	231
Improving stored procedure performance	232
Reducing the number of function calls	232
Using cached plans	233
Assigning costs to functions	233
Using stored procedures	234
Summary	235

Chapter 8: Managing PostgreSQL Security	237
Managing network security	237
Understanding bind addresses and connections	238
Inspecting connections and performance	240
Living in a world without TCP	240
Managing pg_hba.conf	242
Handling SSL	244
Handling instance-level security	246
Creating and modifying users	249
Defining database-level security	251
Adjusting schema-level permissions	253
Working with tables	256
Handling column-level security	257
Configuring default privileges	259
Digging into row-level security - RLS	260
Inspecting permissions	264
Reassigning objects and dropping users	266
Summary	268
Chapter 9: Handling Backup and Recovery	269
Performing simple dumps	269
Running pg_dump	270
Passing passwords and connection information	271
Using environment variables	272
Making use of .pgpass	273
Using service files	273
Extracting subsets of data	274
Handling various formats	275
Replaying backups	276
Handling global data	277
Summary	278
Chapter 10: Making Sense of Backups and Replication	279
Understanding the transaction log	280
Looking at the transaction log	281
Understanding checkpoints	282
Optimizing the transaction log	282
Transaction log archiving and recovery	284
Configuring for archiving	284
Configuring the pg_hba.conf file	286
Creating base backups	286

Reducing the bandwidth of a backup	288
Mapping tablespaces	288
Using different formats	288
Testing transaction log archiving	289
Replaying the transaction log	290
Finding the right timestamp	292
Cleaning up the transaction log archive	294
Setting up asynchronous replication	295
Performing a basic setup	295
Improving security	298
Halting and resuming replication	298
Checking replication to ensure availability	299
Performing failovers and understanding timelines	302
Managing conflicts	303
Making replication more reliable	306
Upgrading to synchronous replication	307
Adjusting durability	309
Making use of replication slots	311
Handling physical replication slots	312
Handling logical replication slots	314
Use cases of logical slots	317
Making use of CREATE PUBLICATION and CREATE SUBSCRIPTION	318
Summary	319
Chapter 11: Deciding on Useful Extensions	321
Understanding how extensions work	322
Checking for available extensions	323
Making use of contrib modules	326
Using the adminpack	326
Applying bloom filters	328
Deploying btree_gist and btree_gin	329
Dblink - considering phasing out	331
Fetching files with file_fdw	332
Inspecting storage using pageinspect	334
Investigating caching with pg_buffercache	336
Encrypting data with pgcrypto	338
Prewarming caches with pg_prewarm	338
Inspecting performance with pg_stat_statements	339
Inspecting storage with pgstattuple	339
Fuzzy searches with pg_trgm	342
Connecting to remote servers using postgres_fdw	342

Handling mistakes and typos	346
Other useful extensions	346
Summary	347
Chapter 12: Troubleshooting PostgreSQL	348
Approaching an unknown database	348
Inspecting pg_stat_activity	349
Querying pg_stat_activity	349
Treating Hibernate statements	351
Figuring out where queries come from	351
Checking for slow queries	352
Inspecting individual queries	353
Digging deeper with perf	354
Inspecting the log	355
Checking for missing indexes	356
Checking for memory and I/O	357
Understanding noteworthy error scenarios	359
Facing clog corruption	359
Understanding checkpoint messages	360
Managing corrupted data pages	361
Careless connection management	362
Fighting table bloat	363
Summary	364
Chapter 13: Migrating to PostgreSQL	365
Migrating SQL statements to PostgreSQL	366
Using lateral joins	366
Supporting lateral	366
Using grouping sets	367
Supporting grouping sets	367
Using the WITH clause – common table expressions	368
Supporting the WITH clause	368
Using the WITH RECURSIVE clause	369
Supporting the WITH RECURSIVE clause	369
Using the FILTER clause	369
Supporting the FILTER clause	370
Using windowing functions	370
Supporting windowing and analytics	371
Using ordered sets – WITHIN GROUP clause	371
Supporting the WITHIN GROUP clause	372
Using the TABLESAMPLE clause	372
Supporting TABLESAMPLE clause	373

Using limit/offset	373
Supporting the FETCH FIRST clause	374
Using OFFSET	374
Supporting the OFFSET clause	374
Using temporal tables	375
Supporting temporal tables	375
Matching patterns in time series	375
Moving from Oracle to PostgreSQL	376
Using the oracle_fdw extension to move data	376
Using ora2pg to migrate from Oracle	378
Common pitfalls	380
Moving from MySQL or MariaDB to PostgreSQL	382
Handling data in MySQL and MariaDB	382
Changing column definitions	384
Handling null values	386
Expecting problems	387
Migrating data and schema	387
Using pg_chameleon	387
Using FDWs	388
Summary	391
Other Books You May Enjoy	392
Index	395

Preface

PostgreSQL is an advanced relational open source database, which is also an excellent foundation for NoSQL workloads. It is capable of handling large datasets and running complex SQL for your business needs. This book will enable you to build better PostgreSQL applications and administer databases more efficiently. It will give you valuable insights into how to use PostgreSQL best for your advantage.

Who this book is for

This book has explicitly been written for people who want to know more about PostgreSQL and who are not satisfied with basic information. The aim is to write a book that goes a bit deeper and explains the most important stuff in a clear and easy-to-understand way.

What this book covers

Chapter 1, *PostgreSQL Overview*, provides an overview of PostgreSQL and its features. You will learn new stuff and the new functionalities available in PostgreSQL.

Chapter 2, *Understanding Transactions and Locking*, covers one of the most important aspects of any database system: proper database work is usually not possible without the existence of transactions. Understanding transactions and locking is vital to performance, as well as professional work.

Chapter 3, *Making Use of Indexes*, covers everything you need to know about indexes. Indexes are key to performance and are therefore an important cornerstone if you want a good user experience and high throughput. All the important aspects of indexing will be covered.

Chapter 4, *Handling Advanced SQL*, introduces you to some of the most important concepts of modern SQL. You will learn about windowing functions as well as other important current elements of SQL.

Chapter 5, *Log Files and System Statistics*, guides you through administrative tasks such as log file management and monitoring. You will learn how to inspect your servers and extract runtime information from PostgreSQL.

Chapter 6, *Optimizing Queries for Good Performance*, tells you everything you need to know about good PostgreSQL performance. The chapter covers SQL tuning as well as information about memory management.

Chapter 7, *Writing Stored Procedures*, teaches you some of the advanced topics related to server-side code. The most important server-side programming languages are covered and important aspects are pointed out.

Chapter 8, *Managing PostgreSQL Security*, is designed to help you improve the security of your server. The chapter features everything from user management to **Row-Level Security (RLS)**. Information about encryption is also included.

Chapter 9, *Handling Backup and Recovery*, is all about backups and data recovery. You will learn to back up your data, which will enable you to restore things in the event of a disaster.

Chapter 10, *Making Sense of Backups and Replication*, is all about redundancy. You will learn to asynchronously and synchronously replicate PostgreSQL database systems. All modern features are covered as extensively as possible.

Chapter 11, *Deciding on Useful Extensions*, describes widely used modules that add more functionality to PostgreSQL. You will learn about the most common extensions.

Chapter 12, *Troubleshooting PostgreSQL*, offers a systematic approach to fixing problems in PostgreSQL. It will enable you to spot common problems and approach them in an organized way.

Chapter 13, *Migrating to PostgreSQL*, is the final chapter of this book and shows you how to migrate from commercial databases to PostgreSQL. The chapter covers the most important databases migrated these days.

To get the most out of this book

This book has been written for a broad audience. In order to follow the examples presented in this book, it makes sense to have at least some experience with SQL and maybe even PostgreSQL in general (although this is not a strict requirement). In general, it is a good idea to be familiar with the UNIX command line.

Download the color images

We also provide a PDF file that has color images of the screenshots/diagrams used in this book. You can download it here: http://www.packtpub.com/sites/default/files/downloads/MasteringPostgreSQL10_ColorImages.pdf.

Conventions used

There are a number of text conventions used throughout this book.

CodeInText: Indicates code words in text, database table names, folder names, filenames, file extensions, pathnames, dummy URLs, user input, and Twitter handles. Here is an example: "To figure out what is going wrong, PostgreSQL offers the `EXPLAIN` command."

Any command-line input or output is written as follows:

```
test=# EXPLAIN SELECT * FROM t_test
ORDER BY id DESC
LIMIT 10;
```



Warnings or important notes appear like this.



Tips and tricks appear like this.

Get in touch

Feedback from our readers is always welcome.

General feedback: Email feedback@packtpub.com and mention the book title in the subject of your message. If you have questions about any aspect of this book, please email us at questions@packtpub.com.

Errata: Although we have taken every care to ensure the accuracy of our content, mistakes do happen. If you have found a mistake in this book, we would be grateful if you would report this to us. Please visit www.packtpub.com/submit-errata, selecting your book, clicking on the Errata Submission Form link, and entering the details.

Piracy: If you come across any illegal copies of our works in any form on the Internet, we would be grateful if you would provide us with the location address or website name. Please contact us at copyright@packtpub.com with a link to the material.

If you are interested in becoming an author: If there is a topic that you have expertise in and you are interested in either writing or contributing to a book, please visit authors.packtpub.com.

Reviews

Please leave a review. Once you have read and used this book, why not leave a review on the site that you purchased it from? Potential readers can then see and use your unbiased opinion to make purchase decisions, we at Packt can understand what you think about our products, and our authors can see your feedback on their book. Thank you!

For more information about Packt, please visit packtpub.com.

1

PostgreSQL Overview

PostgreSQL is one of the world's most advanced open source database systems, and it has many features that are widely used by developers and system administrators alike. Starting with PostgreSQL 10, many new features have been added to PostgreSQL, which contribute greatly to the success of this exceptional open source product. In this book, many of these cool features will be covered and discussed in great detail.

In this chapter, you will be introduced to PostgreSQL and its cool new features available in PostgreSQL 10.0 and beyond. All relevant new functionalities will be covered in detail. Given the sheer number of changes made to the code and given the size of the PostgreSQL project, this list of features is of course by far not complete, so I tried to focus on the most important aspects relevant to most people.

The features outlined in this chapter will be split into the following categories:

- Database administration
- SQL and developer related
- Backup, recovery, and replication
- Performance-related topics

What is new in PostgreSQL 10.0?

PostgreSQL 10.0 has been released in late 2017 and is the first version that follows the new numbering scheme introduced by the PostgreSQL community. From now on, the way major releases are done will change and therefore, the next major version after PostgreSQL 10.0 will not be 10.1 but PostgreSQL 11. Versions 10.1 and 10.2 are merely service releases and will only contain bug fixes.

Understanding new database administration functions

PostgreSQL 10.0 has many new features that can help the administrator reduce work and make systems more robust.

One of these features that makes life easier for administrators is related to additional information in `pg_stat_activity`.

Using additional information in `pg_stat_activity`

Before PostgreSQL 10.0, `pg_stat_activity` only contained information about normal backend processes serving end users (connections). However, this has changed. Since PostgreSQL 10.0, a lot more information is exposed. It is possible to figure out what these other system processes are doing.

The following listing shows the content of `pg_stat_activity` on an idle database instance:

```
test=# \x
Expanded display is on.

test=# SELECT pid, wait_event_type, wait_event, backend_type
       FROM pg_stat_activity ;

-[ RECORD 1 ]-----+-----
pid           | 12159
wait_event_type | Activity
wait_event     | AutoVacuumMain
backend_type   | autovacuum launcher
-[ RECORD 2 ]-----+-----
pid           | 12161
wait_event_type | Activity
wait_event     | LogicalLauncherMain
backend_type   | background worker
-[ RECORD 3 ]-----+-----
pid           | 12628
wait_event_type | 
wait_event     | 
backend_type   | client backend
-[ RECORD 4 ]-----+-----
pid           | 12156
wait_event_type | Activity
wait_event     | BgWriterMain
```

```

backend_type      | background writer
-[ RECORD 5 ]----+-----
pid               | 12155
wait_event_type   | Activity
wait_event        | CheckpointerMain
backend_type      | checkpointer
-[ RECORD 6 ]----+-----
pid               | 12157
wait_event_type   | Activity
wait_event        | WalWriterMain
backend_type      | walwriter

```

What you see here is that every server process is listed. It will allow you to gain some insights into what is happening the server.

Introducing SCRAM-SHA-256

Most people use passwords to connect to the database and manage security. Traditionally, people utilized md5. However, md5 is not safe anymore and therefore new authentication methods are needed. Starting with version 10.0, PostgreSQL supports SCRAM-SHA-256, which is far safer than the previous authentication method.

The old way of doing it is still supported. However, it is strongly recommended to move to SCRAM-SHA-256 in favor of md5.

Improving support for replication

The introduction of PostgreSQL also saw the introduction of logical replication, which has not been in the core before.

Understanding logical replication

Since version 8.0, PostgreSQL has supported binary replication (also often referred to as WAL-shipping). The ability to distribute transaction log (WAL) has been improved steadily over the years.

With the introduction of PostgreSQL 10.0, a new feature has been added to PostgreSQL—Logical replication. How does it work? Logical replication allows you to publish a set of tables on one server and ask other servers to subscribe to the changes.

To publish data, the new `CREATE PUBLICATION` command has been introduced:

```
test=# \h CREATE PUBLICATION
Command:  CREATE PUBLICATION
Description: define a new publication
Syntax:
CREATE PUBLICATION name
    [ FOR TABLE [ ONLY ] table_name [ * ] [, ...]
      | FOR ALL TABLES ]
    [ WITH ( publication_parameter [= value] [, ... ] ) ]
```

Once the data has been published, remote servers can subscribe to these changes and receive information about what has happened to those published data sets:

```
test=# \h CREATE SUBSCRIPTION
Command:  CREATE SUBSCRIPTION
Description: define a new subscription
Syntax:
CREATE SUBSCRIPTION subscription_name
    CONNECTION 'conninfo'
    PUBLICATION publication_name [, ...]
    [ WITH ( subscription_parameter [= value] [, ... ] ) ]
```

`CREATE SUBSCRIPTION` is used on the slave side to attach to these changes. The beauty of the concept is that a server can publish one set of tables while subscribing to some other tables at the same time—there is no such thing as always master or always slave anymore. Logical replication allows you to flexibly distribute data.

Introducing quorum COMMIT

PostgreSQL has offered support to synchronous replication for quite some time now. Traditionally, only one server could act as a synchronous standby. This has changed. In PostgreSQL 10.0, the community has introduced quorum COMMITs. The idea is actually quite simple. Suppose you want five out of seven servers to confirm a transaction before the master returns a `COMMIT`. This is exactly what a quorum COMMIT does. It gives the developers and administrators a chance to define what COMMIT does in a more fine-grained way.

To configure quorum COMMITs, the syntax of `synchronous_standby_names` has been extended. Here are two simple examples:

```
synchronous_standby_names = ANY 1 (s1, s2)  
synchronous_standby_names = ANY 2 (s1, s2, s3)
```

Partitioning data

There have been talks about introducing partitioning to PostgreSQL for years. However, big, important features take time to implement and this is especially true if you are aiming for a good, extensible, and future-proof implementation. In PostgreSQL 10.0, table partitioning has finally made it to the PostgreSQL core. Of course, the implementation is far from complete, and a lot of work has to be done in the future to add even more features. However, support for partitioning is important and will definitely be one of the most desirable things in PostgreSQL 10.0.

As of now, partitioning is able to:

- Automatically create proper child constraints
- Route changes made to the parent table to the child table

However, as stated earlier, there are still a couple of missing features that have not been addressed yet. Here are some of the more important things:

- Create child tables automatically in case data comes in, which is not covered by partitioning criteria yet
- No support for hash partitioning
- Move updated rows that no longer match the partition
- Handle partitions in parallel

The roadmap for PostgreSQL 11.0 already suggests that many of these things might be supported in the next release.

Making use of CREATE STATISTICS

`CREATE STATISTICS` is definitely one of my personal favorite features of PostgreSQL 10.0 because it allows consultants to help customers in many real-world situations. So, what is it all about? When you run SQL, the optimizer has to come up with clever decisions to speed up your queries. However, to do so, it has to rely heavily on estimates to figure out how much data a certain clause or a certain operation returns. Before version 10.0, PostgreSQL only had information about individual columns. Let's look at an example:

```
SELECT * FROM car WHERE vendor = 'Ford' AND model = 'Mini Clubman';
```

In version 9.6, PostgreSQL checks which fraction of the table matches `Ford` and which fraction matches `Mini Clubman`. Then, it would try to guess how many rows match both criteria. Remember, PostgreSQL 9.6 only has information about each column—it does not know that these columns are actually related. Therefore, it will simply multiply the odds of finding `Ford` with the odds of finding `Mini Clubman` and use this number. However, `Ford` does not produce a `Mini Clubman` instance—only BMW does. Therefore, the estimate is wrong. The same cross column correlation problem can happen in other cases too. The number of rows returned by a join might not be clear and the number of groups returned by a `GROUP BY` clause might be an issue.

Consider the following example:

```
SELECT gender, age, count(*) FROM children_born GROUP BY gender, age
```

The number of children born to people of a certain age will definitely depend on their age. The likelihood that some 30 year old women will have children is pretty high and therefore there will be a count. However, if you happen to be 98, you might not be so lucky and it is pretty unrealistic to have a baby, especially if you are a man (men tend to not give birth to children).

`CREATE STATISTICS` will give the optimizer a chance to gain deeper insights into what is going on by storing multivariate statistics. The idea is to help the optimizer handle functional dependencies.

Improving parallelism

PostgreSQL 9.6 was the first version supporting parallel queries in their most basic form. Of course, not all parts of the server are fully parallel yet. Therefore, it is an ongoing effort to speed up even more operations than before. PostgreSQL 10.0 is a major step towards even more parallelism as a lot more operations can now benefit from multi-core systems.

Indexes are a key area of improvement and will benefit greatly from additional features introduced into PostgreSQL 10.0. There is now full support for parallel b-tree scans as well as for bitmap scans. For now, only b-tree indexes can benefit from parallelism but this will most likely change in future releases too, to ensure that all types of indexes can enjoy an even better performance.

In addition to indexing, the PostgreSQL community has also worked hard to introduce support for parallel merge joins and to allow for more procedures to run in parallel. Some of the latest blog posts from the PostgreSQL community already suggest that many new features related to parallelism are in the pipeline for PostgreSQL 11.0.

Introducing ICU encodings

When a PostgreSQL database is created, the administrator can choose the encoding, which should be used to store the data. Basically, the configuration decides which characters exist and in which order they are displayed. Here is an example—`de_AT@UTF-8`. In this case, we will use Unicode characters, which will be displayed in an Austrian sort order (Austrians speak some sort of German). So, `de_AT` will define the order in which the data will be sorted.

To achieve this kind of sorting, PostgreSQL relies heavily on the operating system. The trouble is that if the sort order of characters changes in the operating system for some reason (maybe because of a bug or because of some other reason), PostgreSQL will have troubles with its indexes. A normal b-tree index is basically a sorted list, and if the sort order changes, naturally, there is a problem.

The introduction of the ICU library is supposed to fix this problem. ICU offers stronger promises than the operating system and is, therefore, more suitable for long-term storage of data. With the introduction of PostgreSQL 10.0, ICU encodings can be enabled.

Summary

In PostgreSQL 10.0, a lot of functionalities have been added that allow people to run even more professional applications even faster and more efficiently. All areas of the database server have been improved and many new professional features have been added. In the future, even more improvements will be made. Of course, the changes listed in this chapter are by far not complete because many small changes were made.

2

Understanding Transactions and Locking

Locking is an important topic in any kind of database. It is not enough to understand just how it works to write proper or better applications; it is also essential from a performance point of view. Without handling locks properly, your applications might not only be slow, they might also be wrong and behave in very unexpected ways. In my opinion, locking is the key to performance and having a good overview will certainly help. Therefore, understanding locking and transaction is important for administrators and developers alike. In this chapter, you will learn the following topics:

- Working with PostgreSQL transactions
- Understanding basic locking
- Making use of `FOR SHARE` and `FOR UPDATE`
- Understanding transaction isolation levels
- Considering SSI transactions
- Observing deadlocks and similar issues
- Optimizing storage and managing cleanups

At the end of the chapter, you will be able to understand and utilize PostgreSQL transactions in the most efficient way possible.

Working with PostgreSQL transactions

PostgreSQL provides you with a highly advanced transaction machinery that offers countless features to developers and administrators alike. In this section, it is time to look at the basic concept of transactions.

The first important thing to know is that in PostgreSQL, everything is a transaction. If you send a simple query to the server, it is already a transaction. Here is an example:

```
test=# \x
Expanded display is on.
test=# SELECT now(), now();
              now              |              now
-----+-----
2017-08-24 16:03:27.174253+02 | 2017-08-24 16:03:27.174253+02
(1 row)
```

In this case, the `SELECT` statement will be a separate transaction. If the same command is executed again, different timestamps will be returned.



Keep in mind that the `now()` function will return the transaction time. The `SELECT` statement will, therefore, always return two identical timestamps.

If more than one statement has to be a part of the same transaction, the `BEGIN` statement must be used:

```
test=# \h BEGIN
Command: BEGIN
Description: Start a transaction block
Syntax:
BEGIN [ WORK | TRANSACTION ] [ transaction_mode [, ...] ]
```

where `transaction_mode` is one of:

```
ISOLATION LEVEL { SERIALIZABLE | REPEATABLE READ
| READ COMMITTED | READ UNCOMMITTED }
READ WRITE | READ ONLY
[ NOT ] DEFERRABLE
```

The `BEGIN` statement will ensure that more than one command will be packed into a transaction. Here is how it works:

```
test=# BEGIN;
BEGIN
test=# SELECT now();
           now
-----
2017-08-24 16:04:08.105131+02
(1 row)
test=# SELECT now();
           now
-----
2017-08-24 16:04:08.105131+02
(1 row)
test=# COMMIT;
COMMIT
```

The important point here is that both timestamps will be identical. As mentioned earlier, we are talking about transaction time here.

To end the transaction, `COMMIT` can be used:

```
test=# \h COMMIT
Command: COMMIT
Description: Commit the current transaction
Syntax:
COMMIT [ WORK | TRANSACTION ]
```

There are a couple of syntax elements here. You can just use `COMMIT`, `COMMIT WORK`, or `COMMIT TRANSACTION`. All three options have the same meaning. If this is not enough, there is more:

```
test=# \h END
Command: END
Description: commit the current transaction
Syntax:
END [ WORK | TRANSACTION ]
```

The `END` clause is the same as the `COMMIT` clause.

`ROLLBACK` is the counterpart of `COMMIT`. Instead of successfully ending a transaction, it will simply stop the transaction without ever making things visible to other transactions:

```
test=# \h ROLLBACK
Command: ROLLBACK
Description: Abort the current transaction
Syntax:
ROLLBACK [ WORK | TRANSACTION ]
```

Some applications use `ABORT` instead of `ROLLBACK`. The meaning is the same.

Handling errors inside a transaction

It is not always the case that transactions are correct from beginning to end. However, in PostgreSQL, only error-free transactions can be committed. Here is what happens:

```
test=# BEGIN;
BEGIN
test=# SELECT 1;
?column?
-----
      1
(1 row)
test=# SELECT 1 / 0;
ERROR: division by zero
test=# SELECT 1;
ERROR: current transaction is aborted, commands ignored until end of
transaction block
test=# COMMIT;
ROLLBACK
```

Note that `division by zero` did not work out.



In any proper database, an instruction similar to this will instantly error-out and make the statement fail.

It is important to point out that PostgreSQL will error-out, unlike MySQL, which is far less strict. After an error has occurred, no more instructions will be accepted even if those instructions are semantically and syntactically correct. It is still possible to issue a `COMMIT`. However, PostgreSQL will roll back the transaction because it is the only correct thing to be done at this point.

Making use of SAVEPOINT

In professional applications, it can be pretty hard to write reasonably long transactions without ever encountering a single error. To solve the problem, users can utilize something called `SAVEPOINT`. As the name indicates, it is a safe place inside a transaction that the application can return to in the event things go terribly wrong. Here is an example:

```
test=# BEGIN;
BEGIN
test=# SELECT 1;
?column?
-----
      1
(1 row)

test=# SAVEPOINT a;
SAVEPOINT
test=# SELECT 2 / 0;
ERROR:  division by zero
test=# SELECT 2;
ERROR:  current transaction is aborted, commands ignored until end of
transaction block
test=# ROLLBACK TO SAVEPOINT a;
ROLLBACK
test=# SELECT 3;
?column?
-----
      3
```

```
(1 row)
```

```
test=# COMMIT;  
COMMIT
```

After the first `SELECT` clause, I decided to create `SAVEPOINT` to make sure that the application can always return to this point inside the transaction. As you can see, `SAVEPOINT` has a name, which is referred to later.

After returning the savepoint called `a`, the transaction can proceed normally. The code has jumped back before the error, so everything is fine.

The number of savepoints inside a transaction is practically unlimited. We have seen customers with over 250,000 savepoints in a single operation. PostgreSQL can easily handle this.

If you want to remove a `SAVEPOINT` from inside a transaction, there is a `RELEASE SAVEPOINT`:

```
test=# \h RELEASE SAVEPOINT  
  
Command: RELEASE SAVEPOINT  
Description: Destroy a previously defined SAVEPOINT  
Syntax:  
RELEASE [ SAVEPOINT ] savepoint_name
```

Many people ask, what will happen if you try to reach a savepoint after a transaction has ended? The answer is, the life of a savepoint ends as soon as the transaction ends. In other words, there is no way to return to a certain point in time after the transactions have been completed.

Transactional DDLs

PostgreSQL has a very nice feature that is unfortunately not present in many commercial database systems. In PostgreSQL, it is possible to run DDLs (commands that change the data structure) inside a transaction block. In a typical commercial system, a DDL will implicitly commit the current transaction. Not so in PostgreSQL.

Apart from some minor exceptions (`DROP DATABASE`, `CREATE TABLESPACE/DROP TABLESPACE`, and so on), all DDLs in PostgreSQL are transactional, which is a huge plus and a real benefit to end users.

Here is an example:

```
test=# \d
No relations found.
test=# BEGIN;
BEGIN
test=# CREATE TABLE t_test (id int);
CREATE TABLE
test=# ALTER TABLE t_test ALTER COLUMN id TYPE int8;
ALTER TABLE
test=# \d t_test
      Table "public.t_test"
  Column |  Type  | Modifiers
-----+-----+-----
   id    | bigint |

```

```
test=# ROLLBACK;
ROLLBACK
test=# \d
No relations found.
```

In this example, a table has been created and modified, and the entire transaction is aborted instantly. As you can see, there is no implicit `COMMIT` or any other strange behavior. PostgreSQL simply acts as expected.

Transactional DDLs are especially important if you want to deploy software. Just imagine running a **Content Management System (CMS)**. If a new version is released, you'll want to upgrade. Running the old version would still be OK; running the new version is also OK but you really don't want a mixture of old and new. Therefore, deploying an upgrade in a single transaction is definitely highly beneficial as it upgrades an atomic operation.



In order to facilitate good software practices, we can include several separately-coded modules from our source control system into a single deployment transaction.

Understanding basic locking

In this section, you will learn basic locking mechanisms. The goal is to understand how locking works in general and how to get simple applications right.

To show how things work, a simple table can be created. For demonstration purposes, I will add one row to the table:

```
test=# CREATE TABLE t_test (id int);
CREATE TABLE
test=# INSERT INTO t_test VALUES (1);
INSERT 0 1
```

The first important thing is that tables can be read concurrently. Many users reading the same data at the same time won't block each other. This allows PostgreSQL to handle thousands of users without problems.



Multiple users can read the same data at the same time without blocking each other.

The question now is: what happens if reads and writes occur at the same time? Here is an example. Let us assume that the table contains one row and its `id = 0`:

Transaction 1	Transaction 2
BEGIN;	BEGIN;
UPDATE t_test SET id = id + 1 RETURNING *;	
User will see 1	SELECT * FROM t_test;
	User will see 1
COMMIT;	COMMIT;

Two transactions are opened. The first one will change a row. However, this is not a problem as the second transaction can proceed. It will return the old row as it was before the `UPDATE`. This behavior is called **Multi-Version Concurrency Control (MVCC)**.



A transaction will see data only if it has been committed by the writing transaction prior to the initiation of the read transaction. One transaction cannot inspect the changes made by another active connection. A transaction can see only those changes that have already been committed.

There is also a second important aspect: many commercial or open source databases are still (as of 2017) unable to handle concurrent reads and writes. In PostgreSQL, this is absolutely not a problem. Reads and writes can coexist.



Writing transactions won't block reading transactions.

After the transaction has been committed, the table will contain 2.

What will happen if two people change data at the same time? Here is an example:

Transaction 1	Transaction 2
BEGIN;	BEGIN;
UPDATE t_test SET id = id + 1 RETURNING *;	
It will return 3	UPDATE t_test SET id = id + 1 RETURNING *;
	It will wait for transaction 1
COMMIT;	It will wait for transaction 1
	It will reread the row, find 3, set the value, and return 4
	COMMIT;

Suppose you want to count the number of hits on a website. If you run the code as outlined just now, no hit can be lost because PostgreSQL guarantees that one `UPDATE` is performed after the other.



PostgreSQL will only lock rows affected by `UPDATE`. So, if you have 1,000 rows, you can theoretically run 1,000 concurrent changes on the same table.

It is also noteworthy that you can always run concurrent reads. Our two writes will not block reads.

Avoiding typical mistakes and explicit locking

In my life as a professional PostgreSQL consultant (<https://www.cybertec-postgresql.com>), I have seen a couple of mistakes that are made again and again. If there are constants in life, these typical mistakes are definitely some of the things that never change.

Here is my favorite:

Transaction 1	Transaction 2
<code>BEGIN;</code>	<code>BEGIN;</code>
<code>SELECT max(id) FROM product;</code>	<code>SELECT max(id) FROM product;</code>
User will see 17	User will see 17
User will decide to use 18	User will decide to use 18
<code>INSERT INTO product ... VALUES (18, ...)</code>	<code>INSERT INTO product ... VALUES (18, ...)</code>
<code>COMMIT;</code>	<code>COMMIT;</code>

In this case, there will be either a duplicate key violation or two identical entries. Neither variation of the problem is all that appealing.

One way to fix the problem is to use explicit table locking:

```
test=# \h LOCK
Command: LOCK
Description: lock a table
Syntax:
LOCK [ TABLE ] [ ONLY ] name [ * ] [, ...] [ IN lockmode MODE ]
      [ NOWAIT ]
```

where lockmode is one of the following:

```
ACCESS SHARE | ROW SHARE | ROW EXCLUSIVE |  
SHARE UPDATE EXCLUSIVE | SHARE |  
SHARE ROW EXCLUSIVE | EXCLUSIVE | ACCESS EXCLUSIVE
```

As you can see, PostgreSQL offers eight types of locks to lock an entire table. In PostgreSQL, a lock can be as light as an `ACCESS SHARE` lock or as heavy as an `ACCESS EXCLUSIVE` lock. The following list shows what these locks do:

- `ACCESS SHARE`: This type of lock is taken by reads and conflicts only with `ACCESS EXCLUSIVE`, which is set by `DROP TABLE` and the like. Practically, this means that `SELECT` cannot start if a table is about to be dropped. This also implies that `DROP TABLE` has to wait until a reading transaction is completed.
- `ROW SHARE`: PostgreSQL takes this kind of lock in the case of `SELECT FOR UPDATE/SELECT FOR SHARE`. It conflicts with `EXCLUSIVE` and `ACCESS EXCLUSIVE`.
- `ROW EXCLUSIVE`: This lock is taken by `INSERT`, `UPDATE`, and `DELETE`. It conflicts with `SHARE`, `SHARE ROW EXCLUSIVE`, `EXCLUSIVE`, and `ACCESS EXCLUSIVE`.
- `SHARE UPDATE EXCLUSIVE`: This kind of lock is taken by `CREATE INDEX CONCURRENTLY`, `ANALYZE`, `ALTER TABLE`, `VALIDATE`, and some other flavors of `ALTER TABLE` as well as by `VACUUM` (not `VACUUM FULL`). It conflicts with the `SHARE UPDATE EXCLUSIVE`, `SHARE`, `SHARE ROW EXCLUSIVE`, `EXCLUSIVE`, and `ACCESS EXCLUSIVE` lock modes.
- `SHARE`: When an index is created, `SHARE` locks will be set. It conflicts with `ROW EXCLUSIVE`, `SHARE UPDATE EXCLUSIVE`, `SHARE ROW EXCLUSIVE`, `EXCLUSIVE`, and `ACCESS EXCLUSIVE`.
- `SHARE ROW EXCLUSIVE`: This one is set by `CREATE TRIGGER` and some forms of `ALTER TABLE` and conflicts with everything but `ACCESS SHARE`.
- `EXCLUSIVE`: This type of lock is by far the most restrictive one. It protects against reads and writes alike. If this lock is taken by a transaction, nobody else can read or write to the table affected.
- `ACCESS EXCLUSIVE`: This lock prevents concurrent transactions from reading and writing.

Given the PostgreSQL locking infrastructure, one solution to the max-problem outlined previously would be as follows:

```
BEGIN;  
LOCK TABLE product IN ACCESS EXCLUSIVE MODE;  
INSERT INTO product SELECT max(id) + 1, ... FROM product;  
COMMIT;
```

Keep in mind that this is a pretty nasty way of doing this kind of operation because nobody else can read or write to the table during your operation. Therefore, `ACCESS EXCLUSIVE` should be avoided at all costs.

Considering alternative solutions

There is an alternative solution to the problem. Consider the following example: you are asked to write an application generating invoice numbers. The tax office might require you to create invoice numbers without gaps and without duplicates. How would you do it? Of course, one solution would be a table lock. However, you can really do better. Here is what I would do:

```
test=# CREATE TABLE t_invoice (id int PRIMARY KEY);
CREATE TABLE
test=# CREATE TABLE t_watermark (id int);
CREATE TABLE
test=# INSERT INTO t_watermark VALUES (0);
INSERT 0
test=# WITH x AS (UPDATE t_watermark SET id = id + 1 RETURNING *)
      INSERT INTO t_invoice
      SELECT * FROM x RETURNING *;

id
----
 1
(1 row)
```

In this case, I introduced a table called `t_watermark`. It contains just one row. The `WITH` will be executed first. The row will be locked and incremented, and the new value will be returned. Only one person can do this at a time. The value returned by the CTE is then used in the invoice table. It is guaranteed to be unique. The beauty is that there is only a simple row lock on the watermark table; no reads will be blocked in the invoice table. Overall, this way is more scalable.

Making use of FOR SHARE and FOR UPDATE

Sometimes, data is selected from the database; then some processing happens in the application and, finally, some changes are made back on the database side. This is a classic example of `SELECT FOR UPDATE`.

Here is an example:

```
BEGIN;
SELECT * FROM invoice WHERE processed = false;
** application magic will happen here **
UPDATE invoice SET processed = true ...
COMMIT;
```

The problem here is that two people might select the same unprocessed data. Changes made to these processed rows will then be overwritten. In short, a race condition will occur.

To solve this problem, developers can make use of `SELECT FOR UPDATE`. Here is how it works:

```
BEGIN;
SELECT * FROM invoice WHERE processed = false FOR UPDATE;
** application magic will happen here **
UPDATE invoice SET processed = true ...
COMMIT;
```

The `SELECT FOR UPDATE` will lock rows just like an `UPDATE` would. This means that no changes can happen concurrently. All locks will be released on `COMMIT` as usual.

If one `SELECT FOR UPDATE` is waiting for some other `SELECT FOR UPDATE`, one has to wait until the other one completes (`COMMIT` or `ROLLBACK`). If the first transaction does not want to end, for whatever reason, the second transaction might potentially wait forever. To avoid this, it is possible to use `SELECT FOR UPDATE NOWAIT`.

Here is how it works:

Transaction 1	Transaction 2
BEGIN;	BEGIN;
SELECT ... FROM tab WHERE ... FOR UPDATE NOWAIT;	
Some processing	SELECT ... FROM tab WHERE ... FOR UPDATE NOWAIT;
Some processing	ERROR: could not obtain lock on row in relation tab

If `NOWAIT` is not flexible enough for you, consider using `lock_timeout`. It will contain the amount of time you want to wait on locks. You can set this on a per-session level:

```
test=# SET lock_timeout TO 5000;
SET
```

In this, the value is set to 5 seconds.

While `SELECT` does basically no locking, `SELECT FOR UPDATE` can be pretty harsh. Just imagine the following business process: we want to fill up an airplane providing 200 seats. Many people want to book seats concurrently. In this case, the following might happen:

Transaction 1	Transaction 2
BEGIN;	BEGIN;
SELECT ... FROM flight LIMIT 1 FOR UPDATE;	
Waiting for user input	SELECT ... FROM flight LIMIT 1 FOR UPDATE;
Waiting for user input	It has to wait

The trouble is that only one seat can be booked at a time. There are potentially 200 seats available but everybody has to wait for the first person. While the first seat is blocked, nobody else can book a seat even if people don't care which seat they get in the end.

`SELECT FOR UPDATE SKIP LOCKED` will fix the problem. Let's create some sample data first:

```
test=# CREATE TABLE t_flight AS
      SELECT * FROM generate_series(1, 200) AS id;
SELECT 200
```

Now comes the magic:

Transaction 1	Transaction 2
<code>BEGIN;</code>	<code>BEGIN;</code>
<code>SELECT * FROM t_flight LIMIT 2 FOR UPDATE SKIP LOCKED;</code>	<code>SELECT * FROM t_flight LIMIT 2 FOR UPDATE SKIP LOCKED;</code>
It will return 1 and 2	It will return 3 and 4

If everybody wants to fetch two rows, we can serve 100 concurrent transactions at a time without having to worry about blocking transactions.



Keep in mind that waiting is the slowest form of execution. If only one transaction can be active at a time, it is pointless to buy ever bigger servers.

However, there is more. In some cases, a `FOR UPDATE` can have unintended consequences. Most people are not aware of the fact that `FOR UPDATE` will have an impact on foreign keys. Let's assume that we have two tables: one to store currencies and the other to store accounts:

```
CREATE TABLE t_currency (id int, name text, PRIMARY KEY (id));
INSERT INTO t_currency VALUES (1, 'EUR');
INSERT INTO t_currency VALUES (2, 'USD');

CREATE TABLE t_account (
    id          int,
    currency_id int          REFERENCES t_currency (id)
                                ON UPDATE CASCADE
                                ON DELETE CASCADE,
```

```

        balance      numeric);
INSERT INTO t_account VALUES (1, 1, 100);
INSERT INTO t_account VALUES (2, 1, 200);

```

Now, we want to run `SELECT FOR UPDATE` on the account table:

Transaction 1	Transaction 2
<code>BEGIN;</code>	
<code>SELECT * FROM t_account FOR UPDATE;</code>	<code>BEGIN;</code>
Waiting for user to proceed	<code>UPDATE t_currency SET id = id * 10;</code>
Waiting for user to proceed	It will wait on transaction 1

Although there is a `SELECT FOR UPDATE` on accounts, the `UPDATE` on the currency table be will be blocked. This is necessary because otherwise, there is a chance of breaking the foreign key constraint altogether. In a fairly complex data structure, you can therefore easily end up with contentions in an area where they are least expected (some highly important lookup tables).

On top of `FOR UPDATE`, there are `FOR SHARE`, `FOR NO KEY UPDATE`, and `FOR KEY SHARE`. The following listing describes what these modes actually mean:

- `FOR NO KEY UPDATE`: This one is pretty similar to `FOR UPDATE`. However, the lock is weaker and, therefore, it can coexist with `SELECT FOR SHARE`.
- `FOR SHARE`: `FOR UPDATE` is pretty strong and works on the assumption that you are definitely going to change rows. `FOR SHARE` is different because more than one transaction can hold a `FOR SHARE` lock at the same time.
- `FOR KEY SHARE`: This behaves similarly to `FOR SHARE`, except that the lock is weaker. It will block `FOR UPDATE` but will not block `FOR NO KEY UPDATE`.

The important thing here is to simply try things out and observe what happens. Improving locking behavior is really important as it can dramatically improve the scalability of your application.

Understanding transaction isolation levels

Up until now, you have seen how to handle locking as well as some basic concurrency. In this section, you will learn transaction isolation. To me, this is one of the most neglected topics in modern software development. Only a small fraction of software developers are actually aware of this issue, which in turn leads to mind-boggling bugs.

Here is an example of what can happen:

Transaction 1	Transaction 2
BEGIN;	
SELECT sum(balance) FROM t_account;	
User will see 300	BEGIN;
	INSERT INTO t_account (balance) VALUES (100);
	COMMIT;
SELECT sum(balance) FROM t_account;	
User will see 400	
COMMIT;	

Most users would actually expect the left transaction to always return 300 regardless of the second transaction. However, this is not true. By default, PostgreSQL runs in the `READ COMMITTED` transaction isolation mode. This means that every statement inside a transaction will get a new snapshot of the data, which will be constant throughout the query.



An SQL statement will operate on the same snapshot and will ignore changes by concurrent transactions while it is running.

If you want to avoid this, you can use `TRANSACTION ISOLATION LEVEL REPEATABLE READ`. In this transaction isolation level, a transaction will use the same snapshot through the entire transaction. Here is what will happen:

Transaction 1	Transaction 2
<code>BEGIN TRANSACTION ISOLATION LEVEL REPEATABLE READ;</code>	
<code>SELECT sum(balance) FROM t_account;</code>	
User will see 300	<code>BEGIN;</code>
	<code>INSERT INTO t_account (balance) VALUES (100);</code>
	<code>COMMIT;</code>
<code>SELECT sum(balance) FROM t_account;</code>	<code>SELECT sum(balance) FROM t_account;</code>
User will see 300	User will see 400
<code>COMMIT;</code>	

As just outlined, the first transaction will freeze its snapshot of the data and provide us with constant results throughout the entire transaction. This feature is especially important if you want to run reports. The first and the last page of a report should always be consistent and operate on the same data. Therefore, the repeatable read is key to consistent reports.

Note that isolation-related errors won't always pop up instantly. It can happen that trouble is noticed years after an application has been moved to production.



Repeatable read is not more expensive than read committed. There is no need to worry about performance penalties. For normal **Online-Transaction-Processing (OLTP)**, read committed has various advantages because changes can be seen much earlier and the odds of unexpected errors are usually lower.

Considering SSI transactions

On top of read committed and repeatable read, PostgreSQL offers **Serializable Snapshot Isolation (SSI)** transactions. So, in all, PostgreSQL supports three isolation levels. Note that read uncommitted (which still happens to be the default in some commercial databases) is not supported: if you try to start a read uncommitted transaction, PostgreSQL will silently map to read committed. Let us get back to the serializable isolation level.

The idea behind serializable is simple; if a transaction is known to work correctly when there is only a single user, it will also work in the case of concurrency when this isolation level is chosen. However, users have to be prepared; transactions may fail (by design) and error-out. In addition to this, a performance penalty has to be paid.

If you want to know more about this isolation level, consider checking out <https://wiki.postgresql.org/wiki/Serializable>.



Consider using serializable only when you have a decent understanding of what is going on inside the database engine.

Observing deadlocks and similar issues

Deadlocks are an important issue and can happen in every database I am aware of. Basically, a deadlock will happen if two transactions have to wait on each other.

In this section, you will see how this can happen. Let's suppose we have a table containing two rows:

```
CREATE TABLE t_deadlock (id int);  
INSERT INTO t_deadlock VALUES (1), (2);
```

The next listing shows what can happen:

Transaction 1	Transaction 2
BEGIN;	BEGIN;
UPDATE t_deadlock SET id = id * 10 WHERE id = 1;	UPDATE t_deadlock SET id = id * 10 WHERE id = 2;
UPDATE t_deadlock SET id = id * 10 WHERE id = 2;	
Waiting on transaction 2	UPDATE t_deadlock SET id = id * 10 WHERE id = 1;
Waiting on transaction 2	Waiting on transaction 1
	Deadlock will be resolved after one second (deadlock_timeout)
COMMIT;	ROLLBACK;

As soon as the deadlock is detected, the following error message will show up:

```
ERROR: deadlock detected
DETAIL: Process 91521 waits for ShareLock on transaction 903;
       blocked by process 77185.
Process 77185 waits for ShareLock on transaction 905;
blocked by process 91521.
HINT: See server log for query details.
CONTEXT: while updating tuple (0,1) in relation "t_deadlock"
```

PostgreSQL is even kind enough to tell us which row has caused the conflict. In my example, the root of all evil is a tuple (0, 1). What you can see here is `ctid`, which is a unique identifier of a row in a table. It tells us about the physical position of a row inside the table. In this example, it is the first row in the first block (0).

It is even possible to query this row if it is still visible to your transaction:

```
test=# SELECT ctid, * FROM t_deadlock WHERE ctid = '(0, 1)';
 ctid  | id
-----+----
(0,1)  |  1
(1 row)
```

Keep in mind that this query might not return a row if it has already been deleted or modified.

However, it isn't only the case that deadlocks can lead to potentially failing transactions. It can also happen that transactions are not serialized for various reasons. The following example shows what can happen. To make the example work, I assume that you've still got two rows, `id = 1` and `id = 2`.

Transaction 1	Transaction 2
BEGIN ISOLATION LEVEL REPEATABLE READ;	
SELECT * FROM t_deadlock;	
Two rows will be returned	
	DELETE FROM t_deadlock;
SELECT * FROM t_deadlock;	
Two rows will be returned	
DELETE FROM t_deadlock;	
The transaction will error-out	
ROLLBACK; - we cannot COMMIT anymore	

In this example, two concurrent transactions are at work. As long as transaction 1 is just selecting data, everything is fine because PostgreSQL can easily preserve the illusion of static data. But what happens if the second transaction commits a `DELETE`? As long as there are only reads, there is still no problem. The trouble begins when transaction 1 tries to delete or modify data, which is at this point already really dead. The only solution here for PostgreSQL is to error-out:

```
test=# DELETE FROM t_deadlock;  
ERROR: could not serialize access due to concurrent update
```

Practically, this means that end users have to be prepared to handle erroneous transactions. If something goes wrong, properly written applications must be able to try again.

Utilizing advisory locks

PostgreSQL has a highly efficient and sophisticated transaction machinery that is capable of handling locks in a really fine-grained and efficient way. Some years ago, some people came up with the idea of using this code to synchronize applications with each other.

Thus, advisory locks were born.

When using advisory locks, it is important to mention that they won't go away on `COMMIT` as normal locks do. Therefore, it is really important to make sure that unlocking is done properly and in a totally reliable way.

If you decide to use an advisory lock, what you really lock is a number. So, this is not about rows or data; it is really just a number. Here is how it works:

Session 1	Session 2
<code>BEGIN;</code>	
<code>SELECT pg_advisory_lock(15);</code>	
	<code>SELECT pg_advisory_lock(15);</code>
	It has to wait
<code>COMMIT;</code>	It still has to wait
<code>SELECT pg_advisory_unlock(15);</code>	It still waiting
	Lock is taken

The first transaction will lock 15. The second transaction has to wait until this number has been unlocked again. The second session will even wait after the first one has committed. This is highly important as you cannot rely on the fact that the end of the transaction will nicely and miraculously solve things for you.

If you want to unlock all locked numbers, PostgreSQL offers the `pg_advisory_unlock_all()` function to do exactly this:

```
test=# SELECT pg_advisory_unlock_all();
pg_advisory_unlock_all
-----
(1 row)
```

Sometimes, you might want to see if you can get a lock and error-out if it is not possible. To achieve this, PostgreSQL offers a couple of function, to see a list of all such available functions, at the command line, enter: `df *try*advisory*`.

Optimizing storage and managing cleanup

Transactions are an integral part of the PostgreSQL system. However, transactions come with a small price tag attached. As already shown in this chapter, it can happen that concurrent users will be presented with different data. Not everybody will get the same data returned by a query. In addition to this, `DELETE` and `UPDATE` are not allowed to actually overwrite data as `ROLLBACK` would not work. If you happen to be in the middle of a large `DELETE` operation, you cannot be sure whether you will be able to `COMMIT` or not. In addition to this, data is still visible while you perform `DELETE`, and sometimes data is even visible once your modification has long since finished.

Consequently, this means that cleanup has to happen asynchronously. A transaction cannot clean up its own mess and `COMMIT`/`ROLLBACK` might be too early to take care of dead rows.

The solution to this problem is `VACUUM`:

```
test=# \h VACUUM
Command: VACUUM
Description: garbage-collect and optionally analyze a database
Syntax:
VACUUM [ ( { FULL | FREEZE | VERBOSE | ANALYZE } [, ...] ) ] [ table_name [
(column_name [, ...] ) ] ]
VACUUM [ FULL ] [ FREEZE ] [ VERBOSE ] [ table_name ]
VACUUM [ FULL ] [ FREEZE ] [ VERBOSE ] ANALYZE [ table_name [ (column_name
[, ...] ) ] ]
```

`VACUUM` will visit all pages that potentially contain modifications and find all the dead space. The free space found is then tracked by **Free Space Map (FSM)** of the relation.

Note that `VACUUM` will, in most cases, not shrink the size of a table. Instead, it will track and find free space inside existing storage files.



Tables will usually have the same size after `VACUUM`. If there are no valid rows at the end of a table, file sizes can go down in some rare cases. This is not the rule but rather the exception.

What this means to the end users will be outlined in the Watching `VACUUM` at work section of this chapter.

Configuring `VACUUM` and autovacuum

Back in the early days of PostgreSQL projects, people had to run `VACUUM` manually. Fortunately, this is long gone. Nowadays, administrators can rely on a tool called `autovacuum`, which is part of the PostgreSQL Server infrastructure. It automatically takes care of cleanup and works in the background. It wakes up once per minute (see `autovacuum_naptime = 1` in `postgresql.conf`) and checks if there is work to do. If there is work, `autovacuum` will fork up to three worker processes (see `autovacuum_max_workers` in `postgresql.conf`).

The main question is, when does `autovacuum` trigger the creation of a worker process?



Actually, the `autovacuum` process does not fork processes itself. Instead, it tells the main process to do so. This is done to avoid zombie processes in the case of failure and to improve robustness.

The answer to this question can again be found in `postgresql.conf`:

```
autovacuum_vacuum_threshold = 50
autovacuum_analyze_threshold = 50
autovacuum_vacuum_scale_factor = 0.2
autovacuum_analyze_scale_factor = 0.1
```

`autovacuum_vacuum_scale_factor` tells PostgreSQL that a table is worth vacuuming if 20% of data has been changed. The trouble is that if a table consists of one row, one change is already 100%. It makes absolutely no sense to fork a complete process to clean up just one row. Therefore, `autovacuum_vacuum_threshold` says that we need 20% and this 20% must be at least 50 rows. Otherwise, `VACUUM` won't kick in. The same mechanism is used when it comes to optimizer stats creation. 10% and at least 50 rows are needed to justify new optimizer stats. Ideally, autovacuum creates new statistics during a normal `VACUUM` to avoid unnecessary trips to the table.

Digging into transaction wraparound-related issues

There are two more settings in `postgresql.conf` that are quite important to understand:

```
autovacuum_freeze_max_age = 200000000
autovacuum_multixact_freeze_max_age = 400000000
```

To understand the overall problem, it is important to understand how PostgreSQL handles concurrency. The PostgreSQL transaction machinery is based on the comparison of transaction IDs and the states transactions are in.

Let's look at an example. If I am transaction ID 4711 and if you happen to be 4712, I won't see you because you are still running. If I am transaction ID 4711 but you are transaction ID 3900, I will see you provided you have committed, and I will ignore you if you failed.

The trouble is as follows: transaction IDs are finite, not unlimited. At some point, they will start to wrap around. In reality, this means that transaction number 5 might actually be after transaction number 800,000,000. How does PostgreSQL know what was first? It does so by storing a watermark. At some point, those watermarks will be adjusted, and this is exactly when `VACUUM` starts to be relevant. By running `VACUUM` (or autovacuum), you can ensure that the watermark is adjusted in a way that there are always enough future transaction IDs left to work with.



Not every transaction will increase the transaction ID counter. As long as a transaction is still reading, it will only have a virtual transaction ID. This ensures that transaction IDs are not burned too quickly.

`autovacuum_freeze_max_age` defines the maximum number of transactions (age) that a table's `pg_class.relFrozenxid` field can attain before a `VACUUM` operation is forced to prevent transaction ID wraparound within the table. This value is fairly low because it also has an impact on clog cleanup (the clog or commit log is a data structure that stores two bits per transaction, which indicate whether a transaction is running, aborted, committed, or still in a subtransaction).

`autovacuum_multixact_freeze_max_age` configures the maximum age (in multixacts) that a table's `pg_class.relminmxid` field can attain before a `VACUUM` operation is forced to prevent multixact ID wraparound within the table. Freezing tuples is an important performance issue and there will be more about this process in Chapter 6, *Optimizing Queries for Good Performance*, where we will discuss query optimization.

In general, trying to reduce the `VACUUM` load while maintaining operational security is a good idea. A `VACUUM` instance on large tables can be expensive, and therefore keeping an eye on these settings makes perfect sense.

A word on VACUUM FULL

Instead of normal `VACUUM`, you can also use `VACUUM FULL`. However, I really want to point out that `VACUUM FULL` actually locks the table and rewrites the entire relation. In the case of a small table, this might not be an issue. However, if your tables are large, the table lock can really kill you in minutes! `VACUUM FULL` blocks upcoming writes and therefore some people talking to your database might have the feeling that it is actually down. Hence, a lot of caution is advised.

To get rid of `VACUUM FULL`, I recommend that you check out `pg_squeeze` (http://www.cybertec.at/introducing-pg_squeeze-a-postgresql-extension-to-auto-rebuild-bloated-tables/), which can rewrite a table without blocking writes.

Watching VACUUM at work

After this introduction, it is time to see `VACUUM` in action. I have included this section here because my practical work as a PostgreSQL consultant and supporter (<http://postgresql-support.de/>) indicates that most people only have a very vague understanding of what happens on the storage side.

To stress this point again, in most cases, `VACUUM` will not shrink your tables; space is usually not returned to the filesystem.

Here is my example:

```
CREATE TABLE t_test (id int) WITH (autovacuum_enabled = off);
INSERT INTO t_test
  SELECT * FROM generate_series(1, 100000);
```

The idea is to create a simple table containing 100,000 rows. Note that it is possible to turn autovacuum off for specific tables. Usually, this is not a good idea for most applications. However, there are corner case, where `autovacuum_enabled = off` makes sense. Just consider a table whose life cycle is very short. It does not make sense to clean out tuples if the developer already knows that the entire table will be dropped within seconds. In data warehousing, this can be the case if you use tables as staging areas. `VACUUM` is turned off in this example to ensure that nothing happens in the background; all you see is triggered by me and not by some process.

First of all, the size of the table is checked:

```
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
3544 kB
(1 row)
```

`pg_relation_size` returns the size of a table in bytes. `pg_size_pretty` will take this number and turn it into something human-readable.

Then, all rows in the table will be updated:

```
test=# UPDATE t_test SET id = id + 1;
UPDATE 100000
```

What happens is highly important to understand PostgreSQL; the database engine has to copy all the rows. Why? First of all, we don't know whether the transaction will be successful, so the data cannot be overwritten. The second important aspect is that a concurrent transaction might still be seeing the old version of the data.

The UPDATE operation will copy rows.

Logically, the size of the table will be larger after the change has been made:

```
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
7080 kB
(1 row)
```

After UPDATE, people might try to return space to the filesystem:

```
test=# VACUUM t_test;
VACUUM
```

As stated previously, VACUUM does not return space to the filesystem in most cases. Instead, it will allow space to be reused. The table, therefore, does not shrink at all:

```
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
7080 kB
(1 row)
```

However, the next `UPDATE` will not make the table grow because it will eat the free space inside the table. Only a second `UPDATE` would make the table grow again, because all the space is gone and so additional storage is needed:

```
test=# UPDATE t_test SET id = id + 1;
UPDATE 100000
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
7080 kB
(1 row)

test=# UPDATE t_test SET id = id + 1;
UPDATE 100000
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
10 MB
(1 row)
```

If I had to decide on a single thing, you should remember after reading this book, this is it. Understanding storage is the key to performance and administration in general.

Let us run some more queries:

```
VACUUM t_test;
UPDATE t_test SET id = id + 1;
VACUUM t_test;
```

Again the size is unchanged. Let's see what is inside the table:

```
test=# SELECT ctid, * FROM t_test ORDER BY ctid DESC;
ctid      | id
-----+-----
(1327, 46) | 112
(1327, 45) | 111
(1327, 44) | 110
(884, 20)  | 99798
(884, 19)  | 99797
...
```

`ctid` is the physical position of a row on a disk. Using `ORDER BY ctid DESC`, you will basically read the table backwards in the physical order. Why should you care? The reason is that there are some very small values and some very big values at the end of the table. What happens if they are deleted?

```
test=# DELETE FROM t_test WHERE id > 99000 OR id < 1000;
DELETE 1999
test=# VACUUM t_test;
VACUUM
test=# SELECT pg_size_pretty(pg_relation_size('t_test'));
pg_size_pretty
-----
3504 kB
(1 row)
```

Although only 2% of the data has been deleted, the size of the table has gone down by two thirds. The reason is that if `VACUUM` only finds dead rows after a certain position in the table, it can return space to the filesystem. This is the only case in which you will actually see the table size go down. Of course, normal users have no control over the physical position of data on the disk. Therefore, storage consumption will most likely stay somewhat the same unless all rows are deleted.



Why are there so many small and big values at the end of the table anyway? After the table is initially populated with 100,000 rows, the last block is not completely full, so the first `UPDATE` will fill up the last block with changes. This naturally shuffles the end of the table a bit. In this carefully crafted example, this is the reason for the strange layout at the end of the table.

In real-world applications, the impact of this observation cannot be stressed enough. There is no performance tuning without really understanding storage.

Making use of snapshot too old

VACUUM does a good job and it will reclaim free space as needed. However, when can VACUUM actually clean out rows and turn them into free space? The rule is this: if a row cannot be seen by anybody anymore, it can be reclaimed. In reality, this means that everything that is no longer seen even by the oldest active transaction can be considered to be really dead.

This also implies that really long transactions can postpone cleanup for quite some time. The logical consequence is table bloat. Tables will grow beyond proportion and performance will tend to go downhill. Fortunately, starting with PostgreSQL 9.6, the database has a nice feature that allows the administrator to intelligently limit the duration of a transaction. Oracle administrators will be familiar with the snapshot too old error; since PostgreSQL 9.6, this error message is also available. However, it is more of a feature than an unintended side-effect of bad configuration (which it actually is in Oracle).

To limit the lifetime of snapshots, you can make use of a setting in `postgresql.conf`:

```
old_snapshot_threshold = -1
# 1min-60d; -1 disables; 0 is immediate
```

If this variable is set, transactions will fail after a certain amount of time. Note that this setting is on an instance level and it cannot be set inside a session. By limiting the age of a transaction, the risk of insanely long transactions will decrease drastically.

Summary

In this chapter, you learned transactions, locking and its logical implications, and the general architecture the PostgreSQL transaction machinery can have for storage, concurrency, and administration. You saw how rows are locked and which features are available in PostgreSQL.

In Chapter 3, *Making use of Indexes*, you will learn one of the most important topics in database work: indexing. You will learn about the PostgreSQL query optimizer as well as various types of indexes and their behavior.

3

Making Use of Indexes

In *Chapter 2, Understanding Transactions and Locking*, you learned concurrency and locking. In this chapter, it is time to attack indexing head on. The importance of this topic cannot be stressed enough—indexing is (and will most likely remain) one of the most important topics in the life of every database engineer.

After 18 years of professional, full-time PostgreSQL consulting and PostgreSQL 24x7 support (www.cybertec-postgresql.com), I can say one thing for sure—bad indexing is the main source of bad performance. Of course, it is important to adjust memory parameters and all that. However, it is all in vain if indexes are not used properly. There is simply no replacement for a missing index.

Therefore, I have dedicated an entire chapter to indexing alone to give you as many insights as possible.

In this chapter, you will learn these topics:

- When does PostgreSQL use indexes?
- How does an optimizer handle things?
- What types of indexes are there and how do they work?
- Using your own indexing strategies

At the end of the chapter, you will be able to understand how indexes can be used beneficially in PostgreSQL.

Understanding simple queries and the cost model

In this section, we will get started with indexes. To show how things work, some test data is needed. The following code snippet shows how data can be created easily:

```
test=# CREATE TABLE t_test (id serial, name text);
CREATE TABLE
test=# INSERT INTO t_test (name) SELECT 'hans'
      FROM generate_series(1, 2000000);
INSERT 0 2000000
test=# INSERT INTO t_test (name) SELECT 'paul'
      FROM generate_series(1, 2000000);
INSERT 0 2000000
```

In the first line, a simple table is created. Two columns are used: an autoincrement column that just keeps creating numbers and a column that will be filled with static values.



The `generate_series` function will generate numbers from 1 to 2 million. So, in this example, 2 million static values for `hans` and 2 million static values for `paul` are created.

In all, 4 million rows have been added:

```
test=# SELECT name, count(*) FROM t_test GROUP BY 1;
 name | count
-----+-----
 hans | 2000000
 paul | 2000000
(2 rows)
```

These 4 million rows have some nice properties. IDs are ascending and there are only two distinct names.

Let's run a simple query now:

```
test=# \timing
Timing is on.
test=# SELECT * FROM t_test WHERE id = 432332;
   id   | name
-----+-----
 432332 | hans
(1 row)

Time: 176.949 ms
```

In this case, the `timing` command will tell `psql` to show the runtime of a query. Note that this is not the real execution time on the server, but the time measured by `psql`. In case of very short queries, network latency can be a substantial part of the total time, so this has to be taken into account.

Making use of EXPLAIN

In this example, reading 4 million rows has taken more than 100 milliseconds. From a performance point of view, it is a total disaster. To figure out what goes wrong, PostgreSQL offers the `EXPLAIN` command:

```
test=# \h EXPLAIN
Command: EXPLAIN
Description: show the execution plan of a statement
Syntax:
EXPLAIN [ ( option [, ...] ) ] statement
EXPLAIN [ ANALYZE ] [ VERBOSE ] statement
```

where option can be one of:

```
ANALYZE [ boolean ]
VERBOSE [ boolean ]
COSTS [ boolean ]
BUFFERS [ boolean ]
TIMING [ boolean ]
FORMAT { TEXT | XML | JSON | YAML }
```

When you have a feeling that a query is not performing well, `EXPLAIN` will help you to reveal the real performance problem.

Here is how it works:

```
test=# EXPLAIN SELECT * FROM t_test WHERE id = 432332;
               QUERY PLAN
-----
Gather (cost=1000.00..43463.92 rows=1 width=9)
  Workers Planned: 2
    -> Parallel Seq Scan on t_test
        (cost=0.00..42463.82 rows=1 width=9)
        Filter: (id = 432332)
(4 rows)
```

What you see in this listing is an execution plan. In PostgreSQL, a SQL statement will be executed in four stages. The following components are at work:

- The **parser** will check for syntax errors and obvious problems
- The **rewrite** system takes care of rules (views and other things)
- The **optimizer** will figure out how to execute a query in the most efficient way and work out a plan
- The **plan** provided by the optimizer will be used by the executor to finally create the result

The purpose of `EXPLAIN` is to see what the planner has come up with to run the query efficiently. In my example, PostgreSQL will use a parallel sequential scan. This means that two workers will cooperate and work on the filter condition together. The partial results are then united through a thing called a gather node, which has been introduced in PostgreSQL 9.6 (it is a part of the parallel query infrastructure). If you look at the plan more precisely, you will see how many rows PostgreSQL expects at each stage of the plan (in this example, `rows = 1`, that is, one row will be returned).



In PostgreSQL 9.6 and 10.0, the number of parallel workers will be determined by the size of the table. The larger an operation is, the more parallel workers PostgreSQL will fire up. For a very small table, parallelism is not used as it would create too much overhead.

Parallelism is not a must. It is always possible to reduce the number of parallel workers to mimic pre-PostgreSQL 9.6 behavior by setting the following variable to 0:

```
test=# SET max_parallel_workers_per_gather TO 0;
SET
```

Note that this change has no side effect as it is only in your session. Of course, you can also decide the change in the `postgresql.conf` file, but I would not advise you to do this, as you might lose quite a lot of performance provided by the parallel queries.

Digging into the PostgreSQL cost model

If only one CPU is used, the execution plan will look like this:

```
test=# EXPLAIN SELECT * FROM t_test WHERE id = 432332;
               QUERY PLAN
-----
Seq Scan on t_test (cost=0.00..71622.00 rows=1 width=9)
  Filter: (id = 432332)
(2 rows)
```

PostgreSQL will sequentially read (sequential scan) the entire table and apply the filter. It expects the operation to cost 71622 penalty points. Now, what does this mean? Penalty points (or costs) are mostly an abstract concept. They are needed to compare different ways to execute a query. If a query can be executed by the executor in many different ways, PostgreSQL will decide on the execution plan promising the lowest cost possible. The question now is how did PostgreSQL end up with 71622 points?

Here is how it works:

```
test=# SELECT pg_relation_size('t_test') / 8192.0;
      ?column?
-----
21622.000000
(1 row)
```

The `pg_relation_size` function will return the size of the table in bytes. Given the example, you can see that the relation consists of 21622 blocks (8k each). According to the cost model, PostgreSQL will add costs of one for each block it has to read sequentially.

The configuration parameter to influence that is as follows:

```
test=# SHOW seq_page_cost;
 seq_page_cost
-----
1
(1 row)
```

However, reading a couple of blocks from a disk is not everything we have to do. It is also necessary to apply the filter and to send these rows through a CPU. Two parameters are here to account for these costs:

```
test=# SHOW cpu_tuple_cost;
 cpu_tuple_cost
-----
```

```

0.01
(1 row)
test=# SHOW cpu_operator_cost;
cpu_operator_cost
-----
0.0025
(1 row)

```

This leads to the following calculation:

```

test=# SELECT 21622*1 + 4000000*0.01 + 4000000*0.0025;

?column?
-----
71622.0000
(1 row)

```

As you can see, this is exactly the number seen in the plan. Costs will consist of a CPU part and an I/O part, which will all be turned into a single number. The important thing here is that costs have nothing to do with real execution, so it is impossible to translate costs to milliseconds. The number the planner comes up with is really just an estimate.

Of course, there are some more parameters outlined in this brief example. PostgreSQL also has special parameters for index-related operations, as follows:

- `random_page_cost = 4`: If PostgreSQL uses an index, there is usually a lot of random I/O involved. On traditional spinning disks, random reads are much more important than sequential reads, so PostgreSQL will account for them accordingly. Note that on SSDs, the difference between random and sequential reads does not exist anymore, so it can make sense to set `random_page_cost = 1` in the `postgresql.conf` file.
- `cpu_index_tuple_cost = 0.005`: If indexes are used, PostgreSQL will also consider that there is some CPU cost invoiced.

If you are utilizing parallel queries, there are even more cost parameters:

- `parallel_tuple_cost = 0.1`: This defines the cost of transferring one tuple from a parallel worker process to another process. It basically accounts for the overhead of moving rows around inside the infrastructure.
- `parallel_setup_cost = 1000.0`: This adjusts the costs of firing up a worker process. Of course, starting processes to run queries in parallel is not free, and so, this parameter tries to model those costs associated with process management.

- `min_parallel_relation_size = 8 MB`: This defines the minimum size of a table considered for parallel queries. The larger a table grows, the more CPUs PostgreSQL will use. The size of the table has to triple to allow for one more worker process.

Deploying simple indexes

Firing up more worker processes to scan ever larger tables is sometimes not the solution. Reading entire tables to find just a single row is usually not a good idea.

Therefore, it makes sense to create indexes:

```
test=# CREATE INDEX idx_id ON t_test (id);
CREATE INDEX
test=# SELECT * FROM t_test WHERE id = 43242;
 id   | name
-----+-----
 43242 | hans
(1 row)
Time: 0.259 ms
```

PostgreSQL uses Lehman-Yao's high concurrency b-tree for standard indexes. Along with some PostgreSQL specific optimizations, these trees provide end users with excellent performance. The most important thing is that Lehman-Yao allows you to run many operations (reading and writing) on the very same index at the same time, which helps to improve throughput dramatically.

However, indexes are not free:

```
test=# \di+
                                List of relations
 Schema | Name      | Type  | Owner | Table  | Size  | Description
-----+-----+-----+-----+-----+-----+-----
 public | idx_id    | index | hs    | t_test | 86 MB |
(1 row)
```

As you can see, our index containing 4 million rows will eat up 86 MB of disk space. In addition to this, writes to the table will be slower because the index has to be kept in sync all the time.

In other words, if you insert into a table featuring 20 indexes, you also have to keep in mind that we have to write to all those indexes on `INSERT`, which seriously slows down the writing.

Making use of sorted output

B-tree indexes are not only used to find rows; they are also used to feed sorted data to the next stage in the process:

```
test=# EXPLAIN SELECT * FROM t_test ORDER BY id DESC
LIMIT 10;
```

QUERY PLAN

```
-----
Limit (cost=0.43..0.74 rows=10 width=9)
  -> Index Scan Backward using idx_id on t_test
      (cost=0.43..125505.43 rows=4000000 width=9)
(2 rows)
```

In this case, the index already returns data in the right sort order and therefore there is no need to sort the entire set of data. Reading the last 10 rows of the index will be enough to answer this query. Practically, this means that it is possible to find the top N rows of a table in a fraction of a millisecond.

However, `ORDER BY` is not the only operation requiring sorted output. The `min` and `max` functions are also all about sorted output, so an index can be used to speed up these two operations as well. Here is an example:

```
test=# explain SELECT min(id), max(id) FROM t_test;
```

QUERY PLAN

```
-----
Result (cost=0.93..0.94 rows=1 width=8)
  InitPlan 1 (returns $0)
    -> Limit (cost=0.43..0.46 rows=1 width=4)
        -> Index Only Scan using idx_id on t_test
            (cost=0.43..135505.43 rows=4000000 width=4)
            Index Cond: (id IS NOT NULL)
  InitPlan 2 (returns $1)
    -> Limit (cost=0.43..0.46 rows=1 width=4)
        -> Index Only Scan Backward using idx_id on t_test t_test_1
            (cost=0.43..135505.43 rows=4000000 width=4)
            Index Cond: (id IS NOT NULL)
(9 rows)
```

In PostgreSQL, an index (a b-tree, to be more precise) can be read in normal order or backwards. The thing now is that a b-tree can be seen as a sorted list. So, naturally, the lowest value is at the beginning and the highest value is at the end. Therefore, `min` and `max` are perfect candidates for a speed up. What is also worth noticing is that in this case, the main table needs not be referenced at all.

In SQL, many operations rely on sorted input; therefore, understanding these operations is essential because there are serious implications on the indexing side.

Using more than one index at a time

Up until now, you have seen that one index at a time has been used. However, in many real-world situations, this is, by far, not sufficient. There are cases demanding more logic in the database.

PostgreSQL allows the use of multiple indexes in a single query. Of course, this makes sense if many columns are queried at the same time. However, that's not always the case. It can also happen that a single index is used multiple times to process the very same column.

Here is an example:

```
test=# explain SELECT * FROM t_test WHERE id = 30 OR id = 50;

               QUERY PLAN
-----
Bitmap Heap Scan on t_test (cost=8.88..16.85 rows=2 width=9)
  Recheck Cond: ((id = 30) OR (id = 50))
    -> BitmapOr (cost=8.88..8.88 rows=2 width=0)
      -> Bitmap Index Scan on idx_idv
          (cost=0.00..4.44 rows=1 width=0)
          Index Cond: (id = 30)
      -> Bitmap Index Scan on idx_id (cost=0.00..4.44 rows=1 width=0)
          Index Cond: (id = 50)

(7 rows)
```

The point here is that the `id` column is needed twice. First, the query looks for 30 and then, for 50. As you can see, PostgreSQL will go for a bitmap scan.



A bitmap scan is not the same as a bitmap index, which people from an Oracle background might know. They are two totally distinct things and have nothing in common. Bitmap indexes are an index type in Oracle, while bitmap scans are a scan method.

The idea behind a bitmap scan is that PostgreSQL will scan the first index, collecting a list of blocks containing the data. Then, the next index will be scanned to again compile a list of blocks. This works for as many indexes as desired. In the case of `OR`, these lists will then be unified, leaving us with a large list of blocks containing the data. Using this list, the table will be scanned to retrieve these blocks.

The trouble now is that PostgreSQL has retrieved a lot more data than needed. In our case, the query will look for two rows; however, a couple of blocks might have been returned by the bitmap scan. Therefore, the executor will do as recheck to filter out these rows, which do not satisfy our conditions.

Bitmap scans will also work for `AND` conditions or a mixture of `AND` and `OR`. However, if PostgreSQL sees an `AND` condition, it does not necessarily force itself into a bitmap scan. Let's suppose that we got a query looking for everybody living in Austria and a person with a certain ID. It really makes no sense to use two indexes here because after searching for the ID, there is really not much data left. Scanning both indexes would be much more expensive because there are 8 million people (including me) living in Austria, and reading so many rows to find just one person is pretty pointless from a performance standpoint. The good news is that the PostgreSQL optimizer will make all these decisions for you by comparing the costs of different options and potential indexes, so there is no need to worry.

Using bitmap scans effectively

The question naturally arising now is, when is a bitmap scan most beneficial and when is it chosen by the optimizer? From my point of view, there are really only two use cases:

- Avoiding using the same block over and over again
- Combining relatively bad conditions

The first case is quite common. Suppose you are looking for everybody who speaks a certain language. For the sake of the example, we can assume that 10% of all people speak the required language. Scanning the index would mean that a block in the table has to be scanned all over again as many skilled speakers might be stored in the same block. By applying a bitmap scan, it is ensured that a specific block is only used once, which of course leads to better performance.

The second common use case is to use relatively weak criteria together. Let's suppose we are looking for everybody between 20 and 30 years of age owning a yellow shirt. Now, maybe 15% of all people are between 20 and 30 and maybe 15% of all people actually own a yellow shirt. Scanning a table sequentially is expensive, and so PostgreSQL might decide to choose two indexes because the final result might consist of just 1% of the data. Scanning both indexes might be cheaper than reading all of the data.

In PostgreSQL 10.0, parallel bitmap heap scans are supported. Usually, bitmap scans are used by comparatively expensive queries. Added parallelism in this area is, therefore, a huge step forward and definitely beneficial.

Using indexes in an intelligent way

So far, applying an index feels like the Holy Grail, which always improves performance magically. However, this is not the case. Indexes can also be pretty pointless in some cases.

Before digging into things more deeply, here is the data structure we have used for this example. Remember that there are only two distinct names and unique IDs:

```
test=# \d t_test
               Table "public.t_test"
  Column | Type          | Modifiers
-----+-----+-----
  id     | integer       | not null default nextval('t_test_id_seq'::regclass)
  name   | text          |
Indexes:
    "idx_id" btree (id)
```

At this point, one index has been defined, which covers the `id` column. In the next step, the `name` column will be queried. Before doing this, an index on the `name` will be created:

```
test=# CREATE INDEX idx_name ON t_test (name);
CREATE INDEX
```

Now, it is time to see if the index is used correctly:

```
test=# EXPLAIN SELECT * FROM t_test WHERE name = 'hans2';
               QUERY PLAN
-----
Index Scan using idx_name on t_test
  (cost=0.43..4.45 rows=1 width=9)
  Index Cond: (name = 'hans2'::text)
(2 rows)
```

As expected, PostgreSQL will decide on using the index. Most users would expect this. But note that my query says `hans2`. Remember, `hans2` does not exist in the table and the query plan perfectly reflects this. `rows=1` indicates that the planner only expects a very small subset of data being returned by the query.



There is not a single row in the table, but PostgreSQL will never estimate zero rows because it would make subsequent estimations a lot harder because useful cost calculations of other nodes in the plan would be close to impossible.

Let's see what happens if we look for more data:

```
test=# EXPLAIN SELECT *
      FROM t_test
      WHERE name = 'hans'
             OR name = 'paul';
      QUERY PLAN
-----
Seq Scan on t_test (cost=0.00..81622.00 rows=3000011 width=9)
  Filter: ((name = 'hans'::text) OR (name = 'paul'::text))
(2 rows)
```

In this case, PostgreSQL will go for a straight sequential scan. Why is that? Why is the system ignoring all indexes? The reason is simple; hans and paul make up the entire dataset because there are no other values (PostgreSQL knows that by checking the system statistics). Therefore, PostgreSQL figures that the entire table has to be read anyway. There is no reason to read all of the index and the full table if reading just the table is sufficient.

In other words, PostgreSQL will not use an index just because there is one. PostgreSQL will use indexes when they make sense. If the number of rows is smaller, PostgreSQL will again consider bitmap scans and normal index scans:

```
test=# EXPLAIN SELECT *
      FROM t_test
      WHERE name = 'hans2'
             OR name = 'paul2';
      QUERY PLAN
-----
Bitmap Heap Scan on t_test (cost=8.88..12.89 rows=1 width=9)
  Recheck Cond: ((name = 'hans2'::text) OR (name = 'paul2'::text))
  -> BitmapOr (cost=8.88..8.88 rows=1 width=0)
    -> Bitmap Index Scan on idx_name
        (cost=0.00..4.44 rows=1 width=0)
        Index Cond: (name = 'hans2'::text)
    -> Bitmap Index Scan on idx_name
        (cost=0.00..4.44 rows=1 width=0)
        Index Cond: (name = 'paul2'::text)
```

The most important point to learn here is that execution plans depend on input values.

They are not static and not independent of the data inside the table. This is a very important observation, which has to be kept in mind all the time. In real-world examples, the fact that plans change can often be the reason for unpredictable runtimes.

Improving speed using clustered tables

In this section, you will learn about the power of correlation and the power of clustered tables. What is the whole idea? Consider you want to read a whole area of data. This might be a certain time range, some block, IDs, or so.

The runtime of such queries will vary depending on the amount of data and the physical arrangement of data on the disk. So, even if you are running queries that return the same number of rows, two systems might not provide the answer within the same time span, as the physical disk layout might make a difference.

Here is an example:

```
test=# EXPLAIN (analyze true, buffers true, timing true)
      SELECT *
      FROM t_test
      WHERE id < 10000;
```

QUERY PLAN

```
-----
Index Scan using idx_id on t_test
  (cost=0.43..370.87 rows=10768 width=9)
  (actual time=0.011..2.897 rows=9999 loops=1)
    Index Cond: (id < 10000)
    Buffers: shared hit=85
    Planning time: 0.078 ms
    Execution time: 4.081 ms
(5 rows)
```

As you might remember, the data has been loaded in an organized and sequential way. Data has been added ID after ID, and so it can be expected that the data will be on the disk in a sequential order. This holds true if data is loaded into an empty table using some autoincrement column.

You have already seen EXPLAIN in action. In this example, EXPLAIN (analyze true, buffers true, and timing true) has been utilized. The idea is that analyze will not just show the plan but also execute the query and show us what has happened.

EXPLAIN analyze is perfect for comparing planner estimates with what really happened.

It is the best way to figure out whether the planner was correct or way off. The buffers true parameter will tell us how many 8k blocks were touched by the query. In this example, a total of 85 blocks were touched. Shared hit means that data was coming from the PostgreSQL I/O cache (shared buffers). Altogether, it took PostgreSQL around four milliseconds to retrieve the data.

What happens if the data in your table is somewhat random? Will things change?

To create a table containing the same data but in random order, you can simply use `ORDER BY random()`. It will make sure that the data is indeed shuffled on disk:

```
test=# CREATE TABLE t_random AS SELECT * FROM t_test ORDER BY random();
SELECT 4000000
```

To ensure a fair comparison, the same column is indexed:

```
test=# CREATE INDEX idx_random ON t_random (id);
CREATE INDEX
```

To function properly, PostgreSQL will need optimizer statistics. These statistics will tell PostgreSQL how much data there is, how values are distributed, and whether the data is correlated on disk. To speed things up even more, I have added a `VACUUM` call. Please mind that `VACUUM` will be discussed later in this book in a broader detail:

```
test=# VACUUM ANALYZE t_random;
VACUUM
```

Now, let's run the same query as before:

```
test=# EXPLAIN (analyze true, buffers true, timing true)
      SELECT * FROM t_random WHERE id < 10000;
```

QUERY PLAN

```
-----
Bitmap Heap Scan on t_random
  (cost=203.27..18431.86 rows=10689 width=9)
  (actual time=5.087..13.822 rows=9999 loops=1)
    Recheck Cond: (id < 10000)
    Heap Blocks: exact=8027
    Buffers: shared hit=8057
    -> Bitmap Index Scan on idx_random
      (cost=0.00..200.60 rows=10689 width=0)
      (actual time=3.558..3.558 rows=9999 loops=1)
        Index Cond: (id < 10000)
        Buffers: shared hit=30
Planning time: 0.075 ms
Execution time: 14.411 ms
(9 rows)
```

There are a couple of things to observe here. First of all, a staggering total of 8,057 blocks were needed and the runtime has skyrocketed to over 14 milliseconds. The only thing here is that the somewhat rescued performance was the fact that data was again coming from the memory and not from the disk. Just imagine what it would mean if you had to access the disk 8,057 times just to answer this query. It would be a total disaster because disk wait would certainly slow down things dramatically.

However, there is more to see. You can even see that the plan has changed. PostgreSQL now uses a bitmap scan instead of a normal index scan. This is done to reduce the number of blocks needed in the query to prevent the even worse behavior.

How does the planner know how data is stored on the disk? `pg_stats` is a system view containing all the statistics about the content of the columns. The following query reveals the relevant content:

```
test=# SELECT tablename, attname, correlation
      FROM pg_stats
      WHERE tablename IN ('t_test', 't_random')
      ORDER BY 1, 2;
```

tablename	attname	correlation
t_random	id	-0.0114944
t_random	name	0.493675
t_test	id	1
t_test	name	1

(4 rows)

You can see that PostgreSQL takes care of every single column. The content of the view is created by a thing called `ANALYZE`, which is vital to the performance:

```
test=# \h ANALYZE
Command: ANALYZE
Description: Collect statistics about a database
Syntax:
ANALYZE [ VERBOSE ] [ table_name [ ( column_name [, ...] ) ] ]
```

Usually, `ANALYZE` is automatically executed in the background using the autovacuum daemon, which will be covered later in this book.

Back to our query. As you can see, both tables have two columns (`id` and `name`). In the case of `t_test.id`, the correlation is 1, which means that the next value somewhat depends on the previous one. In my example, numbers are simply ascending. The same applies to `t_test.name`. First, we have entries containing `hans` and then we have entries containing `paul`. All identical names are therefore stored together.

In `t_random`, the situation is quite different; a negative correlation means that data is shuffled. You can also see that the correlation for the name column is around 0.5. In reality, it means that there is usually no straight sequence of identical names in the table, but it rather means that names keep switching all the time when the table is read in the physical order.

Why does this lead to so many blocks being hit by the query? The answer is relatively simple. If the data we need is not packed together tightly but spread out over the table evenly, more blocks are needed to extract the same amount of information, which in turn leads to worse performance.

Clustering tables

In PostgreSQL, there is a command called `CLUSTER` that allows us to rewrite a table in the desired order. It is possible to point to an index and store data in the same order as the index:

```
test=# \h CLUSTER
Command: CLUSTER
Description: cluster a table according to an index
Syntax:
CLUSTER [VERBOSE] table_name [ USING index_name ]
CLUSTER [VERBOSE]
```

The `CLUSTER` command has been around for many years and serves its purpose well. But, there are some things to consider before blindly running it on a production system:

- The `CLUSTER` command will lock the table while it is running. You cannot insert or modify data while `CLUSTER` is running. This might not be acceptable on a production system.
- Data can only be organized according to one index. You cannot order a table by postal code, name, ID, birthday, and so on, at the same time. It means that `CLUSTER` will make sense if there is a search criteria, which is used most of the time.
- Keep in mind that the example outlined in this book is more of a worst-case scenario. In reality, the performance difference between a clustered and a non-clustered table will depend on the workload, the amount of data retrieved, cache hit rates, and a lot more.
- The clustered state of a table will not be maintained as changes are made to a table during normal operations. Correlation will usually deteriorate as time goes by.

Here is an example of how to run the `CLUSTER` command:

```
test=# CLUSTER t_random USING idx_random;  
CLUSTER
```

Depending on the size of the table, the time needed to cluster will vary.

Making use of index only scans

So far, you have seen when an index is used and when it is not. In addition to this, bitmap scans have been discussed.

However, there is more to indexing. The following two examples will only differ slightly although the performance difference might be fairly large. Here is the first query:

```
test=# EXPLAIN SELECT * FROM t_test WHERE id = 34234;
```

QUERY PLAN

```
-----  
Index Scan using idx_id on t_test  
  (cost=0.43..8.45 rows=1 width=9)  
  Index Cond: (id = 34234)
```

There is nothing unusual here. PostgreSQL uses an index to find a single row. What happens if only a single column is selected?

```
test=# EXPLAIN SELECT id FROM t_test WHERE id = 34234;
```

QUERY PLAN

```
-----  
Index Only Scan using idx_id on t_test  
  (cost=0.43..8.45 rows=1 width=4)  
  Index Cond: (id = 34234)  
(2 rows)
```

As you can see, the plan has changed from an index scan to an index only scan. In our example, the `id` column has been indexed, so its content is naturally in the index. There is no need to go to the table in most cases if all the data can already be taken out of the index. Going to the table is (almost) only required if additional fields are queried, which is not the case here. Therefore, the index only scan will promise significantly better performance than a normal index scan.

Practically, it can even make sense to include an additional column into an index here and there to enjoy the benefit of this feature. In MS SQL, adding additional columns is known as covering indexes. Similar behavior can be achieved in PostgreSQL as well.

Understanding additional b-tree features

In PostgreSQL, indexing is a large field and covers many aspects of database work. As I have outlined in this book already, indexing is the key to performance. There is no good performance without proper indexing. Therefore, it is worth inspecting these indexing-related features in more detail.

Combined indexes

In my job, as a professional PostgreSQL support vendor, I am often asked about the difference between combined and individual indexes. In this section, I will try to shed some light on this question.

The general rule is this if a single index can answer your question, it is usually the best choice. However, you cannot index all possible combinations of fields people are filtering on. What you can do is use the properties of combined indexes to achieve as much gain as possible.

Let's suppose we have a table containing three columns: `postal_code`, `last_name`, and `first_name`. A telephone book would make use of a combined index like this. You will see that data is ordered by location. Within the same location, data will be sorted by last name and first name.

The following table will show which operations are possible given the three column index:

Query	Possible	Remarks
<code>postal_code = 2700 AND last_name = 'Schönig' AND first_name = 'Hans'</code>	Yes	This is the ideal use case for this index.
<code>postal_code = 2700 AND last_name = 'Schönig'</code>	Yes	No restrictions.

<code>last_name = 'Schönig'</code> <code>AND</code> <code>postal_code = 2700</code>	Yes	PostgreSQL will simply swap conditions.
<code>postal_code = 2700</code>	Yes	This is just like an index on <code>postal_code</code> ; the combined index just needs more space on the disk.
<code>first_name = 'Hans'</code>	Yes, but a different use case	PostgreSQL cannot use the sorted property of the index anymore. However, in some rare cases (usually very broad tables, including countless columns), PostgreSQL will scan the entire index if it is as cheap as reading the very broad table.

If columns are indexed separately, you will most likely end up seeing bitmap scans. Of course, a single hand-tailored index is better.

Adding functional indexes

So far, you have seen how to index the content of a column as it is. However, this might not always be what you really want. Therefore, PostgreSQL allows the creation of functional indexes. The basic idea is very simple; instead of indexing a value, the output of a function is stored in the index.

The following example shows how the cosine of the `id` column can be indexed:

```
test=# CREATE INDEX idx_cos ON t_random (cos(id));
CREATE INDEX
test=# ANALYZE;
ANALYZE
```

All you have to do is put the function on the list of columns and you are done. Of course, this won't work for all kinds of functions. Functions can only be used if their output is immutable:

```
test=# SELECT age('2010-01-01 10:00:00'::timestampz);
          age
-----
 6 years 9 mons 14:00:00
(1 row)
```

Functions such as `age` are not really suitable for indexing because their output is not constant. Time goes on and consequently, the output of `age` will change too. PostgreSQL will explicitly prohibit functions that have the potential to change their result given the same input. The `cos` function is fine in this respect because the cosine of a value will still be the same in 1,000 years from now.

To test the index, I have written a simple query to show what will happen:

```
test=# EXPLAIN SELECT * FROM t_random WHERE cos(id) = 10;
               QUERY PLAN
-----
Index Scan using idx_cos on t_random (cost=0.43..8.45 rows=1 width=9)
  Index Cond: (cos((id)::double precision) = '10'::double precision)
(2 rows)
```

As expected, the functional index will be used just like any other index.

Reducing space consumption

Indexing is nice and its main purpose is to speed up things as much as possible. As with all the good stuff, indexing comes with a price tag: space consumption. To do its magic, an index has to store values in an organized fashion. If your table contains 10 million integer values, the index belonging to the table will logically contain these 10 million integer values plus additional overhead.

A b-tree will contain a pointer to each row in the table, and so it is certainly not free of charge. To figure out how much space an index will need, you can ask the `psql` using the `di+` command:

```
test=# \di+
               List of relations
 Schema | Name | Type | Owner | Table | Size
-----+-----+-----+-----+-----+-----
 public | idx_cos | index | hs | t_random | 86 MB
 public | idx_id | index | hs | t_test | 86 MB
 public | idx_name | index | hs | t_test | 86 MB
 public | idx_random | index | hs | t_random | 86 MB
(4 rows)
```

In my database, the staggering amount of 344 MB has been burned to store these indexes. Now, compare this to the amount of storage burned by the underlying tables:

```
test=# \d+
               List of relations
 Schema | Name          | Type      | Owner | Size
-----+-----+-----+-----+-----
 public | t_random      | table     | hs    | 169 MB
 public | t_test        | table     | hs    | 169 MB
 public | t_test_id_seq | sequence  | hs    | 8192 bytes
(3 rows)
```

The size of both tables combined is just 338 MB. In other words, our indexing needs more space than the actual data. In the real world, this is common and actually pretty likely. Recently, I visited a Cybertec customer in Germany and I saw a database in which 64% of the database size was made up of indexes that were never used (not a single time over the period of months). So, over-indexing can be an issue just like under-indexing. Remember, these indexes don't just consume space. Every `INSERT` or `UPDATE` must maintain the values in the indexes as well. In extreme cases, like our example, this vastly decreases write throughput.

If there are just a handful of different values in the table, partial indexes are a solution:

```
test=# DROP INDEX idx_name;
DROP INDEX
test=# CREATE INDEX idx_name ON t_test (name)
        WHERE name NOT IN ('hans', 'paul');
CREATE INDEX
```

In this case, the majority has been excluded from the index and a small, efficient index can be enjoyed:

```
test=# \di+ idx_name
               List of relations
 Schema | Name   | Type  | Owner | Table | Size
-----+-----+-----+-----+-----+-----
 public | idx_name | index | hs    | t_test | 8192 bytes
(1 row)
```

Note that it only makes sense to exclude very frequent values that make up a large part of the table (at least 25% or so). Ideal candidates for partial indexes are gender (we assume that most people are male or female), nationality (assuming that most people in your country have the same nationality), and so on. Of course, applying this kind of trickery requires some deep knowledge of your data, but it certainly pays off.

Adding data while indexing

Creating an index is easy. However, keep in mind that you cannot modify a table while an index is being built. The `CREATE INDEX` command will lock up the table using a `SHARE` lock to ensure that no changes happen. While this is clearly no problem for small tables, it will cause issues on large ones on production systems. Indexing a terabyte of data or so will take some time and therefore, blocking a table for too long can become an issue.

The solution to the problem is the `CREATE INDEX CONCURRENTLY` command. Building the index will take a lot longer (usually at least twice as long), but you can use the table normally during index creation.

Here is how it works:

```
test=# CREATE INDEX CONCURRENTLY idx_name2 ON t_test (name);
CREATE INDEX
```

Note that PostgreSQL does not guarantee success if you are using the `CREATE INDEX CONCURRENTLY` command. An index can end up being marked as invalid if the operations going on on your system somehow conflict with the index creation.

Introducing operator classes

So far, the goal was to figure out what to index and to blindly apply an index on this column or on a group of columns. There is one assumption, however, that we have silently accepted to make this work. Up until now, we have worked on the assumption that the order in which the data has to be sorted is a somewhat fixed constant. In reality, this assumption might not hold true. Sure, numbers will always be in the same order, but other kinds of data will most likely not have a predefined, fixed sort order.

To prove my point, I have compiled a real-world example. Take a look at the following two records:

```
1118 09 08 78
2345 01 05 77
```

My question now is, are those two rows ordered properly? They might be because one comes before another. However, this is wrong because these two rows do have some hidden semantics. What you see here are two Austrian social security numbers. 09 08 78 actually means August 9, 1978, and 01 05 77 actually means May 1, 1977. The first four numbers consist of a checksum and some sort of auto-incremented three digit number. So in reality, 1977 comes before 1978 and we might consider swapping those two lines to achieve the desired sort order.

The problem is that PostgreSQL has no idea what these two rows actually mean. If a column is marked as text, PostgreSQL will apply the standard rules to sort the text. If the column is marked as a number, PostgreSQL will apply the standard rules to sort numbers. Under no circumstances will it ever use something as odd as I've described. If you think that the facts I outlined previously are the only things to consider when processing those numbers, you are wrong. How many months does a year have? 12? Far from true. In the Austrian social security system, these numbers can hold up to 14 months. Why? Remember, . . . three digits are simply an auto-increment value. The trouble is that if an immigrant or a refugee has no valid paperwork and if his birthday is not known, he will be assigned an artificial birthday in the 13th month. During the Balkan wars in 1990, Austria offered asylum to over 115,000 refugees. Naturally, this three-digit number was not enough, and a 14th month was added. Now, which standard data type can handle this kind of COBOL-leftover from the early 1970s (that was when the layout of the social security number was introduced)? The answer is, none.

To handle special-purpose fields in a sane way, PostgreSQL offers operator classes:

```
test=# \h CREATE OPERATOR CLASS
Command: CREATE OPERATOR CLASS
Description: define a new operator class
Syntax:
CREATE OPERATOR CLASS name [ DEFAULT ] FOR TYPE data_type
    USING index_method [ FAMILY family_name ] AS
    { OPERATOR strategy_number operator_name [ ( op_type, op_type ) ]
      [ FOR SEARCH | FOR ORDER BY sort_family_name ]
      | FUNCTION support_number [ ( op_type [ , op_type ] ) ]
        function_name ( argument_type [, ...] )
      | STORAGE storage_type
    } [, ... ]
```

An `operator` class will tell an index how to behave. Let's take a look at a standard binary tree. It can perform five operations:

Strategy	Operator	Description
1	<	Less than
2	<=	Less than or equal to
3	=	Equal to
4	>=	Greater than or equal to
5	>	Greater than

The standard operator classes support the standard data types and standard operators we have used throughout this book. If you want to handle social security numbers, it is necessary to come up with your own operators capable of providing you with the logic you need. Those custom operators can then be used to form an `operator` class, which is nothing more than a strategy passed to the index to configure how it should behave.

Hacking up an operator class for a b-tree

To give you a practical example of what an `operator` class looks like, I have hacked up some code to handle social security numbers. To keep it simple, I have paid no attention to details such as checksums.

Creating new operators

The first thing that has to be done is come up with the desired operators. Note that five operators are needed. There is one operator for each strategy. A strategy of an index is really like a plugin that allows you to put in your own code.

Before getting started, I have compiled some test data:

```
CREATE TABLE t_sva (sva text);

INSERT INTO t_sva VALUES ('1118090878');
INSERT INTO t_sva VALUES ('2345010477');
```

Now that the test data is there, it is time to create an operator. For this purpose, PostgreSQL offers the `CREATE OPERATOR` command:

```
test=# \h CREATE OPERATOR
Command: CREATE OPERATOR
Description: define a new operator
Syntax:
CREATE OPERATOR name (
    PROCEDURE = function_name
    [, LEFTARG = left_type ] [, RIGHTARG = right_type ]
    [, COMMUTATOR = com_op ] [, NEGATOR = neg_op ]
    [, RESTRICT = res_proc ] [, JOIN = join_proc ]
    [, HASHES ] [, MERGES ]
)
```

Basically, the concept is as follows; `operator` calls a function, which gets one or two parameters, one for the left argument and one for the right argument of the operator.

As you can see, an operator is nothing more than a function call. So, consequently, it is necessary to implement the logic needed into those functions hidden by the operators. In order to fix the sort order, I have written a function called `normalize_si`:

```
CREATE OR REPLACE FUNCTION normalize_si(text) RETURNS text AS $$
BEGIN
    RETURN substring($1, 9, 2) ||
           substring($1, 7, 2) ||
           substring($1, 5, 2) ||
           substring($1, 1, 4);
END; $$
LANGUAGE 'plpgsql' IMMUTABLE;
```

Calling the function will return the following result:

```
test=# SELECT normalize_si('1118090878');
normalize_si
-----
7808091118 (1 row)
```

As you can see, all we did is swap some digits. It is now possible to just use the normal string sort order. In the next step, this function can already be used to compare social security numbers directly.

The first function needed is the less than function, which is needed by the first strategy:

```
CREATE OR REPLACE FUNCTION si_lt(text, text) RETURNS boolean AS $$
BEGIN
    RETURN normalize_si($1) < normalize_si($2);
```

```
END;  
$$ LANGUAGE 'plpgsql' IMMUTABLE;
```

There are two important things to note here:

- The function must not be written in SQL. It only works in a procedural or in a compiled language. The reason for that is SQL functions can be inline under some circumstances and this would cripple the entire endeavor.
- The second issue is that you should stick to the naming convention used in this chapter—it is widely accepted by the community. Less than functions should be called `_lt`, less or equal to functions should be called `_le`, and so on.

Given this knowledge, the next functions needed by our future operators can be defined:

```
-- lower equals  
CREATE OR REPLACE FUNCTION si_le(text, text)  
  RETURNS boolean AS  
$$  
  BEGIN  
    RETURN normalize_si($1) <= normalize_si($2);  
  END;  
$$  
LANGUAGE 'plpgsql' IMMUTABLE;  
  
-- greater equal  
CREATE OR REPLACE FUNCTION si_ge(text, text)  
  RETURNS boolean AS  
$$  
  BEGIN  
    RETURN normalize_si($1) >= normalize_si($2);  
  END;  
$$  
LANGUAGE 'plpgsql' IMMUTABLE;  
  
-- greater  
CREATE OR REPLACE FUNCTION si_gt(text, text)  
  RETURNS boolean AS  
$$  
  BEGIN  
    RETURN normalize_si($1) > normalize_si($2);  
  END;  
$$  
LANGUAGE 'plpgsql' IMMUTABLE;
```

So far, four functions have been defined. A fifth function for the equals operator is not necessary. We can simply take the existing operator because equals do not depend on sort order anyway.

Now that all functions are in place, it is time to define these operators:

```
-- define operators
CREATE OPERATOR <# ( PROCEDURE=si_lt,
                    LEFTARG=text,
                    RIGHTARG=text);
```

The design of the operator is actually very simple. The operator needs a name (in my case <#), a procedure, which is supposed to be called, as well as the datatype of the left and the right argument. When the operator is called, the left argument will be the first parameter of `si_lt` and the right argument will be the second argument.

The remaining three operators follow the same principle:

```
CREATE OPERATOR <=# ( PROCEDURE=si_le,
                    LEFTARG=text,
                    RIGHTARG=text);

CREATE OPERATOR >=# ( PROCEDURE=si_ge,
                    LEFTARG=text,
                    RIGHTARG=text);

CREATE OPERATOR ># ( PROCEDURE=si_gt,
                    LEFTARG=text,
                    RIGHTARG=text);
```

Depending on the type of index you are using, a couple of support functions are needed. In the case of standard b-trees, there is only one support function needed, which is used to speed things up internally:

```
CREATE OR REPLACE FUNCTION si_same(text, text) RETURNS int AS $$
BEGIN
    IF normalize_si($1) < normalize_si($2)
    THEN
        RETURN -1;
    ELSIF normalize_si($1) > normalize_si($2)
    THEN
        RETURN +1;
    ELSE
        RETURN 0;
    END IF;
END;
$$ LANGUAGE 'plpgsql' IMMUTABLE;
```

The `si_same` function will either return `-1` if the first parameter is smaller, `0` if both parameters are equal, and `1` if the first parameter is greater. Internally, the `_same` function is the workhorse, so you should make sure that your code is optimized.

Creating operator classes

Finally, all components are in place and it is finally possible to create the operator class needed by the index:

```
CREATE OPERATOR CLASS sva_special_ops
FOR TYPE text USING btree
AS
    OPERATOR 1 <# ,
    OPERATOR 2 <=# ,
    OPERATOR 3 = ,
    OPERATOR 4 >=# ,
    OPERATOR 5 ># ,

    FUNCTION 1 si_same(text, text);
```

The `CREATE OPERATOR CLASS` command connects strategies and operators `OPERATOR 1`.

`<#` means that strategy 1 will use the `<#` operator. Finally, the `_same` function is connected with the operator class.

Note that the operator class has a name and that it has been explicitly defined to work with b-trees. The operator class can already be used during index creation:

```
CREATE INDEX idx_special ON t_sva (sva sva_special_ops);
```

Creating an index works in a slightly different way than previously: `sva sva_special_ops` means that the `sva` column is indexed using the `sva_special_ops` operator class. If `sva_special_ops` is not explicitly used, then PostgreSQL will not go for our special sort order but decide on the default operator class.

Testing custom operator classes

In our example, the test data consists of just two rows. Therefore, PostgreSQL will never use an index because the table is just too small to justify the overhead of even opening the index. To be able to still test without having to load too much data, you can advise the optimizer to make sequential scans more expensive.

Making operations more expensive can be done in your session using the following instruction:

```
SET enable_seqscan TO off;
```

The index works as expected:

```
test=# explain SELECT * FROM t_sva WHERE sva = '0000112273';
               QUERY PLAN
```

```
-----
Index Only Scan using idx_special on t_sva
  (cost=0.13..8.14 rows=1 width=32)
  Index Cond: (sva = '0000112273'::text)
(2 rows)
```

```
test=# SELECT * FROM t_sva;
      sva
```

```
-----
2345010477
1118090878
(2 rows)
```

Understanding PostgreSQL index types

So far, only binary trees have been discussed. However, in many cases, b-trees are just not enough. Why is that the case? As discussed in this chapter, b-trees are basically based on sorting. Operators $<$, $<=$, $=$, $>=$, and $>$ can be handled using b-trees. The trouble is, not all.

Data types can be sorted in a useful way. Just imagine a polygon. How would you sort these objects in a useful way? Sure, you can sort by the area covered, its length or so, but doing this won't allow you to actually find them using a geometric search.

The solution to the problem is to provide more than just one index type. Each index will serve a special purpose and do exactly what is needed. The following index types are available (as of PostgreSQL 10.0):

```
test=# SELECT * FROM pg_am;
  amname  | amhandler  | amtype
-----+-----+-----
btree    | bthandler  | i
hash     | hashhandler | i
GiST     | GiSThandler | i
gin      | ginhandler  | i
spGiST   | spghandler  | i
```

```
brin      | brinhandler | i  
(6 rows)
```

There are six types of indexes. B-trees have already been discussed in great detail, but what are those other index types good for? The following sections will outline the purpose of each index type available in PostgreSQL.

Note that there are some extensions out there that can be used on top of what you can see here. Additional index types available on the web are rum, vodka, and in the future, cognac.

Hash indexes

Hash indexes have been around for many years. The idea is to hash the input value and store it for later lookups. Having hash indexes actually makes sense. However, before PostgreSQL 10.0, it was not advised to use hash indexes because PostgreSQL had no WAL support for them. In PostgreSQL 10.0, this has changed. Hash indexes are now fully logged and are therefore ready for replication and are considered to be a 100% crash safe.

Hash indexes are generally a bit larger than b-tree indexes. Suppose you want to index 4 million integer values. A btree will need around 90 MB of storage to do this. A hash index will need around 125 MB on disk. The assumption made by many people that a hash is super small on the disk is therefore, in many cases, just wrong.

GiST indexes

Generalized Search Tree (GiST) indexes are highly important index types because they are used for a variety of different things. GiST indexes can be used to implement R-tree behavior and it is even possible to act as b-tree. However, abusing GiST for b-tree indexes is not recommended.

Typical use cases for GiST are as follows:

- Range types
- Geometric indexes (for example, used by the highly popular PostGIS extension)
- Fuzzy searching

Understanding how GiST works

To many people, GiST is still a black box. Therefore, I have decided to add a section to this chapter outlining how GiST works internally.

Consider the following diagram:




Figure 3.1: Source: http://leopard.in.ua/assets/images/postgresql/pg_indexes/pg_indexes2.jpg

Take a look at the tree. You will see that R1 and R2 are on top. R1 and R2 are the bounding boxes containing everything else. R3, R4, and R5 are contained by R1. R8, R9, and R10 are contained by R3, and so on. A GiST index is therefore hierarchically organized. What you can see in the diagram is that some operations, which are not available in b-trees are supported. Some of those operations are overlaps, left of, right of, and so on. The layout of a GiST tree is ideal for geometric indexing.

Extending GiST

Of course, it is also possible to come up with your own operator classes. The following strategies are supported:

Operation	Strategy number
Strictly left of	1
Does not extend to right of	2
Overlaps	3
Does not extend to left of	4
Strictly right of	5
Same	6
Contains	7
Contained by	8
Does not extend above	9
Strictly below	10
Strictly above	11
Does not extend below	12

If you want to write operator classes for GiST, a couple of support functions have to be provided. In the case of a b-tree, there is only the same function - GiST indexes provide a lot more:

Function	Description	Support function number
consistent	The functions determine whether a key satisfies the query qualifier. Internally, strategies are looked up and checked.	1
union	Calculate the union of a set of keys. In case of numeric values, simply the upper and lower values or a range are computed. It is especially important to geometries.	2
compress	Compute a compressed representation of a key or value.	3
decompress	This is the counterpart of the compress function.	4

penalty	During insertion, the cost of inserting into the tree will be calculated. The cost determines where the new entry will go inside the tree. Therefore, a good penalty function is key to the good overall performance of the index.	5
picksplit	Determines where to move entries in case of a page split. Some entries have to stay on the old page while others will go to the new page being created. Having a good picksplit function is essential to a good index performance.	6
equal	The equal function is similar to the same function you have already seen in b-trees.	7
distance	Calculates the distance (a number) between a key and the query value. The distance function is optional and is needed in case KNN search is supported.	8
fetch	Determine the original representation of a compressed key. This function is needed to handle index only scans as supported by the recent version of PostgreSQL.	9

Implementing operator classes for GiST indexes is usually done in C. If you are interested in a good example, I advise you to check out the `btree_GiST` module in the `contrib` directory. It shows how to index standard data types using GiST and is a good source of information as well as inspiration.

GIN indexes

Generalized inverted (GIN) indexes are a good way to index text. Suppose you want to index a million text documents. A certain word may occur millions of times. In a normal b-tree, this would mean that the key is stored millions of times. Not so in a GIN. Each key (or word) is stored once and assigned to a document list. Keys are organized in a standard b-tree. Each entry will have a document list pointing to all entries in the table having the same key. A GIN index is very small and compact. However, it lacks an important feature found in the b-trees-sorted data. In a GIN, the list of item pointers associated with a certain key is sorted by the position of the row in the table and not by some arbitrary criteria.

Extending GIN

Just like any other index, GIN can be extended. The following strategies are available:

Operation	Strategy number
Overlap	1
Contains	2
Is contained by	3
Equal	4

On top of this, the following support functions are available:

Function	Description	Support function number
<code>compare</code>	The compare function is similar to the same function you have seen in b-trees. If two keys are compared, it returns -1 (lower), 0 (equal), or 1 (higher).	1
<code>extractValue</code>	Extract keys from a value to be indexed. A value can have many keys. For example, a text value might consist of more than one word.	2
<code>extractQuery</code>	Extract keys from a query condition.	3
<code>consistent</code>	Check whether a value matches a query condition.	4
<code>comparePartial</code>	Compare a partial key from a query and a key from the index. Returns -1, 0, or 1 (similar to the same function supported by b-trees).	5
<code>triConsistent</code>	Determine whether a value matches a query condition (ternary variant). It is optional if the consistent function is present.	6

If you are looking for a good example of how to extend GIN, consider looking at the `btree_gin` module in the PostgreSQL `contrib` directory. It is a valuable source of information and a good way to start your own implementation.

If you are interested in full-text search, more information will be provided later on in this chapter.

SP-GiST indexes

Space partitioned GiST (SP-GiST) has mainly been designed for in-memory use. The reason for this is an SP-GiST stored on disk needs a fairly high number of disk hits to function. Disk hits are way more expensive than just following a couple of pointers in RAM.

The beauty is that SP-GiST can be used to implement various types of trees such as quad-trees, k-d trees, and radix trees (tries).

The following strategies are provided:

Operation	Strategy number
Strictly left of	1
Strictly right of	5
Same	6
Contained by	8
Strictly below	10
Strictly above	11

To write your own operator classes for SP-GiST, a couple of functions have to be provided:

Function	Description	Support function number
config	Provides information about the operator class in use	1
choose	Figures out how to insert a new value into an inner tuple	2
picksplit	Figures out how to partition/split a set of values	3
inner_consistent	Determine which subpartitions need to be searched for a query	4
leaf_consistent	Determine whether key satisfies the query qualifier	5

BRIN indexes

Block range indexes (BRIN) are of great practical use. All indexes discussed until now need quite a lot of disk space. Although a lot of work has gone into shrinking GIN indexes and the like, they still need quite a lot because an index pointer is needed for each entry. So, if there are 10 million entries, there will be 10 million index pointers. Space is the main concern addressed by the BRIN indexes. A BRIN index does not keep an index entry for each tuple but will store the minimum and the maximum value of 128 (default) blocks of data (1 MB). The index is therefore very small but lossy. Scanning the index will return more data than we asked for. PostgreSQL has to filter out these additional rows in a later step.

The following example demonstrates how small a BRIN index really is:

```
test=# CREATE INDEX idx_brin ON t_test USING brin(id);
CREATE INDEX
test=# \di+ idx_brin
```

List of relations					
Schema	Name	Type	Owner	Table	Size
public	idx_brin	index	hs	t_test	48 KB

(1 row)

In my example, the BRIN index is 2,000 times smaller than a standard b-tree. The question naturally arising now is, why don't we always use BRIN indexes? To answer this kind of question, it is important to reflect on the layout of BRIN; the minimum and maximum value for 1 MB are stored. If the data is sorted (high correlation), BRIN is pretty efficient because we can fetch 1 MB of data, scan it, and we are done. However, what if the data is shuffled? In this case, BRIN won't be able to exclude chunks of data anymore because it is very likely that something close to the overall high and the overall low is within 1 MB of data. Therefore, BRIN is mostly made for highly correlated data. In reality, correlated data is quite likely in data warehousing applications. Often, data is loaded every day and therefore dates can be highly correlated.

Extending BRIN indexes

BRIN supports the same strategies as a b-tree and therefore needs the same set of operators. The code can be reused nicely:

Operation	Strategy number
Less than	1
Less than or equal	2
Equal	3
Greater than or equal	4
Greater than	5

The support functions needed by BRIN are as follows:

Function	Description	Support function number
opcInfo	Provide internal information about the indexed columns	1
add_value	Add an entry to an existing summary tuple	2
consistent	Check whether a value matches a condition	3
union	Calculate the union of two summary entries (minimum/maximum values)	4

Adding additional indexes

Since PostgreSQL 9.6, there has been an easy way to deploy entirely new index types as extensions. This is pretty cool because if those index types provided by PostgreSQL are not enough, it is possible to add additional ones serving precisely your purpose. The instruction to do this is `CREATE ACCESS METHOD`:

```
test=# \h CREATE ACCESS METHOD
```

Command: `CREATE ACCESS METHOD`

Description: define a new access method

Syntax:

```
CREATE ACCESS METHOD name
    TYPE access_method_type
    HANDLER handler_function
```

Don't worry too much about this command—just in case you ever deploy your own index type, it will come as a ready-to-use extension.

One of these extensions implements bloom filters. Bloom filters are probabilistic data structures. They sometimes return too many rows but never too few. Therefore, a bloom filter is a good method to pre-filter data.

How does it work? A bloom filter is defined on a couple of columns. A bitmask is calculated based on the input values, which is then compared to your query. The upside of a bloom filter is that you can index as many columns as you want. The downside is that the entire bloom filter has to be read. Of course, the bloom filter is smaller than the underlying data and so it is, in many cases, very beneficial.

To use bloom filters, just activate the extension, which is a part of the PostgreSQL contrib package:

```
test=# CREATE EXTENSION bloom;
CREATE EXTENSION
```

As stated previously, the idea behind a bloom filter is that it allows you to index as many columns as you want. In many real-world applications, the challenge is to index many columns without knowing which combinations the user will actually need at runtime. In the case of a large table, it is totally impossible to create standard b-tree indexes on, say, 80 fields or more. A bloom filter might be an alternative in this case:

```
test=# CREATE TABLE t_bloom (x1 int, x2 int, x3 int, x4 int,
                             x5 int, x6 int, x7 int);
CREATE TABLE
```

Creating the index is easy:

```
test=# CREATE INDEX idx_bloom ON t_bloom USING bloom(x1, x2, x3, x4,
                                                     x5, x6, x7);
CREATE INDEX
```

If sequential scans are turned off, the index can be seen in action:

```
test=# SET enable_seqscan TO off;
SET
test=# explain SELECT * FROM t_bloom WHERE x5 = 9 AND x3 = 7;
               QUERY PLAN
-----
Bitmap Heap Scan on t_bloom (cost=18.50..22.52 rows=1 width=28)
  Recheck Cond: ((x3 = 7) AND (x5 = 9))
    -> Bitmap Index Scan on idx_bloom (cost=0.00..18.50 rows=1 width=0)
          Index Cond: ((x3 = 7) AND (x5 = 9))
```

Note that I have queried a combination of random columns; they are not related to the actual order in the index. The bloom filter will still be beneficial.

If you are interested in bloom filters, consider checking out the website: https://en.wikipedia.org/wiki/Bloom_filter.

Achieving better answers with fuzzy searching

Performing precise searching is not the only thing expected by users these days. Modern websites have educated users in a way that they always expect a result, regardless of the user input. If you search on Google, there will always be an answer even if the user input is wrong, full of typos, or simply pointless. People expect good results regardless of the input data.

Taking advantage of pg_trgm

To do fuzzy searching with PostgreSQL, you can add the `pg_trgm` extension. To activate the extension, just run the following instruction:

```
test=# CREATE EXTENSION pg_trgm;
CREATE EXTENSION
```

The `pg_trgm` extension is pretty powerful, and to show what it is capable of, I have compiled some sample data consisting of 2,354 names of villages and cities here in Austria, Europe.

Our sample data can be stored in a simple table:

```
test=# CREATE TABLE t_location (name text);
CREATE TABLE
```

My company website has all the data and PostgreSQL enables you to load the data directly:

```
test=# COPY t_location FROM PROGRAM
      'curl https://www.cybertec-postgresql.com/secret/orte.txt';
COPY 2354
```



The `curl` (a command-line tool to fetch data) has to be installed. If you don't have this tool, download the file normally and import it from your local filesystem.

Once the data has been loaded, it is possible to check out the content of the table:

```
test=# SELECT * FROM t_location LIMIT 4;
          name
-----
Eisenstadt
Rust
Breitenbrunn am Neusiedler See
Donnerskirchen
(4 rows)
```

If German is not your mother tongue, it will be impossible to spell the names of those locations without severe mistakes.

The `pg_trgm` provides us with a distance operator that computes the distance between two strings:

```
test=# SELECT 'abcde' <-> 'abdeacb';
?column?
-----
0.833333
(1 row)
```

The distance is a number between zero and one. The lower the number, the more similar the two strings are.

How does this work? Trigrams take a string and dissect it into sequences of three characters each:

```
test=# SELECT show_trgm('abcdef');
          show_trgm
-----
{" a", " ab", abc, bcd, cde, def, "ef "}
(1 row)
```

These sequences will then be used to come up with the distance you have just seen. Of course, the distance operator can be used inside a query to find the closest match:

```
test=# SELECT *
FROM t_location
ORDER BY name <-> 'Kramertneusiedel'
LIMIT 3;
      name
-----
Gramatneusiedl
Klein-Neusiedl
Patzneusiedl
(3 rows)
```

Gramatneusiedl is pretty close to Kramertneusiedel. It sounds similar and using a K instead of a G is a pretty common mistake. On Google, you will sometimes see did you mean. It is quite likely that Google is using n-grams here to do that.

In PostgreSQL, it is possible to use GiST to index on text using trigrams:

```
test=# CREATE INDEX idx_trgm ON t_location
      USING GiST(name GiST_trgm_ops);
CREATE INDEX
```

`pg_trgm` provides us with the `GIST_trgm_ops` operator class designed to do similarity searches. The following listing shows that the index is used as expected:

```
test=# explain SELECT *
      FROM t_location
      ORDER BY name <-> 'Kramertneusiedel'
      LIMIT 5;

               QUERY PLAN
-----
Limit (cost=0.14..0.58 rows=5 width=17)
-> Index Scan using idx_trgm on t_location
    (cost=0.14..207.22 rows=2354 width=17)
    Order By: (name <-> 'Kramertneusiedel'::text)
(3 rows)
```

Speeding up LIKE queries

`LIKE` queries definitely cause some of the worst performance problems faced by people around the globe these days. In most database systems, `LIKE` is pretty slow and requires a sequential scan. In addition to that, end users quickly figure out that a fuzzy search will, in many cases, return better results than precise queries. A single type of `LIKE` query on a large table can, therefore, often cripple the performance of an entire database server if it is called often enough.

Fortunately, PostgreSQL offers a solution to the problem and the solution happens to be installed already:

```
test=# explain SELECT * FROM t_location WHERE name LIKE '%neusi%';
               QUERY PLAN
-----
Bitmap Heap Scan on t_location
  (cost=4.33..19.05 rows=24 width=13)
  Recheck Cond: (name ~~ '%neusi%'::text)
-> Bitmap Index Scan on idx_trgm (cost=0.00..4.32 rows=24 width=0)
    Index Cond: (name ~~ '%neusi%'::text)
(4 rows)
```

The trigram index deployed in the previous section is also suitable to speed up `LIKE`. Note that the `%` symbols can be used at any point in the search string. This is a major advantage over standard b-trees, which just happen to speed up wildcards at the end of the query.

Handling regular expressions

However, this is still not everything. Trigram indexes are even capable of speeding up simple regular expressions. The following example shows how this can be done:

```
test=# SELECT * FROM t_location WHERE name ~ '[A- C].*neu.*';
      name
-----
 Bruckneudorf
(1 row)

test=# explain SELECT * FROM t_location WHERE name ~ '[A-C].*neu.*';
              QUERY PLAN
-----
Index Scan using idx_trgm on t_location (cost=0.14..8.16
 rows=1 width=13)
  Index Cond: (name ~ '[A-C].*neu.*'::text)
(2 rows)
```

PostgreSQL will inspect the regular expression and use the index to answer the question.



Internally, PostgreSQL can transform the regular expression into a graph and traverse the index accordingly.

Understanding full-text search - FTS

If you are looking up names or for simple strings, you are usually querying the entire content of a field. In **Full-Text-Search (FTS)**, this is different. The purpose of the full-text search is to look for words or groups of words, which can be found in a text. Therefore, FTS is more of a contains operation as you are basically never looking for an exact string.

In PostgreSQL, FTS can be done using GIN indexes. The idea is to dissect a text, extract valuable lexemes (= "preprocessed tokens of words"), and index those elements rather than the underlying text. To make your search even more successful, those words are preprocessed.

Here is an example:

```
test=# SELECT to_tsvector('english', 'A car, I want a car. I would not even
mind having many cars');
               to_tsvector
-----
'car':2,6,14 'even':10 'mani':13 'mind':11 'want':4 'would':8
(1 row)
```

The example shows a simple sentence. The `to_tsvector` function will take the string, apply English rules, and perform a stemming process. Based on the configuration (`english`), PostgreSQL will parse the string, throw away stop words, and stem individual words. For example, `car` and `cars` will be transformed to the `car`. Note that this is not about finding the word stem. In the case of `many`, PostgreSQL will simply transform the string to `mani` by applying standard rules working nicely with the English language.

Note that the output of the `to_tsvector` function is highly language dependent. If you tell PostgreSQL to treat the string as `dutch`, the result will be totally different:

```
test=# SELECT to_tsvector('dutch', 'A car, I want a car. I would not even
mind having many cars');
               to_tsvector
-----
'a':1,5 'car':2,6,14 'even':10 'having':12 'i':3,7 'many':13
'mind':11 'not':9 'would':8
(1 row)
```

To figure out which configurations are supported, consider running the following query:

```
SELECT cfname FROM pg_ts_config;
```

Comparing strings

After taking a brief look at the stemming process, it is time to figure out how a stemmed text can be compared to a user query. The following code snippet checks for the word wanted:

```
test=# SELECT to_tsvector('english', 'A car, I want a car. I would not even
mind having many cars') @@ to_tsquery('english', 'wanted');
?column?
-----
t
(1 row)
```

Note that `wanted` does not actually show up in the original text. Still, PostgreSQL will return `true`. The reason is that `want` and `wanted` are both transformed to the same lexeme, so the result is `true`. Practically, this makes a lot of sense. Imagine you are looking for a car on Google. If you find pages selling cars, this is totally fine. Finding common lexemes is, therefore, an intelligent idea.

Sometimes, people are not only looking for a single word, but want to find a set of words. With `to_tsquery`, this is possible, as shown in the next example:

```
test=# SELECT to_tsvector('english', 'A car, I want a car. I would not even
mind having many cars') @@ to_tsquery('english', 'wanted & bmw');
?column?
-----
f
(1 row)
```

In this case, `false` is returned because `bmw` cannot be found in our input string. In the `to_tsquery` function, `&` means `and` and `|` means `or`. It is therefore easily possible to build complex search strings.

Defining GIN indexes

If you want to apply text search to a column or a group of columns, there are basically two choices:

- Create a functional index using GIN
- Add a column containing ready-to-use tsvectors and a trigger to keep them in sync

In this section, both options will be outlined. To show how things work, I have created some sample data:

```
test=# CREATE TABLE t_fts AS SELECT comment
FROM pg_available_extensions;
SELECT 43
```

Indexing the column directly with a functional index is definitely a slower but more space efficient way to get things done:

```
test=# CREATE INDEX idx_fts_func ON t_fts
USING gin(to_tsvector('english', comment));
CREATE INDEX
```

Deploying an index on the function is easy, but it can lead to some overhead. Adding a materialized column needs more space, but will lead to a better runtime behavior:

```
test=# ALTER TABLE t_fts ADD COLUMN ts tsvector;
ALTER TABLE
```

The only trouble is, how do you keep this column in sync? The answer is by using a trigger:

```
test=# CREATE TRIGGER tsvectorupdate
  BEFORE INSERT OR UPDATE ON t_fts
  FOR EACH ROW
  EXECUTE PROCEDURE
  tsvector_update_trigger(somename, 'pg_catalog.english', 'comment');
```

Fortunately, PostgreSQL already provides a C function that can be used by a trigger to sync the `tsvector` column. Just pass a name, the desired language, as well as a couple of columns to the function, and you are already done. The trigger function will take care of all that is needed. Note that a trigger will always operate within the same transaction as the statement making the modification. Therefore, there is no risk of being inconsistent.

Debugging your search

Sometimes, it is not quite clear why a query matches a given search string. To debug your query, PostgreSQL offers the `ts_debug` function. From a user's point of view, it can be used just like `to_tsvector`. It reveals a lot about the inner workings of the FTS infrastructure:

```
test=# \x
Expanded display is on.

test=# SELECT * FROM ts_debug('english', 'go to
www.postgresql-support.de');
-[ RECORD 1 ]+-----
alias      | asciiword
description | Word, all ASCII
token      | go
dictionaries | {english_stem}
dictionary | english_stem
lexemes    | {go}
-[ RECORD 2 ]+-----
alias      | blank
description | Space symbols
token      |
dictionaries | {}
dictionary |
lexemes    |
```

```

-[ RECORD 3 ]+-----
alias      | asciiword
description | Word, all ASCII
token      | to
dictionaries | {english_stem}
dictionary  | english_stem
lexemes     | {}
-[ RECORD 4 ]+-----
alias      | blank
description | Space symbols
token      |
dictionaries | {}
dictionary  |
lexemes     |
-[ RECORD 5 ]+-----
alias      | host
description | Host
token      | www.postgresql-support.de
dictionaries | {simple}
dictionary  | simple
lexemes     | {www.postgresql-support.de}

```

`ts_debug` will list every token found and display information about the token. You will see which token the parser found, the dictionary used, as well as the type of object. In my example, blanks, words, and hosts have been found. You might also see numbers, email addresses, and a lot more. Depending on the type of string, PostgreSQL will handle things differently. For example, it makes absolutely no sense to stem hostnames and e-mail addresses.

Gathering word statistics

Full-text search can handle a lot of data. To give end users more insights into their texts, PostgreSQL offers the `pg_stat` function, which returns a list of words:

```

SELECT * FROM ts_stat('SELECT to_tsvector(''english'', comment) FROM
pg_available_extensions') ORDER BY 2 DESC LIMIT 3;
 word      | ndoc | nentry
-----+-----+-----
function   | 10   | 10
data       | 10   | 10
type       | 7    | 7
(3 rows)

```

The `word` column contains the stemmed word, `ndoc` tells us about the number of documents a certain word occurs. `nentry` indicates how often a word was found all together.

Taking advantage of exclusion operators

So far, indexes have been used to speed things up and to ensure uniqueness. However, a couple of years ago, somebody came up with the idea of using indexes for even more. As you have seen in this chapter, GiST supports operations such as intersects, overlaps, contains, and a lot more. So, why not use those operations to manage data integrity?

Here is an example:

```
test=# CREATE EXTENSION btree_gist;
test=# CREATE TABLE t_reservation (
    room int,
    from_to tsrange,
    EXCLUDE USING GiST (room with =,
                        from_to with &&)
);
CREATE TABLE
```

The `EXCLUDE USING GiST` clause defines additional constraints. If you are selling rooms, you might want to allow different rooms to be booked at the same time. However, you don't want to sell the same room twice during the same period. What the `EXCLUDE` clause says in my example is this, if a room is booked twice at the same time, an error should pop up (the data in `from_to` with must not overlap (`&&`) if it is related to the same room).

The following two rows will not violate constraints:

```
test=# INSERT INTO t_reservation
    VALUES (10, '['2017-01-01', '2017-03-03']');
INSERT 0 1
test=# INSERT INTO t_reservation
    VALUES (13, '['2017-01-01', '2017-03-03']');
INSERT 0 1
```

However, the next `INSERT` will cause a violation because the data overlaps:

```
test=# INSERT INTO t_reservation
      VALUES (13, '['2017-02-02', '2017-08-14']');
ERROR:  conflicting key value violates exclusion constraint
"t_reservation_room_from_to_excl"
DETAIL:  Key (room, from_to)=(13, ['2017-02-02 00:00:00', '2017-08-14
00:00:00']) conflicts with existing key (room, from_to)=(13, ['2017-01-01
00:00:00', '2017-03-03 00:00:00']).
```

The use of exclusion operators is very useful and can provide you with highly advanced means to handle integrity.

Summary

This chapter was all about indexes. You learned when PostgreSQL will decide on an index and which types of indexes exist. On top of just using indexes, it is also possible to implement your own strategies to speed up your applications with custom operators and indexing strategies.

For those of you who really want to take things to the limit, PostgreSQL offers custom access methods.

Chapter 4, *Handling Advanced SQL*, is all about advanced SQL. Many people are not aware of what SQL is really capable of, and therefore, I am going to show people some efficient, more advanced SQL stuff.

4

Handling Advanced SQL

In *Chapter 3, Making Use of Indexes*, you learned about indexing as well as about PostgreSQL's ability to run custom indexing code to speed up queries. In this chapter, you will learn about advanced SQL. Most readers of this book will have some experience of using SQL. However, experience has shown that the advanced features outlined in this book are not widely known and therefore it makes sense to cover them in this context to help people to achieve their goals faster and more efficiently. There has been a long discussion on whether the database is just a simple data store or whether business logic should be in the database or not. Maybe this chapter will shed some light and show how capable a modern relational database really is.

This chapter is about modern SQL and its features. A variety of different and sophisticated SQL features are included and presented in detail. The topics covered are:

- Grouping sets
- Ordered sets
- Hypothetical aggregates
- Windowing functions and analytics

At the end of the chapter, you will be able to understand and use advanced SQL.

Introducing grouping sets

Every advanced user of SQL should be familiar with `GROUP BY` and `HAVING` clauses. But are you also aware of `CUBE`, `ROLLUP`, and `GROUPING SETS`? If not, you might find this chapter worth reading.

Loading some sample data

To make this chapter a pleasant experience for you, I have compiled some sample data, which has been taken from the BP energy report:

<http://www.bp.com/en/global/corporate/energy-economics/statistical-review-of-world-energy/downloads.html>.

Here is the data structure that will be used:

```
test=# CREATE TABLE t_oil (
    region      text,
    country     text,
    year int,
    production  int,
    consumption int
);
CREATE TABLE
```

The test data can be downloaded from our website using `curl` directly:

```
test=# COPY t_oil FROM PROGRAM '
    curl https://www.cybertec-postgresql.com/secret/oil_ext.txt ';
COPY 644
```

As in the previous chapter, you can download the file before importing it. On some operating systems, `curl` is not there by default or has not been installed, so downloading the file before might be an easier option for many people.

There is data for between 1965 and 2010, for 14 nations in two regions of the world:

```
test=# SELECT region, avg(production) FROM t_oil GROUP BY region;
   region   |      avg
-----+-----
Middle East | 1992.6036866359447005
North America | 4541.3623188405797101
(2 rows)
```

Applying grouping sets

The `GROUP BY` clause will turn many rows into one row per group. However, if you do reporting in real life, you might also be interested in the overall average. One additional line might be needed.

Here is how this can be achieved:

```
test=# SELECT region, avg(production)
      FROM t_oil
      GROUP BY ROLLUP (region);
 region      |      avg
-----+-----
 Middle East | 1992.6036866359447005
 North America | 4541.3623188405797101
              | 2607.5139860139860140
(3 rows)
```

ROLLUP will inject an additional line, which will contain the overall average. If you do reporting, it is highly likely that a summary line will be needed. Instead of running two queries, PostgreSQL can provide the data by running just a single query. There is also a second thing you might notice here: different versions of PostgreSQL might return data in a different order. The reason for that is that in PostgreSQL 10.0 the way those grouping sets are implemented has improved significantly. Back in 9.6 and before, PostgreSQL had to do a lot of sorting. Starting with 10.0, it is already possible to use hashing for those operations, which will speed things up, dramatically in many cases:

```
test=# explain SELECT region, avg(production)
      FROM t_oil
      GROUP BY ROLLUP (region);

              QUERY PLAN
-----
MixedAggregate (cost=0.00..17.31 rows=3 width=44)
  Hash Key: region
  Group Key: ()
  -> Seq Scan on t_oil (cost=0.00..12.44 rows=644 width=16)
(4 rows)
```

In case you want data to be sorted, and if you want to ensure that all versions return the data in exactly the same order, it is necessary to add an ORDER BY clause to the query.

Of course, this kind of operation can also be used if you are grouping by more than just one column:

```
test=# SELECT region, country, avg(production)
      FROM t_oil
      WHERE country IN ('USA', 'Canada', 'Iran', 'Oman')
      GROUP BY ROLLUP (region, country);
 region      | country |      avg
-----+-----+-----
 Middle East | Iran    | 3631.6956521739130435
```

Middle East	Oman	586.45454545454545
Middle East		2142.911111111111111
North America	Canada	2123.2173913043478261
North America	USA	9141.3478260869565217
North America		5632.2826086956521739
		3906.7692307692307692

(7 rows)

In this example, PostgreSQL will inject three lines into the result set. One line will be injected for the Middle East and one for North America. On top of that, we will get a line for the overall averages. If you are building a web application, the current result is ideal because you can easily build a GUI to drill into the result set by filtering out the null values.

ROLLUP is suitable when you instantly want to display a result. I have always used it to display final results to end users. However, if you are doing reporting, you might want to pre-calculate more data to ensure more flexibility. The CUBE keyword is what you might have been looking for:

```
test=# SELECT region, country, avg(production)
FROM t_oil
WHERE country IN ('USA', 'Canada', 'Iran', 'Oman')
GROUP BY CUBE (region, country);
 region | country | avg
-----+-----+-----
Middle East | Iran | 3631.6956521739130435
Middle East | Oman | 586.45454545454545
Middle East |  | 2142.911111111111111
North America | Canada | 2123.2173913043478261
North America | USA | 9141.3478260869565217
North America |  | 5632.2826086956521739
           |  | 3906.7692307692307692
           | Canada | 2123.2173913043478261
           | Iran | 3631.6956521739130435
           | Oman | 586.45454545454545
           | USA | 9141.3478260869565217
(11 rows)
```

Note that even more rows have been added to the result. CUBE will create the same data as: GROUP BY region, country + GROUP BY region + GROUP BY country + the overall average. So, the whole idea is to extract many results and various levels of aggregation at once. The resulting cube contains all possible combinations of groups.

ROLLUP and CUBE are really just convenience features on top of the GROUPING SETS clause. With the GROUPING SETS clause, you can explicitly list the aggregates you want:

```
test=# SELECT region, country, avg(production)
      FROM t_oil
      WHERE country IN ('USA', 'Canada', 'Iran', 'Oman')
      GROUP BY GROUPING SETS ( (), region, country);
 region          | country |      avg
-----+-----+-----
 Middle East    |         | 2142.9111111111111111
 North America  |         | 5632.2826086956521739
                |         | 3906.7692307692307692
                | Canada  | 2123.2173913043478261
                | Iran    | 3631.6956521739130435
                | Oman    |  586.4545454545454545
                | USA     | 9141.3478260869565217
(7 rows)
```

In this, I went for three grouping sets: the overall average, GROUP BY region, and GROUP BY country. If you want regions and countries combined, use (region, country).

Investigating performance

Grouping sets is a powerful feature; they help to reduce the number of expensive queries. Internally, PostgreSQL will basically turn to traditional GroupAggregates to make things work. A GroupAggregate node requires sorted data, so be prepared that PostgreSQL might do a lot of temporary sorting:

```
test=# explain SELECT region, country, avg(production)
      FROM t_oil
      WHERE country IN ('USA', 'Canada', 'Iran', 'Oman')
      GROUP BY GROUPING SETS ( (), region, country);
               QUERY PLAN
-----
GroupAggregate (cost=22.58..32.69 rows=34 width=52)
  Group Key: region
  Group Key: ()
  Sort Key: country
    Group Key: country
    -> Sort (cost=22.58..23.04 rows=184 width=24)
      Sort Key: region
      -> Seq Scan on t_oil
        (cost=0.00..15.66 rows=184 width=24)
```

```

Filter: (country = ANY
        ('{USA,Canada,Iran,Oman}'::text[]))
(9 rows)

```

In PostgreSQL, hash aggregates are only supported for normal `GROUP BY` clauses involving no grouping sets. In PostgreSQL 10.0, the planner already has more options than in PostgreSQL 9.6. Expect grouping sets to be faster in the new version.

Combining grouping sets with the FILTER clause

In real-world applications, grouping sets can often be combined with `FILTER` clauses. The idea behind the `FILTER` clause is to be able to run partial aggregates.

Here is an example:

```

test=# SELECT region,
      avg(production) AS all,
      avg(production) FILTER (WHERE year < 1990) AS old,
      avg(production) FILTER (WHERE year >= 1990) AS new
FROM t_oil
GROUP BY ROLLUP (region);

```

region	all	old	new
Middle East	1992.603686635	1747.325892857	2254.233333333
North America	4541.362318840	4471.653333333	4624.349206349
	2607.513986013	2430.685618729	2801.183150183

(3 rows)

The idea here is that not all columns will use the same data for aggregation. The `FILTER` clauses allow you to selectively pass data to those aggregates. In my example, the second aggregate will only consider data before 1990, while the third aggregate will take care of more recent data.



If it is possible to move conditions to a `WHERE` clause, it is always more desirable, as less data has to be fetched from the table. `FILTER` is only useful if the data left by the `WHERE` clause is not needed by each aggregate.

`FILTER` works for all kinds of aggregates and offers a simple way to pivot your data. Also, `FILTER` is faster than mimicking the same behavior with `CASE WHEN ... THEN NULL ... ELSE END`. You can find some real performance comparison here: <https://www.cybertec-postgresql.com/en/postgresql-9-4-aggregation-filters-they-do-pay-off/>.

Making use of ordered sets

Ordered sets are powerful features, but are not widely regarded as such and not widely known in the developer community. The idea is actually quite simple: data is grouped normally and then the data inside each group is ordered given a certain condition. The calculation is then performed on this sorted data.

A classic example would be the calculation of the median.



The median is the middle value. If you are, for example, earning the median income, the number of people earning less and more than you is identical. 50% of people do better and 50% of people do worse.

One way to get the median is to take sorted data and move 50% into the dataset. This is an example of what the `WITHIN GROUP` clause will ask PostgreSQL to do:

```
test=# SELECT region,
      percentile_disc(0.5) WITHIN GROUP (ORDER BY production)
FROM t_oil
GROUP BY 1;
 region          | percentile_disc
-----+-----
 Middle East     |          1082
 North America   |          3054
(2 rows)
```

The `percentile_disc` function will skip 50% of the group and return the desired value. Note that the median can significantly deviate from the average. In economics, the deviation between median and average income can even be used as an indicator for social equality or inequality. The higher the median compared to the average, the more the income inequality. To provide more flexibility, the ANSI standard does not just propose a median function. Instead, `percentile_disc` allows you to use any value between 0 and 1.

The beauty is that you can even use ordered sets along with grouping sets:

```
test=# SELECT region,
           percentile_disc(0.5) WITHIN GROUP (ORDER BY production)
FROM t_oil
GROUP BY ROLLUP (1);
 region          | percentile_disc
-----+-----
 Middle East     |             1082
 North America   |             3054
                  |             1696
(3 rows)
```

In this case, PostgreSQL will again inject additional lines into the result set.

As proposed by the ANSI SQL standard, PostgreSQL provides you with two `percentile_` functions. The `percentile_disc` function will return a value that is really contained by the dataset. The `percentile_cont` function will interpolate a value if no exact match is found. The following example shows how this works:

```
test=# SELECT percentile_disc(0.62) WITHIN GROUP (ORDER BY id),
           percentile_cont(0.62) WITHIN GROUP (ORDER BY id)
FROM generate_series(1, 5) AS id;
 percentile_disc | percentile_cont
-----+-----
 4               |           3.48
(1 row)
```

4 is a value that really exists—3.48 has been interpolated. The `percentile_` functions are not the only ones provided by PostgreSQL. To find the most frequent value within a group, the mode function is available. Before showing an example of how to use the mode function, I have compiled a query telling us a bit more about the content of the table:

```
test=# SELECT production, count(*)
FROM t_oil
WHERE country = 'Other Middle East'
GROUP BY production
ORDER BY 2 DESC
LIMIT 4;
 production | count
-----+-----
 50         |     5
 48         |     5
 52         |     5
 53         |     4
(4 rows)
```

Three different values occur exactly five times. Of course, the mode function can only give us one of them:

```
test=# SELECT country, mode() WITHIN GROUP (ORDER BY production)
      FROM t_oil
      WHERE country = 'Other Middle East'
      GROUP BY 1;
country          | mode
-----+-----
Other Middle East | 48
(1 row)
```

The most frequent value is returned but SQL won't tell us how often the number actually shows up. It might be that the number only shows up once.

Understanding hypothetical aggregates

Hypothetical aggregates are pretty similar to standard ordered sets. However, they help to answer a different kind of question: what would be the result if a value was there? As you can see, this is not about values inside the database but about the result if a certain value was actually there.

The only hypothetical function provided by PostgreSQL is `rank`:

```
test=# SELECT region,
              rank(9000) WITHIN GROUP
              (ORDER BY production DESC NULLS LAST)
      FROM t_oil
      GROUP BY ROLLUP (1);
 region      | rank
-----+-----
Middle East  | 21
North America | 27
              | 47
(3 rows)
```

It tells us: If somebody produced, 9000 barrels per day, it would be ranked the 27th best year in North America and 21st in the Middle East.



In my example, I used `NULLS LAST`. When data is sorted, nulls are usually at the end. However, if sort order is reversed, nulls should still be at the end of the list. `NULLS LAST` ensures exactly that.

Utilizing windowing functions and analytics

Now we have discussed ordered sets, it is time to take a look at windowing functions. Aggregates follow a fairly simple principle: take many rows and turn them into fewer, aggregated rows. A windowing function is different. It compares the current row with all rows in the group. The number of rows returned does not change.

Here is an example:

```
test=# SELECT avg(production) FROM t_oil;
      avg
-----
 2607.5139
(1 row)
```

```
test=# SELECT country, year, production,
      consumption, avg(production) OVER ()
      FROM t_oil
      LIMIT 4;
```

country	year	production	consumption	avg
USA	1965	9014	11522	2607.5139
USA	1966	9579	12100	2607.5139
USA	1967	10219	12567	2607.5139
USA	1968	10600	13405	2607.5139

(4 rows)

The average production in our dataset is around 2.6 million barrels per day. The goal of this query is to add this value as a column. It is now easy to compare the current row to the overall average.

Keep in mind that the `OVER` clause is essential. PostgreSQL is not able to process the query without it:

```
test=# SELECT country, year, production, consumption, avg(production) FROM
t_oil;
ERROR: column "t_oil.country" must appear in the GROUP BY clause or be
used in an aggregate function
LINE 1: SELECT country, year, production, consumption, avg(productio...
```

This actually makes sense because the average has to be defined precisely. The database engine cannot just guess at any value.



Other database engines can accept aggregate functions without an `OVER` or even a `GROUP BY` clause. However, from a logical point of view this is wrong, and on top of that, a violation of SQL.

Partitioning data

So far, the same result can also easily be achieved using a subselect. However, if you want more than just the overall average, subselects will turn your queries into nightmares. Suppose, you don't just want the overall average but the average of the country you are dealing with. A `PARTITION BY` clause is what you need:

```
test=# SELECT country, year, production, consumption,
      avg(production) OVER (PARTITION BY country)
```

```
FROM t_oil;
```

country	year	production	consumption	avg
Canada	1965	920	1108	2123.2173
Canada	2010	3332	2316	2123.2173
Canada	2009	3202	2190	2123.2173
...				
Iran	1966	2132	148	3631.6956
Iran	2010	4352	1874	3631.6956
Iran	2009	4249	2012	3631.6956
...				

The point here is that each country will be assigned to the average of the country. The `OVER` clause defines the window we are looking at. In this case, the window is the country the row belongs to. In other words, the query returns the rows compared to all rows in this country.



The `year` column is not sorted. The query does not contain an explicit sort order so it might be that data is returned in a random order. Remember, SQL does not promise sorted output unless you explicitly state what you want.

Basically, a `PARTITION BY` clause takes any expression. Usually, most people will use a column to partition the data. Here is an example:

```
test=# SELECT year, production,
      avg(production) OVER (PARTITION BY year < 1990)
FROM t_oil
WHERE country = 'Canada'
ORDER BY year;
```

year	production	avg
1965	920	1631.6000000000000000
1966	1012	1631.6000000000000000
...		
1990	1967	2708.4761904761904762
1991	1983	2708.4761904761904762
1992	2065	2708.4761904761904762
...		

The point is that data is split using the expression. `year < 1990` can return two values: `true` or `false`. Depending on the group a year is in, it will be assigned to the pre-1990 average or to the post-1990 average. PostgreSQL is really flexible here. Using functions to determine group membership is not uncommon in real-world applications.

Ordering data inside a window

A `PARTITION BY` clause is not the only possible thing you can put into an `OVER` clause. Sometimes it is necessary to sort data inside a window. `ORDER BY` will provide data to your aggregate functions in a certain way. Here is an example:

```
test=# SELECT country, year, production,
       min(production) OVER (PARTITION BY country ORDER BY year)
FROM   t_oil
WHERE  year BETWEEN 1978 AND 1983 AND country IN ('Iran', 'Oman');
country | year | production | min
-----+-----+-----+-----
Iran    | 1978 |      5302 | 5302
Iran    | 1979 |      3218 | 3218
Iran    | 1980 |      1479 | 1479
Iran    | 1981 |      1321 | 1321
Iran    | 1982 |      2397 | 1321
Iran    | 1983 |      2454 | 1321
Oman    | 1978 |       314 | 314
Oman    | 1979 |       295 | 295
Oman    | 1980 |       285 | 285
Oman    | 1981 |       330 | 285
...
```

Two countries (Iran and Oman) are chosen from our dataset for the period 1978 to 1983. Keep in mind, there was a revolution going on in Iran in 1979 so this had some impact on the production of oil. The data reflects that.

What the query does is to calculate the minimum production up to a certain point in our time series. At this point is a good way for SQL students to remember what an `ORDER BY` clause does inside an `OVER` clause. In this example, the `PARTITION BY` clause will create one group for each country and order data inside the group. The `min` function will loop over the sorted data and provide the required minimums.

If you are new to windowing functions, there is something you should be aware of: it really makes a difference whether you use an `ORDER BY` clause or not:

```
test=# SELECT country, year, production,
           min(production) OVER (),
           min(production) OVER (ORDER BY year)
FROM t_oil
WHERE year BETWEEN 1978 AND 1983
      AND country = 'Iran';
country | year | production | min | min
-----+-----+-----+----+----
Iran    | 1978 |      5302 | 1321 | 5302
Iran    | 1979 |      3218 | 1321 | 3218
Iran    | 1980 |      1479 | 1321 | 1479
Iran    | 1981 |       1321 | 1321 | 1321
Iran    | 1982 |       2397 | 1321 | 1321
Iran    | 1983 |       2454 | 1321 | 1321
(6 rows)
```

If the aggregate is used without `ORDER BY` it will automatically take the minimum of the entire dataset inside your windows. This doesn't happen if there is an `ORDER BY`. In this case, it will always be the minimum up to this point given the order you have defined.

Using sliding windows

So far the window we have used inside our query has been static. However, for calculations such as a moving average, this is not enough. A moving average needs a sliding window that moves along as data is processed.

Here is an example of how a moving average can be achieved:

```
test=# SELECT country, year, production,
      min(production) OVER (PARTITION BY country
      ORDER BY year ROWS BETWEEN 1 PRECEDING AND 1 FOLLOWING)
FROM t_oil
WHERE year BETWEEN 1978 AND 1983
      AND country IN ('Iran', 'Oman');
country | year | production | min
-----+-----+-----+-----
Iran    | 1978 |      5302 | 3218
Iran    | 1979 |      3218 | 1479
Iran    | 1980 |      1479 | 1321
Iran    | 1981 |      1321 | 1321
Iran    | 1982 |      2397 | 1321
Iran    | 1983 |      2454 | 2397
Oman    | 1978 |       314 | 295
Oman    | 1979 |       295 | 285
Oman    | 1980 |       285 | 285
Oman    | 1981 |       330 | 285
Oman    | 1982 |       338 | 330
Oman    | 1983 |       391 | 338
(12 rows)
```

The most important thing is that a moving window should be used with an `ORDER BY` clause. Otherwise, there will be major problems. PostgreSQL would actually accept the query but the result would be total crap. Remember, feeding data to a sliding window without ordering it first will simply lead to random data.

`ROWS BETWEEN 1 PRECEDING AND 1 FOLLOWING` defines the window. In my example, up to three rows will be in use: the current row, the one before, and the one after the current row. To illustrate how the sliding window works, check out the following example:

```
test=# SELECT *, array_agg(id)
      OVER (ORDER BY id ROWS BETWEEN 1 PRECEDING AND 1 FOLLOWING)
FROM generate_series(1, 5) AS id;
id | array_agg
---+-----
1 | {1,2}
2 | {1,2,3}
3 | {2,3,4}
4 | {3,4,5}
5 | {4,5}
(5 rows)
```

The `array_agg` function will turn a list of values into a PostgreSQL array. It will help to explain how the sliding window operates.

Actually, this trivial query has some very important aspects. What you see is that the first array contains only two values. There is no entry before 1 and therefore the array is not full. PostgreSQL does not add null entries because they would be ignored by aggregates anyway. The same happens at the end of the data.

However, sliding windows offer more. There are a couple of keywords that can be used to specify the sliding window:

```
test=# SELECT *,
        array_agg(id) OVER (ORDER BY id ROWS BETWEEN
                           UNBOUNDED PRECEDING AND 0 FOLLOWING)
FROM generate_series(1, 5) AS id;
 id | array_agg
-----+-----
  1 | {1}
  2 | {1,2}
  3 | {1,2,3}
  4 | {1,2,3,4}
  5 | {1,2,3,4,5}
(5 rows)
```

The `UNBOUNDED PRECEDING` keywords that everything before the current line will be in the window. The counterpart to `UNBOUNDED PRECEDING` is `UNBOUNDED FOLLOWING`:

```
test=# SELECT *,
        array_agg(id) OVER (ORDER BY id ROWS BETWEEN
                           2 FOLLOWING AND UNBOUNDED FOLLOWING)
FROM generate_series(1, 5) AS id;
 id | array_agg
-----+-----
  1 | {3,4,5}
  2 | {4,5}
  3 | {5}
  4 | 
  5 | 
(5 rows)
```

As you can see, it is also possible to use a window, that is in the future. PostgreSQL is very flexible here.

Abstracting window clauses

A windowing function allows us to add columns to the result set that have been calculated on the fly. However, what happens quite frequently is that many columns are based on the same window. Putting the same clauses into your queries over and over again is definitely not a good idea, because your queries will be hard to read and therefore hard to maintain.

The `WINDOW` clause allows developers to predefine a window and use it at various places in the query. Here is how it works:

```
SELECT country, year, production,
       min(production) OVER (w),
       max(production) OVER (w)
FROM t_oil
WHERE country = 'Canada'
      AND year BETWEEN 1980
      AND 1985
WINDOW w AS (ORDER BY year);
```

country	year	production	min	max
Canada	1980	1764	1764	1764
Canada	1981	1610	1610	1764
Canada	1982	1590	1590	1764
Canada	1983	1661	1590	1764
Canada	1984	1775	1590	1775
Canada	1985	1812	1590	1812

(6 rows)

The example shows that `min` and `max` will use the same clause.

Of course, it is possible to have more than just one `WINDOW` clause—PostgreSQL does not impose serious restrictions on users here.

Making use of onboard windowing functions

Having introduced you to the basic concepts, it is time to take a look at which windowing functions PostgreSQL will support out-of-the-box. You have already seen that windowing works with all standard aggregate functions. On top of those functions, PostgreSQL offers some additional functions that are exclusively for windowing and analytics.

In this section, some highly important functions will be explained and discussed.

The rank and dense_rank functions

The `rank()` and `dense_rank()` functions are, in my judgment, the most prominent functions around. The `rank()` function returns the number of the current row within its window. Counting starts at one.

Here is an example:

```
test=# SELECT year, production,
           rank() OVER (ORDER BY production)
FROM t_oil
WHERE country = 'Other Middle East'
ORDER BY rank
LIMIT 7;
 year | production | rank
-----+-----+-----
 2001 |      47    |    1
 2004 |      48    |    2
 2002 |      48    |    2
 1999 |      48    |    2
 2000 |      48    |    2
 2003 |      48    |    2
 1998 |      49    |    7
(7 rows)
```

The `rank` column will number those tuples in your dataset. Note that many rows in my sample are equal. Therefore, rank will jump from 2 to 7 directly, because many production values are identical. If you want to avoid that, the `dense_rank()` function is the way to go:

```
test=# SELECT year, production,
           dense_rank() OVER (ORDER BY production)
FROM t_oil
WHERE country = 'Other Middle East'
ORDER BY dense_rank
LIMIT 7;
 year | production | dense_rank
-----+-----+-----
 2001 |      47    |          1
 2004 |      48    |          2
    ...
 2003 |      48    |          2
 1998 |      49    |          3
(7 rows)
```

PostgreSQL will pack the numbers more tightly. There will be no more gaps.

The `ntile()` function

Some applications require data to be split into ideally equal groups. The `ntile()` function will do exactly that for you.

The following example shows how data can be split into groups:

```
test=# SELECT year, production, ntile(4)
      OVER (ORDER BY production)
      FROM t_oil
      WHERE country = 'Iraq'
      AND year BETWEEN 2000 AND 2006;
```

year	production	ntile
2003	1344	1
2005	1833	1
2006	1999	2
2004	2030	2
2002	2116	3
2001	2522	3
2000	2613	4

(7 rows)

The query splits data into four groups. The trouble is that only seven rows are selected, which makes it impossible to create four, even groups. As you can see, PostgreSQL will fill up the first three groups and make the last one a bit smaller. You can rely on the fact that the groups at the end will always tend to be a bit smaller than the rest.



In this example, only a handful of rows are used. In real-world applications, millions of rows will be involved and therefore it is no problem if groups are not perfectly equal.

The `ntile()` function is usually not used alone. Sure, it helps to assign a group ID to a row. However, in real-world applications, people want to perform calculations on top of those groups. Suppose you want to create a `quartile` distribution for your data. Here is how it works:

```
test=# SELECT grp, min(production), max(production), count(*)
      FROM (
        SELECT year, production, ntile(4)
        OVER (ORDER BY production) AS grp
        FROM t_oil
        WHERE country = 'Iraq'
      ) AS x
```

```
GROUP BY ROLLUP (1);
  grp | min  | max  | count
-----+-----+-----+-----
    1 | 285  | 1228 |    12
    2 | 1313 | 1977 |    12
    3 | 1999 | 2422 |    11
    4 | 2428 | 3489 |    11
      | 285  | 3489 |    46
(5 rows)
```

The most important thing is that the calculation cannot be done in one step. When doing SQL training courses here at Cybertec (<https://www.cybertec-postgresql.com>), I try to explain to students that whenever you don't know how to do it all at once, consider using a subselect. In analytics, this is usually a good idea. In this example, the first thing done (in the subselect) is the attachment of a group label to each group. Then those groups are taken and processed in the main query.

The result is already something that could be used in a real-world application (maybe as a legend located next to a graph, and so on).

The lead() and lag() functions

While the `ntile()` function is essential for splitting a dataset into groups, the `lead()` and `lag()` functions are here to move lines within the result set. A typical use case is to calculate the difference in production from one year to the next:

```
test=# SELECT year, production,
      lag(production, 1) OVER (ORDER BY year)
FROM   t_oil
WHERE  country = 'Mexico'
LIMIT 5;
 year | production | lag
-----+-----+-----
 1965 |          | 362
 1966 |          | 370 | 362
 1967 |          | 411 | 370
 1968 |          | 439 | 411
 1969 |          | 461 | 439
(5 rows)
```

Before actually calculating the change in production, it makes sense to sit back and see what the `lag()` function actually does. You can see that the column is moved by one row. The data moved as defined in the `ORDER BY` clause. In my example, it means down. An `ORDER BY DESC` clause would of course have moved data up.

From this point on, the query is easy:

```
test=# SELECT year, production,
           production - lag(production, 1) OVER (ORDER BY year)
FROM   t_oil
WHERE  country = 'Mexico'
LIMIT 3;
```

year	production	?column?
1965	362	
1966	370	8
1967	411	41

(3 rows)

All you have to do is to calculate the difference as you would with any other column. Note that the `lag()` function has two parameters. The first one indicates which column is to be displayed. The second column tells PostgreSQL how many rows you want to move. Putting in 7 therefore means that everything is off by seven rows.

Note that the first value is `Null` (and all other lagged rows without a preceding value).

The `lead()` function is the counterpart of the `lag()` function; it will move rows up instead of down:

```
test=# SELECT year, production,
           production - lead(production, 1) OVER (ORDER BY year)
FROM   t_oil
WHERE  country = 'Mexico'
LIMIT 3;
```

year	production	?column?
1965	362	-8
1966	370	-41
1967	411	-28

(3 rows)

Basically, PostgreSQL will also accept negative values for lead and lag columns. The `lag(production, -1)` is therefore a replacement for `lead(production, 1)`. However, it is definitely cleaner to use the right function to move data in the direction you want.

So far you have seen how to lag a single column. In most applications, lagging a single value will be the standard case used by most developers. The point is, PostgreSQL can do a lot more than that. It is possible to lag entire lines:

```
test=# \x
Expanded display is on.
test=# SELECT year, production,
        lag(t_oil, 1) OVER (ORDER BY year)
FROM   t_oil
WHERE  country = 'USA'
LIMIT 3;

-[ RECORD 1 ]-----
year          | 1965
production    | 9014
lag           |
-[ RECORD 2 ]-----
year          | 1966
production    | 9579
lag           | ("North America",USA,1965,9014,11522)
-[ RECORD 3 ]-----
year          | 1967
production    | 10219
lag           | ("North America",USA,1966,9579,12100)
```

The beauty here is that more than just a single value can be compared to the previous row. The trouble, though, is that PostgreSQL will return the entire row as a composite type and therefore it is hard to work with. To dissect a composite type, you can use parentheses and a star:

```
test=# SELECT year, production,
        (lag(t_oil, 1) OVER (ORDER BY year)).*
FROM   t_oil
WHERE  country = 'USA'
LIMIT 3;

 year | prod | region      | country | year | prod | consumption
-----+-----+-----+-----+-----+-----+-----
 1965 | 9014 |              |         |      |      |
 1966 | 9579 | N. America   | USA     | 1965 | 9014 | 11522
 1967 | 10219 | N. America   | USA     | 1966 | 9579 | 12100
(3 rows)
```

Why is that useful? Lagging an entire row will make it possible to see if data has been inserted more than once. It is pretty simple to detect duplicate rows (or close-to-duplicate rows) in your time series.

Check out the following example:

```
test=# SELECT *
FROM (SELECT t_oil, lag(t_oil) OVER (ORDER BY year)
      FROM t_oil
      WHERE country = 'USA'
      ) AS x
WHERE t_oil = lag;
 t_oil | lag
-----+-----
(0 rows)
```

Of course, the sample data does not contain duplicates. However, in real-world examples, duplicates can easily happen, and it is easy to detect them even if there is no primary key.



`t_oil` row is really the entire row. The lag returned by the subselect is also a complete row. In PostgreSQL, composite types can be compared directly in case the fields are identical. PostgreSQL will simply compare one field after the other.

The `first_value()`, `nth_value()`, and `last_value()` functions

Sometimes, it is necessary to calculate data based on the first value of a data window.

Unsurprisingly, the function to do that is `first_value()`:

```
test=# SELECT year, production,
      first_value(production) OVER (ORDER BY year)
FROM t_oil
WHERE country = 'Canada'
LIMIT 4;
 year | production | first_value
-----+-----+-----
 1965 |         920 |         920
 1966 |        1012 |         920
 1967 |        1106 |         920
 1968 |        1194 |         920
(4 rows)
```

Again, a sort order is needed to tell the system where the first value actually is. PostgreSQL will then put the same value into the last column. If you want to find the last value in the window, simply use the `last_value()` function instead of the `first_value()` function.

If you are not interested in the first or the last value but are looking for something in the middle, PostgreSQL provides the `nth_value()` function:

```
test=# SELECT year, production,
      nth_value(production, 3) OVER (ORDER BY year)
FROM   t_oil
WHERE  country = 'Canada';
```

year	production	nth_value
1965	920	
1966	1012	
1967	1106	1106
1968	1194	1106
...		

In this, the third value will be put into the last column. However, note that the first two rows are empty. The trouble is that when PostgreSQL starts going through the data, the third value is not known yet. Therefore, null is added. The question now is: how can we make the time series more complete and replace those two null values with the data to come?

Here is one way to do it:

```
test=# SELECT *, min(nth_value) OVER ()
FROM   (
      SELECT year, production,
            nth_value(production, 3) OVER (ORDER BY year)
      FROM   t_oil
      WHERE  country = 'Canada'
    ) AS x
LIMIT  4;
```

year	production	nth_value	min
1965	920		1106
1966	1012		1106
1967	1106	1106	1106
1968	1194	1106	1106

(4 rows)

The subselect will create the incomplete time series. The `SELECT` clause on top of that will complete the data. The clue here is that completing the data might be more complex, and therefore a subselect might create a couple of opportunities to add more complex logic than just doing it in one step.

The `row_number()` function

The last function discussed in this section is the `row_number()` function, which can simply be used to return a virtual ID. Sound simple? Here it is:

```
test=# SELECT country, production,
        row_number() OVER (ORDER BY production)
FROM t_oil
LIMIT 3;
 country | production | row_number
-----+-----+-----
 Yemen   |         10 |          1
 Syria   |         21 |          2
 Yemen   |         26 |          3
(3 rows)
```

The `row_number()` function simply assigns a number to the row. There are definitely no duplicates.

The interesting point here is that this can be done even without an order (in case it is not relevant to you):

```
test=# SELECT country, production,
        row_number() OVER()
FROM t_oil
LIMIT 3;
 country | production | row_number
-----+-----+-----
 USA     |        9014 |          1
 USA     |        9579 |          2
 USA     |       10219 |          3
(3 rows)
```

Writing your own aggregates

In this book, you can see most of the on-board functions provided by PostgreSQL. However, what SQL provides might not be enough for you. The good news is that it is possible to add your own aggregates to the database engine. In this section, you will learn how that can be done.

Creating simple aggregates

For the purpose of this example, the goal is to solve a very simple problem: if a customer takes a taxi, they usually have to pay for getting in the taxi—for example, €2.50. Then, let us assume that for each kilometer, the customer has to pay €2.20. The question now is: what is the total price of a trip?

Of course, this example is simple enough to solve without a custom aggregate, however, let's see how it works. First, some test data is created:

```
test=# CREATE TABLE t_taxi (trip_id int, km numeric);
CREATE TABLE
test=# INSERT INTO t_taxi
VALUES (1, 4.0), (1, 3.2), (1, 4.5), (2, 1.9), (2, 4.5);
INSERT 0 5
```

To create aggregates, PostgreSQL offers the `CREATE AGGREGATE` command. The syntax of this command has become so powerful and long over time that it does not make sense anymore to include the output of here in this book. Instead, I recommend going to the PostgreSQL documentation, which can be found at

<https://www.postgresql.org/docs/devel/static/sql-createaggregate.html>.

The first thing needed when writing an aggregate is a function, which is called for every line. It will take an intermediate value and data taken from the line processed. Here is an example:

```
test=# CREATE FUNCTION taxi_per_line (numeric, numeric)
RETURNS numeric AS
$$
BEGIN
    RAISE NOTICE 'intermediate: %, per row:  %', $1, $2;
    RETURN $1 + $2*2.2;
END;
$$
LANGUAGE 'plpgsql';
CREATE FUNCTION
```

Now, it is already possible to create a simple aggregate:

```
test=# CREATE AGGREGATE taxi_price (numeric)
(
    INITCOND = 2.5,
    SFUNC = taxi_per_line,
    STYPE = numeric
);

CREATE AGGREGATE
```

As stated, every trip starts at €2.50 for getting in the taxi, which is defined by `INITCOND` (the `init` condition). It represents the starting value for each group. Then a function is called for each line in the group. In my example, this function is `taxi_per_line` and has already been defined. As you can see, it needs two parameters. The first parameter is an intermediate value. Those additional parameters (can be many) are the parameters passed to the function by the user.

The following statement shows what data is passed when and how:

```
test=# SELECT trip_id, taxi_price(km) FROM t_taxi GROUP BY 1;
NOTICE: intermediate: 2.5, per row: 4.0
NOTICE: intermediate: 11.30, per row: 3.2
NOTICE: intermediate: 18.34, per row: 4.5
NOTICE: intermediate: 2.5, per row: 1.9
NOTICE: intermediate: 6.68, per row: 4.5
trip_id | taxi_price
-----+-----
      1 |      28.24
      2 |      16.58
(2 rows)
```

The system starts with trip one and €2.50 (the `init` condition). Then 4 kilometers are added. Overall, the price is now $2.50 + 4 \times 2.2$. Then, the next line is added, which will add 3.2×2.2 , and so on. The first trip therefore costs €28.24.

Then the next trip starts. Again, there is a fresh `init` condition and PostgreSQL will call one function per line.

In PostgreSQL, an aggregate can automatically be used as a windowing function too. No additional steps are needed—you can use the aggregate directly:

```
test=# SELECT *, taxi_price(km) OVER (PARTITION BY trip_id ORDER BY km)
      FROM t_taxi;

NOTICE: intermediate: 2.5, per row: 3.2
NOTICE: intermediate: 9.54, per row: 4.0
NOTICE: intermediate: 18.34, per row: 4.5
NOTICE: intermediate: 2.5, per row: 1.9
NOTICE: intermediate: 6.68, per row: 4.5
 trip_id | km | taxi_price
-----+---+-----
      1 | 3.2 |      9.54
      1 | 4.0 |     18.34
      1 | 4.5 |     28.24
      2 | 1.9 |      6.68
      2 | 4.5 |     16.58

(5 rows)
```

What the query does is to give us the price up to a given point in the trip.

The aggregate we have defined will call one function per line. However, how would users be able to calculate an average? Without adding a `FINALFUNC` function, calculations like that are not possible. To demonstrate how `FINALFUNC` works, we must extend our example. Suppose the customer wants to give the taxi driver a 10% tip as soon as they leave the taxi. That 10% has to be added at the end, as soon as the total price is known. That is the point at which `FINALFUNC` kicks in. Here is how it works:

```
test=# DROP AGGREGATE taxi_price(numeric);
DROP AGGREGATE
```

First of all, the old aggregate is dropped. Then, `FINALFUNC` is defined. It will get the intermediate result as a parameter and do its magic:

```
test=# CREATE FUNCTION taxi_final (numeric)
      RETURNS numeric AS
$$
      SELECT $1 * 1.1;
$$
LANGUAGE sql IMMUTABLE;

CREATE FUNCTION
```

The calculation is pretty simple in this case—as stated previously, 10% is added to the final sum.

Once the function has been deployed, it is already possible to recreate the aggregate:

```
test=# CREATE AGGREGATE taxi_price (numeric)
(
    INITCOND = 2.5,
    SFUNC = taxi_per_line,
    STYPE = numeric,
    FINALFUNC = taxi_final
);
CREATE AGGREGATE
```

And finally, the price will simply be a bit higher than before:

```
test=# SELECT trip_id, taxi_price(km) FROM t_taxi GROUP BY 1;
NOTICE:  intermediate: 2.5, per row: 4.0
...
  trip_id | taxi_price
-----+-----
         1 |    31.064
         2 |    18.238
(2 rows)
```

PostgreSQL takes care of all the grouping and so on automatically.

For simple calculations, simple datatypes can be used for the intermediate result. However, not all operations can be done by just passing simple numbers and text around. Fortunately, PostgreSQL allows the use of composite data types, which can be used as intermediate results.

Imagine you want to calculate an average of some data (maybe a time series). An intermediate result might look as follows:

```
test=# CREATE TYPE my_intermediate AS (c int4, s numeric);
CREATE TYPE
```

Feel free to compose any arbitrary type that serves your purpose. Just pass it as the first parameter and add data as additional parameters as needed.

Adding support for parallel queries

What you have just seen is a simple aggregate, which has no support for parallel queries and all that. To solve those challenges, the next couple of examples are all about improvements and speedups.

When creating an aggregate, you can optionally define the following things:

```
[ , PARALLEL = { SAFE | RESTRICTED | UNSAFE } ]
```

By default, an aggregate does not support parallel queries. For performance reasons it does make sense, however, to explicitly state what the aggregate is capable of:

- **UNSAFE**: In this mode, no parallel queries are allowed
- **RESTRICTED**: In this mode, the aggregate can be executed in parallel mode, but the execution is restricted to the parallel group leader
- **SAFE**: In this mode, it provides full support for parallel queries

If you mark a function as **SAFE**, you have to keep in mind that the function must not have side effects. An execution order must not have an impact on the result of the query. Only then, should PostgreSQL be allowed to execute operations in parallel. Examples of functions without side effects would be *sin(x)* and *length(s)*. The **IMMUTABLE** functions are good candidate for this, since they're guaranteed to return the same result given the same inputs. The **STABLE** function can work if certain restrictions apply.

Improving efficiency

The aggregates defined so far can already achieve quite a lot. However, if you are using sliding windows, the number of function calls will simply explode. Here is what happens:

```
test=# SELECT taxi_price(x::numeric)
        OVER (ROWS BETWEEN 0 FOLLOWING AND 3 FOLLOWING)
FROM generate_series(1, 5) AS x;
NOTICE: intermediate: 2.5, per row: 1
NOTICE: intermediate: 4.7, per row: 2
NOTICE: intermediate: 9.1, per row: 3
NOTICE: intermediate: 15.7, per row: 4
NOTICE: intermediate: 2.5, per row: 2
NOTICE: intermediate: 6.9, per row: 3
NOTICE: intermediate: 13.5, per row: 4
NOTICE: intermediate: 22.3, per row: 5
...
```

For every line, PostgreSQL will process the full window. If the sliding window is large, efficiency will go down the drain. To fix that, our aggregates can be extended. Before that the old aggregate can be dropped:

```
DROP AGGREGATE taxi_price(numeric);
```

Basically, two functions are needed: the `msfunc` function will add the next row in the window to the intermediate result:

```
CREATE FUNCTION taxi_msfunc(numeric, numeric)
  RETURNS numeric AS
$$
  BEGIN
    RAISE NOTICE 'taxi_msfunc called with % and %', $1, $2;
    RETURN $1 + $2;
  END;
$$ LANGUAGE 'plpgsql' STRICT;
```

The `minvfunc` function will remove the value falling out of the window from the intermediate result:

```
CREATE FUNCTION taxi_minvfunc(numeric, numeric) RETURNS numeric AS
$$
  BEGIN
    RAISE NOTICE 'taxi_minvfunc called with % and %', $1, $2;
    RETURN $1 - $2;
  END;
$$
LANGUAGE 'plpgsql' STRICT;
```

In my example, all we do is add and subtract. In a more sophisticated example the calculation can be arbitrarily complex.

The next statement shows how the aggregate can be recreated:

```
CREATE AGGREGATE taxi_price (numeric)
(
  INITCOND = 0,
  STYPE = numeric,
  SFUNC = taxi_per_line,
  MSFUNC = taxi_msfunc,
  MINVFUNC = taxi_minvfunc,
  MSTYPE = numeric
);
```

Let us run the same query again now:

```
test# SELECT taxi_price(x::numeric)
      OVER (ROWS BETWEEN 0 FOLLOWING AND 3 FOLLOWING)
FROM    generate_series(1, 5) AS x;
NOTICE: taxi_msfunc called with 1 and 2
NOTICE: taxi_msfunc called with 3 and 3
NOTICE: taxi_msfunc called with 6 and 4
NOTICE: taxi_minfunc called with 10 and 1
NOTICE: taxi_msfunc called with 9 and 5
NOTICE: taxi_minfunc called with 14 and 2
NOTICE: taxi_minfunc called with 12 and 3
NOTICE: taxi_minfunc called with 9 and 4
```

The number of function calls has decreased dramatically. Only a fixed handful of calls per row have to be performed. There is no longer any need to calculate the same frame all over again.

Writing hypothetical aggregates

Writing aggregates is not hard and can be highly beneficial for performing more complex operations. In this section, the plan is to write a hypothetical aggregate, which has already been discussed in this chapter.

Implementing hypothetical aggregates is not too different from writing normal aggregates. The really hard part is to figure out when to actually use one. To make this section as easy to understand as possible, I have decided to include a trivial example: given a specific order, what would the result be if we added `abc` to the end of the string?

Here is how it works:

```
CREATE AGGREGATE name ( [ [ argmode ] [ argname ] arg_data_type [ , ... ]
]
ORDER BY [ argmode ] [ argname ] arg_data_type
[ , ... ])
(
    SFUNC = sfunc,
    STYPE = state_data_type
    [ , SSPACE = state_data_size ] [ , FINALFUNC = ffunc ]
    [ , FINALFUNC_EXTRA ]
    [ , INITCOND = initial_condition ]
    [ , PARALLEL = { SAFE | RESTRICTED | UNSAFE } ] [ , HYPOTHETICAL ]
)
```

Two functions will be needed. The `sfunc` function will be called for every line:

```
CREATE FUNCTION hypo_sfunc(text, text)
  RETURNS text AS
$$
  BEGIN
    RAISE NOTICE 'hypo_sfunc called with % and %', $1, $2;
    RETURN $1 || $2;
  END;
$$ LANGUAGE 'plpgsql';
```

Two parameters will be passed to the procedure. The logic is the same as before. Just as we did earlier, a final function call can be defined:

```
CREATE FUNCTION hypo_final(text, text, text)
  RETURNS text AS
$$
  BEGIN
    RAISE NOTICE 'hypo_final called with %, %, and %',
      $1, $2, $3;
    RETURN $1 || $2;
  END;
$$ LANGUAGE 'plpgsql';
```

Once those functions are in place the hypothetical aggregate can already be created:

```
CREATE AGGREGATE whatif(text ORDER BY text)
(
  INITCOND = 'START',
  STYPE = text,
  SFUNC = hypo_sfunc,
  FINALFUNC = hypo_final,
  FINALFUNC_EXTRA = true,
  HYPOTHETICAL
);
```

Note that the aggregate has been marked as hypothetical so that PostgreSQL will know what kind of aggregate it actually is.

After the aggregate has been created, it is possible to run it:

```
test=# SELECT whatif('abc'::text) WITHIN GROUP (ORDER BY id::text)
FROM      generate_series(1, 3) AS id;
NOTICE:  hypo_sfunc called with  START  and 1
NOTICE:  hypo_sfunc called with  START1 and 2
NOTICE:  hypo_sfunc called with  START12 and 3
NOTICE:  hypo_final called with  START123, abc,  and <NULL>
whatif
-----
START123abc
(1 row)
```

The key to understanding all those aggregates is really to fully see when which kind of function is called and how the overall machinery works.

Summary

In this chapter, you learned about the advanced features provided by SQL. On top of simple aggregates, PostgreSQL provides ordered sets, grouping sets, windowing functions and recursions, as well as an interface to create custom aggregates. The advantage of running aggregations in the database is that code is easy to write, and a database engine will usually have an edge when it comes to efficiency.

In Chapter 5, *Log Files and System Statistics*, we will turn our attention to more administrative tasks, such as handling log files, understanding system statistics, and implementing monitoring.

5

Log Files and System Statistics

In *Chapter 4, Handling Advanced SQL*, you learned a lot about advanced SQL and ways to see SQL in a different light. However, database work does not only consist of hacking up fancy SQL. Sometimes, it is also about keeping things running in a professional manner. To do that, it is highly important to keep an eye on system statistics, log files, and so on. Monitoring is the key to running databases professionally.

In this chapter, you will learn about the following topics:

- Gathering runtime statistics
- Creating log files
- Gathering important information
- Making sense of database statistics

At the end of this chapter, you will be able to configure PostgreSQL's logging infrastructure properly and take care of log files in the most professional way possible.

Gathering runtime statistics

The first thing you really have to learn is to use and understand what PostgreSQL's onboard statistics have got to offer. In my personal opinion, there is no way to improve performance and reliability without first collecting the data to make prudent decisions.

This section will guide you through PostgreSQL's runtime statistics and explain in detail how you can extract more data from your database setups.

Working with PostgreSQL system views

PostgreSQL offers a large set of system views that allow administrators and developers alike to take a deep look into what is really going on in their system. The trouble is that many people actually collect all this data but cannot make real sense out of it. The general rule is this: there is no point in drawing a graph for something you don't understand anyway. The goal in this section, therefore, is to shed some light on what PostgreSQL has to offer to hopefully make it easier for people to fully take advantage of what is there to serve for them to use.

Checking live traffic

Whenever I inspect a system, there is a system view I like to inspect first before digging deeper. I am, of course, talking about `pg_stat_activity`. The idea behind the view is to give you a chance to figure out what is going on right now.

Here is how it works:

```
test=# \d pg_stat_activity
View "pg_catalog.pg_stat_activity"
  Column          |          Type          | ...
-----+-----+-----
 datid            | oid                    | ...
 datname          | name                   | ...
 pid              | integer                | ...
 usesysid         | oid                    | ...
 username         | name                   | ...
 application_name | text                   | ...
 client_addr      | inet                   | ...
 client_hostname  | text                   | ...
 client_port      | integer                | ...
 backend_start    | timestamp with time zone | ...
 xact_start       | timestamp with time zone | ...
 query_start      | timestamp with time zone | ...
 state_change     | timestamp with time zone | ...
 wait_event_type  | text                   | ...
 wait_event       | text                   | ...
 state            | text                   | ...
 backend_xid      | xid                    | ...
 backend_xmin     | xid                    | ...
 query            | text                   | ...
 backend_type     | text                   | ...
```

`pg_stat_activity` will provide you with one line per active connection. You will see the internal object ID of the database (`datid`), the name of the database somebody is connected to, and the process ID serving this connection (`pid`). On top of that, PostgreSQL will tell you who is connected (`username`; note the missing `r`) and that user's internal object ID (`usesysid`).

Then there is a field called `application_name`, which is worth commenting on a bit more extensively. In general, `application_name` can be set freely by the end user:

```
test=# SET application_name TO 'www.cybertec-postgresql.com';
SET
test=# SHOW application_name;
      application_name
-----
www.cybertec-postgresql.com
(1 row)
```

The point is this: assume thousands of connections are coming from a single IP. Can you, as the administrator, tell what a specific connection is really doing right now? You might not know all the SQL by heart. If the client is kind enough to set an `application_name` parameter, it is a lot easier to see what the purpose of a connection really is. In my example, I have set the name to the domain the connection belongs to. This makes it easy to find similar connections, which might cause similar problems.

The next three columns (`client_`) will tell you where a connection comes from. PostgreSQL will show IP addresses and (if it has been configured) even hostnames.

`backend_start` will tell you when a certain connection has started. `xact_start` indicates when a transaction has started. Then there are `query_start` and `state_change`. Back in the dark old days, PostgreSQL would only show active queries. During a time when queries took a lot longer than today, this made sense, of course. On modern hardware, OLTP queries might only consume a fraction of a millisecond, and therefore it is hard to catch such queries doing potential harm. The solution was to either show the active query or the previous query executed by the connection you are looking at.

Here is what you might see:

```
test=# SELECT pid, query_start, state_change, state, query
FROM pg_stat_activity;
...
-[ RECORD 2 ]+-----
pid          | 28001
query_start  | 2016-11-05 10:03:57.575593+01 state_change | 2016-11-05
10:03:57.575595+01
```

```
state          | active
query          | SELECT pg_sleep(10000000);
```

In this case, you can see that `pg_sleep` is being executed in a second connection. As soon as this query is terminated, the output will change:

```
-[ RECORD 2 ]+-----
pid          | 28001
query_start  | 2016-11-05 10:03:57.575593+01
state_change | 2016-11-05 10:05:10.388522+01
state        | idle
query        | SELECT pg_sleep(10000000);
```

The query is now marked as `idle`. The difference between `state_change` and `query_start` is the time the query needed to execute.

`pg_stat_activity` will therefore give you a great overview of what is going on in your system right now. The new `state_change` field makes it a lot more likely to spot expensive queries.

The question now is this: once you have found bad queries, how can you actually get rid of them? PostgreSQL provides two functions to take care of these things:

`pg_cancel_backend` and `pg_terminate_backend`. The `pg_cancel_backend` function will terminate the query but will leave the connection in place.

The `pg_terminate_backend` function is a bit more radical and will kill the entire database connection along with the query.

If you want to disconnect all other users but yourself, here is how you can do that:

```
test=# SELECT pg_terminate_backend(pid)
      FROM pg_stat_activity
      WHERE pid <> pg_backend_pid()
      AND backend_type = 'client backend'
      pg_terminate_backend
-----
t
t
(2 row)
```

If you happen to be kicked out, the following message will be displayed:

```
test=# SELECT pg_sleep(10000000);
FATAL: terminating connection due to administrator command server closed
the connection unexpectedly
```

This probably means the server terminated abnormally before or while processing the request. The connection to the server was lost. Attempting reset: Succeeded.



Only `psql` will try to reconnect. This is not `true` for most other clients, especially not for client libraries.

Inspecting databases

Once you have inspected active database connections, you can dig deeper and inspect database-level statistics. `pg_stat_database` will return one line per database inside your PostgreSQL instance.

This is what you can find there:

```
test=# \d pg_stat_database
          View "pg_catalog.pg_stat_database"
Column          |          Type          | Collation | Nullable | Default
-----+-----+-----+-----+-----
-
 datid          | oid                   |           |          |
 datname        | name                 |           |          |
 numbackends    | integer              |           |          |
 xact_commit    | bigint               |           |          |
 xact_rollback  | bigint               |           |          |
 blks_read      | bigint               |           |          |
 blks_hit       | bigint               |           |          |
 tup_returned   | bigint               |           |          |
 tup_fetched    | bigint               |           |          |
 tup_inserted   | bigint               |           |          |
 tup_updated    | bigint               |           |          |
 tup_deleted    | bigint               |           |          |
 conflicts      | bigint               |           |          |
 temp_files     | bigint               |           |          |
 temp_bytes     | bigint               |           |          |
 deadlocks      | bigint               |           |          |
 blk_read_time  | double precision     |           |          |
 blk_write_time | double precision     |           |          |
 stats_reset    | timestamp with time zone |           |          |
```

Next to the database ID and the database name, there is a column called `numbackends` that shows the number of database connections that are currently open.

Then there are `xact_commit` and `xact_rollback`. These two columns indicate whether your application tends to commit or roll back. `blks_hit` and `blks_read` will tell you about cache hits and cache misses. When inspecting these two columns, keep in mind that we are mostly talking about shared buffer hits and shared buffer misses. There is no reasonable way, on the database level, to distinguish filesystem cache hits and real disk hits. At Cybertec (<https://www.cybertec-postgresql.com>), we like to correlate disk wait with cache misses in `pg_stat_database` to get an idea of what really goes on in the system.

The `tup_` columns will tell you whether there is a lot of reading or a lot of writing going on in your system.

Then we have `temp_files` and `temp_bytes`. These two columns are of incredible importance because they will tell you whether your database has to write temporary files to disk, which will inevitably slow down operations. What can be the reasons for high temporary file usage? The major reasons are as follows:

- **Poor settings:** If your `work_mem` settings are too low, there is no way to do anything in RAM, and therefore PostgreSQL will go to disk.
- **Stupid operations:** It happens quite frequently that people torture their system with fairly expensive, pointless queries. If you see many temporary files on an OLTP system, consider checking for expensive queries.
- **Indexing and other administrative tasks:** Once in a while, indexes might be created or people might run DDLs. These operations can lead to temporary file I/O but are not necessarily considered a problem (in many cases).

In short, temporary files can happen even if your system is perfectly fine. However, it definitely makes sense to keep an eye on them and ensure that temp files are not needed frequently.

Finally, there are two more important fields: `blk_read_time` and `blk_write_time`. By default, these two fields are empty and no data is collected. The idea behind these fields is to give you a way to see how much time was spent on I/O. The reason these fields are empty is that `track_io_timing` is off by default. This is for good reasons. Imagine you want to check how long it takes to read 1 million blocks. To do that, you have to call the time function in your C library twice, which leads to 2 million additional function calls just to read 8 GB of data. It really depends on the speed of your system as to whether this will lead to a lot of overhead or not.

Fortunately, there is a tool that helps you to determine how expensive the timing is:

```
[hs@zenbook ~]$ pg_test_timing
Testing timing overhead for 3 seconds.
Per loop time including overhead: 23.16 nsec
Histogram of timing durations:
```

< usec	%	of total	count
1		97.70300	126549189
2		2.29506	2972668
4		0.00024	317
8		0.00008	101
16		0.00160	2072
32		0.00000	5
64		0.00000	6
128		0.00000	4
256		0.00000	0
512		0.00000	0
1024		0.00000	4
2048		0.00000	2

In my case, the overhead of turning `track_io_timing` on for a session or in the `postgresql.conf` file is around 23 nanoseconds, which is fine. Professional high-end servers can provide you with numbers as low as 14 nanoseconds, while really bad virtualization can return values up to 1,400 nanoseconds or even 1,900 nanoseconds. If you are using some cloud service, you can expect around 100 - 120 nanoseconds (in most cases). In case you are confronted with four digit values, measuring the I/O timing might surely lead to real measurable overhead, which will slow down your system. The general rule is this: on real hardware, timing is not an issue; on virtual systems, check it out before you turn it on.



It is also possible to turn things on selectively by using `ALTER DATABASE`, `ALTER USER`, or the like.

Inspecting tables

Once you have gained an overview of what is going on in your databases, it might be a good idea to dig deeper and see what is going on in individual tables. Two system views are here to help you: `pg_stat_user_tables` and `pg_statio_user_tables`. Here is the first one:

```
test=# \d pg_stat_user_tables
View "pg_catalog.pg_stat_user_tables"
-----+-----+-----
Column | Type | ...
-----+-----+-----
reloid | oid | ...
schemaname | name | ...
relname | name | ...
seq_scan | bigint | ...
seq_tup_read | bigint | ...
idx_scan | bigint | ...
idx_tup_fetch | bigint | ...
n_tup_ins | bigint | ...
n_tup_upd | bigint | ...
n_tup_del | bigint | ...
n_tup_hot_upd | bigint | ...
n_live_tup | bigint | ...
n_dead_tup | bigint | ...
n_mod_since_analyze | bigint | ...
last_vacuum | timestamp with time zone | ...
last_autovacuum | timestamp with time zone | ...
last_analyze | timestamp with time zone | ...
last_autoanalyze | timestamp with time zone | ...
vacuum_count | bigint | ...
autovacuum_count | bigint | ...
analyze_count | bigint | ...
autoanalyze_count | bigint | ...
```

By my judgment, `pg_stat_user_tables` is one of the most important but also one of the most misunderstood or even ignored system views. I have a feeling that many people read it but fail to extract the full potential of what can really be seen here. When used properly, `pg_stat_user_tables` can, in some cases, be nothing short of a revelation.

Before we dig into the interpretation of data, it is important to understand which fields are actually there. First of all, there is one entry for each table, which will show us the number of sequential scans that happened on the table (`seq_scan`). Then we have `seq_tup_read`, which tells us how many tuples the system has to read during those sequential scans.



Remember the `seq_tup_read` column; it contains vital information, which can help to find performance problems.

`idx_scan` is next on the list. It will show us how often an index was used for this table. PostgreSQL will also show how many rows those scans returned. Then there are a couple of columns starting with `n_tup_`. Those will tell us how much we inserted, updated, and deleted. The most important thing here is related to `HOT UPDATE`. When running an `UPDATE`, PostgreSQL has to copy a row to ensure that `ROLLBACK` will work correctly. `HOT UPDATE` is pretty good because it allows PostgreSQL to ensure that a row does not have to leave a block. The copy of the row stays inside the same block, which is beneficial for performance in general. A fair amount of `HOT UPDATE` indicates that you are on the right track in case of an `UPDATE` intense workload. The perfect ratio between normal and `HOT UPDATE` cannot be stated here for all use cases. People have really got to think for themselves to figure out which workload benefits from many in-place operations. The general rule is this: the more `UPDATE` intense your workload is, the better it is to have many `HOT UPDATE` clauses.

Finally, there are some `VACUUM` statistics, which mostly speak for themselves.

Making sense of `pg_stat_user_tables`

Reading all this data might be interesting; however, unless you are able to make sense out of it, it is pretty pointless. One way to use `pg_stat_user_tables` is to detect which tables might need an index. One way to get a clue to the right direction is to use the following query, which has served me well over the years:

```
SELECT schemaname, relname, seq_scan, seq_tup_read,
       seq_tup_read / seq_scan AS avg, idx_scan
FROM   pg_stat_user_tables
WHERE  seq_scan > 0
ORDER BY seq_tup_read DESC
LIMIT  25;
```

The idea is to find large tables that have been used frequently in a sequential scan. Those tables will naturally come out on top of the list to bless us with enormously high `seq_tup_read` values, which can be mind-blowing.



Work your way from top to bottom and look for expensive scans. Keep in mind that sequential scans are not necessarily bad. They appear naturally in backups, analytical statements, and so on without causing any harm. However, if you are running large sequential scans all the time, your performance will go down the drain.

Note that this query is really golden—it will help you to spot tables with missing indexes. Practical experience of close to two decades has shown again and again that missing indexes are the single most important reason for bad performance. Therefore, the query you are looking at is literally gold.

Once you are done looking for potentially missing indexes, consider taking a brief look at the caching behavior of your tables. `pg_statio_user_tables` will contain information about all kinds of things, such as caching behavior of the table (`heap_blks_`), of your indexes (`idx_blks_`), and of as **The Oversized Attribute Storage Technique (TOAST)** tables. Finally, you can find out more about TID scans, which are usually not relevant to the overall performance of the system:

```
test=# \d pg_statio_user_tables
          View "pg_catalog.pg_statio_user_tables"
  Column          | Type   | ...
  -----+-----+...
  relid            | oid    | ...
  schemaname       | name   | ...
  relname          | name   | ...
  heap_blks_read   | bigint | ...
  heap_blks_hit    | bigint | ...
  idx_blks_read    | bigint | ...
  idx_blks_hit     | bigint | ...
  toast_blks_read  | bigint | ...
  toast_blks_hit   | bigint | ...
  tidb_blks_read   | bigint | ...
  tidb_blks_hit    | bigint | ...
```

Although `pg_statio_user_tables` contains important information, it is usually the case that `pg_stat_user_tables` is more likely to provide you with a really relevant insight (such as a missing index or so).

Digging into indexes

While `pg_stat_user_tables` is important to spotting missing indexes, it is sometimes necessary to find indexes which should really not exist. Recently, I was on a business trip to Germany and discovered a system that contained mostly pointless indexes (74% of the total storage consumption). While this might not be a problem if your database is really small, it does make a difference in the case of large systems—having hundreds of gigabytes of pointless indexes can seriously harm your overall performance.

`pg_stat_user_indexes` can be inspected to find those pointless indexes:

```
test=# \d pg_stat_user_indexes
          View "pg_catalog.pg_stat_user_indexes"
   Column      |  Type  | ...
-----+-----+...
 relid         | oid    | ...
 indexrelid    | oid    | ...
 schemaname    | name   | ...
 relname       | name   | ...
 indexrelname   | name   | ...
 idx_scan      | bigint | ...
 idx_tup_read  | bigint | ...
 idx_tup_fetch | bigint | ...
```

The view tells us, for every index on every table in every schema, how often it has been used (`idx_scan`). To enrich this view a bit, I suggest the following SQL:

```
SELECT schemaname, relname, indexrelname, idx_scan,
       pg_size_pretty(pg_relation_size(indexrelid)),
       pg_size_pretty(sum(pg_relation_size(indexrelid))
                       OVER (ORDER BY idx_scan, indexrelid)) AS total
FROM pg_stat_user_indexes
ORDER BY 6 ;
```

The output of this statement is very useful. It doesn't only contain information about how often an index was used—it also tells us how much space has been wasted for each index. Finally, it adds up all the space consumption in column 6. You can now go through the table and rethink all those indexes that have rarely been used. It is hard to come up with a general rule regarding when to drop an index, so some manual checking makes a lot of sense.



Do not just blindly drop indexes. In some cases, indexes are simply not used because end users use the application differently than expected. In case end users change (a new secretary is hired or so on), an index might very well turn into a useful object again.

There is also a view called `pg_statio_user_indexes`, which contains caching information about an index. Although it is interesting, it usually does not contain information leading to big leaps forward.

Tracking the background worker

In this section, it is time to take a look at the background writer statistics. As you might know, database connections will, in many cases, not write blocks to disks directly. Instead, data is written by the background writer process or by the checkpoint.

To see how data is written, the `pg_stat_bgwriter` view can be inspected:

```
test=# \d pg_stat_bgwriter
```

Column	View "pg_catalog.pg_stat_bgwriter"	Type	...
checkpoints_timed	bigint		...
checkpoints_req	bigint		...
checkpoint_write_time	double precision		...
checkpoint_sync_time	double precision		...
buffers_checkpoint	bigint		...
buffers_clean	bigint		...
maxwritten_clean	bigint		...
buffers_backend	bigint		...
buffers_backend_fsync	bigint		...
buffers_alloc	bigint		...
stats_reset	timestamp with time zone		...

The first thing that should catch your attention here is the first two columns. You will learn later in this book that PostgreSQL will perform regular checkpoints, which are necessary to ensure that data has really made it to disk. If your checkpoints are too close to each other, `checkpoint_req` might point you in the right direction. If requested checkpoints are high, it can mean that a lot of data is written and that checkpoints are always triggered because of high throughput. In addition to that, PostgreSQL will tell you about the time needed to write data during a checkpoint and the time needed to sync. In addition to that, `buffers_checkpoint` indicates how many buffers were written during the checkpoint, and how many were written by the background writer (`buffers_clean`).

But there is more: `maxwritten_clean` tells us about the number of times the background writer stopped a cleaning scan because it had written too many buffers.

Finally, there are `buffers_backend` (the number of buffers directly written by a backend database connection), `buffers_backend_fsync` (the number of buffers flushed by a database connection), and `buffers_alloc`, which contains the number of buffers allocated. In general, it is not a good thing if database connections start to write their own stuff themselves.

Tracking, archiving, and streaming

In this section, we will take a look at some features related to replication and transaction log archiving. The first thing to inspect is `pg_stat_archiver`, which tells us about the archiver process moving the transaction log (WAL) from the main server to some backup device:

```
test=# \d pg_stat_archiver
          View "pg_catalog.pg_stat_archiver"
  Column          | Type          | ...
  -----+-----+-----
 archived_count   | bigint        | ...
 last_archived_wal | text          | ...
 last_archived_time | timestamp with time zone | ...
 failed_count     | bigint        | ...
 last_failed_wal   | text          | ...
 last_failed_time  | timestamp with time zone | ...
 stats_reset      | timestamp with time zone | ...
```

`pg_stat_archiver` contains important information about your archiving process. First of all, it will inform you about the number of transaction log files that have been archived (`archived_count`). It will also know the last file that was archived and when that happened (`last_archived_wal` and `last_achived_time`).

While knowing the number of WAL files is certainly interesting, it is not really that important. Therefore, consider taking a look at `failed_count` and `last_failed_wal`. If your transaction log archiving failed, it will tell you the latest file that failed and when that happened. It is recommended to keep an eye on those fields, because otherwise it might be possible that archiving might not work without you even noticing.

If you are running a streaming replication, the following two views will be really important for you. The first one is called `pg_stat_replication` and will provide information about the streaming process from the master to the slave. One entry per WAL sender process will be visible. If there is no single entry, there is no transaction log streaming going on, which might not be what you want.

Let us take a look at `pg_stat_replication`:

```
test=# \d pg_stat_replication
          View "pg_catalog.pg_stat_replication"
   Column          |          Type          | ...
-----+-----+-----
 pid               | integer                | ...
 usesysid          | oid                    | ...
 username          | name                   | ...
 application_name   | text                   | ...
 client_addr       | inet                   | ...
 client_hostname    | text                   | ...
 client_port       | integer                 | ...
 backend_start     | timestamp with time zone | ...
 backend_xmin      | xid                    | ...
 state             | text                   | ...
 sent_lsn          | pg_lsn                 | ...
 write_lsn         | pg_lsn                 | ...
 flush_lsn         | pg_lsn                 | ...
 replay_lsn        | pg_lsn                 | ...
 write_lag         | interval                | ...
 flush_lag         | interval                | ...
 replay_lag        | interval                | ...
 sync_priority     | integer                 | ...
 sync_state        | text                    | ...
```

You will find columns to indicate the username connected via the streaming replication. Then there is the application name, along with the connection data (`client_`). Then, PostgreSQL will tell us when the streaming connection has started. In production, a young connection can point to a network problem or to something even worse (reliability issues and so on). The state column shows in which state the other side of the stream is. Note that there will be more information on this in [Chapter 10, Making Sense of Backups and Replication](#).

There are fields telling us how much transaction log has been sent over the network connection (`sent_location`), how much has been sent to the kernel (`write_location`), how much has been flushed to disk (`flush_location`), and how much has already been replayed (`replay_location`). Finally, the sync status is listed. Since PostgreSQL 10.0 there are also additional fields, which already contain the time difference between the master and the slave. The `*_lag` fields contain intervals, which give some indication about the actual time difference between your servers.

While `pg_stat_replication` can be queried on the sending server of a replication setup, `pg_stat_wal_receiver` can be consulted on the receiving end. It provides similar information and allows this information to be extracted on the replica.

Here is the definition of the view:

```
test=# \d pg_stat_wal_receiver
View "pg_catalog.pg_stat_wal_receiver"
  Column          | Type          | ...
-----+-----+---
 pid              | integer       | ...
 status           | text          | ...
 receive_start_lsn | pg_lsn        | ...
 receive_start_tli | integer       | ...
 received_lsn     | pg_lsn        | ...
 received_tli     | integer       | ...
 last_msg_send_time | timestamp with time zone | ...
 last_msg_receipt_time | timestamp with time zone | ...
 latest_end_lsn   | pg_lsn        | ...
 latest_end_time  | timestamp with time zone | ...
 slot_name        | text          | ...
 conninfo         | text          | ...
```

First of all, PostgreSQL will tell us the process ID of the WAL receiver process. Then the view shows us the status of the connection in use. `receive_start_lsn` will tell us the transaction log position used when the WAL receiver was started. `receive_start_tli` contains the timeline in use when the WAL receiver was started. At some point, you might want to know the latest WAL position and timeline. To get those two numbers, use `received_lsn` and `received_tli`.

In the next two columns, there are two timestamps: `last_msg_send_time` and `last_msg_receipt_time`. The first one states when a message was last sent and when it was received.

`latest_end_lsn` contains the last transaction log position reported to the WAL sender process at `latest_end_time`. Finally, there are the `slot_name` and an obfuscated version of the connection information.

Checking SSL connections

Many people running PostgreSQL use SSL to encrypt connections from the server to the client. More recent versions of PostgreSQL provide a view to gain an overview of those encrypted connections, which is `pg_stat_ssl`:

```
test=# \d pg_stat_ssl
          View "pg_catalog.pg_stat_ssl"
  Column      |  Type  | ...
  -----+-----+...
 pid          | integer | ...
 ssl          | boolean | ...
 version      | text    | ...
 cipher       | text    | ...
 bits         | integer | ...
 compression  | boolean | ...
 clientdn     | text    | ...
```

Every process is represented by the process ID. If a connection uses SSL, the second column is set to `true`. The third and fourth column will define the version as well as the cipher. Finally, there are the number of bits used by the encryption algorithm, an indicator of whether compression is used or not, as well as the **Distinguished Name (DN)** field from the client certificate.

Inspecting transactions in real time

Thus far, some statistics tables have been discussed. The idea behind all of them is to see what is going on in the entire system. But what if you are a developer who wants to inspect an individual transaction? `pg_stat_xact_user_tables` is here to help. It does not contain system-wide transactions, but only data about your current transaction:

```
test=# \d pg_stat_xact_user_tables
          View "pg_catalog.pg_stat_xact_user_tables"
  Column      |  Type  | ...
  -----+-----+...
 relid        | oid     | ...
 schemaname   | name    | ...
 relname      | name    | ...
 seq_scan     | bigint  | ...
```

```

seq_tup_read | bigint | ...
idx_scan    | bigint | ...
idx_tup_fetch | bigint | ...
n_tup_ins   | bigint | ...
n_tup_upd   | bigint | ...
n_tup_del   | bigint | ...
n_tup_hot_upd | bigint | ...

```

Developers can therefore look into a transaction just before it commits to see whether it has caused any performance issues. It helps to distinguish overall data from what has just been caused by your application.

The ideal way for application developers to use this view is to add a function call in the application before a commit to track what the transaction has done.

This data can then be inspected so that the output of the current transaction can be distinguished from the overall workload.

Tracking vacuum progress

In PostgreSQL 9.6, the community introduced a system view many people have been waiting for. For many years, people wanted to track the progress of a vacuum process to see how long things might still take.

`pg_stat_progress_vacuum` has been invented to address this issue:

```

test=# \d pg_stat_progress_vacuum
          View "pg_catalog.pg_stat_progress_vacuum"
   Column      |  Type  | ...
-----+-----+---
pid            | integer | ...
datid         | oid    | ...
datname       | name   | ...
relid         | oid    | ...
phase         | text   | ...
heap_blks_total | bigint | ...
heap_blks_scanned | bigint | ...
heap_blks_vacuumed | bigint | ...
index_vacuum_count | bigint | ...
max_dead_tuples | bigint | ...
num_dead_tuples | bigint | ...

```

Most of the columns speak for themselves, and therefore I won't go into too much detail. There are just a couple of things that should be kept in mind. First of all, the process is not linear—it can jump quite a bit. In addition to that, a vacuum is usually pretty fast, so progress can be rapid and hard to track.

Using pg_stat_statements

After discussing the first couple of views, it is time to turn our attention to one of the most important views, which can be used to spot performance problems. I am, of course, speaking about `pg_stat_statements`. The idea is to have information about queries on your system. It helps to figure out which types of queries are slow and how often queries are called.

To use the module, three steps are necessary:

- Add `pg_stat_statements` to `shared_preload_libraries` in the `postgresql.conf` file
- Restart the database server
- Run `CREATE EXTENSION pg_stat_statements` in the database(s) of your choice

Let's inspect the definition of the view:

```
test=# \d pg_stat_statements
View "public.pg_stat_statements"
  Column      |      Type      | ...
-----+-----+---
userid        | oid             | ...
dbid          | oid             | ...
queryid       | bigint          | ...
query         | text            | ...
calls         | bigint          | ...
total_time    | double precision | ...
min_time      | double precision | ...
max_time      | double precision | ...
mean_time     | double precision | ...
stddev_time   | double precision | ...
rows          | bigint          | ...
shared_blks_hit | bigint          | ...
shared_blks_read | bigint          | ...
shared_blks_dirtied | bigint          | ...
shared_blks_written | bigint          | ...
local_blks_hit | bigint          | ...
```

<code>local_blks_read</code>	<code>bigint</code>	...
<code>local_blks_dirtied</code>	<code>bigint</code>	...
<code>local_blks_written</code>	<code>bigint</code>	...
<code>temp_blks_read</code>	<code>bigint</code>	...
<code>temp_blks_written</code>	<code>bigint</code>	...
<code>blk_read_time</code>	<code>double precision</code>	...
<code>blk_write_time</code>	<code>double precision</code>	...

`pg_stat_statements` provides simply fabulous information. For every user in every database, it provides one line per query. By default it tracks 5,000 (this can be changed by setting `pg_stat_statements.max`).

Queries and parameters are separated. PostgreSQL will put placeholders into the query. This allows identical queries, which just use different parameters, to be aggregated. `SELECT ... FROM x WHERE y = 10` will be turned into `SELECT ... FROM x WHERE y = ?`

For each query, PostgreSQL will tell us the total time it has consumed along with the number of calls. In more recent versions, `min_time`, `max_time`, `mean_time`, and `stddev` have been added. The standard deviation is especially noteworthy because it will tell us whether a query has stable or fluctuating runtimes. Unstable runtimes can happen for various reasons:

- If the data is not fully cached in RAM, queries, which have to go to disk, will take a lot longer than their cached counterparts
- Different parameters can lead to different plans and totally different result sets
- Concurrency and locking can have an impact

PostgreSQL will also tell us about the caching behavior of a query. The `shared_` columns show how many blocks came from the cache (`_hit`) or from the operating system (`_read`). If many blocks come from the operating system, the runtime of a query might fluctuate.

The next block of columns is all about local buffers. Local buffers are memory blocks allocated by the database connection directly.

On top of all this information, PostgreSQL provides information about temporary file I/O. Note that temporary file I/O will naturally happen when a large index is built or when some other large DDL is executed. However, temporary files are usually a very bad thing to have in OLTP as it will slow down the entire system by potentially blocking the disk. A high amount of temporary file I/O can point to some undesirable things. The following list contains my top three:

- Undesirable `work_mem` settings (OLTP)
- Suboptimal `maintenance_work_mem` settings (DDLs)
- Queries, which should not be run in the first place

Finally, there are two fields containing information about I/O timing. By default, those two fields are empty. The reason for this is that measuring timing can involve quite a lot of overhead on some systems. Therefore, the default value for `track_io_timing` is `false`--remember to turn it on if you need this data.

Once the module has been enabled, PostgreSQL is already collecting data and you can use the view.



Never run `SELECT * FROM pg_stat_statements` in front of a customer. More than once, people have started pointing at queries. They happened to know and started to explain why, who, what, when, and so on. When you use this view, always create a sorted output so that the most relevant information can be seen instantly.

Here at Cybertec, we have found the following query very helpful to gain an overview of what is happening on the database server:

```
test=# SELECT round((100 * total_time / sum(total_time)
                    OVER ())::numeric, 2) percent,
               round(total_time::numeric, 2) AS total,
               calls,
               round(mean_time::numeric, 2) AS mean,
               substring(query, 1, 40)
FROM   pg_stat_statements
ORDER BY total_time DESC
LIMIT 10;
```

percent	total	calls	mean	substring
54.47	111289.11	122161	0.91	UPDATE pgbench_branches SET bbalance = b
43.01	87879.25	122161	0.72	UPDATE pgbench_tellers SET tbalance = tb
1.46	2981.06	122161	0.02	UPDATE pgbench_accounts SET

```

0.50 | 1019.83 | 122161 | 0.01 | abalance = a
0.42 | 856.22 | 122161 | 0.01 | SELECT abalance FROM
0.04 | 85.63 | 1 | 85.63 | pgbench_accounts WH
0.02 | 44.11 | 1 | 44.11 | INSERT INTO pgbench_history
0.02 | 42.86 | 122161 | 0.00 | (tid, bid, a
0.02 | 34.08 | 122171 | 0.00 | copy pgbench_accounts from
0.01 | 22.46 | 1 | 22.46 | stdin
vacuum analyze pgbench_accounts
END;
BEGIN;
alter table pgbench_accounts
add primary
(10 rows)

```

It shows the top 10 queries and their runtime, including a percentage. It also makes sense to display the average execution time of the queries so that you can decide whether the runtime of those queries is too high or not.

Work your way down the list and inspect all the queries that seem to run too long on average.

Keep in mind that working through the top 1,000 queries is usually not worth it. In most cases, the first queries are already responsible for most of the load on the system.



In my example, I have used a substring to shorten the query to fit on a page. This makes no sense if you really want to see what is going on.

Remember that `pg_stat_statements` will by default cut off queries at 1,024 bytes:

```

test=# SHOW track_activity_query_size;
track_activity_query_size
-----
1024
(1 row)

```

Consider increasing this value to, say, 16,384. If your clients are running Java applications based on Hibernate, a larger value of `track_activity_query_size` will ensure that queries are not cut off before the interesting part is shown.

At this point, I want to use the situation to point out how important `pg_stat_statements` really is. It is by far the easiest way to track down performance problems. A slow query log can never be as useful as `pg_stat_statements`, because a slow query log will only point to individual slow queries—it won't show us problems caused by tons of medium queries. Therefore, it is recommended to always turn this module on. The overhead is really small and in no way harms the overall performance of the system.

By default, 5,000 types of queries are tracked (as of PostgreSQL 9.6). In most reasonably sane applications, this will be enough.

To reset the data, consider using the following instruction:

```
test=# SELECT pg_stat_statements_reset();
pg_stat_statements_reset
```

```
-----
(1 row)
```

Creating log files

After taking a deep look at the system views provided by PostgreSQL, it is time to configure logging. Fortunately, PostgreSQL provides an easy way to work with log files and helps people to set up a good configuration easily.

Collecting logs is important because it can point to errors and potential database problems.

The `postgresql.conf` file has all the parameters you need to provide you with all the information.

Configuring the `postgresql.conf` file

In this section, we will go through some of the most important entries in the `postgresql.conf` file to configure logging and see how logging can be used in the most beneficial way.

Before we get started, I want to say a few words about logging in PostgreSQL in general. On Unix systems, PostgreSQL will send log information to `stderr` by default. However, `stderr` is not a good place for logs to go because you will surely want to inspect the log stream at some point. Therefore, it really makes sense to work through this chapter to adjust things to your needs.

Defining log destination and rotation

Let us go through the `postgresql.conf` file and see what can be done:

```
#-----
# ERROR REPORTING AND LOGGING
#-----

# - Where to Log -

#log_destination = 'stderr'
# Valid values are combinations of
# stderr, csvlog, syslog, and eventlog,
# depending on platform. csvlog
# requires logging_collector to be on.

# This is used when logging to stderr:
#logging_collector = off
# Enable capturing of stderr and csvlog
# into log files. Required to be on for
# csvlogs.
# (change requires restart)
```

The first configuration option defines how the log is processed. By default, it will go to `stderr` (on Unix). On Windows, the default is `eventlog`, which is the Windows onboard tool to handle logging. Alternatively, you can choose to go with `csvlog` or `syslog`.

In case you want to make PostgreSQL log files, you should go for `stderr` and turn the logging collector on. PostgreSQL will then create log files.

The logical question now is: what will the names of those log files be and where will those files be stored? `postgresql.conf` has the answer:

```
# These are only used if logging_collector is on:
#log_directory = 'pg_log'
#       # directory where log files are written,
#       # can be absolute or relative to PGDATA
#log_filename = 'postgresql-%Y-%m-%d_%H%M%S.log'
#       # log file name pattern,
#       # can include strftime() escapes
```

`log_directory` will tell the system where to store the log. If you are using an absolute path, you can explicitly configure where logs will go. If you prefer the logs to be in the PostgreSQL data directly, simply go for a relative path. The advantage is that the data directory will be self-contained and you can move it without having to worry.

In the next step, you can define the filename PostgreSQL is supposed to use. PostgreSQL is very flexible and allows you to use all the shortcuts provided by `strftime`. To give you an impression of how powerful this feature is, a quick count on my platform reveals that `strftime` provides 43 (!) placeholders to create the filename. Everything people usually need is certainly possible.

Once the filename has been defined, it makes sense to briefly think about cleanup. The following settings will be available:

```
#log_truncate_on_rotation = off
#log_rotation_age = 1d
#log_rotation_size = 10MB
```

By default, PostgreSQL will keep producing log files in case files are older than 1 day or larger than 10 MB. `log_truncate_on_rotation` specifies if you want to append to a log file or not. Sometimes a `log_filename` is defined in a way that it becomes cyclic. The `log_truncate_on_rotation` parameter defines whether to overwrite or to append to the file that already exists. Given the default log file, this will of course not happen.

One way to handle auto-rotation is to use something like `postgresql_%a.log` along with `log_truncate_on_rotation = on`. `%a` means that the day of the week will be used inside the log file. The advantage here is that the day of the week tends to repeat itself every 7 days. Therefore, the log will be kept for a week and recycled. If you are aiming for weekly rotation, a 10 MB file size might not be enough. Consider turning the maximum file size off.

Configuring syslog

Some people prefer to use `syslog` to collect log files. PostgreSQL offers the following configuration parameters:

```
# These are relevant when logging to syslog:
#syslog_facility = 'LOCAL0'
#syslog_ident = 'postgres'
#syslog_sequence_numbers = on
#syslog_split_messages = on
```

`syslog` is pretty popular among `sys` admins. Fortunately, it is easy to configure. Basically, you set a facility and an identifier. If `log_destination` is set to `syslog`, this is already everything there is to do.

Logging slow queries

The log can also be used to track down individual slow queries. Back in the old days, this was pretty much the only way to spot performance problems.

How does it work? `postgresql.conf` has a variable called `log_min_duration_statement`. If this is set to a value greater than zero, every query exceeding our chosen setting will make it to the log:

```
# log_min_duration_statement = -1
```

Most people see the slow query log as the ultimate source of wisdom. However, I would like to add a word of caution. There are many slow queries, and they just happen to eat up a lot of CPU: index creation, data exports, analytics, and so on.

Those long-running queries are totally expected and are in many cases not the root of all evil. It happens frequently that many shorter queries are to blame. Here is an example:

1,000 queries x 500 milliseconds is worse than 2 queries x 5 seconds. The slow query log can be misleading in some cases.

Still, it does not mean that it is pointless—it just means that it is a source of information and not the source of information.

Defining what and how to log

After taking a look at some basic settings, it is time to decide what to log. By default, only errors will be logged. However, this might not be enough. In this section, you will learn what can be logged and what a log line will look like.

By default, PostgreSQL does not log information about checkpoints. The following setting is there to change exactly that:

```
#log_checkpoints = off
```

The same applies to connections; whenever a connection is established or properly destroyed, PostgreSQL can create log entries:

```
#log_connections = off
#log_disconnections = off
```

In most cases, it does not make sense to log connections, as extensive logging significantly slows down the systems. Analytical systems won't suffer much. However, OLTP might be seriously impacted.

If you want to see how long statements take, consider switching the following setting to on:

```
#log_duration = off
```

Let us move on to one of the most important settings. So far, we have not defined the layout of the messages yet. And so far, the log files contain errors in the following form:

```
test=# SELECT 1 / 0;
ERROR: division by zero
```

The log will state `ERROR` along with the error message. Before PostgreSQL 10.0, there wasn't a timestamp, username, and so on. You had to change the value instantly to make any sense of the logs. In PostgreSQL 10.0, the default value has changed to something much more reasonable: to change that, take a look at `log_line_prefix`:

```
#log_line_prefix = '%m [%p] '
# special values:
#   %a = application name
#   %u = user name
#   %d = database name
#   %r = remote host and port
#   %h = remote host
#   %p = process ID
#   %t = timestamp without milliseconds
#   %m = timestamp with milliseconds
```

```
# %n = timestamp with milliseconds (as a Unix epoch)
# %i = command tag
# %e = SQL state
# %c = session ID
# %l = session line number
# %s = session start timestamp
# %v = virtual transaction ID
# %x = transaction ID (0 if none)
# %q = stop here in non-session processes
# %% = '%'
```

`log_line_prefix` is pretty flexible and allows you to configure the log line to exactly match your needs. In general, it is a good idea to log a timestamp. Otherwise, it is close to impossible to see when something bad has happened. Personally, I also like to know the username, the transaction ID, and the database. However, it is up to you to decide on what you really need.

Sometimes slowness is caused by bad locking behavior. In general, locking related issues can be hard to track down. `log_lock_waits` can help to detect such issues. If a lock is held longer than `deadlock_timeout` then a line will be sent to the log, provided the following configuration variable is turned on:

```
#log_lock_waits = off
```

Finally, it is time to tell PostgreSQL what to actually log. So far, only errors, slow queries, and the like have been sent to the log. `log_statement` has two possible settings:

```
#log_statement = 'none'
# none, ddl, mod, all
```

`none` means that only errors will be logged. `ddl` means that errors as well as DDLs (CREATE TABLE, ALTER TABLE, and so on) will be logged. `mod` will already include data changes and `all` will send every statement to the log.



All can lead to a lot of logging information, which can slow down your system. To give you an impression of how much impact there can be, I have compiled a blog post. It can be found at: <https://www.cybertec-postgresql.com/en/logging-the-hidden-speedbrakes/>.

If you want to inspect replication in more detail, consider turning the following setting to on:

```
#log_replication_commands = off
```

It will send replication-related commands to the log. For more information, visit the following website:

<https://www.postgresql.org/docs/current/static/protocol-replication.html>

It can happen quite frequently that performance problems are caused by temporary file I/O. To see which queries cause the problem, the following setting can be used:

```
#log_temp_files = -1
# log temporary files equal or larger
# than the specified size in kilobytes;
# -1 disables, 0 logs all temp files
```

While `pg_stat_statements` contains aggregated information, `log_temp_files` will point to specific queries causing issues. It usually makes sense to set this one to a reasonably low value. The correct value depends on your workload, but maybe 4 MB is already a good start.

By default, PostgreSQL will write log files in the time zone where the server is located. However, if you are running a system that is spread all over the world, it can make sense to adjust the time zone in a way that you can go and compare log entries:

```
log_timezone = 'Europe/Vienna'
```

Keep in mind that on the SQL side, you will still see the time in your local time zone. However, if this variable is set, log entries will be in a different time zone.

Summary

This chapter was all about system statistics. You learned how to extract information from PostgreSQL and how to use system statistics in a beneficial way. The most important views were discussed in detail.

Chapter 6, *Optimizing Queries for Good Performance*, is all about query optimization. You will learn to inspect queries and how they are optimized.

6

Optimizing Queries for Good Performance

In *Chapters 5, Log Files, System Statistics*, you learned how to read system statistics and how to make use of what PostgreSQL provides. Armed with this knowledge, this chapter is all about good query performance. You will learn more about the following topics:

- Optimizer internals
- Execution plans
- Partitioning data
- Enabling and disabling optimizer settings
- Parameters for good query performance

At the end of the chapter, I hope that you will be able to write better and faster queries. And if your queries still happen to be bad, you should be able to understand why this is the case. You will also be able to use the new techniques to partition data.

Learning what the optimizer does

Before even attempting to think about query performance, it makes sense to familiarize yourself with what the query optimizer does. Having a deeper understanding of what is going on under the hood makes a lot of sense because it helps you to see what the database is really up to and what it is doing.

Optimizations by example

To demonstrate how the optimizer works, I have compiled an example, one which I have used over the years in PostgreSQL training. Suppose there are three tables:

```
CREATE TABLE a (aid int, ...);           -- 100 million rows
CREATE TABLE b (bid int, ...);           -- 200 million rows
CREATE TABLE c (cid int, ...);           -- 300 million rows
```

Let us assume further that those tables contain millions, or maybe hundreds of millions, of rows. In addition to that, there are indexes:

```
CREATE INDEX idx_a ON a (aid);
CREATE INDEX idx_b ON b (bid);
CREATE INDEX idx_c ON c (cid);
CREATE VIEW v AS SELECT * FROM a, b
WHERE aid = bid;
```

Finally, there is a view joining the first two tables together.

Let us suppose now the end user wants to run the following query. What will the optimizer do with this query? What choices are there?

```
SELECT *
FROM v, c
WHERE v.aid = c.cid
      AND cid = 4;
```

Before looking at the real optimization process, I want to focus on some options the planner has.

Evaluating join options

The planner has a couple of options here and I want to use the chance to show what can go wrong if trivial approaches are used.

Suppose the planner just steams ahead and calculates the output of the view. What is the best way to join 100 million with 200 million rows?

In this section, a couple of (not all) join options will be discussed to show what PostgreSQL is able to do.

Nested loops

One way to join two tables is to use a nested loop. The principle is simple. Here is some pseudo code:

```
for x in table1:
    for y in table2:
        if x.field == y.field
            issue row
        else
            keep doing
```

Nested loops are often used if one of the sides is very small and contains only a limited set of data. In our example, a nested loop would lead to 100 million x 200 million iterations through the code. This is clearly not an option because runtime would simply explode.

A nested loop is generally $O(n^2)$, so it is only efficient if one side of the join is very small. In my example, this is not the case, so a nested loop can be ruled out to calculate the view.

Hash joins

The second option is a hash join. The following strategy could be applied to solve our little problem:

```
← Hash join
  ← Sequentialscan table 1
  ← Sequentialscan table 2
```

Both sides can be hashed and the hash keys could be compared, leaving us with the result of the join. The trouble here is that all the values have to be hashed and put somewhere.

Merge joins

Finally, there is a merge join. The idea here is to use sorted lists to join the results. If both sides of the join are sorted, the system can just take rows from the top and see if they match and return them. The main requirement here is that the lists are sorted. Here is a sample plan:

```
← Merge join
  ← Sort table 1
    ← Sequential scan table 1
  ← Sort table 2
    ← Sequential scan table 2
```

To join, data has to be provided in sorted order. In many cases, PostgreSQL will just sort the data. However, there are other options to provide the join with sorted data. One way is to consult an index, as shown in the next example:

```
← Merge join
  ← Sort table 1
    ← Sequential scan table 1
  ← Sort table 2
    ← Sequential scan table 2
```

One side of the join or both sides can use sorted data coming from lower levels of the plan. If the table is accessed directly, an index is the obvious choice to do that but only if the returned result set is significantly smaller than the entire table. Otherwise, we encounter almost double the overhead because first we have to read the entire index, then the entire table. If the result set is a large portion of the table, a sequential scan is more efficient, especially if it is being accessed in primary key order.

The beauty of a merge join is that it can handle a lot of data. The downside is that data has to be sorted or taken from an index at some point.

Sorting is $O(n * \log(n))$. Therefore, sorting 300 million rows to perform the join is not attractive either.

Note that since the introduction of PostgreSQL 10.0, all join options described here are also available in a parallel version. The optimizer will therefore not just consider those standard join options, but also evaluate whether it makes sense to do parallel queries or not.

Applying transformations

Obviously, doing the obvious thing (joining the view first) makes no sense at all. A nested loop would send execution times through the roof. A hash join has to hash millions of rows and a nested loop has to sort 300 million rows. All three options are clearly unsuitable here. The way out is to apply logical transformations to make the query fast. In this section, you will learn what the planner does to speed up the query. A couple of steps will be performed.

Inlining the view

The first transformation done by the optimizer is to inline views. Here is what happens:

```
SELECT *
FROM
(
```

```
SELECT *  
FROM a, b  
WHERE aid = bid  
) AS v, c  
WHERE v.aid = c.cid  
AND cid = 4;
```

The view is inlined and transformed to a subselect. What does this one buy us? Actually, nothing. All it does is to open the door for further optimization, which will really be a game changer for this query.

Flattening subselects

The next thing is to flatten subselects. By getting rid of subselects, a couple more options to optimize the query will appear.

Here is what the query will look like after flattening the subselects:

```
SELECT * FROM a, b, c WHERE a.aid = c.cid AND aid = bid AND cid = 4;
```

It is now a normal join. Note we would have done that on our own but the planner will take care of those transformations for us anyway. The door is open for a key optimization.

Applying equality constraints

The following process creates equality constraints. The idea is to detect additional constraints, join options, and filters. Let us take a deep breath and take a look at the query: If `aid = cid` and `aid = bid`, we know that `bid = cid`. If `cid = 4` and all the others are equal. We know that `aid` and `bid` have to be 4 as well, which leads us to the following query:

```
SELECT *  
FROM a, b, c  
WHERE a.aid = c.cid  
AND aid = bid  
AND cid = 4  
AND bid = cid  
AND aid = 4  
AND bid = 4
```

The importance of this optimization cannot be stressed enough. What the planner did here was to open the door for two additional indexes, which were not clearly visible in the original query.

By being able to use indexes on all three columns, there is no need to calculate this expensive horror view anymore. PostgreSQL has the option to just retrieve a couple of rows from the index and use whatever join option makes sense.

Exhaustive searching

Now that those formal transformations have been done, PostgreSQL will perform an exhaustive search. It will try out all possible plans and come up with the cheapest solution to your query. PostgreSQL knows which indexes are possible and just uses the cost model to determine how to do things in the best way possible.

During an exhaustive search, PostgreSQL will also try to determine the best join order. In the original query, the join order was fixed to $A \rightarrow B$ and $A \rightarrow C$. However, using those equality constraints, we could join $B \rightarrow C$ and join A later. All options are open to the planner.

Trying it all out

Now that all those optimizations have been discussed, it is time to see which plan PostgreSQL might create for us:

```
test=# explain SELECT * FROM v, c WHERE v.aid = c.cid AND cid = 4;
               QUERY PLAN
-----
Nested Loop (cost=1.71..17.78 rows=1 width=12)
-> Nested Loop (cost=1.14..9.18 rows=1 width=8)
    -> Index Only Scan using idx_a on a
        (cost=0.57..4.58 rows=1 width=4)
        Index Cond: (aid = 4)
    -> Index Only Scan using idx_b on b
        (cost=0.57..4.59 rows=1 width=4)
        Index Cond: (bid = 4)
-> Index Only Scan using idx_c on c
    (cost=0.57..8.59 rows=1 width=4)
    Index Cond: (cid = 4)
(8 rows)
```

As you can see, PostgreSQL will use three indexes. It is also interesting to see that PostgreSQL decides to go for a nested loop to join the data. This makes perfect sense because there is virtually no data coming back from the index scans. Therefore, using a loop to join things is perfectly feasible and highly efficient.

Making the process fail

So far, you have seen what PostgreSQL can do for you and how the optimizer helps to speed up queries. PostgreSQL is pretty smart but it needs smart users. There are some cases in which the end user cripples the entire optimization process by doing stupid things. Let us drop the view:

```
test=# DROP VIEW v;
DROP VIEW
```

Now, the view is recreated. Note that `OFFSET 0` has been added to the end of the view:

```
test=# CREATE VIEW v AS SELECT *
FROM a, b
WHERE aid = bid
OFFSET 0;
CREATE VIEW
```

While this view is logically equivalent to the example shown previously, the optimizer has to treat things differently. Every `OFFSET` other than 0 will change the result and therefore the view has to be calculated. The entire optimization process is crippled by adding things such as `OFFSET`.



The PostgreSQL community did not dare to optimize this case of having an `OFFSET 0` in a view. People are simply not supposed to do that. I am using this just as an example to show that some operations can cripple performance and that developers should be aware of the underlying optimization process. However, if you are smart and if you happen to know how PostgreSQL works, this trick can be used as optimization.

Here is the new plan:

```
test=# EXPLAIN SELECT * FROM v, c WHERE v.aid = c.cid AND cid = 4;
               QUERY PLAN
-----
Nested Loop (cost=120.71..7949879.40 rows=1 width=12)
  -> Subquery Scan on v
        (cost=120.13..7949874.80 rows=1 width=8)
    Filter: (v.aid = 4)
  -> Merge Join (cost=120.13..6699874.80
                rows=100000000 width=8)
        Merge Cond: (a.aid = b.bid)
        -> Index Only Scan using idx_a on a
              (cost=0.57..2596776.57 rows=100000000
               width=4)
        -> Index Only Scan using idx_b on b
```

```

(cost=0.57..5193532.33 rows=199999984
 width=4)
-> Index Only Scan using idx_c on c
    (cost=0.57..4.59 rows=1 width=4)
    Index Cond: (cid = 4)
(9 rows)

```

Just take a look at the costs predicted by the planner. Costs have skyrocketed from a two-digit number to a staggering one. Clearly, this query is going to provide you with bad performance.

There are more ways to cripple performance and it makes sense to keep the optimization process in mind.

Constant folding

However, there are many more optimizations in PostgreSQL which happen behind the scenes and which contribute to overall good performance. One of those features is called **constant folding**. The idea is to turn expressions into constants, as shown in the following example:

```

test=# explain SELECT * FROM a WHERE aid = 3 + 1;
               QUERY PLAN
-----
Index Only Scan using idx_a on a
    (cost=0.57..4.58 rows=1 width=4)
    Index Cond: (aid = 4)
(2 rows)

```

As you can see, PostgreSQL will try to look for 4. As aid is indexed, PostgreSQL will go for an index scan. Note that our table has just one column, so PostgreSQL even figured that all the data it needs can be found in the index.

What happens if the expression is on the left-hand side?:

```

test=# explain SELECT * FROM a WHERE aid - 1 = 3;
               QUERY PLAN
-----
Seq Scan on a (cost=0.00..1942478.48 rows=500000 width=4)
    Filter: ((aid - 1) = 3)
(2 rows)

```

In this case, the index lookup code will fail and PostgreSQL has to go for a sequential scan. Keep in mind that this is a single-core plan. If the size of the table is large or if your PostgreSQL configuration is different, you might see a multi-core plan. For the sake of simplicity, this chapter only contains single-core plans, to make reading easier.

Understanding function inlining

As already outlined in this section, there are many optimizations which help to speed up queries. One of them is called function **inlining**. PostgreSQL is able to inline immutable SQL functions. The main idea is to reduce the number of function calls which have to be made, in order to speed things up.

Here is an example of a function:

```
test=# CREATE OR REPLACE FUNCTION ld(int)
      RETURNS numeric AS
      $$
        SELECT log(2, $1);
      $$
      LANGUAGE 'sql' IMMUTABLE;
      CREATE FUNCTION
```

The function will calculate the logarithmus dualis of the input value:

```
test=# SELECT ld(1024);
      ld
-----
 10.0000000000000000
(1 row)
```

To demonstrate how things work, I will recreate the table with less content to speed up the index creation:

```
test=# TRUNCATE a;
      TRUNCATE TABLE
```

Then data can be added again and the index can be applied:

```
test=# INSERT INTO a SELECT * FROM generate_series(1, 10000);
      INSERT 0 10000
test=# CREATE INDEX idx_ld ON a (ld(aid));
      CREATE INDEX
```

As expected, the index created on the function will be used just like any other index. However, take a closer look at the indexing condition:

```
test=# EXPLAIN SELECT * FROM a WHERE ld(aid) = 10;
               QUERY PLAN
-----
Index Scan using idx_ld on a (cost=0.29..8.30 rows=1 width=4)
  Index Cond: (log('2'::numeric, (aid)::numeric) = '10'::numeric)
(2 rows)
```

The important observation here is that the indexing condition actually looks for the log function instead of the ld function. The optimizer has completely gotten rid of the function call.

Logically, this opens the door for the following query:

```
test=# EXPLAIN SELECT * FROM a WHERE log(2, aid) = 10;
               QUERY PLAN
-----
Index Scan using idx_ld on a (cost=0.29..8.30 rows=1 width=4)
  Index Cond: (log('2'::numeric, (aid)::numeric) = '10'::numeric)
(2 rows)
```

Join pruning

PostgreSQL provides an optimization called **join pruning**. The idea is to remove joins if they are not needed by the query. This can come in handy if queries are generated by some middleware or some ORM. If a join can be removed, it naturally speeds things up dramatically and leads to less overhead.

The question now is: how does join pruning work? Here is an example:

```
CREATE TABLE x (id int, PRIMARY KEY (id));
CREATE TABLE y (id int, PRIMARY KEY (id));
```

First of all, two tables are created. Make sure that both sides of the join conditions are actually unique. Those constraints will be important in a minute.

Now, we can write a simple query:

```
test=# EXPLAIN SELECT *
FROM x LEFT JOIN y ON (x.id = y.id)
WHERE x.id = 3;
               QUERY PLAN
-----
```

```

Nested Loop Left Join  (cost=0.31..16.36 rows=1 width=8)
  Join Filter: (x.id = y.id)
    -> Index Only Scan using x_pkey on x
        (cost=0.15..8.17 rows=1 width=4)
        Index Cond: (id = 3)
    -> Index Only Scan using y_pkey on y
        (cost=0.15..8.17 rows=1 width=4)
        Index Cond: (id = 3)
(6 rows)

```

As you can see, PostgreSQL will join those tables directly. So far, there are no surprises. However, the following query is slightly modified. Instead of selecting all the columns, it only selects those columns on the left-hand side of the join:

```

test=# EXPLAIN SELECT x.*
FROM x LEFT JOIN y ON (x.id = y.id)
WHERE x.id = 3;
               QUERY PLAN
-----
Index Only Scan using x_pkey on x  (cost=0.15..8.17 rows=1 width=4)
  Index Cond: (id = 3)
(2 rows)

```

PostgreSQL will go for a direct inside scan and skip the join completely. There are two reasons why this is actually possible and logically correct:

- No columns are selected from the right-hand side of the join; thus, looking those columns up does not buy us anything
- The right-hand side is unique, which means that joining cannot increase the number of rows due to duplicates on the right-hand side

If joins can be pruned automatically, it might happen that queries are a magnitude faster. The beauty here is that the speedup can be achieved by just removing columns which might not be needed by the application anyway.

Speedup set operations

Set operations allow the results of multiple queries to be combined into a single result set. Set operators include `UNION`, `INTERSECT`, and `EXCEPT`. PostgreSQL implements all of them and offers many important optimizations to speed them up.

The planner is able to push restrictions down into the set operation, opening the door for fancy indexing and speedups in general. Let us take a look at the following query, which shows how this works:

```
test=# EXPLAIN SELECT *
FROM
(
  SELECT aid AS xid
  FROM a
  UNION ALL
  SELECT bid FROM b
) AS y
WHERE xid = 3;
```

QUERY PLAN

```
-----
Append (cost=0.29..12.89 rows=2 width=4)
-> Index Only Scan using idx_a on a
    (cost=0.29..8.30 rows=1 width=4)
    Index Cond: (aid = 3)
-> Index Only Scan using idx_b on b
    (cost=0.57..4.59 rows=1 width=4)
    Index Cond: (bid = 3)
(5 rows)
```

What you see here is that two relations are added to each other. The trouble is, the only restriction is outside the subselect. However, PostgreSQL figures that the filter can be pushed further down the plan. `xid = 3` is therefore attached to `aid` and `bid`, opening the option to use indexes on both tables. By avoiding the sequential scan on both tables, the query will run a lot faster.

Note that there is a distinction between the `UNION` clause and the `UNION ALL` clause. The `UNION ALL` clause will just blindly append the data and deliver the results of both tables.

The `UNION` clause is different: it will filter out duplicates. The following plan shows how that works:

```
test=# EXPLAIN SELECT *
FROM
(
  SELECT aid AS xid
  FROM a
  UNION SELECT bid
  FROM b
) AS y
WHERE xid = 3;
```

QUERY PLAN

```

-----
Unique (cost=12.92..12.93 rows=2 width=4)
-> Sort (cost=12.92..12.93 rows=2 width=4)
    Sort Key: a.aid
    -> Append (cost=0.29..12.91 rows=2 width=4)
        -> Index Only Scan using idx_a on a
            (cost=0.29..8.30 rows=1 width=4)
            Index Cond: (aid = 3)
        -> Index Only Scan using idx_b on b
            (cost=0.57..4.59 rows=1 width=4)
            Index Cond: (bid = 3)

(8 rows)

```

PostgreSQL has to add a `Sort` node on top of the `Append` node to ensure that duplicates can be filtered later on.



Many people who are not fully aware of the difference between the `UNION` clause and the `UNION ALL` clause complain about bad performance because they are unaware that PostgreSQL has to filter out duplicates, which is especially painful in the case of large datasets.

Understanding execution plans

After digging into some important optimizations implemented into PostgreSQL, I want to shift your attention a bit more to execution plans. You have already seen some plans in this book. However, in order to make full use of plans, it is important to develop a systematic approach to reading this information. Reading plans systematically is exactly within the scope of this section.

Approaching plans systematically

The first thing you have to know is that an `EXPLAIN` clause can do quite a lot for you and, I would highly recommend making full use of those features.

As many readers might already know, an `EXPLAIN ANALYZE` clause will execute the query and return the plan, including real runtime information. Here is an example:

```

test=# EXPLAIN ANALYZE SELECT *
FROM
(
    SELECT *
    FROM b

```

```

LIMIT 1000000
) AS b
ORDER BY cos(bid);

-----
QUERY PLAN
-----
Sort (cost=146173.12..148673.12 rows=1000000)
  (actual time=837.049..1031.587 rows=1000000)
  Sort Key: (cos((b.bid)::double precision))
  Sort Method: external merge Disk: 25408kB
-> Subquery Scan on b
  (cost=0.00..29424.78 rows=1000000 width=12)
  (actual time=0.011..352.717 rows=1000000)
  -> Limit (cost=0.00..14424.78 rows=1000000)
    (actual time=0.008..169.784 rows=1000000)
    -> Seq Scan on b b_1 (cost=0.00..2884955.84
      rows=19999984 width=4)
      (actual time=0.008..85.710 rows=1000000)

Planning time: 0.064 ms
Execution time: 1159.919 ms
(8 rows)

```

The plan looks a bit scary, but don't panic; we will go through it step by step. When reading a plan, make sure that you read it from the inside to the outside. In our example, execution starts with a sequential scan on `b`. There are actually two blocks of information here: the **cost block** and the **actual time block**. While the cost block contains estimations, the actual time block is hard evidence. It shows the real execution time. In this example, the sequential scan has taken 85.7 milliseconds.

Note that the costs shown on your system might not be identical. A small difference in the optimizer statistics can cause differences. The important thing here is really the way the plan has to be read.

Data is then passed on to the `Limit` node, which ensures that there is not too much data. Note that each stage of execution will also show us the number of rows involved. As you can see, PostgreSQL will only fetch 1 million rows from the table in the first place; the `Limit` node ensures that this will actually happen. However, there is a price tag: at this stage, the runtime has jumped to 169 milliseconds already. Finally, the data is sorted, which takes a lot of time. The most important thing when looking at the plan is to figure out where time is actually lost. The best way to do that is to take a look at the actual time block and try to figure out where time jumps. In this example, the sequential scan takes some time, but it cannot be sped up significantly. Instead, we see that time skyrockets as sorting starts.

Of course, sorting can be sped up, but more on that later in this chapter.

Making EXPLAIN more verbose

In PostgreSQL, the output of an `EXPLAIN` clause can be beefed up a little to provide you with more information. To extract as much as possible out of a plan, consider turning the following options on:

```
test=# EXPLAIN (analyze, verbose, costs, timing, buffers)
       SELECT * FROM a ORDER BY random();
              QUERY PLAN
-----
Sort (cost=834.39..859.39 rows=10000 width=12)
    (actual time=6.089..7.199 rows=10000 loops=1)
    Output: aid, (random())
    Sort Key: (random())
    Sort Method: quicksort Memory: 853kB
    Buffers: shared hit=45
    -> Seq Scan on public.a
        (cost=0.00..170.00 rows=10000 width=12)
        (actual time=0.012..2.625 rows=10000 loops=1)
        Output: aid, random()
        Buffers: shared hit=45
Planning time: 0.054 ms
Execution time: 7.992 ms
(10 rows)
```

`analyze true` will actually execute the query as shown previously. `verbose true` will add some more information to the plan (such as column information and so on). `costs true` will show information about costs. `timing true` is equally important, as it will provide us with good runtime data so that we can see where in the plan time gets lost. Finally, there is `buffers true`, which can be very enlightening. In my example, it reveals that we needed to access 45 buffers to execute the query.

Spotting problems

Given all the information shown in [Chapter 5, Log Files and System Statistics](#), it is already possible to spot a couple of potential performance problems which are very important in real life.

Spotting changes in runtime

When looking at a plan, there are always two questions which you have got to ask yourself:

- Is the runtime shown by the `EXPLAIN ANALYZE` clause justified for the given query?
- If the query is slow, where does the runtime jump?

In my case, the sequential scan is rated at 2.625 milliseconds. The sort is done after 7.199 milliseconds, so the sort takes roughly 4.5 milliseconds to complete and is therefore responsible for most of the runtime needed by the query.

Looking for jumps in the execution time of the query will reveal what is really going on. Depending on which type of operation will burn too much time, you have to act accordingly. General advice is not possible here because there are simply too many things which can cause issues.

Inspecting estimates

However, there is something that should always be done: making sure that estimates and real numbers are reasonably close together. In some cases, the optimizer will make poor decisions because the estimates are way off for some reason. It can happen that estimates are off because the system statistics are not up to date. Running an `ANALYZE` clause is therefore definitely a good thing to start with. However, optimizer stats are mostly taken care of by the autovacuum daemon, so it is definitely worth considering other options causing bad estimates. Take a look at the following example:

```
test=# CREATE TABLE t_estimate AS
      SELECT * FROM generate_series(1, 10000) AS id;
SELECT 10000
```

After loading 10,000 rows, optimizer statistics are created:

```
test=# ANALYZE t_estimate;
ANALYZE
```

Let us take a look at the estimates now:

```
test=# EXPLAIN ANALYZE SELECT * FROM t_estimate WHERE cos(id) < 4;
               QUERY PLAN
-----
Seq Scan on t_estimate (cost=0.00..220.00 rows=3333 width=4)
    (actual time=0.010..4.006 rows=10000 loops=1)
    Filter: (cos((id)::double precision) < '4'::double precision)
```

```

Planning time: 0.064 ms
Execution time: 4.701 ms
(4 rows)

```

In many cases, PostgreSQL might not be able to process the `WHERE` clause properly because it only has statistics on columns, not on expressions. What we see here is a nasty underestimation of the data returned from the `WHERE` clause.

Of course, it can also happen that the amount of data is overestimated:

```

test=# EXPLAIN ANALYZE
SELECT *
FROM t_estimate
WHERE cos(id) > 4;
          QUERY PLAN
-----
Seq Scan on t_estimate (cost=0.00..220.00 rows=3333 width=4)
    (actual time=3.802..3.802 rows=0 loops=1)
    Filter: (cos((id)::double precision) > '4'::double precision)
    Rows Removed by Filter: 10000
Planning time: 0.037 ms
Execution time: 3.813 ms
(5 rows)

```

If something like that happens deep inside the plan, the process might very well create a bad plan. Therefore, making sure that estimates are within a certain range makes perfect sense.

Fortunately, there is a way to get around this problem:

```

test=# CREATE INDEX idx_cosine ON t_estimate (cos(id));
CREATE INDEX

```

Creating an index will make PostgreSQL track statistics of the expression:

```

test=# ANALYZE t_estimate;
ANALYZE

```

Apart from the fact that this plan will ensure significantly better performance, it will also fix statistics, even if the index is not used:

```

test=# EXPLAIN ANALYZE SELECT * FROM t_estimate WHERE cos(id) > 4;
          QUERY PLAN
-----
Index Scan using idx_cosine on t_estimate
    (cost=0.29..8.30 rows=1 width=4)
    (actual time=0.002..0.002 rows=0 loops=1)

```

```
Index Cond: (cos((id)::double precision) > '4'::double precision)
Planning time: 0.095 ms
Execution time: 0.011 ms
(4 rows)
```

However, there is more to wrong estimates than meets the eye. One problem which is often underestimated is called **cross-column correlation**. Consider a simple example involving two columns:

- 20% of people like to ski
- 20% of people are from Africa

If we want to count the number of skiers in Africa, mathematics says that the result will be $0.2 \times 0.2 = 4\%$ of the overall population. However, there is no snow in Africa and income is low. Therefore, the real result will surely be lower. The observation Africa and the observation skiing are not statistically independent. In many cases, the fact that PostgreSQL keeps column statistics which do not span more than one column can lead to bad results.

Of course, the planner does a lot to prevent these things from happening as often as possible. Still, it can be an issue.

Starting with PostgreSQL 10.0, we have multivariate statistics in PostgreSQL, which has put an end to cross-column correlation once and for all.

Inspecting buffer usage

However, the plan itself is not the only thing which can cause issues. In many cases, dangerous things are hidden on some other level. Memory and caching can lead to undesired behavior, which is often hard to understand for end users who are not trained to see the problem described in this section.

Here is an example:

```
test=# CREATE TABLE t_random AS
      SELECT * FROM generate_series(1, 10000000) AS id ORDER BY random();
test=# SELECT 10000000
test=# ANALYZE t_random ;
ANALYZE
```

I have generated a simple table containing 10 million rows and created optimizer statistics.

In the next step, a simple query retrieving only a handful of rows is executed:

```
test=# EXPLAIN (analyze true, buffers true, costs true, timing true)
      SELECT * FROM t_random WHERE id < 1000;
      QUERY PLAN
-----
Seq Scan on t_random (cost=0.00..169248.60 rows=1000 width=4)
    (actual time=1.068..685.410 rows=999 loops=1)
    Filter: (id < 1000)
    Rows Removed by Filter: 9999001
    Buffers: shared hit=2112 read=42136
Planning time: 0.035 ms
Execution time: 685.551 ms
(6 rows)
```

Before inspecting the data, make sure that you have executed the query twice. Of course, it makes sense to use an index here. However, I want to point out something else. In my query, PostgreSQL has found 2,112 buffers inside the cache and 421,136 buffers had to be taken from the operating system. Now, there are two things which can happen. If you are lucky, the operating system lands a couple of cache hits and the query is fast. If the filesystem cache is not lucky, those blocks have to be taken from disk. This might look obvious; however, it can lead to wild swings in execution time. A query which runs entirely in cache can be 100 times faster than a query which has to slowly collect random blocks from disk.

Let me try to outline the problem using a simple example. Suppose we have a phone system storing 10 billion rows (which is not uncommon at large phone carriers). Data flows in at a rapid rate and users want to query this data. If you have 10 billion rows, the data will only partially fit into memory and therefore a lot of stuff will naturally end up coming from disk.

We can run a simple query now:

```
SELECT * FROM data WHERE phone_number = '+12345678';
```

Even if you are on the phone, your data will be spread all over the place. If you end a phone call just to start the next call, thousands of people will do the same, so the odds that two of your calls will end up in the very same 8,000 block is naturally close to zero. Just imagine for the time being that there are 100,000 calls going on at the same time. On disk, data will be randomly distributed. If your phone number shows up often, it means that for each row, at least one block has to be fetched from disk (assuming a very low cache hit rate). Suppose 5,000 rows will be returned. Assuming you have to go to disk 5,000 times, it leads to something like $5,000 \times 5 \text{ milliseconds} = 25 \text{ seconds}$ of execution time. Note that the execution time of this query might vary between milliseconds and, say, 30 seconds, depending on how much has been cached by the operating system or by PostgreSQL.

Keep in mind that every server restart will naturally clean out the PostgreSQL and filesystem caches, which can lead to real trouble after a node failure.

Fixing high buffer usage

The question is now: how can the situation be improved? One way to do that is to run a `CLUSTER` clause:

```
test=# \h CLUSTER
Command:      CLUSTER
Description:  cluster a table according to an index
Syntax:
CLUSTER [VERBOSE] table_name
[ USING index_name ] CLUSTER [VERBOSE]
```

The `CLUSTER` clause will rewrite the table in the same order as a (b-tree) index. If you are running an analytical workload, this can make sense. However, in an OLTP system, the `CLUSTER` clause might not be feasible because a table lock is required while the table is rewritten.

Understanding and fixing joins

Joins are important; everybody needs them on a regular basis. Consequently, joins are also relevant to maintaining or achieving good performance. To ensure that you can write good joins, I have decided to include a section about joining in this book.

Getting joins right

Before we dive into optimizing joins, it is important to take a look at some of the most common problems arising with joins and which of them should ring alarm bells for you.

Here is an example:

```
test=# CREATE TABLE a (aid int);
CREATE TABLE
test=# CREATE TABLE b (bid int);
CREATE TABLE
test=# INSERT INTO a VALUES (1), (2), (3);
INSERT 0 3
test=# INSERT INTO b VALUES (2), (3), (4);
INSERT 0 3
```

In the next example, you will see a simple outer join:

```
test=# SELECT * FROM a LEFT JOIN b ON (aid = bid);
 aid | bid 
-----+-----
   1 | 
   2 |    2
   3 |    3
(3 rows)
```

You can see that PostgreSQL will take all rows from the left-hand side and only list the ones fitting the join.

The next example might come as a surprise to many people:

```
test=# SELECT * FROM a LEFT JOIN b ON (aid = bid AND bid = 2);
 aid | bid 
-----+-----
   1 | 
   2 |    2
   3 | 
(3 rows)
```

No, the number of rows does not decrease--it will stay constant. Most people assume that there will only be one row in the join, but this is not true, and will lead to some hidden issues.

Consider the following query:

```
test=# SELECT avg(aid), avg(bid) FROM a LEFT JOIN b
ON (aid = bid AND bid = 2);
      avg      |      avg      
-----+-----
2.0000000000000000 | 2.0000000000000000
(1 row)
```

Most people assume that the average is calculated based on a single row. However, as stated earlier, this is not the case and therefore queries like that are often considered to be a performance problem because, for some reason, PostgreSQL does not index the table on the left-hand side of the join. Of course, we are not looking at a performance problem here--we are definitely looking at a semantic issue. It happens on a regular basis that people writing outer joins don't mean what they order PostgreSQL to do. So, my personal advice is to always question the semantic correctness of an outer join before attacking the performance problem reported by the client.

I cannot stress enough how important this kind of work is to ensure that your queries are correct and do exactly what is needed.

Processing outer joins

After verifying that your queries are actually correct from a business point of view. It makes sense to check what the optimizer can do to speed up your outer joins. The most important thing is that PostgreSQL can, in many cases, reorder inner joins to speed things up dramatically. However, in the case of outer joins, this is not always possible. Only a handful of reordering operations are actually allowed:

- `(A leftjoin B on (Pab)) innerjoin C on (Pac) = (A innerjoin C on (Pac)) leftjoin B on (Pab)`

`Pac` is a predicate referencing `A` and `C`, and so on (in this case, clearly `Pac` cannot reference `B`, or the transformation is nonsensical):

- `(A leftjoin B on (Pab)) leftjoin C on (Pac) = (A leftjoin C on (Pac)) leftjoin B on (Pab)`
- `(A leftjoin B on (Pab)) leftjoin C on (Pbc) = (A leftjoin (B leftjoin C on (Pbc)) on (Pab))`

The last rule only holds if predicate `Pbc` must fail for all null `B` rows (that is, `Pbc` is strict for at least one column of `B`). If `Pbc` is not strict, the first form might produce some rows with non-null `C` columns where the second form would make those entries null.

While some joins can be reordered, a typical type of query cannot benefit from join reordering:

```
SELECT ...
FROM a LEFT JOIN b ON (aid = bid)
      LEFT JOIN c ON (bid = cid)
      LEFT JOIN d ON (cid = did)
...
```

The way to approach this is to check whether all outer joins are really necessary. In many cases, it happens that people write outer joins without actually needing them. Often, the business case does not even contain the necessity to use outer joins.

Understanding the `join_collapse_limit` variable

During the planning process, PostgreSQL tries to check all possible join orders. In many cases, this can be pretty expensive because there can be many permutations, which naturally slows down the planning process.

The `join_collapse_limit` variable is here to give the developer a tool to actually work around these problems and define, in a more straightforward way, how a query should be processed.

To show what this setting is all about, I have compiled a little example:

```
SELECT * FROM tab1, tab2, tab3
WHERE tab1.id = tab2.id
      AND tab2.ref = tab3.id;
SELECT * FROM tab1 CROSS JOIN tab2
CROSS JOIN tab3
WHERE tab1.id = tab2.id
      AND tab2.ref = tab3.id;
SELECT * FROM tab1 JOIN (tab2 JOIN tab3
      ON (tab2.ref = tab3.id))
      ON (tab1.id = tab2.id);
```

Basically, these three queries are identical and treated by the planner in the same way. The first query consists of implicit joins. The last one consists only of explicit joins. Internally, the planner will inspect those requests and order joins accordingly to ensure the best runtime possible. The question now is: how many explicit joins will PostgreSQL plan implicitly? This is exactly what you can tell the planner by setting the `join_collapse_limit` variable. The default value is reasonably good for normal queries. However, if your query contains a very high number of joins, playing around with this setting can reduce planning time considerably. Reducing planning time can be essential to maintain good throughput.

To see how the `join_collapse_limit` variable changes the plan, I have written a simple query:

```
test=# EXPLAIN WITH x AS
(
  SELECT *
  FROM generate_series(1, 1000) AS id
)
SELECT *
FROM x AS a
      JOIN x AS b ON (a.id = b.id)
      JOIN x AS c ON (b.id = c.id)
```

```
JOIN x AS d ON (c.id = d.id)
JOIN x AS e ON (d.id = e.id)
JOIN x AS f ON (e.id = f.id);
```

Try running the query with different settings and see how the plan changes. Unfortunately, the plan is too long to copy here so I cannot include the actual changes in this section.

Enabling and disabling optimizer settings

So far, the most important optimizations performed by the planner have been discussed in more or less detail. PostgreSQL has become very smart over the years. Still, it can happen that something goes south and users have to convince the planner to do the right thing.

To modify plans, PostgreSQL offers a couple of runtime variables, which will have a significant impact on planning. The idea is to give the end user the chance to make certain types of nodes in the plan more expensive than others. What does that mean in practice? Here is a simple plan:

```
test=# explain SELECT *
      FROM generate_series(1, 100) AS a,
           generate_series(1, 100) AS b
      WHERE a = b;
               QUERY PLAN
-----
Merge Join (cost=119.66..199.66 rows=5000 width=8)
  Merge Cond: (a.a = b.b)
    -> Sort (cost=59.83..62.33 rows=1000 width=4)
        Sort Key: a.a
        -> Function Scan on generate_series a
            (cost=0.00..10.00 rows=1000 width=4)
    -> Sort (cost=59.83..62.33 rows=1000 width=4)
        Sort Key: b.b
        -> Function Scan on generate_series b
            (cost=0.00..10.00 rows=1000 width=4)
(8 rows)
```

The plan shows that PostgreSQL reads the data from the function and sorts both results. Then, a merge join is performed.

However, what if a merge join is not the fastest way to run the query? In PostgreSQL, there is no way to put planner hints into comments as you could do in Oracle. Instead, you can ensure that certain operations are simply considered to be expensive. The `SET enable_mergejoin TO off` command will simply make merging too expensive:

```
test=# SET enable_mergejoin TO off;
SET
test=# explain SELECT *
      FROM generate_series(1, 100) AS a,
           generate_series(1, 100) AS b
      WHERE a = b;
               QUERY PLAN
-----
Hash Join (cost=22.50..210.00 rows=5000 width=8)
  Hash Cond: (a.a = b.b)
    -> Function Scan on generate_series a
        (cost=0.00..10.00 rows=1000 width=4)
    -> Hash (cost=10.00..10.00 rows=1000 width=4)
        -> Function Scan on generate_series b
            (cost=0.00..10.00 rows=1000 width=4)
(5 rows)
```

Because merging is too expensive, PostgreSQL decided to try a hash join. As you can see, the costs are a bit higher but the plan is still taken as merging is not desired anymore.

What happens if hash joins are turned off as well?:

```
test=# SET enable_hashjoin TO off;
SET
test=# explain SELECT *
      FROM generate_series(1, 100) AS a,
           generate_series(1, 100) AS b
      WHERE a = b;
               QUERY PLAN
-----
Nested Loop (cost=0.01..22510.01 rows=5000 width=8)
  Join Filter: (a.a = b.b)
    -> Function Scan on generate_series a
        (cost=0.00..10.00 rows=1000 width=4)
    -> Function Scan on generate_series b
        (cost=0.00..10.00 rows=1000 width=4)
(4 rows)
```

PostgreSQL will again try something else and come up with a nested loop. The costs of a nested loop are already staggering, but the planner starts to run out of options.

What happens if nested loops are turned off as well?:

```
test=# SET enable_nestloop TO off;
SET
test=# explain SELECT *
      FROM generate_series(1, 100) AS a,
      generate_series(1, 100) AS b
      WHERE a = b;
               QUERY PLAN
-----
Nested Loop (cost=10000000000.00..10000022510.00
              rows=5000 width=8)
  Join Filter: (a.a = b.b)
    -> Function Scan on generate_series a
        (cost=0.00..10.00 rows=1000 width=4)
    -> Function Scan on generate_series b
        (cost=0.00..10.00 rows=1000 width=4)
(4 rows)
```

PostgreSQL will still perform a nested loop. The important part here is that off does not really mean off—it just means treat as a very expensive thing. This is important because otherwise, the query could not be performed.

Which settings are there to influence the planner? The following switches are available:

- `enable_bitmapscan = on`
- `enable_hashagg = on`
- `enable_hashjoin = on`
- `enable_indexscan = on`
- `enable_indexonlyscan = on`
- `enable_material = on`
- `enable_mergejoin = on`
- `enable_nestloop = on`
- `enable_seqscan = on`
- `enable_sort = on`
- `enable_tidscan = on`

While those settings can definitely be beneficial, I want to point out that those tweaks should be handled with care. Only use them to speed up individual queries and do not turn off things globally. Things can turn against you fairly quickly and destroy performance. Therefore, it really makes sense to think twice before changing these parameters.

Understanding genetic query optimization

The result of the planning process is key to achieving superior performance. As shown in this chapter, planning is far from trivial and involves various complex calculations. The more tables are touched by a query, the more complicated planning will become. The more tables there are, the more choices the planner will have. Logically, planning time will increase. At some point, planning will take so long that performing the classical exhaustive search is not feasible anymore. On top of that, the errors made during planning are so great anyway that finding the theoretically best plan does not necessarily lead to the best plan in terms of runtime.

Genetic query optimization (GEQO) can come to the rescue. What is GEQO? The idea is actually stolen from nature and resembles the natural process of evolution.

PostgreSQL will approach the problem just like a traveling salesman problem and encode the possible joins as integer strings. For example, 4-1-3-2 means first join 4 and 1, then 3, and then 2. The numbers represent the relation's IDs.

At the beginning, the genetic optimizer will generate a random set of plans. Those plans are then inspected. The bad ones are discarded and new ones are generated based on the genes of the good ones. This way, potentially even better plans are generated. The process can be repeated as often as desired. At the end of the day, we are left with a plan which is expected to be a lot better than just using a random plan. GEQO can be turned on and off by adjusting the `geqo` variable:

```
test=# SHOW geqo;
      geqo
-----
      on
(1 row)

test=# SET geqo TO off;
SET
```

By default, the `geqo` variable kicks in if a statement exceeds a certain level of complexity, which is controlled by the following variable:

```
test=# SHOW geqo_threshold ;
      geqo_threshold
-----
12
(1 row)
```

If your queries are so large that you start to reach this threshold, it certainly makes sense to play with this setting to see how plans are changed by the planner if you change those variables.

As a general rule, however, I would say that you should try to avoid GEQO as long as you can and try to fix things first by trying to somehow fix the join order using the `join_collapse_limit` variable. Note that every query is different, so it certainly helps to experiment and gain more experience by learning how the planner behaves under different circumstances.



If you want to see what a really crazy join is, consider checking out a talk I gave in Madrid

at: <http://de.slideshare.net/hansjurgenschonig/postgresql-joining-1-million-tables>.

Partitioning data

Given default 8 k blocks, PostgreSQL can store up to 32 TB of data inside a single table. If you compile PostgreSQL with 32 k blocks, you can even put up to 128 TB into a single table. However, large tables like that are not necessarily too convenient anymore and it can make sense to partition tables to make processing easier and, in some cases, a bit faster. Starting with PostgreSQL 10.0, we have improved partitioning, which will offer end users significantly easier handling of data partitioning.

In this chapter, the old means of partitioning as well as the new features available as of PostgreSQL 10.0 will be covered.

Creating partitions

First, I want to focus your attention on the old method to partition data.

Before digging deeper into the advantages of partitioning, I want to show how partitions can be created. The entire thing starts with a parent table:

```
test=# CREATE TABLE t_data (id serial, t date, payload text);
CREATE TABLE
```

In this example, the parent table has three columns. The date column will be used for partitioning but more on that a bit later.

Now that the parent table is in place, the child tables can be created. This is how it works:

```
test=# CREATE TABLE t_data_2016 () INHERITS (t_data);
CREATE TABLE
test=# \d t_data_2016
```

```

                                Table "public.t_data_2016"
  Column | Type          | Modifiers
-----+-----+-----
  id     | integer       | not null default
                                nextval('t_data_id_seq'::regclass)
  t      | date          |
  payload | text          |
Inherits: t_data
```

The table is called `t_data_2016` and inherits from `t_data`. `()` means that no extra columns are added to the child table. As you can see, inheritance means that all columns from the parents are available in the child table. Also note that the `id` column will inherit the sequence from the parent so that all children can share the very same numbering.

Let's create more tables:

```
test=# CREATE TABLE t_data_2015 () INHERITS (t_data);
CREATE TABLE
test=# CREATE TABLE t_data_2014 () INHERITS (t_data);
CREATE TABLE
```

So far, all the tables are identical and just inherit from the parent. However, there is more: child tables can actually have more columns than parents. Adding more fields is simple:

```
test=# CREATE TABLE t_data_2013 (special text) INHERITS (t_data);
CREATE TABLE
```

In this case, a special column has been added. It has no impact on the parent, but just enriches the children and makes them capable of holding more data.

After creating a handful of tables, a row can be added:

```
test=# INSERT INTO t_data_2015 (t, payload)
      VALUES ('2015-05-04', 'some data');
INSERT 0 1
```

The most important thing now is that the parent table can be used to find all the data in the child tables:

```
test=# SELECT * FROM t_data;
 id |      t      | payload
----+-----+-----
  1 | 2015-05-04 | some data
(1 row)
```

Querying the parent allows you to gain access to everything below the parent in a simple and efficient manner.

To understand how PostgreSQL does partitioning, it makes sense to take a look at the plan:

```
test=# EXPLAIN SELECT * FROM t_data;
               QUERY PLAN
-----
Append (cost=0.00..84.10 rows=4411 width=40)
-> Seq Scan on t_data (cost=0.00..0.00 rows=1 width=40)
-> Seq Scan on t_data_2016
    (cost=0.00..22.00 rows=1200 width=40)
-> Seq Scan on t_data_2015
    (cost=0.00..22.00 rows=1200 width=40)
-> Seq Scan on t_data_2014
    (cost=0.00..22.00 rows=1200 width=40)
-> Seq Scan on t_data_2013
    (cost=0.00..18.10 rows=810 width=40)
(6 rows)
```

Actually, the process is quite simple. PostgreSQL will simply unify all tables and show us all the content from all the tables inside and below the partition we are looking at. Note that all tables are independent and are just connected logically through the system catalog.

Applying table constraints

What happens if filters are applied?

```
test=# EXPLAIN SELECT * FROM t_data WHERE t = '2016-01-04';
               QUERY PLAN
-----
Append (cost=0.00..95.12 rows=23 width=40)
-> Seq Scan on t_data (cost=0.00..0.00 rows=1 width=40)
    Filter: (t = '2016-01-04'::date)
-> Seq Scan on t_data_2016 (cost=0.00..25.00 rows=6 width=40)
    Filter: (t = '2016-01-04'::date)
-> Seq Scan on t_data_2015 (cost=0.00..25.00 rows=6 width=40)
    Filter: (t = '2016-01-04'::date)
-> Seq Scan on t_data_2014 (cost=0.00..25.00 rows=6 width=40)
    Filter: (t = '2016-01-04'::date)
-> Seq Scan on t_data_2013 (cost=0.00..20.12 rows=4 width=40)
    Filter: (t = '2016-01-04'::date)
(11 rows)
```

PostgreSQL will apply the filter to all the partitions in the structure. It does not know that the table name is somehow related to the content of the tables. To the database, names are just names and have nothing to do with what you are looking for. This makes sense, of course, as there is no mathematical justification for doing anything else.

The point now is: how can we teach the database that the 2016 table only contains 2016 data, the 2015 table only contains 2015 data, and so on? Table constraints are here to do exactly that. They teach PostgreSQL about the content of those tables and therefore allow the planner to make smarter decisions than before. The feature is called constraint exclusion and helps dramatically to speed up queries in many cases.

The following listing shows how table constraints can be created:

```
test=# ALTER TABLE t_data_2013
      ADD CHECK (t < '2014-01-01');
ALTER TABLE
test=# ALTER TABLE t_data_2014
      ADD CHECK (t >= '2014-01-01' AND t < '2015-01-01');
ALTER TABLE
test=# ALTER TABLE t_data_2015
      ADD CHECK (t >= '2015-01-01' AND t < '2016-01-01');
ALTER TABLE
test=# ALTER TABLE t_data_2016
      ADD CHECK (t >= '2016-01-01' AND t < '2017-01-01');
ALTER TABLE
```

For each table, a `CHECK` constraint can be added.



PostgreSQL will only create the constraint if all the data in those tables is perfectly correct and if every single row satisfies the constraint. In contrast to MySQL, constraints in PostgreSQL are taken seriously and honored under any circumstances.

In PostgreSQL, those constraints can overlap--this is not forbidden and can make sense in some cases. However, it is usually better to have non-overlapping constraints because PostgreSQL has the option to prune more tables.

Here is what happens after adding those table constraints:

```
test=# EXPLAIN SELECT * FROM t_data WHERE t = '2016-01-04';
               QUERY PLAN
-----
Append (cost=0.00..25.00 rows=7 width=40)
-> Seq Scan on t_data (cost=0.00..0.00 rows=1 width=40)
    Filter: (t = '2016-01-04'::date)
-> Seq Scan on t_data_2016 (cost=0.00..25.00 rows=6 width=40)
    Filter: (t = '2016-01-04'::date)
(5 rows)
```

The planner will be able to remove many of the tables from the query and only keep those which potentially contain the data. The query can greatly benefit from a shorter and more efficient plan. In particular, if those tables are really large, removing them can boost speed considerably.

Modifying inherited structures

Once in a while, data structures have to be modified. The `ALTER TABLE` clause is here to do exactly that. The question is: how can partitioned tables be modified?

Basically, all you have to do is tackle the parent table and add or remove columns. PostgreSQL will automatically propagate those changes through to the child tables and ensure that changes are made to all the relations, as follows:

```
test=# ALTER TABLE t_data ADD COLUMN x int;
ALTER TABLE
test=# \d t_data_2016
               Table "public.t_data_2016"
  Column  |  Type  | Modifiers
-----+-----+-----
      id | integer | not null default
```

```

                                nextval('t_data_id_seq'::regclass)
    t |      date |
payload |      text |
    x | integer |
Check constraints:
    "t_data_2016_t_check"
CHECK (t >= '2016-01-01'::date AND t < '2017-01-01'::date)
Inherits: t_data

```

As you can see, the column is added to the parent and automatically added to the child table here.

Note that this works for columns, and so on. Indexes are a totally different story. In an inherited structure, every table has to be indexed separately. If you add an index to the parent table, it will only be present on the parent—it won't be deployed on those child tables. Indexing all those columns in all those tables is your task and PostgreSQL is not going to make those decisions for you. Of course, this can be seen as a feature or as a limitation. On the upside, you could say that PostgreSQL gives you all the flexibility to index things separately and therefore potentially more efficiently. However, people might also argue that deploying all those indexes one by one is a lot more work.

Moving tables in and out of partitioned structures

Suppose you have an inherited structure. Data is partitioned by date and you want to provide the most recent years to the end user. At some point, you might want to remove some data from the scope of the user without actually touching it. You might want to put data into some sort of archive or something.

PostgreSQL provides a simple means to achieve exactly that. First, a new parent can be created:

```

test=# CREATE TABLE t_history (LIKE t_data);
CREATE TABLE

```

The `LIKE` keyword allows you to create a table which has exactly the same layout as the `t_data` table. If you have forgotten which columns the `t_data` table actually has, this might come in handy as it saves you a lot of work. It is also possible to include indexes, constraints, and defaults.

Then, the table can be moved away from the old parent table and put below the new one. Here is how it works:

```
test=# ALTER TABLE t_data_2013 NO INHERIT t_data;
ALTER TABLE
test=# ALTER TABLE t_data_2013 INHERIT t_history;
ALTER TABLE
```

The entire process can of course be done in a single transaction to assure that the operation stays atomic.

Cleaning up data

One advantage of partitioned tables is the ability to clean data up quickly. Suppose that we want to delete an entire year. If data is partitioned accordingly, a simple `DROP TABLE` clause can do the job:

```
test=# DROP TABLE t_data_2014;
DROP TABLE
```

As you can see, dropping a child table is easy. But what about the parent table? There are depending objects and therefore PostgreSQL naturally errors out to make sure that nothing unexpected happens:

```
test=# DROP TABLE t_data;
ERROR: cannot drop table t_data because other objects depend on it
DETAIL: default for table t_data_2013 column id depends on
        sequence t_data_id_seq
table t_data_2016 depends on table t_data
table t_data_2015 depends on table t_data
HINT: Use DROP ... CASCADE to drop the dependent objects too.
```

The `DROP TABLE` clause will warn us that there are depending objects and refuses to drop those tables. The `CASCADE` clause is needed to force PostgreSQL to actually remove those objects, along with the parent table:

```
test=# DROP TABLE t_data CASCADE;
NOTICE: drop cascades to 3 other objects
DETAIL: drop cascades to default for table t_data_2013 column id drop
cascades to table t_data_2016
drop cascades to table t_data_2015
DROP TABLE
```

Understanding PostgreSQL 10.0 partitioning

For many years, the PostgreSQL community has been working on built-in partitioning. Finally, PostgreSQL 10.0 offers the first implementation of in-core partitioning, which will be covered in this chapter. For now, the partitioning functionality is still pretty basic. However, a lot of infrastructure for future improvements is already in place.

To show you how partitioning works, I have compiled a simple example featuring range partitioning:

```
CREATE TABLE data (  
    payload integer  
) PARTITION BY RANGE (payload);  
  
CREATE TABLE negatives PARTITION  
    OF data FOR VALUES FROM (MINVALUE) TO (0);  
CREATE TABLE positives PARTITION  
    OF data FOR VALUES FROM (0) TO (MAXVALUE);
```

In this example, one partition will hold all negative values while the other one will take care of positive values. While creating the parent table, you can simply specify which way you want to partition data.



In PostgreSQL 10.0, there is range partitioning and list partitioning. Support for hash partitioning and the like might be available as soon as PostgreSQL 11.0.

Once the parent table has been created, it is already time to create the partitions. To do that, the `PARTITION OF` clause has been added. At this point, there are still some limitations. The most important one is that a tuple (= a row) cannot move from one partition to the other, for example:

```
UPDATE data SET payload = -10 WHERE id = 5
```

If there were rows satisfying this condition, PostgreSQL would simply error out and refuse to change the value. However, in case of a good design, it is a bad idea to change the partitioning key anyway. Also, keep in mind that you have to think about indexing each partition.

Adjusting parameters for good query performance

Writing good queries is the first step to reaching good performance. Without a good query, you will most likely suffer from bad performance. Writing good and intelligent code will therefore give you the greatest edge possible. Once your queries have been optimized from a logical and semantical point of view, good memory settings can provide you with a final nice speedup. In this section, you will learn what more memory can do for you and how PostgreSQL can use it for your benefit. Again, this section assumes that we are using single-core queries to make the plans more readable. To ensure that there is always just one core at work, use the following command:

```
test=# SET max_parallel_workers_per_gather TO 0;
SET
```

Here is a simple example demonstrating what memory parameters can do for you:

```
test=# CREATE TABLE t_test (id serial, name text);
CREATE TABLE
test=# INSERT INTO t_test (name)
      SELECT 'hans' FROM generate_series(1, 100000);
INSERT 0 100000
test=# INSERT INTO t_test (name)
      SELECT 'paul' FROM generate_series(1, 100000);
INSERT 0 100000
```

1 million rows containing `hans` will be added to the table. Then 1 million rows containing `paul` are loaded. Altogether, there will be 2 million unique IDs but just two different names.

Let us run a simple query now, using PostgreSQL's default memory settings:

```
test=# SELECT name, count(*) FROM t_test GROUP BY 1;
 name | count
-----+-----
 hans | 100000
 paul | 100000

(2 rows)
```

Two rows will be returned, which should not come as a surprise. The important thing here is not the result, but what PostgreSQL is doing behind the scenes:

```
test=# EXPLAIN ANALYZE SELECT name, count(*)
      FROM t_test
      GROUP BY 1;
               QUERY PLAN
-----
HashAggregate (cost=4082.00..4082.01 rows=1 width=13)
  (actual time=51.448..51.448 rows=2 loops=1)
    Group Key: name
    -> Seq Scan on t_test
        (cost=0.00..3082.00 rows=200000 width=5)
        (actual time=0.007..14.150 rows=200000 loops=1)
  Planning time: 0.032 ms
  Execution time: 51.471 ms
(5 rows)
```

PostgreSQL figured out that the number of groups is actually very small. Therefore, it creates a hash and adds one hash entry per group and starts to count. Due to the low number of groups, the hash is really small and PostgreSQL can quickly do the count by incrementing the numbers for each group.

What happens if we group by ID and not by name? The number of groups will skyrocket:

```
test=# EXPLAIN ANALYZE SELECT id, count(*) FROM t_test GROUP BY 1;
               QUERY PLAN
-----
GroupAggregate (cost=23428.64..26928.64 rows=200000 width=12)
  (actual time=97.128..154.205 rows=200000 loops=1)
    Group Key: id
    -> Sort (cost=23428.64..23928.64 rows=200000 width=4)
        (actual time=97.120..113.017 rows=200000 loops=1)
        Sort Key: id
        Sort Method: external sort Disk: 2736kB
    -> Seq Scan on t_test
        (cost=0.00..3082.00 rows=200000 width=4)
        (actual time=0.017..19.469 rows=200000 loops=1)
  Planning time: 0.128 ms
  Execution time: 160.589 ms
(8 rows)
```

PostgreSQL figures that the number of groups is now a lot larger and quickly changes its strategy. The problem is that a hash containing so many entries does not fit into memory:

```
test=# SHOW work_mem ;
      work_mem
-----
      4MB
(1 row)
```

The `work_mem` variable governs the size of the hash used by the `GROUP BY` clause. As there are too many entries, PostgreSQL has to find a strategy which does not require holding the entire dataset in memory. The solution is to sort the data by ID and group it. Once the data is sorted, PostgreSQL can move down the list and form one group after the other. If the first type of value is counted, the partial result is read and can be emitted. Then, the next group can be processed. Once the value in the sorted list changes when moving down, it will never show up again; thus, the system knows that a partial result is ready.

To speed up the query, a higher value for the `work_mem` variable can be set on the fly (and, of course, globally):

```
test=# SET work_mem TO '1 GB';
SET
```

The plan will now again feature a fast and efficient hash aggregate:

```
test=# EXPLAIN ANALYZE SELECT id, count(*) FROM t_test GROUP BY 1;
              QUERY PLAN
-----
HashAggregate (cost=4082.00..6082.00 rows=200000 width=12)
  (actual time=76.967..118.926 rows=200000 loops=1)
    Group Key: id
    -> Seq Scan on t_test
        (cost=0.00..3082.00 rows=200000 width=4)
        (actual time=0.008..13.570 rows=200000 loops=1)
    Planning time: 0.073 ms
    Execution time: 126.456 ms
(5 rows)
```

PostgreSQL knows (or at least assumes) that data will fit into memory and switch to the faster plan. As you can see, the execution time is lower. The query won't be as fast as in the `GROUP BY` name case because many more hash values have to be calculated but, you will be able to see a nice and reliable benefit in the vast majority of all cases.

Speeding up sorting

The `work_mem` variable does not only speed up grouping. It can also have a very nice impact on simple things such as sorting, which is an essential mechanism mastered by every database system in the world.

The following query shows a simple operation using the default setting of 4 MB:

```
test=# SET work_mem TO default;
SET
test=# EXPLAIN ANALYZE SELECT * FROM t_test ORDER BY name, id;
               QUERY PLAN
-----
Sort (cost=24111.14..24611.14 rows=200000 width=9)
    (actual time=219.298..235.008 rows=200000 loops=1)
    Sort Key: name, id
    Sort Method: external sort Disk: 3712kB
    -> Seq Scan on t_test
        (cost=0.00..3082.00 rows=200000 width=9)
        (actual time=0.006..13.807 rows=200000 loops=1)
Planning time: 0.064 ms
Execution time: 241.375 ms
(6 rows)
```

PostgreSQL needs 13.8 milliseconds to read the data and over 200 milliseconds to sort the data. Due to the low amount of memory available, sorting has to be performed using temporary files. The external sort Disk method needs only small amounts of RAM, but has to send intermediate data to a comparatively slow storage device, which of course leads to poor throughput.

Increasing the `work_mem` variable setting will make PostgreSQL use more memory for sorting:

```
test=# SET work_mem TO '1 GB';
SET
test=# EXPLAIN ANALYZE SELECT * FROM t_test ORDER BY name, id;
               QUERY PLAN
-----
Sort (cost=20691.64..21191.64 rows=200000 width=9)
    (actual time=36.481..47.899 rows=200000 loops=1)
    Sort Key: name, id
    Sort Method: quicksort Memory: 15520kB
    -> Seq Scan on t_test
        (cost=0.00..3082.00 rows=200000 width=9)
        (actual time=0.010..14.232 rows=200000 loops=1)
Planning time: 0.037 ms
```

```
Execution time: 55.520 ms
(6 rows)
```

As there is enough memory now, the database will do all the sorting in memory and therefore speed up the process dramatically. The sort takes just 33 milliseconds now, which is a seven-time improvement compared to the query we had previously. More memory will lead to faster sorting and will speed up the system.

Up til now, you have already seen two mechanisms to sort data: external sort Disk and quicksort Memory. In addition to those two mechanisms, there is also a third algorithm, which is top-N heapsort Memory. It can be used to provide you with only the top N rows:

```
test=# EXPLAIN ANALYZE SELECT * FROM t_test ORDER BY name, id LIMIT 10;
               QUERY PLAN
-----
Limit  (cost=7403.93..7403.95 rows=10 width=9)
  (actual time=31.837..31.838 rows=10 loops=1)
    -> Sort (cost=7403.93..7903.93 rows=200000 width=9)
        (actual time=31.836..31.837 rows=10 loops=1)
        Sort Key: name, id
        Sort Method: top-N heapsort Memory: 25kB
        -> Seq Scan on t_test
            (cost=0.00..3082.00 rows=200000 width=9)
            (actual time=0.011..13.645 rows=200000 loops=1)
Planning time: 0.053 ms
Execution time: 31.856 ms
(7 rows)
```

The algorithm is lightning fast and the entire query will be done in just over 30 milliseconds. The sorting part is now only 18 milliseconds and is therefore almost as fast as reading the data in the first place.

Note that the `work_mem` variable is allocated per operation. It can theoretically happen that a query needs the `work_mem` variable more than once. It is not a global setting--it is really per operation. Therefore, you have to set it in a careful way.

There is one thing you should keep in mind: many books claim that setting the `work_mem` variable too high on an OLTP system might cause your server to run out of memory. Yes, if 1,000 people sort 100 MB at the same time, this can result in memory failures. However, do you expect the disk to be able to handle that? I doubt it. The solution can only be: stop doing stupid things. Sorting 100 MB 1,000 times concurrently is not what should happen in an OLTP system anyway. Consider deploying proper indexes, writing better queries, or simply rethinking your requirements. Under any circumstances, sorting so much data so often concurrently is a bad idea-stop it before those things stop your application.

Speeding up administrative tasks

There are more operations which actually have to do some sorting or memory allocation of some kind. The administrative ones such as the `CREATE INDEX` clause do not rely on the `work_mem` variable, but use the `maintenance_work_mem` variable instead. Here is how it works:

```
test=# SET maintenance_work_mem TO '1 MB';
SET
test=# timing
Timing is on.
test=# CREATE INDEX idx_id ON t_test (id);
CREATE INDEX
Time: 104.268 ms
```

As you can see, creating an index on 2 million rows takes around 100 milliseconds, which is really slow. Therefore, the `maintenance_work_mem` variable can be used to speed up sorting, which is essentially what the `CREATE INDEX` clause does:

```
test=# SET maintenance_work_mem TO '1 GB';
SET
test=# CREATE INDEX idx_id2 ON t_test (id);
CREATE INDEX
Time: 46.774 ms
```

The speed has now doubled just because sorting has been improved so much.

There are more administrative jobs that can benefit from more memory. The most prominent ones are the `VACUUM` clause (to clean out indexes) and `ALTER TABLE` clause. The rules for the `maintenance_work_mem` variable are the same as for the `work_mem` variable. The setting is per operation and only the required memory is allocated on the fly.

Summary

In this chapter, a number of query optimizations have been discussed. You have learned about the optimizer and about various internal optimizations, such as constant folding, view inlining, joins, and a lot more. All those optimizations contribute to good performance and help to speed things up considerably.

After this introduction to optimizations, Chapter 7, *Writing Stored Procedures*, will be about stored procedures. You will see the options PostgreSQL has to handle user-defined code.

7

Writing Stored Procedures

In *Chapter 6, Optimizing Queries for Good Performance*, you learned a lot about the optimizer as well as optimizations going on in the system. This chapter is going to be about stored procedures and how to use them efficiently and easily. You will learn what a stored procedure is made of, which languages are available, and how you can speed things up nicely. On top of that, you will be introduced to some of the more advanced features of PL/pgSQL.

The following topics will be covered:

- Deciding on the right language
- How stored procedures are executed
- Advanced features of PL/pgSQL
- Packaging up extensions
- Optimizing for good performance
- Configuring function parameters

At the end of the chapter, you will be able to write good and efficient procedures.

Understanding stored procedure languages

When it comes to stored procedures, PostgreSQL differs quite significantly from other database systems. Most database engines force you to use a certain programming language to write server-side code. Microsoft SQL Server offers Transact-SQL, while Oracle encourages you to use PL/SQL. PostgreSQL does not force you to use a certain language, but allows you to decide on what you know best and what you like best.

The reason PostgreSQL is so flexible is actually quite interesting in a historical sense too. Many years ago, one of the most well-known PostgreSQL developers, Jan Wieck, who had written countless patches back in its early days, came up with the idea of using TCL as the server-side programming language. The trouble was simple--nobody wanted to use TCL and nobody wanted to have this stuff in the database engine. The solution to the problem was to make the language interface so flexible that basically any language can be integrated with PostgreSQL easily. Then, the `CREATE LANGUAGE` clause was born:

```
test=# \h CREATE LANGUAGE
Command:      CREATE LANGUAGE
Description:  Define a new procedural language
Syntax:
CREATE [ OR REPLACE ] [ PROCEDURAL ] LANGUAGE name
CREATE [ OR REPLACE ] [ TRUSTED ] [ PROCEDURAL ]
    LANGUAGE name HANDLER call_handler
    [ INLINE inline_handler ] [ VALIDATOR valfunction ]
```

Nowadays, many different languages can be used to write stored procedures. The flexibility added to PostgreSQL back in the early days has really paid off, and so you can choose from a rich set of programming languages.

How exactly does PostgreSQL handle languages? If you take a look at the syntax of the `CREATE LANGUAGE` clause, you will see a couple of keywords:

- **HANDLER:** This function is actually the glue between PostgreSQL and any external language you want to use. It is in charge of mapping PostgreSQL data structures to whatever is needed by the language and helps to pass the code around.
- **VALIDATOR:** This is the policeman of the infrastructure. If it is available, it will be in charge of delivering tasty syntax errors to the end user. Many languages are able to parse the code before actually executing it. PostgreSQL can use that and tell you whether a function is correct or not when you create it. Unfortunately, not all languages can do this, so in some cases, you will still be left with problems showing up at runtime.
- **INLINE:** If it is present, PostgreSQL will be able to run anonymous code blocks utilizing this handler function.

The anatomy of a stored procedure

Before actually digging into a specific language, I want to talk a bit about the anatomy of a typical stored procedure. For demo purposes, I have written a function that just adds up two numbers:

```
test=# CREATE OR REPLACE FUNCTION mysum(int, int)
      RETURNS int AS
      '
        SELECT $1 + $2;
      ' LANGUAGE 'sql';
CREATE FUNCTION
```

The first thing you can see is that the procedure is written in SQL. PostgreSQL has to know which language we are using, so we have to specify that in the definition. Note that the code of the function is passed to PostgreSQL as a string ('). That is somewhat noteworthy because it allows a function to become a black box to the execution machinery. In other database engines, the code of the function is not a string, but is directly attached to the statement. This simple abstraction layer is what gives the PostgreSQL function manager all its power.

Inside the string, you can basically use all that the programming language of your choice has to offer. In my example, I am simply adding up two numbers passed to the function. For this example, two integer variables are in use. The important part here is that PostgreSQL provides you with function overloading. In other words, the `mysum(int, int)` function is not the same as the `mysum(int8, int8)` function. PostgreSQL sees these things as two distinct functions. Function overloading is a nice feature; however, you have to be very careful not to accidentally deploy too many functions if your parameter list happens to change from time to time. Always make sure that functions that are not needed anymore are really deleted.



The `CREATE OR REPLACE FUNCTION` clause will not change the parameter list. You can, therefore, use it only if the signature does not change. It will either error out or simply deploy a new function.

Let's run the function:

```
test=# SELECT mysum(10, 20);
      mysum
-----
      30
(1 row)
```

The result is not really surprising.

Introducing dollar quoting

Passing code to PostgreSQL as a string is very flexible. However, using single quotes can be an issue. In many programming languages, single quotes show up frequently. To be able to use quotes, people have to escape them when passing the string to PostgreSQL. For many years, this has been the standard procedure. Fortunately, those old times have passed by and new means to pass the code to PostgreSQL are available:

```
test=# CREATE OR REPLACE FUNCTION mysum(int, int)
      RETURNS int AS
      $$
          SELECT $1 + $2;
      $$ LANGUAGE 'sql';
CREATE FUNCTION
```

The solution to the problem of quoting strings is called dollar quoting. Instead of using quotes to start and end strings, you can simply use `$$`. Currently, I am only aware of two languages that have assigned a meaning to `$$`. In Perl as well as in bash scripts, `$$` represents the process ID. To overcome even this little obstacle, you can use `$` almost anything `$` to start and end the string. The following example shows how that works:

```
test=# CREATE OR REPLACE FUNCTION mysum(int, int) RETURNS int AS
      $body$
          SELECT $1 + $2;
      $body$ LANGUAGE 'sql';
CREATE FUNCTION
```

All this flexibility allows you to really overcome the problem of quoting once and for all. As long as the start string and the end string match, there won't be any problems left.

Making use of anonymous code blocks

So far, you have learned to write the most simplistic stored procedures possible, and you have learned to execute code. However, there is more to code execution than just full-blown stored procedures. In addition to full-blown procedures, PostgreSQL allows the use of anonymous code blocks. The idea is to run code that is needed only once. This kind of code execution is especially useful to deal with administrative tasks. Anonymous code blocks don't take parameters and are not permanently stored in the database as they don't have a name anyway.

Here is a simple example:

```
test=# DO
$$
    BEGIN
        RAISE NOTICE 'current time: %', now();
    END;
$$ LANGUAGE 'plpgsql';
NOTICE: current time: 2016-12-12 15:25:50.678922+01
CONTEXT: PL/pgSQL function inline_code_block line 3 at RAISE
DO
```

In this example, the code only issues a message and quits. Again, the code block has to know which language it uses. The string is again passed to PostgreSQL using simple dollar quoting.

Using functions and transactions

As you know, everything that PostgreSQL exposes in userland is a transaction. The same, of course, applies if you are writing stored procedures. The procedure is always part of the transaction you are in. It is not autonomous—it is just like an operator or any other operation.

Here is an example:

```
test=# SELECT now(), mysum(id, id) FROM generate_series(1, 3) AS id;
```

now	mysum
2017-10-12 15:54:32.287027+01	2
2017-10-12 15:54:32.287027+01	4
2017-10-12 15:54:32.287027+01	6

(3 rows)

All three function calls happen in the same transaction. This is important to understand because it implies that you cannot do too much transactional flow control inside a function. Suppose the second function call commits. What happens in such a case anyway? It cannot work.

However, Oracle has a mechanism that allows for autonomous transactions. The idea is that even if a transaction rolls back, some parts might still be needed and should be kept. The classic example is as follows:

1. Start a function to look up secret data
2. Add a log line to the document that somebody has modified this important secret data
3. Commit the log line but roll back the change
4. You still want to know that somebody attempted to change data

To solve problems like this one, autonomous transactions can be used. The idea is to be able to commit a transaction inside the main transaction independently. In this case, the entry in the log table will prevail while the change will be rolled back.

As of PostgreSQL 10.0, autonomous transactions are not happening. However, I have already seen patches floating around that implement this feature. We will see when these features make it to the core.

To give you an impression of how things will most likely work, here is a code snippet based on the first patches:

```
...
AS
$$
DECLARE
    PRAGMA AUTONOMOUS_TRANSACTION;
BEGIN
    FOR i IN 0..9 LOOP
        START TRANSACTION;
```

```
INSERT INTO test1 VALUES (i);
IF i % 2 = 0 THEN
    COMMIT;
ELSE
    ROLLBACK;
END IF;
END LOOP;
RETURN 42;
END;
$$;
...
```

The point in this example is that we can decide on the fly whether to commit or to roll back the autonomous transaction.

Understanding various stored procedure languages

As already stated previously in this chapter, PostgreSQL gives you the power to write stored procedures in various languages. The following options are available and shipped along with the PostgreSQL core:

- SQL
- PL/pgSQL
- PL/Perl and PL/PerlU
- PL/Python
- PL/Tcl and PL/TclU

SQL is the obvious choice to write stored procedures, and it should be used whenever possible as it gives the most freedom to the optimizer. However, if you want to write slightly more complex code, PL/pgSQL might be the language of your choice. It offers flow control and a lot more. In this chapter, some of the more advanced and less known features of PL/pgSQL will be shown (this chapter is not meant to be a complete tutorial on PL/pgSQL).

Then, the core contains code to run stored procedures in Perl. Basically, the logic is the same here. Code will be passed as a string and executed by Perl. Remember that PostgreSQL does not speak Perl--it merely has the code to pass things on to the external programming language.

Maybe you have noticed that Perl and TCL are available in two flavors: trusted (PL/Perl and PL/TCL) and untrusted (PL/PerlU and PL/TCLU). The difference between a trusted and an untrusted language is actually an important one. In PostgreSQL, a language is loaded directly into the database connection. Therefore, the language is able to do quite a lot of nasty stuff. To get rid of security problems, the concept of trusted languages has been invented. The idea is that a trusted language is restricted to the very core of the language. It is not possible to do the following:

- Include libraries
- Open network sockets
- Perform system calls of any kind (opening files and so on)

Perl offers something called taint mode, which is used to implement this feature in PostgreSQL. Perl will automatically restrict itself to trusted mode and error out if a security violation is about to happen. In untrusted mode, everything is possible, and therefore, only the superuser is allowed to run untrusted code.

If you want to run trusted as well as untrusted code, you have to activate both languages: `plperl` and `plperlU` (respectively, `pltcl` and `pltclU`).

Python is currently only available as an untrusted language; therefore, administrators have to be very careful when it comes to security in general, as a stored procedure running in untrusted mode can bypass all security mechanisms enforced by PostgreSQL. Just keep in mind that Python is running as part of your database connection and is in no way responsible for security.

Introducing PL/pgSQL

Let's get started with the most awaited topic, and I am sure you will love to know more about it.

In this section, you will be introduced to some of the more advanced features of PL/pgSQL, which are important for writing proper and highly efficient code. Note that this is not a beginner's introduction to programming or PL/pgSQL in general.

Handling quoting

One of the most important things in database programming is quoting. If you are not using proper quoting, you will surely get into trouble with SQL injection and open, unacceptable security holes.

What is SQL injection? Consider the following example:

```
CREATE FUNCTION broken(text) RETURNS void AS
$$
DECLARE
    v_sql text;
BEGIN
    v_sql := 'SELECT schemaname
              FROM pg_tables
              WHERE tablename = ''' || $1 || ''';
    RAISE NOTICE 'v_sql: %', v_sql;
    RETURN;
END;
$$ LANGUAGE 'plpgsql';
```

In this example, the SQL code is simply pasted together without ever worrying about security. All I am doing here is using the `||` operator to concatenate strings. This works fine if people run normal queries:

```
SELECT broken('t_test');
```

However, we have to be prepared for bad people all the time. Consider the following example:

```
SELECT broken(''; DROP TABLE t_test;');
```

Running the function with this parameter will give us a nice little problem:

```
NOTICE: v_sql: SELECT schemaname FROM pg_tables
WHERE tablename = ''; DROP TABLE t_test; '
CONTEXT: PL/pgSQL function broken(text) line 6 at RAISE
broken
-----
(1 row)
```

Dropping a table when you just want to do a lookup is not a desirable thing to do. It is definitely not acceptable to make the security of your application depend on the parameters passed to your statements.

To avoid SQL injection, PostgreSQL offers various functions; these should be used at all times to ensure that your security stays intact:

```
test=# SELECT quote_literal(E'o''reilly'), quote_ident(E'o''reilly');
 quote_literal | quote_ident 
-----+-----
 'o''reilly'   | "o'reilly" (1 row)
```

The `quote_literal` function will escape a string in such a way that nothing bad can happen anymore. It will add all the quotes around the string and escape problematic characters inside the string. Therefore, there is no longer any need to start and end the string manually.

The second function shown here is `quote_ident`. It can be used to quote object names properly. Note that double quotes are used, which is exactly what is needed to handle table names and the like:

```
test=# CREATE TABLE "Some stupid name" ("ID" int);
CREATE TABLE
test=# \d "Some stupid name" Table "public.Some stupid name"
 Column | Type   | Modifiers 
-----+-----+-----
 ID     | integer |
```

Normally, all table names in PostgreSQL are lowercase. However, if double quotes are used, object names can contain capitalized letters. In general, it is not a good idea to do this kind of trickery as you have to use double quotes all the time in this case, which can be a bit inconvenient.

After a basic introduction to quoting, it is important to take a look at how `NULL` values are handled:

```
test=# SELECT quote_literal(NULL);
 quote_literal 
-----
(1 row)
```

If you call the `quote_literal` function on a `NULL` value, it will simply return `NULL`. There is no need to take care of quoting in this case too.

PostgreSQL provides even more functions to explicitly take care of a NULL value:

```
test=# SELECT quote_nullable(123), quote_nullable(NULL);
 quote_nullable | quote_nullable 
-----+-----
      '123'      | NULL (1 row)
```

It is not only possible to quote strings and object names. It is also possible to use PL/pgSQL onboard means to format and prepare entire queries. The beauty here is that you can use the format function to add parameters to a statement. Here is how it works:

```
CREATE FUNCTION simple_format() RETURNS text AS
$$
DECLARE
    v_string text;
    v_result text;
BEGIN
    v_string := format('SELECT schemaname|| ' ' . ' || tablename
                      FROM pg_tables
                      WHERE %I = $1
                      AND %I = $2', 'schemaname', 'tablename');
    EXECUTE v_string USING 'public', 't_test' INTO v_result;
    RAISE NOTICE 'result: %', v_result;
    RETURN v_string;
END;
$$ LANGUAGE 'plpgsql';
```

The names of the fields are passed to the format function. Finally, the USING clause of the EXECUTE statement is here to add the parameters to the query, which is then executed. Again, the beauty here is that no SQL injection can happen.

Here is what happens:

```
test=# SELECT simple_format ();
NOTICE: result: public .t_test
              simple_format
-----+-----
SELECT schemaname|| ' ' . ' || tablename      +
                      FROM pg_tables          +
                      WHERE schemaname = $1+
                      AND tablename = $2
(1 row)
```

As you can see, the debug message correctly displays the table, including the schema, and correctly returns the query.

Managing scopes

After dealing with quoting and basic security (SQL injection) in general, I want to shift your focus to another important topic: scopes.

Just like most popular programming languages I am aware of, PL/pgSQL uses variables depending on their context. Variables are defined in the `DECLARE` statement of a function. However, PL/pgSQL allows you to nest a `DECLARE` statement:

```
CREATE FUNCTION scope_test () RETURNS int AS
$$
DECLARE
    i int := 0;
BEGIN
    RAISE NOTICE 'i1: %', i;
    DECLARE
        i int;
        BEGIN
            RAISE NOTICE 'i2: %', i;
        END;
    RETURN i;
END;
$$ LANGUAGE 'plpgsql';
```

In the `DECLARE` statement, a variable `i` is defined and a value is assigned to it. Then, `i` is displayed. The output will, of course, be 0. Then, a second `DECLARE` statement starts. It contains an additional incarnation of `i`, which is not assigned a value. Therefore, the value will be `NULL`. Note that PostgreSQL will now display the inner `i`. Here is what happens:

```
test=# SELECT scope_test();
NOTICE:  i1: 0
NOTICE:  i2: <NULL>
 scope_test
-----
      0
(1 row)
```

As expected, the debug messages will show 0 and `NULL`.



PostgreSQL allows you to do all kinds of trickery. However, it is strongly recommended to keep your code simple and easy to read.

Understanding advanced error handling

In every programming language, in every program, and in every module, error handling is an important thing. Everything is expected to go wrong once in a while, and therefore it is vital and of key importance to handle errors properly and professionally. In PL/pgSQL, you can use `EXCEPTION` blocks to handle errors. The idea is that if the `BEGIN` block does something wrong, the `EXCEPTION` block will take care of it and handle the problem correctly. Just like many other languages, such as Java, you can react on different types of errors and catch them separately.

In the following example, the code might run into a division by zero problem. The goal is to catch this error and react accordingly:

```
CREATE FUNCTION error_test1(int, int) RETURNS int AS
$$
BEGIN
    RAISE NOTICE 'debug message: % / %', $1, $2;
    BEGIN
        RETURN $1 / $2;
    EXCEPTION
        WHEN division_by_zero THEN
            RAISE NOTICE 'division by zero detected: %', sqlerrm;
        WHEN others THEN
            RAISE NOTICE 'some other error: %', sqlerrm;
    END;
    RAISE NOTICE 'all errors handled';
    RETURN 0;
END;
$$ LANGUAGE 'plpgsql';
```

The `BEGIN` block can clearly throw an error. However, the `EXCEPTION` block catches the error we are looking at and also takes care of all other potential problems that can unexpectedly pop up.

Technically, this is more or less the same as a savepoint, and therefore the error does not cause the entire transaction to fail completely. Only the block causing the error will be subject to a mini rollback.

By inspecting the `sqlerrm` variable, you can also have direct access to the error message itself. Let us run the code:

```
test=# SELECT error_test1(9, 0);
NOTICE:  debug message: 9 / 0
NOTICE:  division by zero detected: division by zero
NOTICE:  all errors handled
 error_test1
-----
          0
(1 row)
```

PostgreSQL catches the exception and shows the message in the `EXCEPTION` block. PostgreSQL is already kind enough to tell us in which line the error has happened, which makes it a lot easier to debug and fix the code if it is broken.

In some cases, it can also make sense to raise your own exception. As you might expect, this is easy to do:

```
RAISE unique_violation
USING MESSAGE = 'Duplicate user ID: ' || user_id;
```

On top of what you have already seen, PostgreSQL offers many predefined error codes and exceptions. The following page contains a complete list of those error messages:

<https://www.postgresql.org/docs/10/static/errcodes-appendix.html>.

Making use of GET DIAGNOSTICS

Many of you who have used Oracle in the past might be familiar with the `GET DIAGNOSTICS` clause. The idea behind the `GET DIAGNOSTICS` clause is to allow users to see what is going on in the system. While the syntax might appear a bit strange to people who are used to modern code, it is still a valuable tool you can use to make your applications better.

From my point of view, there are two main tasks that the `GET DIAGNOSTICS` clause can be used for:

- Inspecting the row count
- Fetching context information and getting a backtrace

Inspecting the row count is definitely something you will need during everyday programming. Extracting context information will be useful if you want to debug applications.

The following example shows how the `GET DIAGNOSTICS` clause can be used inside your code:

```
CREATE FUNCTION get_diag() RETURNS int AS
$$
DECLARE
    rc int;
    _sqlstate text;
    _message text;
    _context text;
BEGIN
    EXECUTE 'SELECT * FROM generate_series(1, 10)';
    GET DIAGNOSTICS rc = ROW_COUNT;
    RAISE NOTICE 'row count: %', rc;
    SELECT rc / 0;
EXCEPTION
    WHEN OTHERS THEN
        GET STACKED DIAGNOSTICS
            _sqlstate = returned_sqlstate,
            _message = message_text,
            _context = pg_exception_context;
        RAISE NOTICE 'sqlstate: %, message: %, context: [%]',
            _sqlstate,
            _message,
            replace( _context, E'n', ' <- ' );
    RETURN rc;
END;
$$ LANGUAGE 'plpgsql';
```

The first thing after declaring those variables is to execute a SQL statement and ask the `GET DIAGNOSTICS` clause for a row count, which is then displayed in a debug message. Then, the function forces PL/pgSQL to error out. Once this happens, I use the `GET DIAGNOSTICS` clause to extract information from the server to display it.

Here is what happens:

```
test=# SELECT get_diag();
NOTICE: row count: 10
CONTEXT: PL/pgSQL function get_diag() line 12 at RAISE
NOTICE: sqlstate: 22012,
message: division by zero,
context: [SQL statement "SELECT rc / 0"
<- PL/pgSQL function get_diag() line 14 at
SQL statement]
CONTEXT: PL/pgSQL function get_diag() line 22 at RAISE
get_diag
-----
```

```
10
(1 row)
```

As you can see, the `GET DIAGNOSTICS` clause gives us quite detailed information about what is going on in the system.

Using cursors to fetch data in chunks

If you execute SQL, the database will calculate the result and send it to your application. Once the entire result set has been sent to the client, the application can continue to do its job. The problem is just this: what happens if the result set is so large that it does not fit into the memory anymore? What if the database returns 10 billion rows? The client application usually cannot handle so much data at once, and actually, it should'nt. The solution to the problem is a cursor. The idea behind a cursor is that data is generated only when it is needed (when `FETCH` is called). Therefore, the application can already start to consume data while it is actually being generated by the database. On top of that, the memory required to perform an operation is a lot lower.

When it comes to PL/pgSQL, cursors also play a major role. Whenever you loop over a result set, PostgreSQL will internally use a cursor automatically. The advantage is that the memory consumption of your applications will be reduced dramatically and there is hardly a chance of ever running out of memory due to processing large amounts of data. There are various ways to use cursors. Here is the most simplistic one:

```
CREATE OR REPLACE FUNCTION c(int)
  RETURNS setof text AS
$$
DECLARE
  v_rec record;
BEGIN
  FOR v_rec IN SELECT tablename
                FROM pg_tables
                LIMIT $1
  LOOP
    RETURN NEXT v_rec.tablename;
  END LOOP;
  RETURN;
END;
$$ LANGUAGE 'plpgsql';
```

This code is interesting for two reasons. First of all, it is a **Set Returning Function (SRF)**. It produces an entire column and not just a single row. The way to achieve this is to use the set of variable instead of just the datatype. The `RETURN NEXT` clause will build up the result set until we have reached the end. The `RETURN` clause will tell PostgreSQL that we want to leave the function and that the result is done.

The second important issue is that looping over the cursor will automatically create an internal cursor. In other words, there is no need to be afraid that you could potentially run out of memory. PostgreSQL will optimize the query in a way that it tries to produce the first 10% of the data (defined by the `cursor_tuple_fraction` variable) as fast as possible. Here is what the query will return:

```
test=# SELECT * FROM c(3);
 c
-----
 t_test
 pg_statistic
 pg_type
(3 rows)
```

In this example, there will simply be a list of random tables. If the result differs on your side, this is somewhat expected.

What you have just seen is, in my opinion, the most frequent and most common way to use implicit cursors in PL/pgSQL. The following example shows an older mechanism that many people from Oracle might know:

```
CREATE OR REPLACE FUNCTION d(int)
  RETURNS setof text AS
$$
DECLARE
  v_cur refcursor;
  v_data text;
BEGIN
  OPEN v_cur FOR
    SELECT tablename
    FROM pg_tables
    LIMIT $1;
  WHILE true LOOP
    FETCH v_cur INTO v_data;
    IF FOUND THEN
      RETURN NEXT v_data;
    ELSE
      RETURN;
    END IF;
  END LOOP;
```

```
END;  
$$ LANGUAGE 'plpgsql';
```

In this example, the cursor is explicitly declared and opened. Inside, the loop data is then explicitly fetched and returned to the caller. Basically, the query does exactly the same thing—it is merely a matter of taste which syntax developers actually prefer.

Do you still have the feeling that you don't know enough about cursors yet? There is more; here is a third option to do exactly the same thing:

```
CREATE OR REPLACE FUNCTION e(int)  
  RETURNS setof text AS  
$$  
DECLARE  
  v_cur CURSOR (param1 int) FOR  
    SELECT tablename  
    FROM pg_tables  
    LIMIT param1;  
  v_data text;  
BEGIN  
  OPEN v_cur ($1);  
  WHILE true LOOP  
    FETCH v_cur INTO v_data;  
    IF FOUND THEN  
      RETURN NEXT v_data;  
    ELSE  
      RETURN;  
    END IF;  
  END LOOP;  
END;  
$$ LANGUAGE 'plpgsql';
```

In this case, the cursor is fed with an integer parameter, which comes directly from the function call (\$1).

Sometimes, a cursor is not used up by the stored procedure itself but returned for later use. In this case, you can return a simple use `refcursor` as the return value:

```
CREATE OR REPLACE FUNCTION cursor_test(c refcursor)  
  RETURNS refcursor AS  
$$  
BEGIN  
  OPEN c FOR SELECT *  
    FROM generate_series(1, 10) AS id;
```

```
    RETURN c;  
END;  
$$ LANGUAGE plpgsql;
```

The logic here is quite simple. The name of the cursor is passed to the function. Then, the cursor is opened and returned. The beauty here is that the query behind the cursor can be created on the fly and compiled dynamically.

The application can fetch from the cursor just like from any other application. Here is how it works. Note that it works only when a transaction block is used:

```
test=# BEGIN;  
BEGIN  
test=# SELECT cursor_test('mytest');  
    cursor_test  
-----  
    mytest  
(1 row)  
test=# FETCH NEXT FROM mytest;  
    id  
-----  
    1  
(1 row)  
test=# FETCH NEXT FROM mytest;  
    id  
-----  
    2  
(1 row)
```

Actually, in this section, you learned that cursors will only produce data as it is consumed. This holds true for most queries. However, I have added a little catch to this example; whenever an SRF is used, the entire result has to be materialized. It is not created on the fly, but at once. The reason is that SQL must be able to rescan a relation, which is easily possible in the case of a normal table. However, for functions, the situation is different. Therefore, an SRF is always calculated and materialized, making the cursor in this example totally useless. In other words, be careful when writing functions--in some cases, danger is hidden in nifty details.

Utilizing composite types

In most other database systems, stored procedures are only used with primitive datatypes such as integer, numeric, varchar, and so on. However, PostgreSQL is very different. You can basically use all datatypes available to you. This includes primitive as well as composite and custom types. There are simply no restrictions as far as datatypes are concerned. To unleash the full power of PostgreSQL, composite types are highly important and are often used by extensions which can be found on the internet.

The following example shows how a composite type can be passed to a function and how it can be used internally. Finally, the composite type will be returned again:

```
CREATE TYPE my_cool_type AS (s text, t text);

CREATE FUNCTION f(my_cool_type)
  RETURNS my_cool_type AS
$$
DECLARE
  v_row my_cool_type;
BEGIN
  RAISE NOTICE 'schema: (%) / table: (%)'
    , $1.s, $1.t;
  SELECT schemaname, tablename
  INTO v_row
  FROM pg_tables
  WHERE tablename = trim($1.t)
    AND schemaname = trim($1.s)
  LIMIT 1;
  RETURN v_row;
END;
$$ LANGUAGE 'plpgsql';
```

The main issue here is that you can simply use `$1.field_name` to access the composite type. Returning the type is not hard either. You just have to assemble the composite type variable on the fly and return it just like any other datatype. You can even use arrays or even more complex structures easily.

The following listing shows what PostgreSQL will return:

```
test=# SELECT (f).s, (f).t
        FROM f ('("public", "t_test")'::my_cool_type);
NOTICE:  schema: (public) / table: ( t_test)
   s   |   t
-----+-----
 public | t_test
(1 row)
```

Writing triggers in PL/pgSQL

Server-side code is especially popular if you want to react to certain events happening in the database. A trigger allows you to call a function if an `INSERT`, `UPDATE`, `DELETE`, or `TRUNCATE` clause happens on a table. The function called by the trigger can then modify the data changed in your table or simply perform some necessary operation.

In PostgreSQL, triggers have become ever more powerful over the years and provide a rich set of features:

```
test=# \h CREATE TRIGGER
Command: CREATE TRIGGER
Description: Define a new trigger
Syntax:
CREATE [ CONSTRAINT ] TRIGGER name { BEFORE | AFTER | INSTEAD OF }
{ event [ OR ... ] }
ON table_name
[ FROM referenced_table_name ]
[ NOT DEFERRABLE | [ DEFERRABLE ] [ INITIALLY IMMEDIATE |
INITIALLY DEFERRED ] ]
[ REFERENCING { { OLD | NEW } TABLE
[ AS ] transition_relation_name } [ ... ] ]
[ FOR [ EACH ] { ROW | STATEMENT } ]
[ WHEN ( condition ) ]
EXECUTE PROCEDURE function_name ( arguments )
```

Here, event can be one of the following:

```
INSERT
UPDATE [ OF column_name [, ... ] ]
DELETE
TRUNCATE
```

The first thing to observe is that a trigger is always fired for a table or a view and calls a function. A trigger has a name and can happen before or after an event. The beauty of PostgreSQL is that you can have as many triggers on a single table as you want. While this does not come as a surprise to hardcore PostgreSQL users, I want to point out that this is not possible in many expensive commercial database engines still in use around the world.

If there is more than one trigger on the same table, the following rule was introduced many years ago in PostgreSQL 7.3: triggers are fired in alphabetical order. First, all those before triggers happen in alphabetical order. Then, PostgreSQL performs the row operation the trigger has been fired for and continues executing the after triggers in alphabetical order. In other words, the execution order of triggers is absolutely deterministic and the number of triggers is basically unlimited.

Triggers can modify data before or after the actual modification has happened. In general, this is a good way to verify data and to error out if some custom restrictions are violated. The following example shows a trigger that is fired in the `INSERT` clause and which changes data added to the table:

```
CREATE TABLE t_sensor (  
    id serial,  
    ts timestamp,  
    temperature numeric  
);
```

Our table just stores a couple of values. The goal now is to call a function as soon as a row is inserted:

```
CREATE OR REPLACE FUNCTION trig_func()  
RETURNS trigger AS  
$$  
    BEGIN  
        IF NEW.temperature < -273  
        THEN  
            NEW.temperature := 0;  
        END IF;  
  
        RETURN NEW;  
    END;  
$$ LANGUAGE 'plpgsql';
```

As stated previously, the trigger will always call a function, which allows you to nicely abstract code. The important thing here is that the trigger function has to return a trigger. To access the row you are about to insert, you can access the `NEW` variable.



INSERT and UPDATE triggers always provide a `NEW` variable. UPDATE and DELETE will offer a variable called `OLD`. Those variables contain the row you are about to modify.

In my example, the code checks whether the temperature is too low. If it is, the value is not okay; it is dynamically adjusted. To ensure that the modified row can be used, `NEW` is simply returned. If there is a second trigger called after this one, the next function call will already see the modified row.

In the next step, the trigger can be created:

```
CREATE TRIGGER sensor_trig
  BEFORE INSERT ON t_sensor
  FOR EACH ROW
  EXECUTE PROCEDURE trig_func();
```

Here is what the trigger will do:

```
test=# INSERT INTO t_sensor (ts, temperature)
VALUES ('2017-05-04 14:43', -300) RETURNING *;
```

id	ts	temperature
1	2017-05-04 14:43:00	0

```
(1 row)

INSERT 0 1
```

As you can see, the value has been adjusted correctly. The content of the table shows 0 for the temperature.

If you are using triggers, you should be aware of the fact that a trigger knows a lot about itself. It can access a couple of variables that allow you to write more sophisticated code and to achieve better abstraction.

Let us drop the trigger first:

```
test=# DROP TRIGGER sensor_trig ON t_sensor;
DROP TRIGGER
```

Then, a new function can be added:

```
CREATE OR REPLACE FUNCTION trig_demo()
  RETURNS trigger AS
$$
BEGIN
  RAISE NOTICE 'TG_NAME: %', TG_NAME;
  RAISE NOTICE 'TG_RELNAME: %', TG_RELNAME;
  RAISE NOTICE 'TG_TABLE_SCHEMA: %', TG_TABLE_SCHEMA;
  RAISE NOTICE 'TG_TABLE_NAME: %', TG_TABLE_NAME;
  RAISE NOTICE 'TG_WHEN: %', TG_WHEN;
  RAISE NOTICE 'TG_LEVEL: %', TG_LEVEL;
  RAISE NOTICE 'TG_OP: %', TG_OP;
  RAISE NOTICE 'TG_NARGS: %', TG_NARGS;
  -- RAISE NOTICE 'TG_ARGV: %', TG_ARGV;
  RETURN NEW;
END;
$$ LANGUAGE 'plpgsql';
```

All those variables used here are predefined and are available by default. All our code does is display them so that we can see the content:

```
test=# INSERT INTO t_sensor (ts, temperature)
test=# VALUES ('2017-05-04 14:43', -300) RETURNING *;

NOTICE: TG_NAME: demo_trigger
NOTICE: TG_RELNAME: t_sensor
NOTICE: TG_TABLE_SCHEMA: public
NOTICE: TG_TABLE_NAME: t_sensor
NOTICE: TG_WHEN: BEFORE
NOTICE: TG_LEVEL: ROW
NOTICE: TG_OP: INSERT
NOTICE: TG_NARGS: 0

 id | ts                      | temperature
-----+-----+-----
  2 | 2017-05-04 14:43:00    | -300
(1 row)

INSERT 0 1
```

What you see here is that the trigger knows its name, the table it has been fired for, and a lot more. If you want to apply similar actions on various tables, those variables help you to avoid duplicate code by just writing a single function, which can then be used for all tables you are interested in.

So far, you have seen simple row-level triggers, which are fired once per statement. However, with the introduction of PostgreSQL 10.0, there are a couple of new features. Statement-level triggers have been around for a while already. However, it was not possible to access the data changed by the trigger. This has been fixed in PostgreSQL 10.0. It is now possible to make use of transition tables, which contain all the changes made.

The following listing contains a complete example showing how a transition table can be used:

```
CREATE OR REPLACE FUNCTION transition_trigger()
RETURNS TRIGGER AS $$
    DECLARE
    v_record record;
    BEGIN
        IF (TG_OP = 'INSERT') THEN
            RAISE NOTICE 'new data: ';
            FOR v_record IN SELECT * FROM new_table
            LOOP
                RAISE NOTICE '%', v_record;
            END LOOP;
        ELSE
            RAISE NOTICE 'old data: ';
            FOR v_record IN SELECT * FROM old_table
            LOOP
                RAISE NOTICE '%', v_record;
            END LOOP;
        END IF;
        RETURN NULL; -- result is ignored since this is an AFTER trigger
    END;
$$ LANGUAGE plpgsql;

CREATE TRIGGER transition_test_trigger_ins
AFTER INSERT ON t_sensor
REFERENCING NEW TABLE AS new_table
FOR EACH STATEMENT EXECUTE PROCEDURE transition_trigger();

CREATE TRIGGER transition_test_trigger_del
AFTER DELETE ON t_sensor
REFERENCING OLD TABLE AS old_table
FOR EACH STATEMENT EXECUTE PROCEDURE transition_trigger();
```

In this case, we need two trigger definitions because we cannot just squeeze everything into just one definition. Inside the trigger function, the transition table is easy to use: it can be accessed just like a normal table.

Let us test the code of the trigger:

```
INSERT INTO t_sensor
  SELECT  *, now(), random() * 20
  FROM    generate_series(1, 5);

DELETE FROM t_sensor;
```

In my example, the code will simply issue a `NOTICE` for each entry in the transition table:

```
NOTICE: new data:
NOTICE: (1, "2017-10-04 15:47:14.129151", 10.4552665632218)
NOTICE: (2, "2017-10-04 15:47:14.129151", 12.8670312650502)
NOTICE: (3, "2017-10-04 15:47:14.129151", 14.3934494629502)
NOTICE: (4, "2017-10-04 15:47:14.129151", 4.35718866065145)
NOTICE: (5, "2017-10-04 15:47:14.129151", 10.9121138229966)
INSERT 0 5

NOTICE: old data:
NOTICE: (1, "2017-10-04 15:47:14.129151", 10.4552665632218)
NOTICE: (2, "2017-10-04 15:47:14.129151", 12.8670312650502)
NOTICE: (3, "2017-10-04 15:47:14.129151", 14.3934494629502)
NOTICE: (4, "2017-10-04 15:47:14.129151", 4.35718866065145)
NOTICE: (5, "2017-10-04 15:47:14.129151", 10.9121138229966)
DELETE 5
```

Keep in mind that it is not necessarily a good idea to use transition tables for billions of rows. PostgreSQL really is scalable but at some point it is necessary to see that there are performance implications as well.

Introducing PL/Perl

There is a lot more to say about PL/pgSQL. However, as I've only got 40 pages to cover this topic, it is time to move on to the next procedural language. PL/Perl has been adopted by many people as the ideal language to do string crunching. As you might know, Perl is famous for its string manipulation capabilities and is therefore still fairly popular after all these years.

To enable PL/Perl, you have two choices:

```
test=# create extension plperl;  
CREATE EXTENSION  
  
test=# create extension plperlu;  
CREATE EXTENSION
```

You can deploy trusted or untrusted Perl. If you want both, you have to enable both languages.

To show you how PL/Perl works, I have implemented a function that simply parses an email address and returns `true` or `false`. Here is how it works:

```
test=# CREATE OR REPLACE FUNCTION verify_email(text)  
RETURNS boolean AS  
$$  
if ($_[0] =~ /^[a-z0-9.]+@[a-z0-9.-]+$/)  
{  
    return true;  
}  
return false;  
$$ LANGUAGE 'plperl'; CREATE FUNCTION
```

A text parameter is passed to the function. Inside the function, all those input parameters can be accessed using `$_`. In this example, the regular expression is executed and the function returns.

The function can be called just like any other procedure written in any other language:

```
test=# SELECT verify_email('hs@cybertec.at');  
verify_email  
t  
(1 row)  
  
test=# SELECT verify_email('totally wrong');  
  
verify_email  
f  
(1 row)
```

Keep in mind that you cannot load packages and so on if you are inside a trusted function. For example, if you want to use the `w` command to find words, Perl will internally load `utf8.pm`, which is, of course, not allowed.

Using PL/Perl for datatype abstraction

As stated in this chapter, functions in PostgreSQL are pretty universal and can be used in many different contexts. If you want to use functions to improve data quality, you can use a `CREATE DOMAIN` clause:

```
test=# \h CREATE DOMAIN
Command: CREATE DOMAIN
Description: Define a new domain
Syntax:
CREATE DOMAIN name [ AS ] data_type
[ COLLATE collation ]
[ DEFAULT expression ] [ constraint [ ... ] ]
```

Here, constraint is as follows:

```
[ CONSTRAINT constraint_name ]
{ NOT NULL | NULL | CHECK (expression) }
```

In this example, the PL/Perl function will be used to create a domain called `email`, which in turn can be used as a datatype.

The following listing shows how the domain can be created:

```
test=# CREATE DOMAIN email AS text
CHECK (verify_email(VALUE) = true);
CREATE DOMAIN
```

As mentioned previously, the domain functions just like a normal datatype:

```
test=# CREATE TABLE t_email (id serial, data email);
CREATE TABLE
```

The Perl function ensures that nothing violating our checks can be inserted into the database, as the following example demonstrates successfully:

```
test=# INSERT INTO t_email (data)
VALUES ('somewhere@example.com');
INSERT 0 1
test=# INSERT INTO t_email (data)
VALUES ('somewhere_wrong_example.com');
ERROR: value for domain email violates check constraint
"email_check"
```

Perl might be a good option to do string crunching but, as always, you have to decide whether you want this code in the database directly or not.

Deciding between PL/Perl and PL/PerlU

So far, the Perl code has not opened any security-related problems because all I did was regular expressions. The question now is: what if somebody tries to do something nasty inside the `Perl` function? As stated already, PL/Perl will simply error out:

```
test=# CREATE OR REPLACE FUNCTION test_security()
RETURNS boolean AS
$$
use strict;
my $fp = open("/etc/password", "r");

return false;
$$ LANGUAGE 'plperl';
ERROR:  'open' trapped by operation mask  at line
CONTEXT:  compilation of PL/Perl function "test_security"
```

PL/Perl will complain as soon as you try to create the function. An error will be displayed instantly.

If you really want to run untrusted code in Perl, you have to use PL/PerlU:

```
test=# CREATE OR REPLACE FUNCTION first_line()
RETURNS text AS
$$
open(my $fh, '<:encoding(UTF-8)', "/etc/passwd")
    or elog(NOTICE, "Could not open file '$filename' $!");

my $row = <$fh>;
close($fh);

return $row;
$$ LANGUAGE 'plperlU';
CREATE FUNCTION
```

Basically, the procedure is the same. It returns a string. However, it is allowed to do everything. The only difference is that the function is marked as `plperlU`.

The result is somewhat unsurprising:

```
test=# SELECT first_line();
 first_line
-----
root:x:0:0:root:/root:/bin/bash+

(1 row)
```

Making use of the SPI interface

Once in a while, your Perl procedure has to do database work. Remember, the function is part of the database connection. Therefore, it is pointless to actually create a database connection. To talk to the database, the PostgreSQL server infrastructure provides the SPI interface, which is a C interface to talk to database internals. All procedural languages that help you to run server-side code use this interface to expose functionality to you. PL/Perl does the same, and in this section, you will learn how to use the Perl wrapper around the SPI interface.

The most important thing you might want to do is simply run SQL and retrieve the number of rows fetched. The `spi_exec_query` function is here to do exactly that. The first parameter passed to the function is the query. The second parameter has the number of rows you actually want to retrieve. For simplicity reasons, I decided to fetch all of them:

```
test=# CREATE OR REPLACE FUNCTION spi_sample(int)
RETURNS void AS
$$
my $rv = spi_exec_query(" SELECT *
    FROM generate_series(1, $_[0])", $_[0]
);
elog(NOTICE, "rows fetched: " . $rv->{processed});
elog(NOTICE, "status: " . $rv->{status});

return;
$$ LANGUAGE 'plperl';
```

SPI will nicely execute the query and display the number of rows. The important thing here is that all stored procedure languages provide a means to send log messages. In the case of PL/Perl, this function is called `elog` and takes two parameters. The first one defines the importance of the message (INFO, NOTICE, WARNING, ERROR, and so on) and the second parameter contains the actual message.

The following message shows what the query returns:

```
test=# SELECT spi_sample(9);
NOTICE: rows fetched: 9
NOTICE: status: SPI_OK_SELECT
spi_sample
-----
(1 row)
```

Using SPI for set returning functions

In many cases, you don't just want to execute some SQL and forget about it. In most cases, a procedure will loop over the result and do something with it. The following example will show how you can loop over the output of a query. On top of that, I decided to beef up the example a bit and make the function return a composite datatype. Working with composite types in Perl is very easy because you can simply stuff the data into a hash and return it.

The `return_next` function will gradually build up the result set until the function is terminated with a simple return statement.

The example in this listing generates a table consisting of random values:

```
CREATE TYPE random_type AS (a float8, b float8);

CREATE OR REPLACE FUNCTION spi_srf_perl(int)
    RETURNS setof random_type AS
$$
my $rv = spi_query("SELECT random() AS a,
                        random() AS b
                        FROM generate_series(1, $_[0])");
while (defined (my $row = spi_fetchrow($rv)))
{
    elog(NOTICE, "data: " .
        $row->{a} . " / " . $row->{b});
    return_next(({a => $row->{a},
                  b => $row->{b}}));
}
return;
$$ LANGUAGE 'plperl';

CREATE FUNCTION
```

First, the `spi_query` function is executed and a loop using the `spi_fetchrow` function is started. Inside the loop, the composite type will be assembled and stuffed into the result set.

As expected, the function will return a set of random values:

```
test=# SELECT * FROM spi_srf_perl(3);
NOTICE: data: 0.154673356097192 / 0.278830723837018
CONTEXT: PL/Perl function "spi_srf_perl"
NOTICE: data: 0.615888888947666 / 0.632620786316693
CONTEXT: PL/Perl function "spi_srf_perl"
NOTICE: data: 0.910436692181975 / 0.753427186980844
CONTEXT: PL/Perl function "spi_srf_perl"
 a_col          |    b_col
-----+-----
```

```
0.154673356097192 | 0.278830723837018
0.615888888947666 | 0.632620786316693
0.910436692181975 | 0.753427186980844
(3 rows)
```

Keep in mind that set returning functions have to be materialized so that the entire result set will be stored in-memory.

Escaping in PL/Perl and support functions

So far, we have only used integers, so SQL injection or special table names were not an issue. Basically, the following functions are available:

- `quote_literal`: It returns a string quote as string literal
- `quote_nullable`: It quotes a string
- `quote_ident`: It quotes SQL identifiers (object names and so on)
- `decode_bytea`: It decodes a PostgreSQL byte array field
- `encode_bytea`: It encodes data and turns it into a byte array
- `encode_literal_array`: It encodes an array of literals
- `encode_typed_literal`: It converts a Perl variable to the value of the datatype passed as a second argument and returns a string representation of this value
- `encode_array_constructor`: It returns the contents of the referenced array as a string in array constructor format
- `looks_like_number`: It returns `true` if a string looks like a number
- `is_array_ref`: It returns `true` if something is an array reference

These functions are always available and can be called directly without having to include any library.

Sharing data across function calls

Sometimes, it is necessary to share data across calls. The infrastructure has means to actually do that. In Perl, a hash can be used to store whatever data is needed:

```
CREATE FUNCTION perl_shared(text) RETURNS int AS
$$
if ( !defined $_SHARED{$_[0]} )
{
    $_SHARED{$_[0]} = 0;
}
```

```
else
{
    $_SHARED{$_[0]}++;
}
return $_SHARED{$_[0]};
$$ LANGUAGE 'plperl';
```

The `$_SHARED` variable will be initialized with 0 as soon as we figure out that the key passed to the function is not there yet. For every other call, 1 is added to the counter, leaving us with the following output:

```
test=# SELECT perl_shared('some_key') FROM generate_series(1, 3);
perl_shared
-----
          0
          1
          2
(3 rows)
```

In case of a more complex statement, the developer usually does not know in which order the functions will be called. It is important to keep that in mind. In most cases, you cannot rely on an execution order.

Writing triggers in Perl

Every stored procedure language shipped with the core of PostgreSQL allows you to write triggers in that language. The same, of course, applies to Perl. As the length of this chapter is limited, I have decided not to include an example of a trigger written in Perl, but instead point you to the official PostgreSQL documentation:

<https://www.postgresql.org/docs/10/static/plperl-triggers.html>.

Basically, writing a trigger in Perl does not differ from writing one in PL/pgSQL. All predefined variables are in place, and as far as return values are concerned, the rules apply in every stored procedure language.

Introducing PL/Python

If you don't happen to be a Perl expert, PL/Python might be the right thing for you. Python has been part of the PostgreSQL infrastructure for a long time and is therefore a solid, well-tested implementation.

When it comes to PL/Python, there is one thing you have to keep in mind: PL/Python is only available as an untrusted language. From a security point of view, it is important to keep that in mind at all times.

To enable PL/Python, you can run the following line from your command line. `test` is the name of the database you want to use with PL/Python:

```
createlang plpythonu test
```

Once the language is enabled, it is already possible to write code.

Alternatively, you can use a `CREATE LANGUAGE` clause, of course. Also keep in mind that in order to use server-side languages, PostgreSQL packages containing those languages are needed (`postgresql-plpython-$ (VERSIONNUMBER)` and so on).

Writing simple PL/Python code

In this section, you will learn to write simple Python procedures. The example discussed here is quite simple: if you are visiting a client by car in Austria, you can deduct 42 euro cents per kilometer as expenses in order to reduce your income tax. So, what the function does is to take the number of kilometers and return the amount of money we can deduct from our tax bill. Here is how it works:

```
CREATE OR REPLACE FUNCTION calculate_deduction(km float)  
RETURNS numeric AS  
$$  
if km <= 0:  
    elog(ERROR, 'invalid number of kilometers')  
else:  
  
    return km * 0.42  
  
$$ LANGUAGE 'plpythonu';
```

The function ensures that only positive values are accepted. Finally, the result is calculated and returned. As you can see, the way a Python function is passed to PostgreSQL does not really differ from Perl or PL/pgSQL.

Using the SPI interface

As with all procedural languages, PL/Python gives you access to the SPI interface. The following example shows how numbers can be added up:

```
CREATE FUNCTION add_numbers(rows_desired integer)
    RETURNS integer AS
$$
mysum = 0

cursor = plpy.cursor("SELECT * FROM
    generate_series(1, %d) AS id" % (rows_desired))

while True:
    rows = cursor.fetch(rows_desired)
    if not rows:
        break

    for row in rows:
        mysum += row['id']
return mysum
$$ LANGUAGE 'plpythonu';
```

When you try this example out, make sure that the call to cursor is actually a single line. Python is all about indentation, so it does make a difference if your code consists of one or of two lines.

Once the cursor has been created, we can loop over it and add up those numbers. The columns inside those rows can easily be referenced using column names.

Calling the function will return the desired result:

```
test=# SELECT add_numbers(10);
    add_numbers
-----
           55
(1 row)
```

If you want to inspect the result set of an SQL statement, PL/Python offers various functions to retrieve more information from the result. Again, those functions are wrappers around what SPI offers on the C level.

The following function inspects a result more closely:

```
CREATE OR REPLACE FUNCTION result_diag(rows_desired integer)
  RETURNS integer AS
$$
rv = plpy.execute("SELECT *
  FROM generate_series(1, %d) AS id" % (rows_desired))
plpy.notice(rv.nrows())
plpy.notice(rv.status())
plpy.notice(rv.colnames())
plpy.notice(rv.coltypes())
plpy.notice(rv.coltypmods())
plpy.notice(rv. str  ())

return 0
$$ LANGUAGE 'plpythonu';
```

The `nrows()` function will display the number of rows. The `status()` function tells us whether everything worked out fine. The `colnames()` function returns a list of columns. The `coltypes()` function returns the object IDs of the datatypes in the result set. 23 is the internal number of integers:

```
test=# SELECT typename FROM pg_type WHERE oid = 23;
      typename
-----
      int4
(1 row)
```

Then comes `typmod`. Consider something like `varchar(20)`: the configuration part if the type is what `typmod` is all about.

Finally, there is a function to return the entire thing as a string for debugging purposes. Calling the function will return the following result:

```
test=# SELECT result_diag(3);
NOTICE:  3
NOTICE:  5
NOTICE:  ['id']
NOTICE:  [23]
NOTICE:  [-1]
NOTICE:  <PLyResult status=5 nrows=3 rows=[{'id': 1},
      {'id': 2}, {'id': 3}]>
result_diag
-----
          0
(1 row)
```

There are many more functions in the SPI interface that help you to execute SQL.

Handling errors

Once in a while, you might have to catch an error. Of course, this is also possible in Python. The following example shows how this works:

```
CREATE OR REPLACE FUNCTION trial_error()
  RETURNS text AS
$$
try:
    rv = plpy.execute("SELECT surely_a_syntax_error")
except plpy.SPIError:
    return "we caught the error" else:
    return "all fine"
$$ LANGUAGE 'plpythonu';
```

You can use a normal try/except block and access `plpy` to treat the error you want to catch. The function can then return normally without destroying your transaction:

```
test=# SELECT trial_error();
 trial_error
-----
we caught the error
(1 row)
```

Remember, PL/Python has full access to the internals of PostgreSQL. Therefore, it can also expose all kinds of errors to your procedure. Here is an example:

```
except spiexceptions.DivisionByZero:
    return "found a division by zero"
except spiexceptions.UniqueViolation:
    return "found a unique violation"
except plpy.SPIError, e:
    return "other error, SQLSTATE %s" % e.sqlstate
```

Catching errors in Python is really easy and can help prevent your functions from failing.

Improving stored procedure performance

So far, you have seen how to write basic stored procedures as well as triggers in various languages. Of course, there are many more languages supported. Some of the most prominent ones are PL/R (R is a powerful statistics package) and PL/v8 (which is based on the Google JavaScript engine). However, those languages are beyond the scope of this chapter (regardless of their usefulness).

In this section, we will focus on improving the performance of a stored procedure. There are a few ways in which we can speed up processing:

- Reducing the number of calls
- Using cached plans
- Giving hints to the optimizer

In this chapter, all three main areas will be discussed.

Reducing the number of function calls

In many cases, performance is bad because functions are called way too often. I cannot stress this point too much: calling things too often is the main reason for bad performance. When you create a function, you can choose from three types of functions: volatile, stable, and immutable. Here is an example:

```
test=# SELECT random(), random();
 random                | random
-----+-----
 0.276252629235387    | 0.710661871358752
(1 row)

test=# SELECT now(), now();
          now                |          now
-----+-----
2016-12-16 12:57:17.135751+01 | 2016-12-16 12:57:17.135751+01
(1 row)

test=# SELECT pi();
 pi
-----
 3.14159265358979
(1 row)
```

A volatile function means that the function cannot be optimized away. It has to be executed over and over again. A volatile function can also be the reason why a certain index is not used. By default, every function is considered to be volatile. A stable function will always return the same data within the same transaction. It can be optimized and calls can be removed. The `now()` function is a good example of a stable function; within the same transaction, it returns the same data.

Immutable functions are the gold standard because they allow for most optimizations, which is because they always return the same result given the same input. As a first step to optimizing functions, always make sure that they are marked correctly by adding volatile, stable, or immutable to the end of the definition.

Using cached plans

In PostgreSQL, a query is executed using four stages:

- **Parser:** It checks the syntax
- **Rewrite system:** It takes care of rules and so on
- **Optimizer/planner:** It optimizes the query
- **Executor:** It executes the plan provided by the planner

If the query is short, the first three steps are relatively time-consuming compared to the real execution time. Therefore, it can make sense to cache execution plans. PL/pgSQL basically does all the plan caching for you automatically behind the scenes. You don't have to care. PL/Perl and PL/Python will give you the choice. The SPI interface provides functions to handle and run prepared queries, so the programmer has the choice whether a query should be prepared or not. In the case of long queries, it can actually make sense to use unprepared queries--short queries should usually always be prepared to reduce the internal overhead.

Assigning costs to functions

From the optimizer point of view, a function is basically just like an operator. PostgreSQL will also treat the costs the same way as if it was a standard operator. The problem is just this: adding two numbers is usually cheaper than intersecting coastlines using some PostGIS-provided function. The thing is that the optimizer does not know whether a function is cheap or expensive.

Fortunately, we can tell the optimizer to make functions cheaper or more expensive:

```
test=# \h CREATE FUNCTION
Command: CREATE FUNCTION
Description: Define a new function
Syntax:
CREATE [ OR REPLACE ] FUNCTION
...
| COST    execution_cost
| ROWS    result_rows
...
```

The `COST` parameter indicates how much more expensive than a standard operator your operator really is. It is a multiplier for `cpu_operator_cost` and not a static value. In general, the default value is 100 unless the function has been written in C.

The second parameter is the `ROWS` parameter. By default, PostgreSQL assumes that a set returning function will return 1,000 rows because the system has no way to figure out precisely how many rows there will be. The `ROWS` parameter allows developers to tell PostgreSQL about the expected number of rows.

Using stored procedures

In PostgreSQL, stored procedures can be used for pretty much everything. In this chapter, you have already learned about the `CREATE DOMAIN` clause and so on, but it is also possible to create your own operators, type casts, and even collations.

In this section, you will see how a simple type cast can be created and how it can be used to your advantage. To define the type cast, consider taking a look at the `CREATE CAST` clause:

```
test=# \h CREATE CAST
Command: CREATE CAST
Description: Define a new cast
Syntax:
CREATE CAST (source_type AS target_type)
WITH FUNCTION function_name (argument_type [, ...])
[ AS ASSIGNMENT | AS IMPLICIT ]

CREATE CAST (source_type AS target_type) WITHOUT FUNCTION
[ AS ASSIGNMENT | AS IMPLICIT ]

CREATE CAST (source_type AS target_type) WITH INOUT
[ AS ASSIGNMENT | AS IMPLICIT ]
```

Using this stuff is very simple. You simply tell PostgreSQL which procedure it is supposed to call to cast whatever type to your desired datatype.

In standard PostgreSQL, you cannot cast an IP address to a boolean. Therefore, it makes a good example. First, the stored procedure has to be defined:

```
CREATE FUNCTION inet_to_boolean(inet)
RETURNS boolean AS
$$
    BEGIN
        RETURN true;
    END;
$$ LANGUAGE 'plpgsql';
```

For simplicity reasons, it returns `true`. However, you can use any code (of course) in any language to do the actual transformation.

In the next step, it is already possible to define the type cast:

```
CREATE CAST (inet AS boolean)
WITH FUNCTION inet_to_boolean(inet) AS IMPLICIT;
```

The first thing is to tell PostgreSQL that we want to cast `inet` to `boolean`. Then, the function is listed and we tell PostgreSQL that we prefer an implicit cast.

It is simply a straightforward process and we can test the cast:

```
test=# SELECT '192.168.0.34'::inet::boolean;
bool
-----
t
(1 row)
```

Basically, the same logic can also be applied to define collations. Again, a stored procedure can be used to perform whatever has to be done:

```
test=# \h CREATE COLLATION
Command: CREATE COLLATION
Description: Define a new collation
Syntax:
CREATE COLLATION name (
    [ LOCALE = locale, ]
    [ LC_COLLATE = lc_collate, ] [ LC_CTYPE = lc_ctype ]
)
CREATE COLLATION name FROM existing_collation
```

Summary

In this chapter, you learned how to write stored procedures. After a theoretical introduction, our attention was focused on some selected features of PL/pgSQL. In addition to that, you learned how to use PL/Perl and PL/Python, which are simply two important languages provided by PostgreSQL. Of course, there are many more languages available. However, due to the limitations of the scope (and length) of this book, those could not be covered in detail. If you want to know more, check out the following website:

https://wiki.postgresql.org/wiki/PL_Matrix.

In Chapter 8, *Managing PostgreSQL Security*, you will learn about PostgreSQL security. You will learn how to manage users and permissions in general. On top of that, you will also learn about network security.

8

Managing PostgreSQL Security

Chapter 7, *Writing Stored Procedures*, was all about stored procedures and writing server-side code. After introducing you to many important topics, it is now time to shift our focus to PostgreSQL security. You will learn how to secure a server and configure permissions.

The following topics will be covered:

- Configuring network access
- Managing authentication
- Handling users and roles
- Configuring database security
- Managing schemas, tables, and columns
- Row-level security

At the end of the chapter, you will be able to write good and efficient procedures.

Managing network security

Before moving on to real-world, practical examples, I want to briefly shift your attention to the various layers of security we will be dealing with. When dealing with security, it makes sense to keep those levels in mind in order to approach security-related issues in an organized way.

Here is my mental model:

- **Bind addresses:** `listen_addresses` in the `postgresql.conf` file
- **Host-based access control:** The `pg_hba.conf` file
- **Instance-level permissions:** Users, roles, database creation, login, and replication
- **Database-level permissions:** Connecting, creating schemas, and so on
- **Schema-level permissions:** Using schemas and creating objects inside a schema
- **Table-level permissions:** Selecting, inserting, updating, and so on
- **Column-level permissions:** Allowing or restricting access to columns
- **Row-level security:** Restricting access to rows

In order to read a value, PostgreSQL has to ensure that you have sufficient permissions on every level. The entire chain of permissions has to be correct.

Understanding bind addresses and connections

When you configure a PostgreSQL server, one of the first things you have to do is define remote access. By default, PostgreSQL does not accept remote connections. The important thing here is that PostgreSQL does not even reject the connection because it simply does not listen on the port. If you try to connect, the error message will actually come from the operating system because PostgreSQL does not care at all.

Assuming that there is a database server using the default configuration on `192.168.0.123`, the following will happen:

```
iMac:~ hs$ telnet 192.168.0.123 5432
Trying 192.168.0.123...
telnet: connect to address 192.168.0.123: Connection refused
telnet: Unable to connect to remote host
```

Telnet tries to create a connection on port 5432 and is instantly rejected by the remote box. From the outside, it looks as if PostgreSQL is not running at all.

The key to success can be found in the `postgresql.conf` file:

```
# - Connection Settings -

#listen_addresses = 'localhost'
# what IP address(es) to listen on;
# comma-separated list of addresses;
# defaults to 'localhost'; use '*' for all
# (change requires restart)
```

The `listen_addresses` setting will tell PostgreSQL which addresses to listen on. Technically speaking, those addresses are bind addresses. What does that actually mean? Suppose you have four network cards in your machine. You can listen on, say, three of those IP addresses. PostgreSQL takes requests to those three cards into account and does not listen on the fourth one. The port is simply closed.



You have to put your server's IP address into `listen_addresses` and not the IPs of the clients.

If you put an `*` in, PostgreSQL will listen to every IP assigned to your machine.



Keep in mind that changing `listen_addresses` requires a PostgreSQL service restart. It cannot be changed on the fly without a restart.

However, there are more settings related to connection management that are highly important to understand:

```
#port = 5432
# (change requires restart)
max_connections = 100
# (change requires restart)
# Note: Increasing max_connections costs ~400 bytes of
# shared memory per
# connection slot, plus lock space
# (see max_locks_per_transaction).
#superuser_reserved_connections = 3
# (change requires restart)
#unix_socket_directories = '/tmp'
# comma-separated list of directories
# (change requires restart)
#unix_socket_group = ''
# (change requires restart)
#unix_socket_permissions = 0777
# begin with 0 to use octal notation
# (change requires restart)
```

First of all, PostgreSQL listens to a single TCP port (the default value is 5432). Keep in mind that PostgreSQL will listen on a single port only. Whenever a request comes in, the postmaster will fork and create a new process to handle the connection. By default, up to 100 normal connections are allowed. On top of that, three additional connections are reserved for superusers. This means that you can either have 97 connections plus 3 superusers or 100 superuser connections. Note that those connection-related settings will also need a restart. The reason for this is that a static amount of memory is allocated to shared memory, which cannot be changed on the fly.

Inspecting connections and performance

When I am consulting, many people ask whether raising the connection limit will have an impact on performance in general. The answer is: not much (there is always some overhead due to context switches and all that). It basically makes little difference how many connections there are. However, what does make a difference is the number of open snapshots. The more open snapshots there are (not connections), the more the overhead on the database side. In other words, you can increase `max_connections` cheaply.

If you are interested in some real-world data, consider taking a look at one of my older blog posts: https://www.cybertec-postgresql.com/max_connections-performance-impacts/.

Living in a world without TCP

In some cases, you might not want to use a network. It often happens that a database will only talk to a local application anyway. Maybe your PostgreSQL database has been shipped along with your application, or maybe you just don't want the risk of using a network: in this case, Unix sockets are what you need. Unix sockets are a network-free means of communication. Your application can connect through a Unix socket locally without exposing anything to the outside world.

What you need, however, is a directory. By default, PostgreSQL will use the `/tmp` directory. However, if more than one database server is running per machine, each one will need a separate data directory to live in.

Apart from security, there are various reasons why not using a network might be a good idea. One of these reasons is performance. Using Unix sockets is a lot faster than going through the loopback device (`127.0.0.1`). If that sounds surprising to you, don't worry--it does to many people. However, the overhead of a real network connection should not be underestimated if you are only running very small queries.

To show you what this really means, I have included a simple benchmark.

I have created a `script.sql` file. This is a simple script that just creates a random number and selects it. It is the most simplistic statement possible. There is nothing simpler than just fetching a number.

So, let's run this simple benchmark on a normal laptop. To do so, I have written a small thing called `script.sql`. It will be used by the benchmark:

```
[hs@linuxpc ~]$ cat /tmp/script.sql
SELECT 1
```

Then, you can simply run `pgbench` to execute the SQL over and over again. The `-f` option allows passing the name of the SQL to the script. `-c 10` means that we want 10 concurrent connections to be active for 5 seconds (`-T 5`). The benchmark is running as the `postgres` user and is supposed to use the `postgres` database, which should be there by default. Note that the following examples will work on RHEL derivatives. Debian-based systems will use different paths:

```
[hs@linuxpc ~]$ pgbench -f /tmp/script.sql
                    -c 10 -T 5
                    -U postgres postgres 2>
/dev/null transaction type: /tmp/script.sql
scaling factor: 1
query mode: simple
number of clients: 10
number of threads: 1
duration: 5 s
number of transactions actually processed: 871407
latency average = 0.057 ms
tps = 174278.158426 (including connections establishing)
tps = 174377.935625 (excluding connections establishing)
```

As you can see, no hostname is passed to `pgbench`, so the tool connects locally to the Unix socket and runs the script as fast as possible. On this four-core Intel box, the system was able to achieve around 174,000 transactions per second.

What happens if `-h localhost` is added:

```
[hs@linuxpc ~]$ pgbench -f /tmp/script.sql
                    -h localhost -c 10 -T 5
                    -U postgres postgres 2>
/dev/null transaction type: /tmp/script.sql
scaling factor: 1
query mode: simple
number of clients: 10
```

```
number of threads: 1
duration: 5 s
number of transactions actually processed: 535251
latency average = 0.093 ms
tps = 107000.872598 (including connections establishing)
tps = 107046.943632 (excluding connections establishing)
```

The throughput will drop like a stone to 107000 transactions per second. The difference is clearly related to networking overhead.



By using the `-j` option (the number of threads assigned to `pgbench`), you can squeeze some more transactions out of your systems. However, it does not change the overall picture of the benchmark in my situation. In other tests, it does because `pgbench` can be a real bottleneck if you don't provide enough CPU power.

As you can see, networking can not only be a security issue, but also a performance issue.

Managing `pg_hba.conf`

After configuring bind addresses, we can move on to the next level. The `pg_hba.conf` file will tell PostgreSQL how to authenticate people coming over the network. In general, `pg_hba.conf` file entries have the following layout:

```
# local DATABASE USER METHOD [OPTIONS]
# host DATABASE USER ADDRESS METHOD [OPTIONS]
# hostssl DATABASE USER ADDRESS METHOD [OPTIONS]
# hostnossl DATABASE USER ADDRESS METHOD [OPTIONS]
```

There are four types of rules that can be put into the `pg_hba.conf` file:

- `local`: This can be used to configure local Unix socket connections.
- `host`: This can be used for SSL and non-SSL connections.
- `hostssl`: These are only valid for SSL connections. To make use of this option, SSL must be compiled into the server, which is the case if you are using prepackaged versions of PostgreSQL. In addition to that, `ssl = on` has to be set in the `postgresql.conf` file when the server is started.
- `hostnossl`: This works for non-SSL connections.

A list of rules can be put into the `pg_hba.conf` file. Here is an example:

You can see three simple rules. The local record says that all users from local Unix sockets for all databases are to be trusted. The trust method means that no password has to be sent to the server and people can log in directly. The other two rules say that the same applies to connections from localhost 127.0.0.1 and ::1/128, which is an IPv6 address.

As connecting without a password is certainly not the best of all choices for remote access, PostgreSQL provides various authentication methods that can be used to configure `pg_hba.conf` file flexibly. Here is the list of possible authentication methods:

```
# local      DATABASE USER METHOD [OPTIONS]
# host       DATABASE USER ADDRESS METHOD [OPTIONS]
# hostssl    DATABASE USER ADDRESS METHOD [OPTIONS]
# hostnossl  DATABASE USER ADDRESS METHOD [OPTIONS]
```

- **trust:** This allows authentication without providing a password. The desired user has to be available on the PostgreSQL side.
- **reject:** The connection will be rejected.
- **md5 and password:** The connections can be created using a password. md5 means that the password is sent over the wire encrypted. In the case of passwords, the credentials are sent in plain text, which should not be done on a modern system anymore. md5 is not considered safe anymore. You should use `scram-sha-256` instead in PostgreSQL 10 and beyond.
- **scram-sha-256:** This setting is the successor of md5 and uses a far more secure hash than the previous version.
- **GSS and SSPI:** This uses GSSAPI or SSPI authentication. This is only possible for TCP/IP connections. The idea here is to allow for single sign-on.
- **ident:** This obtains the operating system username of the client by contacting the ident server of the client and checking whether it matches the requested database username.
- **peer:** Suppose you are logged in as *abc* on Unix. If peer is enabled, you can only log in to PostgreSQL as *abc*. If you try to change the username, you will be rejected. The beauty is that *abc* won't need a password in order to authenticate. The idea here is that only the database administrator can log in to the database on a Unix system and not somebody else who just has the password or a Unix account on the same machine. This only works for local connections.

- **PAM:** It uses the **pluggable authentication module (PAM)**. This is especially important if you want to use a means of authentication that is not provided by PostgreSQL out of the box. To use PAM, create a file called `/etc/pam.d/postgresql` on your Linux system and put the desired PAM modules you are planning to use into the config file. Using PAM, you can even authenticate against less common components. However, it can also be used to connect to Active Directory and so on.
- **LDAP:** This configuration allows you to authenticate using **lightweight directory access protocol (LDAP)**. Note that PostgreSQL will only ask LDAP for authentication; if a user is present only on the LDAP but not on the PostgreSQL side, you cannot log in. Also note that PostgreSQL has to know where your LDAP server is. All of this information has to be stored in the `pg_hba.conf` file as outlined in the official documentation:
<https://www.postgresql.org/docs/10/static/auth-methods.html#AUTH-LDAP>.
- **RADIUS:** The **remote authentication dial-in user service (RADIUS)** is a means to do single sign-on. Again, parameters are passed using configuration options.
- **cert:** This authentication method uses SSL client certificates to perform authentication, and therefore it is possible only if SSL is used. The advantage here is that no password has to be sent. The CN attribute of the certificate will be compared to the requested database username, and if they match, the login will be allowed. A map can be used to allow for user mapping.

Rules can simply be listed one after the other. The important thing here is that the order does make a difference, as shown in the following example:

```
host    all    all    192.168.1.0/24    scram-sha-256
host    all    all    192.168.1.54/32   reject
```

When PostgreSQL walks through the `pg_hba.conf` file, it will use the first rule that matches. So, if our request is coming from `192.168.1.54`, the first rule will always match before we make it to the second one. This means that `192.168.1.54` will be able to log in if the password and user are correct; therefore, the second rule is pointless.

If you want to exclude the IP, make sure that those two rules are swapped.

Handling SSL

PostgreSQL allows you to encrypt the transfer between the server and the client. Encryption is highly beneficial, especially if you are communicating over long distances. SSL offers a simple and secure way to ensure that nobody is able to listen to your communication.

In this section, you will learn to set up SSL.

The first thing to do is to set the `ssl` parameter to on in the `postgresql.conf` file on server start. In the next step, you can put SSL certificates into the `$PGDATA` directory. If you don't want the certificates to be in some other directory, change the following parameters:

```
#ssl_cert_file = 'server.crt'      # (change requires restart)
#ssl_key_file = 'server.key'       # (change requires restart)
#ssl_ca_file = ''                  # (change requires restart)
#ssl_crl_file = ''                 # (change requires restart)
```

If you want to use self-signed certificates, perform the following steps:

```
openssl req -new -text -out server.req
```

Answer the questions asked by OpenSSL. Make sure you enter the local hostname as common name. You can leave the password empty. This call will generate a key that is passphrase protected; it will not accept a passphrase that is less than four characters long.

To remove the passphrase (as you must if you want automatic startup of the server), run the following commands:

```
openssl rsa -in privkey.pem -out server.key
rm privkey.pem
```

Enter the old passphrase to unlock the existing key. Now, do this to turn the certificate into a self-signed certificate and to copy the key and certificate to where the server will look for them:

```
openssl req -x509 -in server.req -text
-key server.key -out server.crt
```

At the end, make sure that the files have the right set of permissions:

```
chmod og-rwx server.key
```

Once the proper rules have been put into the `pg_hba.conf` file, you can use SSL to connect to your server. To verify that you are indeed using SSL, consider checking out the `pg_stat_ssl` function. It will tell you every connection and whether it uses SSL or not, and it will provide some important information about encryption:

```
test=# \d pg_stat_sslView "pg_catalog.pg_stat_ssl"
```

Column	Type	Modifiers
pid	integer	

<code>ssl</code>	<code> boolean</code>	<code> </code>
<code>version</code>	<code> text</code>	<code> </code>
<code>cipher</code>	<code> text</code>	<code> </code>
<code>bits</code>	<code> integer</code>	<code> </code>
<code>compression</code>	<code> boolean</code>	<code> </code>
<code>clientdn</code>	<code> text</code>	<code> </code>

If the `ssl` field for a process contains `true`, PostgreSQL does what you would expect it to do:

```
postgres=# select * from pg_stat_ssl;
-[ RECORD 1 ]
-----
pid          | 20075
ssl          | t
version      | TLSv1.2
cipher       | ECDHE-RSA-AES256-GCM-SHA384
bits         | 256
compression  | f
clientdn     |
```

Handling instance-level security

So far, we have configured bind addresses and we have told PostgreSQL which means of authentication to use for which IP ranges. Up to now, the configuration was purely network-related.

In the next step, we can shift our attention to permissions at the instance level. The most important thing to know is that users in PostgreSQL exist at the instance level. If you create a user, it is not just visible inside one database—it can be seen by all the databases. A user might have permissions to access just a single database, but basically users are created at the instance level.

To those of you who are new to PostgreSQL, there is one more thing you should keep in mind: users and roles are the same thing. `CREATE ROLE` and `CREATE USER` clauses have different default values (literally, the only difference is that roles do not get the `LOGIN` attribute by default), but at the end of the day, users and roles are the same. Therefore, `CREATE ROLE` and `CREATE USER` clauses support the very same syntax:

```
test=# \h CREATE USER
Command: CREATE USER
Description: define a new database role
Syntax:
CREATE USER name [ [ WITH ] option [ ... ] ]
where option can be:
```

```
SUPERUSER | NOSUPERUSER
| CREATEDB | NOCREATEDB
| CREATEROLE | NOCREATEROLE
| INHERIT | NOINHERIT
| LOGIN | NOLOGIN
| REPLICATION | NOREPLICATION
| BYPASSRLS | NOBYPASSRLS
| CONNECTION LIMIT connlimit
| [ ENCRYPTED | UNENCRYPTED ] PASSWORD 'password'
| VALID UNTIL 'timestamp'
| IN ROLE role_name [, ...]
| IN GROUP role_name [, ...]
| ROLE role_name [, ...]
| ADMIN role_name [, ...]
| USER role_name [, ...]
| SYSID uid
```

Let's discuss those syntax elements one by one. The first thing you see is that a user can be a super user or a normal user. If somebody is marked as a `SUPERUSER`, there are no longer any restrictions that a normal user has to face. A `SUPERUSER` can drop objects (databases and so on) as they wish.

The next important thing is that it takes permissions on the instance level to create a new database. Note that when somebody creates a database, this user will automatically be the owner of the database. The rule is this: the creator is always automatically the owner of an object (unless specified otherwise, as can be done with the `CREATE DATABASE` clause). The beauty is that object owners can also drop an object again.



The `CREATEROLE/NOCREATEROLE` clause defines whether somebody is allowed to create new users/roles or not.

The next important thing is the `INHERIT/NOINHERIT` clause. If the `INHERIT` clause is set (which is the default value), a user can inherit permissions from some other user. Using inherited permissions allows using roles as a good way to abstract permissions. For example, you can create the role of bookkeeper and make many other roles inherit from bookkeeper. The idea is that you only have to tell PostgreSQL once what a bookkeeper is allowed to do, even if you have many people working in accounting.

The `LOGIN/NOLOGIN` clause defines whether a role is allowed to log in to the instance. Note that the `LOGIN` clause is not enough to actually connect to a database. To do that, more permissions are needed. At this point, we are trying to make it into the instance, which is basically the gate to all the databases inside the instance. Let's get back to our example: the bookkeeper might be marked as `NOLOGIN` because you want people to log in with their real name. All your accountants (say, Joe and Jane) might be marked as the `LOGIN` clause but can inherit all the permissions from the bookkeeper role. A structure like this makes it easy to assure that all bookkeepers will have the same permissions while ensuring their individual activity is operated and logged under their separate identities.

If you are planning to run PostgreSQL with streaming replication, you can do all the transaction log streaming as a superuser. However, doing that is not recommended from a security point of view. To assure that you don't have to be a superuser to stream xlog, PostgreSQL allows you to give replication rights to a normal user, which can then be used to do streaming. It is common practice to create a special user just for the purpose of managing streaming.

As you will see later in this chapter, PostgreSQL provides a feature called row-level security. The idea is that you can exclude rows from the scope of a user. If a user is explicitly supposed to bypass RLS, set this value to `BYPASSRLS`. The default value is `NOBYPASSRLS`.

Sometimes, it makes sense to restrict the number of connections allowed for a user. `CONNECTION LIMIT` allows you to do exactly that. Note that overall, there can never be more connections than defined in the `postgresql.conf` file (`max_connections`). However, you can always restrict certain users to a lower value.

By default, PostgreSQL will store passwords in the system table encrypted, which is a good default behavior. However, suppose you are doing a training course. 10 students are attending and everybody is connected to your box. You can be 100% certain that one of those people will forget his or her password once in a while. As your setup is not security critical, you might decide to store the password in plain text so that you can easily look it up and give it to a student. This feature might also come in handy if you are testing software.

Often, you already know that somebody will leave your organization fairly soon. The `VALID UNTIL` clause allows you to automatically lock out a specific user if his or her account has expired.

The `IN ROLE` clause lists one or more existing roles to which the new role will be immediately added as a new member. It helps to avoid additional manual steps. An alternative to `IN ROLE` is `IN GROUP`.

`ROLE` clause will define roles that are automatically added as members of the new role.

`ADMIN` clause is the same as the `ROLE` clause but adds the `WITH ADMIN OPTION`.

Finally, you can use the `SYSID` clause to set a specific ID for the user (similar to what some Unix administrators do for usernames at the operating system level).

Creating and modifying users

After this theoretical introduction, it is time to actually create users and see how things can be used in a practical example:

```
test=# CREATE ROLE bookkeeper NOLOGIN;
CREATE ROLE
test=# CREATE ROLE joe LOGIN;
CREATE ROLE
test=# GRANT bookkeeper TO joe;
GRANT ROLE
```

The first thing done here is that a role called `bookkeeper` is created. Note that we don't want people to log in as `bookkeeper`, so the role is marked as `NOLOGIN`.



Note also that `NOLOGIN` is the default value if you use the `CREATE ROLE` clause. If you prefer the `CREATE USER` clause, the default setting is `LOGIN`.

Then, the `joe` role is created and marked as `LOGIN`. Finally, the `bookkeeper` role is assigned to the `joe` role so that he can do everything a `bookkeeper` is actually allowed to do.

Once the users are in place, we can test what we have so far:

```
[hs@zenbook ~]$ psql test -U bookkeeper
psql: FATAL:  role "bookkeeper" is not permitted to log in
```

As expected, the `bookkeeper` role is not allowed to log in to the system. What happens if the `joe` role tries?

```
[hs@zenbook ~]$ psql test -U joe
...
test=>
```

This will actually work as expected. However, note that Command Prompt has changed. This is just a way for PostgreSQL to show you that you are not logged in as a superuser.

Once a user has been created, it might be necessary to modify it. One thing you might want to change is the password. In PostgreSQL, users are allowed to change their own passwords. Here is how it works:

```
test=> ALTER ROLE joe PASSWORD 'abc';
ALTER ROLE
test=> SELECT current_user;
current_user
-----
joe
(1 row)
```

The `ALTER ROLE` clause (or `ALTER USER`) will allow you to change most settings which can be set during user creation. However, there is even more to managing users. In many cases, you want to assign special parameters to a user. The `ALTER USER` clause gives you the means to do that:

```
ALTER ROLE { role_specification | ALL }
    [ IN DATABASE database_name ]
        SET configuration_parameter { TO | = } { value | DEFAULT }
ALTER ROLE { role_specification | ALL }
    [ IN DATABASE database_name ]
        SET configuration_parameter FROM CURRENT
ALTER ROLE { role_specification | ALL }
    [ IN DATABASE database_name ] RESET configuration_parameter
ALTER ROLE { role_specification | ALL }
    [ IN DATABASE database_name ] RESET ALL
```

The syntax is fairly simple and pretty straightforward. To show you why this is really useful, I have added a real-world example. Let's suppose that Joe happens to live on the island of Mauritius. When he logs in, he wants to be in his own time zone, even if his database server is located in Europe:

```
test=> ALTER ROLE joe SET TimeZone = 'UTC-4';
ALTER ROLE
test=> SELECT now();
```

```

              now
-----
2017-01-09 20:36:48.571584+01
(1 row)

test=> q
[hs@zenbook ~]$ psql test -U joe
...
test=> SELECT now();
              now
-----
2017-01-09 23:36:53.357845+04
(1 row)

```

The `ALTER ROLE` clause will modify the user. As soon as `joe` reconnects, the time zone will already be set for him.



The time zone is not changed immediately. You should either reconnect or use a `SET ... TO DEFAULT` clause.

The important thing here is that this is also possible for some memory parameters, such as `work_mem` and so on, which have already been covered earlier in this book.

Defining database-level security

After configuring users at the instance level, it is possible to dig deeper and see what can be done at the database level. The first major question that arises is: we explicitly allowed Joe to log in to the database instance, but who or what allowed Joe to actually connect to one of the databases? Maybe you don't want Joe to access all the databases in your system. Restricting access to certain databases is exactly what you can achieve on this level.

For databases, the following permissions can be set using a `GRANT` clause:

```

GRANT { { CREATE | CONNECT | TEMPORARY | TEMP } [, ...]
      | ALL [ PRIVILEGES ] }
ON DATABASE database_name [, ...]
TO role_specification [, ...] [ WITH GRANT OPTION ]

```

There are two major permissions on the database level that deserve close attention:

- **CREATE**: It allows somebody to create a schema inside the database. Note that a **CREATE** clause does not allow for the creation of tables; it is about schemas. In PostgreSQL, a table resides inside a schema, so you have to get to the schema level first to be able to create a table.
- **CONNECT**: It allows somebody to connect to a database.

The question now is: nobody has explicitly assigned **CONNECT** permissions to the `joe` role, so where do those permissions actually come from? The answer is this: there is a thing called `public`, which is similar to the Unix world. If the world is allowed to do something, so is Joe, who is part of the general public.

The main thing is that `public` is not a role in the sense that it can be dropped and renamed. You can simply see it as the equivalent for everybody on the system.

So, to ensure that not everybody can connect to any database at any time, **CONNECT** may have to be revoked from the general public. To do so, you can connect as superuser and fix the problem:

```
[hs@zenbook ~]$ psql test -U postgres
...
test=# REVOKE ALL ON DATABASE test FROM public;
REVOKE
test=# \q
[hs@zenbook ~]$ psql test -U joe
psql: FATAL: permission denied for database "test"
DETAIL: User does not have CONNECT privilege.
```

As you can see, the `joe` role is not allowed to connect anymore. At this point, only superusers have access to `test`.

In general, it is a good idea to revoke permissions from the `postgres`, database even before other databases are created. The idea behind this concept is that those permissions won't be in all those newly created databases anymore. If somebody needs access to a certain database, rights have to be explicitly granted. Rights are not automatically there anymore.

If you want to allow the `joe` role to connect to the test database, try the following line as superuser:

```
[hs@zenbook ~]$ psql test -U postgres
...
test=# GRANT CONNECT ON DATABASE test TO bookkeeper;
GRANT
test=# \q
[hs@zenbook ~]$ psql test -U joe
...
test=>
```

Basically, there are two choices here:

- You can allow the `joe` role directly so that only the `joe` role will be able to connect.
- Alternatively, you can grant permissions to the `bookkeeper` role. Remember, the `joe` role will inherit all the permissions from the `bookkeeper` role, so if you want all accountants to be able to connect to the database, assigning permissions to the `bookkeeper` role seems like an attractive idea.

If you grant permissions to the `bookkeeper` role, it is not risky because the role is not allowed to log in to the instance in the first place, so it purely serves as a source of permissions.

Adjusting schema-level permissions

Once you are done configuring the database level, it makes sense to take a look at the schema level.

Before actually taking a look at the schema, I want to run a small test:

```
test=> CREATE DATABASE test;
ERROR:  permission denied to create database test=>
CREATE USER xy;
ERROR:  permission denied to create role test=>
CREATE SCHEMA sales;
ERROR:  permission denied for database test
```

As you can see, Joe is having a bad day and basically nothing but connecting to the database is allowed.

However, there is a small exception, and it comes as a surprise to many people:

```
test=> CREATE TABLE t_broken (id int);
CREATE TABLE
test=> \d
           List of relations
Schema | Name      | Type  | Owner
-----+-----+-----+-----
public | t_broken  | table | joe
(1 rows)
```

By default, public is allowed to work with the public schema, which is always around. If you are seriously interested in securing your database, make sure that this problem is taken care of. Otherwise, normal users will potentially spam your public schema with all kinds of tables and your entire setup might suffer. Also keep in mind that if somebody is allowed to create an object, this person is also its owner. Ownership means that there are automatically all permissions available to the creator (this includes the destruction of the object).

To take away those permissions from public, run the following line as superuser:

```
test=# REVOKE ALL ON SCHEMA public FROM public;
REVOKE
```

From now on, nobody can put things into your public schema without permissions anymore:

```
[hs@zenbook ~]$ psql test -U joe
...
test=> CREATE TABLE t_data (id int);
ERROR:  no schema has been selected to create in
LINE 1: CREATE TABLE t_data (id int);
```

As you can see, the command will fail. The important thing here is the error message you will get; PostgreSQL does not know where to put these tables. By default, it will try to put the table into one of the following schemas:

```
test=> SHOW search_path ;
search_path
-----
"$user", public
(1 row)
```

As there is no schema called `joe`, it is not an option and PostgreSQL will try the public schema. As there are no permissions, it will complain that it does not know where to put the table.

If the table is explicitly prefixed, the situation will change instantly:

```
test=> CREATE TABLE public.t_data (id int);
ERROR:  permission denied for schema public
LINE 1: CREATE TABLE public.t_data (id int);
```

In this case, you will get the error message you expect. PostgreSQL denies access to the public schema.

The next logical question now is: which permissions can be set at the schema level to give some more power to the `joe` role:

```
GRANT { { CREATE | USAGE } [, ...] | ALL [ PRIVILEGES ] }
ON SCHEMA schema_name [, ...]
TO role_specification [, ...] [ WITH GRANT OPTION ]
```

CREATE means that somebody can put objects into a schema. USAGE means that somebody is allowed to enter the schema. Note that entering the schema does not mean that something inside the schema can actually be used—those permissions have not been defined yet. Basically, this just means the user can see the system catalog for this schema.

To allow the `joe` role to access the table it has created previously, the following line will be necessary (executed as superuser):

```
test=# GRANT USAGE ON SCHEMA public TO bookkeeper;
GRANT
```

The `joe` role is now able to read its table as expected:

```
[hs@zenbook ~]$ psql test -U joe
test=> SELECT count(*) FROM t_broken;
 count
-----
      0
(1 row)
```

The `joe` role is also able to add and modify rows because it happens to be the owner of the table. However, although it can do quite a lot of things already, the `joe` role is not yet almighty. Consider the following statement:

```
test=> ALTER TABLE t_broken RENAME TO t_useful;
ERROR:  permission denied for schema public
```

Let's take a closer look at the actual error message. As you can see, the message complains about permissions on the schema, not about permissions on the table itself (remember, the `joe` role owns the table). To fix the problem, it has to be tackled on the schema and not on the table level. Run the following line as superuser:

```
test=# GRANT CREATE ON SCHEMA public TO bookkeeper;  
GRANT
```

The `joe` role can now change the name of its table to a more useful name:

```
[hs@zenbook ~]$ psql test -U joe  
test=> ALTER TABLE t_broken RENAME TO t_useful;  
ALTER TABLE
```

Keep in mind that this is necessary if DDLs are used. In my daily work as a PostgreSQL support service provider, I have seen a couple of issues where this turned out to be a problem.

Working with tables

After taking care of bind addresses, network authentication, users, databases, and schemas, you have finally made it to the table level. The following snippet shows which permissions can be set for a table:

```
GRANT { { SELECT | INSERT | UPDATE | DELETE | TRUNCATE  
        | REFERENCES | TRIGGER }  
        [, ...] | ALL [ PRIVILEGES ] }  
ON { [ TABLE ] table_name [, ...]  
     | ALL TABLES IN SCHEMA schema_name [, ...] }  
TO role_specification [, ...] [ WITH GRANT OPTION ]
```

Let me explain those permissions one by one:

- **SELECT:** Allows you to read a table.
- **INSERT:** Allows you to add rows to the table (this also includes copy and so on—it is not only about the `INSERT` clause). Note that if you are allowed to insert, you are not automatically allowed to read. `SELECT` and `INSERT` clauses are needed to be able to read the data you have inserted.
- **UPDATE:** Modifies the content of a table.
- **DELETE:** Is used to remove rows from a table.

- **TRUNCATE:** Allows you to use the `TRUNCATE` clause. Note that the `DELETE` and `TRUNCATE` clauses are two separate permissions because the `TRUNCATE` clause will lock the table, which is not done by the `DELETE` clause (not even if there is no `WHERE` condition).
- **REFERENCES:** Allows the creation of foreign keys. It is necessary to have this privilege on both the referencing and referenced columns, otherwise the creation of the key won't work.
- **TRIGGER:** Allows for the creation of triggers.



The nice thing about the `GRANT` clause is that you can set permissions on all tables in a schema at the same time.

This greatly simplifies the process of adjusting permissions. It is also possible to use the `WITH GRANT OPTION` clause. The idea is to ensure that normal users can pass on permissions to others, which has the advantage of being able to reduce the workload of administrators quite a bit. Just imagine a system that provides access to hundreds of users—it can start to be a lot of work to manage all those people, and therefore administrators can appoint people managing a subset of the data themselves.

Handling column-level security

In some cases, not everybody is allowed to see all the data. Just imagine a bank. Some people might see the entire information about a bank account, while others might be limited to only a subset of the data. In a real-world situation, somebody might not be allowed to read the balance column or somebody might not see the interest rates of people's loans.

Another example would be that people are allowed to see people's profiles but not their pictures or some other private information. The question now is: how can column-level security be used?

To demonstrate that, I will add a column to the existing table belonging to the `joe` role:

```
test=> ALTER TABLE t_useful ADD COLUMN name text;  
ALTER TABLE
```

The table now consists of two columns. The goal of the example is to ensure that a user can see only one of those columns:

```
test=> \d t_useful
      Table "public.t_useful"
  Column |   Type   | Modifiers
  -----+-----+-----
   id    | integer  |
   name  | text     |
```

As a superuser, let's create a user and give it access to the schema containing our table:

```
test=# CREATE ROLE paul LOGIN;
CREATE ROLE
test=# GRANT CONNECT ON DATABASE test TO paul;
GRANT
test=# GRANT USAGE ON SCHEMA public TO paul;
GRANT
```

Do not forget to give `CONNECT` rights to the new guy because earlier in the chapter, `CONNECT` was revoked from the public. Explicit granting is therefore absolutely necessary to ensure that we can even get to the table.

The `SELECT` permissions can be given to the `paul` role:

```
test=# GRANT SELECT (id) ON t_useful TO paul;
GRANT
```

Basically, this is already enough. It is already possible to connect to the database as user `paul` and read the column:

```
[hs@zenbook ~]$ psql test -U paul
...
test=> SELECT id FROM t_useful;
 id
----
(0 rows)
```

If you are using column-level permissions, there is an important thing to keep in mind: you should stop using `SELECT *` as it does not work anymore:

```
test=> SELECT * FROM t_useful;
ERROR:  permission denied for relation t_useful
```

`*` still means *all columns*, but as there is no way to access all columns, things will error out instantly.

Configuring default privileges

So far, a lot of stuff has already been configured. The trouble naturally arising now is: what happens if new tables are added to the system? It can be quite painful and risky to process these tables one by one and to set proper permissions. Wouldn't it be nice if those things would just happen automatically? This is exactly what the `ALTER DEFAULT PRIVILEGES` clause does. The idea is to give users an option to make PostgreSQL automatically set the desired permissions as soon as an object comes into existence. It cannot happen anymore that somebody simply forgets to set those rights.

The following listing shows the first part of the syntax specification:

```
test=# \h ALTER DEFAULT PRIVILEGES
Command: ALTER DEFAULT PRIVILEGES
Description: define default access privileges
Syntax:
ALTER DEFAULT PRIVILEGES
[ FOR { ROLE | USER } target_role [, ...] ] [ IN SCHEMA schema_name [,
... ] ] abbreviated_grant_or_revoke
where abbreviated_grant_or_revoke is one of: GRANT { { SELECT | INSERT |
UPDATE | DELETE
| TRUNCATE
| REFERENCES | TRIGGER }
[, ...] | ALL [ PRIVILEGES ] } ON TABLES
TO { [ GROUP ] role_name | PUBLIC } [, ...] [ WITH GRANT OPTION ]
...
```

Basically, the syntax works similar to the `GRANT` clause and is therefore easy and intuitive to use. To show you how it works, I compiled a simple example. The idea is that if the `joe` role creates a table, the `paul` role will automatically be able to use it:

```
test=# ALTER DEFAULT PRIVILEGES FOR ROLE joe
      IN SCHEMA public GRANT ALL ON TABLES TO paul;
ALTER DEFAULT PRIVILEGES
```

Let me connect as the `joe` role now and create a table:

```
[hs@zenbook ~]$ psql test -U joe
...
test=> CREATE TABLE t_user (id serial, name text, passwd text);
CREATE TABLE
```

Connecting as the `paul` role will prove that the table has been assigned to the proper set of permissions:

```
[hs@zenbook ~]$ psql test -U paul
...
test=> SELECT * FROM t_user;
 id | name | passwd
-----+-----+-----
(0 rows)
```

Digging into row-level security - RLS

Up to this point, a table has always been shown as a whole. When the table contained 1 million rows, it was possible to retrieve 1 million rows from it. If somebody had the rights to read a table, it was all about the entire table. In many cases, this is not enough. Often, it is desirable that a user is not allowed to see all the rows.

Consider the following real-world example: an accountant is doing accounting work for many people. The table containing tax rates should really be visible to everybody as everybody has to pay the same rates. However, when it comes to the actual transactions, the accountant might want to ensure that everybody is only allowed to see his or her own transactions. Person *A* should not be allowed to see person *B*'s data. In addition to that, it might also make sense that the boss of a division is allowed to see all the data in his part of the company.

Row-level security has been designed to do exactly this and enables you to build multi-tenant systems in a fast and simple way. The way to configure those permissions is to come up with policies. The `CREATE POLICY` command is here to provide you with a means to write those rules:

```
test=# \h CREATE POLICY
Command:  CREATE POLICY
Description: define a new row level security policy for a table
Syntax:
CREATE POLICY name ON table_name
    [ AS { PERMISSIVE | RESTRICTIVE } ]
    [ FOR { ALL | SELECT | INSERT | UPDATE | DELETE } ]
    [ TO { role_name | PUBLIC |
CURRENT_USER | SESSION_USER } [, ...] ]
    [ USING ( using_expression ) ]
    [ WITH CHECK ( check_expression ) ]
```

To show you how a policy can be written, I will first log in as superuser and create a table containing a couple of entries:

```
test=# CREATE TABLE t_person (gender text, name text);
CREATE TABLE
test=# INSERT INTO t_person
VALUES      ('male', 'joe'),
            ('male', 'paul'),
            ('female', 'sarah'),
            (NULL, 'R2- D2');
INSERT 0 4
```

Then access is granted to the `joe` role:

```
test=# GRANT ALL ON t_person TO joe;
GRANT
```

So far, everything is pretty normal and the `joe` role will be able to actually read the entire table as there is no RLS in place. But what happens if row-level security is enabled for the table:

```
test=# ALTER TABLE t_person ENABLE ROW LEVEL SECURITY;
ALTER TABLE
```

There is a deny all default policy in place, so the `joe` role will actually get an empty table:

```
test=> SELECT * FROM t_person;
gender | name
-----+-----
(0 rows)
```

Actually, the default policy makes a lot of sense as users are forced to explicitly set permissions.

Now that the table is under row-level security control, policies can be written (as superuser):

```
test=# CREATE POLICY joe_pol_1
ON t_person
FOR SELECT TO joe
USING (gender = 'male');
CREATE POLICY
```

Logging in as the `joe` role and selecting all the data will return just two rows:

```
test=> SELECT * FROM t_person;
gender | name
-----+-----
male   | joe
male   | paul
(2 rows)
```

Let's inspect the policy I have just created in a more detailed way. The first thing you see is that a policy actually has a name. It is also connected to a table and allows for certain operations (in this case, the `SELECT` clause). Then comes the `USING` clause. It basically defines what the `joe` role will be allowed to see. The `USING` clause is therefore a mandatory filter attached to every query to only select the rows our user is supposed to see.

There is also one important side note: if there is more than just a single policy, PostgreSQL will use an `OR` condition; in short, more policies will make you see more data by default. In PostgreSQL 9.6, this was always the case. However, with the introduction of PostgreSQL 10.0, the user can choose whether conditions should be `OR` and `AND` connected:

PERMISSIVE | RESTRICTIVE

By default, PostgreSQL is `PERMISSIVE` so `OR` connections are at work. If you decide to use `RESTRICTIVE`, then those clauses will be connected with `AND`.

Now suppose that, for some reason, it has been decided that the `joe` role is also allowed to see robots. There are two choices to achieve our goal. The first option is to simply use the `ALTER POLICY` clause to change the existing policy:

```
test=> \h ALTER POLICY
Command: ALTER POLICY
Description: change the definition of a row level security policy
Syntax:
ALTER POLICY name ON table_name RENAME TO new_name
ALTER POLICY name ON table_name
[ TO { role_name | PUBLIC | CURRENT_USER | SESSION_USER } [, ...] ] [
USING ( using_expression ) ]
[ WITH CHECK ( check_expression ) ]
```

The second option is to create a second policy, as shown in the next example:

```
test=# CREATE POLICY joe_pol_2
      ON t_person
      FOR SELECT TO joe
      USING (gender IS NULL);
CREATE POLICY
```

The beauty is that those policies are simply connected using an OR condition as stated before, unless `RESTRICTIVE` is used. Therefore, PostgreSQL will now return three rows instead of two:

```
test=> SELECT * FROM t_person;
gender | name
-----+-----
male   | joe
male   | paul
       | R2-D2
(3 rows)
```

The R2-D2 role is now also included in the result as it matches the second policy.

To show you how PostgreSQL runs the query, I have decided to include an execution plan of the query:

```
test=> explain SELECT * FROM t_person;
               QUERY PLAN
-----
Seq Scan on t_person (cost=0.00..21.00 rows=9 width=64)
  Filter: ((gender IS NULL) OR (gender = 'male'::text))
(2 rows)
```

As you can see, both the `USING` clauses have been added as mandatory filters to the query. You might have noticed in the syntax definition that there are two types of clauses:

- **USING:** This clause filters rows that already exist. This is relevant to `SELECT` and `UPDATE` clauses, and so on.
- **CHECK:** This clause filters new rows that are about to be created, so they are relevant to `INSERT` and `UPDATE` clauses, and so on.

Here is what happens if we try to insert a row:

```
test=> INSERT INTO t_person VALUES ('male', 'kaarel');
ERROR:  new row violates row-level security policy for table "t_person"
```

As there is no policy for the `INSERT` clause, the statement will naturally error out. Here is the policy to allow insertions:

```
test=# CREATE POLICY joe_pol_3
      ON t_person
      FOR INSERT TO joe
      WITH CHECK (gender IN ('male', 'female'));
CREATE POLICY
```

The `joe` role is allowed to add males and females to the table, which is shown in the next listing:

```
test=> INSERT INTO t_person VALUES ('female', 'maria');
INSERT 0 1
```

However, there is also a catch; consider the following example:

```
test=> INSERT INTO t_person VALUES ('female', 'maria') RETURNING *;
ERROR:  new row violates row-level security policy for table "t_person"
```

Remember, there is only a policy to select males. The trouble here is that the statement will return a woman, which is not allowed because the `joe` role is under a male-only policy.

Only for men will the `RETURNING *` clause actually work:

```
test=> INSERT INTO t_person VALUES ('male', 'max') RETURNING *;
gender | name
-----+-----
male   | max
(1 row)
INSERT 0 1
```

If you don't want this behavior, you have to write a policy that actually contains a proper `USING` clause.

Inspecting permissions

When all permissions are set, it is sometimes necessary to know who has which permissions. It is vital for administrators to find out who is allowed to do what. Unfortunately, this process is not so easy and requires a bit of knowledge. Usually, I am a big fan of command-line usage. However, in the case of the permission system, it can really make sense to use a graphical user interface to do things.

Before I show you how to read PostgreSQL permissions, I will assign rights to the `joe` role so that we can inspect them in the next step:

```
test=# GRANT ALL ON t_person TO joe;
GRANT
```

Retrieving information about permissions can be done using the `z` command in `psql`:

```
test=# \x
Expanded display is on.
test=# \z t_person
Access privileges
-[ RECORD 1 ]-----+-----
Schema          | public
Name             | t_person
Type            | table
Access privileges | postgres=arwdDxt/postgres
+
                  | joe=arwdDxt/postgres
Column privileges |
Policies         | joe_pol_1 (r):
+               | (u):  (gender = 'male'::text)
+               | to: joe
+               | joe_pol_2 (r):
+               | (u):  (gender IS NULL)
+               | to: joe
+               | joe_pol_3 (a):
+               | (c):  (gender = ANY (ARRAY['male'::text,
'female'::text]))
+               | to: joe
```

This will return all those policies along with information about access privileges. Unfortunately, those shortcuts are hard to read and I have a feeling that they are not widely understood by administrators. In our example, the `joe` role has gotten `arwdDxt` from Postgres. What do those codes actually mean:

- a: Appends for the INSERT clause
- r: Reads for the SELECT clause
- w: Writes for the UPDATE clause
- d: Deletes for the DELETE clause
- D: Is used for the TRUNCATE clause (when this was introduced, t was already taken)

- x: Is used for references
- t: Is used for triggers

If you don't know those codes, there is also a second way to make things more readable. Consider the following function call:

```
test=# SELECT * FROM aclexplode('{joe=arwdDxt/postgres}');
 grantor | grantee | privilege_type | is_grantable
-----+-----+-----+-----
      10 |   18481 |      INSERT    |          f
      10 |   18481 |      SELECT    |          f
      10 |   18481 |      UPDATE    |          f
      10 |   18481 |      DELETE    |          f
      10 |   18481 |  TRUNCATE     |          f
      10 |   18481 | REFERENCES    |          f
      10 |   18481 |      TRIGGER   |          f
(7 rows)
```

As you can see, the set of permissions is returned as a simple table, which makes life really easy.

Reassigning objects and dropping users

After assigning permissions and restricting access, it can happen that users will be dropped from the system. Unsurprisingly, the commands to do that are the `DROP ROLE` and `DROP USER` commands:

```
test=# \h DROP ROLE
Command:  DROP ROLE
Description: remove a database role
Syntax:
DROP ROLE [ IF EXISTS ] name [, ...]
```

Let's give it a try:

```
test=# DROP ROLE joe;
ERROR:  role "joe" cannot be dropped because some objects depend on it
DETAIL:  target of policy joe_pol_3 on table t_person
target of policy joe_pol_2 on table t_person
target of policy joe_pol_1 on table t_person
privileges for table t_person
owner of table t_user
owner of sequence t_user_id_seq
owner of default privileges on new relations belonging to role joe in
```

```
schema public
owner of table t_useful
```

PostgreSQL will issue error messages because a user can only be removed if everything has been taken away from him. This makes sense for this reason: just suppose somebody owns a table. What should PostgreSQL do with that table? Somebody has to own them.

To reassign tables from one user to the next, consider taking a look at the `REASSIGN` clause:

```
test=# \h REASSIGN
Command:  REASSIGN OWNED
Description: change the ownership of database objects owned by a database
role
Syntax:
REASSIGN OWNED BY { old_role | CURRENT_USER | SESSION_USER } [, ...]
    TO { new_role | CURRENT_USER | SESSION_USER }
```

The syntax is again quite simple and helps to simplify the process of handing over. Here is an example:

```
test=# REASSIGN OWNED BY joe TO postgres;
REASSIGN OWNED
```

So, let's try to drop the `joe` role again:

```
test=# DROP ROLE joe;
ERROR:  role "joe" cannot be dropped because some objects depend on it
DETAIL: target of policy joe_pol_3 on table t_person target of policy
joe_pol_2 on table t_person
target of policy joe_pol_1 on table t_person privileges for table t_person
owner of default privileges on new relations belonging to role joe in
schema public
```

As you can see, the list of problems has been reduced significantly. What we can do now is resolve all of those problems one after the other and drop the role. There is no shortcut I am aware of. The only way to make that more efficient is to make sure that as few permissions as possible are assigned to real people. Try to abstract as much as you can into roles, which in turn can be used by many people. If individual permissions are not assigned to real people, things tend to be easier in general.

Summary

Database security is a wide field, and a 30-page chapter can hardly cover all the aspects of PostgreSQL security. Many things, such as SELinux, security definer/invoker, and so on, were left untouched. However, in this chapter, you learned the most common things you will face as a PostgreSQL developer and DBA. You learned how to avoid the basic pitfalls and how to make your systems more secure.

In [Chapter 9, *Handling Backup and Recovery*](#), you will learn about PostgreSQL streaming replication and incremental backups. The chapter will also cover failover scenarios.

9

Handling Backup and Recovery

In *Chapter 8, Managing PostgreSQL Security*, I tried to teach you all you need to know about securing PostgreSQL in the most simplistic and most beneficial way possible. The topics of this chapter will be backup and recovery. Performing backups should be a regular task and every administrator is supposed to keep an eye on this vital stuff. Fortunately, PostgreSQL provides an easy means to create backups.

Therefore, in this chapter, we will cover the following topics:

- Running `pg_dump`
- Partially dumping data
- Restoring backups
- Making use of parallelism
- Saving global data

At the end of the chapter, you will be able to set up proper backup mechanisms.

Performing simple dumps

If you are running a PostgreSQL setup, there are basically two major methods to perform backups:

- Logical dumps (extract an SQL script representing your data)
- Transaction log shipping

The idea behind transaction log shipping is to archive binary changes made to the database. Most people claim that transaction log shipping is the only real way to do backups. However, in my opinion, this is not necessarily true.

Many people rely on `pg_dump` to simply extract a textual representation of the data. `pg_dump` is also the oldest method of creating a backup and has been around since the very early days of the project (transaction log shipping was added much later). Every PostgreSQL administrator will become familiar with `pg_dump` sooner or later, so it is important to know how it really works and what it does.

Running `pg_dump`

The first thing we want to do is to create a simple textual dump:

```
[hs@linuxpc ~]$ pg_dump test > /tmp/dump.sql
```

This is the most simplistic backup you can imagine. `pg_dump` logs in to the local database instance, connects to a database `test`, and starts to extract all the data, which will be sent to stdout and redirected to the file. The beauty is that standard output gives you all the flexibility of a Unix system. You can easily compress the data using a pipe or do whatever you want.

In some cases, you might want to run `pg_dump` as a different user. All PostgreSQL client programs support a consistent set of command-line parameters to pass user information. If you just want to set the user, use the `-U` flag:

```
[hs@linuxpc ~]$ pg_dump -U whatever_powerful_user test > /tmp/dump.sql
```

The following set of parameters can be found in all PostgreSQL client programs:

```
...
Connection options:
-d, --dbname=DBNAME database to dump
-h, --host=HOSTNAME database server host or
    socket directory
-p, --port=PORT database server port number
-U, --username=NAME connect as specified database user
-w, --no-password never prompt for password
-W, --password force password prompt (should
    happen automatically)
--role=ROLENAME do SET ROLE before dump
...
```

Just pass the information you want to `pg_dump`, and if you have enough permissions, PostgreSQL will fetch the data. The important thing here is to see how the program really works. Basically, `pg_dump` connects to the database and opens a large repeatable read transaction that simply reads all the data. Remember, repeatable read ensures that PostgreSQL creates a consistent snapshot of the data, which does not change throughout the transactions. In other words, a dump is always consistent—no foreign keys will be violated. The output is a snapshot of data as it was when the dump started. Consistency is a key factor here. It also implies that changes made to the data while the dump is running won't make it to the backup anymore.



A dump simply reads everything—therefore, there are no separate permissions to be able to dump something. As long as you can read it, you can back it up.

Also note that the backup is by default in a textual format. This means that you can safely extract data from say, Solaris, and move it to some other CPU architecture. In the case of binary copies, that is clearly not possible as the on-disk format depends on your CPU architecture.

Passing passwords and connection information

If you take a close look at the connection parameters shown in the previous section, you will notice that there is no way to pass a password to `pg_dump`. You can enforce a password prompt, but you cannot pass the parameter to `pg_dump` using a command-line option. The reason for that is simple: the password might show up in the process table and be visible to other people. Therefore, this is not supported. The question now is: if `pg_hba.conf` on the server enforces a password, how can the client program provide it?

There are various means of doing that:

- Making use of environment variables
- Making use of `.pgpass`
- Using service files

In this section, you will learn about all three methods.

Using environment variables

One way to pass all kinds of parameters is to use environment variables. If information is not explicitly passed to `pg_dump`, it will look for the missing information in predefined environment variables. A list of all potential settings can be found here:

<https://www.postgresql.org/docs/10/static/libpq-envvars.html>.

The following overview shows some environment variables commonly needed for backups:

- `PGHOST`: It tells the system which host to connect to
- `PGPORT`: It defines the TCP port to be used
- `PGUSER`: It tells a client program about the desired user
- `PGPASSWORD`: It contains the password to be used
- `PGDATABASE`: It is the name of the database to connect to

The advantage of these environments is that the password won't show up in the process table. However, there is more. Consider the following example:

```
psql -U ... -h ... -p ... -d ...
```

Suppose you are a system administrator: do you really want to type a long line like that a couple of times every day? If you are working with the very same host again and again, just set those environment variables and connect with plain SQL:

```
[hs@linuxpc ~]$ export PGHOST=localhost
[hs@linuxpc ~]$ export PGUSER=hs
[hs@linuxpc ~]$ export PGPASSWORD=abc
[hs@linuxpc ~]$ export PGPORT=5432
[hs@linuxpc ~]$ export PGDATABASE=test
[hs@linuxpc ~]$ psql
psql (10.1)
Type "help" for help.
```

As you can see, there are no command-line parameters anymore. Just type `psql` and you are in.



All applications based on the standard PostgreSQL-language client library (`libpq`) will understand these environment variables, so you cannot only use them for `psql` and `pg_dump`, but for many other applications.

Making use of .pgpass

A very common way to store login information is via the use of `.pgpass` files. The idea is simple: put a file called `.pgpass` into your home directory and put your login information there. The format is simple:

```
hostname:port:database:username:password
```

An example would be:

```
192.168.0.45:5432:mydb:xy:abc
```

PostgreSQL offers some nice additional functionality: most fields can contain `*`. Here is an example:

```
*:*:*:xy:abc
```

This means that on every host, on every port, for every database, the user called `xy` will use `abc` as the password. To make PostgreSQL use the `.pgpass` file, make sure that the right file permissions are in place:

```
chmod 0600 ~/.pgpass
```

`.pgpass` can also be used on a Windows system. In this case, the file can be found in the `%APPDATA%\postgresql\pgpass.conf` path.

Using service files

However, there is not just the `.pgpass` file. You can also make use of service files. Here is how it works. If you want to connect to the very same servers over and over again, you can create a `.pg_service.conf` file. It will hold all the connection information you need.

Here is an example of a `.pg_service.conf` file:

```
Mac:~ hs$ cat .pg_service.conf
# a sample service
[hansservice]
host=localhost
port=5432
dbname=test
user=hs
password=abc

[paulservice]
host=192.168.0.45
```

```
port=5432
dbname=xyz
user=paul
password=cde
```

To connect to one of the services, just set the environment and connect:

```
iMac:~ hs$ export PGSERVICE=hansservice
```

A connection can now be established without passing parameters to `psql`:

```
iMac:~ hs$ psql
psql (10.1)
Type "help" for help.
test=#
```

Alternatively, you can use:

```
psql service=hansservice
```

Extracting subsets of data

Up to now, you have seen how to dump an entire database. However, this is not what you might wish for. In many cases, you might just want to extract a subset of tables or schemas. `pg_dump` can do that and provides a number of switches:

- `-a`: It dumps only the data and does not dump the data structure
- `-s`: It dumps only the data structure but skips the data
- `-n`: It dumps only a certain schema
- `-N`: It dumps everything but excludes certain schemas
- `-t`: It dumps only certain tables
- `-T`: It dumps everything but certain tables (this can make sense if you want to exclude logging tables and so on)

Partial dumps can be very useful to speed things up considerably.

Handling various formats

So far, you have seen that `pg_dump` can be used to create text files. The problem is that a text file can only be replayed completely. If you have saved an entire database, you can only replay the entire thing. In many cases, this is not what you want. Therefore, PostgreSQL has additional formats that also offer more functionality.

At this point, four formats are supported:

```
-F, --format=c|d|t|p output file format (custom, directory, tar, plain
text (default))
```

You have already seen plain, which is just normal text. On top of that, you can use a custom format. The idea behind a custom format is to have a compressed dump, including a table of contents. Here are two ways to create a custom format dump:

```
[hs@linuxpc ~]$ pg_dump -Fc test > /tmp/dump.fc
[hs@linuxpc ~]$ pg_dump -Fc test -f /tmp/dump.fc
```

In addition to the table of contents, the compressed dump has one more advantage: it is a lot smaller. The rule of thumb is that a custom format dump is around 90% smaller than the database instance you are about to back up. Of course, this highly depends on the number of indexes and all that, but for many database applications, this rough estimation will hold true.

Once you have created the backup, you can inspect the backup file:

```
[hs@linuxpc ~]$ pg_restore --list /tmp/dump.fc
;
; Archive created at 2017-11-04 15:44:56 CET
; dbname: test
; TOC Entries: 18
; Compression: -1
; Dump Version: 1.12-0
; Format: CUSTOM
; Integer: 4 bytes
; Offset: 8 bytes
; Dumped from database version: 10.1
; Dumped by pg_dump version: 10.1
;
; Selected TOC Entries:
;
3103; 1262 16384 DATABASE - test hs
3; 2615 2200 SCHEMA - public hs
3104; 0 0 COMMENT - SCHEMA public hs
1; 3079 13350 EXTENSION - plpgsql
```

```
3105;  0 0 COMMENT - EXTENSION plpgsql
187;  1259 16391  TABLE  public t_test hs
...
```

`pg_restore --list` will return the table of contents of the backup.

Using a custom format is a good idea as the backup will shrink in size. However, there is more; the `-Fd` command will create a backup in a directory format. Instead of a single file, you will now get a directory containing a couple of files:

```
[hs@linuxpc ~]$ mkdir /tmp/backup
[hs@linuxpc ~]$ pg_dump -Fd test -f /tmp/backup/
[hs@linuxpc ~]$ cd /tmp/backup/
[hs@linuxpc backup]$ ls -lh total 86M
-rw-rw-r--. 1 hs hs 85M Jan 4 15:54 3095.dat.gz
-rw-rw-r--. 1 hs hs 107 Jan 4 15:54 3096.dat.gz
-rw-rw-r--. 1 hs hs 740K Jan 4 15:54 3097.dat.gz
-rw-rw-r--. 1 hs hs 39 Jan 4 15:54 3098.dat.gz
-rw-rw-r--. 1 hs hs 4.3K Jan 4 15:54 toc.dat
```

One advantage of the directory format is that you can use more than one core to perform the backup. In the case of a plain or custom format, only one process will be used by `pg_dump`. The directory format changes that rule. The following example shows how you can tell `pg_dump` to use four cores (jobs):

```
[hs@linuxpc backup]$ rm -rf *
[hs@linuxpc backup]$ pg_dump -Fd test -f /tmp/backup/ -j 4
```

Note that the more objects you have in your database, the more potential speedup there will be.

Replaying backups

Having a backup is pointless unless you have tried to actually replay it. Fortunately, it is easy to do. If you have created a plain text backup, you can simply take the SQL file and execute it:

```
psql your_db < your_file.sql
A plain text backup is simply a text file containing everything. You can
always simply replay a text file.
```

If you have decided on a custom format or directory format, you can use `pg_restore` to replay the backup. `pg_restore` allows you to do all kinds of fancy things such as replaying just part of a database and so on. In most cases, however, you will simply replay the entire database. In my example, I will create an empty database and just replay a custom format dump:

```
[hs@linuxpc backup]$ createdb new_db
[hs@linuxpc backup]$ pg_restore -d new_db -j 4 /tmp/dump.fc
```

Note that `pg_restore` will add data to an existing database. If your database is not empty, `pg_restore` might error out but continue.

Again, `-j` is used to throw up more than one process. In my example, four cores are used to replay the data (this works only if you are going to replay more than one table).



If you are using a directory format, you can simply pass the name of the directory instead of the file.

As far as performance is concerned, dumps are a good solution if you are working with small or medium amounts of data. There are two major downsides:

- You will get a snapshot, so everything since the last snapshot will be lost
- Rebuilding a dump from scratch is comparatively slow compared to binary copies because all the indexes have to be rebuilt

We will take a look at binary backups in Chapter 10, *Making Sense of Backups and Replication*.

Handling global data

In the previous sections, you have learned about `pg_dump` and `pg_restore`, which are two vital programs when it comes to creating backups. The thing is, `pg_dump` creates database dumps—it works on the database level. If you want to back up an entire instance, you have to use `pg_dumpall` or dump all the databases separately. Before we dig into that, it makes sense to see how `pg_dumpall` works:

```
pg_dumpall > /tmp/all.sql
```

`pg_dumpall` will connect to one database after the other and send stuff to standard out, where you can process it with Unix. `pg_dumpall` can be used just like `pg_dump`. However, it has some downsides. It does not support a custom or directory format and therefore does not offer multicore support—you will be stuck with one thread.

However, there is more to `pg_dumpall`. Keep in mind that users live on the instance level. If you create a normal database dump, you will get all the permissions, but you won't get all the `CREATE USER` statements. Those `globals` are not included in a normal dump—they will only be extracted by `pg_dumpall`.

If you only want the `globals`, you can run `pg_dumpall` using the `-g` option:

```
pg_dumpall -g > /tmp/globals.sql
```

In most cases, you might want to run `pg_dumpall -g` along with custom or directory format dumps to extract your instances. A simple backup script might look like this:

```
#!/bin/sh
BACKUP_DIR=/tmp/
pg_dumpall -g > $BACKUP_DIR/globals.sql
for x in $(psql -c "SELECT datname FROM pg_database
WHERE datname NOT IN ('postgres', 'template0', 'template1')" postgres -A -
t)
do
pg_dump -Fc $x > $BACKUP_DIR/$x.fc done
```

It will first dump the `globals` and then loop through the list of databases to extract them one by one in a custom format.

Summary

In this chapter, you have learned about creating backups and dumps in general. So far, binary backups have not been covered, but you are already able to extract textual backups from the server to save and replay your data in the most simplistic way possible.

In Chapter 10, *Making Sense of Backups and Replication*, will be about transaction log shipping, streaming replication, and binary backups. You will learn how to use PostgreSQL onboard tools to replicate instances.

10

Making Sense of Backups and Replication

In *Chapter 9, Handling Backup and Recovery*, you learned a lot about backup and recovery, which is essential for administration. So far, only logical backups have been covered; I am about to change that in this chapter.

This chapter is all about PostgreSQL's transaction log and what you can do with it to improve your setup and to make things more secure.

The following things will be covered:

- What the transaction log does and why it is needed
- Performing point-in-time recovery
- Setting up streaming replication
- Replication conflicts
- Monitoring replication
- Synchronous versus asynchronous replication
- Understanding timelines
- Logical replication

At the end of the chapter, you will be able to set up transaction log archiving and replication. Keep this in mind: this chapter can never be a comprehensive guide to replication; it is only a short introduction. Full coverage of replication would require around 500 pages. Just for a comparison, *PostgreSQL Replication* by Packt Publishing alone is close to 400 pages.

This chapter will cover the most essential things in a more compact form.

Understanding the transaction log

Every modern database system provides functionality to make sure that the system can survive a crash in case something goes wrong or somebody pulls the plug. This is true for filesystems and database systems alike.

PostgreSQL also provides a means to ensure that a crash cannot harm the data's integrity or the data itself. It is guaranteed that if the power cuts out, the system will always be able to come back up again and do its job.

The means to provide this kind of security is provided by the **Write Ahead Log (WAL)** or **xlog**. The idea is to not write into the data file directly, but instead write to the log first. Why is that important? Imagine you are writing some data:

```
INSERT INTO data ... VALUES ('12345678');
```

Suppose data was written directly to the data file. If the operation fails somewhere in the middle, the data file would be corrupted. It might contain half-written rows, columns without index pointers, missing commit information, and so on. As hardware does not really guarantee atomic writes of large chunks of data, a way has to be found to make this more robust. By writing to the log instead of writing to the file directly, the problem can be solved.



In PostgreSQL, the transaction log consists of records.

A single write can consist of various records, which all have a checksum and are chained together. A single transaction might contain B-tree, index, storage manager, commit records, and a lot more. Each type of object has its own WAL entries and ensures that the object can survive a crash. If there is a crash, PostgreSQL will start up and repair the data files based on the transaction log to ensure that no permanent corruption is allowed to happen.

Looking at the transaction log

In PostgreSQL, the WAL can usually be found in the `pg_wal` directory in the data directory (unless specified otherwise on `initdb`). In older versions of PostgreSQL, the WAL directory was called `pg_xlog`, but with the introduction of PostgreSQL 10.0, the directory has been renamed. The reason for that is that more often than not, people would delete the content of the `pg_xlog` directory, which of course led to serious issues and potential database corruption. The community has therefore taken the unprecedented step of renaming a directory inside a PostgreSQL instance. The hope is to make the name scary enough that nobody dares to delete the content again.

The following listing shows what the `pg_wal` directory looks like:

```
[postgres@zenbook pg_xlog]$ pwd
/var/lib/pgsql/10/data/pg_xlog
[postgres@zenbook pg_xlog]$ ls -l
total 688132
-rw-----. 1 postgres postgres 16777216 Jan 19 07:58
000000010000000000000000CD
-rw-----. 1 postgres postgres 16777216 Jan 13 17:04
000000010000000000000000CE
-rw-----. 1 postgres postgres 16777216 Jan 13 17:04
000000010000000000000000CF
-rw-----. 1 postgres postgres 16777216 Jan 13 17:04
000000010000000000000000D0
-rw-----. 1 postgres postgres 16777216 Jan 13 17:04
000000010000000000000000D1
-rw-----. 1 postgres postgres 16777216 Jan 13 17:04
000000010000000000000000D2
```

What you can see is that the transaction log is always a 16 MB file that consists of 24 digits. The numbering is hexadecimal. As you can see, CF is followed by D0. The files are always a fixed size.



One thing to notice is that in PostgreSQL, the number of transaction log files is not related to the size of a transaction. You can have a very small set of transaction log files and still run a multi-TB transaction easily.

Understanding checkpoints

As I have mentioned earlier, every change is written to the WAL in binary format (it does not contain SQL). The problem is this: the database server cannot keep writing to the WAL forever as it will consume more and more space over time. So, at some point, the transaction log has to be recycled. This is done by a **checkpoint**, which happens automatically in the background. The idea is the following: when data is written, it first goes to the transaction log, and then a dirty buffer is put into shared buffers. Those dirty buffers have to go to disk and are written out to the data files by the background writer or during a checkpoint. As soon as all dirty buffers up to that point have been written, the transaction log can be deleted.



Please never ever delete transaction log files manually. In the event of a crash, your database server will not be able to start up again, and the amount of disk space needed will be reclaimed anyway as new transactions come in. Never touch the transaction log manually. PostgreSQL takes care of things on its own, and doing things in there is really harmful.

Optimizing the transaction log

Checkpoints happen automatically and are triggered by the server. However, there are configuration settings that decide when a checkpoint is initiated. The following parameters in the `postgresql.conf` file are in charge of handling checkpoints:

```
#checkpoint_timeout = 5min           # range 30s-1d
#max_wal_size = 1GB
#min_wal_size = 80MB
```

There are two reasons to initiate a checkpoint: we can run out of time or we can run out of space. The maximum time between two checkpoints is defined by the `checkpoint_timeout` variables. The amount of space provided to store transaction logs will vary between the `min_wal_size` and `max_wal_size` variable. PostgreSQL will automatically trigger checkpoints in a way that the amount of space really needed will be between those two numbers.



The `max_wal_size` variable is a soft limit and PostgreSQL may (under heavy load) temporarily need a bit more space. In other words, if your transaction log is on a separate disk, it makes sense to make sure that there is actually a bit more space available to store the WAL.

How can somebody tune the transaction log in PostgreSQL 9.6 and 10.0? In 9.6, some changes have been made to the background writer and checkpointing machinery. In older versions, there were some use cases where smaller checkpoint distances could actually make sense from a performance point of view. In 9.6 and beyond, this has pretty much changed and wider checkpoint distances are basically always highly favorable because many optimizations can be applied at the database and OS-level to speed things up. The most noteworthy optimization is that blocks are sorted before they are written out, which greatly reduces random I/O on mechanical disks.

But there is more. Large checkpoint distances will actually decrease the amount of WAL created. Yes, that is right—larger checkpoint distances will lead to less WAL.

The reason for that is simple. Whenever a block is touched after a checkpoint for the first time, it has to be sent to the WAL completely. If the block is changed more often, only the changes make it to the log. Larger distances basically cause fewer full-page writes, which in turn reduces the amount of WAL created in the first place. The difference can be quite substantial, as can be seen in one of my blog posts: <https://www.postgresql-support.com/checkpoint-distance-and-amount-of-wal/>.

But there is more. PostgreSQL also allows us to configure whether checkpoints should be short and intense or whether they should be spread out over a longer period. The default value is `0.5`, which means that the checkpoint should be done in a way that the process has finished halfway between the current and the next checkpoint:

```
#checkpoint_completion_target = 0.5
```

Increasing this value basically means that the checkpoint is stretched out and less intensive. In many cases, a higher value has proven beneficial for flattening out I/O spikes caused by intense checkpointing.

Transaction log archiving and recovery

After this brief introduction to the transaction log in general, it is time to focus our attention on the process of transaction log archiving. As you have seen, the transaction log contains a sequence of binary changes made to the storage system. So, why not use it to replicate database instances and do a lot of other cool stuff?

Configuring for archiving

The first thing we want to achieve in this chapter is to create a configuration to perform standard **Point-In-Time Recovery (PITR)**. There are a couple of advantages of PITR over ordinary dumps:

- You will lose less data because you can restore to a certain point in time and not just to the fixed backup point
- Restoring will be faster because indexes don't have to be created from scratch. They are just copied over and are ready to use

Configuring for PITR is easy. Just a handful of changes have to be made in the `postgresql.conf` file:

```
wal_level = replica      # used to be "hot_standby" in older versions
max_wal_senders = 10     # at least 2, better at least 2
```

The `wal_level` variable says that the server is supposed to produce enough transaction logs to allow for PITR. If the `wal_level` variable is set to `minimal` (which is the default value up to PostgreSQL 9.6), the transaction log will only contain enough information to recover a single node setup—it is not rich enough to handle replication. In PostgreSQL 10.0, the default value is already correct and there is no longer a need to change most settings.

The `max_wal_senders` variable will allow us to stream WAL from the server. It will allow you to use `pg_basebackup` to create an initial backup instead of traditional file-based copying. The advantage here is that `pg_basebackup` is a lot easier to use. Again, the default value in 10.0 has been changed in a way so that for 90% of all setups, no changes are needed.

The idea behind WAL streaming is that the transaction log created is copied to a safe place for storage. Basically, there are two means of transporting the WAL:

- Using `pg_receivewal` (up to 9.6 known as `pg_receivexlog`)
- Using `filesystem` as a means to archive

In this section, you will see how to set up the second option. During normal operations, PostgreSQL keeps writing to those WAL files. When `archive_mode = on` in the `postgresql.conf` file, PostgreSQL will call the `archive_command` variable for every single file.

A configuration might look like this—first, a directory storing those transaction log files can be created:

```
mkdir /archive
chown postgres.postgres archive
```

The following entries can be changed in the `postgresql.conf` file:

```
archive_mode = on
archive_command = 'cp %p /archive/%f'
```

A restart will enable archiving, but let us configure the `pg_hba.conf` file first to reduce downtime to an absolute minimum.

Note that you can put any command into the `archive_command` variable. Many people use `rsync`, `scp` and others to transport their WAL files to a safe location. If your script returns 0, PostgreSQL will assume that the file has been archived. If anything else is returned, PostgreSQL will try to archive the file again. This is necessary because the database engine has to ensure that no files are lost. To perform the recovery process, not a single file is allowed to go missing.

Configuring the `pg_hba.conf` file

Now that the `postgresql.conf` file has been configured successfully, it is necessary to configure the `pg_hba.conf` file for streaming. Note that this is only necessary if you are planning to use `pg_basebackup`, which is the state-of-the-art tool to create base backups.

Basically, the options you have in the `pg_hba.conf` file are the same you have already seen in Chapter 8, *Managing PostgreSQL Security*. There is just one major issue to keep in mind:

```
# Allow replication connections from localhost, by a user with the
# replication privilege.
```

local	replication	postgres		trust
host	replication	postgres	127.0.0.1/32	trust
host	replication	postgres	:::1/128	trust

You can define standard `pg_hba.conf` file rules. The important thing is that the second column says `replication`. Normal rules are not enough—it is really important to add explicit replication permissions. Also keep in mind that you don't have to do this as a superuser. You can create a specific user who is only allowed to do login and replication.

Again, PostgreSQL 10 and later versions are already configured the way we have outlined in this section. Local replication works out-of-the-box—remote IPs have to be added to `pg_hba.conf`.

Now that the `pg_hba.conf` file has been configured correctly, PostgreSQL can be restarted.

Creating base backups

After teaching PostgreSQL to archive those WAL files, it is time to create a first backup. The idea is to have a backup and to replay WAL files based on that backup to reach any point in time.

To create an initial backup, you can turn to `pg_basebackup`, which is a command-line tool used to perform backups. Let us call `pg_basebackup` and see how it works:

```
pg_basebackup -D /some_target_dir
              -h localhost
              --checkpoint=fast
              --xlog-method=stream
```

As you can see, I am using four parameters here:

- `-D`: Where do you want the base backup to live? PostgreSQL requires an empty directory. At the end of the backup you will see a copy of the server's data directory there (destination).
- `-h`: Indicates the IP address or the name of the master (source). This is the server you want to backup.
- `--checkpoint=fast`: Usually, `pg_basebackup` waits for the master to checkpoint. The reason is that the replay process has to start somewhere. A checkpoint ensures that data has been written up to a certain point and so PostgreSQL can safely jump in there and start the replay process. Basically, it can also be done without the `--checkpoint=fast` parameter. However, it might take a while before `pg_basebackup` starts to copy data in this case. Checkpoints can be up to one hour apart, which can delay your backups unnecessarily.
- `--wal-method=stream`: By default, `pg_basebackup` connects to the master server and starts copying files over. Now, keep in mind that those files are modified while they are copied. The data reaching the backup is therefore inconsistent. This inconsistency can be repaired during the recovery process using the WAL. The backup itself, however, is not consistent. By adding the `--wal-method=stream` parameter it is possible to create a self-contained backup; it can be started directly without replaying the transaction log (this is nice if you just want to clone an instance and not use PITR). Fortunately `--wal-method=stream` is actually already the default in PostgreSQL 10.0. However, in 9.6 or earlier it is recommended to use the predecessor, named `--xlog-method=stream`.

Reducing the bandwidth of a backup

When `pg_basebackup` starts, it tries to finish its work as quickly as possible. If you have a good network connection, `pg_basebackup` is definitely able to fetch hundreds of megabytes a second from the remote server. If your server has a weak I/O system, it could mean that `pg_basebackup` could suck up all the resources easily and end users might experience bad performance because their I/O requests are simply too slow.

To control the maximum transfer rate, `pg_basebackup` offers the following:

```
-r, --max-rate=RATE maximum transfer rate to transfer data directory (in  
kB/s, or use suffix "k" or "M")
```

When you create a base backup, make sure that the disk system on the master can actually stand the load. Adjusting your transfer rate can therefore make a lot of sense.

Mapping tablespaces

`pg_basebackup` can be called directly if you are using an identical filesystem layout on the target system. If this is not the case, `pg_basebackup` allows mapping the master's filesystem layout to the desired layout:

```
-T, --tablespace-mapping=OLDDIR=NEWDIR  
relocate tablespace in OLDDIR to NEWDIR
```



If your system is small, it could be a good idea to keep everything in one tablespace.

This holds true if I/O is not the problem (maybe because you are only managing a few gigabytes of data).

Using different formats

`pg_basebackup` can create various formats. By default, it will put data in an empty directory. Essentially, it will connect to the source server and create a `.tar` over a network connection and put the data into the desired directory.

The trouble with this approach is that `pg_basebackup` will create many files, which is not suitable if you want to move the backup to an external backup solution (maybe Tivoli storage manager or some other solution):

```
-F, --format=p|t output format (plain (default), tar)
```

To create a single file, you can use the `-F=t` option. By default, it will create a file called `base.tar`, which can then be managed more easily. The downside, of course, is that you have to inflate the file again before performing PITR.

Testing transaction log archiving

Before we dig into the actual replay process, it makes sense to actually check archiving to make sure it is working perfectly and as expected:

```
[hs@zenbook archive]$ ls -l
total 212996
-rw----- 1 hs hs 16777216 Jan 30 09:04 00000001000000000000000001
-rw----- 1 hs hs 16777216 Jan 30 09:04 00000001000000000000000002
-rw----- 1 hs hs 302 Jan 30 09:04
0000000100000000000000002.00000028.backup
-rw----- 1 hs hs 16777216 Jan 30 09:20 00000001000000000000000003
-rw----- 1 hs hs 16777216 Jan 30 09:20 00000001000000000000000004
-rw----- 1 hs hs 16777216 Jan 30 09:20 00000001000000000000000005
-rw----- 1 hs hs 16777216 Jan 30 09:20 00000001000000000000000006
...
```

As soon as there is serious activity in the database, WAL files should be sent to the archive.

In addition to just checking for files, the following view can be useful:

```
test=# \d pg_stat_archiver
```

```
View "pg_catalog.pg_stat_archiver"
```

Column	Type	Modifiers
archived_count	bigint	
last_archived_wal	text	
last_archived_time	timestamp with time zone	
failed_count	bigint	
last_failed_wal	text	
last_failed_time	timestamp with time zone	
stats_reset	timestamp with time zone	

The `pg_stat_archiver` system view is very useful for figuring out if and when archiving has stalled for whatever reason. It will tell you about the number of files already archived (`archived_count`). You can also see which file was the last one and when it happened. Finally, the `pg_stat_archiver` system view can tell you when archiving has gone wrong, which is vital information. Unfortunately, the error code or the error message is not shown in the table, but as `archive_command` can be an arbitrary command, it is easy to log.

There is one more thing to see in the archive. As described already, it is important to see that those files are actually archived. But there is more: when the `pg_basebackup` command-line tool is called, you will see a `.backup` file in the stream of WAL files. It is small and contains only some information about the base backup itself—it is purely informative and is not needed by the replay process. However, it gives you some vital clues. When you start to replay the transaction log later on, you can delete all WAL files that are older than the `.backup` file. In this case, our backup file is called `00000001000000000000000002.00000028.backup`. This means that the replay process starts somewhere within file `...0002` (at position `...28`). It also means that we can delete all files older than `...0002`. Older WAL files won't be needed for recovery anymore. Keep in mind that you can keep more than just one backup around, so I am only referring to the current backup.

Now that archiving works, we can turn our attention to the replay process.

Replaying the transaction log

Let us sum up the process so far. We have adjusted the `postgresql.conf` file (`wal_level`, `max_wal_senders`, `archive_mode`, and `archive_command`) and we have allowed for the `pg_basebackup` command in the `pg_hba.conf` file. Then, the database was restarted and a base backup was successfully produced.

Keep in mind that base backups can happen only while the database is fully operational—only a brief restart to change the `max_wal_sender` and `wal_level` variables is needed. The backup can happen only while the database is fully active.

Now the system is working properly, we might face a crash from which we want to recover. Therefore, we can perform PITR to restore as much data as possible. The first thing we've got to do is take the base backup and put it at the desired location.



It can be a good idea to save the old database cluster. Even if it is broken, your PostgreSQL support company might need it to track down the reason for the crash. You can still delete it later on, once you've got everything up and running again.

Given the preceding filesystem layout, you might want to do something like this:

```
cd /some_target_dir cp -Rv * /data
```

I am assuming that your new database server will be located in the `/data` directory. Make sure that the directory is empty before you copy the base backup over.

In the next step, a file called `recovery.conf` can be created. It will contain all the information concerning the replay process such as the position of the WAL archive, the time you want to reach, and all that.



In PostgreSQL 10.0, the `recovery.conf` file will most likely not exist anymore. Settings are expected to be moved to the `postgresql.conf` file. At the time of writing, it is not totally clear what will happen precisely.

Here is a sample `recovery.conf` file:

```
restore_command = 'cp /archive/%f %p'
recovery_target_time = '2019-04-05 15:43:12'
```

After putting the `recovery.conf` file into the `$PGDATA` directory, you can simply start up your server. The output might look like this:

```
server starting
LOG: database system was interrupted; last known up
      at 2017-01-30 09:04:07 CET
LOG: starting point-in-time recovery to 2019-04-05 15:43:12+02
LOG: restored log file "000000010000000000000002" from archive
LOG: redo starts at 0/2000028
LOG: consistent recovery state reached at 0/20000F8
LOG: restored log file "000000010000000000000003" from archive
LOG: restored log file "000000010000000000000004" from archive
LOG: restored log file "000000010000000000000005" from archive
...
LOG: restored log file "00000001000000000000000E" from archive
cp: cannot stat '/archive/00000001000000000000000F':
      No such file or directory
LOG: redo done at 0/E7BF710
LOG: last completed transaction was at log time
      2017-01-30 09:20:47.249497+01
```

```
LOG: restored log file "000000010000000000000000E" from archive
cp: cannot stat '/archive/00000002.history': No such file or directory
LOG: selected new timeline ID: 2
cp: cannot stat '/archive/00000001.history': No such file or directory
LOG: archive recovery complete
LOG: MultiXact member wraparound protections are now enabled
LOG: database system is ready to accept connections
LOG: autovacuum launcher started
```

When the server is started, there are a couple of messages to look for to ensure that your recovery works perfectly: the first one is consistent recovery state reached. This message means that PostgreSQL could replay enough of the transaction log to bring the database back to a state that makes it usable.

Then, PostgreSQL will copy one file after the other and replay them. However, remember we have told the `recovery.conf` file to bring us all the way up to 2019. This text is written in 2017 so there is clearly not enough WAL to reach 2019. Therefore, PostgreSQL will error out and tell us about the last completed transaction.

Of course, this is just a showcase, and in real-world examples you will most likely use a date in the past, which you can use to safely recover. However, I wanted to show that it is perfectly feasible to use a date in the future—just be prepared to accept the fact that errors will happen.

After the recovery has finished, the `recovery.conf` file will be renamed `recovery.done` so that you can see what you have done during recovery. All the processes of your database server will be up and running and you will have a ready-to-use database instance.

Finding the right timestamp

So far, I have silently assumed that you know the timestamp you want to recover to, or that you simply want to replay the whole transaction log to reduce data loss. However, what if you don't want to replay everything? What if you don't know which point in time to recover to? In everyday life, this is actually a very common scenario. One of your developers loses some data in the morning and you are supposed to make things fine again. The trouble is this: at what time in the morning? Once recovery has ended, it cannot be restarted easily. Once recovery is completed, the system will be promoted, and once it has been promoted, you cannot continue to replay WAL.

However, what you can do is pause recovery without promotion, check what is inside the database, and continue.

Doing that is easy. The first thing you have to make sure of is that the `hot_standby` variable is set to `on` in the `postgresql.conf` file. This will make sure that the database is readable while it is still in recovery mode. Then you have to adapt the `recovery.conf` file before starting the replay process:

```
recovery_target_action = 'pause'
```

There are various `recovery_target_action` settings. If you use `pause`, PostgreSQL will pause at the desired time and let you check what has already been replayed. You can adjust the time you want, restart, and try again. Alternatively, you can set the value to `promote` or `shutdown`.

There is a second way to pause transaction log replay. Basically, it can also be used when performing PITR. However, in most cases, it is used with streaming replication. Here is what can be done during WAL replay:

```
postgres=# \x
Expanded display is on.
postgres=# \df *pause*
List of functions
-[ RECORD 1 ]-----+-----
Schema          | pg_catalog
Name             | pg_is_wal_replay_paused
Result data type | boolean
Argument data types |
Type            | normal
-[ RECORD 2 ]-----+-----
Schema          | pg_catalog
Name             | pg_wal_replay_pause
Result data type | void
Argument data types |
Type            | normal

postgres=# \df *resume*
List of functions
-[ RECORD 1 ]-----+-----
Schema          | pg_catalog
Name             | pg_wal_replay_resume
Result data type | void
Argument data types |
Type            | normal
```

You can call the `SELECT pg_wal_replay_pause();` command to halt WAL replay until you call the `SELECT pg_wal_replay_resume();` command.

The idea is to figure out how much WAL has already been replayed and to continue as necessary. However, keep this in mind: once a server has been promoted, you cannot just continue to replay WAL without further precautions.

As you have seen already, it can be pretty tricky to figure out how far you have to recover. Therefore, PostgreSQL provides some help. Consider the following real-world example: at midnight, you are running a nightly process that ends at some point that is usually not known. The goal is to recover exactly to the end of the nightly process. The trouble is this: how do you know when the process has ended? In most cases, this is hard to figure out. So why not add a marker to the transaction log:

```
postgres=# SELECT pg_create_restore_point('my_daily_process_ended');
pg_create_restore_point
-----
1F/E574A7B8
(1 row)
```

If your process calls this SQL statement as soon as it ends, it will be possible to use this label in the transaction log to recover exactly to this point in time by adding the following directive to the `recovery.conf` file:

```
recovery_target_name = 'my_daily_process_ended'
```

Use this setting instead of `recovery_target_time` and the replay process will beam you exactly to the end of the nightly process.

Of course, you can also replay up to a certain transaction ID. However, in real life, this has proven to be difficult as the exact transaction ID is rarely ever known to the administrator, and therefore, there is not much practical value here.

Cleaning up the transaction log archive

So far, data is being written to the archive all the time and no attention has been paid to cleaning out the archive again to free up some space in the filesystem. PostgreSQL cannot do this job for you because it has no idea whether you want to use the archive again. Therefore, you are in charge of cleaning up the transaction log. Of course, you can also use a backup tool—however, it is important to know that PostgreSQL has no chance of doing the cleanup for you.

Suppose we want to clean up an old transaction log that is not needed anymore. Maybe you want to keep several base backups around and clean out all transaction logs that won't be needed anymore to restore one of those backups.

In this case, the `pg_archivecleanup` command-line tool is exactly what you need. You can simply pass the archive directory and the name of the backup file to the `pg_archivecleanup` command, and it will make sure that files are removed from disk. Using this tool makes life easier for you because you don't have to figure out which transaction log files to keep on your own. Here is how it works:

```
[hs@pgnode01 ~]$ pg_archivecleanup --help
pg_archivecleanup removes older WAL files from PostgreSQL archives.
```

Usage:

```
pg_archivecleanup [OPTION]... ARCHIVELOCATION OLDESTKEPTWALFILE
```

Options:

```
-d generate debug output (verbose mode)
-n dry run, show the names of the files that
    would be removed
-V, --version output version information, then exit
-x EXT clean up files if they have this extension
-?, --help show this help, then exit
```

For use as `archive_cleanup_command` in `recovery.conf` when `standby_mode = on`:

```
archive_cleanup_command = 'pg_archivecleanup
    [OPTION]... ARCHIVELOCATION %r'
```

e.g.

```
archive_cleanup_command = 'pg_archivecleanup
    /mnt/server/archiverdir %r'
```

Or for use as a standalone archive cleaner:

e.g.

```
pg_archivecleanup /mnt/server/archiverdir
    00000001000000000000000010.00000020.backup
```

The tool can be used easily. It is available on all platforms.

Setting up asynchronous replication

After taking a look at transaction log archiving and PITR, we can focus our attention on one of the most widely used features in the PostgreSQL world today: streaming replication. The idea behind streaming replication is simple. After an initial base backup, the secondary can connect to the master and fetch a transaction log in real time and apply it. Transaction log replay is not a single operation anymore, but rather a continuous process that is supposed to keep running as long as the cluster exists.

Performing a basic setup

In this section, you will learn how to set up asynchronous replication quickly and easily. The goal is to set up a system consisting of two nodes.

Basically, most of the work has already been done for WAL archiving. However, to make it easy for you I will explain the entire process of setting up streaming, because we cannot assume that WAL shipping is really already set up as needed.

The first thing to do is to go to the `postgresql.conf` file and adjust the following parameters (note that some of them are already default in PostgreSQL 10.0):

```
wal_level = replica
max_wal_senders = 5 # or whatever value >= 2
hot_standby = on    # already a sophistication
```

Just like previously, the `wal_level` variable has to be adjusted to ensure that PostgreSQL produces enough transaction logs to sustain a slave. Then we have to configure the `max_wal_senders` variable. When a slave is up and running or when a base backup is created, a WAL sender process will talk to a WAL receiver process on the client side. The `max_wal_senders` setting allows PostgreSQL to create enough processes to serve those clients.



Theoretically, it is enough to have just one WAL sender process. However, it is pretty inconvenient. A base backup that uses the `--wal-method=stream` parameter will already need two WAL sender processes. If you want to run a slave and perform a base backup at the same time, there are already three processes in use. So, make sure that you allow PostgreSQL to create enough processes to prevent pointless restarts.

Then comes the `hot_standby` variable. Basically, a master ignores the `hot_standby` variable and does not take it into consideration. All it does is make the slave readable during WAL replay. So why do we care? Keep in mind: the `pg_basebackup` command will clone the entire server, including its configuration. This means that if you have already set the value on the master, the slaves will automatically get it when the data directory is cloned.

After setting the `postgresql.conf` file, we can turn our attention to the `pg_hba.conf` file: just allow the slave to perform replication by adding rules. Basically, those rules are the same as you have already seen for PITR.

Then, restart the database server as has been done for PITR already.

Then, the `pg_basebackup` command can be called on the slave. Before you do that, make sure that the `/target` directory is empty. If you are using RPM packages, ensure that you shut down a potentially running instance and empty the directory (for example, `/var/lib/pgsql/data`):

```
pg_basebackup -D /target
               -h master.example.com
               --checkpoint=fast
               --xlog-method=stream -R
```

Just replace the `/target` directory with your desired destination directory and replace `master.example.com` with the IP or DNS name of your master. The `--checkpoint=fast` parameter will trigger an instant checkpoint. Then there is the `--wal-method=stream` parameter: it will open two streams. One will copy the data; the other one will fetch the WAL, which is created while the backup is running.

Finally, there is the `-R` flag:

```
-R, --write-recovery-conf
write recovery.conf after backup
```

The `-R` flag is a really good feature. The `pg_basebackup` command has the ability to automatically create the slave configuration. It will add various entries to the `recovery.conf` file:

```
standby_mode = on primary_conninfo = ' ... '
```

The first setting says that PostgreSQL should keep replaying WAL all the time—if the whole transaction log has been replayed, it should wait for a new WAL to arrive. The second setting will tell PostgreSQL where the master is. It is a normal database connection.



Slaves can also connect to other slaves to stream transaction logs. It is possible to cascade replication by simply creating base backups from a slave. So, *master* really means source server in this context.

After running the `pg_basebackup` command, the services can be already started. The first thing you should check is whether the master shows a WAL sender process:

```
[hs@linuxpc ~]$ ps ax | grep sender
17873 ? Ss 0:00 postgres: wal sender process
                  ah ::1(57596) streaming 1F/E9000060
```

If there is one, the slave will also carry a WAL receiver process:

```
17872 ? Ss 0:00 postgres: wal receiver process
                        streaming 1F/E9000060
```

If those processes are there, you are already on the right track and replication is working as expected. Both sides are now talking to each other and WAL flows from the master to the slave.

Improving security

So far, you have seen that data is streamed as a superuser. However, it is not a good idea to allow super access from a remote side. Fortunately, PostgreSQL allows you to create a user that is only allowed to consume the transaction log stream but cannot do anything else.

Creating a user just for streaming is easy:

```
test=# CREATE USER repl LOGIN REPLICATION;
CREATE ROLE
```

By assigning replication to the user, it is possible to use it just for streaming—everything else is forbidden.

It is highly recommended to not use your superuser account to set up streaming. Simply change the `recovery.conf` file to the newly created user. Not exposing superuser accounts will dramatically improve security (just like giving the replication user a password).

Halting and resuming replication

Once streaming replication has been set up, it works flawlessly without too much administrator intervention. However, in some cases it might make sense to halt replication and to resume it at some later point. Why would anybody want to do that?

Consider the following use case: you are in charge of a master/slave setup, which is running some rubbish CMS or some dubious forum software. Suppose you want to update your application from awful CMS 1.0 to dreadful CMS 2.0. Some changes will be executed in your database, which will instantly be replicated to the slave database. What if the upgrade process does something wrong? The error will instantly be replicated to both nodes due to streaming.

To avoid instant replication you can halt replication and resume as needed. In the case of our CMS update we could simply do the following things:

1. Halt replication
2. Perform the app update on the master
3. Check if your application still works. If yes, resume replication. If not, failover to the replica, which still has the old data

With this mechanism you can protect your data, because you can fall back to the data as it was before the problem. You will learn later in this chapter how to promote a slave to become the new master server.

The main question now is: how can you halt replication? Here is how it works. Execute the following line on the standby:

```
test=# SELECT pg_wal_replay_pause();
```

This line will halt replication. Note that the transaction log will still flow from the master to the slave—only the replay process is halted. Your data is still protected as it is persisted on the slave. In case of a server crash, no data will be lost.

Keep in mind that replay has to be halted on the slave. Otherwise, an error will be thrown by PostgreSQL:

```
ERROR: recovery is not in progress
HINT: Recovery control functions can only be executed during recovery.
```

Once replication is to be resumed, the following line will be needed on the slave:

```
SELECT pg_wal_replay_resume();
```

PostgreSQL will start to replay WAL again.

Checking replication to ensure availability

One of the core jobs of every administrator is to ensure that replication stays up and running all the time. If replication is down, it is possible that data could be lost if the master crashes. Therefore, keeping an eye on replication is absolutely necessary.

Fortunately, PostgreSQL provides system views, which allow you to take a deep look at what is going on. One of those views is `pg_stat_replication`:

```
test=# \d pg_stat_replication
        View "pg_catalog.pg_stat_replication"
```

Column	Type	Modifiers
<code>pid</code>	<code>integer</code>	
<code>usesysid</code>	<code>oid</code>	
<code>username</code>	<code>name</code>	
<code>application_name</code>	<code>text</code>	
<code>client_addr</code>	<code>inet</code>	
<code>client_hostname</code>	<code>text</code>	
<code>client_port</code>	<code>integer</code>	
<code>backend_start</code>	<code>timestamp with time zone</code>	
<code>backend_xmin</code>	<code>xid</code>	
<code>state</code>	<code>text</code>	
<code>sent_lsn</code>	<code>pg_lsn</code>	
<code>write_lsn</code>	<code>pg_lsn</code>	
<code>flush_lsn</code>	<code>pg_lsn</code>	
<code>replay_lsn</code>	<code>pg_lsn</code>	
<code>write_lag</code>	<code>interval</code>	
<code>flush_lag</code>	<code>interval</code>	
<code>replay_lag</code>	<code>interval</code>	
<code>sync_priority</code>	<code>integer</code>	
<code>sync_state</code>	<code>text</code>	

The `pg_stat_replication` view will contain information on the sender. I don't want to use the word master here because slaves can be connected to some other slave. It is possible to build a tree of servers. In the case of a tree of servers, the master will only have information about the slaves it is directly connected to.

The first thing you will see in this view is the process ID of the WAL sender process. It helps you to identify the process in case something goes wrong (which is usually not the case). Then you will see the username the slave uses to connect to its sending server. The `client_*` fields will indicate where the slaves are. You will be able to extract network information from those fields. The `backend_start` field shows when the slaves started to stream from your server.

Then there is this magical `backend_xmin` field. Suppose you are running a master/slave setup. It is possible to tell the slave to report back its transaction ID to the master. The idea behind that is to delay cleanup on the master so that data is not taken from a transaction running on the slave.

The `state` field informs you about the state of the server. If your system is fine, the field will contain `streaming`. Otherwise, closer inspection is needed.

The next four fields are really important. The `sent_lsn` field, formerly the `sent_location` field, indicates how much WAL has already reached the other side (accepted by the WAL receiver). You can use it to figure out how much data has already made it to the slave. Then there is the `write_lsn` field, formerly the `write_location` field. Once the WAL has been accepted, it is passed on to the OS. The `write_lsn` field will tell us the WAL position that has safely made it to the OS already. The `flush_lsn` field, formerly the `flush_location` field, will know how much WAL the database has already flushed to disk.

Finally, there is the `replay_lsn`, formerly `replay_location` field. The fact that the WAL has made it to the disk on the standby does not mean that PostgreSQL has already replayed (made visible to the end user) yet. Suppose replication is paused. Data will still flow to the standby. However, it will be applied later. The `replay_lsn` field will tell you how much data is already visible.

In PostgreSQL 10, more fields have been added to `pg_stat_replication`: the `*_lag` fields indicate the delay of the slave and offer a convenient way to see how far a slave is behind. Note that the fields are at intervals so you can see the time difference directly.

Finally, PostgreSQL tells us whether replication is synchronous or asynchronous.

If you are still on PostgreSQL 9.6 you might find it useful to calculate the difference between the sending and the receiving server in bytes. The `*_lag` fields don't for 9.6 yet so having the difference in bytes can be very beneficial. Here is how it works:

```
SELECT client_addr, pg_current_wal_location() - sent_location AS diff FROM
pg_stat_replication;
```

When running this on the master, the `pg_current_wal_location()` function returns the current transaction log position. PostgreSQL 9.6 has a special datatype for transaction log positions called `pg_lsn`. It features a couple of operators, which are used here to subtract the slave's WAL position from the master's WAL position. The view outlined here therefore returns the difference between two servers in bytes (replication delay).

Note that this statement only works in PostgreSQL 10. The function used to be called `pg_current_xlog_location()` in older releases.

While the `pg_stat_replication` system view contains information on the sending side, the `pg_stat_wal_receiver` system view will provide you with similar information on the receiving side:

```
test=# \d pg_stat_wal_receiver
          View "pg_catalog.pg_stat_wal_receiver"
Column          | Type          | Modifiers
-----+-----+-----
pid             | integer       |
status          | text          |
receive_start_lsn | pg_lsn        |
receive_start_tli | integer       |
received_lsn     | pg_lsn        |
received_tli     | integer       |
last_msg_send_time | timestamp with time zone |
last_msg_receipt_time | timestamp with time zone |
latest_end_lsn   | pg_lsn        |
latest_end_time  | timestamp with time zone |
slot_name       | text          |
conninfo        | text          |
```

After the process ID of the WAL receiver process, PostgreSQL will provide you with the status of the process. Then the `receive_start_lsn` field will tell you about the transaction log position the WAL receiver started at, while the `receive_start_tli` field will inform us about the timeline used when the WAL receiver was started.

The `received_lsn` field contains information about the WAL position, which was already received and flushed to disk. Then we've got some information about the time as well as information about slots and connections.

In general, many people find it easier to read the `pg_stat_replication` system view than the `pg_stat_wal_receiver` view and most tools are built around the `pg_stat_replication` view.

Performing failovers and understanding timelines

Once a master/slave setup has been created, it usually works flawlessly for a very long time. However, everything can fail, and therefore it is important to understand how a failed server can be replaced with a backup system.

PostgreSQL makes failovers and promotion easy. Basically, all you have to do is use the `pg_ctl` parameter to tell a replica to promote itself:

```
pg_ctl -D data_dir promote
```

The server will disconnect itself from the master and perform the promotion instantly. Remember, the slave might already support thousands of read-only connections while being promoted. One nice feature of PostgreSQL is that all open connections will be turned into read/write connections during promotion—there is not even a need to reconnect.

When promoting a server, PostgreSQL will increment the timeline: if you set up a brand new server, it will be in timeline one. If a slave is cloned from that server, it will be in the same timeline as its master. So, both boxes will be in timeline one. If the slave is promoted to an independent master, it will move on to timeline two.

Timelines are especially important to PITR. Suppose you have created a base backup around midnight. At 12:00 AM, the slave is promoted. At 3:00 PM, something crashes and you want to recover to 2:00 PM. You will replay the transaction log created after the base backup and follow the WAL stream of your desired server, as those two nodes started to diverge at 12.00 AM.

The timeline change will also be visible in the name of the transaction log files. Here is an example of a WAL file in timeline one:

```
000000010000000000000000F5
```

If the timeline switches to 2 the new filename would be as follows:

```
000000020000000000000000F5
```

As you can see, WAL files from different timelines could theoretically exist in the same archive directory.

Managing conflicts

So far, you have learned a lot about replication. In the next step, it is important to take a look at replication conflicts. The main question that arises is this: how can a conflict ever happen in the first place?

Consider the following example:

Master	Slave
	BEGIN;
	SELECT ... FROM tab WHERE ...
	... running ...
DROP TABLE tab;	... conflict happens ...
	... transaction is allowed to continue for 30 seconds ...
	... conflict is resolved or ends before timeout ...

The problem here is that the master does not know that there is a transaction happening on the slave. Therefore, the `DROP TABLE` command does not block until the reading transaction is gone. If those two transactions happened on the same node, this would of course be the case. However, we are looking at two servers here. The `DROP TABLE` command will execute normally, and a request to kill those data files on disk will reach the slave through the transaction log. The slave is not in trouble: if the table is removed from disk, the `SELECT` clause has to die—if the slave waits for the `SELECT` clause to complete before applying the WAL, it might fall hopelessly behind.

The ideal solution is a compromise that can be controlled using a configuration variable:

```
max_standby_streaming_delay = 30s
# max delay before canceling queries
# when reading streaming WAL;
```

The idea is to wait for 30 seconds before resolving the conflict by killing the query on the slave. Depending on your application, you might want to change this variable to a more or less aggressive setting. Note that 30 seconds is for the entire replication stream and not for a single query. It might be that a single query is killed a lot earlier because some other query has already waited for some time.

While the `DROP TABLE` command is clearly a conflict, there are some operations that are less obvious. Here is an example:

```
BEGIN;  
...  
DELETE FROM tab WHERE id < 10000;  
COMMIT;  
...  
VACUUM tab;
```

Let us assume again that there is a long-running `SELECT` clause happening on the slave. The `DELETE` clause is clearly not the problem here as it only flags the row as deleted—it does not actually remove it. Nor is the commit a problem, because it simply marks the transaction as done. Physically, the row is still there.

The problem starts when an operation such as vacuum kicks in. It will destroy the row on disk. Of course, those changes will make it to the WAL and eventually reach the slave, which is now in trouble.

To prevent typical problems caused by standard OLTP workloads, the PostgreSQL development team has introduced a config variable:

```
hot_standby_feedback = off  
    # send info from standby to prevent  
    # query conflicts
```

If this setting is `on`, the slave will periodically send the oldest transaction ID to the master. The vacuum will then know that there is an older transaction going on somewhere in the system and defer the cleanup age to a later point when it is safe to clean out those rows. In fact, the `hot_standby_feedback` parameter causes the same effect as a long transaction on the master.

As you can see, the `hot_standby_feedback` parameter is `off` by default. Why is that the case? Well, there is a good reason for that: if it is `off`, a slave does not have a real impact on the master. Transaction log streaming does not consume a lot of CPU power, making streaming replication cheap and efficient. However, if a slave (which might not even be under your control) keeps transactions open for too long, your master might suffer from table bloat due to late cleanup. In a default setup this is less desirable than reduced conflicts.

Having `hot_standby_feedback = on` will usually avoid 99% of all OLTP-related conflicts, which is especially important if your transactions take longer than just a couple of milliseconds.

Making replication more reliable

In this chapter, you have already seen that setting up replication is easy and does not require a lot of effort. However, there are always some corner cases which can cause operational challenges. One of those corner cases is all about transaction log retention.

Consider the following scenario:

1. A base backup is fetched
2. After the backup, nothing happens for one hour
3. The slave is started

Keep in mind that the master does not care too much about the existence of the slave. Therefore, the transaction log needed for the slave to start up might not exist on the master anymore as it might have been removed by checkpoints already. The problem is that a re-sync is needed to be able to fire up the slave. In the case of a multi-TB database, this is clearly a problem.

A potential solution to the problem is to use the `wal_keep_segments` setting:

```
wal_keep_segments = 0      # in logfile segments, 16MB each; 0 disables
```

By default, PostgreSQL keeps enough transaction logs around to survive an unexpected crash, but not much more. With the `wal_keep_segments` setting, you can tell the server to preserve more data so that a slave can catch up even if it falls behind.

It is important to keep in mind that servers not only fall behind because they are too slow or too busy—in many cases, a delay happens because the network is too slow. Suppose you are creating an index on a 1 TB table: PostgreSQL will sort the data, and when the index is actually built it is also sent to the transaction log. Just imagine what happens when hundreds of megabytes of WAL is sent over a wire that can maybe only handle 1 gigabyte or so. The loss of many gigabytes of data might be the consequence within seconds. Therefore, adjusting the `wal_keep_segments` setting should not focus on the typical delay but on the highest delay tolerable to the administrator (maybe some margin of safety).

Investing in a reasonably high setting for the `wal_keep_segments` setting makes a lot of sense, and I recommend ensuring that there is always enough data around.

An alternative solution to the problem of running out of transaction logs is replication slots, which will be covered later in this chapter.

Upgrading to synchronous replication

So far, asynchronous replication has been covered in reasonable detail. However, asynchronous replication means that a commit on the slave is allowed to happen after the commit on the master. If a master crashes, data that has not made it to the slave yet might be lost even if replication is occurring.

Synchronous replication is here to solve the problem: if PostgreSQL replicates synchronously, a commit has to be flushed to disk by at least one replica in order to go through on the master. Therefore, synchronous replication basically reduces the odds of data loss quite substantially.

In PostgreSQL, configuring synchronous replication is easy. Basically, just two things have to be done:

- Adjust the `synchronous_standby_names` setting in the `postgresql.conf` file on the master
- Add an `application_name` setting to the `primary_conninfo` parameter in the `recovery.conf` file in the replica

Let us get started with the `postgresql.conf` file on the master:

```
synchronous_standby_names = ''
    # standby servers that provide sync rep
    # number of sync standbys and comma-separated
    # list of application_name
    # from standby(s); '*' = all
```

If you put in `'*'`, all nodes will be considered as synchronous candidates. However, in real-life scenarios it is more likely that only a couple of nodes will be listed. Here is an example:

```
synchronous_standby_names = 'slave1, slave2, slave3'
```

Now we have to change the `recovery.conf` file and add `application_name`:

```
primary_conninfo = '... application_name=slave2'
```

The replica will now connect to the master as `slave2`. The master will check its config and figure that `slave2` is the first one in the list that makes a viable slave. PostgreSQL will therefore ensure that a commit on the master will only be successful if the slave confirms that the transaction is there.

Let us assume now that `slave2` goes down for some reason: PostgreSQL will try to turn one of the other two nodes into a synchronous standby. The problem is this: what if there is no other server? In this case, PostgreSQL will wait on commit forever if a transaction is supposed to be synchronous. Yes, this is true: PostgreSQL will not continue to commit unless there are at least two viable nodes available. Remember, you have asked PostgreSQL to store data on at least two nodes—if you cannot provide enough hosts at any given point in time, it is your fault. In reality, this means that synchronous replication is best achieved with at least three nodes: one master and two slaves, as there is always a chance that one host is lost.

Talking about host failures, there is an important thing to note at this point: if a synchronous partner dies while a commit is going in, PostgreSQL will wait for it to return. Alternatively, the synchronous commit can happen with some other potential synchronous partner. The end user might not even notice that the synchronous partners change.

In some cases, storing data on just two nodes might not be enough: maybe you want to improve safety even more and store data on even more nodes. To achieve that, you can make use of the following syntax (in PostgreSQL 9.6 or higher):

```
synchronous_standby_names =  
'4(slave1, slave2, slave3, slave4, slave5, slave6)'
```

In this case, data is supposed to end up on four out of six nodes before the commit is confirmed by the master.

Of course, this comes with a price tag—keep in mind that speed will go down if you add more and more synchronous replicas. There is no such thing as a free lunch. PostgreSQL provides a couple of ways to keep the performance overhead under control, which we'll discuss in the following section.

In PostgreSQL 10, even more functionality has been added:

```
[FIRST] num_sync ( standby_name [, ...] )  
ANY num_sync ( standby_name [, ...] )  
standby_name [, ...]
```

The `ANY` and `FIRST` keywords have been introduced. `FIRST` allows you to set the priorities of your servers, while `ANY` gives PostgreSQL a bit more flexibility when it commits a synchronous transaction.

Adjusting durability

In this chapter, you have seen that data is either replicated synchronously or asynchronously. However, this is not a global thing. To ensure good performance, PostgreSQL allows you to configure things in a very flexible way. It is possible to replicate everything synchronously or asynchronously, but in many cases you might want to do things in a more fine-grained way. This is exactly when the `synchronous_commit` setting is needed.

Assuming that synchronous replication has been configured (the `application_name` setting in the `recovery.conf` file as well as the `synchronous_standby_names` setting in the `postgresql.conf` file), the `synchronous_commit` setting will offer the following options:

- `off`: This is basically asynchronous replication. WAL won't be flushed to disk on the master instantly and the master won't wait for the slave to write everything to disk. If the master fails, some data might be lost (up to three times `wal_writer_delay`).
- `local`: The transaction log is flushed to disk on commit on the master. However, the master does not wait on the slave (asynchronous replication).
- `remote_write`: The `remote_write` setting already makes PostgreSQL replicate synchronously. However, only the master saves data to disk. For the slave, it is enough to send the data to the operating system. The idea is to not wait for the second disk flush to speed things up. It is very unlikely that both storage systems crash at exactly the same time. Therefore, the risk of data loss is close to zero.
- `on`: In this case, a transaction is okay if the master and the slave(s) have successfully flushed the transaction to disk. The application will not receive a commit unless data is safely stored on two servers (or more, depending on the configuration).

- `remote_apply`: While `on` ensures that data is safely stored on two nodes, it does not guarantee that you can simply load balance right away. The fact that data is flushed on the disk does not ensure that the user can already see the data. For example, if there is a conflict, a slave will halt transaction replay—however, a transaction log is still sent to the slave during a conflict and flushed to disk. In short, it can happen that data is flushed on the slave even if it is not visible to the end user yet. The `remote_apply` option fixes this problem. It ensures that data must be visible on the replica so that the next read request can be safely executed on the slave, which can already see the changes made to the master and expose them to the end user. The `remote_apply` option is, of course, the slowest way to replicate data because it requires the slave to already expose the data to the end user.

In PostgreSQL, the `synchronous_commit` parameter is not a global value. It can be adjusted on various levels, just like many other settings. You might want to do something like this:

```
test=# ALTER DATABASE test SET synchronous_commit TO off;  
ALTER DATABASE
```

Sometimes, only a single database should replicate in a certain way. It is also possible to just synchronously replicate if you are connected as a specific user. Last but not least, it is also possible to tell a single transaction how to commit. By adjusting the `synchronous_commit` parameter on the fly it is even possible to control things on a per-transaction level.

For example, consider the following two scenarios:

- Writing to a log table where you might want to use asynchronous commit because you want to be quick
- Storing a credit card payment where you want to be safe so a synchronous transaction might be the desired thing

As you can see, the very same database might have different requirements depending on which data is modified. Therefore, changing data at the transaction level is very useful and helps to improve speed.

Making use of replication slots

After that introduction to synchronous replication and dynamically adjustable durability, I want to focus your attention on a feature called the replication slot.

What is the purpose of a replication slot? Let us consider the following example: there is a master and a slave. On the master, a large transaction is executed and the network connection is not fast enough to ship all the data in time. At some point, the master removes its transaction log (checkpoint). If the slave is too far behind, a re-sync is needed. As you have already seen, the `wal_keep_segments` setting can be used to reduce the risk of failing replication. The question is this: what is the best value for the `wal_keep_segments` setting? Sure, more is better, but how much is best?

Replication slots will solve this problem for you: if you are using a replication slot, a master can only recycle the transaction log once it has been consumed by all replicas. The advantage here is that a slave can never fall behind so much that a re-sync is needed.

The trouble is, suppose you shut down a replica without telling the master about it. The master would keep a transaction log forever and the disk on the primary server would eventually fill up, causing unnecessary downtime.

To reduce the risk for the master, replication slots should only be used in conjunction with proper monitoring and alerting. It is simply necessary to keep an eye on open replication slots that could potentially cause issues, or might not be in use anymore.

In PostgreSQL there are two types of replication slot:

- Physical replication slots
- Logical replication slots

Physical replication slots can be used for standard streaming replication. They will make sure that data is not recycled too early. Logical replication slots do the same thing. However, they are used for logical decoding. The idea behind logical decoding is to give users a chance to attach to the transaction log and decode it with a plugin. A logical transaction slot is therefore some sort of tail -f for database instances. It allows the user to extract changes made to the database—and therefore to the transaction log—in any format and for any purpose. In many cases, a logical replication slot is used for logical replication.

Handling physical replication slots

To make use of replication slots, changes have to be made to the `postgresql.conf` file:

```
wal_level = logical
max_replication_slots = 5    # or whatever number is needed
```

With physical slots, logical is not yet necessary—replica is enough. However, for logical slots, we need a higher `wal_level` setting. Then the `max_replication_slots` setting has to be changed if you are on PostgreSQL 9.6 or below. PostgreSQL 10 already has the improved default setting. Basically, just put in a number that serves your purpose. My recommendation is to add some spare slots so that you can easily attach more consumers without restarting the server along the way.

After a restart, the slot can be created:

```
test=# \x
Expanded display is on.

test=# \df *create*physical*slot*
List of functions

-[ RECORD 1 ]-----+-----
Schema          | pg_catalog
Name             | pg_create_physical_replication_slot
Result data type | record
Argument data types | slot_name name, immediately_reserve
                  | boolean DEFAULT false, temporary
                  | boolean DEFAULT false, OUT slot_name
                  | name, OUT lsn pg_lsn
Type             | normal
```

The `pg_create_physical_replication_slot` function is here to help you create the slot. It can be called with one of two parameters: if only a slot name is passed, the slot will be active when it is used for the first time. If `true` is passed as the second parameter, the slot will immediately start to conserve the transaction log:

```
test=# SELECT * FROM pg_create_physical_replication_slot('some_slot_name',
true);
 slot_name          | lsn
-----+-----
 some_slot_name    | 0/EF8AD1D8

(1 row)
```

To see which slots are active on the master, consider running the following SQL statement:

```
test=# \x
Expanded display is on.
test=# SELECT * FROM pg_replication_slots;
-[ RECORD 1 ]-----+-----
slot_name          | some_slot_name
plugin             |
slot_type          | physical
datoid             |
database           |
active             | f
active_pid         | xmin
                  |
catalog_xmin       |
restart_lsn        |
0/EF8AD1D8 confirmed_flush_lsn |
```

The view will tell us a lot about the slot. It contains information about the type of slot in use, the transaction log positions, and more.

To make use of the slot, all you have to do is to add it to the `recovery.conf` file:

```
primary_slot_name = 'some_slot_name'
```

Once streaming is restarted, the slot will be used directly and protect replication. If you don't want your slot anymore, you can drop it easily:

```
test=# \df *drop*slot*
List of functions
-[ RECORD 1 ]-----+-----
Schema          | pg_catalog
Name            | pg_drop_replication_slot
Result data type | void
Argument data types | name
Type            | normal
```

When a slot is dropped, there is no distinction between a logical and a physical slot anymore. Just pass the name of the slot to the function and execute it.



Nobody is allowed to use the slot when it is dropped. Otherwise, PostgreSQL will error out (for good reason).

Handling logical replication slots

Logical replication slots are essential to logical replication. Due to space limitations in this chapter it is unfortunately not possible to cover all aspects of logical replication. However, I want to outline some of the basic concepts that are essential for logical decoding and therefore also for logical replication.

If you want to create a replication slot, here is how it works. The function needed here takes two parameters: the first one will define the name of the replication slot, while the second one carries the plugin used to decode the transaction log. It will determine the format PostgreSQL is going to use to return the data:

```
test=# SELECT * FROM pg_create_logical_replication_slot('logical_slot',
'test_decoding');
 slot_name      | lsn
-----+-----
 logical_slot   | 0/EF8AD4B0

(1 row)
```

You can check for the existence of the slot using the same command as earlier. To show you what a slot really does, a small test can be created:

```
test=# CREATE TABLE t_demo (id int, name text, payload text);
CREATE TABLE
test=#BEGIN;
BEGIN
test=# INSERT INTO t_demo
VALUES (1, 'hans', 'some data');
INSERT 0 1
test=# INSERT INTO t_demo VALUES (2, 'paul', 'some more data');
INSERT 0 1
test=# COMMIT;
COMMIT
test=# INSERT INTO t_demo VALUES (3, 'joe', 'less data');
INSERT 0 1
```

Note that two transactions were executed. The changes made to those transactions can now be extracted from the slot:

```
test=# SELECT pg_logical_slot_get_changes('logical_slot', NULL, NULL);
               pg_logical_slot_get_changes
-----
(0/EF8AF5B0,606546,"BEGIN 606546")
(0/EF8CCCA0,606546,"COMMIT 606546")
(0/EF8CCCD8,606547,"BEGIN 606547")
(0/EF8CCCD8,606547,"table public.t_demo: INSERT: id[integer]:1
 name[text]:'hans' payload[text]:'some data'")
(0/EF8CCD60,606547,"table public.t_demo: INSERT: id[integer]:2
 name[text]:'paul' payload[text]:'some more data'")
(0/EF8CCDE0,606547,"COMMIT 606547")
(0/EF8CCE18,606548,"BEGIN 606548")
(0/EF8CCE18,606548,"table public.t_demo: INSERT: id[integer]:3
 name[text]:'joe' payload[text]:'less data'")
(0/EF8CCE98,606548,"COMMIT 606548")
(9 rows)
```

The format used here depends on the output plugin we have chosen previously. There are various output plugins for PostgreSQL, such as `wal2json`.

Note that if default values are used, the logical stream will contain real values and not just functions. The logical stream has the data that ended up in the underlying tables.

Also keep in mind that the slot does not return data anymore once it is consumed:

```
test=# SELECT pg_logical_slot_get_changes('logical_slot', NULL, NULL);

pg_logical_slot_get_changes
-----
(0 rows)
```

The result set on the second call is therefore empty. If you want to fetch data repeatedly, PostgreSQL offers the `pg_logical_slot_peek_changes` function. It works just like the `pg_logical_slot_get_changes` function but assures that data will still be available in the slot.

Using plain SQL is, of course, not the only way to consume a transaction log. There is also a command-line tool called `pg_recvlogical`. It can be compared to doing `tail -f` on an entire database instance and receives the flow of data in real time.

Let us start the `pg_recvlogical` command:

```
[hs@zenbook ~]$ pg_recvlogical -S logical_slot -P test_decoding
-d test -U postgres --start -f -
```

In this case, the tool connects to the test database and consumes data from the `logical_slot`. `-f` means that the stream will be sent to `stdout`. Let us kill some data:

```
test=# DELETE FROM t_demo WHERE id < random()*10;
DELETE 3
```

The changes will make it into the transaction log. However, by default the database only cares about what the table will look like after the deletion. It knows which blocks have to be touched and all that—it does not know what it was like previously:

```
BEGIN 606549
table public.t_demo: DELETE: (no-tuple-data)
table public.t_demo: DELETE: (no-tuple-data)
table public.t_demo: DELETE: (no-tuple-data)
COMMIT 606549
```

Therefore, the output is pretty pointless. To fix that, the following line comes to the rescue:

```
test=# ALTER TABLE t_demo REPLICA IDENTITY FULL;  
ALTER TABLE
```

If the table is repopulated with data and deleted again, the transaction log stream looks like this:

```
BEGIN 606558  
table public.t_demo: DELETE: id[integer]:1 name[text]:'hans'  
  payload[text]:'some data'  
table public.t_demo: DELETE: id[integer]:2 name[text]:'paul'  
  payload[text]:'some more data'  
table public.t_demo: DELETE: id[integer]:3 name[text]:'joe'  
  payload[text]:'less data'  
COMMIT 606558
```

Now all the changes are in.

Use cases of logical slots

There are various use cases of replication slots. The most simplistic use case is the one shown here. Data can be fetched from the server in the desired format and used to audit, debug, or simply monitor a database instance.

The next logical step of course is to take this stream of changes and use it for replication. Solutions such as **Bi-Directional Replication (BDR)** are totally based on logical decoding because changes at the binary level would not work with multi-master replication.

Finally, there is the need to upgrade without downtime. Remember, the binary transaction log stream cannot be used to replicate between different versions of PostgreSQL. Therefore, future versions of PostgreSQL will support a tool called `pglogical`, which helps to upgrade without downtime.

Making use of CREATE PUBLICATION and CREATE SUBSCRIPTION

For version 10.0, the PostgreSQL community created two new commands: `CREATE PUBLICATION` and `CREATE SUBSCRIPTION`. These can be used for logical replication. So far, binary replication and transaction log replication has been fully covered. However, sometimes you might not want to replicate an entire database instance—replicating a table or two might be enough. This is exactly when logical replication is the right thing to use.

Before getting started, the first thing to do is to change `wal_level` to `logical` in `postgresql.conf` and restart:

```
wal_level = logical
```

Then you can create a simple table:

```
test=# CREATE TABLE t_test (a int, b int);
CREATE TABLE
```

The same table layout has to exist in the second database as well to make this work. PostgreSQL will not automatically create those tables for you:

```
test=# CREATE DATABASE repl;
CREATE DATABASE
```

After creating the database, the identical table can be added:

```
repl=# CREATE TABLE t_test (a int, b int);
CREATE TABLE
```

The goal here is to publish the content of the `t_test` table in the test database to somewhere else. In my case, it will simply be replicated into a database on the same instance. To publish those changes, PostgreSQL offers the `CREATE PUBLICATION` command:

```
test=# \h CREATE PUBLICATION
Command: CREATE PUBLICATION
Description: define a new publication
Syntax:
    CREATE PUBLICATION name
        [ FOR TABLE [ ONLY ] table_name [ * ] [, ...]
        | FOR ALL TABLES ]
        [ WITH ( publication_parameter [= value] [, ... ] ) ]
```

The syntax is actually pretty easy. All we need is a name and a list of all tables the system is supposed to replicate:

```
test=# CREATE PUBLICATION pub1 FOR TABLE t_test;
CREATE PUBLICATION
```

In the next step, the subscription can be created. The syntax is again pretty simple and really straightforward:

```
test=# \h CREATE SUBSCRIPTION
Command: CREATE SUBSCRIPTION
Description: define a new subscription
Syntax:
CREATE SUBSCRIPTION subscription_name
CONNECTION 'conninfo'
PUBLICATION publication_name [, ...]
[ WITH ( subscription_parameter [= value] [, ... ] ) ]
```

Basically, creating a subscription directly is absolutely no problem. However, if we play this game inside the same instance (from the test database to the repl database, in my case) it is necessary to create the replication slot in use manually. Otherwise, CREATE SUBSCRIPTION will never finish:

```
test=# SELECT pg_create_logical_replication_slot('sub1', 'pgoutput');
pg_create_logical_replication_slot
-----
(sub1,0/27E2B2D0)
(1 row)
```

In this case, the name of the slot created on the master database is called sub1. Then, connect to the target database and run the following command:

```
repl=# CREATE SUBSCRIPTION sub1
      CONNECTION 'host=localhost dbname=test user=postgres'
      PUBLICATION pub1
      WITH (create_slot = false);
CREATE SUBSCRIPTION
```

Of course, you have to adjust your database connect parameters. Then, PostgreSQL will sync the data and you are done. Note that create_slot = false is only used because the test is running inside the same database server instance. If you happen to use different databases, there is no need for manually creating the slot and no need for create_slot = false.

Summary

In this chapter, you have learned about the most important features of PostgreSQL replication, such as streaming replication and replication conflicts. You have learned about PITR as well as replication slots. Note that a book on replication is never complete unless it spans around 400 pages or so, but you have learned the most important things every administrator should know.

Chapter 11, *Deciding on Useful Extensions*, will be about useful extensions to PostgreSQL. You will learn about extensions that have been widely adopted by the industry and that provide even more functionality.

11

Deciding on Useful Extensions

In Chapter 10, *Making Sense of Backups and Replication*, of this book, our attention was focused on replication, transaction log shipping, and logical decoding. After this mostly administration-related stuff, the goal is to aim at a broader topic. In the PostgreSQL world, many things are done through extensions. The advantage of extensions is that functionality can be added without bloating the PostgreSQL core. People can choose from sometimes-competing extensions and find what is best for them. The philosophy is to keep the core slim, relatively easy to maintain, and ready for the future.

In this chapter, some of the most widespread extensions for PostgreSQL are discussed. However, before digging deeper into the issue, I want to state that this chapter only features a list of extensions that I personally find useful. There are so many modules out there these days that it is impossible to cover them all in a reasonable way. Stuff is published every day and it is sometimes even hard for a professional to be aware of everything out there. New stuff is published as we speak, and it might be a good idea to take a look at PGXN (<https://pgxn.org/>), which contains a large variety of extensions for PostgreSQL.

The following main topics will be covered in this chapter:

- How extensions work
- A selection of `contrib` modules
- A quick look at GIS-related modules
- Other useful extensions

Note that only the most important extensions will be covered.

Understanding how extensions work

Before digging into the extensions available out there, it is a good idea to take a look at how extensions work in the first place. Understanding the inner workings of the extension machinery can be quite beneficial.

Let's take a look at the syntax first:

```
test=# \h CREATE EXTENSION
Command:  CREATE EXTENSION
Description: Install an extension
Syntax:
CREATE EXTENSION [ IF NOT EXISTS ] extension_name
[ WITH ] [ SCHEMA schema_name ]
[ VERSION version ]
[ FROM old_version ]
[ CASCADE ]
```

When you want to deploy an extension, simply call the `CREATE EXTENSION` command. It will check for the extension and load it into your database. Note that the extension will be loaded into a database and not into the entire database instance.

If you are loading an extension, you can decide on the schema you want to use. Many extensions can be relocated so the user has the choice of which schema to use. Then, it is possible to decide on a specific version of the extension. Often, you don't want to deploy the latest version of an extension because your client is running outdated software. In such cases, it might be handy to be able to deploy any version available on the system.

The `FROM old_version` clause requires some more attention. Back in the old days, PostgreSQL did not support extensions, so a lot of unpackaged code is still around. This option causes the `CREATE EXTENSION` clause to run an alternative installation script that absorbs the existing objects into the extension, instead of creating new objects. Be careful that the `SCHEMA` clause specifies the schema containing these preexisting objects. Use it only when you have old modules around.

Finally, there is the `CASCADE` clause. Some extensions depend on other extensions. The `CASCADE` option will automatically deploy those software packages too. Here is an example:

```
test=# CREATE EXTENSION earthdistance;
ERROR: required extension "cube" is not installed
HINT: Use CREATE EXTENSION ... CASCADE to install required extensions too.
```

The `earthdistance` module implements great circle distance calculations. As you might know, the shortest distance between two points on earth is not in a straight line; instead, a pilot has to adjust his course constantly to find the fastest route to fly from one point to the other. The thing is, the `earthdistance` extension depends on the `cube` extension, which allows you to perform operations on a sphere.

To automatically deploy the dependency, the `CASCADE` clause can be used as just described:

```
test=# CREATE EXTENSION earthdistance CASCADE;
NOTICE: installing required extension "cube" CREATE EXTENSION
```

In this case, both extensions will be deployed.

Checking for available extensions

PostgreSQL offers various views to figure out which extensions are there on the system and which ones are actually deployed. One of those views is `pg_available_extensions`:

```
test=# \d pg_available_extensions
View "pg_catalog.pg_available_extensions"
Column          | Type | Modifiers
-----+-----+-----
name             | text |
default_version  | text |
installed_version| text |
comment          | text |
```

It contains a list of all extensions available, including their names, their default version, and the version currently installed. To make it easier for the end user, there is also a description available, telling us more about the extension.

The following listing contains two lines taken from `pg_available_extensions`:

```
test=# \x
Expanded display is on.
test=# SELECT * FROM pg_available_extensions LIMIT 2;

-[ RECORD 1 ]-----+-----
name             | earthdistance
default_version  | 1.1
installed_version| 1.1
comment          | calculate great-circle distances on the surface of the
Earth
```

```

-[ RECORD 2 ]-----+-----
name          | plpgsql
default_version | 1.0
installed_version | 1.0
comment       | PL/pgSQL procedural language

```

As you can see, the `earthdistance` and `plpgsql` extensions are both enabled in my database. The `plpgsql` extension is there by default and `earthdistance` has been added just before along with `cube`. The beauty of this view is that you can quickly get an overview of what is installed and what can be installed.

However, in some cases, extensions are available in more than just one version. To find out more about versioning, consider checking out the following view:

```

test=# \d pg_available_extension_versions
View "pg_catalog.pg_available_extension_versions"
Column          | Type          | Modifiers
-----+-----+-----
name            | name          |
version         | text          |
installed       | boolean       |
superuser       | boolean       |
relocatable     | boolean       |
schema          | name          |
requires        | name[]        |
comment         | text          |

```

Some more detailed information is available here, as shown in the next listing:

```

test=# SELECT * FROM pg_available_extension_versions LIMIT 1;
-[ RECORD 1 ]-----+-----
name          | earthdistance
version       | 1.1
installed     | t
superuser     | t
relocatable   | t
schema        |
requires      | {cube}
comment       | calculate great-circle distances on the surface of the Earth

```

PostgreSQL will also tell you whether the extension can be relocated, which schema it has been deployed in, and what other extensions are needed. Then, there is the comment describing the extension, which has already been shown previously.

The main question now is: where does PostgreSQL find all this information about extensions on the system? Assuming that you have deployed PostgreSQL 10 from the official PostgreSQL RPM repository, the `/usr/pgsql-10/share/extension` directory will contain a couple of files:

```
...
-bash-4.3$ ls -l citext*
-rw-r--r-- 1 root root 1028 Oct 26 13:28 citext--1.0--1.1.sql
-rw-r--r-- 1 root root 2748 Oct 26 13:28 citext--1.1--1.2.sql
-rw-r--r-- 1 root root 307 Oct 26 13:28 citext--1.2--1.3.sql
-rw-r--r-- 1 root root 12991 Oct 26 13:28 citext--1.3.sql
-rw-r--r-- 1 root root 158 Oct 26 13:28 citext.control
-rw-r--r-- 1 root root 9781 Oct 26 13:28 citext-unpackaged--1.0.sql
...
```

The default version of the `citext` (case-insensitive text) extension is 1.4, so there is a file called `citext--1.3.sql`. In addition to that, there are files used to move from one version to the next ($1.0 \rightarrow 1.1$, $1.1 \rightarrow 1.2$, and so on).

Then, there is the `.control` file:

```
-bash-4.3$ cat citext.control
# citext extension
comment = 'data type for case-insensitive character strings'
default_version = '1.4'
module_pathname = '$libdir/citext' relocatable = true
```

It contains all the metadata related to this extension; the first entry contains the comment. Note that this content is what will be shown in the system views just discussed. When you access those views, PostgreSQL will go to this directory and read all the `.control` files. Then, there is the default version and the path to the binaries. If you are installing a typical extension from RPM, the directory is going to be `$libdir`, which is inside your PostgreSQL binary directory. However, if you have written your own commercial extension, it might very well reside somewhere else.

The last setting will tell PostgreSQL whether the extension can reside in any schema or whether it has to be in a fixed, predefined schema.

Finally, there is the unpackaged file. Here is an extract:

```
...
ALTER EXTENSION citext ADD type citext;
ALTER EXTENSION citext ADD function citextin(cstring); ALTER EXTENSION
citext ADD function citextout(citext); ALTER EXTENSION citext ADD function
citextrecv(internal);
...
```

The unpackaged file will turn existing code into an extension. It is therefore important to consolidate existing things in your database.

Making use of contrib modules

After this theoretical introduction to extensions, it is time to take a look at some of the most important extensions. In this section, you will learn about modules provided to you as part of the PostgreSQL `contrib` module. When you install PostgreSQL, I recommend that you always install those `contrib` modules as they contain vital extensions that can really make your life easier.

In the coming section, you will be guided through some of the ones I find most interesting.

Using the adminpack

The idea behind the `adminpack` module is to give administrators a way to access the file system without SSH access. The package contains a couple of functions to make that possible.

To load the module into the database, run the following command:

```
test=# CREATE EXTENSION adminpack;
CREATE EXTENSION
```

One of the most interesting features of the `adminpack` module is the ability to inspect log files. The `pg_logdir_ls` function checks out the log directory and returns a list of log files:

```
test=# SELECT * FROM pg_catalog.pg_logdir_ls() AS (a timestamp, b text);
ERROR: the log_filename parameter must equal 'postgresql-%Y-%m-%d_%H%M%S.log'
```

The important thing here is that the `log_filename` parameter has to be adjusted to the `adminspack` module's needs. If you happen to run RPMs downloaded from the PostgreSQL repositories, the `log_filename` parameter is defined as `postgresql-%a`, which has to be changed in this case to avoid the error.

After the change, a list of log filenames is returned:

```
test=# SELECT * FROM pg_catalog.pg_logdir_ls() AS (a timestamp, b text);
      a      |      b
-----+-----
2017-03-03 16:32:58 | pg_log/postgresql-2017-03-03_163258.log

(1 row)
```

It is also possible to determine the size of a file on disk. Here is an example:

```
test=# SELECT b, pg_catalog.pg_file_length(b) FROM
pg_catalog.pg_logdir_ls() AS (a timestamp, b text);
      b      | pg_file_length
-----+-----
pg_log/postgresql-2017-03-03_163258.log | 1525

(1 row)
```

In addition to those features, there are some more functions provided by the module:

```
test=# SELECT proname FROM pg_proc WHERE proname ~ 'pg_file_*';
      proname
-----
pg_file_write
pg_file_rename
pg_file_unlink
pg_file_read
pg_file_length
(5 rows)
```

You can read, write, rename, or simply delete files.

Note that these functions can, of course, only be called by superusers.

Applying bloom filters

Since PostgreSQL 9.6, it has been possible to add index types on the fly using extensions. The new `CREATE ACCESS METHOD` command as well as some additional features has made it possible to create fully functional and transaction logged index types on the fly.

The bloom extension provides PostgreSQL users with bloom filters, which are pre-filters that help to efficiently reduce the amount of data as soon as possible. The idea behind a bloom filter is to calculate a bit mask and to compare the bit mask to the query. The bloom filter might produce some false positives, but still reduces the amount of data dramatically.

It is especially useful when a table consists of hundreds of columns and millions of rows. It is not possible to index hundreds of columns with b-trees, so a bloom filter is a good alternative because it allows for indexing everything at once.

To show you how things work, I have installed the extension:

```
test=# CREATE EXTENSION bloom;
CREATE EXTENSION
```

In the next step, a table containing various columns is created:

```
test=# CREATE TABLE t_bloom
(
    id serial,
    col1 int4 DEFAULT random() * 1000,
    col2 int4 DEFAULT random() * 1000,
    col3 int4 DEFAULT random() * 1000,
    col4 int4 DEFAULT random() * 1000,
    col5 int4 DEFAULT random() * 1000,
    col6 int4 DEFAULT random() * 1000,
    col7 int4 DEFAULT random() * 1000,
    col8 int4 DEFAULT random() * 1000,
    col9 int4 DEFAULT random() * 1000
);
CREATE TABLE
```

To make it easier, those columns have a default value so that data can easily be added using a simple `SELECT` clause:

```
test=# INSERT INTO t_bloom (id)
      SELECT * FROM generate_series(1, 1000000);
INSERT 0 1000000
```

The query adds 1 million rows to the table. Now, the table can be indexed:

```
test=# CREATE INDEX idx_bloom ON t_bloom
      USING bloom(col1, col2, col3, col4, col5, col6, col7, col8, col9);
CREATE INDEX
```

Not that the index contains nine columns at a time. In contrast to a b-tree, the order of those columns does not really make a difference. Note that the table I just created is around 65 MB without indexes.

The index adds another 15 MB to the storage footprint:

```
test=# \di+ idx_bloom
              List of relations
 Schema | Name       | Type  | Owner | Table  | Size  | Description
-----+-----+-----+-----+-----+-----+-----
 public | idx_bloom | index | hs    | t_bloom | 15 MB |
(1 row)
```

The beauty of the `bloom` filter is that it is possible to look for any combination of columns:

```
test=# explain SELECT count(*)
      FROM t_bloom
      WHERE col4 = 454 AND col3 = 354 AND col9 = 423;
              QUERY PLAN
-----
Aggregate (cost=20352.02..20352.03 rows=1 width=8)
-> Bitmap Heap Scan on t_bloom
   (cost=20348.00..20352.02 rows=1 width=0)
   Recheck Cond: ((col3 = 354) AND (col4 = 454) AND (col9 = 423))
-> Bitmap Index Scan on idx_bloom
   (cost=0.00..20348.00 rows=1 width=0)
   Index Cond: ((col3 = 354) AND (col4 = 454)
               AND (col9 = 423))
(5 rows)
```

What you have seen so far feels exceptional. A natural question that might arise is: why not always use a bloom filter? The reason is simple—the database has to read the entire bloom filter in order to use it. In the case of, say, a b-tree, this is not necessary.

In the future, more index types will most likely be added to ensure that even more use cases can be covered with PostgreSQL.

If you want to read more about bloom filters, consider reading our blog:

<https://www.cybertec-postgresql.com/en/trying-out-postgres-bloom-indexes/>.

Deploying btree_gist and btree_gin

After this brief section about indexes, there are more indexing-related features that can be added. In PostgreSQL, there is the concept of operator classes, which has already been discussed in one of the earlier chapters. The contrib module offers two extensions (namely, `btree_gist` and `btree_gin`) to add b-tree functionality to GiST and GIN indexes.

Why is that so useful? GiST indexes offer various features that are not supported by b-trees. One of those features is the ability to perform a **K-Nearest Neighbor (KNN)** search.

Why is that relevant? Imagine somebody is looking for data that was added yesterday around noon. So, when is that? In some cases, it might be hard to come up with boundaries, for example, if somebody is looking for a product that costs around 70 euros. KNN might come to the rescue. Here is an example:

```
test=# CREATE TABLE t_test (id int);
CREATE TABLE
```

In the next step, some simple data is added:

```
test=# INSERT INTO t_test SELECT * FROM generate_series(1, 100000);
INSERT 0 100000
```

Now, the extension can be added:

```
test=# CREATE EXTENSION btree_gist;
CREATE EXTENSION
```

Adding a GiST index to the column is easy. Just use the `USING gist` clause. Note that adding a GiST index on an integer column works only if the extension is present. Otherwise, PostgreSQL will report that there is no suitable operator class:

```
test=# CREATE INDEX idx_id ON t_test USING gist(id);
CREATE INDEX
```

Once the index has been deployed, it is possible to order by distance already:

```
test=# SELECT *
      FROM t_test
      ORDER BY id <-> 100
      LIMIT 6;

 id
-----
 100
 101
```

```

99
102
98
97
(6 rows)

```

As you can see, the first row is an exact match. The next matches are already less precise and are getting worse. The query will always return a fixed number of rows.

The important thing is the execution plan:

```

test=# explain SELECT *
      FROM t_test
      ORDER BY id <-> 100
      LIMIT 6;

```

QUERY PLAN

```

-----
Limit (cost=0.28..0.64 rows=6 width=8)
  -> Index Only Scan using idx_id on t_test
      (cost=0.28..5968.28 rows=100000 width=8)
    Order By: (id <-> 100)
(3 rows)

```

As you can see, PostgreSQL goes straight for an index scan, which speeds up the query significantly.

In future versions of PostgreSQL, b-trees will most likely also support KNN search. A patch to add this feature has already been added to the development mailing list. Maybe it will eventually make it to the core. Having KNN as a b-tree feature could eventually lead to fewer GiST indexes on standard datatypes.

Dblink - considering phasing out

The desire to use database links has been around for many years already. However, around the turn of the century, PostgreSQL foreign data wrappers were not even on the horizon and a traditional database link implementation was definitely not in sight either. Around this time, a PostgreSQL developer from California (Joe Conway) pioneered work on database connectivity by introducing the concept of dblink into PostgreSQL. While dblink served people well over the years, it is no longer state of the art.

Therefore, it is recommended to move away from dblink to the more modern SQL/MED implementation (which is a specification that defines the way external data can be integrated in a relational database). The `postgres_fdw` extension has been built on top of SQL/MED and offers more than just database connectivity as it allows you to connect to basically any data source.

Fetching files with `file_fdw`

In some cases, it can make sense to read a file from a disk and expose it to PostgreSQL as a table. This is exactly what you can achieve with `file_fdw` extension. The idea is to have a module that allows you to read data from a disk and query it using SQL.

Installing the module works as expected:

```
CREATE EXTENSION file_fdw;
```

In the next step, we create a virtual server:

```
CREATE SERVER file_server
  FOREIGN DATA WRAPPER file_fdw;
```

The `file_server` is based on the `file_fdw` extension foreign data wrapper, which tells PostgreSQL how to access the file.

To expose a file as a table, the following command can be used:

```
CREATE FOREIGN TABLE t_passwd
(
  username  text,
  passwd    text,
  uid       int,
  gid       int,
  gecos     text,
  dir       text,
  shell     text
) SERVER file_server
OPTIONS (format 'text', filename '/etc/passwd', header 'false', delimiter
':');
```

In my example, the `/etc/passwd` file will be exposed. All fields have to be listed and data types have to be mapped accordingly. All the additional important information is passed to the module using options. In this example, PostgreSQL has to know the type of file (text), the name, and the path of the file, as well as the delimiter. It is also possible to tell PostgreSQL whether there is a header. If the setting is true, the first line will be skipped and not important. Skipping headers is especially important if you happen to load a CSV file.

Once the table has been created, it is already possible to read data:

```
SELECT * FROM t_passwd;
```

Unsurprisingly, PostgreSQL returns the content of `/etc/passwd`:

```
test=# \x
Expanded display is on.
test=# SELECT * FROM t_passwd LIMIT 1;

-[ RECORD 1 ]-----
username | root
passwd   | x
uid      | 0
gid      | 0
gecos    | root
dir      | /root
shell    | /bin/bash
```

When looking at the execution plan, you will see that PostgreSQL uses a foreign scan to fetch the data from the file:

```
test=# explain (verbose true, analyze true) SELECT * FROM t_passwd;
```

```

                                QUERY PLAN
-----
Foreign Scan on public.t_passwd (cost=0.00..2.80 rows=18 width=168)
    (actual time=0.022..0.072 rows=61 loops=1)
    Output: username, passwd, uid, gid, geccos, dir, shell
    Foreign File: /etc/passwd
    Foreign File Size: 3484
    Planning time: 0.058 ms
    Execution time: 0.138 ms
(6 rows)
```

The execution plan also tells us about the file size and so on. Since we're talking about the planner, there is a side note that is worth mentioning. PostgreSQL will even fetch statistics for the file. The planner checks the file size and assigns the same costs to the file as it would to a normal PostgreSQL table of the same size.

Inspecting storage using pageinspect

If you are facing storage corruption or some other storage-related problem that might be related to bad blocks in a table, the `pageinspect` extension might be the module you are looking for:

```
test=# CREATE EXTENSION pageinspect;
CREATE EXTENSION
```

The idea behind `pageinspect` is to provide you with a module that allows you to inspect a table on the binary level.

When using the module, the most important thing to do is to fetch a block:

```
test=# SELECT * FROM get_raw_page('pg_class', 0);
...
```

The function will return a single block. In the preceding example, it is the first block in the `pg_class` parameter, which is a system table (of course, you can use any other table you want).

In the next step, you can extract the page header:

```
test=# \x
Expanded display is on.

test=# SELECT * FROM page_header(get_raw_page('pg_class', 0));
-[ RECORD 1 ]-----
lsn          | 1/35CAE5B8
checksum     | 0
flags       | 1
lower       | 240
upper       | 1288
special     | 8192
pagesize    | 8192
version     | 4
prune_xid   | 606562
```

It already contains a lot of information about the page. If you want to know even more, you can call the `heap_page_items` function, which dissects the page and returns one row per tuple:

```
test=# SELECT * FROM heap_page_items(get_raw_page('pg_class', 0))
LIMIT 1;
```

```
-[ RECORD 1 ]---
lp           | 1
lp_off       | 49
lp_flags     | 2
lp_len       | 0
t_xmin       |
t_xmax       |
t_field3     |
t_ctid       |
t_infomask2  |
t_infomask   |
t_hoff       |
t_bits       |
t_oid        |
t_data       | ...
```

You can also split the data into various tuples:

```
test=# SELECT tuple_data_split('pg_class'::regclass,  
                                t_data, t_infomask, t_infomask2, t_bits)  
        FROM heap_page_items(get_raw_page('pg_class', 0))  
        LIMIT 2;  
-[ RECORD 1 ]----+-----  
tuple_data_split |  
-[ RECORD 2 ]----+-----  
tuple_data_split |  
{ "\\x6100000000000000000000000000000000000000000000000000000000000000"  
0000000000000000000000000000000000000000000000000000000000000000", "\\x98080000", "  
\\x50ac0c00", "\\x00000000", "\\x01400000", "\\x00000000", "\\x4eac0c00", "\\x00  
000000", "\\xbb010000", "\\x0050c347", "\\x00000000", "\\x00000000", "\\x01", "\\  
x00", "\\x70", "\\x72", "\\x0100", "\\x0000", "\\x00", "\\x00", "\\x00", "\\x00", "\\  
x00", "\\x00", "\\x00", "\\x00", "\\x01", "\\x64", "\\xc3400900", "\\x01000000", NULL, NULL  
}
```

To read the data, you have to familiarize yourself with the on-disk format of PostgreSQL. Otherwise, the data might appear to be pretty obscure.

`pageinspect` provides functions for all access methods (tables, indexes, and so on) and allows for dissecting storage in detail.

Investigating caching with `pg_buffercache`

After this brief introduction to the `pageinspect` extension, I want to focus your attention on the `pg_buffercache` extension, which allows you to take a deep look at the content of your I/O cache:

```
test=# CREATE EXTENSION pg_buffercache;
CREATE EXTENSION
```

The `pg_buffercache` extension provides you with a view containing a couple of fields:

```
test=# \d pg_buffercache
View "public.pg_buffercache"
Column          | Type          | Modifiers
-----+-----+-----
bufferid        | integer       |
relfilenode     | oid           |
reltablespace   | oid           |
reldatabase     | oid           |
relforknumber   | smallint      |
relblocknumber  | bigint        |
isdirty         | boolean       |
usagecount      | smallint      |
pinning_backends | integer       |
```

The `bufferid` field is just a number; it identifies the buffer. Then comes the `relfilenode` field, which points to the file on disk. If you want to look up which table a file belongs to, you can check out the `pg_class` module, which also contains a field, `relfilenode`. Then, there are the `reldatabase` and the `reltablespace` fields. Note that all fields are defined as `oid` type, so to extract data in a more useful way, it is necessary to join system tables together.

The `relforknumber` field tells us which part of the table is cached. It could be the heap, the free space map, or some other component such as the visibility map. In the future, there will surely be more types of relation forks.

The next, `relblocknumber`, tells us which block is cached. Finally, there is the `isdirty` flag, which indicates that a block has been modified, the usage counter, and the number of backends pinning the block.

If you want to make sense of the `pg_buffercache` extension, it is important to add additional information. Suppose you want to figure out which database uses the cache the most. The following query might help:

```
test=# SELECT datname,
              count(*),
              count(*) FILTER (WHERE isdirty = true) AS dirty
        FROM pg_buffercache AS b, pg_database AS d
        WHERE d.oid = b.reldatabase
        GROUP BY ROLLUP (1);
 datname  | count | dirty
-----+-----+-----
 abc      |    132 |     1
 postgres |     30 |     0
 test     |   11975 |    53
          |   12137 |    54
(4 rows)
```

In this case, the `pg_database` extension has to be joined. As you can see, the `oid` is the join criteria, which might not be obvious to people who are new to PostgreSQL.

Sometimes, you might want to know which blocks in the database you are connected to are cached:

```
test=# SELECT relname,
              relkind,
              count(*),
              count(*) FILTER (WHERE isdirty = true) AS dirty
        FROM pg_buffercache AS b, pg_database AS d, pg_class AS c
        WHERE d.oid = b.reldatabase
              AND c.relfilenode = b.relfilenode
              AND datname = 'test'
        GROUP BY 1, 2
        ORDER BY 3 DESC
        LIMIT 7;
 relname          | relkind | count | dirty
-----+-----+-----+-----
 t_bloom          | r       |  8338 |     0
 idx_bloom        | i       |  1962 |     0
 idx_id           | i       |   549 |     0
 t_test           | r       |   445 |     0
 pg_statistic     | r       |    90 |     0
 pg_depend        | r       |    60 |     0
 pg_depend_reference_index | i       |    34 |     0
(7 rows)
```

In this case, I filtered the current database and joined with the `pg_class` module, which contains the list of objects. The `relkind` column is especially noteworthy: `r` refers to table (relation) and `i` refers to index. It will tell you which object you are looking at.

Encrypting data with pgcrypto

One of the most powerful modules in the entire `contrib` module section is `pgcrypto`. It was originally written by one of the Skype sysadmins and offers countless functions to encrypt and decrypt data.

It offers functions for symmetric as well as asymmetric encryption. Due to the large number of functions, it is definitely recommended to check out the documentation page:

<https://www.postgresql.org/docs/current/static/pgcrypto.html>.

Due to the limited scope of this chapter, it is impossible to dig into all the details of the `pgcrypto` module.

Prewarming caches with pg_prewarm

When PostgreSQL operates normally, it tries to cache important data. The `shared_buffers` variable is important as it defines the size of the cache managed by PostgreSQL. The problem now is this: if you restart the database server, all the cache managed by PostgreSQL will be lost. Maybe the operating system will still have some data to reduce the impact on disk wait, but in many cases, this won't be enough. The solution to the problem is called the `pg_prewarm` extension:

```
test=# CREATE EXTENSION pg_prewarm;
CREATE EXTENSION
```

The extension deploys a function that allows us to explicitly prewarm the cache whenever it is needed:

```
test=# \x
Expanded display is on.
test=# \df *prewa*
List of functions
-[ RECORD 1 ]-----+-----
--
Schema          | public
Name             | pg_prewarm
Result data type | bigint
Argument data types | regclass, mode text DEFAULT 'buffer'::text,
```

```

fork text DEFAULT 'main'::text,
first_block bigint DEFAULT NULL::bigint,
last_block bigint DEFAULT NULL::bigint
Type | normal

```

The easiest and most common way to call the `pg_prewarm` extension is to ask it to cache an entire object:

```

test=# SELECT pg_prewarm('t_test');
pg_prewarm
-----
         443
(1 row)

```

Note that if the table is so large that it does not fit into the cache, only parts of the table will stay in cache, which is fine in most cases.

The function returns the number of 8 K blocks processed by the function call.

If you don't want to cache all blocks of an object, you can also select a specific range inside the table. In the next example, you can see that blocks 10 to 30 are cached in the main fork:

```

test=# SELECT pg_prewarm('t_test', 'buffer', 'main', 10, 30);
pg_prewarm
-----
         21
(1 row)

```

As you can see, 21 blocks were cached.

Inspecting performance with `pg_stat_statements`

`pg_stat_statements` is the most important module available in the `contrib` modules. It should always be enabled and is there to provide you with superior performance data. Without the `pg_stat_statements` module, it is really hard to track down performance problems.

Due to its importance, `pg_stat_statements` has already been discussed earlier in this book.

Inspecting storage with pgstattuple

Sometimes, it can happen that tables in PostgreSQL grow out of proportion. The technical term for a table that has grown too much is **table bloat**. The question arising now is: which tables have bloated and how much bloat is there? The `pgstattuple` extension will help to answer those questions:

```
test=# CREATE EXTENSION pgstattuple;
CREATE EXTENSION
```

The module again deploys a couple of functions. In the case of the `pgstattuple` extension, those functions return a row consisting of a composite type. Therefore, the function has to be called in the `FROM` clause to ensure a readable result:

```
test=# \x
Expanded display is on.

test=# SELECT * FROM pgstattuple('t_test');
-[ RECORD 1 ]
-----+-----
table_len      | 3629056
tuple_count    | 100000
tuple_len      | 2800000
tuple_percent  | 77.16
dead_tuple_count | 0
dead_tuple_len  | 0
dead_tuple_percent | 0
free_space     | 16652
free_percent   | 0.46
```

In my example, the table I used for testing seems to be in a pretty good state; the table is 3.6 MB in size and does not contain any dead rows. Free space is also limited. If you are suffering from table bloat, the number of dead rows and the amount of free space has grown out of proportion. Some free space and a handful of dead rows are normal—however, if the table has grown so much that it mostly consists of dead rows and free space, decisive action is needed to bring the situation under control again.

The `pgstattuple` extension also provides a function to inspect indexes:

```
test=# CREATE INDEX idx_id ON t_test (id);
CREATE INDEX
```

The `pgstattindex` function returns a lot of information about the index you want to inspect:

```
test=# SELECT * FROM pgstattindex('idx_id');
```

```

-[ RECORD 1 ]
-----+-----
version      | 2
tree_level   | 1
index_size    | 2260992
root_block_no | 3
internal_pages | 1
leaf_pages    | 274
empty_pages   | 0
deleted_pages | 0
avg_leaf_density | 89.83
leaf_fragmentation | 0

```

Our index is pretty dense (89%). This is a good sign. The default `FILLFACTOR` setting for an index is 90%, so a value close to 90% indicates that the index is very good.

Sometimes, you don't want to check a simple table, but check all of them or just all tables in a schema. How can this be achieved? Normally, the list of objects you want to process is in the `FROM` clause. However, in my example, the function is already in the `FROM` clause, so how can we make PostgreSQL loop over a list of tables? The answer is a `LATERAL` join. Here is an example.

Note that the following example only works if you do not have partitioned tables:

```

test=# SELECT * FROM pgstatindex('idx_id');
-[ RECORD 1 ]-----+-----
version      | 2
tree_level   | 1
index_size    | 2260992
root_block_no | 3
internal_pages | 1
leaf_pages    | 274
empty_pages   | 0
deleted_pages | 0
avg_leaf_density | 89.83
leaf_fragmentation | 0

```

The first part of the `FROM` clause finds the table we are looking for. Each of the tables returned is then sent to the `LATERAL` join. A `LATERAL` join can be seen as a for each statement.

Keep in mind that `pgstattuple` has to read the entire object. If your database is large, it can take quite a long time to process. Therefore, it can be a good idea to store the results of the query you have just seen so that you can inspect it thoroughly without having to rerun the query again and again.

Fuzzy searches with pg_trgm

pg_trgm is a module that allows you to perform fuzzy searching. The module has already been discussed in [Chapter 3, Making Use of Indexes](#).

Connecting to remote servers using postgres_fdw

Data is not always in one location only. More often than not, data is spread all over the infrastructure and it can be that data residing in various places which has to be integrated.

The solution to the problem is a foreign data wrapper, as defined by the SQL/MED standard.

In this section, the postgres_fdw extension will be discussed. It is a module that allows you to dynamically fetch data from a PostgreSQL data source. The first thing is to deploy the foreign data wrapper:

```
test=# \h CREATE FOREIGN DATA WRAPPER
Command: CREATE FOREIGN DATA WRAPPER
Description: define a new foreign-data wrapper
Syntax:
CREATE FOREIGN DATA WRAPPER name
[ HANDLER handler_function | NO HANDLER ]
[ VALIDATOR validator_function | NO VALIDATOR ] [ OPTIONS ( option 'value'
[, ... ] ) ]
```

Fortunately, the CREATE FOREIGN DATA WRAPPER command is hidden inside an extension; it can easily be installed using the normal process:

```
test=# CREATE EXTENSION postgres_fdw;
CREATE EXTENSION
```

In the next step, a virtual server has to be defined. It will point to the other host and tell PostgreSQL where to get the data. At the end of the data, PostgreSQL has to build a complete connect string—the server data is the first kind of thing PostgreSQL has to know. User information will be added later on. The server will only contain host, port, and so on:

```
test=# \h CREATE SERVER
Command: CREATE SERVER
Description: define a new foreign server
Syntax:
CREATE SERVER server_name
```

```
[ TYPE 'server_type' ]
[ VERSION 'server_version']
FOREIGN DATA WRAPPER fdw_name
[ OPTIONS ( option 'value' [, ... ] ) ]
```

To show you how this works, I created a second database on the same host and created a server:

```
[hs@zenbook~]$ createdb customer
[hs@zenbook~]$ psql customer
customer=# CREATE TABLE t_customer (id int, name text);
CREATE TABLE
customer=# CREATE TABLE t_company (
    country      text,
    name         text,
    active       text
);
CREATE TABLE

customer=# \d
List of relations
 Schema      | Name           | Type  | Owner
-----+-----+-----+-----
 public      | t_company      | table |
 hs public   | t_customer     | table | hs

(2 rows)
```

Now, the server should be added to the standard test database:

```
test=# CREATE SERVER customer_server
        FOREIGN DATA WRAPPER postgres_fdw
        OPTIONS (host 'localhost', dbname 'customer', port '5432');
CREATE SERVER
```

Note that all the important information is stored as an `OPTIONS` clause. That is somewhat important because it gives a lot of flexibility to users. There are many different foreign data wrappers and each of them will need different options.

Once the server has been defined, it is time to map users. If you connect from one server to the other, you might not have the same user in both locations. Therefore, foreign data wrappers require people to define the actual user mapping:

```
test=# \h CREATE USER MAPPING
Command:  CREATE USER MAPPING
Description: define a new mapping of a user to a foreign server
Syntax:
```

```
CREATE USER MAPPING FOR { user_name | USER | CURRENT_USER | PUBLIC }
    SERVER server_name
    [ OPTIONS ( option 'value' [ , ... ] ) ]
```

The syntax is pretty simple and it can be used easily:

```
test=# CREATE USER MAPPING
        FOR CURRENT_USER SERVER customer_server
        OPTIONS (user 'hs', password 'abc');
CREATE USER MAPPING
```

Again, all of the important information is hidden in the `OPTIONS` clause. Depending on the type of foreign data wrapper, the list of options will again differ. Note that you have to use proper user data here, working for your setup. In my case, I simply used local users.

Once the infrastructure is in place, you can create foreign tables. The syntax to create a foreign table is pretty similar to how one would create a normal local table. All the columns have to be listed, including their data types:

```
test=# CREATE FOREIGN TABLE f_customer (id int, name text)
        SERVER customer_server
        OPTIONS (schema_name 'public', table_name 't_customer');
CREATE FOREIGN TABLE
```

All columns are listed just like in the case of a normal `CREATE TABLE` clause. The special thing is that the foreign table points to a table on a remote side. The name of the schema and the name of the table have to be specified in the `OPTIONS` clause.

Once it has been created, the table can be used:

```
test=# SELECT * FROM f_customer ;
 id | name
-----+-----
(0 rows)
```

To check what PostgreSQL does internally, it is a good idea to run the `EXPLAIN` clause with the `analyze` parameter. It will reveal some information about what is really going on in the server:

```
test=# EXPLAIN (analyze true, verbose true)
        SELECT * FROM f_customer ;
        QUERY PLAN

-----
Foreign Scan on public.f_customer
  (cost=100.00..150.95 rows=1365 width=36)
  (actual time=0.221..0.221 rows=0 loops=1)
Output: id, name
```

```

Remote SQL: SELECT id, name FROM public.t_customer
Planning time: 0.067 ms
Execution time: 0.451 ms
(5 rows)

```

The important part here is Remote SQL. The foreign data wrapper will send a query to the other side and fetch as little data as possible, since many restrictions as possible are executed on the remote side to ensure that not much data has to be processed locally. Filter conditions, joins, and even aggregates can be performed remotely (as of PostgreSQL 10.0).

While the `CREATE FOREIGN TABLE` clause is surely a nice thing to use, it can be quite cumbersome to list all those columns over and over again.

The solution to the problem is called the `IMPORT` clause. It allows you to quickly and easily import entire schemas into your local database and to create foreign tables:

```

test=# \h IMPORT
Command: IMPORT FOREIGN SCHEMA
Description: Import table definitions from a foreign server
Syntax:
IMPORT FOREIGN SCHEMA remote_schema
    [ { LIMIT TO | EXCEPT } ( table_name [, ...] ) ]
FROM SERVER server_name
INTO local_schema
[ OPTIONS ( option 'value' [, ...] ) ]

```

`IMPORT` allows you to link large sets of tables easily. It also reduces the odds of typos and mistakes as all the information is directly fetched from the remote data source.

Here is how it works:

```

test=# IMPORT FOREIGN SCHEMA public
      FROM SERVER customer_server INTO public;
IMPORT FOREIGN SCHEMA

```

In this case, all tables previously created in the public schema are linked directly. As you can see, all remote tables are now available:

```

test=# \det
List of foreign tables
 Schema | Table          | Server
-----+-----+-----
 public | f_customer     | customer_server
 public | t_company      | customer_server
 public | t_customer     | customer_server
(3 rows)

```

Handling mistakes and typos

Creating foreign tables is not really hard—however, it sometimes happens that people make mistakes, or maybe the passwords used simply change. To handle such issues, PostgreSQL offers two commands.

`ALTER SERVER` allows you to modify a server:

```
test=# \h ALTER SERVER
Command:  ALTER SERVER
Description: change the definition of a foreign server
Syntax:
ALTER SERVER name [ VERSION 'new_version' ]
[ OPTIONS ( [ ADD | SET | DROP ] option ['value'] [, ... ] ) ] ALTER SERVER
name OWNER TO { new_owner | CURRENT_USER | SESSION_USER } ALTER SERVER name
RENAME TO new_name
```

You can use this command to add and remove options for a specific server, which is a good thing if you have forgotten something.

If you want to modify user information, you can alter the user mapping as well:

```
test=# \h ALTER USER MAPPING
Command:  ALTER USER MAPPING
Description: change the definition of a user mapping
Syntax:
ALTER USER MAPPING FOR { user_name | USER | CURRENT_USER | SESSION_USER |
PUBLIC }
SERVER server_name
OPTIONS ( [ ADD | SET | DROP ] option ['value'] [, ... ] )
```

The SQL/MED interface is regularly improved and features are added as we speak. In the future, even more optimizations will make it to the core, making the SQL/MED interface a good choice to improve scalability.

Other useful extensions

The extensions described so far are all part of the PostgreSQL contrib package, which is shipped as part of the PostgreSQL source code. However, the packages you have seen are not the only ones available in the PostgreSQL community. There are many more packages that allow you to do all kinds of things.

Unfortunately, this chapter is too short to dig into all the stuff that is currently out there. The number of modules is growing day by day and it is impossible to cover them all. Therefore, I only want to point out the ones I find the most important.

PostGIS (<http://postgis.net/>) is the **Geographical Information Systems (GIS)** database interface in the open source world. It has been adopted around the globe and is one of the de facto standards in the relational open source database world. It is a professional and extremely powerful solution.

If you are looking for geospatial routing, `pgRouting` is what you might be looking for. It offers various algorithms to find the best connections between locations and works on top of PostgreSQL.

In this chapter, you have already learned about the `postgres_fdw` extension, which allows you to connect to some other PostgreSQL databases. There are many more foreign data wrappers around. One of the most famous and most professional ones is the `oracle_fdw` extension. It allows you to integrate with Oracle and fetch data over the wire, as can be done with the `postgres_fdw` extension.

In some cases, you might also be interested in testing the stability of your infrastructure with `pg_crash` (https://github.com/cybertec-postgresql/pg_crash). The idea is to have a module that constantly crashes your database. `pg_crash` is an excellent choice to test and debug connection pools and the ability of an application to reconnect to a failing database. `pg_crash` will periodically run amok and kill database sessions or corrupt memory. It is ideal for long-term testing.

Summary

In this chapter, you learned about some of the most promising modules shipped with the PostgreSQL standard distribution. These modules are pretty diverse and offer everything from database connectivity to case-insensitive text and modules to inspect your server.

After dealing with extensions, I want to shift your attention to migration. You will learn how you can move to PostgreSQL in the most simplistic way.

12

Troubleshooting PostgreSQL

In Chapter 11, *Deciding on Useful Extensions*, you learned about some useful extensions that are widely adopted and that can give your deployment a real boost. Following up, you will now be introduced to PostgreSQL troubleshooting. The idea is to give you a systematic approach to inspecting and fixing your system.

The following topics will be of interest:

- Approaching an unknown database
- Gaining a brief overview
- Identifying the key bottlenecks
- Handling storage corruption
- Inspecting broken replicas

Keep in mind that many things can go wrong, so it is important to professionally monitor the database.

Approaching an unknown database

If you happen to administer a large-scale system, you might not know what the system is actually doing. Managing hundreds of systems implies that you won't know what is going on with each of them.

The most important thing when it comes to troubleshooting boils down to a single word: **data**. If there is not enough data, there is no way to fix things. Therefore, the first step to troubleshooting is always to set up a monitoring tool such as `pgwatch2`

(<https://www.cybertec-postgresql.com/en/products/pgwatch2/>) that gives you some insights into your database server.

Once the reporting has told you about a situation worth checking, it means it has been proven useful to approach the system in an organized way.

Inspecting pg_stat_activity

The first thing I recommend is checking out `pg_stat_statements`. Answer the following questions:

- How many concurrent queries are currently executed on your system?
- Do you see similar types of query showing up in the query column all the time?
- Do you see queries that have been running for a long time?
- Are there any locks that have not been granted?
- Do you see connections from suspicious hosts?

The `pg_stat_activity` view should always be checked first because it will give you an idea of what is happening on the system. Of course, graphical monitoring is supposed to give you a first impression of the system. However, at the end of the day, it really boils down to the queries actually running on the server. Therefore, a good overview of the system provided by `pg_stat_activity` is more than vital for tracking down issues.

To make it easier for you, I have compiled a couple of queries that I find useful to spot problems as quickly as possible.

Querying pg_stat_activity

The following query shows how many queries are currently executed on your database:

```
test=# SELECT datname,
        count(*) AS open,
        count(*) FILTER (WHERE state = 'active') AS active,
        count(*) FILTER (WHERE state = 'idle') AS idle,
        count(*) FILTER (WHERE state = 'idle in transaction')
        AS idle_in_trans
FROM   pg_stat_activity
GROUP BY ROLLUP (1);
 datname  | open | active | idle | idle_in_trans
-----+-----+-----+-----+-----
 postgres |    2 |      1 |    0 |             1
          |    2 |      1 |    0 |             1

(2 rows)
```

To show as much information as possible on the same screen, partial aggregates are used. You can see active, idle, and idle-in-transaction queries. If you see a high number of idle-in-transaction queries, it is definitely important to dig deeper to figure out how long those transactions have been kept open:

```
test=# SELECT pid, xact_start, now() - xact_start AS duration
        FROM pg_stat_activity
        WHERE state LIKE '%transaction%'
        ORDER BY 3 DESC;
```

pid	xact_start	duration
19758	2017-11-26 20:27:08.168554+01	22:12:10.194363

(1 row)

The transaction in the listing has been open for more than 22 hours. The main question now is: how can a transaction be open for that long? In most applications, a transaction that takes so long is highly suspicious and potentially highly dangerous. Where does the danger come from? As you have learned earlier in this book already, the `VACUUM` command can only clean up dead rows if no transaction can see that anymore. Now, if a transaction stays open for hours or even days, the `VACUUM` command cannot produce useful results, which will lead to table bloat.

It is therefore highly recommended to ensure that long transactions are monitored or killed in case they are too long. From version 9.6 onwards, PostgreSQL has a feature called **snapshot too old**, which allows you to terminate long transactions if snapshots are around for too long.

It is also a good idea to check whether there are any long-running queries going on:

```
test=# SELECT
        now() - query_start AS duration, datname, query
        FROM pg_stat_activity
        WHERE state = 'active'
        ORDER BY 1 DESC;
```

duration	datname	query
00:00:38.814526	dev	SELECT pg_sleep(10000);
00:00:00	test	SELECT now() - query_start AS duration, datname, query FROM pg_stat_activity WHERE state = 'active' ORDER BY 1 DESC;

(2 rows)

In this case, all active queries are taken and the statements calculate how long each query has already been active. Often you see similar queries coming out on top, which can give you some valuable clues about what is happening on your system.

Treating Hibernate statements

Many ORMs such as Hibernate generate insanely long SQL statements. The trouble is this: `pg_stat_activity` will store only the first 1024 bytes of the query in the system view. The rest is truncated. In case of a long query generated by an ORM such as Hibernate, the query is cut off before the interesting parts (the `FROM` clause, among others) actually start.

The solution to the problem is to set a config parameter in the `postgresql.conf` file:

```
test=# SHOW track_activity_query_size;
      track_activity_query_size
-----
      1024
(1 row)

test=# SHOW track_activity_query_size;

      track_activity_query_size
-----
      1024
(1 row)
```

Increase this parameter to a reasonably high value (maybe 32,768) and restart PostgreSQL. You will then be able to see much longer queries and be able to detect issues more easily.

Figuring out where queries come from

When inspecting `pg_stat_activity`, there are some fields that will tell you where a query comes from:

```
client_addr    | inet      |
client_hostname | text      |
client_port    | integer   |
```

Those fields will contain IP addresses and hostnames (if configured). But what happens if all applications send their requests from the very same IP because all applications reside on the same application server? It will be very hard for you to see which application generated a certain query.

The solution to the problem is to ask the developers to set an `application_name` variable:

```
test=# SHOW application_name ;
      application_name
-----
psql
(1 row)

test=# SET application_name TO 'some_name';
SET

test=# SHOW application_name ;
      application_name
-----
some_name
(1 row)
```

If people are cooperative, the `application_name` variable will show up in the system view and make it a lot easier to see where a query comes from. The `application_name` variable can also be set as part of the connect string.

Checking for slow queries

After inspecting `pg_stat_activity`, it makes sense to take a look at slow time-consuming queries. Basically, there are two ways to approach the problem:

- Look for individual slow queries in the log
- Look for types of queries that take too much time

Finding single, slow queries is the classic approach to performance tuning. By setting the `log_min_duration_statement` variable to a desired threshold, PostgreSQL will start to write a log line for each query exceeding this threshold. By default, the slow-query log is off:

```
test=# SHOW log_min_duration_statement;
log_min_duration_statement
-----
-1
(1 row)
```

However, setting this variable to a reasonably good value makes perfect sense. Depending on your workload, the desired time might of course vary.

In many cases, the desired value might differ from database to database. Therefore, it is also possible to use the variable in a more fine-grained way:

```
test=# ALTER DATABASE test SET log_min_duration_statement TO 10000;  
ALTER DATABASE
```

Setting the parameter only for a certain database makes perfect sense if your databases face different workloads.

When using the slow-query log, it is important to consider one important factor—many smaller queries might cause more load than a handful of slow-running queries. Of course, it always makes sense to be aware of individual slow queries, but sometimes those queries are not the problem. Consider the following example: on your system, 1 million queries taking 500 milliseconds each are executed along with some analytical queries running for a couple of milliseconds each. Clearly, the real problem will never show up in the slow-query log while every data export, every index creation, and every bulk load (which cannot be avoided in most cases anyway) will spam the log and point you in the wrong direction.

My personal recommendation, therefore, is to use a slow-query log but to use it carefully, with caution. And most importantly, be aware of what you are really measuring.

The better approach in my opinion is to work more intensively with the `pg_stat_statements` view. It will offer aggregated information and not just information about single queries. The `pg_stat_statements` view has already been discussed earlier in this book. However, the importance of the module cannot be stressed enough.

Inspecting individual queries

Sometimes, slow queries are identified but you still don't have a clue of what is really going on. The next step is, of course, to inspect the execution plan of the query and see what happens. Identifying those key operations in the plan that are responsible for bad runtime is fairly simple. Try to use the following checklist:

- Try to see where it is in the plan that time starts to skyrocket
- Check for missing indexes (one of the main reasons for bad performance)
- Use the `EXPLAIN` clause (`buffers true`, `analyze true`, and so on) to see if your query uses too many buffers

- Turn on the `track_io_timing` parameter to figure out whether there is an I/O problem or a CPU problem (explicitly check if there is random I/O going on)
- Look for wrong estimates and try to fix them
- Look for stored procedures that are executed too frequently
- Try to figure out whether some of them can be marked as `STABLE` or `IMMUTABLE`, provided this is possible

Note that `pg_stat_statements` does not account for parse time, so if your queries are very long (query string), `pg_stat_statements` might be slightly misleading.

Digging deeper with perf

In most cases, working through this tiny checklist will help you to track down the majority of problems in a pretty fast and efficient way. However, even the information extracted from the database engine is sometimes not enough.

The `perf` tool is an analysis tool for Linux that allows you to directly see which C functions cause problems on your system. Usually `perf` is not installed by default, so it is recommended to install it. To use `perf` on your server, just log in to a root and run:

```
perf top
```

The screen will refresh itself every couple of seconds and you will have a chance to see what is going on live. The next listing shows what a standard read-only benchmark might look like:

```
Samples: 164K of event 'cycles:ppp', Event count (approx.): 109789128766
Overhead Shared Object    Symbol
 3.10% postgres          [.] AllocSetAlloc
 1.99% postgres          [.] SearchCatCache
 1.51% postgres          [.] base_yyparse
 1.42% postgres          [.] hash_search_with_hash_value
 1.27% libc-2.22.so       [.] vfprintf
 1.13% libc-2.22.so       [.] _int_malloc
 0.87% postgres          [.] palloc
 0.74% postgres          [.] MemoryContextAllocZeroAligned
 0.66% libc-2.22.so       [.] __strcmp_sse2_unaligned
 0.66% [kernel]           [k] _raw_spin_lock_irqsave
 0.66% postgres          [.] _bt_compare
 0.63% [kernel]           [k] __fget_light
 0.62% libc-2.22.so       [.] strlen
```

You can see that no single function takes too much CPU time in our sample, which tells us that the system is just fine.

However, this may not always be the case. There is a problem, one that is quite common, called spinlock contention. What is that? Spinlocks (<https://en.wikipedia.org/wiki/Spinlock>) are used by the PostgreSQL core to synchronize things such as buffer access. A spinlock is a feature provided by modern CPUs to avoid operating-system interaction for small operations (such as incrementing a number). It is a good thing, but in some very special cases, spinlocks can go crazy. If you are facing spinlock contention, the symptoms are as follows:

- Really high CPU load
- Incredibly low throughput (queries that usually take milliseconds suddenly take seconds)
- I/O is usually low because the CPU is busy trading locks

In many cases, spinlock contention happens suddenly. Your system is just fine, and all of a sudden, load goes up and throughput drops like a stone. The `perf top` command will reveal that most of the time is spent in a C function called `s_lock`. If this is the case, you should try to do the following:

```
huge_pages = try # on, off, or try
```

Change `huge_pages` from `try` to `off`. It can be a good idea to turn off huge pages altogether on the operating-system level. In general, it seems that some kernels are more prone to producing these kinds of problems than others. The Red Hat 2.6.32 series seems to be especially bad (note that I have used the word *seems* here).

The `perf` tool is also interesting if you are using PostGIS. If the top functions in the list are all GIS-related (some underlying library), you know that the problem is most likely not coming from bad PostgreSQL tuning but is simply related to expensive operations that take time to complete.

Inspecting the log

If your system smells trouble, it makes sense to inspect the log to see what is going on. The important point is this: not all log entries are created equal. PostgreSQL has a hierarchy of log entries that range from `DEBUG` messages to `PANIC`.

For the administrator, the following three error levels are of great importance:

- ERROR
- FATAL
- PANIC

ERROR is used for problems such as syntax errors, permission-related problems, and more. Your log will always contain error messages. The critical factor is: how often does a certain type of error show up? Producing millions of syntax errors is certainly not the ideal strategy to run a database server.

FATAL is more scary than ERROR; you will see messages such as `could not allocate memory for shared memory name or unexpected walreceiver state`. In other words, those error messages are already really scary and will tell you that things are going wrong.

Finally, there is PANIC. If you hit this kind of message, you know that something is really, really wrong. Classic examples of PANIC are lock table corrupted or too many semaphores created. It will result in a shutdown.

Checking for missing indexes

Once you are done with the first three steps, it is important to take a look at performance in general. As I keep stating throughout this book, missing indexes are super responsible for super bad performance. So, whenever you are facing a slow system, is it recommended that you check for missing indexes and deploy whatever is needed.

Usually customers ask you to optimize the RAID level, tune the kernel, or some other fancy stuff. In reality, those complicated requests often boil down to a handful of missing indexes. By my judgment, it always makes sense to spend some extra time on just checking whether all desired indexes are there. Checking for missing indexes is neither hard nor time-consuming, so it should be done all the time regardless of the kind of performance problem you are facing.

Here is my favorite query to get an impression of where an index might be missing:

```
SELECT schemaname, relname, seq_scan, seq_tup_read,
       idx_scan, seq_tup_read / seq_scan AS avg
FROM pg_stat_user_tables
WHERE seq_scan > 0
ORDER BY seq_tup_read DESC
LIMIT 20;
```

Try to find large tables (high `avg`) that are scanned often. Those tables will typically come on top.

Checking for memory and I/O

Once you are done finding missing indexes, you can inspect memory and I/O. To figure out what is going on, it makes sense to activate `track_io_timing`. If it is on, PostgreSQL will collect information about disk wait and present it to you.

Often the main question asked by a customer is: if we add more disks, is it going to be faster? It is possible to guess what will happen, but in general, measuring is the better and more useful strategy. Enabling `track_io_timing` will help you gather the data to really figure it out.

PostgreSQL exposes disk wait in various ways. One way to inspect things is to take a look at `pg_stat_database`:

```
test=# \d pg_stat_database
      View "pg_catalog.pg_stat_database"
Column          | Type          | Modifiers
-----+-----+-----
datid           | oid           |
datname         | name          |
...
conflicts       | bigint        |
temp_files      | bigint        |
temp_bytes      | bigint        |
...
blk_read_time   | double precision |
blk_write_time  | double precision |
```

Note that there are two fields towards the end: `blk_read_time` and `blk_write_time`. They will tell you about the amount of time PostgreSQL has spent waiting for the operating system to respond. Note that we are not really measuring disk wait here but rather the time the operating system needs to return data.

If the operating system produces cache hits, this time will be fairly low. If the operating system has to do really nasty random I/O, you will see that a single block can even take a couple of milliseconds.

In many cases, high `blk_read_time` and `blk_write_time` happen when `temp_files` and `temp_bytes` show high numbers. Also, in many cases, this points to a bad `work_mem` or bad `maintenance_work_mem` setting. Remember this: if PostgreSQL cannot do things in memory, it has to spill to the disk. The `temp_files` operation is the way to detect that. Whenever there are `temp_files`, there is the chance of nasty disk wait.

While a global view on a per-database-level makes sense, it does not yield in-depth information about the real source of trouble. Often, only a few queries are to blame for bad performance. The way to spot those is to use `pg_stat_statements`:

```
test=# \d pg_stat_statements
      View "public.pg_stat_statements"
      Column          | Type          | Modifiers
-----+-----+-----
...
query                 | text          |
calls                 | bigint        |
total_time             | double precision |
...
temp_blks_read         | bigint        |
temp_blks_written      | bigint        |
blk_read_time          | double precision |
blk_write_time         | double precision |
```

You will be able to see, on a per-query-basis, whether there is disk wait or not. The important part is the `blk_` time in combination with `total_time`. The ratio is what counts. In general, a query that shows more than 30% of disk wait can be seen as heavily I/O-bound.

Once you are done checking the PostgreSQL system tables, it makes sense to inspect what the `vmstat` command on Linux tells you. Alternatively, you can use the `iostat` command:

```
[hs@zenbook ~]$ vmstat 2
procs -----memory----- ---swap-- -----io----- -system-- -----
cpu-----
 r b swpd free buff cache si so bi bo in cs us sy id wa st
 0 0 367088 199488 96 2320388 0 2 83 96 106 156 16 6 78 0 0
 0 0 367088 198140 96 2320504 0 0 0 10 595 2624 3 1 96 0 0
 0 0 367088 191448 96 2320964 0 0 0 8 920 2957 8 2 90 0 0
```

When doing database work, you should focus your attention on three fields: `bi`, `bo`, and `wa`. The `bi` field tells you about the number of blocks read; 1,000 is the equivalent to 1 MB/second. The `bo` field is about blocks out. It tells us about the amount of data written to the disk. In a way, `bi` and `bo` are the raw throughput. I would not consider a number to be harmful. What is a problem is a high `wa` value. Low values for `bi` and `bo` fields, combined with a high `wa` value, tell you about a potential disk bottleneck, which is most likely related to a lot of random I/O taking place on your system. The higher the `wa` value, the slower your queries, because you are waiting on the disk to respond.



Good raw throughput is a good thing; it can also point to a problem. If high throughput is needed on an OLTP system, it can tell you that there is not enough RAM to cache things or that indexes are missing and PostgreSQL has to read too much data. Keep in mind that things are interconnected and data should not be seen as isolated.

Understanding noteworthy error scenarios

After those basic guidelines to hunt down the most common issues, the upcoming sections will discuss some of the most common error scenarios happening in the PostgreSQL world.

Facing clog corruption

PostgreSQL has a thing called the commit log (now called `pg_xact`; it is formally known as `pg_clog`). It tracks the state of every transaction on the system and helps PostgreSQL determine whether a row can be seen or not. In general, a transaction can be in four states:

```
#define TRANSACTION_STATUS_IN_PROGRESS    0x00
#define TRANSACTION_STATUS_COMMITTED      0x01
#define TRANSACTION_STATUS_ABORTED        0x02
#define TRANSACTION_STATUS_SUB_COMMITTED  0x03
```

The clog has a separate directory in the PostgreSQL database instance (`pg_xact`).

In the past, people have reported something called **clog corruption**, which can be caused by faulty disks or bugs in PostgreSQL that have been fixed over the years. A corrupted commit log is a pretty nasty thing to have, because all your data is there but PostgreSQL does not know whether things are valid or not anymore. Corruption in this area is nothing short of a total disaster.

How does the administrator figure out that the commit log is broken? Here is what you normally see:

```
ERROR: could not access status of transaction 118831
```

If PostgreSQL cannot access the status of a transaction, trouble is certain. The main question is: how can this be fixed? To put it straight, there is no way to really fix the problem—you can only try to rescue as much data as possible.

As stated already, the commit log keeps two bits per transaction. This means that we have four transactions per byte, leaving us with 32,768 transactions per block. Once you have figured out which block it is, you can fake the transaction log:

```
dd if=/dev/zero of=<data directory location>/pg_clog/0001  
bs=256K count=1
```

You can use `dd` to fake the transaction log and set the commit status to the desired value. The core question is really: which transaction state should be used? The answer is that any state is actually wrong because you really don't know how those transactions ended.

However, usually it is a good idea to just set them to committed in order to lose less data. It really depends on your workload and your data when deciding what is less disruptive.

When you have to do that, you should fake as little clog as necessary. Remember, you are essentially faking the commit status, which is not a nice thing to do to a database engine.

Once you are done faking the clog, you should try to create a backup as fast as you can and recreate the database instance from scratch. The system you are working with is not too trustworthy anymore so you should try to extract data as fast as you can. Keep this in mind: the data you are about to extract could be contradictory and wrong, so make sure that some quality checks are imposed on whatever you are able to rescue from your database server.

Understanding checkpoint messages

Checkpoints are essential to data integrity as well as performance. The further checkpoints are apart, the better performance usually is. In PostgreSQL, the default configuration is usually fairly conservative and checkpoints are therefore comparatively fast. If a lot of data is changed in the database core at the same time, it can be that PostgreSQL tells us that it considers checkpoints to be too frequent. The LOG file will show the following entries:

```
LOG: checkpoints are occurring too frequently (2 seconds apart)  
LOG: checkpoints are occurring too frequently (3 seconds apart)
```

During heavy writing due to dump/restore or due to some other large operation, PostgreSQL might notice that the configuration parameters are too low. A message is sent to the LOG file to tell us exactly that.

If you see this kind of message, it is strongly recommended for performance reasons to increase checkpoint distances by increasing the `max_wal_size` parameter dramatically (in older versions the setting was called `checkpoint_segments`). In recent versions of PostgreSQL, the default configuration is already a lot better than it used to be. However, writing data too frequently can still happen easily.

When you see a message about checkpoints, there is one thing you have to keep in mind. Check pointing too frequently is not dangerous at all—it just happens to lead to bad performance. Writing is simply a lot slower than it could be but your data is not in danger. Increasing the distance between two checkpoints sufficiently will make the error go away and speed up your database instance at the same time.

Managing corrupted data pages

PostgreSQL is a very stable database system. It protects data as much as possible and has proven its worth over the years. However, PostgreSQL relies on hardware and a properly working filesystem. If storage breaks, so will PostgreSQL—there is not much you can do about it apart from adding replicas to make things more fail-safe.

Once in a while, it happens that the filesystem or the disk fails. But in many cases, the entire thing will not go south; just a couple of blocks are corrupted for whatever reason. Recently, we have seen that happening in virtual environments. Some virtual machines don't flush to the disk by default, which means that PostgreSQL cannot rely on things being written to the disk. This kind of behavior can lead to random problems which are hard to predict.

When a block cannot be read anymore, you might face an error message like the following one:

```
"could not read block %u in file \"%s\": %m"
```

The query you are about to run will error out and stop working.

Fortunately, PostgreSQL has a means of dealing with these things:

```
test=# SET zero_damaged_pages TO on;
SET
test=# SHOW zero_damaged_pages;
 zero_damaged_pages
-----
on
(1 row)
```

The `zero_damaged_pages` variable is a `config` variable that allows you to deal with broken pages. Instead of throwing an error, PostgreSQL will take the block and simply fill it with zeros.

Note that this will definitely lead to data loss. But remember, data was broken or lost before anyway, so this is simply a way to deal with corruption caused by bad things happening in your storage system.

I would advise everybody to handle the `zero_damaged_pages` variable with care—be aware of what you are doing when you call it.

Careless connection management

In PostgreSQL, every database connection is a separate process. All those processes are synchronized using shared memory (technically, in most cases it is mapped memory, but for this example, that makes no difference). This shared memory contains the I/O cache, the list of active database connections, locks, and more vital stuff which makes the system function properly.

When a connection is closed, it will remove all relevant entries from shared memory and leave the system in a sane state. However, what happens when a database connection simply crashes for whatever reason?

The postmaster (the main process) will detect that one of the child processes is missing. Then, all other connections will be terminated and a roll-forward process will be initialized. Why is that necessary? When a process crashes it might very well happen that the shared memory area is edited by the process. In other words, a crashing process might leave shared memory in a corrupted state. Therefore, the postmaster reacts and kicks everybody out before the corruption can spread in the system. All memory is cleaned and everybody has to reconnect.

From an end-user point of view, this feels like PostgreSQL has crashed and restarted, which is not the case. As a process cannot react on its own crash (segmentation fault) or on some other signals, cleaning out everything is absolutely essential to protect your data.

The same happens if you use the `kill -9` command on a database connection. The connection cannot catch the signal (`-9` cannot be caught by definition), and therefore the postmaster has to react again.

Fighting table bloat

Table bloat is one of the most important issues when dealing with PostgreSQL. When you are facing bad performance, it is always a good idea to figure out whether there are objects that need a lot more space than they are supposed to have.

How can you figure out where table bloat is happening? Check out the `pg_stat_user_tables` view:

```
test=# \d pg_stat_user_tables
View "pg_catalog.pg_stat_user_tables"
Column          | Type          | Modifiers
-----+-----+-----
 relid           | oid           |
 schemaname      | name          |
 relname         | name          |
 ...
 n_live_tup      | bigint        |
 n_dead_tup      | bigint        |
```

The `n_live_tup` and `n_dead_tup` fields will give you an impression of what is going on. You can also use `pgstattuple` as outlined in an earlier chapter.

What can you do if there is serious table bloat? The first option is to run the `VACUUM FULL` command. The trouble is that the `VACUUM FULL` clause needs a table lock. On a large table, this can be a real problem because users cannot write to the table while it is rewritten.

If you are using at least PostgreSQL 9.6, you can use a tool called `pg_squeeze`. It organizes a table behind the scenes without

blocking: https://www.cybertec-postgresql.com/en/products/pg_squeeze/.



This is especially useful if you are reorganizing a very large table.

Summary

In this chapter, you learned to systematically approach a database system and detect the most common issues people face with PostgreSQL. You learned about some important system tables, as well as some other important factors that can determine whether you will succeed or fail.

In the final chapter of this book, we will focus our attention on migrating to PostgreSQL. If you are using Oracle or some other database system, you might be willing to check out PostgreSQL. [Chapter 13, *Migrating to PostgreSQL*](#), will tell you how to do that.

13

Migrating to PostgreSQL

In *Chapter 12, Troubleshooting PostgreSQL*, of this book, I showed you how to approach the most common issues related to PostgreSQL troubleshooting. The important thing is to have a systematic approach to tracking down problems, which is exactly what I have tried to provide.

The final chapter of this book is about moving from other databases to PostgreSQL. Many readers might still be suffering from the pain caused by commercial database license costs. I want to give all those users out there a way out and show how data can be moved from some proprietary system to PostgreSQL. Moving to PostgreSQL not only makes sense from a financial point of view, but also makes sense if you are looking for more advanced features and more flexibility. PostgreSQL has so much to offer and new features are being added as we speak. The same applies to the number of tools available to migrate to PostgreSQL. Things are getting better and better and developers are publishing more and better tools all the time.

The following things will be covered in this chapter:

- Migrating SQL statements to PostgreSQL
- Moving from Oracle to PostgreSQL
- Moving MySQL to PostgreSQL

At the end of the chapter, you should be able to move a basic database from some other system to PostgreSQL.

Migrating SQL statements to PostgreSQL

When moving from a database to PostgreSQL, it makes sense to take a look and figure out which database engine provides which kind of functionality. Moving the data and the structure itself is usually fairly easy. However, rewriting SQL might not be. Therefore, I decided to include a section that explicitly focuses on various advanced features of SQL and their availability in today's database engines.

Using lateral joins

In SQL, a lateral join can basically be seen as some sort of loop. It basically allows us to parameterize a join and execute everything inside the `LATERAL` clause more than once. Here is a simple example:

```
test=# SELECT *
      FROM generate_series(1, 4) AS x,
           LATERAL (SELECT array_agg(y)
                   FROM generate_series(1, x) AS y
                   ) AS z;
```

x		array_agg
1		{1}
2		{1,2}
3		{1,2,3}
4		{1,2,3,4}

(4 rows)

The `LATERAL` clause will be called for each `x`. To the end user, it is basically some sort of loop.

Supporting lateral

One important SQL feature is lateral join. The following list shows which engines support lateral join and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 9.3

- **SQLite:** Not supported
- **Db2 LUW:** Supported since version 9.1 (2005)
- **Oracle:** Supported since 12c
- **Microsoft SQL Server:** Supported since 2005 but using a different syntax

Using grouping sets

Grouping sets are very useful if you want to run more than one aggregate at the same time. Using grouping sets can speed up aggregation because you don't have to process the data more than once.

Here is an example:

```
test=# SELECT x % 2, array_agg(x)
        FROM generate_series(1, 4) AS x
        GROUP BY ROLLUP (1);
?column? | array_agg
-----+-----
0 | {2,4}
1 | {1,3}
    | {2,4,1,3}
(3 rows)
```

PostgreSQL offers more than just the `ROLLUP` clause. The `CUBE` and `GROUPING SETS` clauses are also supported.

Supporting grouping sets

Grouping sets are essential to generate more than just one aggregation in a single query. The following list shows which engines support grouping sets and which don't:

- **MariaDB:** Only `ROLLUP` clause is supported since 5.1 (incomplete support)
- **MySQL:** Only `ROLLUP` clause is supported since 5.0 (incomplete support)
- **PostgreSQL:** Supported since PostgreSQL 9.5
- **SQLite:** Not supported
- **Db2 LUW:** Supported since at least 1999
- **Oracle:** Supported since 9iR1 (around 2000)
- **Microsoft SQL Server:** Supported since 2008

Using the WITH clause – common table expressions

Common table expressions are a nice way to execute things inside an SQL statement only once. PostgreSQL will execute all `WITH` clauses and allow you to use the results all over the query.

Here is a simplified example:

```
test=# WITH x AS (SELECT avg(id)
                  FROM generate_series(1, 10) AS id)
      SELECT *, y - (SELECT avg FROM x) AS diff
      FROM generate_series(1, 10) AS y
      WHERE y > (SELECT avg FROM x);
 y | diff
----+-----
 6 | 0.5000000000000000
 7 | 1.5000000000000000
 8 | 2.5000000000000000
 9 | 3.5000000000000000
10 | 4.5000000000000000
(5 rows)
```

In this example, the `WITH` clause **common table extension** (CTE) calculates the average value of the time series generated by the `generate_series` function. The resulting `x` can be used just like a table all over the query. In my example, `x` is used twice.

Supporting the WITH clause

The following list shows which engines support the `WITH` clause and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 8.4
- **SQLite:** Supported since 3.8.3
- **Db2 LUW:** Supported since 8 (year 2000)
- **Oracle:** Supported since 9iR2
- **Microsoft SQL Server:** Supported since 2005



Note that in PostgreSQL, a CTE can even support writes (`INSERT`, `UPDATE`, and `DELETE` clauses). There is no other database I am aware of that can actually do that.

Using the `WITH RECURSIVE` clause

The `WITH` clause comes in two forms:

- Standard CTEs as shown in the previous section (using the `WITH` clause)
- A method to run recursions in SQL

The simple form of a CTE has already been covered in the previous section. In the next section, the recursive version will be covered.

Supporting the `WITH RECURSIVE` clause

The following list shows which engines support the `WITH RECURSIVE` clause and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 8.4
- **SQLite:** Supported since 3.8.3
- **Db2 LUW:** Supported since 7 (2000)
- **Oracle:** Supported since 11gR2 (in Oracle, it is usually more common to use the `CONNECT BY` clause instead of the `WITH RECURSIVE` clause)
- **Microsoft SQL Server:** Supported since 2005

Using the `FILTER` clause

When looking at the SQL standard itself, you will notice that the `FILTER` clause has already been around with SQL (2003). However, not many systems actually support this highly useful syntax element.

Here is an example:

```
test=# SELECT count(*),
           count(*) FILTER (WHERE id < 5),
           count(*) FILTER (WHERE id > 2)
       FROM generate_series(1, 10) AS id;
 count | count | count 
-----+-----+-----
      10 | 4 | 8 
(1 row)
```

The `FILTER` clause is useful if a condition cannot be used inside a normal `WHERE` clause because some other aggregate is in need of the data.

Before the introduction of the `FILTER` clause, the same could be achieved using a more cumbersome syntax:

```
SELECT sum(CASE WHEN .. THEN 1 ELSE 0 END) AS whatever FROM some_table;
```

Supporting the `FILTER` clause

The following list shows which engines support the `FILTER` clause and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 9.4
- **SQLite:** Not supported
- **Db2 LUW:** Not supported
- **Oracle:** Not supported
- **Microsoft SQL Server:** Not supported

Using windowing functions

Windowing and analytics have already been discussed extensively in this book. Therefore, we can jump straight to SQL compliance.

Supporting windowing and analytics

The following list shows which engines support window functions and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 8.4
- **SQLite:** Not supported
- **Db2 LUW:** Supported since version 7
- **Oracle:** Supported since version 8i
- **Microsoft SQL Server:** Supported since 2005



Some other databases, such as Hive, Impala, Spark, and NuoDB, also support analytics.

Using ordered sets – WITHIN GROUP clause

Ordered sets are fairly new to PostgreSQL. The difference between an ordered set and a normal aggregate is that in the case of an ordered set, the way data is fed to the aggregate does make a difference. Suppose you want to find a trend in your data—the order of data is relevant.

Here is a simple example of calculating a median value:

```
test=# SELECT id % 2,
        percentile_disc(0.5) WITHIN GROUP (ORDER BY id)
FROM generate_series(1, 123) AS id
GROUP BY 1;
?column? | percentile_disc
-----+-----
0 | 62
1 | 61
(2 rows)
```

The median can be determined only if there is sorted input.

Supporting the WITHIN GROUP clause

This list shows which engines support windows functions and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 9.4
- **SQLite:** Not supported
- **Db2 LUW:** Not supported
- **Oracle:** Supported since version 9iR1
- **Microsoft SQL Server:** Supported but the query has to be remodeled using the windowing function

Using the TABLESAMPLE clause

Table sampling has long been the real strength of commercial database vendors. Traditional database systems have provided sampling for many years. However, the monopoly has been broken. Since PostgreSQL 9.5, we have also had a solution to the problem of sampling.

Here is how it works:

```
test=# CREATE TABLE t_test (id int);
CREATE TABLE
test=# INSERT INTO t_test
      SELECT * FROM generate_series(1, 1000000);
INSERT 0 1000000
```

First, a table containing 1 million rows is created. Then tests can be executed:

```
test=# SELECT count(*), avg(id)
      FROM t_test TABLESAMPLE BERNOULLI (1);
 count |      avg
-----+-----
  9802 | 502453.220873291165
(1 row)
test=# SELECT count(*), avg(id)
      FROM t_test TABLESAMPLE BERNOULLI (1);
 count |      avg
-----+-----
 10082 | 497514.321959928586
(1 row)
```

In this example, the same test is executed twice. A 1% random sample is used in each case. Both average values are pretty close to 5 million, so the result is pretty good from a statistical point of view.

Supporting TABLESAMPLE clause

The following list shows which engines support the `TABLESAMPLE` clause and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Supported since PostgreSQL 9.5
- **SQLite:** Not supported
- **Db2 LUW:** Supported since version 8.2
- **Oracle:** Supported since version 8
- **Microsoft SQL Server:** Supported since 2005

Using limit/offset

Limiting a result in SQL is a somewhat sad story. To make it short, every database does things somewhat differently. Although there is actually a SQL standard on limiting results, not everybody fully supports the way things are supposed to be. The correct way to limit data is to actually use the following syntax:

```
test=# SELECT * FROM t_test FETCH FIRST 3 ROWS ONLY;  
id  
----  
 1  
 2  
 3  
(3 rows)
```

If you have never seen this syntax before, don't worry. You are definitely not alone.

Supporting the FETCH FIRST clause

The following list shows which engines support the `FETCH FIRST` clause and which don't:

- **MariaDB:** Supported since 5.1 (usually, `limit/offset` is used)
- **MySQL:** Supported since 3.19.3 (usually, `limit/offset` is used)
- **PostgreSQL:** Supported since PostgreSQL 8.4 (usually, `limit/offset` is used)
- **SQLite:** Supported since version 2.1.0
- **Db2 LUW:** Supported since version 7
- **Oracle:** Supported since version 12c (uses subselects with the `row_num` function)
- **Microsoft SQL Server:** Supported since 2012 (traditionally, `top-N` is used)

As you can see, limiting result sets is quite tricky, and when you are porting a commercial database to PostgreSQL, you will most likely always be confronted with some proprietary syntax.

Using OFFSET

The `OFFSET` clause is similar to the `FETCH FIRST` clause. It is easy to use but it has not been widely adopted. It is not as bad as in the `FETCH FIRST` clause, but it still tends to be an issue.

Supporting the OFFSET clause

The following list shows which engines support the `OFFSET` clause and which don't:

- **MariaDB:** Supported since 5.1
- **MySQL:** Supported since 4.0.6
- **PostgreSQL:** Supported since PostgreSQL 6.5
- **SQLite:** Supported since version 2.1.0
- **Db2 LUW:** Supported since version 11.1
- **Oracle:** Supported since version 12c
- **Microsoft SQL Server:** Supported since 2012

As you can see, limiting result sets is quite tricky and, when you are porting a commercial database to PostgreSQL, you will most likely always be confronted with some proprietary syntax.

Using temporal tables

Temporal tables are provided by some database engines to handle versioning. Unfortunately, there is no such thing as out-of-the-box versioning in PostgreSQL. So, if you are moving from Db2 or Oracle, there is some work ahead of you to port the desired functionality to PostgreSQL. Basically, changing the code a bit on the PostgreSQL side is not hard. However, it does need some manual intervention—it is not a straight copy-and-paste thing anymore.

Supporting temporal tables

The following list shows which engines support temporal tables and which don't:

- **MariaDB:** Not supported
- **MySQL:** Not supported
- **PostgreSQL:** Not supported
- **SQLite:** Not supported
- **Db2 LUW:** Supported since version 10.1
- **Oracle:** Supported since version 12cR1
- **Microsoft SQL Server:** Supported since 2016

Matching patterns in time series

The most recent SQL standard I am aware of (SQL 2016) provides a feature designed to find matches in time series. So far, only Oracle has implemented this functionality into their latest version of the product.

At this point, no other database vendor has followed them and added similar functionality. If you want to model this state-of-the-art technology in PostgreSQL, you have to work with the windowing function and subselects. Matching time series patterns in Oracle is pretty powerful; there is not just one type of query to achieve this in PostgreSQL.

Moving from Oracle to PostgreSQL

So far, you have seen how the most important advanced SQL features can be ported or used in PostgreSQL. Given this introduction, it is time to take a look at migrating Oracle database systems in particular.

These days, migrating from Oracle to PostgreSQL has become really popular due to Oracle's new license and business policy. Around the world, people are moving away from Oracle and adopting PostgreSQL. To help people make Oracle a thing of the past, I have included a special section here.

Using the `oracle_fdw` extension to move data

One of my preferred methods to move people from Oracle to PostgreSQL is Laurenz Albe's `oracle_fdw` extension (https://github.com/laurenz/oracle_fdw). It is a **foreign-data wrapper (FDW)** that allows you to represent a table in Oracle as a table in PostgreSQL. The `oracle_fdw` extension is one of the most sophisticated FDWs and is rock solid, well-documented, free, and open source.

Installing the `oracle_fdw` extension requires you to install the Oracle client library. Fortunately, there are already RPM packages that can be used out of the box (<http://www.oracle.com/technetwork/topics/linuxx86-64soft-092277.html>). The `oracle_fdw` extension needs the OCI driver to talk to Oracle. In addition to ready-made Oracle client drivers, there is also an RPM package for the `oracle_fdw` extension itself, which is provided by the community. If you are not using an RPM-based system, you might have to compile things on your own, which is clearly possible but a bit more labor-intensive.

Once the software has been installed, it can be enabled easily:

```
test=# CREATE EXTENSION oracle_fdw;
```

The `CREATE EXTENSION` clause loads the extension into your desired database. In the next step, a server can be created and users can be mapped to their counterparts on the Oracle side:

```
test=# CREATE SERVER oraserver FOREIGN DATA WRAPPER oracle_fdw
      OPTIONS (dbserver '//dbserver.example.com/ORADB');
test=# CREATE USER MAPPING FOR postgres SERVER oradb
      OPTIONS (user 'orauser', password 'orapass');
```

Then it is time to fetch some data. My preferred way is to use the `IMPORT FOREIGN SCHEMA` clause to import the data definitions. The `IMPORT FOREIGN SCHEMA` clause will create a foreign table for each table in a remote schema and expose the data on the Oracle side, which can then be read easily.

The easiest way to make use of the schema import is to create separate schemas on PostgreSQL, which just hold the database schema. Then data can be sucked into PostgreSQL easily using the FDW. The last section of this book, about migrating from MySQL, shows you an example of how this can be done with MySQL/MariaDB. Keep in mind that the `IMPORT FOREIGN SCHEMA` clause is part of the SQL/MED standard and therefore the process is the same as with MySQL/MariaDB. This applies to pretty much every FDW that supports the `IMPORT FOREIGN SCHEMA` clause.

While the `oracle_fdw` extension does most of the work for you, it still makes sense to see how datatypes are mapped. Oracle and PostgreSQL don't provide the exact same data types, so some mapping is either done by the `oracle_fdw` extension or by you manually. The following list gives you an overview of how types are mapped. The left column shows the Oracle types and the right column presents the potential PostgreSQL counterparts:

Oracle types	PostgreSQL types
CHAR	char, varchar, and text
NCHAR	char, varchar, and text
VARCHAR	char, varchar, and text
VARCHAR2	char, varchar, and text
NVARCHAR2	char, varchar, and text
CLOB	char, varchar, and text
LONG	char, varchar, and text
RAW	uuid and bytea
BLOB	bytea

BFILE	bytea (read-only)
LONG RAW	bytea
NUMBER	numeric, float4, float8, char, varchar, and text
NUMBER (n, m) with m<=0	numeric, float4, float8, int2, int4, int8, boolean, char, varchar, and text
FLOAT	numeric, float4, float8, char, varchar, and text
BINARY_FLOAT	numeric, float4, float8, char, varchar, and text
BINARY_DOUBLE	numeric, float4, float8, char, varchar, and text
DATE	date, timestamp, timestamptz, char, varchar, and text
TIMESTAMP	date, timestamp, timestamptz, char, varchar, and text
TIMESTAMP WITH TIME ZONE	date, timestamp, timestamptz, char, varchar, and text
TIMESTAMP WITH LOCAL TIME ZONE	date, timestamp, timestamptz, char, varchar, and text
INTERVAL YEAR TO MONTH	interval, char, varchar, and text
INTERVAL DAY TO SECOND	interval, char, varchar, and text
MDSYS.SDO_GEOMETRY	geometry

If you want to use geometries, make sure that PostGIS is installed on your database server.

The downside of the `oracle_fdw` extension is definitely that it cannot migrate procedures out of the box. Stored procedures are a somewhat special thing and need some manual intervention.

Using ora2pg to migrate from Oracle

People migrated from Oracle to PostgreSQL long before FDWs existed. High license costs have plagued people for a long time, and so moving to PostgreSQL has been a natural thing to do for many years.

The alternative to the `oracle_fdw` extension is something called **ora2pg**, which has been around for many years and can be downloaded for free from <https://github.com/darold/ora2pg>. Ora2pg has been written in Perl and has a long tradition of new releases.

The features provided by ora2pg are stunning:

- Migration of the full database schema, including tables, views, sequences, and indexes (unique, primary, foreign key, and check constraints)
- Migration of privileges for users and groups
- Migration of partitioned tables
- Ability to export predefined functions, triggers, procedures, packages, and package bodies
- Migration of full or partial data (using a `WHERE` clause)
- Full support of Oracle BLOB objects as PostgreSQL `bytea`
- Ability to export Oracle views as PostgreSQL tables
- Ability to export Oracle user-defined types
- Basic automatic conversion of PL/SQL code to PL/pgSQL code. Note that a fully automated conversion of everything is not possible. However, a lot of stuff can be transformed automatically
- Ability to export Oracle tables as FDW tables
- Ability to export materialized views
- Ability to display detailed reports about Oracle database content
- Assessment of the complexity of the migration process of an Oracle database
- Migration cost assessment of PL/SQL code from a file
- Ability to generate XML files to be used with Pentaho data integrator (Kettle)
- Ability to export Oracle locator and spatial geometries into PostGIS
- Ability to export database links as Oracle FDW
- Ability to export synonyms as views
- Ability to export a directory as an external table or a directory for the `external_file` extension
- Ability to dispatch a list of SQL orders over multiple PostgreSQL connections
- Ability to perform a `diff` between Oracle and PostgreSQL databases for test purposes

Using ora2pg looks hard at first glance. However, it is actually a lot easier than it seems. The basic concept is as follows:

```
/usr/local/bin/ora2pg -c /some_path/new_ora2pg.conf
```

ora2pg needs a config file to run. The config file contains all the information needed to handle the process. Basically, the default config file is already really nice and it is a good start for most migrations. In ora2pg language, a migration is a project.

The configuration will drive the entire project. When you run it, `ora2pg` will create a couple of directories with all the data extracted from Oracle:

```
ora2pg --project_base /app/migration/ --init_project test_project
Creating project test_project.
/app/migration/test_project/
    schema/
        dblinks/
        directories/
        functions/
        grants/
        mviews/
        packages/
        partitions/
        procedures/
        sequences/
        synonyms/
        tables/
        tablespaces/
        triggers/
        types/
        views/
    sources/
        functions/
        mviews/
        packages/
        partitions/
        procedures/
        triggers/
        types/
        views/
    data/
    config/
    reports/

Generating generic configuration file
Creating script export_schema.sh to automate all exports.
Creating script import_all.sh to automate all imports.
```

As you can see, scripts are generated that can just be executed. The resulting data can then be imported in PostgreSQL nicely. Be prepared to change procedures here and there. Not everything can be migrated automatically, so manual intervention is expected.

Common pitfalls

There are some very basic syntax elements that work in Oracle but might not work in PostgreSQL. This section lists some of the most important things. Of course, this list is not complete by far, but it should point you in the right direction.

In Oracle, you might find the following statement:

```
DELETE mytable;
```

In PostgreSQL, this statement is wrong as PostgreSQL requires you to use a `FROM` clause in the `DELETE` statement. The good news is that this kind of statement is easy to fix.

The next thing you might find is:

```
SELECT sysdate FROM dual;
```

PostgreSQL has neither a `sysdate` function nor a `dual` function. The `dual` function part is easy to fix as you can simply create a `VIEW` returning one line. In Oracle, the `dual` function works like this:

```
SQL> desc dual
Name Null? Type
-----
DUMMY VARCHAR2(1)

SQL> select * from dual;

D
-
X
```

In PostgreSQL, the same can be achieved by creating the following `VIEW`:

```
CREATE VIEW dual AS SELECT 'X' AS dummy;
```

The `sysdate` function is also easy to fix. It can be replaced with the `clock_timestamp()` function.

Another common problem is the lack of data types such as `VARCHAR2`, as well as the lack of special functions only supported by Oracle. A good way to get around these issues is to install the `orafce` extension, which provides most of the stuff typically needed. It certainly makes sense to check out <https://github.com/orafce/orafce> to learn more about the `orafce` extension. It has been around for many years and is a solid piece of software.

A recent study shows that the `orafce` extension helps to ensure that 73% of all Oracle SQL can be executed on PostgreSQL without modifications if the `orafce` extension is around (done by NTT).

One of the most common pitfalls is the way Oracle handles outer joins. Consider the following example:

```
SELECT employee_id, manager_id
FROM employees
WHERE employees.manager_id(+) = employees.employee_id;
```

This kind of syntax is not provided by PostgreSQL and never will be. Therefore, the join has to be rewritten as a proper outer join. The `+` is highly Oracle-specific and has to be removed.

Moving from MySQL or MariaDB to PostgreSQL

In this chapter, you have already learned some valuable lessons about how to move from databases such as Oracle to PostgreSQL. Migrating both MySQL and MariaDB database systems to PostgreSQL is fairly easy. The reason for that is that Oracle might be expensive and a bit cumbersome from time to time. The same applies to Informix. However, both Informix and Oracle have one important thing in common: `CHECK` constraints are honored properly and data types are properly handled. In general, you can safely assume that the data in those commercial systems is somewhat correct and doesn't violate the most basic rules of data integrity and common sense.

Our next candidate is different. Many things you know about commercial databases are not true in MySQL. The term `NOT NULL` does not mean much to MySQL (unless you explicitly use strict mode). In Oracle, Informix, Db2, and all other systems I am aware of, `NOT NULL` is a law that is obeyed under all circumstances. MySQL does not take those constraints that seriously by default (although, to be fair, this has been changed in recent versions. Strict mode was not *on* by default up to very recently. However, many old databases still use the old default settings). In case of migration, this causes some issues. What are you going to do with data that is technically wrong? If your `NOT NULL` column suddenly reveals countless `NULL` entries, how are you going to handle that? MySQL doesn't just insert `NULL` values in `NOT NULL` columns. It will insert an empty string or zero based on the datatype. So, things can be pretty nasty.

Handling data in MySQL and MariaDB

As you might imagine, and as you might have noticed already, I am far from unbiased when it comes to databases. However, I don't want to turn this into blind MySQL/MariaDB bashing. My goal is really to show you why MySQL and MariaDB can be such a pain in the long run. I am biased for a reason and I really want to point out why this is the case. All the things you are going to see are deeply scary and have serious implications on the migration process in general. I have pointed out already that MySQL is somewhat special, and this section will try to prove my point.

Again, the following examples assume that you are using a version of MySQL/MariaDB that does not have strict mode on, which was the case when this chapter was originally written (as of PostgreSQL 9.6). As of PostgreSQL 10.0, strict mode is already on, so most of what you are going to read here only applies to older versions of MySQL/MariaDB.

Let me get started by creating a simple table:

```
MariaDB [test]> CREATE TABLE data (  
    id integer NOT NULL,  
    data numeric(4, 2)  
);  
Query OK, 0 rows affected (0.02 sec)  
  
MariaDB [test]> INSERT INTO data VALUES (1, 1234.5678);  
Query OK, 1 row affected, 1 warning (0.01 sec)
```

So far, there is nothing special. I have created a table consisting of two columns. The first column is explicitly marked as `NOT NULL`. The second column is supposed to contain a numeric value, which is limited to four digits. Finally, I have added a simple row. Can you see a potential landmine about to blow up? Most likely not. However, check the following listing:

```
MariaDB [test]> SELECT * FROM data;  
+----+-----+  
| id | data |  
+----+-----+  
| 1  | 99.99 |  
+----+-----+  
1 row in set (0.00 sec)
```

If I remember correctly, I have added a four digit number, which should not have worked in the first place. However, MariaDB has simply changed my data. Sure, a warning is issued, but this is not supposed to happen as the content of the table does not reflect what I have actually inserted.

Let me try to do the same thing in PostgreSQL:

```
test=# CREATE TABLE data
(
    id integer NOT NULL,
    data numeric(4, 2)
);
CREATE TABLE
test=# INSERT INTO data VALUES (1, 1234.5678);
ERROR: numeric field overflow
DETAIL: A field with precision 4, scale 2 must round to an absolute value
less than 10^2.
```

The table is created just like earlier, but in stark contrast to MariaDB/MySQL, PostgreSQL will error out because we are trying to insert a value into the table that is clearly not allowed. What is the point in clearly defining what we want if the database engine just does not care? Suppose you have won the lottery—you might have just lost a couple of million because the system has decided what is good for you.

I have been fighting commercial databases all my life, but I have never seen similar things in any of the expensive commercial systems (Oracle, Db2, Microsoft SQL Server, and so on). They might have issues of their own but the data is just fine in general.

Changing column definitions

Let's see what happens if you want to modify the table definition:

```
MariaDB [test]> ALTER TABLE data MODIFY data numeric(3, 2);
Query OK, 1 row affected, 1 warning (0.06 sec)
Records: 1 Duplicates: 0 Warnings: 1
```

You should see a problem here:

```
MariaDB [test]> SELECT * FROM data;
+-----+-----+
| id | data |
+-----+-----+
| 1  | 9.99 |
+-----+-----+
1 row in set (0.00 sec)
```

As you can see, the data has been modified again. It should not have been there in the first place and has been changed all over again. Remember, you might have lost money again, or some other nice asset, because MySQL tried to be clever.

This is what happens in PostgreSQL:

```
test=# INSERT INTO data VALUES (1, 34.5678);
INSERT 0 1
test=# SELECT * FROM data;
 id | data 
-----+-----
  1  | 34.57
(1 row)
```

Let's change the column definition now:

```
test=# ALTER TABLE data ALTER COLUMN data
      TYPE numeric(3, 2);
ERROR: numeric field overflow
DETAIL:  A field with precision 3, scale 2 must round to
an absolute value less than 10^1.
```

Again, PostgreSQL will error out and it won't allow you to do nasty things to your data. The same is expected to happen in any important database. The rule is simple: PostgreSQL and others won't allow you to destroy your data.

However, PostgreSQL allows you to do one thing:

```
test=# ALTER TABLE data
      ALTER COLUMN data
      TYPE numeric(3, 2)
      USING (data / 10);
ALTER TABLE
```

You can explicitly tell the system how to behave. In this case, I explicitly told PostgreSQL to divide the content of the column by 10. Developers can explicitly provide the rules applied to the data. PostgreSQL won't try to be smart, and it does so for good reason:

```
test=# SELECT * FROM data;
 id | data 
-----+-----
  1  |  3.46
(1 row)
```

The data is exactly as expected.

Handling null values

I don't want to turn this into a why MariaDB is bad chapter, but I wanted to add a final example here, which I consider to be of high importance:

```
MariaDB [test]> UPDATE data SET id = NULL WHERE id = 1;
Query OK, 1 row affected, 1 warning (0.01 sec)
Rows matched: 1 Changed: 1 Warnings: 1
```

Remember, the `id` column was explicitly marked as `NOT NULL`:

```
MariaDB [test]> SELECT * FROM data;
+----+-----+
| id | data |
+----+-----+
| 0  | 9.99 |
+----+-----+
1 row in set (0.00 sec)
```

Obviously, MySQL and MariaDB think that null and zero are the same thing. Let me try to explain the problem with a simple analogy: if you know your wallet is empty, it is not the same as *not knowing how much you have*. As I am writing these lines, I don't know how much money I have with me (null = unknown), but I am 100% sure that it is way more than zero (I know with certainty that it is enough to refuel my beloved car on the way home from the airport, which is hard to do if you have nothing in your pocket).

Here is more scary news:

```
MariaDB [test]> DESCRIBE data;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id    | int(11) | NO | | NULL | |
| data  | decimal(3,2) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

MariaDB does remember that the column is supposed to be `NOT NULL`. However, it simply modifies your data again.

Expecting problems

The main problem is that you might have trouble moving data to PostgreSQL. Just imagine you want to move some data and there is a `NOT NULL` constraint on the PostgreSQL side.

We know MySQL does not care:

```
MariaDB [test]> SELECT
    CAST('2014-02-99 10:00:00' AS datetime) AS x,
    CAST('2014-02-09 10:00:00' AS datetime) AS y;
+-----+-----+
| x | y |
+-----+-----+
| NULL | 2014-02-09 10:00:00 |
+-----+-----+
1 row in set, 1 warning (0.00 sec)
```

PostgreSQL will definitely reject February 99 (for a good reason), but it might not accept the `NULL` value either if you have explicitly banned it (for a good reason). What you have to do in this case is to somehow fix the data to make sure that it honors the rules of your data models, which are in place for a reason. You should not take this lightly because you might have to change data, which is actually wrong in the first place.

Migrating data and schema

After trying to explain why moving to PostgreSQL is a good idea, and after outlining some of the most important issues, it is time for me to explain some of the possible options you have to finally get rid of MySQL/MariaDB.

Using pg_chameleon

One way to move from MySQL/MariaDB to PostgreSQL is to use Federico Campoli's tool, called `pg_chameleon`, which can be downloaded for free from GitHub:

https://github.com/the4thdoctor/pg_chameleon. It has been explicitly designed to replicate data to PostgreSQL and does a lot of work, such as converting the schema for you.

Basically, the tool performs the following four steps:

1. `pg_chameleon` reads the schema and data from MySQL and creates a schema in PostgreSQL.
2. Stores MySQL's master connection information in PostgreSQL.
3. Creates primary keys and indices in PostgreSQL.
4. Replicates from MySQL/MariaDB to PostgreSQL.

The `pg_chameleon` tool provides basic support for DDLs such as `CREATE`, `DROP`, `ALTER TABLE`, and `DROP PRIMARY KEY`. However, due to the nature of MySQL/MariaDB, it does not support all DDLs. Instead, it covers the most important features.

However, there is more to `pg_chameleon`. I have stated extensively already that data is not always the way it should be or is expected to be. The way `pg_chameleon` approaches the problem is to discard rubbish data and store it in a table called `sch_chameleon.t_discarded_rows`. Of course, this is not a perfect solution but, given the fairly low-quality input, it is the only sensible solution that comes to my mind. The idea is to let developers decide what to do with all the broken rows. There is really no way for `pg_chameleon` to decide on how to handle something which has been broken by somebody else.

Recently, a lot of development has taken place and a lot of work has gone into the tool. Therefore, it is really recommended to check out the GitHub page and read through all the documentation. Features and bug fixes are being added as we speak. Given the limited scope of this chapter, full coverage is not possible here.



Stored procedures, triggers, and more need special treatment and can only be handled manually. The `pg_chameleon` tool cannot process those things automatically.

Using FDWs

If you want to move from MySQL/MariaDB to PostgreSQL there is more than one way to succeed. The use of FDWs is an alternative to `pg_chameleon` and offers a way to quickly fetch the schema as well as the data and import it into PostgreSQL. The ability to connect MySQL and PostgreSQL has been around for quite a while and therefore FDWs are definitely a field that can be exploited to your advantage.

Basically, the `mysql_fdw` extension works just like any other FDW out there. Compared to other, lesser-known FDWs, the `mysql_fdw` extension is actually quite powerful and offers the following features:

- Writing to MySQL/MariaDB
- Connection pooling
- The `WHERE` clause push down (which means that filters applied on a table can actually be executed remotely for better performance)
- Column push down (only the columns needed are fetched from the remote side; older versions are used to fetch all the columns, which leads to more network traffic)
- Prepared statements on the remote side

The way to use the `mysql_fdw` extension is to make use of the `IMPORT FOREIGN SCHEMA` statement, which allows for moving data over to PostgreSQL. Fortunately, this is fairly easy to do on a Unix system.

The first thing you have to do is to download the code from GitHub:

```
git clone https://github.com/EnterpriseDB/mysql_fdw.git
```

Then run the following commands to compile the FDW. Note that the paths might differ on your system. For this chapter, I have assumed that both MySQL and PostgreSQL are under `/usr/local` directory, which might not be the case on your system:

```
$ export PATH=/usr/local/pgsql/bin/:$PATH
$ export PATH=/usr/local/mysql/bin/:$PATH
$ make USE_PGXS=1
$ make USE_PGXS=1 install
```

Once the code has been compiled, the FDW can be added to your database:

```
CREATE EXTENSION mysql_fdw;
```

The next step is to create the server you want to migrate:

```
CREATE SERVER migrate_me_server
  FOREIGN DATA WRAPPER mysql_fdw
  OPTIONS (host 'host.example.com', port '3306');
```

Once the server has been created you can create the desired user mappings:

```
CREATE USER MAPPING FOR postgres
  SERVER migrate_me_server
  OPTIONS (username 'joe', password 'public');
```

Finally, it is time to do the real migration. The first thing to do is to import the schema. I suggest creating a special schema for the linked tables first:

```
CREATE SCHEMA migration_schema;
```

When running the `IMPORT FOREIGN SCHEMA` statement, you can use this schema as the target schema in which all the database links will be stored. The advantage is that you can delete it conveniently after the migration.

Once you are done with the `IMPORT FOREIGN SCHEMA` statement, you can create real tables. The easiest way to do that is to use the `LIKE` keyword provided by the `CREATE TABLE` clause. It allows you to copy the structure of a table and create a real local PostgreSQL table. Fortunately, this also works if the table you are cloning is just an FDW. Here is an example:

```
CREATE TABLE t_customer
  (LIKE migration_schema.t_customer);
```

Then, you can process the data:

```
INSERT INTO t_customer
  SELECT * FROM migration_schema.t_customer
```

This is actually the point where you can correct the data, eliminate chunk rows, or do a bit of processing of the data. Given the low-quality origin of the data, it can be useful to apply constraints and so on after moving the data for the first time. It might be less painful.

Once the data has been imported, you are ready to deploy all the constraints, indexes, and so on. At this point, you will actually start to see some nasty surprises because as I stated previously, you can't expect the data to be rock-solid. In general, migration can be pretty hard in the case of MySQL.


Summary

In this chapter, you learned how to move to PostgreSQL. Migration is an important topic and more and more people are adopting PostgreSQL as we speak.

PostgreSQL 10 has many new features such as built-in partitioning, the ability to create more statistics (`CREATE STATISTICS`), and logical replication features. In future, we will see many more developments in all areas of PostgreSQL, especially to allow users to scale out more and to run queries even faster. We are yet to see what the future has in store for us.

Other Books You May Enjoy

If you enjoyed this book, you may be interested in these other books by Packt:




Learning PostgreSQL 10 - Second Edition

Salahaldin Juba, Andrey Volkov

ISBN: 978-1-78839-201-3

- Understand the fundamentals of relational databases, relational algebra, and data modeling
- Install a PostgreSQL cluster, create a database, and implement your data model
- Create tables and views, define indexes, and implement triggers, stored procedures, and other schema objects
- Use the Structured Query Language (SQL) to manipulate data in the database
- Implement business logic on the server side with triggers and stored procedures using PL/pgSQL
- Make use of advanced data types supported by PostgreSQL 10: Arrays, hstore, JSONB, and others
- Develop OLAP database solutions using the most recent features of PostgreSQL 10
- Connect your Python applications to a PostgreSQL database and work with the data efficiently
- Test your database code, find bottlenecks, improve performance, and enhance the reliability of the database applications



PostgreSQL Administration Cookbook, 9.5/9.6 Edition

Simon Riggs, Gianni Ciolli, Gabriele Bartolini

ISBN: 978-1-78588-318-7

- Implement PostgreSQL features for performance and reliability
- Harness the power of the latest PostgreSQL 9.6 features
- Manage open source PostgreSQL versions 9.5 and 9.6 on various platforms
- Discover advanced technical tips for experienced users
- Explore best practices for planning and designing live databases
- Select and implement robust backup and recovery techniques
- Explore concise and clear guidance on replication and high availability
- See the latest details on Logical Replication and Bi-Directional Replication

Leave a review - let other readers know what you think

Please share your thoughts on this book with others by leaving a review on the site that you bought it from. If you purchased the book from Amazon, please leave us an honest review on this book's Amazon page. This is vital so that other potential readers can see and use your unbiased opinion to make purchasing decisions, we can understand what our customers think about our products, and our authors can see your feedback on the title that they have worked with Packt to create. It will only take a few minutes of your time, but is valuable to other potential customers, our authors, and Packt. Thank you!

Index

A

- administrative tasks
 - speeding up 194
- adminpack
 - using 326
- advisory locks
 - utilizing 34, 35
- aggregates
 - efficiency, improving 121
 - hypothetical aggregates, writing 123
 - simple aggregates, creating 117, 120
 - support, adding for parallel queries 121
 - writing 117
- analytics
 - utilizing 102
- asynchronous replication
 - basic setup, performing 296
 - checking, for availability 299, 302
 - conflicts, managing 303
 - failovers, performing 303
 - halting 298
 - reliability feature, adding 306
 - replication 298
 - security, improving 298
 - setting up 295
 - timelines 302
- autovacuum 36

B

- b-tree features
 - about 61
 - combined indexes 61
 - data, adding while indexing 65
 - functional indexes, adding 62
 - space consumption, reducing 63
- backups

- replaying 276
- basic locking
 - about 20, 21
 - alternative solutions 24
 - typical mistakes, avoiding 22, 23
- Bi-Directional Replication (BDR) 317
- bind addresses 238
- bitmap scans
 - using 53
- block range indexes (BRIN) indexes
 - extending 80
- bloom filters
 - applying 328
 - reference 82, 329
- btree_gin
 - deploying 330
- btree_gist
 - deploying 330

C

- checkpoints 282
- cleanup
 - managing 35, 36
- clog corruption
 - about 359
 - facing 359
- clustered tables
 - used, for improving speed 56
- column-level security
 - handling 257
- combined indexes 61
- common table extension (CTE) 368
- connections 238
- constant folding 161
- contrib modules
 - adminpack, using 326

- bloom filters, applying 328
- btree_gin, deploying 330
- btree_gist, deploying 330
- Dblink 331
- files, fetching with file_fdw 332
- pageinspect, used for storage inspection 334
- pg_buffercache, used for caching investigation 336
- pg_prewarm variable, used for prewarming caches 338
- pg_stat_statements, used for performance inspection 339
- pg_trgm, used for fuzzy searches 342
- pgcrypto, used for data encryption 338
- pgstattuple, used for storage inspection 340
- postgres_fdw, used for remote servers connection 342
- using 326
- cost model 45
- CREATE PUBLICATION
 - using 318
- CREATE SUBSCRIPTION
 - using 318
- Cybertec
 - reference 111

D

- data partitions
 - creating 182, 183
 - data, cleaning up 187
 - inherited structures, modifying 185
 - PostgreSQL 10.0 partitioning 188
 - table constraints, applying 184
 - tables, moving in and out 186
- data
 - partitioning 181
- database administration functions
 - about 6
 - additional information, using in pg_stat_activity 6
- database-level security
 - defining 252
- databases
 - inspecting 130
 - tables, inspecting 133
- Dblink 331

- deadlocks
 - observing 31, 32, 34
- default privileges
 - configuring 259

E

- execution plans
 - about 166
 - approaching 166
- EXPLAIN
 - making verbose 168
 - using 46
- explicit locking 22, 23
- extensions
 - about 346
 - available extensions, checking 323, 325
 - working 322

F

- FDWs
 - using 388, 390
- file_fdw
 - used, for fetching files 332
- FILTER clause
 - and grouping sets, combining 98
 - supporting engines 370
- FOR SHARE
 - using 25, 26, 28
- FOR UPDATE
 - using 25, 26, 28
- foreign-data wrapper (FDW) 376
- format
 - handling 275
- Free Space Map (FSM) 36
- Full-Text-Search (FTS)
 - about 86
 - exclusion operators, suing 91
 - GIN indexes, defining 88
 - search, debugging 89
 - strings, comparing 87
 - word statistics, gathering 90
- function calls
 - cached plans, using 233
 - costs, assigning to functions 233

- count, reducing 232
- query execution stages 233

function inlining 162

functional indexes

- adding 62

fuzzy searching

- answers, achieving 82
- LIKE queries, speeding up 85
- pg_trgm, using 82
- regular expressions, handling 86

G

generalized inverted (GIN) indexes

- about 76
- extending 77

Generalized Search Tree (GiST) indexes

- about 73
- extending 75
- working 74

genetic query optimization 180, 181

Geographical Information Systems (GIS) 347

global data

- handling 277

grouping sets

- about 93
- applying 94
- combining, with FILTER clause 98
- performance, investigating 97
- sample data, loading 94
- supporting sets 367
- using 367

H

hash indexes 73

high temporary file usage

- reasons 131

hypothetical aggregates

- about 101
- writing 123

I

I/O

- checking for 357

ICU encodings 11

index only scans

- using 60

indexes

- using 54

instance-level security

- handling 246
- users, creating 249
- users, modifying 249

issues

- buffer usage, inspecting 171
- changes, spotting in runtime 169
- estimates, inspecting 169
- high buffer usage, fixing 173

J

join options evaluation

- hash joins 156
- merge joins 156
- nested loops 156

join pruning 163

join_collapse_limit variable 176

joins

- fixing 173
- join_collapse_limit variable 176
- obtaining 173
- outer joins, processing 175

K

K-Nearest Neighbor (KNN) 330

L

lateral joins

- supporting lateral joins 366
- using 366

lightweight directory access protocol (LDAP) 244

limit/offset

- FETCH FIRST clause 374
- using 374

log files

- creating 147
- postgresql.conf file, configuring 147

log

- inspecting 355

logical replication slots

- handling 314, 317
- use cases 317

M

MariaDB

- column definitions, changing 384, 385
- data migration, with pg_chameleon 387
- data, handling 383
- expecting problems 387
- FDWs, using 388
- migrating, to PostgreSQL 382
- null values, handling 386
- schema, migrating 387

memory

- checking for 357

missing indexes

- checking for 356

Multi-Version Concurrency Control (MVCC) 20

MySQL

- column definitions, changing 384, 385
- data migration, with pg_chameleon 388
- data, handling 383
- data, migrating 387
- expecting problems 387
- FDWs, using 388
- migrating, to PostgreSQL 382
- null values, handling 386

N

network security

- bind addresses and connections 238
- column-level security 257
- connections, inspecting 240
- database-level security, defining 251
- default privileges, configuring 259
- instance-level security, handling 246
- managing 237
- performance, inspecting 240
- pg_hba.conf file, managing 242
- schema-level permissions, adjusting 253
- tables, working with 256
- TCP, avoiding 240

noteworthy error scenarios

- about 359

- careless connection management 363
- checkpoint messages 360
- clog corruption, facing 359
- corrupted data pages, managing 361
- table bloat, fighting 363

O

objects

- reassigning 266

OFFSET clause

- supporting engines 374

onboard windowing functions

- dense_rank function 109
- first_value() function 114
- lag() function 111, 114
- last_value() function 114
- lead() function 111, 114
- nth_value() function 114
- ntile() function 110
- rank function 109
- row_number() function 116

Online-Transaction-Processing (OLTP) 30

operator classes

- about 65
- creating 71
- custom operator classes, testing 71
- hacking, up for b-tree 67
- new operators, creating 67

optimization

- by example 155
- constant folding 161
- equality constraints, applying 158
- exhaustive searching 159
- function inlining 162
- join options, evaluating 155
- join pruning 163
- process, making to fail 160
- set operations, speeding up 164
- transformations, applying 157
- trying 159

optimizer 154

optimizer settings

- disabling 177, 180
- enabling 177, 180
- genetic query optimization 180

- ora2pg
 - features 379
 - reference 378

Oracle, migration to PostgreSQL

- about 376
- common pitfalls 381
- ora2pg, using 378, 380
- oracle_fdw extension, used for moving data 376, 378

- orafce extension
 - reference 381

- ordered sets
 - using 99

- outer joins
 - processing 175

P

- pageinspect
 - used, for storage inspection 334

- parameters
 - adjusting, for good query performance 189, 191
 - administrative tasks, speeding up 194
 - sorting, speed up 192

passwords and connection information

- passing 271
- passing, with .pgpass 273
- passing, with environment variables 272
- passing, with service files 273

- permissions
 - inspecting 264

- pg_buffercache
 - used, for caching investigation 336, 338

- pg_chameleon
 - reference 387
 - using 387

- pg_crash
 - reference 347

- pg_hba.conf file
 - managing 242
 - SSL, handling 244

- pg_prewarm variable
 - used, for prewarming caches 338

- pg_squeeze
 - reference 38, 363

- pg_stat_activity

- Hibernate statements, treating 351
- inspecting 349
- queries origin, searching 351
- querying 349

- pg_stat_statements
 - used, for inspecting performance 339

- pg_trgm
 - used, for fuzzy searches 342

- pgcrypto
 - reference 338
 - used, for data encryption 338

- pgstattuple
 - used, for inspecting storage 340

- pgwatch2
 - reference 348

- physical replication slots
 - handling 312

PL/Perl

- about 220
- data, sharing across function calls 226
- escaping 226
- PL/PerlU, selecting between 223
- SPI , used for set returning functions 225
- SPI interface, using 224
- support functions 226
- triggers, writing 227
- used, for datatype abstraction 222

PL/pgSQL

- advanced error handling 207
- composite types, utilizing 214
- cursors, used for data fetching in chunks 210
- GET DIAGNOSTICS, using 208
- quoting, handling 203
- scopes, managing 206
- triggers, writing 215, 218

PL/Python

- about 227
- code, writing 228
- errors, handling 231
- SPI interface, using 229

- pluggable authentication module (PAM) 244

- Point-In-Time-Recovery (PITR) 284

- PostGIS
 - reference 347

- postgres_fdw

- mistakes and typos, handling 346
 - used, for connecting remote servers 342, 345
- PostgreSQL 10.0 partitioning 188
- PostgreSQL 10.0
 - database administration functions 6
 - features 5
- PostgreSQL consultant
 - reference 22, 39
- PostgreSQL cost model
 - exploring 48
- PostgreSQL index types
 - about 72
 - additional indexes, adding 80
 - block range indexes (BRIN) indexes 79
 - generalized inverted (GIN) indexes 76
 - GiST indexes 73
 - hash indexes 73
 - SP-GiST indexes 78
- PostgreSQL system views
 - archiving 138
 - background worker, tracking 137
 - databases, inspecting 130
 - indexes, exploring 136
 - live traffic, checking 127
 - pg_stat_statements, using 143
 - pg_stat_user_tables 134
 - SSL connections, checking 141
 - streaming 138
 - tracking 138
 - transactions, inspecting 141
 - vacuum progress, tracking 142
 - working with 127
- PostgreSQL transactions
 - errors, handling 16
 - SAVEPOINT, using 17
 - transactional DDLs 18
 - working with 14, 16
- postgresql.conf file configuration
 - about 148
 - log destination and rotation, defining 148
 - logging 151
 - slow queries, logging 150
 - syslog, configuring 150
- PostgreSQL
 - reference 117, 227

- SQL statements, migrating 366

Q

- quorum COMMIT
 - about 8
 - CREATE STATISTICS, using 10
 - data, partitioning 9
 - parallelism, improving 11

R

- remote authentication dial-in user service (RADIUS) 244
- replication slots
 - about 311
 - logical replication slots, handling 314
 - physical replication slots, handling 312
 - using 311
- row-level security (RLS)
 - exploring 260, 263, 264
- runtime statistics
 - gathering 126
 - PostgreSQL system views, working with 127

S

- schema-level permissions
 - adjusting 255
- SCRAM-SHA-256
 - about 7
 - logical replication 7
 - support, for replication 7
- Serializable Snapshot Isolation (SSI) 31
- serizable
 - reference 31
- Set Returning Function (SRF) 211
- simple aggregates
 - creating 117, 120
- simple dumps
 - passwords and connection information, passing 271
 - performing 269
 - pg_dump logs, executing 270
 - subsets of data, extracting 274
- simple indexes
 - deploying 50

- simple queries 45
- slow queries
 - checking for 352
 - individual queries, inspecting 353
 - perf, using 354
- snapshot too old feature 350
- snapshot
 - using 43
- sorted output
 - multiple index, using 52
 - using 51
- space consumption
 - reducing 63
- space partitioned GiST (SP-GiST) indexes 78
- Spinlocks
 - reference 355
- SQL statements, migration to PostgreSQL
 - about 366
 - FILTER clause, using 369
 - grouping sets, using 367
 - lateral joins, using 366
 - limit/offset, using 373
 - OFFSET, using 374
 - TABLESAMPLE clause, using 372
 - temporal tables, using 375
 - time series, matching patterns 375
 - windowing functions, using 370
 - WITH clause, using 368
 - WITH RECURSIVE clause, using 369
 - WITHIN GROUP clause, using 371
- storage
 - optimizing 35, 36
- stored procedure languages
 - about 195, 201
 - anatomy 197
 - anonymous code blocks, using 199
 - dollar quoting 198
 - functions and transactions, using 199
 - performance, improving 232
 - PL/Perl 220
 - PL/pgSQL 202
 - PL/Python 228
- stored procedure performance
 - function calls count, reducing 232
 - improving 232

- stored procedures
 - using 234
- synchronous replication
 - durability, adjusting 309
 - upgrading to 307

T

- table bloat 340
- tables
 - clustering 59
- TABLESAMPLE clause
 - supporting engines 373
 - using 372
- temporal tables
 - supporting tables 375
- The Oversized Attribute Storage Technique (TOAST) 135
- transaction isolation levels 29, 30, 31
- transaction log
 - about 280
 - archive, cleaning up 295
 - archiving 284
 - archiving, configuration 284
 - base backups, creating 286
 - checkpoints 282
 - optimizing 282
 - pg_hba.conf file, configuring 286
 - recovery 284
 - replaying 290
 - right timestamp, finding 292
 - viewing 281
- transaction wraparound-related issues
 - exploring 37, 38
- transformations, applying
 - subselects, flattening 158
 - view, inlining 157

U

- unknown database
 - approaching 348
- users
 - dropping 266

V

VACUUM FULL 38

VACUUM

- about 36

- working 39, 41, 42

W

windowing functions

- data, ordering inside window 104

- data, partitioning 103

- onboard windowing functions, using 108

- sliding windows, using 105

- supporting windowing and analytics 371

- utilizing 102

- window clauses, abstracting 108

WITH clause

- supporting engines 368

- using 368

WITH RECURSIVE clause

- supporting engine 369

WITHIN GROUP clause

- supporting engines 372

Write Ahead Log (WAL) 280