

eICU-CRD — schema reference

31 tables, 391 columns, 4,605,753 rows. Generated from the database itself by `scripts/build_schema_reference.py`, so it cannot disagree with it.

Where each **description comes from** is printed beside it. **eICU** — a documented convention of the published dataset. **glossary** — the column is declared in `config/glossary.yaml`, and the note shown is the one the cloud model receives. **measured** — nothing documents this column, so what is printed is what it holds, counted here. No description is invented to fill a cell.

tier is the indexing decision (`db/value_index.py`): **A** indexed — every distinct value is stored, so a mention resolves to it; **B** on demand — too many distinct values to store; searched with a bounded LIKE; **C** excluded — an identifier, a timestamp or free text; never resolved.

Example values are real, from eICU-CRD Demo v2.0.1 — a public, de-identified research database published by the MIT Laboratory for Computational Physiology. They are shown because a column named `splitemvalue` means nothing until you see three of them.

table	rows	cols	what it holds
admissiondrug	7,417	14	Drugs the patient was already taking when admitted, as recorded on the admission form.
admissiondx	7,578	6	The admission diagnosis as entered in the APACHE flowsheet.
allergy	2,475	13	Recorded allergies, with the drug involved.
apacheapsvar	2,205	26	The raw physiological variables the APACHE score is computed from.
apachepatientresult	3,676	23	APACHE scores and the predicted outcomes derived from them, with the actual outcome beside each.
apachepredvar	2,205	51	The predictor variables feeding the APACHE model, including chronic conditions.
careplancareprovider	5,627	8	Which specialty was responsible for the patient, and when.
careplaneol	15	5	End-of-life care plan entries.
careplangeneral	33,148	6	General care plan entries, as item/value pairs.
careplangoal	3,633	7	Care plan goals, as item/value pairs.
careplaninfectiousdisease	112	8	Infectious-disease care plan entries.
customlab	30	7	Laboratory results outside the standard set.
diagnosis	24,978	7	Diagnoses recorded during the stay, as a hierarchy plus an ICD-9 code.
hospital	186	4	One row per hospital: region, bed count, teaching status.
infusiondrug	38,256	9	Continuous infusions, with rate and volume over time.
intakeoutput	100,466	12	Fluid intake and output, charted as labelled cells.
lab	434,660	10	Laboratory results: name, numeric value, unit, time.
medication	75,604	15	Medication orders: drug, dose, route, frequency, start and stop.
microlab	342	7	Microbiology cultures: site, organism, antibiotic sensitivity.
note	24,758	8	Clinical notes, stored as path/value pairs rather than free prose.
nurseassessment	91,589	8	Nursing assessments, as attribute/value pairs.
nursecare	42,080	8	Nursing care items, as attribute/value pairs.

table	rows	cols	what it holds
nursecharting	1,477,163	8	The nursing flowsheet — the largest table here. Cell type, label and value, one row per charted item.
pasthistory	12,109	8	Medical history recorded on admission, as a hierarchy.
patient	2,520	29	One row per ICU stay: demographics, admission and discharge. The centre of the schema — every other table joins here.
physicalexam	84,058	6	Physical examination findings, as path/value pairs.
respiratorycare	5,436	34	Ventilator settings and respiratory care events.
respiratorycharting	176,089	7	The respiratory flowsheet, charted like nursecharting.
treatment	38,290	5	Treatments given, as a hierarchy.
vitalaperiodic	274,088	13	Vital signs recorded intermittently, one row per measurement time.
vitalperiodic	1,634,960	19	Vital signs recorded automatically, typically every five minutes. The largest table by row count.

admissiondrug

7,417 rows · 14 columns · Drugs the patient was already taking when admitted, as recorded on the admission form.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
admissiondrugid	INT	PK	7,417			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	551			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
drugoffset	INT		560			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
drugenteredoffset	INT		576			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
drugnotetype	TEXT		6		A	A category from a small controlled list.	eICU	Daily Progress · Admission · Comprehensive Progress
specialtytype	TEXT		3		A	A category from a small controlled list.	eICU	eCM Primary · critical care medicine (CCM) · nephrology
usertype	TEXT		11		A	A category from a small controlled list.	eICU	THC Physician · THC Nurse · Other
rxincluded	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	False · True
writtenineicu	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	True · False
drugname	TEXT		820		A	The drug as recorded by the hospital, including strength and form: 'ASPIRIN EC 81 MG PO TBEC'. This is why a question saying 'aspirin' has to be resolved against the value index before any query is written.	eICU	ABILIFY · ABILIFY DISCMELT · ACCUPRIL
drugdosage	REAL		46			46 distinct values.	measured	0 · 50 · 20
drugunit	TEXT		11		A	A bounded vocabulary of 11 distinct values.	measured	mg · tablet(s) / capsule(s) · puffs
drugadmitfrequency	TEXT		7		A	A bounded vocabulary of 7 distinct values.	measured	twice a day · daily · PRN
drughclseqno	INT		578			578 distinct values.	measured	20769 · 1100 · 182

admissiondx

7,578 rows · 6 columns · The admission diagnosis as entered in the APACHE flowsheet.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
admissiondxid	INT	PK	7,578			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,221			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
admitdxenteredoffset	INT		528			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
admitdxpath	TEXT		294		A	A path naming where this value sits in the charting hierarchy.	eICU	admission diagnosis Elective Yes · admission diagnosis Elective No
admitdxname	TEXT		268		A	The glossary declares this column as 'diagnosis'. diagnosisstring is hierarchical, pipe-separated from general to specific.	glossary	Cardiovascular · No · Sepsis, pulmonary
admitdxtext	TEXT		280		A	Free text as entered.	eICU	Cardiovascular · No · Sepsis, pulmonary

allergy

2,475 rows · 13 columns · Recorded allergies, with the drug involved.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
allergyid	INT	PK	2,475			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	774			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
allergyoffset	INT		470			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
allergyenteredoffset	INT		498			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
allergytype	TEXT		6		A	A category from a small controlled list.	eICU	Comprehensive Progress · Admission · Daily Progress
specialtytype	TEXT		2		A	A category from a small controlled list.	eICU	eCM Primary · critical care medicine (CCM)
usertype	TEXT		10		A	A category from a small controlled list.	eICU	THC Nurse · THC Physician · Other
rxincluded	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	True · False
writtenineicu	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	True · False
drugname	TEXT		297		A	The drug as recorded by the hospital, including strength and form: 'ASPIRIN EC 81 MG PO TBEC'. This is why a question saying 'aspirin' has to be resolved against the value index before any query is written.	eICU	CODEINE PHOSPHATE · VALSARTAN · HYDROCHLOROTHIAZIDE
allergytype	TEXT		2		A	The glossary declares this column as 'allergy'.	glossary	Non Drug · Drug
allergyname	TEXT		666		A	The glossary declares this column as 'allergy'.	glossary	"CAN'T take narcs" · ? lasix · ? norco / opiates
drughiclseqno	INT		251			251 distinct values.	measured	1721 · 12204 · 3649

apacheapsvar

2,205 rows · 26 columns · The raw physiological variables the APACHE score is computed from.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
apacheapsvarid	INT	PK	2,205			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,205			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
intubated	INT		2			2 distinct values.	measured	0 · 1
vent	INT		2			2 distinct values.	measured	0 · 1
dialysis	INT		2			2 distinct values.	measured	0 · 1
eyes	INT		5			5 distinct values.	measured	4 · -1 · 1
motor	INT		7			7 distinct values.	measured	6 · -1 · 5
verbal	INT		6			6 distinct values.	measured	5 · 3 · -1
meds	INT		3			3 distinct values.	measured	0 · -1 · 1
urine	REAL		1,027			1,027 distinct values.	measured	-1.0 · 674.9568 · 0.0
wbc	REAL		490			490 distinct values.	measured	10.2 · 11.7 · 7.9
temperature	REAL		109			109 distinct values.	measured	36.2 · 36.4 · 36.7
respiratoryrate	REAL		57			57 distinct values.	measured	39.0 · 60.0 · 6.0
sodium	REAL		55			55 distinct values.	measured	139.0 · 133.0 · 141.0
heartrate	REAL		163			163 distinct values.	measured	88.0 · 40.0 · 131.0
meanbp	REAL		151			151 distinct values.	measured	108.0 · 47.0 · 61.0
ph	REAL		159			159 distinct values.	measured	-1.0 · 7.38 · 7.23
hematocrit	REAL		303			303 distinct values.	measured	37.8 · 34.1 · 36.6
creatinine	REAL		357			357 distinct values.	measured	1.04 · 1.14 · 0.63
albumin	REAL		37			37 distinct values.	measured	-1.0 · 3.6 · 2.8
pao2	REAL		230			230 distinct values.	measured	-1.0 · 76.0 · 91.0
pco2	REAL		186			186 distinct values.	measured	-1.0 · 81.0 · 26.0
bun	REAL		124			124 distinct values.	measured	28.0 · 14.0 · 6.0
glucose	REAL		392			392 distinct values.	measured	61.0 · 140.0 · 82.0
bilirubin	REAL		81			81 distinct values.	measured	-1.0 · 0.5 · 0.7
fio2	REAL		28			28 distinct values.	measured	-1.0 · 60.0 · 28.0

apachepatientresult

3,676 rows · 23 columns · APACHE scores and the predicted outcomes derived from them, with the actual outcome beside each.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
apachepatientresultsid	INT	PK	3,676			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	1,838			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
physicianspeciality	TEXT		34		A	A bounded vocabulary of 34 distinct values.	measured	hospitalist · family practice · internal medicine
physicianinterventioncategory	TEXT		5		A	A bounded vocabulary of 5 distinct values.	measured	Unknown · I · III
acutephysiologyscore	INT		126			126 distinct values.	measured	23 · 43 · 25
apachescore	INT		141			The glossary declares this column as 'severity score'. APACHE IV and IVa coexist: filter on apacheversion to avoid counting the same stay twice.	glossary	-1 · 0 · 7
apacheversion	TEXT		2		A	IV or IVa. The two versions coexist in this table and their scores are not comparable; filter on one.	eICU	IV · IVa
predictedicumortality	TEXT		3,507		C	3,507 distinct values.	measured	
actualicumortality	TEXT		2		A	The glossary declares this column as 'mortality'. Discharge status is recorded as text, not as a boolean.	glossary	ALIVE · EXPIRED
predictediculos	REAL		3,491			Length of stay, in days.	eICU	0.722231399105669 · 1.37480651018718 · 3.0216711758903
actualiculos	REAL		1,559			The glossary declares this column as 'length of stay'. Columns ending in los are in days. Columns ending in offset are in minutes since ICU admission and can be negative.	glossary	0.1694 · 0.1708 · 0.1798
predictedhospitalmortality	TEXT		3,367		C	The glossary declares this column as 'severity score'. APACHE IV and IVa coexist: filter on apacheversion to avoid counting the same stay twice.	glossary	
actualhospitalmortality	TEXT		2		A	The glossary declares this column as 'mortality'. Discharge status is recorded as text, not as a boolean.	glossary	ALIVE · EXPIRED
predictedhospitallos	REAL		3,366			Length of stay, in days.	eICU	2.88170958065951 · 3.17392534799226 · 6.03262662378308
actualhospitallos	REAL		1,683			The glossary declares this column as 'length of stay'. Columns ending in los are in days. Columns ending in offset are in minutes since ICU admission and can be negative.	glossary	1.8222 · 0.8465 · 0.8063
preopmi	INT		2			2 distinct values.	measured	0 · 1
preopcardiaccath	INT		2			2 distinct values.	measured	0 · 1
ptcawithin24h	INT		2			2 distinct values.	measured	0 · 1
unabridgedunitlos	REAL		1,559			Length of stay, in days.	eICU	1.5625 · 0.5506 · 0.7784
unabridgedhosplos	REAL		1,688			Length of stay, in days.	eICU	1.8222 · 0.8465 · 0.8063
actualventdays	REAL		21			21 distinct values.	measured	1.0 · 2.0 · 3.0

column	type	key	distinct	empty	tier	what it is	source	examples
predventdays	REAL		1,005			1,005 distinct values.	measured	4.83146023372939 · 3.18891809873627 · 0.569796801077842
unabridgedactualventdays	REAL		23			23 distinct values.	measured	1.0 · 2.0 · 3.0

apachepredvar

2,205 rows · 51 columns · The predictor variables feeding the APACHE model, including chronic conditions.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
apachepredvarid	INT	PK	2,205			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,205			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
sicuday	INT		1			One value or empty throughout this extract.	measured	
saps3day1	INT		1			One value or empty throughout this extract.	measured	
saps3today	INT		1			One value or empty throughout this extract.	measured	
saps3yesterday	INT		1			One value or empty throughout this extract.	measured	
gender	INT		3			Male, Female, Unknown or empty.	eICU	1 · 0 · -1
teachtype	INT		1			A category from a small controlled list.	eICU	
region	INT		1			One value or empty throughout this extract.	measured	
bedcount	INT		54			54 distinct values.	measured	12 · 14 · 8
admitsource	INT		9			9 distinct values.	measured	8 · 1 · 4
graftcount	INT		6			6 distinct values.	measured	3 · 2 · 5
meds	INT		3			3 distinct values.	measured	0 · -1 · 1
verbal	INT		6			6 distinct values.	measured	5 · 3 · -1
motor	INT		7			7 distinct values.	measured	6 · -1 · 5
eyes	INT		5			5 distinct values.	measured	4 · -1 · 1
age	INT		77			Stored as TEXT, not a number: patients over 89 are recorded as '> 89' to de-identify them, so a numeric comparison must cast and handle that value.	eICU	87 · 76 · 34
admitdiagnosis	TEXT		240		A	A bounded vocabulary of 240 distinct values.	measured	RHYTHATR · S-CAROTEND · ODOTHER
thrombolytics	INT		2			2 distinct values.	measured	0 · 1
diedinhospital	INT		2			2 distinct values.	measured	0 · 1
aids	INT		1			One value or empty throughout this extract.	measured	
hepaticfailure	INT		2			2 distinct values.	measured	0 · 1
lymphoma	INT		2			2 distinct values.	measured	0 · 1
metastaticcancer	INT		2			2 distinct values.	measured	0 · 1
leukemia	INT		2			2 distinct values.	measured	0 · 1
immunosuppression	INT		2			2 distinct values.	measured	0 · 1
cirrhosis	INT		2			2 distinct values.	measured	0 · 1

column	type	key	distinct	empty	tier	what it is	source	examples
electivesurgery	INT		3			3 distinct values.	measured	0 · 1
activetx	INT		2			2 distinct values.	measured	0 · 1
readmit	INT		2			2 distinct values.	measured	0 · 1
ima	INT		2			2 distinct values.	measured	0 · 1
midur	INT		2			2 distinct values.	measured	0 · 1
ventday1	INT		2			2 distinct values.	measured	0 · 1
oobventday1	INT		2			2 distinct values.	measured	0 · 1
oobintubday1	INT		2			2 distinct values.	measured	0 · 1
diabetes	INT		2			2 distinct values.	measured	0 · 1
managementsystem	INT		1			One value or empty throughout this extract.	measured	
var03hspxlos	REAL		1			Length of stay, in days.	eICU	
pao2	REAL		230			230 distinct values.	measured	-1.0 · 76.0 · 91.0
fio2	REAL		28			28 distinct values.	measured	-1.0 · 60.0 · 28.0
ejectfx	REAL		14			14 distinct values.	measured	-1.0 · 35.0 · 20.0
creatinine	REAL		357			357 distinct values.	measured	1.04 · 1.14 · 0.63
dischargelocation	INT		7			7 distinct values.	measured	4 · 8 · 7
visitnumber	INT		4			4 distinct values.	measured	1 · 2 · 3
amilocation	INT		7			7 distinct values.	measured	-1 · 2 · 4
day1meds	INT		3			3 distinct values.	measured	0 · -1 · 1
day1verbal	INT		6			6 distinct values.	measured	5 · 3 · -1
day1motor	INT		7			7 distinct values.	measured	6 · -1 · 5
day1eyes	INT		5			5 distinct values.	measured	4 · -1 · 1
day1pao2	REAL		230			230 distinct values.	measured	-1.0 · 76.0 · 91.0
day1fio2	REAL		28			28 distinct values.	measured	-1.0 · 60.0 · 28.0

careplancareprovider

5,627 rows · 8 columns · Which specialty was responsible for the patient, and when.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
cplcareproviderid	INT	PK	5,627			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,132			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
careprovidersaveoffset	INT		1,157			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
providertype	TEXT		1		C	A category from a small controlled list.	eICU	
specialty	TEXT		40		A	A bounded vocabulary of 40 distinct values.	measured	family practice · obstetrics/gynecology · internal medicine
interventioncategory	TEXT		6		A	A bounded vocabulary of 6 distinct values.	measured	I · Unknown · III
managingphysician	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	Managing · Consulting
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	True · False

careplaneol

15 rows · 5 columns · End-of-life care plan entries.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
cpleolid	INT	PK	15			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	13			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
cpleolsaveoffset	INT		15			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cpleoldiscussionoffset	INT		4			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	True · False

careplangeneral

33,148 rows · 6 columns · General care plan entries, as item/value pairs.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
cplgeneralid	INT	PK	33,148			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,455			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	True · False
cplitemoffset	INT		4,424			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cplgroup	TEXT		28		A	A bounded vocabulary of 28 distinct values.	measured	Ventilation · Care Limitation · Stress Ulcer Prophylaxis
cplitemvalue	TEXT		251		A	The glossary declares this column as 'nursing'.	glossary	Spontaneous - adequate · Full therapy · Proton pump inhibitor

careplangoal

3,633 rows · 7 columns · Care plan goals, as item/value pairs.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
cplgoalid	INT	PK	3,633			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	186			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
cplgoaloffset	INT		485			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cplgoalcategory	TEXT		9		A	A bounded vocabulary of 9 distinct values.	measured	Infection/Labs · Cardiovascular · Pulmonary
cplgoalvalue	TEXT		76		A	The charted value, as text.	eICU	Normal electrolytes · Absence of sepsis · Stable Hgb and Hct
cplgoalstatus	TEXT		4		A	A status from a small controlled list.	eICU	Active · Resolved · Progressing towards goal
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	True · False

careplaninfectiousdisease

112 rows · 8 columns · Infectious-disease care plan entries.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
cplinfectid	INT	PK	112			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	64			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	True · False
cplinfectdiseaseoffset	INT		97			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
infectdiseasesite	TEXT		11		A	A bounded vocabulary of 11 distinct values.	measured	Urinary tract · Skin & Soft tissue · Lung
infectdiseaseassessment	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	Definite infection · Possible infection · Probable infection
responsetotherapy	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	No change
treatment	TEXT		4		A	A bounded vocabulary of 4 distinct values.	measured	Directed · Prophylactic · Empiric

customlab

30 rows · 7 columns · Laboratory results outside the standard set.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
customlabid	INT	PK	30			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	7			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
labotheroffset	INT		19			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
labothertypeid	INT		4			Identifier. Not a business value: nobody names one in a question.	eICU	
labothername	TEXT		19		A	A name from a controlled vocabulary.	eICU	Creatinine w Est GFR · GFR · Vitamin B12
labotherresult	TEXT		17		A	A bounded vocabulary of 17 distinct values.	measured	51.0000 · 319.0000 · 7.5000
labothervaluetext	TEXT		24		A	Free text as entered.	eICU	51 · >60 · >1000

diagnosis

24,978 rows · 7 columns · Diagnoses recorded during the stay, as a hierarchy plus an ICD-9 code.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
diagnosisid	INT	PK	24,978			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,155			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	False · True
diagnosisoffset	INT		2,661			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
diagnosisstring	TEXT		1,091		A	A pipe-separated hierarchy, from body system down to the specific diagnosis: 'renal disorder of kidney acute renal failure'.	eICU	burns/trauma dermatology cellulitis · burns/trauma dermatology pressure sore · burns/trauma dermatology pressure sore stage 4
icd9code	TEXT		501		A	ICD-9 code, sometimes several separated by commas, sometimes empty.	eICU	008.45, A04.7 · 009.1, A09 · 038.9, 348.31, R65.20, G93.41
diagnosispriority	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	Other · Major · Primary

hospital

186 rows · 4 columns · One row per hospital: region, bed count, teaching status.

column	type	key	distinct	empty	tier	what it is	source	examples
hospitalid	INT	PK	186			The hospital. Joins to hospital.hospitalid.	eICU	
numbedscategory	TEXT		5		A	The glossary declares this column as 'hospital'.	glossary	<100 · 100 - 249 · >= 500
teachingstatus	INT		2			The glossary declares this column as 'hospital'.	glossary	f · t
region	TEXT		5		A	The glossary declares this column as 'hospital'.	glossary	Midwest · Northeast · South

infusiondrug

38,256 rows · 9 columns · Continuous infusions, with rate and volume over time.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
infusiondrugid	INT	PK	38,256			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	826			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
infusionoffset	INT		10,364			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
drugname	TEXT		257		A	The drug as recorded by the hospital, including strength and form: 'ASPIRIN EC 81 MG PO TBEC'. This is why a question saying 'aspirin' has to be resolved against the value index before any query is written.	eICU	.9NS (ml/hr) · 0.9% NSS (ml/hr) · 0.9% nacl (ml/hr)
drugrate	TEXT		2,274		A	A bounded vocabulary of 2,274 distinct values.	measured	25 · 25.42 · 27.92
infusionrate	TEXT		415		A	A bounded vocabulary of 415 distinct values.	measured	16.7 · 50 · 40
drugamount	TEXT		54		A	A bounded vocabulary of 54 distinct values.	measured	900 · 50 · 20
volumeoffluid	TEXT		23		A	Identifier. Not a business value: nobody names one in a question.	eICU	
patientweight	TEXT		93		A	A bounded vocabulary of 93 distinct values.	measured	51 · 84.1 · 90.7

intakeoutput

100,466 rows · 12 columns · Fluid intake and output, charted as labelled cells.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
intakeoutputid	INT	PK	100,466			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,185			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
intakeoutputoffset	INT		20,544			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
intaketotal	REAL		3,964			3,964 distinct values.	measured	0 · 120 · 100
outputtotal	REAL		1,047			1,047 distinct values.	measured	0 · 75 · 1
dialysistotal	REAL		84			84 distinct values.	measured	0 · -2000 · -1800
nettotal	REAL		5,361			5,361 distinct values.	measured	0 · 120 · 100
intakeoutputentryoffset	INT		20,028			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cellpath	TEXT		775		A	A slash- or pipe-separated path naming where the value sits in the charting hierarchy.	eICU	
celllabel	TEXT		740		A	The glossary declares this column as 'intake output'.	glossary	Bodyweight (lb) · Bodyweight (kg) · P.O.
cellvaluenumeric	REAL		5,613			The glossary declares this column as 'intake output'.	glossary	159.8 · 72.5 · 120
cellvaluetext	TEXT		5,769		B	Free text as entered.	eICU	159.8 · 72.5 · 120

lab

434,660 rows · 10 columns · Laboratory results: name, numeric value, unit, time.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
labid	INT	PK	434,660			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,444			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
labresultoffset	INT		21,247			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
labtypeid	REAL		6			Identifier. Not a business value: nobody names one in a question.	eICU	
labname	TEXT		147		A	The name of the laboratory test, e.g. 'bedside glucose', 'potassium'.	eICU	-bands · -basos · -eos
labresult	REAL		5,562			The numeric result. `labresulttext` holds the same value as written.	eICU	38.3 · 181 · 4.86
labresulttext	TEXT		7,669		B	Free text as entered.	eICU	38.3 · 181 · 4.86
labmeasurenamesystem	TEXT		32		A	The glossary declares this column as 'lab test'. labresult is numeric and queryable; labresulttext is its text form and should be avoided in filters.	glossary	% · K/mcL · M/mcL
labmeasurenameinterface	TEXT		342		A	A bounded vocabulary of 342 distinct values.	measured	% · k/mm cu · m/mm cu
labresultrevisedoffset	INT		24,633			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	

medication

75,604 rows · 15 columns · Medication orders: drug, dose, route, frequency, start and stop.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
medicationid	INT	PK	75,604			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	1,857			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
drugorderoffset	INT		11,643			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
drugstartoffset	INT		16,383			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
drugivadmixture	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	No · Yes
drugordercancelled	TEXT		2		A	A bounded vocabulary of 2 distinct values.	measured	No · Yes
drugname	TEXT		1,402		A	The drug as recorded by the hospital, including strength and form: 'ASPIRIN EC 81 MG PO TBEC'. This is why a question saying 'aspirin' has to be resolved against the value index before any query is written.	eICU	0.9% NaCl infusion · 0.9%NaCl 1,000 mL · 1 EACH VIAL : ALTEPLASE 2 MG IJ SOLR
drughiclseqno	INT		1,028			1,028 distinct values.	measured	2812 · 182 · 1820
dosage	TEXT		633		A	The glossary declares this column as 'dosage'.	glossary	5 3 · 15 3 · 81 3
routeadmin	TEXT		377		A	The glossary declares this column as 'dosage'.	glossary	.ROUTE · AEROSOL · Apply externally
frequency	TEXT		528		A	The glossary declares this column as 'dosage'.	glossary	Once PRN · Daily · Q6H SCH
loadingdose	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	0 mg · 150 ml
prn	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	No · Yes
drugstopoffset	INT		16,016			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
gtc	INT		42			42 distinct values.	measured	0 · 38 · 17

microlab

342 rows · 7 columns · Microbiology cultures: site, organism, antibiotic sensitivity.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
microlabid	INT	PK	342			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	64			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
culturetakenoffset	INT		144			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
culturesite	TEXT		13		A	The glossary declares this column as 'microbiology'.	glossary	Sputum, Expectorated · Bronchial Lavage · Urine, Catheter Specimen
organism	TEXT		16		A	The glossary declares this column as 'microbiology'.	glossary	mixed flora · gram negative rods · gram positive cocci
antibiotic	TEXT		30		A	The glossary declares this column as 'microbiology'.	glossary	meropenam · gentamicin · ertapenem
sensitivitylevel	TEXT		4		A	The glossary declares this column as 'microbiology'.	glossary	Sensitive · Resistant · Intermediate

note

24,758 rows · 8 columns · Clinical notes, stored as path/value pairs rather than free prose.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
noteid	INT	PK	24,758			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,257			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
noteoffset	INT		2,327			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
noteenteredoffset	INT		2,366			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
notetype	TEXT		16		A	A category from a small controlled list.	eICU	Comprehensive Progress · Brief Progress · Admission
notepath	TEXT		360		A	A path naming where this value sits in the charting hierarchy.	eICU	
notevalue	TEXT		280		A	The content of the note field named by `notepath`.	eICU	Include Past Medical History · System View · Include Rx
notetext	TEXT		283		A	Free text as entered.	eICU	Include Past Medical History · SystemView · Include Rx

nurseassessment

91,589 rows · 8 columns · Nursing assessments, as attribute/value pairs.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
nurseassessid	INT	PK	91,589			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	122			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
nurseassessoffset	INT		1,623			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
nurseassessentryoffset	INT		1,684			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cellattributepath	TEXT		81		A	A path naming where this value sits in the charting hierarchy.	eICU	
celllabel	TEXT		20		A	The glossary declares this column as 'nursing'.	glossary	Edema · Secretions · Pacemaker/AICD
cellattribute	TEXT		73		A	A bounded vocabulary of 73 distinct values.	measured	Edema · Secretions · Pacemaker/AICD
cellattributevalue	TEXT		247		A	The charted value, as text.	eICU	generalized · minimal · thin

nursecare

42,080 rows · 8 columns · Nursing care items, as attribute/value pairs.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
nursecareid	INT	PK	42,080			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	122			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
celllabel	TEXT		10		A	The label of the charted item.	eICU	Hygiene/ADLs · Equipment · Treatments
nursecareoffset	INT		2,093			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
nursecareentryoffset	INT		2,082			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
cellattributepath	TEXT		19		A	A path naming where this value sits in the charting hierarchy.	eICU	
cellattribute	TEXT		19		A	A bounded vocabulary of 19 distinct values.	measured	Hygiene/ADLs · Equipment · Treatments
cellattributevalue	TEXT		133		A	The charted value, as text.	eICU	ADLs assist · oral care · air mattress

nursecharting

1,477,163 rows · 8 columns · The nursing flowsheet — the largest table here. Cell type, label and value, one row per charted item.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
nursingchartid	INT	PK	1,477,163			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,395			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
nursingchartoffset	INT		37,374			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
nursingchartentryoffset	INT		36,860			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
nursingchartcelltypecategory	TEXT		7		A	A bounded vocabulary of 7 distinct values.	measured	Other Vital Signs and Infusions · Vital Signs · Scores
nursingchartcelltypevaluelabel	TEXT		60		A	The label of the charted item.	eICU	Eye, Ear, Nose, Throat Assessment · Gastrointestinal Assessment · Pain Assessment
nursingchartcelltypevaluename	TEXT		49		A	The glossary declares this column as 'nursing'.	glossary	Value · Respiratory Rate · O2 Saturation
nursingchartvalue	TEXT		2,765		A	The charted value, as text.	eICU	WDL · X · 15

pasthistory

12,109 rows · 8 columns · Medical history recorded on admission, as a hierarchy.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
pasthistoryid	INT	PK	12,109			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,211			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
pasthistoryoffset	INT		1,244			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
pasthistoryenteredoffset	INT		1,267			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
pasthistorynotetype	TEXT		6		A	A category from a small controlled list.	eICU	Comprehensive Progress · Past History Edit · Admission
pasthistorypath	TEXT		190		A	The glossary declares this column as 'medical history'.	glossary	
pasthistoryvalue	TEXT		174		A	The glossary declares this column as 'medical history'.	glossary	No Health Problems · Performed · medication dependent
pasthistoryvaluetext	TEXT		174		A	Free text as entered.	eICU	NoHealthProblems · Performed · medication dependent

patient

2,520 rows · 29 columns · One row per ICU stay: demographics, admission and discharge. The centre of the schema — every other table joins here.

joins hospitalid -> hospital.hospitalid

column	type	key	distinct	empty	tier	what it is	source	examples
patientunitstayid	INT	PK	2,520			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
patienthealthsystemstayid	INT		2,174			One hospital stay. A person may have several; each may contain several ICU stays.	eICU	
gender	TEXT		3		A	Male, Female, Unknown or empty.	eICU	Female · Male
age	TEXT		77		A	Stored as TEXT, not a number: patients over 89 are recorded as '> 89' to de-identify them, so a numeric comparison must cast and handle that value.	eICU	15 · 16 · 17
ethnicity	TEXT		7		A	Self-reported, seven categories including an empty one.	eICU	African American · Asian · Caucasian
hospitalid	INT	FK	186			The hospital. Joins to hospital.hospitalid.	eICU	
wardid	INT		292			The ward inside the hospital. No separate ward table exists.	eICU	
apacheadmissiondx	TEXT		237		A	The APACHE admission diagnosis, one string from a controlled list.	eICU	Rhythm disturbance (atrial, supraventricular) · Endarterectomy, carotid · Overdose, other toxin, poison or drug
admissionheight	REAL		143			Centimetres at ICU admission.	eICU	157.5 · 167 · 172.7
hospitaladmittime24	TEXT		1,339		A	Time of day, HH:MM, as a 24-hour clock. No date.	eICU	23:36:00 · 20:46:00 · 01:44:00
hospitaladmitoffset	INT		1,263			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
hospitaladmitsource	TEXT		14		A	Where the patient came from when entering the hospital.	eICU	Operating Room · Emergency Department · Floor
hospitaldischargeyear	INT		2			Year only, the single unshifted time field.	eICU	2014 · 2015
hospitaldischargestime24	TEXT		715		A	Time of day, HH:MM, as a 24-hour clock. No date.	eICU	19:20:00 · 17:05:00 · 21:05:00
hospitaldischargeoffset	INT		2,324			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
hospitaldischargelocation	TEXT		9		A	Where the patient went: Home, Skilled Nursing Facility, Death, and so on.	eICU	Home · Other Hospital · Other
hospitaldischargestatus	TEXT		3		A	Alive or Expired at hospital discharge. This is the mortality outcome.	eICU	Alive · Expired
unittype	TEXT		8		A	Type of ICU: Med-Surg ICU, MICU, CCU-CTICU, Neuro ICU, and so on.	eICU	CCU-CTICU · CSICU · CTICU
unitadmittime24	TEXT		1,148		A	Time of day, HH:MM, as a 24-hour clock. No date.	eICU	13:14:00 · 23:44:00 · 20:47:00
unitadmitsource	TEXT		14		A	Where the patient came from when entering the ICU.	eICU	ICU to SDU · Emergency Department · Operating Room
unitvisitnumber	INT		5			5 distinct values.	measured	2 · 1 · 3

column	type	key	distinct	empty	tier	what it is	source	examples
unitstaytype	TEXT		4		A	admit, readmit, stepdown/other, or transfer.	eICU	stepdown/other · admit · readmit
admissionweight	REAL		896			Kilograms at ICU admission.	eICU	46.5 · 77.5 · 60.3
dischargeweight	REAL		802			Kilograms at ICU discharge.	eICU	45 · 79.4 · 60.7
unitdischargetime24	TEXT		978		A	Time of day, HH:MM, as a 24-hour clock. No date.	eICU	18:58:00 · 13:14:00 · 10:00:00
unitdischargeoffset	INT		2,017			The glossary declares this column as 'length of stay'. Columns ending in los are in days. Columns ending in offset are in minutes since ICU admission and can be negative.	glossary	
unitdischargelocation	TEXT		16		A	The glossary declares this column as 'discharge'.	glossary	Home · Step-Down Unit (SDU) · Floor
unitdischargestatus	TEXT		3		A	Alive or Expired at ICU discharge.	eICU	Alive · Expired
uniquepid	TEXT		1,841		C	The person. One patient may have several hospital stays, so this is the id to COUNT DISTINCT when a question asks how many patients.	eICU	

physicalexam

84,058 rows · 6 columns · Physical examination findings, as path/value pairs.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
physicalexamid	INT	PK	84,058			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,217			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
physicalexamoffset	INT		1,271			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
physicalexampath	TEXT		310		A	The glossary declares this column as 'physical exam'.	glossary	
physicalexamvalue	TEXT		215		A	The glossary declares this column as 'physical exam'.	glossary	scored · Performed - Structured · Admission
physicalexamtext	TEXT		3,460		A	Free text as entered.	eICU	scored · Performed - Structured · 86.2

respiratorycare

5,436 rows · 34 columns · Ventilator settings and respiratory care events.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
respcareid	INT	PK	5,436			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	395			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
respcaresetatusoffset	INT		3,580			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
currenthistoryseqnum	INT		243			243 distinct values.	measured	2 · 1 · 3
airwaytype	TEXT		5		A	The glossary declares this column as 'ventilation'.	glossary	Tracheostomy · Oral ETT · Other
airwaysize	TEXT		5		A	A bounded vocabulary of 5 distinct values.	measured	8.0 · 7.5 · 7.0
airwayposition	TEXT		26		A	A bounded vocabulary of 26 distinct values.	measured	23 · 22 · 21
cuffpressure	REAL		12			12 distinct values.	measured	30 · 28 · 20
ventstartoffset	INT		261			The glossary declares this column as 'ventilation'.	glossary	
ventendoffset	INT		1			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
priorventstartoffset	INT		209			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
priorventendoffset	INT		265			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
apneaparams	TEXT		5		A	A bounded vocabulary of 5 distinct values.	measured	20 · 30 · set
lowexhmvlimit	REAL		29			29 distinct values.	measured	2.5 · 2.3 · 2
hiexhmvlimit	REAL		20			20 distinct values.	measured	40 · 24 · 50
lowexhtvlimit	REAL		15			15 distinct values.	measured	250 · 170 · 100
hipeakpreslimit	REAL		14			14 distinct values.	measured	35 · 40 · 50
lowpeakpreslimit	REAL		10			10 distinct values.	measured	3 · 8 · 5
hirespratelimit	REAL		13			13 distinct values.	measured	45 · 40 · 30
lowrespratelimit	REAL		13			13 distinct values.	measured	5 · 18 · 17
sighpreslimit	REAL		1			One value or empty throughout this extract.	measured	
lowironoxlimit	REAL		1			One value or empty throughout this extract.	measured	
highironoxlimit	REAL		1			One value or empty throughout this extract.	measured	
meanairwaypreslimit	REAL		1			One value or empty throughout this extract.	measured	

column	type	key	distinct	empty	tier	what it is	source	examples
peeplimit	REAL		12			12 distinct values.	measured	25 · 13 · 16
cpaplimit	REAL		9			9 distinct values.	measured	2 · 5 · 8
setapneainterval	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	20 · 30
setapneatv	TEXT		15		A	A bounded vocabulary of 15 distinct values.	measured	600 · 700 · 450
setapneaippeephhigh	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	450 · 500
setapnearr	TEXT		10		A	A bounded vocabulary of 10 distinct values.	measured	12 · 16 · 20
setapneapeakflow	TEXT		11		A	A bounded vocabulary of 11 distinct values.	measured	50 · 80 · 60
setapneainsptime	TEXT		3		C	3 distinct values.	measured	
setapneaie	TEXT		1		C	One value or empty throughout this extract.	measured	
setapneafio2	TEXT		6		A	A bounded vocabulary of 6 distinct values.	measured	100 · 50 · 60

respiratorycharting

176,089 rows · 7 columns · The respiratory flowsheet, charted like nursecharting.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
respchartid	INT	PK	176,089			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	1,302			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
respchartoffset	INT		20,904			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
respchartentryoffset	INT		20,173			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
respcharttypecat	TEXT		3		A	A bounded vocabulary of 3 distinct values.	measured	respFlowSettings · respFlowCareData · respFlowPtVentData
respchartvaluelabel	TEXT		172		A	The glossary declares this column as 'ventilation'.	glossary	LPM O2 · FiO2 · Vent Rate
respchartvalue	TEXT		2,662		A	The charted value, as text.	eICU	1 · 80 · 6

treatment

38,290 rows · 5 columns · Treatments given, as a hierarchy.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
treatmentid	INT	PK	38,290			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	1,910			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
treatmentoffset	INT		2,399			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
treatmentstring	TEXT		1,199		A	A pipe-separated hierarchy of the treatment given.	eICU	burns/trauma burns analgesics · burns/trauma burns anesthetics ketamine · burns/trauma skin care dressing change
activeupondischarge	TEXT		2		A	True if the item was still active when the patient left.	eICU	False · True

vitalaperiodic

274,088 rows · 13 columns · Vital signs recorded intermittently, one row per measurement time.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
vitalaperiodicid	INT	PK	274,088			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,331			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
observationoffset	INT		28,736			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
noninvasivesystolic	REAL		241			241 distinct values.	measured	171.0 · 153.0 · 176.0
noninvasivediastolic	REAL		220			220 distinct values.	measured	90.0 · 78.0 · 87.0
noninvasivemean	REAL		222			The glossary declares this column as 'vital signs'. vitalaperiodic is sampled every 5 minutes and holds 12 million rows: always filter on a stay and aggregate.	glossary	116.0 · 103.0 · 107.0
paop	REAL		27			27 distinct values.	measured	8.0 · 11.0 · 14.0
cardiacoutput	REAL		257			257 distinct values.	measured	7.0 · 5.0 · 4.8000002
cardiacinput	REAL		185			185 distinct values.	measured	2.9300001 · 2.0899999 · 2.01
svr	REAL		1,667			1,667 distinct values.	measured	410.0 · 809.0 · 348.0
svri	REAL		1,746			1,746 distinct values.	measured	1911.0 · 2523.0 · 2508.0
pvr	REAL		99			99 distinct values.	measured	137.0 · 96.0 · 83.0
pvri	REAL		119			119 distinct values.	measured	328.0 · 229.0 · 199.0

vitalperiodic

1,634,960 rows · 19 columns · Vital signs recorded automatically, typically every five minutes. The largest table by row count.

joins patientunitstayid -> patient.patientunitstayid

column	type	key	distinct	empty	tier	what it is	source	examples
vitalperiodicid	INT	PK	1,634,960			Identifier. Not a business value: nobody names one in a question.	eICU	
patientunitstayid	INT	FK	2,375			One ICU stay. The join key of the whole database: 28 of the 31 tables carry it.	eICU	
observationoffset	INT		51,492			Minutes since ICU admission; a negative value means before admission. Never a date: the export is de-identified by shifting every timestamp.	eICU	
temperature	REAL		666			The glossary declares this column as 'vital signs'. vitalperiodic is sampled every 5 minutes and holds 12 million rows: always filter on a stay and aggregate.	glossary	35.8 · 36.4 · 37.2
sao2	INT		100			The glossary declares this column as 'vital signs'. vitalperiodic is sampled every 5 minutes and holds 12 million rows: always filter on a stay and aggregate.	glossary	97 · 96 · 98
heartrate	INT		198			The glossary declares this column as 'vital signs'. vitalperiodic is sampled every 5 minutes and holds 12 million rows: always filter on a stay and aggregate.	glossary	82 · 76 · 84
respiration	INT		150			The glossary declares this column as 'vital signs'. vitalperiodic is sampled every 5 minutes and holds 12 million rows: always filter on a stay and aggregate.	glossary	30 · 22 · 29
cvp	INT		425			425 distinct values.	measured	19 · 223 · 222
etco2	INT		116			116 distinct values.	measured	29 · 31 · 30
systemicsystolic	INT		317			317 distinct values.	measured	113 · 111 · 117
systemicdiastolic	INT		311			311 distinct values.	measured	45 · 36 · 46
systemicmean	INT		366			366 distinct values.	measured	64 · 54 · 65
pasystolic	INT		101			101 distinct values.	measured	19 · 37 · 33
padiastolic	INT		83			83 distinct values.	measured	11 · 22 · 20
pamean	INT		101			101 distinct values.	measured	11 · 28 · 25
st1	REAL		703			703 distinct values.	measured	0.0 · -0.1 · -0.30000001
st2	REAL		802			802 distinct values.	measured	-1.7 · -0.69999999 · -1.0
st3	REAL		966			966 distinct values.	measured	-1.7 · -0.69999999 · -1.0
icp	INT		83			83 distinct values.	measured	8 · 1 · 7