

MBS-fast Manual

August 12, 2026

Contents

1	Build	2
1.1	Requirements	2
1.2	CPU build	2
1.3	GPU build	2
1.4	EPYC Zen5, AVX-512, and AVX2	3
1.5	Legacy root Makefile	4
2	Quick runs	4
3	Physical model	4
3.1	Pipeline	4
3.2	Ray Jones matrices	5
3.3	Dyadic rotation into the scattering basis	5
3.4	Kirchhoff diffraction integral	6
3.5	Coherent and incoherent Mueller accumulation	6
3.6	Orientation averaging	7
3.7	Scattering-angle weights	7
4	Particles and sizes	7
4.1	Native particle file and geometry export	8
5	Orientation grids	9
5.1	Symmetry-reduced SO(3) quadrature	10
6	Scattering grids	11
6.1	Diffraction-limit and latitude-phi grids	12
6.2	Unified convergence criterion	12
6.3	Adaptive configuration file	13
6.4	Why column symmetry does not divide Nphi	13
7	Beam and trace cutoffs	13
7.1	Coherent presets	13
7.2	Individual controls	14
8	GPU and multi-GPU	15
8.1	CUDA backend	15
8.2	FFT phi compression and error control	15
8.3	Why the GPU version is faster	16
8.4	Atomic and no-atomic GPU accumulation	16
8.5	Automatic CUDA tracing profile	17
8.6	Multi-size scans	18
9	All flags	19
9.1	Method, particle, and physical parameters	19
9.2	Orientation flags	19
9.3	Scattering grid and acceleration flags	20
9.4	Output, diagnostics, and legacy flags	21

MBS-fast computes light scattering by non-spherical particles with geometrical ray tracing plus Physical Optics (PO) diffraction. The code is optimized for CPU OpenMP/MPI runs and CUDA GPU diffraction runs. This manual describes the current command line interface, build targets, grids, multi-GPU scans, and the main diffraction/Jones/Mueller formulas used by the implementation.

1 Build

1.1 Requirements

Component	Required for	Notes
GCC >= 9 or Clang >= 14	CPU and host CUDA code	GCC is the normal path on EPYC
OpenMP	CPU parallelism	GCC links with libgomp
MPI	cpu/ split build	mpicxx is used when available
CUDA toolkit	gpu/ split build	nvcc, libcudart, libcufft
NVIDIA driver	GPU runs	Must support the requested sm_XX binary

The split build is the recommended build path. CPU objects are kept under `cpu/build/`; CUDA objects are kept under `gpu/build/`. The shared physics code remains in `src/`.

1.2 CPU build

MPI + OpenMP CPU binary

```
make -C cpu -j
```

Run one MPI rank with 64 OpenMP threads

```
OMP_NUM_THREADS=64 cpu/bin/mbs_po_mpi --po -p 1 125.9 78.09 \
  --ri 1.3116 0 -w 0.532 -n 12 --oldauto 2 \
  --grid 0 180 600 180 --threads 64 --close -o out_cpu
```

Run four MPI ranks, each with 16 OpenMP threads

```
mpirun -np 4 cpu/bin/mbs_po_mpi --po -p 1 125.9 78.09 \
  --ri 1.3116 0 -w 0.532 -n 12 --oldauto 2 \
  --grid 0 180 600 180 --threads 16 --close -o out_cpu_mpi
```

Debug help build:

```
make -C cpu debug
```

```
cpu/bin/mbs_po_mpi_debug --help-debug
```

1.3 GPU build

Default/reference GPU binary: FP64 with precise math

```
PATH=/usr/local/cuda/bin:$PATH make -C gpu -j
```

Explicit variants

```
make -C gpu fp32 -j # gpu/bin/mbs_po_gpu_float
make -C gpu fp64 -j # gpu/bin/mbs_po_gpu_double
make -C gpu fp32_fast -j # gpu/bin/mbs_po_gpu_float_fast
make -C gpu fp64_fast -j # gpu/bin/mbs_po_gpu_double_fast
```

Target	Binary	CUDA precision	Fast math	Typical use
<code>make -C gpu or make -C gpu fp64</code>	<code>gpu/bin/mbs_po_gpu_double</code>	FP64	no	Numerical reference and production default
<code>make -C gpu fp32</code>	<code>gpu/bin/mbs_po_gpu_float</code>	FP32	no	Calibrated FP32 throughput
<code>make -C gpu fp32_fast</code>	<code>gpu/bin/mbs_po_gpu_float_fast</code>	FP32	yes	Experimental profile; benchmark after validation
<code>make -C gpu fp64_fast</code>	<code>gpu/bin/mbs_po_gpu_double_fast</code>	FP64	yes	FP64 throughput after validation
<code>make -C gpu double_debug</code>	<code>gpu/bin/mbs_po_gpu_double_debug</code>	FP64	yes	Debug help and diagnostics

FP32 applies to diffraction-beam storage, Jones sums, and Mueller output. Visibility/topology tracing, optical paths, absorption, cancellation-prone polygon moments, and critical phase trigonometry remain FP64. `-/-version` reports the storage, critical-phase, math, and target architecture profile.

Verify every rebuilt binary before starting a queue:

```
gpu/bin/mbs_po_gpu_double --version # fp64-diffraction-storage ... precise-math
gpu/bin/mbs_po_gpu_float --version # fp32-diffraction-storage ... precise-math
```

CUDA host compilation requires exactly one FP32/FP64 profile. A binary that reports unknown-precision is stale or was built outside the supported profiles and must not be used for production calculations.

On an RTX 3080 Ti, a representative absorbing nonconvex test ($k_{\text{eq}} = 20$, 64 SO(3) orientations, $N_\phi = 720$, $N_\theta = 360$) gave the following medians:

Profile	Time	Speedup over FP64	Mueller error against FP64
Precise FP64	4.92 s	1.00	reference
Precise mixed FP32	3.45 s	1.43	global $L_2 = 1.00 \times 10^{-6}$
FP32 with fast math	3.63 s	1.36	global $L_2 = 1.02 \times 10^{-6}$

The precise mixed-FP32 binary is therefore the recommended consumer-GPU profile after validation on the target particle and size range. Fast math is not enabled automatically: in this measured case it was slightly slower and did not improve accuracy. Final reference points and numerically sensitive absorbing or deep nonconvex cases should still be checked in FP64.

The GPU split build enables CUDA diffraction by default. `--gpu` is accepted but optional. Use `--cpu` only when you deliberately want the CPU diffraction backend from a GPU-capable binary.

The Makefile detects the GPU compute capability with `nvidia-smi`. Override when needed:

```
# Ampere, e.g. RTX 3080 Ti
make -C gpu fp32 -j GPU_ARCH=86
```

```
# Ada, e.g. RTX 4070
make -C gpu fp32 -j GPU_ARCH=89
```

1.4 EPYC Zen5, AVX-512, and AVX2

`scripts/detect_arch_flags.sh` is used by the Makefiles through `ARCH_FLAGS`. On a native machine, the safest high-performance option is usually:

```
make -C cpu clean
make -C cpu -j ARCH_FLAGS="-march=native -mtune=native"

make -C gpu clean
make -C gpu double_fast -j ARCH_FLAGS="-march=native -mtune=native"
```

For named AMD targets:

CPU target	GCC/Clang flags	Notes
EPYC Zen2	ARCH_FLAGS="-march=znver2 -mtune=znver2"	AVX2/FMA path
EPYC Zen3	ARCH_FLAGS="-march=znver3 -mtune=znver3"	AVX2/FMA path
EPYC Zen4	ARCH_FLAGS="-march=znver4 -mtune=znver4"	AVX-512 capable on GCC versions that support it
EPYC Zen5	ARCH_FLAGS="-march=znver5 -mtune=znver5"	Use with a compiler that knows znver5
Portable AVX2	ARCH_FLAGS="-O3 -mavx2 -mfma"	Runs on AVX2 machines
Explicit AVX-512	ARCH_FLAGS="-O3 -mavx512f -mavx512dq -mavx512cd -mavx512bw -mavx512vl"	Use only on machines that support these flags

There is no GCC/Clang option named AVX12. If the intended target is Zen5 with AVX-512, use `-march=znver5` when the compiler supports it. If the compiler is older, either upgrade GCC/Clang or use the explicit AVX-512 flags above after checking `lscpu | grep avx512`.

1.5 Legacy root Makefile

The root Makefile still exists for compatibility:

```
make                                # bin/mbs_po, CPU
make gpu_double_fast               # delegates to gpu/double_fast
make gpu_float_fast                # delegates to gpu/float_fast
make USE_CUDA=1                   # legacy single-tree CUDA build
```

Prefer the split `cpu/` and `gpu/` builds for normal work.

2 Quick runs

```
# GPU double, oldauto orientation grid, full 0..180 degree output
gpu/bin/mbs_po_gpu_double_fast --po -p 1 125.9 78.09 \
  --ri 1.3116 0 -w 0.532 -n 12 --oldauto 2 \
  --grid 0 180 600 180 --threads 64 --close -o hex_gpu_double

# Same run, force CPU backend from the GPU binary
gpu/bin/mbs_po_gpu_double_fast --po --cpu -p 1 125.9 78.09 \
  --ri 1.3116 0 -w 0.532 -n 12 --oldauto 2 \
  --grid 0 180 600 180 --threads 64 --close -o hex_cpu_from_gpu_bin

# File particle scaled by equivalent size parameter
gpu/bin/mbs_po_gpu_float_fast --po --pf particle.dat --k_eq 58.81 \
  --ri 1.6 0.002 -w 1.064 -n 14 --oldauto 2 --pole \
  --grid 0 180 600 180 --threads 16 --close -o particle_keq

# Two-point forward/backward check
gpu/bin/mbs_po_gpu_double_fast --po -p 1 125.9 78.09 \
  --ri 1.3116 0 -w 0.532 -n 1 --oldauto 2 --pole \
  --grid 0 180 600 1 --threads 64 --close -o check_0_180
```

3 Physical model

3.1 Pipeline

Stage	Main code path	Result
Particle setup	src/particle, src/main.cpp	Facets, normals, area, volume, symmetry
Geometrical tracing	src/scattering, src/tracer, src/Splitting.cpp	Output beams with direction, polygon, area, optical path, Jones matrix
PO diffraction	HandlerPO::ApplyDiffraction*, Handler::DiffractIncline*, CUDA equivalents	Far-field Jones amplitude per beam and direction
Coherent sum	HandlerPO::AddToMueller, GPU fused Mueller kernels	Sum Jones matrices over beams for one orientation
Mueller conversion	src/math/Mueller.cpp	4x4 Mueller matrix
Orientation average	HandlerPOTotal, TracerPOTotal	Final randomly oriented Mueller matrix

3.2 Ray Jones matrices

Each traced beam carries a 2x2 complex Jones matrix `beam.J`. Refraction and reflection multiply it by Fresnel coefficients in `Splitting.cpp`. The two polarization channels are the local vertical/horizontal basis of the incident and outgoing ray.

For a beam with local Jones matrix

$$J = \begin{bmatrix} J_{vv} & J_{vh} \\ J_{hv} & J_{hh} \end{bmatrix},$$

the code treats J as the coherent amplitude transform accumulated along the ray path. Cutoffs based on $|J|^2$, area, or $|J|^2 \cdot \text{area}$ can remove weak beams before expensive diffraction.

3.3 Dyadic rotation into the scattering basis

Before adding a beam to a detector direction, the beam-local Jones matrix must be expressed in the detector polarization basis. `HandlerPO::RotateJones` and `RotateJonesFast` build this 2x2 rotation/projection using dot products between:

Vector	Meaning
<code>beam.Direction()</code>	Beam propagation direction after tracing
<code>direction</code>	Requested far-field scattering direction
<code>vf</code>	Forward reference direction
info polarization vectors	Precomputed beam polarization basis

The optimized CPU and CUDA paths use the transversality of $\mathbf{v}_f$ and $\mathbf{v}_t = \mathbf{v}_f \times \mathbf{s}$ to avoid constructing longitudinally projected temporary vectors. With $\mathbf{X}_T = \mathbf{n} \times \mathbf{D}_T$ and $\mathbf{X}_P = \mathbf{n} \times \mathbf{D}_P$, the same rotation is evaluated as

$$\mathbf{R}_{\text{out}} = \frac{1}{2} \begin{pmatrix} \mathbf{X}_T \cdot \mathbf{v}_t - \mathbf{N}_T \cdot \mathbf{v}_f & \mathbf{X}_P \cdot \mathbf{v}_t - \mathbf{N}_P \cdot \mathbf{v}_f \\ \mathbf{X}_T \cdot \mathbf{v}_f + \mathbf{N}_T \cdot \mathbf{v}_t & \mathbf{X}_P \cdot \mathbf{v}_f + \mathbf{N}_P \cdot \mathbf{v}_t \end{pmatrix}.$$

The omitted term is parallel to $\mathbf{s}$, whereas both output basis vectors are perpendicular to $\mathbf{s}$. This scalar-triple-product reduction is exact, not a polarization approximation, and removes two temporary vectors and their longitudinal projections from every beam/detector-direction contribution.

The effective far-field Jones contribution has the structure used in `ApplyDiffractionFast`:

$$J_{\text{beam}}(\theta, \phi) = F_{\text{edge}}(\theta, \phi) * R_{\text{out}}(\theta, \phi) * F_{\text{n}}(\theta, \phi)$$

where:

Factor	Code	Meaning
<code>F_edge</code>	<code>DiffractInclineFast</code> , <code>DiffractIncline</code> , <code>DiffractInclineAbs</code>	Scalar Kirchhoff edge diffraction integral for the beam polygon
<code>R_out</code>	<code>RotateJones</code> or <code>KarczewskiJones</code>	Jones-basis rotation/projection from beam coordinates to scattering coordinates

Factor	Code	Meaning
F_n	ComputeFnJones	Fresnel/Jones correction for the beam normal and direction

The optional `--karczewski` flag replaces the default rotation with the Karczewski polarization matrix. The code comments note that M11 is unchanged because the Frobenius norm is preserved, while polarization-sensitive elements can change.

The transverse norms are evaluated with `exttthypot`, and each basis is validated before normalization. A degenerate pole configuration or a non-finite result falls back to the default `extttRotateJones`. This safeguard prevents `extttNaN` values but does not turn the incomplete GOAD convention implementation into a physical reference.

3.4 Kirchhoff diffraction integral

For each traced output beam the illuminated aperture is a polygon. The PO far field is evaluated by a boundary/edge form of the Kirchhoff integral. In code this lives in:

Function	Use
Handler::DiffractIncline	CPU scalar non-absorbing edge integral
Handler::DiffractInclineFast	CPU optimized edge integral with precomputed edge data
Handler::DiffractInclineAbs	Absorbing variant
GpuDiffraction.cu kernels	CUDA implementation of the same aperture/edge calculation

Conceptually the scalar diffraction factor is the aperture phase integral

$$F(q) = \text{integral}_A \exp(i k q \cdot r) dA,$$

where A is the projected beam polygon, $k = 2\pi/\lambda$, and q is the difference between the outgoing beam direction and the requested far-field direction. The implementation evaluates the polygon integral through its edges to avoid sampling the aperture area directly. For an edge from vertex a to b , the contribution is a stable complex exponential difference divided by the corresponding phase denominator; special small-denominator branches use sinc-like limits.

The GPU and CPU branches should use the same geometry, phase convention, and theta grid. Differences normally come from precision (float vs double), fast math, FFT interpolation, atomics/reduction order, and special pole or endpoint handling.

3.5 Coherent and incoherent Mueller accumulation

Default PO mode is coherent per orientation:

```
J_total(theta, phi) = sum_beams J_beam(theta, phi)
M(theta, phi)       = Mueller(J_total(theta, phi))
```

With `--incoh`, the conversion happens before beam summation:

```
M(theta, phi) = sum_beams Mueller(J_beam(theta, phi))
```

The Jones-to-Mueller conversion is implemented in `src/math/Mueller.cpp`. For Jones elements $S1..S4$, the code computes the standard 4×4 real Mueller matrix from bilinear products such as $|S1|^2$, $|S2|^2$, $\text{Re}(S1 \text{ conj}(S2))$, and $\text{Im}(S1 \text{ conj}(S2))$.

The coherent sum is limited to ray paths of one particle at one fixed orientation. For a randomly and independently oriented ensemble, the code first forms `Mueller(J_total)` for each orientation and then averages Mueller matrices with orientation weights. Jones matrices from distinct orientations cannot be summed without particle positions and relative incident phases. The deprecated `--coherent-orientations` option is therefore disabled; its previous implementation was effectively the ordinary incoherent orientation average.

This single-particle model does not reproduce coherent backscattering of a particulate medium caused by interference of reciprocal multiple scattering paths between distinct particles. That problem requires a multi-particle solver with particle positions and inter-particle field propagation.

--beam-cutoff* and --trace-cutoff* remove amplitudes before coherent summation and can bias cross terms even when the removed intensities are small. Validate backscatter with --cutoff-profile safe or --cutoff-profile off.

3.6 Orientation averaging

For randomly oriented particles, each orientation produces a Mueller matrix on the scattering grid. HandlerP0Total and TracerP0Total average orientations with the beta/gamma weights selected by the orientation mode. At beta poles, --pole uses one gamma value because all gamma rotations are equivalent at the exact pole. In current code, --pole keeps beta endpoints instead of midpoint beta sampling, so the beta pole is actually present in the grid.

3.7 Scattering-angle weights

Uniform theta grids output $N_{\text{th}} + 1$ rows. $2\pi \cdot d\cos$ is the solid-angle ring weight assigned to the theta row:

$$d\Omega(\theta_j) = 2\pi * (\cos(\theta_{\text{left}}) - \cos(\theta_{\text{right}}))$$

For endpoint rows the interval is half-width and clipped to the requested range. For a full $0 \dots 180$ grid the sum of $2\pi \cdot d\cos$ over all rows is 4π .

4 Particles and sizes

Flag	Arguments	Description
-p	TYPE PARAMETERS...	Built-in particle. Exactly one of -p or --pf is required.
--pf	FILE	Load particle from file.
--save-geometry	FILE	Save the effective particle, after input scaling and geometry classification, in the native text format. Alias: --save-particle. The calculation then continues.
--rs	SIZE	Resize file particle to $D_{\text{max}} = \text{SIZE}$. Mutually exclusive with --k_eq.
--k_eq	X	Resize so $k_{\text{eq}} = 2\pi \cdot r_{\text{eq}} / \lambda$. Requires wavelength.
--ri	Re Im	Complex refractive index. Absorption is enabled automatically when $\text{Im} \neq 0$, or explicitly with --abs.
-w	LAMBDA	Wavelength in micrometers.
-n	N	Maximum internal reflection/refraction depth.


File coordinates and all internal tracing geometry are stored in double precision. The loader translates coordinates relative to the order-independent bounding-box centre and removes only scale-relative binary serialization noise. A global translation changes only a common optical phase; this canonical form preserves the Mueller matrix, small edges, and facet order for files with large absolute coordinates.

Built-in particle types:


Type	Shape	Parameters
1	Hexagonal column/plate	L D: axial length and vertex-to-vertex diameter. The same type represents a column or a plate according to L/D .
2	Bullet	L D: total axial length and diameter. The pyramidal cap height is derived from the fixed 62° construction angle.
3	Bullet rosette	L D [CAP]: six bullets arranged as a rosette. If CAP is omitted, the same 62° construction is used.
4	Droxtal	SCALE: multiplies the fixed droxtal template. Legacy L D SCALE is accepted but L, D are ignored.

Type	Shape	Parameters
10	Concave hexagonal	L D CAVITY_DEG: column with top and bottom pyramidal cavities. The angle must be positive and less than $\arctan(L/D)$.
12	Two-column hexagonal aggregate	L D 2: exactly two equal eight-facet columns in the built-in relative placement. Use a file for a general aggregate.
999	Fixed built-in aggregate	SCALE: multiplies the fixed aggregate template used as a reproducible regression geometry.


1 Hexagonal column
L=2, D=1
convex




2 Bullet
L=2, D=1; cap=auto
convex




3 Bullet rosette
L=2, D=1; cap=auto
nonconvex, aggregate




4 Droxtal
scale=1
convex




10 Concave column
L=2, D=1; cavity=30 deg
nonconvex



12 Two-column aggregate
L=2, D=1; parts=2
nonconvex, aggregate



999 Fixed aggregate
scale=1
nonconvex, aggregate



Rendered from the native files
written by --save-geometry.

D: vertex-to-vertex hexagon diameter
L: prism or branch length
scale: uniform geometry scale

Figure 1: Geometries produced by the current built-in constructors. The images are rendered from the native files in examples/particles, not from separate drawing models.

4.1 Native particle file and geometry export

The native format starts with three nonempty header records:

```
CONCAVE
AGGREGATE [FACETS_PER_PART]
BETA_DOMAIN_DEG GAMMA_DOMAIN_DEG
```

```
x0 y0 z0
x1 y1 z1
x2 y2 z2
```

```
x0 y0 z0      # next facet
...
```

CONCAVE is 0 or 1. AGGREGATE is 0 for one object, or 1 FACETS_PER_PART for equal-size aggregate components. The third record gives the positive beta and gamma fundamental-domain widths. Blank lines separate facets; each facet must have at least three finite, non-collinear vertices. Full-line and

inline comments begin with #. Each facet must be a simple planar convex polygon. Vertex order defines its normal; every component must be a closed manifold with consistent outward winding. A facet may contain at most 64 vertices and a particle at most 256 facets.

--save-geometry FILE writes 17-digit coordinates. Loading validates facet geometry, closed manifold topology, outward winding, and aggregate metadata before tracing. A useful round-trip check is:

```
gpu/bin/mbs_po_gpu_double_fast --po -p 10 20 12 15 \
  --save-geometry concave.particle ...
gpu/bin/mbs_po_gpu_double_fast --po --pf concave.particle ...
```

The export consists of FILE and FILE.visibility. The sidecar stores the two clipping-visibility flags of every facet and is loaded automatically when it is present. Keep both files together: coordinates alone are insufficient for an exact round trip of concave built-in particles. Geometry is not written automatically; request it explicitly with --save-geometry FILE (alias --save-particle).

Equivalent-size scaling:

```
r_eq = (3 V / (4*pi))^(1/3)
k_eq = 2*pi*r_eq/lambda
scale = (k_eq_target * lambda / (2*pi)) / r_eq_original
```

5 Orientation grids

Mode	Arguments	Best use	Notes
--oldauto	DIV	Production regular grid	Grid step follows diffraction-limited angular scale; common values are 2, 4, 8.
--random	Nb Ng	Manual beta/gamma regular grid	Uses symmetry-reduced beta/gamma domain unless overridden.
--fixed	BETA GAMMA	Single-orientation debugging	Angles are degrees.
--orientfile	FILE	Reproducible custom orientations	One beta/gamma pair in degrees per line.
--sobol	N	Quasi-random orientation average	Good convergence for broad scans.
--sobol_seed	N S	Seeded Sobol/Owen sequence	Useful for repeatable convergence checks.
--sobol_ring	Nb Ng	Sobol beta with uniform gamma rings	Hybrid orientation grid.
--so3_quat	N	Isotropic SO(3) average	Hammersley on the symmetry quotient; laboratory alpha is integrated by scattering phi.
--so3_full_quat	N	Independent SO(3) audit	Direct full-group Shoemake quaternions; particle symmetry is deliberately ignored.
--hammersley	N	Low-discrepancy orientations	Debug/experimental.
--lattice	N	Rank-1 lattice orientations	Debug/experimental.
--lattice_z	N Z	Rank-1 lattice with explicit generator	Debug/experimental.
--euler_quad	Nb Ng	Gauss in cos(beta), periodic gamma	High-order quadrature.
--euler_adapt	Nb NgMax	Adaptive gamma count per beta ring	Reduces work near beta poles.
--adaptive_euler	EPS	Converged regular Euler grid	Refines N_β and N_γ separately, then together.
--adaptive	EPS	Adaptive Sobol count only	Doubles N ; it does not silently alter theta, phi, or reflection depth.
--auto	EPS	Auto theta, phi, orientation count	Keeps the requested reflection depth fixed.
--autofull	EPS	Auto n, theta, phi, orientations	Slower, more complete search.

Mode	Arguments	Best use	Notes
--oldautofull	EPS	Autofull with converged Euler grid	Independently converges N_β and N_γ .
--adaptive-config	FILE	Reproducible adaptive settings	Per-parameter minimum, maximum, and tolerance.

Orientation modifiers:

Flag	Arguments	Description
--ring_points	N	Points per diffraction ring for oldauto estimates; default 3.
--mirror_gamma	none	For a verified reflection-symmetric particle, sample half the gamma range and restore the omitted Mueller contribution with Stokes parity. Supported by --so3_quat.
--so3_mirror_audit	none	With an even --so3_quat N, explicitly trace nested reflected pairs for a direct validation of --mirror_gamma.
--sym	Sb Sg	Override symmetry domain: beta range is π/S_b , gamma range is $2\pi/S_g$.
--b	B1 B2	Manual beta range in degrees for --random.
--g	G1 G2	Manual gamma range in degrees for --random.
--maxorient	N	Maximum orientations for adaptive modes.
--max_beta_points	N	Hard adaptive N_β limit.
--max_gamma_points	N	Hard adaptive N_γ limit.
--chunk	N	Orientation/gamma chunk size.
--coh_orient	none	Disabled legacy mode; cross-orientation coherence is undefined without relative phases.
--pole	none	Use one gamma value at beta poles. Best with endpoint grids such as --oldauto.
--owen_avg	K	Average K nested Owen final seeds in --autofull; default can be controlled by environment.
--owen_seeds	S...	Explicit Owen seeds for --autofull final averaging.

5.1 Symmetry-reduced SO(3) quadrature

For an isotropic ensemble, the Haar measure in the Euler convention used by the program is

$$dR \propto \sin \beta d\beta d\gamma d\alpha.$$

The production mode --so3-quaternion N traces only the particle's fundamental domain $0 \leq \beta \leq \beta_{\text{sym}}, 0 \leq \gamma < \gamma_{\text{sym}}$. For point $i = 0, \dots, N-1$,

$$u_i = \frac{i + 1/2}{N}, \quad v_i = \text{radical_inverse}_2(i),$$

$$\beta_i = \arccos[1 - (1 - \cos \beta_{\text{sym}})u_i], \quad \gamma_i = \gamma_{\text{sym}}v_i, \quad w_i = \frac{1}{N}.$$

Thus the nodes are uniform in $\cos \beta$, not in β , and the normalized weights satisfy $\sum_i w_i = 1$. The option --sym Sb Sg overrides the domain with $\beta_{\text{sym}} = \pi/S_b$ and $\gamma_{\text{sym}} = 2\pi/S_g$; use it only for an actual particle symmetry.

For a paired mirror validation, add --so3-mirror-audit to an even full count and put $K = N/2$. The audit evaluates the same formulas for $i = 0, \dots, K-1$ with $u_i = (i + 1/2)/K$ and $\gamma_i = (\gamma_{\text{sym}}/2)v_i$, then explicitly traces both (β_i, γ_i) and $(\beta_i, \gamma_{\text{sym}} - \gamma_i)$ with weight $1/N$. This layout nests exactly with a K -point --mirror-gamma run. Without the audit modifier the production full-domain Hammersley sequence is unchanged.

With `--mirror-gamma`, the sampled range becomes $0 \leq \gamma < \gamma_{\text{sym}}/2$. The omitted half is restored before the α quadrature as

$$M_{\text{full}}(\theta, \phi) = \frac{1}{2} [M_{\text{half}}(\theta, \phi) + P M_{\text{half}}(\theta, -\phi) P], \quad P = \text{diag}(1, 1, -1, -1).$$

This is valid only when the complete optical particle, including facet visibility and material assignment, has the asserted reflection plane and the selected PO tracer is numerically invariant under that reflection. The program cannot prove this property from a particle file; validate every new particle class and parameter regime against one full-gamma run. The value N remains the number of actually traced β, γ orientations. For a strict paired check, compare `--so3-quaternion 4096 --so3-mirror-audit` with `--so3-quaternion 2048 --mirror-gamma`. Their base nodes are identical, so the difference measures numerical mirror consistency rather than two-sample Hammersley noise. Also check the ordinary full-domain sequence against an independent dense result and inspect backscatter separately.

The remaining laboratory angle α is not retraced. Rotation about the incident beam is equivalent to changing scattering azimuth ϕ , hence each theta row is accumulated as

$$\overline{M}(\theta) = \frac{1}{N_\phi} \sum_{\phi} M(\theta, \phi) L(-\phi).$$

Here L is the Stokes reference-plane rotation whose Q/U block contains $\cos(2\phi)$ and $\sin(2\phi)$. Multiplication is on the right because the incident polarization basis changes. At $\theta = 0$ and $\theta = \pi$ the azimuthal basis is singular; the implementation averages without L and then applies the exact forward/backward pole form.

This mode requires $N_\phi \geq 2$. A production command should combine it with `--scattering-diffraction-sampling Q` and `--latitude-phi-grid`. The slower `--so3-full-quaternion N` retains direct full-group sampling as an independent audit. Its N counts complete three-dimensional rotations, whereas the production mode's N counts traced beta/gamma orientations and uses the phi grid for the alpha quadrature.

6 Scattering grids

Flag	Arguments	Description
<code>--grid</code>	T1 T2 Nphi Nth	Uniform theta grid from T1 to T2 degrees. Output has Nth + 1 theta rows.
<code>--grid</code>	R Nphi Nth	Backscatter cone grid of radius R degrees.
<code>--tgrid</code>	FILE	Non-uniform theta grid in degrees, one row per theta value.
<code>--auto_tgrid</code>	EPS	Adaptive theta grid by bisection of measured full-Mueller interpolation error; no fixed halo angles are used.
<code>--auto_phi</code>	none	Compatibility form of measured phi convergence with tolerance 0.02.
<code>--adaptive_phi</code>	EPS	Converge N_ϕ only.
<code>--</code>	EPS	Converge internal reflection depth n only.
<code>adaptive_reflections</code>		
<code>--nphi</code>	N	Override phi count. Highest priority for phi.
<code>--diffraction-limit-grid</code>	FACTOR	Derive uniform theta and equatorial-phi steps from the diffraction estimate.
<code>--latitude-phi-grid</code>	none	Reduce the phi count in proportion to $\sin \theta$ away from the equator.
<code>--max_theta_points</code>	N	Hard theta-point limit; default 4097.
<code>--max_phi_points</code>	N	Hard N_ϕ limit; default 2400.
<code>--convergence_passes</code>	N	Consecutive passing refinements required; default 2.
<code>--filter</code>	DEG	Restrict output to a backscattering cone.
		Legacy/debug use.
<code>--point</code>	none	Backscatter point mode. Legacy; avoid for optimized regular-grid production.

6.1 Diffraction-limit and latitude-phi grids

For a PO `--diffraction-grid` DIV run, `--diffraction-limit-grid` FACTOR derives the scattering grid from the current particle maximum dimension $l_{\max}$ and wavelength λ :

$$\xi = \text{FACTOR} 0.69 \frac{\lambda}{l_{\max}}, \quad N_{\theta} = \left\lceil \frac{\pi}{\xi} \right\rceil,$$

$$N_{\phi, \text{eq}} = \text{round_up}_6 \left[\max \left(12, \left\lceil \frac{2\pi}{\xi} \right\rceil \right) \right].$$

The output contains $N_{\theta} + 1$ rows from zero to π . FACTOR=1 uses the estimate literally; FACTOR=0.5 approximately halves both angular steps, while a factor above one makes the grid coarser. This is an a-priori resolution estimate, not an a-posteriori accuracy guarantee. Validate a production factor against a finer value for every required Mueller element.

With `--latitude-phi-grid`, each theta row uses

$$N_{\phi}(\theta) = \min \left\{ N_{\phi, \text{eq}}, \text{round_up}_6 \left[\max \left(12, \left\lceil \frac{2\pi \sin \theta}{\xi} \right\rceil \right) \right] \right\}.$$

Equatorial spacing is unchanged while redundant azimuth samples are removed near the poles. Counts are rounded to a multiple of six, and a pole shares its neighboring work group for stable basis handling. Accumulation still uses the full rectangular $N_{\phi, \text{eq}}$ output layout, so the file format does not change.

The variable latitude grid supports both `--method po --diffraction-grid` DIV and the symmetry-reduced `--so3-quaternion` N path, with one particle size per process. For SO(3), prefer `--scattering-diffraction-sampling Q`; the unified `--diffraction-sampling Q` is itself a primary regular orientation rule. The diffraction-limit option conflicts with explicit `--nphi`; the latitude grid is not supported by a shared serial multi-size trace. Run each size in its own process so $l_{\max}$ and the grid are recomputed.

```
CUDA_VISIBLE_DEVICES=0,1,2,3 \
MBS_GPU_GROUPS=1 MBS_GPU_MULTI_MAX=4 \
gpu/bin/mbs_po_gpu_double ... --diffraction-limit-grid 0.5 --latitude-phi-grid
```

Selection rules:

Quantity	Rule
Theta grid	Exactly one of <code>--tgrid</code> , <code>--grid</code> , or <code>--auto_tgrid</code> ; unified auto modes treat an explicit grid as fixed.
Phi grid	Standalone adaptive phi selection and explicit <code>--nphi</code> are mutually exclusive. Unified auto modes treat explicit <code>--nphi</code> as fixed and tune the remaining dimensions.

6.2 Unified convergence criterion

For two approximations A and B , phi, reflection, and Euler candidate comparisons use the row error

$$e_{\text{row}} = \max \left(\frac{|M_{11}^A - M_{11}^B|}{\max(|M_{11}^A|, |M_{11}^B|, \epsilon_0)}, \max_{(i,j) \neq (1,1)} \frac{|R_{ij}^A - R_{ij}^B|}{\max(1, |R_{ij}^A|, |R_{ij}^B|)} \right), \quad R_{ij} = \frac{M_{ij}}{M_{11}}.$$

Here M_{ij} is a Mueller element, R_{ij} is its normalized value, and ϵ_0 protects a vanishing M_{11} . The maximum over theta rows is combined with the relative change of $\int M_{11} d\Omega$. Reflection-depth tests also include outgoing energy. Theta convergence is different: it evaluates the actual Mueller row at one-third and two-thirds of every interval against interpolation and checks the same integrated M_{11} . Sobol orientation convergence checks incoming energy and all 16 Mueller elements on control-theta rows selected from the actual scattering grid.

The parameters are not strictly independent. Reflection depth changes the beam tree; phi changes the azimuth average used to expose theta structure; and orientation sampling changes every averaged row. Therefore the joint order is

$$n \longrightarrow N_{\phi} \longrightarrow \{\theta_j\} \longrightarrow N_{\text{orient}}.$$

The `--auto` modes repeat the complete sequence on a common larger pilot set until the pilot implied by the selected orientation count and all selected values form a coupled fixed point. Regular Euler convergence alternates N_β and N_γ , then doubles both together. Reaching any hard limit in phi, reflection, theta, Euler, or a unified mode is reported as an error rather than accepted as convergence. Standalone `--adaptive-orientations` is exploratory: at its orientation cap it warns and writes the best result; unified modes use strict orientation convergence. The configured passing streak applies to phi, reflection, Euler, and orientation searches, while theta uses interval refinement directly. Every trial is written to `<output>/<name>_convergence.tsv`.

6.3 Adaptive configuration file

Use `--adaptive-config FILE` to keep production convergence settings outside a long command line. The documented template is `configs/adaptive.example.conf`. It uses strict `key = value` assignments and accepts inline comments after `#` or `;`.

The file defines separate minimum, maximum, and relative tolerance values for reflection depth, laboratory alpha (internally N_ϕ), theta points, Sobol orientations, beta points, and gamma points. It also defines the number of consecutive passing refinements and the pilot and sweep limits of the coupled controller. A tolerance of `0.01` means one percent.

```
mbs_po --autofull 0.02 --adaptive-config configs/adaptive.example.conf ...
```

Per-parameter tolerances in the file replace the mode-wide EPS; a missing tolerance inherits EPS. Explicit command-line `--max-*`, `--max-reflections`, and `--convergence-passes` values override the file. Unknown keys, duplicates, invalid ranges, non-power-of-two Sobol limits, and malformed lines are rejected before the calculation, with the file line and a corrective hint.

6.4 Why column symmetry does not divide Nphi

The code uses the Euler convention

$$\mathbf{R} = R_z(\alpha)R_y(\beta)R_z(\gamma).$$

The scattering-azimuth loop is the rotationally covariant implementation of the laboratory-angle α average, so $N_\phi = N_\alpha$ in this context. A hexagonal column has the body-axis symmetry $R_z(2\pi/6)$; it reduces the γ domain to $0 \leq \gamma < \pi/3$. For $\beta \neq 0, \pi$, it does not make the tilted particle invariant under a laboratory $R_z(2\pi/6)$ rotation, hence $0 \leq \alpha < 2\pi$ is still required. An automatic division of N_ϕ by six would therefore be incorrect. The aliases `--alpha-points` and `--adaptive-alpha` only clarify the meaning of the existing phi controls; they do not enable an approximation.

For full angular integrals use `--grid 0 180 Nphi Nth`. Endpoint rows are physical half-cells; they must not have zero weight.

7 Beam and trace cutoffs

Cutoffs act at two different stages. Output-beam cutoffs discard a completed ray branch before PO diffraction. Trace cutoffs stop an internal branch while the reflection/refraction tree is being built. With reference values taken from the current orientation, the three dimensionless tests are

$$j_b = \frac{\|J_b\|_F^2}{J_{\text{ref}}^2}, \quad a_b = \frac{A_b}{A_{\text{ref}}}, \quad i_b = j_b a_b.$$

Here J_b is the accumulated Jones matrix of branch b , A_b is its polygon area, and i_b is a simple intensity-area importance estimate. When several tests are enabled, rejection uses logical *OR*: satisfying any one smallness test removes the branch. Reason counters can therefore overlap.

7.1 Coherent presets

`--cutoff-profile MODE` configures all relative thresholds and the small-fragment ratio together. It cannot be combined with an individual cutoff or `--beam-area-ratio`.

Profile	Output i_b	Trace i_b	Area ratio	Intended use
off	0	0	disabled	Reference and convergence runs; no configurable cutoff approximation.
safe	10^{-10}	10^{-12}	10^8	First production candidate after comparison with off.
balanced	10^{-8}	10^{-10}	10^5	Faster scans after particle-class calibration.
fast	10^{-6}	10^{-8}	10^3	Exploratory scans; not a validation setting.
legacy default	0	$j_b = 10^{-7}$	100	Scale-invariant replacement of the historical weak-branch test when no profile or individual cutoff is supplied.

The named `safe`, `balanced`, and `fast` presets enable the combined importance criterion, not separate Jones and area OR thresholds. This avoids removing a large but weak branch or a small but intense branch solely because one factor is small. The legacy default additionally terminates a branch when its Jones norm is below 10^{-7} of the strongest incident branch; this replaces the former area-dependent threshold. Its area-ratio simplification remains at 100; use `--cutoff-profile off` when a genuinely uncut reference is required. The profiles do not set `--trace-max-beams`. For unattended runs on deeply concave particles, use a finite beam limit as a diagnostic guard: strict profiles can still produce a very large tree for an isolated orientation. A nonzero “Configured beam-limit hits” counter means that the result is incomplete; increase the limit or calibrate stronger cutoffs before using that run as physical data.

7.2 Individual controls

Flag	Range	Exact action
<code>--beam-cutoff EPS</code>	$[0, 1]$	Legacy shortcut setting both output Jones and output area thresholds; a beam is rejected if either test passes.
<code>--beam-cutoff-jones EPS</code>	$[0, 1]$	Output test $j_b < \text{EPS}$.
<code>--beam-cutoff-area EPS</code>	$[0, 1]$	Output test $a_b < \text{EPS}$.
<code>--beam-cutoff-importance EPS</code>	$[0, 1]$	Output test $i_b < \text{EPS}$.
<code>--trace-cutoff EPS</code>	$[0, 1]$	Legacy shortcut setting both internal Jones and area thresholds; pruning uses OR.
<code>--trace-cutoff-jones EPS</code>	$[0, 1]$	Internal test $j_b < \text{EPS}$.
<code>--trace-cutoff-area EPS</code>	$[0, 1]$	Internal test $a_b < \text{EPS}$.
<code>--trace-cutoff-importance EPS</code>	$[0, 1]$	Internal test $i_b < \text{EPS}$.
<code>--beam-area-ratio R</code>	$R \geq 1$	After a nonconvex split, replace two fragments by the larger one only when their area ratio is at least R .
<code>--trace-max-beams N</code>	$N \geq 0$	Hard per-orientation beam-tree cap; 0 disables the configured cap. Reaching it aborts the calculation so an incomplete orientation cannot enter the average.

If a legacy common shortcut and a corresponding specific Jones/area option are supplied together, the specific value overrides that side and the program prints a warning. A profile instead rejects such mixing as an input error, so a command cannot silently become a partly modified preset.

Every completed run appends `OUTPUT BEAM CUTOFF REPORT` and `TRACE CUTOFF REPORT` blocks to the log. They contain the selected profile, effective thresholds, candidate/kept/rejected counts, overlapping reason counts, fragment simplifications, configured-cap hits, and hard internal tree-limit hits. Calibrate a profile by running the same geometry, orientation set, n , theta grid, and N_ϕ with `off` and with the candidate profile; compare all 16 M_{ij}/M_{11} , not only runtime or the rejected-beam percentage.

8 GPU and multi-GPU

8.1 CUDA backend

Flag	Description
--gpu	Use CUDA diffraction backend. Optional in gpu/ binaries because they default to GPU.
--cpu	Force CPU backend from a GPU-capable binary.
--fft	Use cuFFT angular phi interpolation backend. Requires GPU. The direct-phi compression factor is selected automatically.
--fft-factor N	Enable FFT interpolation with an explicit compression factor $1 \leq N \leq 64$. $N = 1$ keeps the direct phi grid and is useful as a same-backend reference.
--fft-tolerance EPS	Enable a nested-grid error estimate and one automatic refinement when the estimate exceeds $0 < \text{EPS} < 1$.
--threads N	OpenMP host worker threads. Also controls tracing-side parallelism before GPU diffraction.

8.2 FFT phi compression and error control

Let N_ϕ be the requested output azimuth count and f the compression factor. The first CUDA pass evaluates approximately

$$N_{\phi,\text{direct}} = \max\left(16, \left\lfloor \frac{N_\phi}{f} \right\rfloor\right)$$

direct samples, then uses periodic Fourier zero-padding to reconstruct the N_ϕ output grid. For $f = 1$, $N_\phi < 32$, or a factor that cannot reduce the grid, the implementation uses the direct path. The speed gain is therefore workload dependent and is bounded by the fraction of runtime spent in phi-direction diffraction; tracing itself is not reduced.

--fft asks the implementation to select f . --fft-factor N makes the requested compression explicit and has priority over MBS_FFT_PHI_FACTOR. Large factors are not an accuracy promise: sharp azimuthal structure has high Fourier modes and can be smoothed or aliased.

With --fft-tolerance EPS, the code also evaluates a nested grid with

$$N_{\phi,2} = \min(N_\phi, 2N_{\phi,\text{direct}}).$$

It compares significant M_{11} samples and all 16 Mueller elements using an M_{11} -based scale. The reported estimate is

$$\hat{e} = \max\left(\max_{M_{11} \text{ significant}} \frac{|M_{11}^{(1)} - M_{11}^{(2)}|}{|M_{11}^{(2)}|}, \max_{i,j} \frac{|M_{ij}^{(1)} - M_{ij}^{(2)}|}{\max(|M_{11}^{(2)}|, 10^{-3}M_{11,\text{max}}^{(2)})}\right).$$

If $\hat{e} > \text{EPS}$, the result reconstructed from the doubled direct grid is retained. This is a one-step a-posteriori estimator, not a rigorous bound and not an iterative convergence proof. It costs an additional diffraction pass and temporarily holds coarse, refined, and output arrays. For a final reference, omit all FFT flags or use --fft-factor 1; for production, first calibrate f and EPS on representative sizes and particle shapes.

Explicit 4x compression, refine once when the estimate exceeds 1 percent
 gpu/bin/mbs_po_gpu_float_fast ... --fft-factor 4 --fft-tolerance 0.01

The final FFT INTERPOLATION REPORT records the requested and effective factor, direct and output N_ϕ , number of FFT-path and validation calls, number of refined calls, and the worst nested-grid estimate. Factor 1 is labelled as direct/no interpolation. The fused multi- k_{eq} FFT path does not perform this validation; when tolerance or the diagnostic check is requested, the dispatcher uses a supported fallback instead of silently skipping the check.

GPU runtime errors are fatal in the split GPU build. For debugging only:

For regular polygon phases, the CPU PO loop evaluates four adjacent theta directions together with AVX2. The edge accumulation order is retained in every vector lane. A small phase or an active near-singular denominator selects the original stable scalar formula for that group. This selection is automatic, has no command-line tolerance, and is enabled in the standard CPU build.

`MBS_GPU_ALLOW_FALLBACK=1 gpu/bin/mbs_po_gpu_float_fast ...`

8.3 Why the GPU version is faster

The expensive PO part is the repeated evaluation of the same beam aperture integral for many detector directions and many orientations. The CPU traces rays and prepares compact beam records; the GPU then evaluates diffraction and, in the fast paths, Mueller accumulation on a large regular grid.

Work item	CPU path	GPU path	Parallel granularity
Ray tracing through facets	OpenMP over orientations/gamma blocks	Automatic CUDA ordering and conservative candidate filtering; exact intersections and beam splitting remain CPU-side	Orientation/chunk level
Beam packing	CPU host code	CPU prepares GpuBeam/packed beam buffers and copies to device	Beam records
Edge diffraction	Scalar/vector CPU loops	CUDA kernels in <code>GpuDiffraction.cu</code>	Beam x theta x phi x orientation
Jones coherent sum	CPU arrays of complex 2x2 matrices	Atomic or no-atomic device kernels	Grid cell and orientation
Jones to Mueller	CPU after Jones sum	Separate <code>mueller_batch_kernel</code> or fused in diffraction kernel	Grid cell
Multi-k_eq scans	Repeat diffraction per size	Optional fused multi-k_eq CUDA pass	Size x beam x grid
FFT phi interpolation	CPU direct phi grid unless disabled	cuFFT low-phi pass plus zero-padding reconstruction	Theta/orientation batches

The main speedup comes from exposing a very large product of independent operations:

$N_{\text{work}} \approx N_{\text{orient}} * N_{\text{beams_per_orientation}} * N_{\text{theta}} * N_{\text{phi}}$

Each beam/direction contribution is mostly independent until the coherent Jones sum. That makes the diffraction stage a good CUDA workload: many threads do the same edge-integral arithmetic over different (orientation, beam, theta, phi) combinations.

8.4 Atomic and no-atomic GPU accumulation

There are two families of CUDA accumulation paths in `src/cuda/GpuDiffraction.cu`.

Mode	Main kernels	How accumulation works	When useful
Atomic Jones accumulation	<code>diffraction_kernel</code>	Each thread computes one beam/grid contribution and uses <code>atomicAdd</code> into the complex Jones buffer. Afterwards <code>mueller_batch_kernel</code> converts the summed Jones matrix to Mueller.	General fallback, supports more combinations such as no-shadow output.
No-atomic grid kernels	<code>diffraction_grid_kernel</code>	Work is reorganized so a thread owns a grid/output slot and loops over beams, avoiding multiple writers to the same Jones cell.	Full-only output when memory/layout allows it.

Mode	Main kernels	How accumulation works	When useful
Fused Mueller kernels	<code>diffraction_grid_mueller_kernel</code> , <code>diffraction_grid_mueller_full_kernel</code> , <code>*_full8_kernel</code> , <code>*_mixed8_kernel</code>	The kernel computes coherent Jones locally for an output slot and immediately converts/adds Mueller, avoiding large intermediate Jones buffers.	Fast production path for full-only GPU runs.
Staged orientation Mueller	<code>diffraction_grid_mueller_orient_kernel</code> + <code>reduce_mueller_orient_kernel</code>	First writes per-orientation Mueller, then reduces orientations.	Reduces contention and gives a deterministic reduction shape for large orientation batches.
Multi-k_eq fused	<code>diffraction_grid_mueller_multik_kernel</code>	Computes several nearby equivalent sizes from one packed beam batch.	Shared-batch --multikeq scans.

In the atomic path the atomics are on the real and imaginary components of the 2x2 Jones matrix:

```
J00.re, J00.im, J01.re, J01.im,
J10.re, J10.im, J11.re, J11.im
```

For `_noshadow` output the same set of atomics is also applied to the no-shadow Jones buffer. This is correct for coherent PO because beams must be summed as Jones amplitudes before conversion to Mueller. The cost is contention when many beams hit the same detector cell.

The no-atomic/fused paths avoid that contention by changing ownership: one CUDA thread or thread group owns an output grid element and accumulates the beams for that element in registers/local variables. This is often faster for full Mueller output because it reduces global-memory atomics and may skip the large intermediate Jones buffer. The tradeoff is that these paths are more specialized and may be disabled for diagnostic modes that require extra outputs.

Useful controls:

Environment variable	Effect
<code>MBS_GPU_NO_ATOMICS=1</code>	Force no-atomic path when supported.
<code>MBS_GPU_NO_ATOMICS=0</code>	Force atomic path for comparison/debugging.
<code>MBS_GPU_FUSED_MUELLER=1</code>	Prefer fused diffraction-to-Mueller kernels when no-atomic mode is active.
<code>MBS_GPU_STAGE_MUELLER=1</code>	Use staged per-orientation Mueller plus reduction where supported.
<code>MBS_GPU_NO_VERTEX_CACHE=1</code>	Disable cached/packed vertex path for debugging.
<code>MBS_GPU_COMPACT_BEAMS=0</code>	Disable compact packing for beams with at most 8 vertices and use the general layout for diagnostics.
<code>MBS_GPU_WARP_BEAMS=0</code>	Restore the serial per-thread beam loop instead of the default warp-per-output reduction.
<code>MBS_GPU_WARP_GRID_3D=0</code>	Disable only the default 3D-grid warp specialization.
<code>MBS_GPU_TIMING=1</code>	Print GPU timing breakdown for count/pack/copy/kernels/d2h/add.
<code>MBS_GPU_BLOCK=N</code>	Override CUDA block size for kernel tuning.

8.5 Automatic CUDA tracing profile

The CUDA PO backend automatically enables batched facet ordering and conservative projected candidate filtering. The same mode can be requested explicitly with `--gpu-trace-prefilter`; use `--no-gpu-trace-prefilter` for an A/B reference. This is not an approximate beam tracer: exact intersection polygons, topology decisions, Fresnel splitting, and child-beam construction remain on the CPU.

The validated automatic profile uses exact CUDA topological ordering, an ordering cache, conservative skip flags for 25–256 candidates, cached facet geometry, 64 threads for the large-list kernel, and one nonblocking CUDA stream per OpenMP worker. The per-worker batch is $\max(64, \lceil 512/N_{\text{workers}} \rceil)$, which avoids the CUDA-stack exhaustion observed with oversized fixed batches. If this initial batch still exhausts kernel-stack backing, the code recursively splits it and remembers the reduced process-wide limit for all later batches and orientations. When trace-limit retries are enabled, worker copies also share the largest successful retry beam limit. Later orientations skip the known-insufficient first pass, but retry levels are still counted from the original configured limit, so the retry ceiling is unchanged.

On a 32-orientation nonconvex test, this changed 11.12 s to 8.00 s and reduced full retries from 30 to 7. Nonblocking per-worker streams changed a 256-orientation run from 61.39 s to 42.26 s. Output tables and integral files were byte-identical in both A/B checks. Independent processes on the same physical GPU serialize only the heavy trace batch through a lock keyed by the PCI address. OpenMP workers within one process retain independent streams and overlap. This default prevents combined CUDA kernel-stack reservations from exhausting device memory and does not serialize diffraction kernels. On a deeply nonconvex production orientation this reduced wall time from 7.93 s to 0.98 s (8.09 times); on a smaller representative case the gain was about 1.08 times. The benefit therefore depends strongly on trace complexity.

Expert controls are provided for reproducible profiling; their defaults form the automatic profile:

Variable	Default	Meaning
MBS_GPU_TRACE_OPENMP	1	Allow CUDA tracing from OpenMP workers.
MBS_GPU_TRACE_BATCH_BEAMS	automatic	Override the initial per-worker batch; after OOM the process lowers and remembers the limit.
MBS_GPU_TRACE_FULL_SORT	1	Exact CUDA topological ordering.
MBS_GPU_TRACE_SORT_CACHE	1	Reuse exact ordering for identical keys.
MBS_GPU_TRACE_LARGE_SKIP_FLAGS	1	Conservative projected skip flags.
MBS_GPU_TRACE_LARGE_THREADS	64	Large-list block size (64, 128, or 256).
MBS_GPU_TRACE_CACHE_FACETS	1	Retain packed facet geometry per worker.
MBS_GPU_TRACE_MIN_CANDIDATES	1024	Minimum batch candidate count sent to CUDA.
MBS_GPU_TRACE_NONBLOCKING_STREAM	1	Per-worker nonblocking streams; set 0 only for serialization diagnostics.
MBS_GPU_TRACE_PROCESS_LOCK	1	Serialize heavy trace batches across independent processes on one physical GPU.
MBS_GPU_TRACE_PREFILTER_FIRST	0	Diagnostic projected filtering before sorting.
MBS_GPU_TRACE_MARGIN	automatic	Override the conservative projection margin.
MBS_GPU_TRACE_TIMING	0	Print transfer and kernel timings.
MBS_GPU_TRACE_VERIFY_SORT	0	Compare CUDA ordering and skip flags with CPU.

The verification mode reported zero ordering and skip-flag mismatches in the production regression. Because a different but equivalent facet traversal can change floating-point summation order, validate sensitive runs against `--no-gpu-trace-prefilter`; the release gate performs this A/B check.

For a variable latitude-phi grid, `MBS_GPU_GROUPS=1` enables a dedicated exact scheduler. Independent theta-row work groups are assigned dynamically to visible GPUs. Orientation tracing and prepared beams remain shared in host memory, while each device owns one CUDA workspace. Packed beams, weights, and offsets are uploaded once per orientation chunk per device and reused for subsequent theta groups handled by that worker.

Use `CUDA_VISIBLE_DEVICES` to select devices. Use `MBS_GPU_MULTI=N` or `MBS_GPU_MULTI_MAX=N` to limit the number of workers; `MBS_GPU_MULTI=0` leaves one GPU. The scheduler requires direct CUDA diffraction; FFT interpolation and theta-zone beam filtering retain the existing path. Speedup need not be linear because CPU tracing, packing, PCIe transfers, final reduction, and theta-group imbalance remain in wall time.

8.6 Multi-size scans

Flag	Arguments	Description
<code>--multigrid</code>	<code>Dmin Dmax N</code>	Log-spaced scan in absolute maximum particle dimension; each value uses $x = \pi D_{\max}/\lambda$, independent of the source size.

Flag	Arguments	Description
--multikeq	Kmin Kmax N	Log-spaced scan in equivalent size parameter.
--multikeq_list	FILE	Exact list of k_eq values, one per line.
--multigrid_parallel	N	Run scan points as child processes; 0 means auto.
--multigrid_threads	N	OpenMP threads per child process.
--gpu_devices	LIST	Comma-separated CUDA device list, for example 0,1,2,3,4.
--multikeq_shared_batches	none	Batch nearby k_eq values per GPU child and reuse tracing from the largest value in the batch.
--	R	Maximum kmax/kmin inside one shared batch;
multikeq_batch_ratio		default 1.05.

Exact multi-GPU scan, one process per active GPU slot:

```
gpu/bin/mbs_po_gpu_float_fast --po --pf particle.dat \
  --multikeq_list keq.txt --ri 1.6 0.002 -w 1.064 -n 12 \
  --oldauto 2 --grid 0 180 600 180 --fft --close \
  --multigrid_parallel 0 --multigrid_threads 16 --gpu_devices 0,1,2,3,4 \
  -o scan_exact
```

Shared-batch scan:

```
gpu/bin/mbs_po_gpu_float_fast --po --pf particle.dat \
  --multikeq_list keq.txt --ri 1.6 0.002 -w 1.064 -n 12 \
  --oldauto 2 --grid 0 180 600 180 --fft --close \
  --multigrid_parallel 0 --multigrid_threads 16 --gpu_devices 0,1,2,3,4 \
  --multikeq_shared_batches --multikeq_batch_ratio 1.05 \
  -o scan_shared
```

Experimental fused multi-k_eq GPU diffraction:

```
MBS_GPU_MULTI_K_FULL=1 gpu/bin/mbs_po_gpu_float_fast ...
```

Use tighter --multikeq_batch_ratio for accuracy; use exact mode when each size must have its own oldauto reference grid.

9 All flags

9.1 Method, particle, and physical parameters

Flag	Arguments	Description
--po	none	Physical Optics mode.
--go	none	Geometrical Optics mode.
-p	TYPE L D [extra]	Built-in particle.
--pf	FILE	Particle from file.
--save-geometry	FILE	Save the effective native particle and continue; alias --save-particle.
--rs	SIZE	Resize file particle by Dmax.
--k_eq	X	Resize by equivalent size parameter.
--ri	Re Im	Refractive index.
-w	LAMBDA	Wavelength in micrometers.
-n	N	Maximum internal reflections/refractions.
--abs	none	Enable absorption accounting. Also enabled automatically for nonzero Im(ri).
--abs_points	N or all	Absorption sampling: center point or all polygon vertices.

9.2 Orientation flags

Flag	Arguments	Description
--fixed	BETA GAMMA	Single orientation in degrees.
--random	Nb Ng	Regular beta/gamma grid.
--sobol	N	Sobol orientations.
--so3_quat	N	Symmetry-reduced SO(3); alpha is integrated by scattering phi.
--so3_full_quat	N	Direct full-SO(3) quaternion audit.
--sobol_seed	N S	Sobol with explicit Owen seed.
--sobol_ring	Nb Ng	Sobol beta with gamma rings.
--hammersley	N	Hammersley orientation set.
--lattice	N	Rank-1 lattice orientation set.
--lattice_z	N Z	Rank-1 lattice with explicit generator.
--euler_quad	Nb Ng	Gauss beta x periodic gamma quadrature.
--euler_adapt	Nb NgMax	Gauss beta with adaptive gamma count.
--adaptive_euler	EPS	Independently converge N_β and N_γ , then verify them jointly.
--montecarlo	N	Pseudo-random Monte Carlo orientations.
--adaptive	EPS	Adaptive Sobol orientation count only.
--auto	EPS	Auto theta, phi, and orientation count.
--autofull	EPS	Auto n, theta, phi, and orientations.
--oldautofull	EPS	Autofull search with a converged regular Euler final grid.
--adaptive-config	FILE	Load per-parameter adaptive ranges and tolerances.
--owen_avg	K	Average final Owen seeds.
--owen_seeds	S...	Explicit final Owen seeds.
--oldauto	DIV	Physics-based regular grid.
--ring_points	N	Points per diffraction ring estimate.
--mirror_gamma	none	Use mirrored half gamma domain.
--orientfile	FILE	Load beta/gamma orientations in degrees from file.
--b	B1 B2	Beta range for --random.
--g	G1 G2	Gamma range for --random.
--maxorient	N	Maximum adaptive orientation count.
--max_beta_points	N	Maximum adaptive N_β .
--max_gamma_points	N	Maximum adaptive N_γ .
--chunk	N	Chunk size for orientation/gamma processing.
--coh_orient	none	Disabled legacy mode; do not use.
--pole	none	Exact beta-pole gamma shortcut.
--sym	Sb Sg	Override particle symmetry.

9.3 Scattering grid and acceleration flags

Flag	Arguments	Description
--grid	T1 T2 Nphi Nth	Uniform theta range.
--grid	R Nphi Nth	Backscatter cone.
--tgrid	FILE	Non-uniform theta grid.
--auto_tgrid	EPS	Adaptive theta grid.
--auto_phi	none	Measured phi convergence at tolerance 0.02.
--adaptive_phi	EPS	Converge N_ϕ only.
--	EPS	Converge n only.
adaptive_reflections		
--nphi	N	Override phi count.
--diffraction-limit-grid	FACTOR	Set theta and equatorial-phi steps to FACTOR $0.69\lambda/l_{\max}$.
--latitude-phi-grid	none	Use a row-dependent phi count proportional to $\sin \theta$.
--max_theta_points	N	Adaptive theta limit.
--max_phi_points	N	Adaptive phi limit.
--convergence_passes	N	Required passing streak.
--threads	N	OpenMP worker threads.
--gpu	none	CUDA backend.
--cpu	none	Force CPU backend in GPU build.

Flag	Arguments	Description
--fft	none	cuFFT phi interpolation with automatic compression.
--fft-factor	N	Explicit direct/output phi compression, 1 ... 64; also enables FFT.
--fft-tolerance	EPS	Nested-grid estimate in $0 < \text{EPS} < 1$ with one doubled-direct-grid refinement.
--cutoff-profile	MODE	Complete preset: off, safe, balanced, or fast.
--beam-cutoff	EPS	Legacy output shortcut; reject when relative Jones OR area is below EPS.
--beam-cutoff-jones	EPS	Output cutoff by relative squared Jones magnitude.
--beam-cutoff-area	EPS	Output cutoff by relative beam area.
--beam-cutoff-importance	EPS	Output cutoff by relative Jones intensity times area.
--trace-cutoff	EPS	Legacy internal shortcut; prune when relative Jones OR area is below EPS.
--trace-cutoff-jones	EPS	Prune trace tree by relative squared Jones magnitude.
--trace-cutoff-area	EPS	Prune trace tree by relative area.
--trace-cutoff-importance	EPS	Prune trace tree by relative Jones intensity times area.
--trace-max-beams	N	Hard per-orientation beam-tree cap; 0 disables it and reaching it aborts the calculation.
--gpu-trace-prefilter	none	Explicitly enable the automatic batched CUDA ordering and candidate-filtering profile.
--no-gpu-trace-prefilter	none	Disable automatic CUDA tracing for a reference comparison.
--trace_prefilter	none	Enable CPU projected-AABB prefilter.
--no_trace_prefilter	none	Disable CPU projected-AABB prefilter.
--trace_prefilter_margin	M	AABB prefilter margin.
--	none	Print prefilter counters.
trace_prefilter_stats		
-r, --beam-area-ratio	RATIO	Small-fragment area ratio, at least 1; legacy default 100.

9.4 Output, diagnostics, and legacy flags

Flag	Arguments	Description
-o	NAME	Output path/name.
--close	none	Exit after computation.
--log	SEC	Progress logging interval.
--checkpoint	none	Save/resume long --orientfile, --oldauto, and --random runs.
--save_betas	none	Save per-beta Mueller files.
--full_only	none	Write only full Mueller output. This is the default.
--noshadow_output	none	Also write _noshadow Mueller output.
--shadow	none	Legacy flag; currently no effect.
--shadow_off	none	Disable shadow beam. Diagnostic use.
--incoh	none	Incoherent per-beam Mueller sum.
--jones	none	Write Jones matrices where supported.
--karczewski	none	Use Karczewski polarization matrix.
--legacy_sign	none	Use old Fresnel sign convention.
--ot_phase_avg	none	Average optical-theorem extinction over one far-reference phase period.
--ot_phase_shift	F	Diagnostic optical-theorem phase shift in wavelengths.
--ot_ping	D	Legacy far-screen optical-theorem phase rotation.
--filter	DEG	Restrict output to backscatter cone.
--point	none	Legacy backscatter point mode.
--tr	FILE	Load trajectory file.
--all	none	Calculate all loaded trajectories.
--gr	none	Output trajectory groups.
--forced_convex	none	Force convex processing.

Flag	Arguments	Description
--forced_nonconvex	none	Force nonconvex processing.
--help, -h	none	Print help.
--help-debug	none	Print full debug/experimental help.

10 Environment variables

Every active MBS_* variable is written to the run summary. Variables that alter sampling, geometry, cutoffs, or numerical results are rejected by default. The debug option --allow-experimental-environment permits them after explicit acknowledgement and records their names and values. Prepared-orientation modes start with a 16-orientation pilot, measure nested beam/path allocations, and adapt the next chunk to current available RAM and the configured limits.

Production-use variables:

Variable	Meaning
CUDA_VISIBLE_DEVICES	Standard CUDA device visibility control.
OMP_NUM_THREADS	OpenMP default thread count when --threads is not used.
MBS_GPU_ALLOW_FALLBACK=1	Allow old GPU-to-CPU fallback after CUDA failure. Debug only.
MBS_GPU_MEM_FRACTION	Fraction of free GPU memory allowed for internal buffers.
MBS_GPU_NO_ATOMICS	Select no-atomic (1) or atomic (0) GPU accumulation path when possible.
MBS_GPU_FUSED_MUELLER	Select fused diffraction-to-Mueller kernels when no-atomic mode is active.
MBS_GPU_STAGE_MUELLER	Enable staged per-orientation Mueller reduction when supported.
MBS_GPU_NO_VERTEX_CACHE	Disable cached/packed vertex path for debugging.
MBS_GPU_COMPACT_BEAMS=0	Disable compact packing for beams with at most 8 vertices.
MBS_GPU_WARP_BEAMS=0	Restore the serial per-thread beam loop for diagnostics.
MBS_GPU_WARP_GRID_3D=0	Disable only the default 3D-grid warp specialization.
MBS_GPU_TIMING	Print CUDA timing breakdowns.
MBS_GPU_BLOCK	Override CUDA kernel block size.
MBS_GPU_TRACE_OPENMP	Enable automatic CUDA tracing from OpenMP workers; default 1.
MBS_GPU_TRACE_BATCH_BEAMS	Override the automatic per-worker batch $\max(64, \lceil 512/N_{\text{workers}} \rceil)$.
MBS_GPU_TRACE_FULL_SORT	Exact CUDA topological ordering; default 1.
MBS_GPU_TRACE_SORT_CACHE	Cache exact CUDA ordering; default 1.
MBS_GPU_TRACE_LARGE_SKIP_FLAGS	Conservative projected skip flags for large candidate lists; default 1.
MBS_GPU_TRACE_LARGE_THREADS	Large-list CUDA block size; default 64.
MBS_GPU_TRACE_CACHE_FACETS	Cache packed facet geometry; default 1.
MBS_GPU_TRACE_MIN_CANDIDATES	Minimum candidates per submitted batch; default 1024.
MBS_GPU_TRACE_NONBLOCKING_STREAM	Per-worker nonblocking streams; default 1; set 0 for serialization diagnostics.
MBS_GPU_TRACE_PROCESS_LOCK	Per-physical-GPU process lock for heavy trace batches; default 1; set 0 only for diagnostics.
MBS_GPU_TRACE_TIMING	Print CUDA tracing timing breakdown.
MBS_GPU_TRACE_VERIFY_SORT	Verify CUDA ordering against CPU.
MBS_ORIENTATION_TIMING	Print summed CPU time for rotation, tracing, and prepared-beam construction.
MBS_HOST_MEM_FRACTION	Fraction of current available host memory for measured prepared-orientation chunks.
MBS_HOST_MEM_RESERVE_MB	Host memory reserve in MB.
MBS_HOST_MEM_BUDGET_MB	Hard host memory budget, also set for parallel children.
MBS_FFT_PHI_FACTOR	Legacy FFT compression-factor override when --fft-factor is absent; the explicit CLI value has priority.
MBS_GPU_MULTI=0	Disable automatic multi-orientation GPU batching.
MBS_GPU_MULTI_MAX=N	Cap automatic GPU multi batching.
MBS_GPU_GROUPS=1	Distribute variable latitude-phi theta groups across visible GPUs.
MBS_GPU_MULTI_K_FULL=1	Experimental fused multi-k_eq diffraction.
MBS_BEAM_LOG=PATH	Write the first handled PO beam set to the explicit diagnostic path. No beam log is written by default.

Variable	Meaning
MBS_SHARED_BETA_GROUP=N	Override shared-batch beta grouping.
MBS_SHARED_ORIENT_CHUNK=N	Override shared-batch orientation chunk size.
MBS_PARALLEL_MEM_FRACTION	Memory fraction used by parallel multi-size scheduler.
MBS_PARALLEL_SHARED_KEQ=1	Environment equivalent of shared k_eq batching.
MBS_PARALLEL_KEQ_BATCH_RATIO=R	Environment default for shared batch ratio.

Diagnostic variables exist for FFT refinement, autofull heuristics, trace prefilters, and internal debug ranges. They are intentionally not recommended for normal production runs; inspect `grep -R "getenv(\"MBS_\" src` when debugging a specific subsystem.

11 Output

Main output is a whitespace-separated .dat file:

ScAngle 2pi*dcos M11 M12 M13 M14 M21 M22 M23 M24 M31 M32 M33 M34 M41 M42 M43 M44

Column	Meaning
ScAngle	Scattering angle theta in degrees.
2pi*dcos	Solid-angle ring weight for this theta row.
Mij	Mueller matrix elements after beam and orientation averaging.

Common companion outputs:

Output	Created by	Meaning
_noshadow file	--noshadow_output	Mueller matrix without shadow/external beam contribution.
_betas/ directory	--save_betas	Per-beta Mueller diagnostics.
checkpoint files	--checkpoint	Resume data for long orientation-grid runs.
Jones output	--jones	Raw Jones matrices in supported PO modes.
FILE from	explicit request	Effective scaled native particle at a stable user-selected path.
--save-geometry		
<result>_integrals.tsv	PO and GO output	Machine-readable primary extinction, scattering, absorption, efficiencies, and the numerical C_{sca} error estimate.

The log and TSV expose exactly one method-specific definition of each physical quantity:

$$C_{\text{ext}}, C_{\text{sca}}, C_{\text{abs}}, Q_{\text{ext}}, Q_{\text{sca}}, Q_{\text{abs}}, Q_x = \frac{C_x}{A_{\text{proj}}}.$$

For PO, C_{ext} comes from the forward-amplitude optical theorem. For an absorbing material, $C_{\text{sca}} = \sum_j M_{11}(\theta_j) \Delta\Omega_j$ and $C_{\text{abs}} = C_{\text{ext}} - C_{\text{sca}}$. For a nonabsorbing material, conservation gives $C_{\text{sca}} = C_{\text{ext}}$ and $C_{\text{abs}} = 0$. For GO, $C_{\text{ext}} = A_{\text{proj}}$; the absorbing case uses the total outgoing beam energy for C_{sca} and the difference for C_{abs} . The nonabsorbing GO case again enforces $C_{\text{sca}} = C_{\text{ext}}$ and $C_{\text{abs}} = 0$. Legacy PO/GO hybrids and duplicate labels are deliberately omitted from the report.

The C_{sca} integration estimate compares the full theta grid with a nested grid formed from every second theta row:

$$\hat{\epsilon}_{\text{sca}} = \frac{|C_{\text{sca},h} - C_{\text{sca},2h}|}{\max(|C_{\text{sca},h}|, |C_{\text{sca},2h}|)}.$$

For a nonabsorbing run the report conservatively takes the larger of this estimate and the independent conservation mismatch: the M_{11} integral versus optical-theorem extinction in PO, or outgoing beam sum versus projected area in GO. Fewer than five theta rows cannot form the estimate and are marked

unavailable. A value above 1 percent produces `check_csca_integration`. This is an a-posteriori resolution check, not a rigorous error bound and not an orientation-convergence estimate.

The TSV columns are `method`, `label`, `status`, the six C/Q values, and `Csca_error_estimate_rel`. It contains no legacy, GO-in-PO, or PO-in-GO alternatives.

The startup and final log blocks also record hostname, CPU model, logical and physical core counts, effective OpenMP thread count, total/available RAM, process RSS and peak RSS, visible GPU models, and active-device VRAM when CUDA is available. The final log contains the FFT and cutoff audit blocks described above. These records make timing and accuracy comparisons attributable to a specific resource state; GPU timings obtained while another process occupies the device are not comparable to an idle-device benchmark.

Normal runs do not create diagnostic files in the current working directory. Use `MBS_BEAM_LOG=PATH` only when an explicit first-beam dump is needed.

For nonabsorbing runs physical absorption is fixed to zero. The reported C_{sca} error remains a convergence diagnostic and does not replace inspection of the output Mueller matrix.