

Name: Kirithick Raja

Roll no.: 240701627

Week-15

Question 1:

Question 1

Correct

Marked out of
1.00

 Flag question

Given an array of integers, reverse the given array in place using an index and loop rather than a built-in function.

Example

`arr = [1, 3, 2, 4, 5]`

Return the array `[5, 4, 2, 3, 1]` which is the reverse of the input array.

Function Description

Complete the function `reverseArray` in the editor below.

`reverseArray` has the following parameter(s):

`int arr[n]`: an array of integers

Return

`int[n]`: the array in reverse order

Constraints

$1 \leq n \leq 100$

$0 < arr[i] \leq 100$

Input Format For Custom Testing

The first line contains an integer, n , the number of elements in `arr`.

Each line i of the n subsequent lines (where $0 \leq i < n$) contains an integer, `arr[i]`.

Source code:

```
1 #include<stdio.h>
2 #include<stdlib.h>
3 int* reverseArray(int arr_count, int *arr, int *result_count) {
4     *result_count=arr_count;
5     int *reversedArr=(int*)malloc(arr_count*sizeof(int));
6     if(reversedArr==NULL)
7     {
8         printf("Memory allocation failed\n");
9         return NULL;
10    }
11    for(int i=0;i<arr_count;i++)
12    {
13        reversedArr[i]=arr[arr_count-i-1];
14    }
15    return reversedArr;
16 }
17 int main1()
18 {
19     int arr_count;
20     scanf("%d",&arr_count);
21     int *arr=(int*)malloc(arr_count*sizeof(int));
22     if(arr==NULL)
23     {
24         printf("Memory allocation failed\n");
25         return 1;
26     }
27     for(int i=0;i<arr_count;i++)
28     {
29         scanf("%d",&arr[i]);
30     }
31     int result_count;
32     int *reversedArr=reverseArray(arr_count,arr,&result_count);
33     if(reversedArr==NULL)
34     {
35         free(arr);
36         return 1;
37     }
38     for(int i=0;i<result_count;i++)
39     {
40         printf("%d\n",*(reversedArr+i));
41     }
42     printf("\n");
43     free(arr);
44     free(reversedArr);
45     return 0;
46 }
```

Result:

	Test	Expected	Got	
✓	int arr[] = {1, 3, 2, 4, 5};	5	5	✓
	int result_count;	4	4	
	int* result = reverseArray(5, arr, &result_count);	2	2	
	for (int i = 0; i < result_count; i++)	3	3	
	printf("%d\n", *(result + i));	1	1	

Passed all tests! ✓

Question 2:

Question 2

Correct

Marked out of 1.00

Flag question

An automated cutting machine is used to cut rods into segments. The cutting machine can only hold a rod of *minLength* or more, and it can only make one cut at a time. Given the array *lengths[]* representing the desired lengths of each segment, determine if it is possible to make the necessary cuts using this machine. The rod is marked into lengths already, in the order given.

Example

n = 3
lengths = [4, 3, 2]
minLength = 7

The rod is initially $\text{sum}(\text{lengths}) = 4 + 3 + 2 = 9$ units long. First cut off the segment of length $4 + 3 = 7$ leaving a rod $9 - 7 = 2$. Then check that the length 7 rod can be cut into segments of lengths 4 and 3. Since 7 is greater than or equal to *minLength* = 7, the final cut can be made. Return "Possible".

Example

n = 3
lengths = [4, 2, 3]
minLength = 7

The rod is initially $\text{sum}(\text{lengths}) = 4 + 2 + 3 = 9$ units long. In this case, the initial cut can be of length 4 or $4 + 2 = 6$. Regardless of the length of the first cut, the remaining piece will be shorter than *minLength*. Because $n - 1 = 2$ cuts cannot be made, the answer is "Impossible".

Function Description

Complete the function *cutThemAll* in the editor below.

cutThemAll has the following parameter(s):

int lengths[n]: the lengths of the segments, in order

int minLength: the minimum length the machine can accept

Returns

string: "Possible" if all $n-1$ cuts can be made. Otherwise, return the string "Impossible".

Source code and Result:

```
1 #include<stdio.h>
2 char* cutThemAll(int lengths_count, long *lengths, long minLength) {
3     long t=0,i=1;
4     for(int i=0;i<lengths_count-1;i++)
5     {
6         t=t+lengths[i];
7     }
8     do
9     {
10        if(t-lengths[lengths_count-1]<minLength)
11        {
12            return "Impossible";
13        }
14        i++;
15    }
16    while(i<lengths_count-i){
17        return "Possible";
18    }
19 }
20
21
```

	Test	Expected	Got	
✓	long lengths[] = {3, 5, 4, 3}; printf("%s", cutThemAll(4, lengths, 9))	Possible	Possible	✓
✓	long lengths[] = {5, 6, 2}; printf("%s", cutThemAll(3, lengths, 12))	Impossible	Impossible	✓

Passed all tests! ✓