

Rajalakshmi Engineering College

Name: Kirithick R
Email: 240701627@rajalakshmi.edu.in
Roll no: 2116240701627
Phone: 9952595005
Branch: REC
Department: I CSE FF
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 7.5

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
int doesKeyExist(Dictionary *dict, const char *key) {  
    for (int i = 0; i < dict->size; i++) {  
        if (strcmp(dict->pairs[i].key, key) == 0) {  
            return i;  
        }  
    }  
}
```

```

    return 0;
}
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {
    if (dict->size == dict->capacity) {
        initDictionary(dict);
    }
    int idx = doesKeyExist(dict, key);
    if (idx != 0) {
        strncpy(dict->pairs[idx].value, value, 49);
        dict->pairs[idx].value[49] = '\0';
    } else {
        strncpy(dict->pairs[dict->size].key, key, 49);
        dict->pairs[dict->size].key[49] = '\0';
        strncpy(dict->pairs[dict->size].value, value, 49);
        dict->pairs[dict->size].value[49] = '\0';
        dict->size++;
    }
}
void removeKeyValuePair(Dictionary *dict, const char *key) {
    int idx = doesKeyExist(dict, key);
    if (idx != -1) {
        for (int i = idx; i < dict->size - 1; i++) {
            dict->pairs[i] = dict->pairs[i + 1];
        }
        dict->size--;
    }
}
void printDictionary(Dictionary *dict) {
    for (int i = 0; i < dict->size; i++) {
        printf("Key: %s; Value: %s\n", dict->pairs[i].key, dict->pairs[i].value);
    }
}

```

Status : Partially correct

Marks : 7.5/10